Experimental limit on the blue shift of the frequency of light implied by a q-nonlinearity

V.I.M an rko^1 and G.M.Tino

D ipartim ento di Scienze Fisiche, Universita di Napoli "Federico II" M ostra d'Oltrem are, Pad 20 - 80125 Napoli, Italy

Abstract

W e discuss the in plications of an experiment in which the frequencies of two laser beams are compared for dierent intensities in order to search for a dependence of the frequency of light on its intensity. Since no such dependence was found it is possible to place bounds on a description of the electrom agnetic eld in terms of q-oscillators. We conclude that the value of the nonlinearity parameter is smaller than 10¹⁷.

1 Introduction

The q{oscillators [1], [2] have been introduced in the study of the mathematical structures of quantum groups [3] which are used to explain the peculiarities of the rotational spectra of nuclei. [4]. The g{deform ation changes the Brownian motion [5]. The physical nature of g{oscillators is not clear yet. It is related som et in es to the problem of fundam ental length [6], [7] or to the discrete structure of time [8]. The quantum group structure may be related to nonlinear modi cations of quantum mechanics [9], [10], [11], reviewed in [12]. The nonlinearity of vibrations produces also changes in the Bose distribution [13], [14]. In [15], [16] it was suggested an interpretation of the q{oscillators as usual nonlinear oscillators with speci c exponential dependence of the oscillator frequency on the amplitude of vibrations. Such hypothesis leads to the same algebraic structure of the commutation relations in the quantum case and Poisson brackets in classical dom ain that g{oscillators of [1], [2] have. Som e predictions have been form ulated on the basis of this hypothesis. If q{nonlinear vibrations are considered as vibrations of the real electrom agnetic eld, they must be "visible" for high eld intensity as for nonlinearities of any kind. In particular, a dependence of light frequency on its intensity has been proposed in [17]. It implies that for increasing electrom agnetic eld intensity the frequency increases, which is not the case, of course, for linear M axwell electrodynam ics. W hile the nonlinear phenom ena in media electrodynam ics are well known and they are the base for nonlinear optics, the q{nonlinearity considered in this work would be a property of the electrom agnetic eld vibration in vacuum.

In this paper, we discuss in the frame of the theory of q-nonlinearity the results of a simple experiment which allows to set an upper limit to a possible dependence of the frequency of light on the intensity. A heterodyne technique is used to compare the frequency of two laser beam s as their intensity is changed. Two narrow-band diode lasers are phase-locked with a xed frequency

¹On leave from Lebedev Physical Institute, M oscow, Russia.

o set and a portion of their output is mixed in a fast photodiode. The measurement of the frequency of the beat note provides a very sensitive method to detect small frequency changes. A lthough the work is motivated by the interpretation of q{oscillators as describing the q{nonlinear vibrations of electrom agnetic eld, the accuracy of the experiment allows to set an upper limit to any dependence of the "colour" of light on the intensity.

In the next section, we describe shortly the theory of q{oscillators and review the results of [15], [16] and [17]. In Section 3, the experimental set{up is described. The results of the experiment are discussed in Section 4.

2 q{vibrations

The photon creation and annihilation operators a and a^y satisfy boson commutation relations

$$aa^{Y} \quad a^{Y}a = 1: \tag{1}$$

The one {mode H am iltonian describing the electrom agnetic eld oscillations is taken as the H am iltonian of the usual harm onic oscillator

$$H = \frac{1}{2}h! (a^{y}a + aa^{y});$$
 (2)

that yields the Heisenberg equation of motion for the amplitude a

$$\underline{a}(t) = i! a(t):$$
 (3)

The solution of this linear equation is

$$a(t) = a(0)e^{-itt};$$
 (4)

and it is seen from this solution that for linear oscillations the frequency does not depend on the amplitude of vibrations.

The q{oscillator is described by the creations and annihilations operators a_q ; a_q^y which satisfy the following relation [1], [2]

$$a_{q}a_{q}^{y} \quad qa_{q}^{y}a_{q} = q^{n} :$$
 (5)

Here the real number $q = \exp$, the parameter is considered as the nonlinearity parameter [15], and the operator $\hat{n} = a^y a$ is the operator of the photon number in the mode. In [15], [16] and [17] it was suggested using the nonlinear relations

$$a_{q} = a \frac{\sin h(a^{y}a)}{a^{y}a \sinh}; \quad a_{q}^{y} = \frac{\sin h(a^{y}a)}{a^{y}a \sinh}a^{y}; \quad (6)$$

which give relation (5). The modi ed Ham iltonian (2) has the form

$$H_{q} = \frac{1}{2}h! (a_{q}^{y}a_{q} + a_{q}a_{q}^{y}) = \frac{h!}{2\sinh} fsinh[(a^{y}a + 1)] + \sinh((a^{y}a)g);$$
(7)

It describes nonlinear vibrations given by the Heisenberg equation of motion

$$a(t) = i! [n]a(t); a(0) = a:$$
 (8)

The solution to this equation has the form

$$a(t) = a(0) \exp f = \frac{1}{2} [a^{\gamma}(0)a(0)] tg;$$
 (9)

The frequency of vibration \oint depends on the amplitude and for large eld intensities (n 0) it has the form

$$e = ! \frac{1}{\sinh} \cosh n : \tag{10}$$

In the lim it of sm all nonlinearity, ! 0 and the frequency e! !:

The nonlinearity parameter is supposed to be smalland the "blue shift e ect" [16][17] which is interpreted as a change of the frequency due to increasing number of photons in the mode is described by

$$\frac{!}{!} = \frac{1}{2} {}^{2}n^{2}; \qquad ! = \bullet \quad !; \qquad (11)$$

which is the approximate expression (10) for 1, n 0 and n 1. This relation allows to check experimentally whether there is a change of light frequency if one increases the photon number in the mode (eld intensity). A null result in the search for a frequency shift provides an upper bound for the nonlinearity parameter .

3 Experiment

The basic idea of this experiment is to search for a change of the frequency of laser radiation when its intensity is varied. In this experiment, this was done by comparing the frequencies of two laser beam susing a heterodyne scheme. The output of two narrow band sem iconductor diode lasers was mixed in a fast photodiode. By varying the intensity of the beam s, a dependence of the frequency of the beat note on the intensity was searched for. A very high accuracy was obtained by phase-locking one of the lasers to the other. In this way, the frequency di erence at the output of two laser sources was extremely stable and small changes could be observed.

A simplied scheme of the apparatus used for the measurements reported in this paper is shown in Fig. 1. Two diode lasers emitting at 850 nm were used as radiation sources. In order to reduce their linewidth, they were mounted in an extended-cavity con guration using optical feedback from an external grating [18]. This allowed to reduce the linewidth to about 50 kHz. The output of the lasers was the zero-order rejection from the grating. The output beam of each laser passed through an optical isolator, to avoid feedback to the laser, and through an anam orphic prism pair to correct the elliptical cross-section of the beam. At the output of the prism s the beam had a near-circular cross-section with a diameter of 8 mm.

The two diode lasers were phase-locked with a frequency o set of 9 GHz using the scheme described in [19]. When two lasers are phase-locked, the frequency di erence becomes equal to the frequency of the reference signal. The relative linewidth of the locked lasers is therefore negligible and is only limited by the linewidth of the frequency generators and by vibrations of optical components. In the set-up we used for this experiment, under locked conditions the measured phase error variance was less than $4:10^{-3} \text{ rad}^2$:

The frequency di erence between two laser beams, each coming from one laser, was measured by measuring the frequency of the beat note obtained at the output of the photodetector (PD 2)

on which the two beams were superposed. The two beams were combined on a beam -splitter and focused on the photodetector using a 3 cm focal length lens. Before reaching the beam splitter, each beam passed through a variable attenuator formed by a halfwave plate and a polarizing cube. The maximum power of each beam at the photodiode was 2 mW. The photodetector was a commercial InG aAs Schottky diode with a diameter of 25 m icrometers. The conversion gain was 5V/W. W ith an intensity of 0.1 mW per beam, the beat signal at the output of the photodetector was -78 dBm, limited by the not perfect matching of the two beams at the detector.

The beat signal from photodetector PD2 was observed with an rf spectrum analyzer. The resolution bandwidth was 10 Hz. The peak frequency could be determined with a sensitivity of 1 Hz. A fler proper therm all stabilization of the apparatus, the uctuations of the values obtained for the frequency of the beat signal were reduced to less than 1 Hz.

D ata were taken by m easuring the frequency of the beat note with the spectrum analyzer while varying the intensity of the laser beam s between 0.1 m W and 2 m W using the variable attenuators. No dependence of the beat signal frequency on the light intensity was observed at the accuracy level set by the spectrum analyzer nor any change of the signal shape.

It is worth stressing that the sensitivity of this method is extrem ely high. A fractional change of the frequency of 10¹⁴ would have been detected in this experiment. In fact, using essentially the same scheme illustrated here, the accuracy can still be improved by several orders of magnitude by electronical down-conversion of the beat note and FFT analysis. A lso, a higher laser power and better moderm atching on the photodiode would increase the signi cancy of the results.

4 D iscussion

The null result of this experiment can be translated into an upper bound for the nonlinearity parameter . Assuming ideal conditions in which all the photons are in a single mode, at the maximum laser power of 2 mW one obtains a photon number n 10^{10} . Using Eq. (2) and considering the minimum frequency change $\frac{1}{10}$ 10¹⁴ detectable in this experiment, one obtains

 10^{17} . This value is obtained under the ideal conditions mentioned above and assuming that the frequency of a mode depends only on the number of photons in that mode. A dierent bound for the parameter is obtained, of course, if a dierent model is assumed in the interpretation of the experimental result.

Several in provements of the method proposed here are possible. A possibility already mentioned above is to increase the sensitivity of the apparatus by electronical down-conversion of the heterodyne signal and FFT analysis. Since the signi cancy of the results increases with increasing power, the use of a higher laser power would be desirable. For high laser power, how ever, a di erent photodetector should be used. Such detectors are tipically slow and this would force to work at a smaller frequency di erence. Reduction of the noise would then require a long integration time. As suggested in [15], other types of experiments can be envisaged in order to test the possibility of describing electrodynam ics using q-oscillators. An accurate test could be performed using interferometric methods. Another possibility is to study the dependence of the time correlation function of the q-oscillator on the intensity.

A cknow ledgem ents

One of us (V JM .) would like to acknow ledge the University of Naples and IN F N ., Section of Naples, for kind hospitality. G M .T . acknow ledges useful discussions with M . P revedelli about the experiment.

References

- [1] L.C.Biedenham, J.Phys.A 22, L873 (1989).
- [2] A.J.Macfarlane, J.Phys.A 22, 4581 (1989).
- [3] M. Jimbo, Int. J. Mod. Phys. A 4, 3759 (1989).
- [4] R.N.Alvarez, D.Bonatsos, and Yu.F.Smirnov, Phys. Rev.A 50, 1088 (1994).
- [5] V.I.M an'ko and R.V.M endes, Phys. Lett. A 180, 39 (1993).
- [6] S.V. Shabanov, Quantum and Classical Mechanics and q-deformed Systems, Preprint BUTP 92/24 (1992).
- [7] E.Celeghini, M.Rasetti, and G.Vitiello, Phys. Rev. Lett. 66, 2056 (1991).
- [8] J. Lukierski, A. Nowicki, and H. Ruegg, Phys. Lett. B 293, 344 (1992).
- [9] M.D.Kostin, J.Chem. Phys. 57, 3589 (1973).
- [10] S.W einberg, Phys. Rev. Lett. 62, 485 (1989).
- [11] H.-D. Doebner and G.A. Goldin, Phys. Lett. A 162, 397 (1992).
- [12] V.V.D odonov and S.S.M izrahi, Ann. Phys. 237, 226 (1995).
- [13] G. Su and M. Ge, Phys. Lett. A 173, 17 (1993).
- [14] J.A. Tuszynski, J.L. Rubin, JM eyer and M. Kibler, Phys. Lett. A 175, 173 (1993).
- [15] V.I.M an'ko, G.M arm o, S.Solin eno, and F.Zaccaria, Int.J.M od. Phys. A 8, 3577 (1993).
- [16] V.I.M an'ko, G.M arm o, and F.Zaccaria, Phys. Lett. A 191, 13 (1994).
- [17] V. I. Man'ko, G. Manmo, S. Solimeno, and F. Zaccaria, Phys. Lett. A 176, 173 (1993);
 "Q {nonlinearity of Electrom agnetic Field and Deformed Planck Distribution," in: Technical Digests of EQEC '93-EQUAP '93, Firenze, September 10-13, 1993, eds. P. De Natale, R. Meucci, and S. Pelli, vol. 2 (1993).
- [18] G.M. Tino, Physica Scripta, T51, 58 (1994).
- [19] G. Santarelli, A. Clairon, S.N. Lea, and G.M. Tino, Opt. Commun. 104, 339 (1994).