

Reducing Quantum Errors and Improving Large Scale Quantum Cryptography

Tal Mor⁽¹⁾

(1) Physics Department, Technion, Haifa 32000, Israel;
(March 14, 2022)

Noise causes severe difficulties in implementing quantum computing and quantum cryptography. Several schemes have been suggested to reduce this problem, mainly focusing on quantum computation. Motivated by quantum cryptography, we suggest a coding which uses N quantum bits ($N = n^2$) to encode one quantum bit, and reduces the error exponentially with n . Our result suggests the possibility of distributing a secure key over very long distances, and maintaining quantum states for very long times. It also provides a new quantum privacy amplification against a strong adversary.

The ability to correct errors in a quantum bit (qubit) is crucial to the success of quantum computing, and it is very important to the success of quantum cryptography. Motivated by quantum computing, Shor [1] shows that quantum errors can be corrected (in some analogy to classical error correction [2]). The many works which follow Shor's idea focus on improving his result [3-6] to better fit the requirements of quantum computing, or to provide a better understanding of the properties of the error-correction codes (the previous works and also [7-9]). In this work we apply this idea to quantum cryptography, where reducing the error rate is the main aim. We emphasize the properties of quantum error-correction which are relevant to quantum cryptography, and we show that quantum cryptography can be tremendously improved using a simple generalization of Shor's scheme.

Quantum cryptography [10] has already taken some promising experimental steps [11], and, to certain limits, it can work without involving the complications added by error-correction (or more precisely, error-reduction) schemes. In reality, there is noise due to preparing, transmitting and receiving the quantum states, and practical protocols deal with small error-rates. However, the noise still causes a severe problem due to the combination of the following two reasons: (1) The information available to an eavesdropper (Eve) on a single bit depends on the error-rate which the legitimate users (Alice and Bob) accept [12,13], and reducing this error-rate reduces Eve's information on the key. Moreover, security analysis (e.g., [13]) is restricted to small error rates, and removing this restriction might make the analysis (technically) impossible. (2i) Existing error-rates do not allow key distribution over long distances, due to error accumulation over distance. This is the main problem of practical quantum key distribution, and currently [11] the best existing systems distribute a key to distances of up to 30 km. The scheme we present here might enable one to increase this distance significantly, suggesting that a lot of effort should be spent on this direction. (2ii) Some quantum cryptographic schemes [14,15] use quantum memory instead of (or in addition to) quantum channels. Reducing the errors in such schemes is important since it allows keeping the states unchanged for a desirable time. (This was partly suggested in [16]; a discussion of related works is done in the concluding paragraph.) Moreover, the quantum cryptographic network [15] which allows communication between any two users (while using no quantum channels between them) already uses the same experimental ingredients as error-reduction schemes. Therefore, improving quantum cryptography in the future, using error-reduction schemes, might make such a scheme favorite.

The error-reduction scheme we suggest here allows, in principle, to reduce the noise in a transmission channel or in a quantum memory to any desirable level. This result is important (from a theoretical point of view) for im-

plementing a "quantum privacy amplification" scheme, as an alternative to another quantum privacy amplification scheme [17] which is based on purification of singlet-pairs [18]. Such schemes provide a promising direction for proving the ultimate security of quantum cryptography, as an alternative to the more practical approach of [13].

Classical error-correction is based on redundant encoding which uses more than one bit (on average) to encode one bit. The simplest scheme is the 1 ! 3 repetition code in which each bit is repeated three times in the encoding, and a majority vote is chosen for decoding. In this case, if a single bit contains an error with probability p (where p is small), and $p_1 = \binom{3}{1} p^1 (1-p)^{3-1}$ is the probability of having exactly 1 errors, then the probability to have a remainder error (the probability of having two or three errors in three bits) is $P = p_2 + p_3 = 3(1-p)p^2 + p^3 = 3p^2 - 2p^3$. One must keep in mind that this result is true on average, but in case we know that one error was identified and corrected [which happens with probability $p_2 + p_1 = 3p^2(1-p) + 3p(1-p)^2$] the probability of having a remainder error is exactly $p_2 = (p_1 + p_2) = p$, and we gain no error reduction at all!

The analogous quantum error-correction [1] uses 9 qubits to encode a single qubit (to perfectly correct a single error) using the following procedure: a 1 ! 3 repetition code in the z basis $|j_i\rangle = |j_00i\rangle$ and $|j_i\rangle = |j_11i\rangle$ (where $|j_00i\rangle$ stands for the tensor product $|j_i\rangle|j_i\rangle|j_i\rangle$ of three qubits); a transformation to the x basis $|j_i\rangle = (1/\sqrt{2})(|j_i + j_i\rangle$ and $|j_i\rangle = (1/\sqrt{2})(|j_i - j_i\rangle$ for each qubit; and finally, again a 1 ! 3 repetition code in the (new) z basis. All together, the encoding is:

$$|j_i\rangle = \frac{1}{\sqrt{8}} (|j_00i\rangle + |j_11i\rangle) (|j_00i\rangle + |j_11i\rangle) (|j_00i\rangle + |j_11i\rangle);$$

$$|j_i\rangle = \frac{1}{\sqrt{8}} (|j_00i\rangle - |j_11i\rangle) (|j_00i\rangle - |j_11i\rangle) (|j_00i\rangle - |j_11i\rangle); \quad (1)$$

We denote it as R_3UR_3 where R_n stands for 1 ! n repetition code, and U for rotation from the z basis to the x basis.

For cryptographic purposes, one is interested in error-reduction schemes, which leave a minimal remainder error, rather than in error-correction schemes, which leave a higher remainder error. For that aim, the majority vote decoding should be replaced by an unanimous decision; in case of a disagreement the bit is thrown away. The classical (1 ! n) repetition code R_n with $n = 2t + 1$ provides successful unanimous decision with probability $Q = (1-p)^n + p^n$, and the remainder error in this case is $P = p^n = Q$ which is $P = \frac{p}{1-p}$ for small p . This code can also be used to correct up to t errors, but with a much higher (average) remainder error, which can be calculated from the binomial expansion of $[p + (1-p)^t]^n$. However, if exactly t errors were identified and corrected, the probability that there were actually $t + 1$ errors (hence, a remainder error) is p .

For $n = 3$ the remainder error in the error-reduction scheme is $P = p^3 + 3p^4$ which is much improved in comparison to the (average) remainder error in case of error-correction, and even the $n = 2$ error-reduction code provides a remainder error $P = p^2 + 3p^3$ which is better than $3p^2 - p^3$ for small p . This was first noted by Vaidman, Goldenberg and Wiesner (VGW) [16] who presented the quantum error-reduction scheme R_2UR_2 to improve the remainder error while using only 4 qubits instead of 9 for the encoding. The error-reduction process is done by projecting the state of the code qubits on a desirable subspace; for instance, in case of the $n = 3$ quantum error-reduction code, it is projected on the subspace spanned by the two states of eq. 1. If the projection fails, the qubit is not corrected but is thrown away. Throwing the bits has only small influence on a quantum key distribution protocol since the legitimate users throw away most of the bits due to other reasons. Note that this is not appropriate for quantum computing, where throwing one bit in the computing process destroys the computation. On the other hand, for cryptographic purposes, the number of bits used for the decoding is less important (in comparison to the requirements of quantum computing), since neither of the existing protocols makes use of the coherence of more than two particles.

Error-correction can be easily combined into an error-reduction scheme for the price of increasing the remainder error P . The benefit of such a combination is that the probability of successful projection, Q , is increased. For simplicity we shall consider only "pure" error-reduction scheme, but our scheme can be generalized to combine the correction of few bits as well. In a scheme which combines error-reduction and (t^0 -errors) error-correction, one has to check into which subspace the state is projected, and if this subspace corresponds to t^0 errors (or less) the state is corrected by simple transformations (see [1] etc.).

We conclude that the codes which are used for quantum error-correction must be modified to provide error reduction in order to meet the requirements of quantum cryptography much better. For example, we suggest to use error-reduction codes R_nUR_n with large n . Such codes encode one qubit into $N = n^2$ qubits, in order to reduce the error-rates exponentially with n (more efficient codes could be used as well, based, for instance, on [5,7,6]). The rest of this paper is devoted to the analysis of these codes. As in all discussions on quantum error-correction, coherent transformations of many particles are dismissed since, in real channels, such errors are much smaller than errors in individual bits. However, we consider also eavesdropping aspects, and therefore, this issue is more subtle and we elaborate it further later on.

It is generally believed that it is enough to correct phase errors, bit errors and bit-phase errors in order to protect against any independent error (see the analysis in [3,8]). The intuitive problem with such argument is the assumption that each qubit is either strongly disturbed

(due to bit flip in some basis) or not disturbed at all, while in reality, all qubits are slightly changed. Following [1,8,3,16,5,7] and other works on this subject we find the remainder error P and the probability of success Q given that bit errors, phase errors and phase-bit errors occur with probability p . However, for the simple special case of the code R_2UR_2 we demonstrate the error reduction explicitly by discussing a general transformation on each bit.

A qubit is described by a two-dimensional Hilbert space (say, spin of a spin-half particle) $|j\rangle + |j\rangle$ with $j = \frac{1}{2}$ or $j = \frac{3}{2}$. When it is encoded using R_n we get the state $|j_R\rangle = |j_R\rangle + |j_R\rangle$ in a 2^n dimensional Hilbert space, with $|j_R\rangle = |j_1 0_2 \dots n_1\rangle$ and $|j_R\rangle = |j_1 1_2 \dots n_1\rangle$. When it is encoded using R_nUR_n we get the state $|j_{RUR}\rangle = |j_{RUR}\rangle + |j_{RUR}\rangle$ of $N = n^2$ qubits in a $2^{(n^2)}$ dimensional Hilbert space, with

$$\begin{aligned} |j_{RUR}\rangle &= \frac{1}{\left(\frac{p}{2}\right)^n} (|j_1 \dots n_1 0 \dots j_1 \dots n_1\rangle \\ &+ |j_1 \dots n_1 1 \dots j_1 \dots n_1\rangle :: (|j_1 \dots n_1 0 \dots j_1 \dots n_1\rangle \\ &+ |j_1 \dots n_1 1 \dots j_1 \dots n_1\rangle) \\ |j_{RUR}\rangle &= \frac{1}{\left(\frac{p}{2}\right)^n} (|j_1 \dots n_1 0 \dots j_1 \dots n_1\rangle \\ &+ |j_1 \dots n_1 1 \dots j_1 \dots n_1\rangle :: (|j_1 \dots n_1 0 \dots j_1 \dots n_1\rangle \\ &+ |j_1 \dots n_1 1 \dots j_1 \dots n_1\rangle) \end{aligned} \quad (2)$$

where there are n multiplets of n bits each. In the decoding process, the disturbed state is projected on the desirable 2-dimensional subspace spanned by the two states $|j_{RUR}\rangle$ and $|j_{RUR}\rangle$. Let us see the influence of the different types of errors on the final state. (1) Bit errors: Opening the parentheses, it is easily seen that bit-errors in less than n bits cannot bring the state back into the desirable subspace. (2) Phase errors: It is not easy to calculate the number of phase errors which can bring the state back to the relevant subspace, if we use the z basis; however, phase errors in the z basis are bit errors in the x basis (see [1,9], etc.). Therefore by transforming this state to the x basis of each qubit, the two states $|j_{RUR}\rangle$ and $|j_{RUR}\rangle$ become superposed from different words which differ by at least n bits, and thus, n phase errors are required in order to bring the original state back to the relevant subspace. (3) Phase-bit errors: Showing that only n such errors bring the state back to the desirable subspace is done using the same approach, by a transformation to the y basis. We conclude that the probability of success and the remainder error are indeed $Q = (1-p)^n$ and $P = p^n = Q$, as calculated for the classical error reduction scheme R_n .

We now provide a partial analysis of more realistic type of errors. Let each qubit in the code be transformed arbitrarily (but independently). In general, the transformation is not unitary since an ancilla (e.g., environment) might be involved. However, we can still deal only with unitary transformations and the effect of decoherence (non-unitary transformations) is obtained by averaging

over several different unitary transformations with appropriate probabilities. A similar argument is provided in [8]. Restricting ourselves to "pure" error-reduction schemes, we must demand that all the individual unitary transformations be weak (close to unity). In a generalization of our scheme which corrects errors, up to t^0 (which is somewhat smaller than t^0) of the transformations are permitted not to be weak.

We provide a complete analysis only for the code R_2UR_2 , but such analysis can be extended to codes R_nUR_n with $n > 2$. Let each qubit j in the code be exposed to the most general one-particle transformation

$$U_j = \begin{pmatrix} \cos \theta_j & \sin \theta_j e^{i\phi_j} \\ \sin \theta_j e^{i\phi_j} & \cos \theta_j \end{pmatrix} \quad (3)$$

(up to an irrelevant overall phase), where all angles are smaller than some small angle θ , so that $\theta^2 \ll 1$. We write how the original state $|j_{RUR}\rangle$ in the $2^{(2^2)} = 16$ dimensional Hilbert space is transformed (due to the matrix elements $|0000\rangle\langle j_1U_1U_3U_4|j\rangle$ etc.):

$$\begin{array}{ccccccc} & 0 & + & 1 & 0 & + & 1 \\ \begin{array}{c} |0000\rangle \\ |0001\rangle \\ |0010\rangle \\ |0011\rangle \\ |0101\rangle \\ |1100\rangle \\ |1101\rangle \\ |1110\rangle \\ |1111\rangle \end{array} & \begin{array}{c} 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \end{array} & \begin{array}{c} C \\ C \\ C \\ C \\ ! \\ C \\ C \\ A \end{array} & \begin{array}{c} |0000\rangle \\ |0001\rangle \\ |0010\rangle \\ |0011\rangle \\ |0101\rangle \\ |1100\rangle \\ |1101\rangle \\ |1110\rangle \\ |1111\rangle \end{array} & \begin{array}{c} 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \end{array} & \begin{array}{c} C \\ C \\ C \\ C \\ C \\ C \\ C \\ A \end{array} & \begin{array}{c} x_{0000} \\ x_{0001} \\ x_{0010} \\ x_{0011} \\ x_{0101} \\ x_{1100} \\ x_{1101} \\ x_{1110} \\ x_{1111} \end{array} \end{array} \quad (4)$$

with $x_{0000} = (\cos \theta_1 \cos \theta_2 \cos \theta_3 \cos \theta_4 + \sin \theta_1 \cos \theta_2 \sin \theta_3 \sin \theta_4 e^{i\phi_3} e^{i\phi_4} + \sin \theta_1 \sin \theta_2 \cos \theta_3 \cos \theta_4 e^{i\phi_1} e^{i\phi_2} + \sin \theta_1 \sin \theta_2 \sin \theta_3 \sin \theta_4 e^{i\phi_1} e^{i\phi_2} e^{i\phi_3} e^{i\phi_4})$ etc. Projecting the state onto the subspace spanned by $|j_{RUR}\rangle = (1/2)(|0000\rangle + |0111\rangle + |1100\rangle + |1111\rangle)$ and $|j_{RUR}\rangle = (1/2)(|0000\rangle - |0111\rangle - |1100\rangle + |1111\rangle)$, and defining $C = (\cos \theta_1 \cos \theta_2 \cos \theta_3 \cos \theta_4 + \sin \theta_1 \cos \theta_2 \sin \theta_3 \sin \theta_4 e^{i\phi_3} e^{i\phi_4} + \sin \theta_1 \sin \theta_2 \cos \theta_3 \cos \theta_4 e^{i\phi_1} e^{i\phi_2} + \sin \theta_1 \sin \theta_2 \sin \theta_3 \sin \theta_4 e^{i\phi_1} e^{i\phi_2} e^{i\phi_3} e^{i\phi_4})$, we obtain, after a lengthy calculation, the (unnormalized) final state $|j_{RUR}\rangle = C|0000\rangle + O(\theta^2)$. The final state, when normalized, is almost identical to the initial state $|j_{RUR}\rangle$, where the terms which contribute to the correction are $\sin \theta_1 \sin \theta_2$; $\sin \theta_3 \sin \theta_4$, etc., all of order $O(\theta^2)$ or smaller. Thus, the remainder error probability is indeed $O(\theta^4) = O(p^2)$, with probability of success C^2 .

This code can be used for t^0 -bit error-correction scheme if we do not reject the encoded bit when the projection fails. Instead, we check into which subspace the state is projected. In this case the assumption that all angles are small can be dismissed, so that t^0 (which is smaller than t^0) angles can be large. Recall however that in these cases the remainder error-rate is not $O(\theta^{2n})$ anymore.

The main problem of a scheme which performs only error reduction is that the probability of successful pro-

jection diminishes when n is increased as $(1-p)^n$. We could combine it with some (small t^0) error-correction as previously explained, but there is also a different solution, which should be preferable in case the noise changes in time as θ etc. In this case the probability of success can be much improved using the Zeno effect (see discussion in [16,19]) by performing M projections in between, at equal time steps, reducing p to $p=(M^{-2})$, and Q to $(1 - \frac{p}{M^2})^{nM} \approx 1 - np=M$. The remainder error is also much improved by this process. Performing M projections is rather simple when enhancing a quantum memory is considered (meaning that it does not add any further complication). When transmission to long distances is considered, Alice and Bob need to have "projection stations" between them. This greatly improves Q and does not affect the security of the transmission. Indeed, since each such station is only required to perform the desired projection, it can even be controlled by the eavesdropper; if Eve tries to do anything other than the required projections she increases the error-rate and will be detected.

The only assumption required for the success of any error-correction or error-reduction scheme is that each code bit is disturbed independently of the others. If real noise causes many-particle transformations the scheme will fail, but for bits stored or transmitted separately, such effects are expected to be negligible. Thus, the legitimate users of quantum cryptography can use error-reduction schemes to decrease much of the noise, and, as a result, expect much less errors when comparing a portion of the data. It is important to note that the added assumption does not restrict the adversary, Eve. She is still allowed to do whatever she likes, including creating many-particle coherence. The eavesdropping analysis needs only to take the final error-rate into account. We could even let Eve do all the transformations from the initial bit, through the encoding till she obtains the final bit. If she deviates from the protocols and the error-rate is larger than expected Alice and Bob quit the transmission. If she deviates from the protocol but provides the final state with the allowed error-rate, Alice and Bob do not care which operations she has done, since the allowed small error-rate (which is verified), promises them that her information is limited as desired. This provides a new type of a privacy amplification scheme, simpler than the one recently suggested [17] which is based on purification of singlets [18]. Such schemes provide a proof of the ultimate security of quantum cryptography under the assumption that the legitimate users have perfect devices. Moreover, in case Eve gets the code bits without knowing which code bits encode a particular qubit, her information is reduced even more. This argument is similar to the randomization argument used in [13,17]. It may provide the proof of perfect security even when Alice and Bob have real devices, since Eve cannot know which coherence would be useful to her in advance, hence, her

information is reduced whether the legitimate users can observe this reduction or not! However, analyzing this aspect of quantum privacy amplification is rather complicated and it is beyond the scopes of this work.

In conclusion, we have shown that quantum cryptography can be much improved by using quantum error-reduction schemes. Our result might be crucial for implementing quantum cryptography over large scale distances and times. It also provides an alternative quantum privacy amplification scheme. We suggested a specific encoding which yields exponentially small remainder error, and we suggested to implement it in a "many-stations" system, so that the probability of success will not become too small. The errors due to the frequent projections in a "many-stations" system were not considered here. As in the case of a fault-tolerant calculations [9], it may well be that there is some optimal number of stations M such that a larger number of stations causes an increase of the remainder error. Note also that some errors are due to creation and measurement of the state in the labs of Alice and Bob, and for the time being these limits our ability to reduce P . However, the main limitations on quantum cryptography are maintaining coherence over long distances and times and these limitations are solved efficiently using the scheme we suggest.

>From all works which recently appeared, the work of V.G.W. [16] is more related to ours than the others. It considers the use of the quantum Zeno effect and the R_2UR_2 error-reduction scheme to maintain quantum states in a quantum memory for a longer time. However, this work does not deal with the benefits of using a large number of code bits, and with improving transmission to large distances. Other less related works are these of [8,3] which discusses quantum communication, and these of Steane [5,7] which discusses large n .

The author is grateful to Gilles Brassard and Asher Peres for motivating this work, and to Eli Biham, Netta Cohen, Lior Goldenberg and Lev Vaidman for very helpful discussions.

- correcting codes exist," accepted to Phys. Rev. A.
- [7] A. Steane, Phys. Rev. Lett. 77, 793 (1996).
 - [8] A. Ekert and C. M. Acchiavello, "Quantum Error Correction for Communication", quant-ph/9602022.
 - [9] P. W. Shor, "Fault-tolerant quantum computation"; quant-ph 9605011.
 - [10] C. H. Bennett and G. Brassard, in Proc. of IEEE Inter. Conf. on Computers, Systems and Signal Processing, Bangalore, India (IEEE, New York, 1984) p. 175. A. K. Ekert, Phys. Rev. Lett. 67, 661 (1991). C. H. Bennett, Phys. Rev. Lett. 68, 3121 (1992).
 - [11] A. Muller, H. Zbinden and N. Gisin, Nature, 378, 449 (1995). R. J. Hughes et al, "Quantum cryptography over underground optical fibers", crypto96. C. Marand and P. D. Townsend, Optics Letters, 20, 1695 (1995).
 - [12] C. H. Bennett, T. Mor and J. Smolin, "The Parity Bit in Quantum Cryptography", accepted to Phys. Rev. A; quant-ph 9604040.
 - [13] E. Biham and T. Mor, "Security against collective attacks", submitted to Phys. Rev. Lett.; quant-ph 9605007. "Bounds on Information and the Security of Quantum Cryptography", submitted to PhysComp96; quant-ph 9605010 (journal version is on preparation).
 - [14] L. Goldenberg and L. Vaidman, Phys. Rev. Lett. 75, 1239 (1995).
 - [15] E. Biham, B. Huttner and T. Mor, "Quantum Cryptographic Network Based on Quantum Memory", accepted to Phys. Rev. A; quant-ph 9604021.
 - [16] L. Vaidman, L. Goldenberg and S. Wiesner, accepted to Phys. Rev. A; quant-ph 9603031.
 - [17] D. Deutsch, A. Ekert, R. Jozsa, C. M. Acchiavello, S. Popescu, and A. Sanpera, "Quantum Privacy Amplification and the Security of Quantum Cryptography over Noisy Channels", submitted to Phys. Rev. Lett.; quant-ph 9604039.
 - [18] C. H. Bennett, G. Brassard, S. Popescu, B. Schumacher, J. Smolin and W. K. Wootters, Phys. Rev. Lett. 76, 722 (1996).
 - [19] I. L. Chuang and Y. Yamamoto, Phys. Rev. Lett. 76, 4281 (1996).

-
- [1] P. Shor, Phys. Rev. A 52, R2493 (1995).
 - [2] F. J. MacWilliams and N. J. A. Sloane, The Theory of Error Correction Codes, North Holland, Amsterdam (1977).
 - [3] C. H. Bennett, D. DiVincenzo, J. A. Smolin and W. K. Wootters, "Mixed state entanglement and quantum error correction," submitted to Phys. Rev. A; quant-ph/9604024.
 - [4] R. Laflamme, C. Miquel, J. P. Paz and W. H. Zurek, Phys. Rev. Lett. 77, 198 (1996).
 - [5] A. Steane, "Multiple Particle Interference and Quantum Error Correction", accepted to Proc. Roy. Soc. London.
 - [6] A. R. Calderbank and P. W. Shor, "Good quantum error-