

# The Complexity of Satisfiability in Non-Iterated and Iterated Probabilistic Logics

Ioannis Kokkinis

*Technical University of Dortmund*  
*ioannis.kokkinis@tu-dortmund.de*

October 20, 2021

## Abstract

Let  $L$  be some extension of classical propositional logic. The non-iterated probabilistic logic over  $L$  is the logic  $PL$  that is defined by adding non-nested probabilistic operators in the language of  $L$ . For example, in  $PL$  we can express a statement like “the probability of truthfulness of  $A$  is at least 0.3” where  $A$  is a formula of  $L$ . The iterated probabilistic logic over  $L$  is the logic  $PPL$ , where the probabilistic operators may be iterated (nested). For example, in  $PPL$  we can express a statement like “this coin is counterfeit with probability 0.6”. In this paper we investigate the influence of probabilistic operators in the complexity of satisfiability in  $PL$  and  $PPL$ . We obtain complexity bounds, for the aforementioned satisfiability problem, which are parameterized in the complexity of satisfiability of conjunctions of positive and negative formulas that have neither a probabilistic nor a classical operator as a top-connective. As an application of our results we obtain tight complexity bounds for the satisfiability problem in  $PL$  and  $PPL$  when  $L$  is classical propositional logic or justification logic.

**keywords:** probabilistic logic, computational complexity, satisfiability, justification logic

**Acknowledgements.** The author is grateful to Antonis Achilleos and Thomas Studer for several useful discussions and suggestions and to the anonymous reviewers for many valuable comments and remarks that helped him improve the quality of this paper substantially. The initial part of this research was conducted when the author was at the Institute of Computer Science (INF) in Bern, Switzerland (financial support by the Swiss National Science Foundation project 153169, *Structural Proof Theory and the Logic of Proofs*), and the final part when the author was at the Lorraine Research Laboratory in Computer Science and its Applications (LORIA) in Nancy, France (financial support by the European Research Council project 313360, *Epistemic Protocol Synthesis*).

# 1 Introduction

## 1.1 Background and Related Work

Probabilistic logics (also known as probability logics) are logics that can be used to model uncertain reasoning. Although the idea of probabilistic logic was first proposed by Leibniz [24], the modern development of this topic started only in the 1970s and 1980s in the papers of H. Jerome Keisler [15] and Nils Nilsson [26]. Following Nilsson’s research, Fagin, Halpern and Meggido [10] introduced a logic with arithmetical operations built into the syntax so that Boolean combinations of linear inequalities of probabilities of formulas can be expressed. Based on Nilsson’s research Ognjanović, Rašković and Marković [28] defined the logic  $LPP_2$ , which is a non-iterated probabilistic logic with classical base. The language of  $LPP_2$  is defined by adding (non-nested) operators of the form  $P_{\geq s}$  (where  $s$  is a rational number) to the language of classical propositional logic. In  $LPP_2$  we can have expressions of the form  $P_{\geq s}\alpha$ , which read as “the probability of truthfulness of classical propositional formula  $\alpha$  is at least  $s$ ”. In addition to  $LPP_2$ , the authors of [28] define the logic  $LPP_1$ , which is a probabilistic logic over classical propositional logic, that allows iterations (nesting) of the probabilistic operators ( $P_{\geq s}$ ). In  $LPP_1$  we can describe a situation like the following: let  $c$  be a coin and let  $p$  be the event “ $c$  lands tails”. Assume that the probability of  $c$  landing tails is at least 60% (because  $c$  is counterfeit). We can express this fact in non-iterated probabilistic logics with the formula  $P_{\geq 0.6}p$ . Assume now that we are uncertain about the fact of  $c$  being counterfeit. In order to express this statement we need nested applications of the probabilistic operators. In  $LPP_1$  for example we can have a formula like  $P_{\geq 0.8}P_{\geq 0.6}p$ .

In addition to classical propositional logic, probabilistic logics have been defined over several other logics (see the recent [29] for an overview). For example in [18, 19] we defined two probabilistic logics over justification logic (*probabilistic justification logics* for short). Justification logic [2] can be understood as an explicit analogue of modal logic [5]. Whereas traditional modal logic uses formulas of the form  $\Box\alpha$  to express that an agent believes  $\alpha$ , the language of justification logic ‘unfolds’ the  $\Box$ -modality into a family of so-called *justification terms*, which are used to represent evidence for the agent’s belief. Hence, instead of  $\Box\alpha$ , justification logic includes formulas of the form  $t : \alpha$ , where  $t$  is a justification term. Formulas of the form  $t : \alpha$  are called *justification assertions* and read as

the agent believes  $\alpha$  for reason  $t$ .

Justification terms can represent any kind of objects that we use as evidence: for example proofs in Peano arithmetic or informal justifications (like everyday observations, texts in newspapers, or someone’s words). Artemov developed the first justification logic, the Logic of Proofs (usually abbreviated as LP), to provide intuitionistic logic with a classical provability semantics [3, 4]. Except from LP, several other justification logics have been introduced. The minimal justification logic is called J [2]. By the famous realization theorem [4, 6] J

corresponds to the minimal modal logic K. That is, we can translate any theorem of J to a theorem of K by replacing any term with the  $\Box$  and also any theorem of K to a theorem of J by replacing any occurrence of  $\Box$  with an appropriate justification term.

The non-iterated probabilistic logic over J, the logic PJ, is defined in [18] and the iterated probabilistic logic over J, the logic PPJ, is defined in [19]. In PJ we can describe a situation like the following: assume that an agent reads in some reliable newspaper that fact  $\alpha$  holds and also that the agent hears that fact  $\alpha$  holds from some unreliable neighbour. Then, the agent has two justifications for  $\alpha$ : the text of the newspaper, represented by  $s$ , and the words of their neighbour, represented by  $t$ . We can express the fact that the newspaper is a more reliable source than the neighbour using the PJ-formulas  $P_{\geq 0.8}(s : \alpha)$  and  $P_{\geq 0.2}(t : \alpha)$ . So, we can use probabilistic justification logic to model the idea that

different kinds of evidence for  $\alpha$  lead to different degrees of belief in  $\alpha$ .

It is tempting to try to model the above idea using formulas of the form  $s \rightarrow P_{\geq 0.8}\alpha$  (which are not allowed in the syntax of PJ). However this approach treats justifications as statements: in order for  $P_{\geq 0.8}\alpha$  to hold,  $s$  has to hold too. In our approach this is not necessary. We believe that justifications do not need to be true, simply because one might want to believe something for a false reason. Also this approach places the uncertainty on top of formula  $\alpha$ . The approach of PJ places the uncertainty where it should be: on the the fact that  $s$  justifies  $\alpha$ .

The most interesting property of the logic PPJ is the fact that the language of PPJ allows applying justification terms to probabilistic operators and vice versa (as we will see later this is the property that makes finding complexity bounds for the satisfiability problem in PPJ a challenging task). So, continuing our example with the counterfeit coin, if  $p$  is the event “the coin lands tails”, and  $t$  is some explicit reason to believe that, then in PPJ we could have the formula  $P_{\geq 0.8}(t : P_{\geq 0.3}p)$ , with a meaning like “I am uncertain for a particular justification of this coin being counterfeit, e.g. because this coin looks similar to a counterfeit coin I have seen some time ago”. As another application of PPJ, in [19] we have shown that the lottery paradox [23] can be analysed in this logic. The lottery paradox goes as follows: assume that we have 1,000 tickets in a lottery where every ticket has the same probability to win and there is exactly one winning ticket. Now assume a proposition is believed if and only if its degree of belief is greater than 0.99. In this setting it is rational to believe that ticket 1 does not win, it is rational to believe that ticket 2 does not win, and so on. However, this entails that it is rational to believe that no ticket wins because rational belief is closed under conjunction. Hence, it is rational to believe that no ticket wins and (of course) it is rational to believe that one ticket wins, which is absurd. In [19] we have formalized the lottery paradox in PPJ and we have also proposed a solution for avoiding the paradox via restricting the axioms that are justified in PPJ.

A model for a non-iterated probabilistic logic is a probability space where the events are models of the base logic. A model for an iterated probabilistic

logic is a probability space where the events contain models of the base logic and other probability spaces, so that we can deal with iterated probabilities. One can say that the models for iterated probabilistic logics look like Kripke structures, where the accessibility relation is replaced by a probability measure. The satisfiability problem for a probabilistic logic is to decide whether such a model that satisfies a given formula exists. In the 1980s Georgakopoulos et al. [12] studied a problem that is very similar to the satisfiability problem in probabilistic logics. This problem is called PSAT and it is a probabilistic version of the famous satisfiability problem in classical propositional logic (i.e. the well known SAT-problem [31]). The problem PSAT can be formalized as follows: assume that we are given a formula in conjunctive normal form and a probability for each clause. Is there a probability distribution (over the set of all possible truth assignments of the variables appearing in the clauses) that satisfies all the clauses? Georgakopoulos et al. reduced PSAT to solving a linear system, and proved that PSAT is NP-complete. Although the expressive power of the formal systems of [10] and [28] is richer than the one of [12], the authors of [10] and [28] were able to use arguments similar to those in [12] to show that the satisfiability problem in their logics is also NP-complete. In [16] we obtained tight bounds for the complexity of the satisfiability problem in non-iterated probabilistic justification logic, using again some results from the theory of linear programming. Fagin and Halpern [11] mention (without giving a complete formal proof) that complexity bounds for the satisfiability problem in a modal logic that allows nesting of the probabilistic operators (like in  $LPP_1$ ) can be obtained by employing an algorithm based on a tableau construction as in classical modal logic [13]. In [17] we used the idea of Fagin and Halpern in order to obtain tight bounds for the complexity of satisfiability in PPJ.

## 1.2 Our Contribution

The goal of this paper is to summarize and generalize the results for the complexity of the satisfiability problem in non-iterated and iterated probabilistic logics. This paper is the extended journal version of [16] and [17] which were presented at "Foundations of Information and Knowledge Systems" in 2016 and the "11th Panhellenic Logic Symposium" in 2017 respectively. The results of [16, 17] refer only to probabilistic justification logic, whereas in the present paper we make clear that our results can be applied to a non-iterated and iterated probabilistic logic over any extension of classical propositional logic. Whereas the result of [16] is a straightforward adaptation of some arguments from [10], the result of [17] is new and non-trivial. The fact that a tableaux method can be used for obtaining complexity bounds for iterated probabilistic logics was already observed in [11], but no formal proof was given. In the short conference papers [19] and [17] we gave decidability and complexity proofs respectively for iterated probabilistic justification logic. In the present paper we give the complexity (and thus decidability proof) for PPJ in full detail using a tableaux method. More precisely, we present upper and lower complexity bounds, for the aforementioned satisfiability problem, which are parameterized on the complex-

ity of satisfiability of conjunctions of positive and negative formulas that have neither a probabilistic nor a classical operator as a top-connective. We also show how our results can be applied to the special cases where the probabilistic logics are defined over classical propositional logic or justification logic.

### 1.3 Outline of the Paper

In Section 2 we give some preliminary definitions and prove a lemma from the theory of linear programming that is necessary for our analysis. In Sections 3 and 4 we obtain complexity bounds for the satisfiability problem in non-iterated and iterated probabilistic logics over any extension of classical propositional logic. In Section 5 we apply the results of Sections 3 and 4 to determine the complexity of satisfiability in probabilistic logics over classical propositional logic and over justification logic. In Section 6 we present our final remarks and present some directions for further research.

## 2 Preliminaries

For the purposes of this paper a *logic* is a formal system, defined via a set of axioms and inference rules, a notion of semantics (i.e. a formal definition of the notion of *model* for the logic), together with a provability and satisfiability relation over some formal language. In this paper we are interested in obtaining complexity bounds for the following decision problem:

**Definition 1** (Satisfiability Problem). Let  $L$  be a logic over some language  $\mathcal{L}$ . The satisfiability problem for  $L$  (denoted as  $L_{SAT}$ ) is the following problem:

given some  $\alpha \in \mathcal{L}$ , is there a model of  $L$  that satisfies  $\alpha$ ?

For a formula  $\alpha$  in the language of some logic  $L$ ,  $\alpha$  is *satisfiable* means that there is an  $L$ -model that satisfies  $\alpha$ . If the satisfiability in  $L$  is defined in worlds of the models, then  $\alpha$  is satisfiable means that there is a model of  $L$ ,  $M$ , and a world  $w$ , such that  $\alpha$  is satisfied in the world  $w$  of  $M$ . Since the satisfiability problem depends only on semantical notions, we will present all the logics without the corresponding axiomatization. The only exceptions are the basic justification logic  $J$  and the iterated probabilistic logic over  $J$ ,  $PPJ$ , where it is necessary to know what the axioms of the logic are, for properly defining the models.

All the logics in this paper are extensions of classical propositional logic. The following definition is very important for our analysis.

**Definition 2** (Basic Formulas). Let  $L$  be a logic over language  $\mathcal{L}$ . The basic formulas of  $\mathcal{L}$  (represented as  $\mathcal{B}(\mathcal{L})$ ) are the formulas of  $\mathcal{L}$  that do not have  $\neg$ ,  $\wedge$  or a probabilistic operator  $P_{\geq s}$  (the probabilistic operators will be formally defined later) as their top-connectives. We assume that  $\mathcal{B}(\mathcal{L})$  contains at least  $\text{Prop}$ , which is a countable set of atomic propositions. We will refer to the elements of  $\mathcal{B}(\mathcal{L})$  as the basic formulas of language  $\mathcal{L}$  or the basic formulas of logic  $L$ .

In the rest of the paper we fix a logic  $L$  over a language  $\mathcal{L}$ . We assume that  $L$  is an extension of classical propositional logic and that  $\mathcal{L}$  is defined by the following grammar:

$$\alpha ::= b \mid \neg\alpha \mid \alpha \wedge \alpha,$$

where  $b \in \mathcal{B}(\mathcal{L})$ . We assume that we are given a function  $v$  which assigns a truth value (T for true and F for false) to elements of  $\mathcal{B}(\mathcal{L})$ . The extension of  $v$  to the elements of  $\mathcal{L}$  is the function  $\bar{v}$ , which is defined classically. Sometimes, we will abuse notation and use the symbol  $v$  in place of  $\bar{v}$ . We will refer to  $v$  (or its extension) as an *evaluation*. We use Greek lower-case letters like  $\alpha, \beta, \gamma, \dots$  for members of  $\mathcal{L}$ . The symbol  $\mathcal{P}$  stands for powerset. We also define the following abbreviations in the standard way:

$$\begin{aligned} \alpha \vee \beta &\equiv \neg(\neg\alpha \wedge \neg\beta) ; \\ \alpha \rightarrow \beta &\equiv \neg\alpha \vee \beta . \end{aligned}$$

From the above discussion it is clear that in order to define the semantics of  $L$  it suffices to determine which are the basic formulas and how the evaluation behaves on them. For example, if we assume that the basic formulas are atomic propositions (i.e. elements of **Prop**) and that the evaluation is a classical truth assignment, then we have defined the language and semantics of classical propositional logic.

In the next sections we define probabilistic logics over  $L$ . Models for these logics are probability spaces where the events are models for  $L$  (and in the iterated case contain other probability spaces too). In order to formally present these models, we need the following definitions:

**Definition 3** ( $\sigma$ -Algebra Over a Set). Let  $W$  be a non-empty set and let  $H$  be a non-empty subset of  $\mathcal{P}(W)$ . We call  $H$  a  $\sigma$ -algebra over  $W$  if the following hold:

- $W \in H$  ;
- $U \in H \implies W \setminus U \in H$  .
- For any countable collection of elements of  $H, U_0, U_1, \dots$ , it holds that:

$$\bigcup_{i \in \mathbb{N}} U_i \in H .$$

**Definition 4** ( $\sigma$ -Additive Measure). Let  $H$  be a  $\sigma$ -algebra over  $W$  and assume that  $\mu : H \rightarrow [0, 1]$ . We call  $\mu$  a  $\sigma$ -additive measure if the following hold:

- (1)  $\mu(W) = 1$ .
- (2) Let  $U_0, U_1, \dots$  be a countable collection of pairwise disjoint elements of  $H$ . Then:

$$\mu \left( \bigcup_{i \in \mathbb{N}} U_i \right) = \sum_{i \in \mathbb{N}} \mu(U_i).$$

**Definition 5** (Probability Space). A *probability space* is a structure  $\langle W, H, \mu \rangle$ , where:

- $W$  is a non-empty set;
- $H$  is a  $\sigma$ -algebra over  $W$ ;
- $\mu : H \rightarrow [0, 1]$  is a  $\sigma$ -additive measure.

The members of  $H$  are called *measurable* sets.

A *finitely additive* measure can be defined by assuming a finite, instead of a countable, union in the previous definitions. Semantics for probabilistic logics over classical propositional logic has been given both for  $\sigma$ - and for finitely additive measures [28]. Semantics for probabilistic logics over justification logic [18, 19] has been given only for finitely additive measures. However, after the small model theorems that we will prove, the probability spaces in the models will be finite, so the results of this paper hold for the finitely additive case too.

As we mentioned in the introduction, decidability and complexity results in probabilistic logics heavily depend on results from the theory of linear programming. In this paper we will use a theorem that provides bounds on the size of a solution of a linear system using the sizes of the constants that appear in the system. Before showing this result, we need to define the size for non-negative integers and rational numbers and to present Theorem 7. We use **bold** font for vectors. The superscript  $*$  in a vector denotes that the vector represents a solution of some linear system.

**Definition 6** (Sizes). Let  $r$  be a non-negative integer. The size of  $r$ , represented as  $|r|$ , is the number of bits needed for representing  $r$  in the binary system. If  $r = \frac{s_1}{s_2}$  is a rational number, where  $s_1$  and  $s_2$  are relatively prime non-negative integers with  $s_2 \neq 0$ , then the size of  $r$  is  $|r| := |s_1| + |s_2|$ .

**Theorem 7** ([7, p. 145]). Let  $\mathcal{S}$  be a system of  $r$  linear equalities. Assume that the vector  $\mathbf{x}^*$  is a solution of  $\mathcal{S}$  such that all of  $\mathbf{x}^*$ 's entries are non-negative. Then there is a vector  $\mathbf{y}^*$  such that

- (1)  $\mathbf{y}^*$  is a solution of  $\mathcal{S}$ ;
- (2) all the entries of  $\mathbf{y}^*$  are non-negative;
- (3) at most  $r$  entries of  $\mathbf{y}^*$  are positive.

Theorem 8 provides the announced bounds on the solution of a linear system. A sketch of its proof was given in [10, Lemmata 2.5 and 2.7]. To make our presentation complete, we provide a detailed proof here.

**Theorem 8.** Let  $\mathcal{S}$  be a linear system of  $n$  variables and of  $r$  linear equalities and/or inequalities with integer coefficients each of size at most  $l$ . Assume that the vector  $\mathbf{x}^* = x_1^*, \dots, x_n^*$  is a solution of  $\mathcal{S}$  such that for all  $i \in \{1, \dots, n\}$ ,  $x_i^* \geq 0$ . Then, there is a vector  $\mathbf{y}^* = y_1^*, \dots, y_n^*$  that satisfies the following properties

- (1)  $\mathbf{y}^*$  is a solution of  $\mathcal{S}$ ;
- (2) at most  $r$  entries of  $\mathbf{y}^*$  are positive;
- (3) for all  $i$ ,  $y_i^*$  is a non-negative rational number with size bounded by

$$2 \cdot (r \cdot l + r \cdot \log_2(r) + 1) .$$

*Proof.* We make the following conventions:

- All vectors used in this proof have  $n$  entries. The entries of the vectors are assumed to be in one to one correspondence with the variables that appear in the original system  $\mathcal{S}$ .
- Let  $\mathbf{y}^*$  be a solution of a linear system  $\mathcal{T}$ . If  $\mathbf{y}^*$  has more entries than the variables of  $\mathcal{T}$  we imply that entries of  $\mathbf{y}^*$  that correspond to variables appearing in  $\mathcal{T}$  compose a solution of  $\mathcal{T}$ .
- Assume that system  $\mathcal{T}$  has less variables than system  $\mathcal{T}'$ . When we say that any solution of  $\mathcal{T}$  is a solution of  $\mathcal{T}'$  we imply that the missing variables are set to 0.

Assume that the original system  $\mathcal{S}$  contains an inequality of the form:

$$b_1 \cdot x_1 + \dots + b_n \cdot x_n \odot c , \tag{1}$$

for  $\odot \in \{<, \leq, \geq, >\}$  where  $x_1, \dots, x_n$  are variables and  $b_1, \dots, b_n, c$  are constants that appear in  $\mathcal{S}$ . Vector  $\mathbf{x}^*$  is a solution of (1). We replace the inequality (1) in  $\mathcal{S}$  with the following equality:

$$b_1 \cdot x_1 + \dots + b_n \cdot x_n = b_1 \cdot x_1^* + \dots + b_n \cdot x_n^* .$$

We repeat this procedure for every inequality of  $\mathcal{S}$ . This way we obtain a system of linear equalities which we call  $\mathcal{S}_0$ . It is easy to see that  $\mathbf{x}^*$  is a solution of  $\mathcal{S}_0$  and that any solution of  $\mathcal{S}_0$  is also a solution of  $\mathcal{S}$ .

Now we will transform  $\mathcal{S}_0$  to another linear system by applying the following algorithm:

- (i) Set  $i := 0$ ,  $e_0 := r$ ,  $v_0 := n$ ,  $\mathbf{x}^{*,0} := \mathbf{x}^*$ . Go to step (ii).
- (ii) If  $e_i = v_i$  then go to step (iii). Otherwise go to step (iv).
- (iii) If the determinant of  $\mathcal{S}_i$  is non-zero then stop. Otherwise go to step (vi).
- (iv) If  $e_i < v_i$  then go to step (v), else go to step (vi).
- (v) We know that the vector  $\mathbf{x}^{*,i}$  is a non-negative solution for the system  $\mathcal{S}_i$ . From Theorem 7 we obtain a solution  $\mathbf{x}^{*,i+1}$  for the system  $\mathcal{S}_i$  which has at most  $e_i$  entries positive. In  $\mathcal{S}_i$  we replace the variables that correspond to zero entries of the solution  $\mathbf{x}^{*,i+1}$  with zeros. We obtain a new system which we call  $\mathcal{S}_{i+1}$  with  $e_{i+1} = e_i$  equalities and  $v_{i+1} = e_i < v_i$  variables. Vector  $\mathbf{x}^{i+1}$  is a solution of  $\mathcal{S}_{i+1}$  and any solution of  $\mathcal{S}_{i+1}$  is a solution of  $\mathcal{S}_i$ . We set  $i := i + 1$  and we go to step (ii).
- (vi) We know that the vector  $\mathbf{x}^{*,i}$  is a non-negative solution for the system  $\mathcal{S}_i$ . From Theorem 7 we obtain a solution  $\mathbf{x}^{*,i+1}$  for the system  $\mathcal{S}_i$  which has at most  $e_i$  entries positive. In  $\mathcal{S}_i$  we replace the variables that correspond to zero entries of the solution  $\mathbf{x}^{*,i+1}$  with zeros. We obtain a new system which we call  $\mathcal{S}_{i+1}$  with  $e_{i+1} = e_i$  equalities and  $v_{i+1} = e_i < v_i$  variables. Vector  $\mathbf{x}^{i+1}$  is a solution of  $\mathcal{S}_{i+1}$  and any solution of  $\mathcal{S}_{i+1}$  is a solution of  $\mathcal{S}_i$ . We set  $i := i + 1$  and we go to step (ii).

- (vi) We remove only one equation that can be written as a linear combination of some others. We obtain a new system which we call  $\mathcal{S}_{i+1}$  with  $e_{i+1} = e_i - 1$  equalities and  $v_{i+1} = v_i$  variables. We set  $i := i + 1$  and  $\mathbf{x}^{*,i+1} := \mathbf{x}^{*,i}$ . We go to step (ii).

From steps (v) and (vi) it is clear that during the execution of the above algorithm, the sum of the number of variables and equations decreases. Therefore, the algorithm terminates.

Let  $I$  be the final value of  $i$  after the execution of the algorithm. Since the only way for our algorithm to terminate is through step (iii) it holds that system  $\mathcal{S}_I$  is an  $e_I \times e_I$  system of linear equalities with non-zero determinant (for  $e_I \leq r$ ). System  $\mathcal{S}_I$  is obtained from system  $\mathcal{S}_0$  by possibly replacing some variables that correspond to zero entries of the solution with zeros and by possibly removing some equalities (that have a linear dependence on others). So, any solution of  $\mathcal{S}_I$  is also a solution of  $\mathcal{S}_0$  and thus a solution of  $\mathcal{S}$ . From the algorithm we have that  $\mathbf{x}^{*,I}$  is a solution of  $\mathcal{S}_I$ . Since  $\mathcal{S}_I$  has a non-zero determinant Cramer's rule can be applied. Hence, the vector  $\mathbf{x}^{*,I}$  is the unique solution of system  $\mathcal{S}_I$ . Let  $x_i^{*,I}$  be an entry of  $\mathbf{x}^{*,I}$ . Entry  $x_i^{*,I}$  is equal to the following rational number:

$$\frac{\begin{vmatrix} a_{11} & \dots & a_{1e_I} \\ & \ddots & \\ a_{e_I 1} & \dots & a_{e_I e_I} \end{vmatrix}}{\begin{vmatrix} b_{11} & \dots & b_{1e_I} \\ & \ddots & \\ b_{e_I 1} & \dots & b_{e_I e_I} \end{vmatrix}},$$

where all the  $a_{ij}$  and  $b_{ij}$  are integers that appear in the original system  $\mathcal{S}$ . By properties of the determinant we know that the numerator and the denominator of the above rational number will each be at most equal to  $r! \cdot (2^l - 1)^r$ . So we have that:

$$\begin{aligned} |x_i^{*,I}| &\leq 2 \cdot (\log_2(r! \cdot (2^l - 1)^r) + 1) && \implies \\ |x_i^{*,I}| &\leq 2 \cdot (\log_2(r^r \cdot 2^{l \cdot r}) + 1) && \implies \\ |x_i^{*,I}| &\leq 2 \cdot (r \cdot \log_2(r) + l \cdot r + 1). \end{aligned}$$

As we already mentioned the final vector  $\mathbf{x}^{*,I}$  is a solution of the original linear system  $\mathcal{S}$ . We also have that all the entries of  $\mathbf{x}^{*,I}$  are non-negative, at most  $r$  of its entries are positive and the size of each entry of  $\mathbf{x}^{*,I}$  is bounded by  $2 \cdot (r \cdot \log_2 r + r \cdot l + 1)$ . So,  $\mathbf{x}^{*,I}$  is the desired vector  $\mathbf{y}^*$ .  $\blacksquare$

### 3 Non-Iterated Probabilistic Logics

In Subsection 3.1 we define the semantics for non-iterated probabilistic logics. In Subsection 3.2 we prove a small model property and in Subsection 3.3 we present a conditional complexity upper bound for these logics.

### 3.1 Semantics

The non-iterated probabilistic logic over  $L$  is the logic PL. The language of PL is defined by adding non-nested probabilistic operators to the language  $\mathcal{L}$ . Formally,  $\mathcal{L}_{\text{PL}} = \mathcal{L}'_{\text{PL}} \cup \mathcal{L}$ , where  $\mathcal{L}'_{\text{PL}}$  is described by the following grammar:

$$A ::= P_{\geq s}\alpha \mid \neg A \mid A \wedge A ,$$

where  $s \in \mathbb{Q} \cap [0, 1]$  and  $\alpha \in \mathcal{L}$ . Recall that by definition, the basic formulas of PL are the formulas of  $\mathcal{L}_{\text{PL}}$  that do not have  $\neg, \wedge$  or a probabilistic operator as a top connective. Hence we have that  $\mathcal{B}(\mathcal{L}_{\text{PL}}) = \mathcal{B}(\mathcal{L}) \supseteq \text{Prop}$ , i.e.  $\mathcal{L}_{\text{PL}}$  has the same basic formulas as  $\mathcal{L}$ . The intended meaning of the formula  $P_{\geq s}\alpha$  is that “the probability of truthfulness for  $\alpha$  is at least  $s$ ”. For  $\mathcal{L}_{\text{PL}}$ , we assume the same abbreviations as for  $\mathcal{L}$ . The operator  $P_{\geq s}$  is assumed to have greater precedence than all the connectives of  $\mathcal{L}$ . We also define the following syntactical abbreviations:

$$\begin{aligned} P_{< s}\alpha &\equiv \neg P_{\geq s}\alpha ; \\ P_{\leq s}\alpha &\equiv P_{\geq 1-s}\neg\alpha ; \\ P_{> s}\alpha &\equiv \neg P_{\leq s}\alpha ; \\ P_{= s}\alpha &\equiv P_{\geq s}\alpha \wedge P_{\leq s}\alpha . \end{aligned}$$

We use capital Latin letters like  $A, B, C, \dots$  for members of  $\mathcal{L}'_{\text{PL}}$  possibly primed or with subscripts.

*Remark 9.* In the literature non-iterated logics either contained [28] or did not contain [18] the formulas of the base logic. In this paper we opted for the first choice. This makes our approach more uniform since all of our logics are extension of classical propositional logic. We have to point out that as far as decidability and complexity is concerned, both approaches are practically the same: if the language of the non-iterated probabilistic logic contains formulas of the base logic, then we simply have to use the decidability algorithm for the base logic too.

A model for PL is a probability space where the events (also called worlds) are models for  $L$ . In order to determine the probability of truthfulness for an  $\mathcal{L}$ -formula  $\alpha$  in such a probability space we have to find the measure of the set containing all  $\mathcal{L}$ -models that satisfy  $\alpha$ . More formally, we have the following:

**Definition 10** (PL-Model). Let  $M = \langle W, H, \mu, v \rangle$  where

- $\langle W, H, \mu \rangle$  is a probability space ;
- $v$  is a function that assigns an evaluation to every  $w$  in  $W$ . We write  $v_w$  instead of  $v(w)$ .

$M$  is a PL-model if  $[\alpha]_M \in H$  for every  $\alpha \in \mathcal{L}$ , where

$$[\alpha]_M = \{w \in W \mid v_w(\alpha) = \top\} .$$

We will drop the subscript  $M$ , i.e. we will simply write  $[\alpha]$ , if this causes no confusion.

**Definition 11** (Truth in a PL-model). Let  $M = \langle W, H, \mu, v \rangle$  be a PL-model. The truth of  $\mathcal{L}'_{\text{PL}}$ -formulas that have a probabilistic operator as their top-connective is defined as follows (the formulas with top-connectives  $\neg$  and  $\wedge$  are treated classically):

$$M \models P_{\geq s} \alpha \iff \mu([\alpha]_M) \geq s .$$

Also if  $\alpha$  is an  $\mathcal{L}$ -formula then

$$M \models \alpha \iff [\alpha]_M = W .$$

We observe that in order to present the formal semantics of a non-iterated probabilistic logic, we have to define the basic formulas and explain how the evaluation behaves on them.

### 3.2 Small Model Property

In this subsection we show that if  $A \in \mathcal{L}'_{\text{PL}}$  is satisfiable then it is satisfiable in a model that satisfies the following properties:

- the number of worlds and the probabilities assigned to them have size polynomial in the size of  $A$
- the evaluations assigned to every world depend only on the subformulas of  $A$ .

After we have established this result, it is easy to obtain the upper complexity bound for PL: we can simply guess the model in polynomial time and then, with the help of some oracles, verify that it satisfies  $A$ .

First we need some definitions. The set of subformulas of some formula  $A$ , represented as  $\text{subf}(A)$ , is defined as usual. The size of  $A$ , represented as  $|A|$ , is the number of symbols needed to write  $A$ . In order to compute  $|A|$ , the size of every probabilistic operator counts as one. For example,  $|\neg P_{\geq \frac{1}{5}} p| = 3$ . For  $A \in \mathcal{L}_{\text{PL}}$  we define

$$\|A\| := \max \{ |s| \mid P_{\geq s} \alpha \in \text{subf}(A) \} .$$

**Definition 12** (Conjunctions of Positive and Negative Basic Formulas). Let  $A \in \mathcal{L}_{\text{PL}}$ . The set of conjunctions of positive and negative basic formulas of  $A$  is the following set:

$$\text{cpnb}(A) = \left\{ a \mid a \text{ is of the form } \bigwedge_{B \in \text{subf}(A) \cap \mathcal{B}(\mathcal{L})} \pm B \right\} ,$$

where  $\pm B$  denotes either  $B$  or  $\neg B$ . The acronym **cpnb** stands for conjunction of positive and negative basic formulas. If  $a \in \text{cpnb}(A)$  for some  $A$  and there is no danger of confusion we may say that  $a$  is **cpnb**-formula. We use the lower-case Latin letter  $a$  for **cpnb**-formulas, possibly with subscripts.

Let  $A$  be of the form  $\bigwedge_i B_i$  or of the form  $\bigvee_i B_i$ . Then  $C \in A$  means that for some  $i$ ,  $B_i \equiv C$ .

Theorem 13 proves the announced small model property. It is an adaptation of the small model Theorem 2.6 of [10]. In [16] the proof of the small property unnecessarily depends on the completeness theorem for PJ. In Theorem 13 we remedy this mistake.

**Theorem 13** (Small Model Property for PL). *Let  $A \in \mathcal{L}'_{\text{PL}}$ . If  $A$  is PL-satisfiable then it is satisfiable in a PL-model  $M = \langle W, H, \mu, v \rangle$  such that*

- (1)  $|W| \leq |A|$ ;
- (2)  $H = \mathcal{P}(W)$ ;
- (3) For every  $w \in W$ ,  $\mu(\{w\})$  is a non-negative rational number with size at most  $2 \cdot (|A| \cdot ||A|| + |A| \cdot \log_2(|A|) + 1)$ ;
- (4) For every  $a \in \text{cpnb}(A)$ , there exists at most one  $w \in W$  such that  $\bar{v}_w(a) = \text{T}$ .

*Proof.* Let  $A$  be satisfiable in some PL-model. We divide the proof in two parts:

- we show that the satisfiability of  $A$  implies that a linear system  $\mathcal{S}$  is satisfiable;
- we use a solution of  $\mathcal{S}$  to define the model  $M$  for  $A$  that satisfies the properties (1)–(4).

**Finding the Satisfiable Linear System.** Let  $R$  be some PL-model. By propositional reasoning we can show that

$$R \models A \iff R \models \bigvee_{i=1}^K \bigwedge_{j=1}^{l_i} P_{\odot_{ij} s_{ij}}(\alpha^{ij}) . \quad (2)$$

for some  $K$  and  $l_i$ 's, such that for each  $i$  and for each  $j$ ,  $\odot_{ij} \in \{\geq, <\}$  and  $\alpha^{ij}$  is a disjunction of elements of  $\text{cpnb}(A)$ . Since  $A$  is satisfiable, Eq. (2) implies that there exists a PL-model  $M' = \langle W', H', \mu', v' \rangle$  and some  $1 \leq i \leq K$  such that

$$M' \models \bigwedge_{j=1}^{l_i} P_{\odot_{ij} s_{ij}}(\alpha^{ij}) . \quad (3)$$

Let  $\text{cpnb}(A) = \{a_1, \dots, a_n\}$ . For every  $k \in \{1, \dots, n\}$  we define

$$x_k^* = \mu'([a_k]_{M'}) . \quad (4)$$

In every world of  $M'$  some atom of  $A$  must hold. Thus, we have

$$\mu' \left( \bigcup_{k=1}^n [a_k]_{M'} \right) = 1 . \quad (5)$$

All the  $a_k$ 's belong to  $\text{cpnb}(A)$ , so for all  $k, k' \in \{1, \dots, n\}$ , we have

$$k \neq k' \implies [a_k]_{M'} \cap [a_{k'}]_{M'} = \emptyset. \quad (6)$$

By Eqs. (4),(5),(6) and the additivity of  $\mu'$  we get

$$\sum_{k=1}^n x_k^* = 1. \quad (7)$$

Let  $j \in \{1, \dots, l_i\}$ . From Eq. (3) we get  $M' \models P_{\odot_{ij} s_{ij}}(\alpha^{ij})$ . This implies that  $\mu'([\alpha^{ij}]_{M'}) \odot_{ij} s_{ij}$ , i.e.

$$\mu' \left( \left[ \bigvee_{a_k \in \alpha^{ij}} a_k \right]_{M'} \right) \odot_{ij} s_{ij},$$

from which we can show that

$$\mu' \left( \bigcup_{a_k \in \alpha^{ij}} [a_k]_{M'} \right) \odot_{ij} s_{ij}.$$

By Eq. (4), (6) and the additivity of  $\mu'$  we have that

$$\sum_{a_k \in \alpha^{ij}} x_k^* \odot_{ij} s_{ij}.$$

So we have that

$$\text{for every } j \in \{1, \dots, l_i\}, \quad \sum_{a_k \in \alpha^{ij}} x_k^* \odot_{ij} s_{ij}. \quad (8)$$

By Eqs. (7) and (8) it is clear that the vector  $\mathbf{x}^* = x_1^*, \dots, x_n^*$  is a non-negative solution of a linear system, call it  $\mathcal{S}$ . By Theorem 8 we have that there exists a vector  $\mathbf{y}^* = y_1^*, \dots, y_n^*$ , with non-negative entries, that is a solution of  $\mathcal{S}$  and has at most  $N$  entries (strictly) positive, where  $0 < N \leq |A|$ . Without loss of generality we assume that  $y_1^*, \dots, y_N^*$  are the positive entries of  $\mathbf{y}^*$ . Since every  $x_k^*$  corresponds to a  $\text{cpnb}$ -formula of  $A$  we can associate every positive  $y_k^*$  with the satisfiable atom  $a_k$ .

**Defining the Model  $M$  for  $A$ .** The quadruple  $M = \langle W, H, \mu, v \rangle$  is defined as follows:

- (a)  $W = \{w_1, \dots, w_N\}$ , for some  $w_1, \dots, w_N$ ;
- (b)  $H = \mathcal{P}(W)$ ;
- (c) For all  $V \in H$ ,

$$\mu(V) = \sum_{w_k \in V} y_k^*;$$

(d) Let  $i \in \{1, \dots, N\}$ .  $v_{w_i}$  is an evaluation that satisfies  $a_i$ .  
 By using the fact that each  $y^*$  is a solution of  $\mathcal{S}$  we can show that  $M$  is a PL-model. We will now prove the following statement:

$$(\forall 1 \leq k \leq N) [w_k \in [\alpha^{ij}]_M \iff a_k \in \alpha^{ij}] . \quad (9)$$

Let  $k \in \{1, \dots, N\}$ . We prove the two directions of Eq. (9) separately.

( $\implies$ ) Assume that  $w_k \in [\alpha^{ij}]_M$ . This means that  $v_{w_k}(\alpha^{ij}) = \top$ . Assume that  $a_k \notin \alpha^{ij}$ . Then, since  $\alpha^{ij}$  is a disjunction of some atoms of  $A$ , there must exist some  $a_{k'} \in \alpha^{ij}$ , with  $k \neq k'$ , such that  $v_{w_k}(a_{k'}) = \top$ . However, by definition we have that  $v_{w_k}(a_k) = \top$ . But this is a contradiction, since  $a_k$  and  $a_{k'}$  are different atoms of the same formula, which means that they cannot be satisfied in the same evaluation. Hence,  $a_k \in \alpha^{ij}$ .

( $\impliedby$ ) Assume that  $a_k \in \alpha^{ij}$ . We know that  $v_{w_k}(a_k) = \top$ , which implies that

$$v_{w_k}(\alpha^{ij}) = \top, \text{ i.e. } w_k \in [\alpha^{ij}]_M .$$

Hence, Eq. (9) holds. Now, we will prove the following statement:

$$(\forall 1 \leq j \leq l_i) [M \models P_{\odot_{ij} s_{ij}} \alpha^{ij}] . \quad (10)$$

Let  $j \in \{1, \dots, l_i\}$ . It holds

$$\begin{aligned} M \models P_{\odot_{ij} s_{ij}}(\alpha^{ij}) & \iff \\ \mu([\alpha^{ij}]_M) \odot_{ij} s_{ij} & \iff \\ \sum_{w_k \in [\alpha^{ij}]_M} y_k^* \odot_{ij} s_{ij} & \stackrel{\text{Eq. (9)}}{\iff} \\ \sum_{a_k \in \alpha^{ij}} y_k^* \odot_{ij} s_{ij} . & \end{aligned}$$

The last statement holds because  $y^*$  is a solution of  $\mathcal{S}$ . Thus, Eq. (10) holds.

By Eq. (10) we have that  $M \models \bigwedge_{j=1}^{l_i} P_{\odot_{ij} s_{ij}}(\alpha^{ij})$ , which implies that

$$M \models \bigvee_{i=1}^K \bigwedge_{j=1}^{l_i} P_{\odot_{ij} s_{ij}}(\alpha^{ij}),$$

which, by Eq. (2), implies that  $M \models A$ .

So, we have that each  $w_i$  corresponds to one satisfiable  $a_i$  and also that  $\mu(\{w_i\}) = y_i^*$ . Since the number of positive  $y_i^*$ 's is at most  $|A|$  and the size of every positive  $y_i^*$  is at most  $2 \cdot (|A| \cdot ||A|| + |A| \log_2(|A|) + 1)$ , we have that  $M$  is, indeed, the model in question.  $\blacksquare$

The small model property shows that the formula is satisfied in a structure with small number of worlds, small probabilities assigned to each world and that in every world of this structure a unique **cpnb**-formula holds. The following Lemma shows these **cpnb**-formulas that hold in the worlds practically define evaluations for the formula that is tested for satisfiability.

**Lemma 14.** *Let  $\alpha \in \mathcal{L}$ , let  $v_1, v_2$  be two evaluations and assume that, for every basic formula  $\beta$  that appears in  $\alpha$*

$$v_1(\beta) = v_2(\beta) .$$

*Then we have*

$$\bar{v}_1(\alpha) = \bar{v}_2(\alpha) .$$

### 3.3 Complexity Bounds

In this subsection we obtain the conditional upper bound for  $\text{PL}_{\text{SAT}}$ . The upper bound follows from the fact that for a given PL-formula  $A$ , we can guess a small model for it and then verify that this model indeed satisfies  $A$ .

As a first step we need the following Lemma which can be proved by an easy induction on the complexity of the formula.

**Lemma 15.** *Let  $\alpha \in \mathcal{L}$  and let  $a \in \text{cpnb}(\alpha)$ . Let  $v$  be an evaluation and assume that  $\bar{v}(a) = \text{T}$ . The decision problem*

*does  $\bar{v}$  satisfy  $\alpha$ ?*

*belongs to the complexity class P.*

Now we are ready to prove the upper complexity bound for  $\text{PL}_{\text{SAT}}$ .

**Theorem 16.** *Assume that the satisfiability problem for cpnb-formulas in the logic L belongs to the complexity class C. Then  $\text{PL}_{\text{SAT}} \in \text{NP}^{\text{C}}$ .*

*Proof.* Let  $A \in \mathcal{L}_{\text{PL}}$  and let  $\mathcal{A}$  be the C-algorithm that can test cpnb-formulas in L for satisfiability. If  $A \in \mathcal{L}$  then  $A$  is equivalent to a disjunction of cpnb-formulas (i.e.  $A$  can be seen as a formula in disjunctive normal form). So, we guess one of these formulas and using  $\mathcal{A}$  verify that it is satisfiable in polynomial time using Lemma 15. Of course this can be done in nondeterministic polynomial time using a C-oracle.

For the rest of the proof we assume that  $A \in \mathcal{L}'_{\text{PL}}$ , i.e. that  $A$  contains probabilistic operators. A non-deterministic algorithm that tests  $A$  for satisfiability can simply guess a model for  $A$  that satisfies conditions (1)–(4) that appear in the statement of Theorem 13. We present a non-deterministic algorithm that performs this guess and we evaluate its complexity.

**Algorithm.** We guess  $n$  elements of  $\text{cpnb}(A)$ , call them  $a_1, \dots, a_n$ , and we also choose  $n$  worlds,  $w_1, \dots, w_n$ , for  $n \leq |A|$ . Using  $\mathcal{A}$  we can verify that for each  $i \in \{1, \dots, n\}$  there exists an evaluation  $\bar{v}_i$  such that  $\bar{v}_i(a_i) = \text{T}$ . We define  $W = \{w_1, \dots, w_n\}$  and for every  $i \in \{1, \dots, n\}$  we set  $v_{w_i} = \bar{v}_i$ . Since we are only interested in the satisfiability of basic formulas that appear in  $A$ , by Lemma 14, the choice of the  $v_{w_i}$  is not important (as long as  $v_{w_i}$  satisfies  $a_i$ ). We assign to every  $\mu(\{w_i\})$  a rational number with size at most

$$2 \cdot (|A| \cdot \|A\| + |A| \cdot \log_2(|A|) + 1) .$$

We set  $H = \mathcal{P}(W)$  and for every  $V \in H$  we set

$$\mu(V) = \sum_{w_i \in V} \mu(\{w_i\}) .$$

It is then straightforward to see that conditions (1)–(4) that appear in the statement of Theorem 13 hold.

Now we have to verify that our guess is correct, i.e. that  $M \models A$ . Assume that  $P_{\geq s}\alpha$  appears in  $A$ . In order to see whether  $P_{\geq s}\alpha$  holds we need to calculate the measure of the set  $[\alpha]_M$  in the model  $M$ . The set  $[\alpha]_M$  will contain every  $w_i \in W$  such that  $v_{w_i}(\alpha) = \mathbf{T}$ . Since  $v_{w_i}$  satisfies an atom of  $A$  it also satisfies an atom of  $\alpha$ . So, by Lemma 15, we can check whether  $*_{w_i}$  satisfies  $\alpha$  in polynomial time. If  $\sum_{w_i \in [\alpha]_M} \mu(\{w_i\}) \geq s$  then we replace  $P_{\geq s}\alpha$  in  $A$  with the truth value  $\mathbf{T}$ , otherwise with the truth value  $\mathbf{F}$ . We repeat the above procedure for every formula of the form  $P_{\geq s}\alpha$  that appears in  $A$ . At the end we have a formula that is constructed only from the connectives  $\neg, \wedge$  and the truth constants  $\mathbf{T}$  and  $\mathbf{F}$ . Obviously, we can verify in polynomial time that the formula is true. This, of course, implies that  $M \models A$ .

**Complexity Evaluation.** All the objects that are guessed in our algorithm have size that is polynomial in the size of  $A$ . Also the verification phase of our algorithm can be made in polynomial time. Furthermore checking whether an element of  $\text{cpnb}(\alpha)$  is satisfiable is possible with a C-oracle. Thus, our  $\text{PL}_{\text{SAT}}$  belongs to the class  $\text{NP}^{\text{C}}$ . ■

## 4 Iterated Probabilistic Logics

### 4.1 Semantics

The iterated probabilistic logic over  $\mathbf{L}$  is the logic PPL (the two P’s stand for the iterations of the probability operator). The language of PPL,  $\mathcal{L}_{\text{PPL}}$ , is defined by adding nested probabilistic operators to the language  $\mathcal{L}$ . Formally,  $\mathcal{L}_{\text{PPL}}$  is defined by the following grammar:

$$A ::= b \mid \neg A \mid A \wedge A \mid P_{\geq s}A ,$$

where  $s \in \mathbb{Q} \cap [0, 1]$  and  $b \in \mathcal{B}(\mathcal{L}_{\text{PPL}}) \supseteq \mathcal{B}(\mathcal{L})$ . We will use upper-case latin letters like  $A, B, C, \dots$  for members of  $\mathcal{L}_{\text{PPL}}$ .

Models for PPL are probability spaces where the worlds contain evaluations and probability spaces (so that we can deal with iterated probabilities). Formally, we have

**Definition 17** (PPL-Model and Truth in a PPL-Model). Assume that  $M = \langle U, W, H, \mu, v \rangle$  where:

1.  $U$  is a non-empty set of objects called worlds;
2. for every  $w \in U$ ,

$\langle W_w, H_w, \mu_w \rangle$  is a probability space with  $W_w \subseteq U$  and  $v_w$  is an evaluation.

Truth in  $M$  is defined as follows (the connectives  $\neg$  and  $\wedge$  are treated classically):

$$\begin{aligned} M, w \models A &\iff v_w(A) = \top \text{ for } A \in \mathcal{B}(\mathcal{L}_{\text{PPL}}) ; \\ M, w \models P_{\geq s} A &\iff \mu_w([A]_{M,w}) \geq s. \end{aligned}$$

$M$  is a PPL-model if for every  $A \in \mathcal{L}_{\text{PPL}}$  and every  $w \in U$ ,  $[A]_{M,w} \in H_w$ , where

$$[A]_{M,w} = \{u \in W_w \mid M, u \models A\}.$$

We observe that, as in the non-iterated case, in order to formally define the semantics of an iterated probabilistic logic it suffices to define the basic formulas of PPL and how the evaluation behaves on them.

## 4.2 Complexity Bounds

In this section we obtain complexity bounds for  $\text{PPL}_{\text{SAT}}$ . The upper bound is obtained via a tableaux procedure, which resembles the tableaux procedure for modal logic [13]. The idea for obtaining this upper bound for a modal logic that contains probabilistic operators similar to ours was sketched in [11, Theorem 4.5], but no complete formal proof was given there. The lower bound is obtained by drawing a reduction from modal logic D [13].

### 4.2.1 The Upper Bound

As a first step we need the following definition:

**Definition 18** (Conjunctions of Positive and Negative Formulas). For  $A_1, \dots, A_n \in \mathcal{L}_{\text{PPL}}$ , we define the following set:

$$\text{cpnf}(A_1, \dots, A_n) = \left\{ a \mid a \text{ is of the form } \bigwedge_{i=1}^n \pm A_i \right\}.$$

The acronym **cpnf** stands for conjunction of positive and negative formulas. As for the **cpnb**-formulas we will use the possibly primed or subscripted lower-case Latin letter  $a$  for **cpnf**-formulas. If  $a \in \text{cpnf}(A_1, \dots, A_n)$  for some  $A_1, \dots, A_n$  and there is no danger of confusion, we may say that  $a$  is a **cpnf**-formula.

We now present the announced tableaux method. Our tableaux are trees where the nodes are formulas prefixed with world and truth signs. So, the node  $w \top A$  ( $w \text{ F } A$ ) intuitively means that formula  $A$  is true (respectively false) at world  $w$  of some model. The root of a tableau contains the formula that is tested for satisfiability. The tableaux rules are presented in Table 1. The first line consists of the propositional rules and the second line of the probabilistic rule **prob**. A separator, i.e. the symbol “|”, in the result of the rule means that

$\mathbf{notT} \frac{w \top \neg A}{w \text{ F } A}$	$\mathbf{notF} \frac{w \text{ F } \neg A}{w \top A}$	$\mathbf{andT} \frac{w \top A \wedge B}{w \top A \quad w \top B}$	$\mathbf{andF} \frac{w \text{ F } A \wedge B}{w \text{ F } A \mid w \text{ F } B}$
$\mathbf{prob} \frac{p_{w_{ij}}}{w.1 \top a_1 \mid \cdots \mid w.n \top a_n}$			

Table 1: The Tableaux Rules

the formulas in the conclusion belong to distinct branches. So, only the rules **prob** and **andF** create new branches; the other rules simply add formulas to the branch where the premise belongs.

Every propositional rule gives simpler conditions for satisfiability: if the premise is satisfiable then at least one of the results has to be satisfiable too. The function of rule **prob** is more complicated and requires some explanation. Rule **prob** is the only rule that creates new worlds. So, formulas that belong to a path between two applications of rule **prob** are marked with the same world. Therefore, we can define the notion of a *world path*. A world path is a shortest path in a tableau that starts either from the root or from a result of an application of the rule **prob** and ends either in a leaf or at a premise of an application of the rule **prob**. We assume that the root, each one of the leaves and each application of rule **prob** are marked with unique natural numbers. In the following we will refer to the numbers assigned to the root, the leaves, or the applications of rule **prob** as points. Due to the fact that all nodes in a world path are marked with the same world and lay between two points, we can represent a world path as  $p_{w_{ij}}$  where  $w$  is the world prefix of the formulas in the world path and  $i, j$  are the points. If formula  $A$  appears in world path  $p_{w_{ij}}$  (prefixed either with  $\top$  or with  $\text{F}$ ) we write  $A \in p_{w_{ij}}$ . Now, the function of rule **prob** in Table 1 can be explained in full detail: it is applied in the world path  $p_{w_{ij}}$  and it creates several new branches. Each of these branches is marked with a new world symbol  $w.k$  ( $1 \leq k \leq n$ ). Assume that

$$\{B_1, \dots, B_m\} = \{B \mid P_{\geq s} B \in p_{w_{ij}}\} .$$

Then the formulas  $a_l$  appearing in the result of rule **prob** are defined as follows:

$$\{a_1, \dots, a_n\} = \text{cpnf}(B_1, \dots, B_m) .$$

It is not difficult to see that each  $B_k$  is equivalent to a disjunction of some  $a_l$ 's. Hence the world path  $p_{w_{ij}}$  imposes probabilistic conditions of the form  $P_{\geq s} \bigvee_l a_l$  or  $P_{< s} \bigvee_l a_l$ , which using the fact that the  $a_l$ 's cannot hold in the same world, translate to a condition like “the sum of the measures of some  $a_l$ 's is at least or less than  $s$ ”. So, even if in every result of the rule **prob** a different cpnf-formula has to hold, each of these formulas will be assigned a (possibly) different probability (which could be 0) and these probabilities will have to satisfy some linear conditions imposed by the formulas in  $p_{w_{ij}}$ . Thus, while in the propositional rules we have the property “if the premise holds,

at least one of the results has to hold”, in rule **prob** we have “if the premise holds (i.e. if the conjunction of all the formulas that appear in the world path of the premise hold) then each one of the results have to hold with (possibly) different probability and some sums of these probabilities have to satisfy some linear conditions”.

A world path is called  $P$ -open if there is some  $P_{\geq s}B \in p_{w_{ij}}$ . Otherwise it is called  $P$ -closed. Let  $p_{w_{ij}}$  be a  $P$ -open world path that ends in the application of rule **prob**  $j$ . All the world paths that start from a result of  $j$  are called the *children* of  $p_{w_{ij}}$ . To make the presentation simpler we will use the nodes with the subscription of points as expressions in the metalanguage. So, we simply write “ $w_{ij} \top A$ ” instead of the phrase “the node  $w \top A$  appears in the tableau in the world path between the points  $i$  and  $j$ ”. Observe that the simpler notation  $w \top A$  is ambiguous. The reason is that the application of rule **andF** creates two branches, where the formulas are prefixed with the same world sign. This means that the same formula may occur with the same world sign in different places in the tableau tree. We also have to point out that the points are only necessary for defining the worlds of the model that will be obtained from the tableaux. Even if some points appear in the premise of rule **prob**, they play no role for constructing the tableaux.

For every  $p_{w_{ij}}$  we define the following PPL-formulas:

$$F_{p_{w_{ij}}} = \bigwedge_{w_{ij} \top C} C \wedge \bigwedge_{w_{ij} \text{ F } C} \neg C ;$$

$$B_{p_{w_{ij}}} = \bigwedge_{w_{ij} \top C, C \in \mathcal{B}(\mathcal{L}_{\text{PPL}})} C \wedge \bigwedge_{w_{ij} \text{ F } C, C \in \mathcal{B}(\mathcal{L}_{\text{PPL}})} \neg C .$$

The intuition behind these definitions is that  $F_{p_{w_{ij}}}$  is a conjunction of all the positive and negative formulas (hence the letter  $F$ ) that appear in a world path, whereas  $B_{p_{w_{ij}}}$  is a conjunction of all the positive and negative basic formulas (hence the letter  $B$ ) that appear in a world path. Observe that  $B_{p_{w_{ij}}}$  is always a **cpnb**-formula. Also if  $F_{p_{w_{ij}}}$  is PPL-satisfiable this implies that there is an evaluation that satisfies  $B_{p_{w_{ij}}}$ . Let  $p_{w_{ij}}$  be a premise of an application of rule **prob**. When the conjunction of formulas in  $p_{w_{ij}}$  hold (i.e. when formula  $F_{p_{w_{ij}}}$  holds) some probabilistic conditions are imposed (which are translated to linear conditions in the probabilities assigned to the children of  $p_{w_{ij}}$ ) and also some non-probabilistic conditions have to hold (which are translated to satisfiability conditions imposed to basic formulas appearing in  $p_{w_{ij}}$ , i.e. to the formula  $B_{p_{w_{ij}}}$ ).

The tableau for some  $A \in \mathcal{L}_{\text{PPL}}$  is a tree that is created as follows:

1. Create the node  $w \top A$  (this is the root of the tableau). Go to step 2.
2. Assign to the root, each one of the leaves and every application of the rule **prob** a unique natural number. Go to step 3.
3. Apply the propositional rules for as long as possible. If there exists a  $P$ -open world path, go to step 4. Otherwise stop.

4. Apply the rule **prob** to every  $P$ -open world path. Go to step 3.

Every time a tableaux rule is applied, at least one operator ( $\neg$ ,  $\wedge$  or  $P_{\geq s}$ ) is eliminated. This implies that the tableau for  $A$  is a finite tree.

The goal of the tableaux procedure is to create a model for some formula, if such a model exists. It is important for the reader to keep in mind that the worlds of this model will not be the worlds assigned to each node, i.e. the  $w$ 's. The actual worlds of the model will be the  $w$ 's, subscripted with points, i.e. the  $w_{ij}$ 's. So, it might help the reader to think of the  $w$ 's as pre-worlds, which can be instantiated to several actual worlds, i.e.  $w_{ij}$ 's.

Now we are ready to prove the main theorem of this section.

**Theorem 19.** *Assume that the satisfiability problem for **cpnb**-formulas in the logic PPL belongs to the complexity class  $C$ . Then  $\text{PPL}_{\text{SAT}} \in \text{PSPACE}^C$ .*

*Proof.* Let  $A$  be the  $\mathcal{L}_{\text{PPL}}$ -formula that we want to test for satisfiability. Let  $\mathcal{A}$  be the  $C$ -algorithm that decides the satisfiability problem for **cpnb**-formulas in logic PPL. We present an algorithm that decides whether  $A$  is satisfiable by traversing the tableau for  $A$  in a depth first fashion. Then, we prove the correctness of the algorithm and analyse its complexity.

**Algorithm.** The goal of the algorithm is to traverse the tableau for  $A$  and decide which world paths should be marked *realizable*. A realizable world path  $p_{w_{ij}}$  contains all the formulas that are satisfied in world  $w_{ij}$  of the model for  $A$  (if our algorithm decides that such a model exists). On the other hand, a world path that is not marked realizable implies that the formulas in this path cannot be satisfied in a PPL-model. We execute the following steps:

1. If all the world paths have been examined then stop. Otherwise, let  $p_{w_{ij}}$  be the next (in depth first fashion) world path. Go to step 2.
2. Mark  $p_{w_{ij}}$  examined. If  $\mathcal{A}$  fails in  $B_{p_{w_{ij}}}$ , do not mark it realizable and go to step 1, else if  $p_{w_{ij}}$  is  $P$ -closed, mark  $p_{w_{ij}}$  realizable and go to step 1, else go to step 3.
3. Recall that by entering this step, we have selected an open world path  $p_{w_{ij}}$ , such that  $\mathcal{A}$  succeeds in  $B_{p_{w_{ij}}}$ . Now we proceed as follows: elect at most  $|A|$  rational numbers (not necessarily different from each other) of size at most  $2 \cdot (|A| \cdot \|A\| + |A| \cdot \log_2(|A|) + 1)$  from the interval  $(0, 1]$  and assign each one of them to a child of  $p_{w_{ij}}$ . Assign the number 0 to the rest of  $p_{w_{ij}}$ 's children. Now for each  $w \top P_{\geq s}B$  that appears in  $p_{w_{ij}}$  we run the procedure **prob\_test\_pos**( $P_{\geq s}B, p_{w_{ij}}$ ). And for each  $w \text{F} P_{\geq s}B$  that appears in  $p_{w_{ij}}$  we run the procedure **prob\_test\_neg**( $P_{\geq s}B, p_{w_{ij}}$ ). These procedures are defined as follows:

**prob\_test\_pos**( $P_{\geq s}B, p_{w_{ij}}$ )

find all the children of  $p_{w_{ij}}$  that contain  $B$  prefixed with  $\top$  and add the rational numbers assigned to them. If the sum is less than  $s$  return failure. Otherwise return success.

**prob\_test\_neg**( $P_{\geq s}B, p_{w_{ij}}$ )

find all the children of  $p_{w_{ij}}$  that contain  $B$  prefixed with  $\top$  and add the rational numbers assigned to them. If the sum is greater or equal to  $s$  return failure. Otherwise return success.

If at least one of the above executions of the two procedures returns failure, then mark  $p_{w_{ij}}$  as not realizable and move to step **1**.

Let  $X$  be the set of all children of  $p_{w_{ij}}$  to which a positive rational number is assigned. Run step **2** of the algorithm to every member of  $X$ . If there exists one member of  $X$  where step **2** of the algorithm fails then mark  $p_{w_{ij}}$  unrealizable. Otherwise mark  $p_{w_{ij}}$  realizable. Go to step **1**.

If, at the end of the algorithm there exists a world path starting from the root, that is marked realizable, return “satisfiable”. Otherwise, return “not satisfiable”.

**Correctness.** In order to prove our algorithm correct it suffices to show that for every world path  $p_{w_{ij}}$ :

$$p_{w_{ij}} \text{ is marked realizable} \iff F_{p_{w_{ij}}} \text{ is PPL-satisfiable.} \quad (11)$$

Let  $p_{w_{ij}}$  be a world path. We prove the two directions of (11) separately:  
 $(\implies)$  We define the structure  $M = \langle U, W, H, \mu, v \rangle$  as follows:

$$U = \{u_{kl} \mid p_{u_{kl}} \text{ is marked realizable in the subtree of the tableau that has the first node of } p_{w_{ij}} \text{ as a root}\} .$$

And for every  $u_{kl} \in U$ , we have:

- $W_{u_{kl}} = U$  and  $H_{u_{kl}} = \mathcal{P}(W_{u_{kl}})$ .
- For every  $v_{mn}$ , such that  $p_{v_{mn}}$  is a child of  $p_{u_{kl}}$  we define  $\mu_{u_{kl}}(\{v_{mn}\})$  to be the rational number assigned to  $p_{v_{mn}}$  (which can be 0). For every  $v_{mn} \in U$  such that  $v_{mn}$  is not a child of  $p_{u_{kl}}$ , we set  $\mu_{u_{kl}}(\{v_{mn}\}) = 0$ .
- for every  $V \in H_u$ :  $\mu_{u_{kl}}(V) = \sum_{v_{mn} \in V} \mu_{u_{kl}}(\{v_{mn}\})$ .
- $v_{u_{kl}}$  is the evaluation that satisfies  $B_{p_{u_{kl}}}$ . We know that such an evaluation exists since  $p_{u_{kl}}$  can be marked satisfiable only if  $\mathcal{A}$  succeeds in  $B_{p_{u_{kl}}}$ .

Since for every  $u_{kl} \in U$  the rational numbers assigned to  $p_{u_{kl}}$ 's children were selected in a way such that their sum equals 1, it is straightforward to show

that  $M$  is a PPL-model. We will now show that for every  $B \in \text{subf}(A)$  and for every  $u_{kl} \in U$ :

$$(u_{kl} \top B \implies M, u_{kl} \models B) \text{ and } (u_{kl} \text{ F } B \implies M, u_{kl} \not\models B). \quad (12)$$

We proceed by induction on  $B$ . The only interesting case is when  $B \equiv P_{\geq s}C$ . Assume that  $u_{kl} \top P_{\geq s}C$ . Then we have

$$\sum_{\{p_{v_{mn}} \mid p_{v_{mn}} \text{ is a child of } p_{u_{kl}} \text{ and } v_{mn} \top C\}} r_{v_{mn}} \geq s,$$

where  $r_{v_{mn}}$  is the rational number that is assigned to  $p_{v_{mn}}$ . By i.h. and by the definition of  $M$  we have

$$\sum_{\{v_{mn} \mid v_{mn} \in W_{u_{kl}} \text{ and } M, v_{mn} \models C\}} \mu_{u_{kl}}(\{v_{mn}\}) \geq s,$$

which by the additivity of  $\mu_{u_{kl}}$  gives us

$$\mu_{u_{kl}}([C]_{M, u_{kl}}) \geq s,$$

i.e.

$$M, u_{kl} \models P_{\geq s}C.$$

Exactly the same arguments prove the right conjunct of (12) and this concludes the proof of the if direction of (11).

( $\Leftarrow$ ) We prove the claim by induction on the depth of  $p_{w_{ij}}$  in the tableau for  $A$ .

If  $p_{w_{ij}}$  ends in a leaf, then  $p_{w_{ij}}$  is a  $P$ -closed world path, which implies that  $F_{p_{w_{ij}}} \equiv B_{p_{w_{ij}}}$ . The fact that  $F_{p_{w_{ij}}}$  is PPL-satisfiable implies that there is an evaluation that satisfies  $B_{p_{w_{ij}}}$ . This implies that  $\mathcal{A}$  is successful on  $B_{p_{w_{ij}}}$ , so  $p_{w_{ij}}$  is marked realizable.

Assume that  $p_{w_{ij}}$  has children. Assume that  $F_{p_{w_{ij}}}$  is satisfiable in world  $w_{ij}$  of the PPL-model  $M$ . Since  $p_{w_{ij}}$  is  $P$ -open there is a  $K$  and some  $C_r$ 's and  $s_r$ 's such that  $M, w \models \bigwedge_{r=1}^K P_{\odot_r s_r} C_i$  for  $\odot_r \in \{\geq, <\}$ . Let

$$\text{cfnf}(C_1, \dots, C_K) = \{a_1, \dots, a_m\}.$$

By propositional reasoning we can show that  $M, w \models \bigwedge_{r=1}^K P_{\odot_r s_r} D_r$  where every  $D_r$  is equivalent to a disjunction of some  $a_k$ 's. Now we proceed as in the proof of Theorem 13. We show that the fact that the  $P_{\odot_r s_r} D_r$ 's are satisfied in  $w_{ij}$  implies that there is a linear system  $\mathcal{S}$  which has as a solution a vector, every entry of which corresponds to the measure of some  $a_k$ . By Theorem 8 we can show that at most  $|A|$  entries of a solution for  $\mathcal{S}$  have to be positive. And each of these entries has size at most  $2 \cdot (|A| \cdot ||A|| + |A| \cdot \log_2(|A|) + 1)$ . Recall that each  $a_k$  is assigned to a child of  $p_{w_{ij}}$ . So, there are at most  $|A|$  positive rational numbers that are assigned to children of  $p_{w_{ij}}$ . The algorithm that traverses the tableau for  $A$  should be able to find them. Then the algorithm should be able to

verify that these rational numbers sum to 1 and satisfy the nodes that contain  $P_{\odot_r} C_r$  in  $p_{w_{ij}}$ . Also the fact that  $F_{p_{w_{ij}}}$  is satisfiable implies that  $\mathcal{A}$  succeeds in  $B_{p_{w_{ij}}}$ . Furthermore the  $a_j$ 's that correspond to positive measures are satisfiable in  $M$ . This implies that for every  $p_{u_{jk}}$ , such that  $p_{u_{jk}}$  is a child of  $p_{w_{ij}}$  and a positive rational number is assigned to  $p_{u_{jk}}$ , then  $F_{p_{u_{jk}}}$  is satisfied in  $M$ . By the induction hypothesis we have that the children of  $p_{w_{ij}}$  that correspond to positive measures are marked realizable. We conclude that  $p_{w_{ij}}$  is marked realizable.

This concludes the proof of (11).

**Complexity Analysis.** We will show that our algorithm can decide whether there exists a world path starting from  $A$  that should be marked realizable by using only a polynomial number of bits and a C-oracle. We observe that whether  $p_{w_{ij}}$  should be marked realizable only depends on  $p_{w_{ij}}$  and the subtree below it. So, we can traverse the tableau tree in depth first fashion, reusing space. For every  $p_{w_{ij}}$  we need a polynomial number of bits to store  $p_{w_{ij}}$  itself, the positive rational numbers assigned to some of its children and the `cnf`-formulas that are assigned to these children. We can verify (using the C-oracle) that  $B_{p_{w_{ij}}}$  is satisfiable and that the probabilistic constraints in  $p_{w_{ij}}$  are satisfied. Then we can move to the first child of  $p_{w_{ij}}$  (among those of which a positive probability is assigned) and repeat the same procedure. Clearly, once we have that the first child of  $p_{w_{ij}}$  is marked realizable we do not need the space used for this child any more. So, this space can be used for the next child. We conclude that the maximum number of information that we have to store each time is at most equal to the depth of the tree (which is polynomial on  $|A|$ ) times the number of bits needed to process a single world path (which as we observed is polynomial on  $|A|$  again). We conclude that our algorithm runs in polynomial space using a C-oracle. ■

#### 4.2.2 The Lower Bound

Before showing the reduction from modal logic D we observe that the tableau decision procedure implies a small model property for PPL.

**Corollary 20.** *(Small Model Property for PPL) Let  $A \in \mathcal{L}_{\text{PPL}}$  be satisfiable. Then  $A$  is satisfiable in a PPL-model  $M = \langle U, W, H, \mu, v \rangle$ , where*

1.  $U \leq 2^{|A|}$ ;
2. for each  $w \in U$ ,
  - (a)  $W_w = U$  and  $H_w = \mathcal{P}(U_w)$ ;
  - (b) for every  $V \in H_w : \mu_w(V) = \sum_{v \in V} \mu(\{v\})$ .

*Proof.* The fact that  $A$  is satisfiable implies that the tableau procedure for  $A$  succeeds. So, if we start a tableau procedure with  $w \top A$  in the root we should find a realizable world path that starts from  $w \top A$ . Then as in the proof of

the proof of the "if" direction of (11) we can construct a PPL-model for  $A$  that satisfies the properties in the statement of this corollary. Since the tableau for  $A$  is finite, the size of the model satisfying  $A$  is finite. ■

Now we proceed with some standard definitions from modal logic. The language of modal logic,  $\mathcal{L}_\square$ , is described by the following grammar:

$$A ::= p \mid \neg A \mid A \wedge A \mid \square A ,$$

where  $p \in \text{Prop}$ . A Kripke model is structure  $M = \langle W, R, v \rangle$  where  $W$  is a non-empty set of worlds,  $R \subseteq W \times W$  and  $v$  is a function that assigns a truth assignment (for classical propositional logic) to every world in  $W$ . For each  $w \in W$  we define the following set:

$$R[w] = \{u \mid (w, u) \in R\} .$$

The semantics of  $\mathcal{L}_\square$ -formulas is given by the following definition:

**Definition 21** (Truth in a Kripke model). Let  $M = \langle W, H, v \rangle$  be a Kripke model and let  $A \in \mathcal{L}_\square$ . We define what it means for  $A$  to hold in the world  $w$  of  $M$  (written as  $M, w \models A$ ) by distinguishing the following cases:

$A \equiv \square B$ :

$$M, w \models \square B \iff (\forall u \in R[w])[M, u \models B]$$

$A \equiv p \in \text{Prop}$ :

$$M, w \models p \iff v_w(p) = \top .$$

The propositional connectives are treated classically.

A Kripke model  $M = \langle W, R, v \rangle$  is serial if for every  $w \in W$ ,  $R[w] \neq \emptyset$ .  $D$  is the modal logic that is sound and complete with respect to serial Kripke models [13].

Now we can show the lower bound.

**Theorem 22.**  $\text{PPL}_{\text{SAT}}$  is PSPACE-hard.

*Proof.* We will reduce  $\text{D}_{\text{SAT}}$  to  $\text{PPL}_{\text{SAT}}$ . Since  $\text{D}_{\text{SAT}}$  is PSPACE-complete [13] our theorem follows. Let  $A \in \mathcal{L}_\square$  and let  $f(A)$  be the PPL-formula obtained from  $A$  by replacing every occurrence of  $\square$  by  $P_{\geq 1}$ . We will show the following equivalence:

$$A \text{ is } D\text{-satisfiable if and only if } f(A) \text{ is PPL-satisfiable .} \quad (13)$$

( $\implies$ ) Assume that  $A$  is satisfiable. By the small model theorem for modal logic  $D$  [13] it is satisfiable in a serial Kripke model  $M_D = \langle U, R, v \rangle$ , where  $U$  is finite. We define  $M_{\text{PPL}} = \langle U, W, H, \mu, v' \rangle$  where for every  $w \in U$ ,

$$\begin{aligned} W_w &= R[w], \\ H_w &= \mathcal{P}(W_w), \\ v'_w &\text{ is an extension of } v_w \text{ to } \mathcal{B}(\mathcal{L}_{\text{PPL}})\text{-formulas,} \end{aligned}$$

and for every  $V \in H_w$ ,

$$\mu_w(V) = \frac{|V|}{|R[w]|} .$$

It is easy to show that  $M_{\text{PPL}}$  is a PPL-model. We will now show that

$$(\forall w \in U)(\forall B \in \text{subf}(A))[M_D, w \models B \iff M_{\text{PPL}}, w \models f(B)]$$

by induction on the complexity of  $B$ . The only interesting case is when  $B$  is of the form  $\Box C$ . Then we have

$$\begin{aligned} M_D, w \models \Box C & \iff \\ (\forall u \in R[w])[M_D, u \models C] & \stackrel{\text{i.h.}}{\iff} \\ (\forall u \in W_w)[M_{\text{PPL}}, u \models f(C)]. & \end{aligned} \quad (14)$$

Now we have that  $W_w = [f(C)]_{M_{\text{PPL}}, w}$  which immediately implies that

$$\mu_w([f(C)]_{M_{\text{PPL}}, w}) = 1 .$$

On the other hand assume that  $\mu_w([f(C)]_{M_{\text{PPL}}, w}) = 1$ . Then if  $[f(C)]_{M_{\text{PPL}}, w} \subsetneq W_w$  then, by the definition of  $\mu_w$  we get that  $\mu_w(W_w \setminus [f(C)]_{M_{\text{PPL}}, w}) > 0$ , which, by the additivity of  $\mu_w$  contradicts the fact that  $\mu_w([f(C)]_{M_{\text{PPL}}, w}) = 1$ . We conclude that (14) is equivalent to the following:

$$\begin{aligned} \mu_w([f(C)]_{M_{\text{PPL}}, w}) = 1 & \iff \\ M_{\text{PPL}}, w \models_{P \geq 1} f(C) & \iff \\ M_{\text{PPL}}, w \models f(B). & \end{aligned}$$

( $\Leftarrow$ ) Assume that  $f(A)$  is satisfiable. Then  $f(A)$  is satisfiable in a model  $M_{\text{PPL}} = \langle U, W, H, \mu, v \rangle$  that satisfies the properties of Corollary 20. Let  $M_D = \langle U, R, v' \rangle$ , where, for every  $w \in W$ ,

$$R[w] = \{u \in W_w \mid \mu_w(\{u\}) > 0\}$$

and  $v'_w$  is the restriction of  $v_w$  to **Prop**. It is straightforward to show that  $M_D$  is a serial Kripke structure. We will now show that

$$(\forall w \in W)(\forall B \in \text{subf}(A))[M_{\text{PPL}}, w \models f(B) \iff M_D, w \models B]$$

by induction on the complexity of  $B$ . The only interesting case is when  $B \equiv \Box C$ . We have that

$$\begin{aligned} M_D, w \models \Box C & \iff \\ (\forall u \in R[w])[M_D, u \models C] & \stackrel{\text{i.h.}}{\iff} \\ (\forall u \in W_w)[\mu_w(\{u\}) > 0 \implies M_{\text{PPL}}, u \models f(C)] . & \end{aligned} \quad (15)$$

So  $[f(C)]_{M_{\text{PPL},w}} \supseteq \{u \in W_w \mid \mu_w(\{u\}) > 0\}$ . Hence

$$\begin{aligned} \mu_w([f(C)]_{M_{\text{PPL},w}}) &= \sum_{u \in [f(C)]_{M_{\text{PPL},w}}} \mu(\{u\}) \\ &= \sum_{u \in W_w \mid \mu_w(\{u\}) > 0} \mu(\{u\}) = \sum_{u \in W_w} \mu(\{u\}) = 1. \end{aligned}$$

On the other hand assume that  $\mu_w([f(C)]_{M_{\text{PPL},w}}) = 1$ . Let  $u \in W_w$  such that  $\mu_w(\{u\}) > 0$ . Assume that  $M_{\text{PPL},u} \not\models f(C)$ . Then  $u \in W_w \setminus [f(C)]_{M_{\text{PPL},w}}$ . So  $\mu_w(W_w \setminus [f(C)]_{M_{\text{PPL},w}}) > 0$ , which contradicts the fact that  $\mu_w([f(C)]_{M_{\text{PPL},w}}) = 1$ . So for all  $u \in W_w$ ,  $\mu_w(\{u\}) > 0$  implies that  $M_{\text{PPL},u} \models f(C)$ . We conclude that (15) is equivalent to

$$\begin{aligned} \mu_w([f(C)]_{M_{\text{PPL},w}}) = 1 & \iff \\ M_{\text{PPL},w} \models_{P \geq 1} f(C) & \iff \\ M_{\text{PPL},w} \models f(B). & \end{aligned}$$

We conclude that (13) holds, which proves our theorem.  $\blacksquare$

## 5 Applications

In this section we apply the results of Sections 3 and 4 in probabilistic logics over classical propositional logic and justification logic.

### 5.1 Probabilistic Logics over Classical Propositional Logic

Let CP denote classical propositional logic. If we define as basic formulas the atomic propositions (i.e. elements of the set  $\text{Prop}$ ) and if we define as evaluations traditional truth assignments for classical propositional logic (on the set  $\text{Prop}$ ), then we can define the non-iterated and the iterated probabilistic logic over classical propositional logic, which according to our notation are PCP and PPCP respectively. These logics have already been defined in [28] as  $\text{LPP}_2$  and  $\text{LPP}_1$  respectively. So, we have have the following corollary:

**Corollary 23.** 1.  $\text{LPP}_{2,\text{SAT}}$  is NP-complete.

2.  $\text{LPP}_{1,\text{SAT}}$  is PSPACE-complete.

*Proof.* The satisfiability problem for  $\text{cpnb}$ -formulas in classical propositional logic can be decided in polynomial time (we simply have to check whether the  $\text{cpnb}$  formula contains an atomic proposition and its negation). So if we set  $\text{C} = \text{P}$  in Theorems 16 and 19 we conclude that  $\text{LPP}_{2,\text{SAT}} \in \text{NP}$  and that  $\text{LPP}_{1,\text{SAT}} \in \text{PSPACE}$ . The lower bounds follow from the fact that  $\text{LPP}_2$  is an extension of classical propositional logic and from Theorem 22.  $\blacksquare$

As it was observed in [28] the result of Corollary 23(1) can be obtained a straightforward application of the methods of [10]. Also in [11], a proof sketch (without many details) for Corollary 23(2) was given. In this paper we gave formal proofs for both results.

## 5.2 Probabilistic Logics over Justification Logic

Before defining the non-iterated and the iterated probabilistic justification logic, we briefly recall justification logic J and its satisfiability algorithm.

### 5.2.1 The basic Justification Logic J

The language of justification logic [2] is defined by extending the language of classical propositional logic with formulas of the form  $t : \alpha$  where  $t$  is a justification term, which is used to represent evidence, and  $\alpha$  is a justification formula, which is used to represent propositions, statements or facts. As we will see later, formula  $\alpha$  might contain terms as well. The formula  $t : \alpha$  reads as "*t is a justification for believing  $\alpha$* " or as "*t justifies  $\alpha$* ". For example, assume that we have an agent who sees a snake behind him/her. Whereas in traditional modal logic we can express a statement like "the agent believes/knows that he/she is in danger", in justification logic we can express a statement like "the agent is in danger because there is a snake behind him/her". In the last statement an observation of the snake can serve as a justification. So, in justification logic the representation of knowledge becomes explicit.

*Justification terms* are built from countably many constants and countably many variables according to the following grammar:

$$t ::= c \mid x \mid (t \cdot t) \mid (t + t) \mid !t ,$$

where  $c$  is a constant and  $x$  is a variable.  $\mathsf{Tm}$  denotes the set of all terms and  $\mathsf{Con}$  denotes the set of all constants. For  $c \in \mathsf{Con}$  and  $n \in \mathbb{N}$  we define

$$!^0 c := c \quad \text{and} \quad !^{n+1} c := !(^n c) .$$

The operators  $\cdot$  and  $+$  are assumed to be left-associative. The intended meaning of the connectives used in the set  $\mathsf{Tm}$  will be clear when we present the deductive system for J.

Formulas of the language  $\mathcal{L}_J$  (justification formulas) are built according to the following grammar:

$$\alpha ::= p \mid t : \alpha \mid \neg \alpha \mid \alpha \wedge \alpha ,$$

where  $t \in \mathsf{Tm}$  and  $p \in \mathsf{Prop}$ . Following our previous notation we have

$$\mathcal{B}(\mathcal{L}_J) = \mathsf{Prop} \cup \{t : \alpha \mid \alpha \in \mathcal{L}_J\} .$$

The deductive system for J is the Hilbert system presented in Table 2. Axiom (J) is also called the *application axiom* and is the justification logic analogue of application axiom in modal logic. It states that we can combine a justification for  $\alpha \rightarrow \beta$  and a justification for  $\alpha$  in order to obtain a justification for  $\beta$ . Axiom (+), which is also called the *monotonicity axiom*, states that if  $s$  or  $t$  is a justification for  $\alpha$  then the term  $s + t$  is also a justification for  $\alpha$ . This operator can model monotone reasoning like proofs in some formal system of

Axioms:	
(P)	finite set of axiom schemata axiomatizing classical propositional logic in the language $\mathcal{L}_J$
(J)	$\vdash s : (\alpha \rightarrow \beta) \rightarrow (t : \alpha \rightarrow s \cdot t : \beta)$
(+)	$\vdash (s : \alpha \vee t : \alpha) \rightarrow s + t : \alpha$
Rules:	
(MP)	if $T \vdash \alpha$ and $T \vdash \alpha \rightarrow \beta$ then $T \vdash \beta$
(AN!)	$\vdash !^n c : !^{n-1} c : \dots : !c : c : \alpha$ , where $c$ is a constant, $\alpha$ is an instance of (P), (J) or (+) and $n \in \mathbb{N}$

Table 2: The Deductive System J

mathematics: if I already have a proof  $t$  for a formula  $\alpha$ , then  $t$  remains a proof for  $\alpha$  if I add a few more lines in  $t$ . Rule (AN!) states that any constant can be used to justify any axiom and also that we can use the operator  $!$  to express positive introspection: if  $c$  justifies axiom instance  $\alpha$ , then  $!c$  justifies  $c : \alpha$ ,  $!!c$  justifies  $!c : c : \alpha$  and so on. The previous situation is the explicit analogue of the positive iteration of modalities in traditional modal logic: I know  $\alpha$ , I know that I know  $\alpha$  and so on. The operator  $!$  is also called proof checker or proof verifier. This is because we can think that  $\alpha$  is a problem given to a student,  $c$  is the solution (or the proof) given by the student and  $!c$  is the verification of correctness for the proof given by the tutor. So justification logic can model the following situation:

**student:** I have a proof for  $\alpha$  (i.e.  $c : \alpha$ ).

**tutor:** I can verify your proof for  $\alpha$  (i.e.  $!c : c : \alpha$ )

In justification logic it is common to assume that only some constants justify some axioms (see the notion of *constant specification* in [2]). However, for the purposes of this paper it suffices to assume that every constant justifies every axiom (this assumption corresponds to the notion of a *total constant specification* [2]).

In order to illustrate the usage of axioms and rules in J we present the following example:

*Example 24.* Let  $a, b \in \text{Con}$ ,  $\alpha, \beta \in \mathcal{L}_J$  and  $x, y$  be variables. Then we have the following:

$$\vdash_J (x : \alpha \vee y : \beta) \rightarrow a \cdot x + b \cdot y : (\alpha \vee \beta).$$

*Proof.* Since  $\alpha \rightarrow \alpha \vee \beta$  and  $\beta \rightarrow \alpha \vee \beta$  are instances of (P), we can use (AN!) to obtain

$$\vdash_J a : (\alpha \rightarrow \alpha \vee \beta)$$

and

$$\vdash_J b : (\beta \rightarrow \alpha \vee \beta).$$

Using (J) and (MP) we obtain

$$\vdash_J x : \alpha \rightarrow a \cdot x : (\alpha \vee \beta)$$

and

$$\vdash_J y : \beta \rightarrow b \cdot y : (\alpha \vee \beta).$$

Using (+) and propositional reasoning we obtain

$$\vdash_J x : \alpha \rightarrow a \cdot x + b \cdot y : (\alpha \vee \beta)$$

and

$$\vdash_J y : \beta \rightarrow a \cdot x + b \cdot y : (\alpha \vee \beta).$$

We can now obtain the desired result by applying propositional reasoning.  $\blacksquare$

Logic J also enjoys the *internalization property*, which is presented in the following theorem. Internalization states that the logic internalizes its own notion of proof. The version without premises is an explicit form of the necessitation rule of modal logic. A proof of the following theorem can be found in [22].

**Theorem 25** (Internalization). *For any  $\alpha, \beta_1, \dots, \beta_n \in \mathcal{L}_J$  and  $t_1, \dots, t_n \in \mathsf{Tm}$ , if*

$$\beta_1, \dots, \beta_n \vdash_J \alpha$$

*then there exists a term  $t$  such that*

$$t_1 : \beta_1, \dots, t_n : \beta_n \vdash_J t : \alpha.$$

The models for J which we are going to use in this paper are called M-models and were introduced by Mkrtychev [25] for the logic LP. Later Kuznets [20] adapted these models for other justification logics (including J) and proved the corresponding soundness and completeness theorems. Formally, we have the following:

**Definition 26** (M-Model). An M-model is a pair  $\langle v, \mathcal{E} \rangle$ , where  $v : \mathsf{Prop} \rightarrow \{\mathsf{T}, \mathsf{F}\}$  and  $\mathcal{E} : \mathsf{Tm} \rightarrow \mathcal{P}(\mathcal{L}_J)$  such that for every  $s, t \in \mathsf{Tm}$ , for  $c \in \mathsf{Con}$  and  $\alpha, \beta \in \mathcal{L}_J$ , for  $\gamma$  being an axiom instance of J and  $n \in \mathbb{N}$  we have

1.  $(\alpha \rightarrow \beta \in \mathcal{E}(s) \text{ and } \alpha \in \mathcal{E}(t)) \implies \beta \in \mathcal{E}(s \cdot t)$  ;
2.  $\mathcal{E}(s) \cup \mathcal{E}(t) \subseteq \mathcal{E}(s + t)$  ;
3.  $!^{n-1}c : !^{n-2}c : \dots : !c : c : \gamma \in \mathcal{E}(!^n c)$ .

**Definition 27** (Truth in an M-model). We define what it means for an  $\mathcal{L}_J$ -formula to hold in the M-model  $M = \langle v, \mathcal{E} \rangle$  inductively as follows (the connectives  $\neg$  and  $\wedge$  are treated classically):


$$\begin{aligned} M \models p &\iff v(p) = \mathsf{T} && \text{for } p \in \mathsf{Prop} ; \\ M \models t : \alpha &\iff \alpha \in \mathcal{E}(t) . \end{aligned}$$

We close this section by briefly recalling the known complexity bounds for  $J_{SAT}$ . The next theorem is due to Kuznets [20, 21]. We present it here briefly using our own notation.

**Theorem 28.** *The satisfiability problem for cnpb-formulas in logic J belongs to coNP.*

*Proof.* Let  $a$  be the cnpb-formula of logic J that is tested for satisfiability. Assume that there is no  $p \in Prop$  such that  $p$  appears both positively and negatively in  $a$  (otherwise it is clear that  $a$  is not satisfiable). So, the satisfiability of  $a$  depends only on the justification assertions that appear in  $a$ .

Let  $p_i : \alpha_i$  be the assertions that appear positively in  $a$  and let  $n_i : \beta_i$  be the assertions that appear negatively in  $a$ . A short no-certificate is an object that has size polynomial in the size of the input (i.e. of  $|a|$ ) and that can witness that the input is a no-instance of the problem in polynomial time. So, if we can show that the question “does a model, which satisfies all the  $p_i : \alpha_i$ ’s and falsifies all the  $n_i : \beta_i$ ’s, exist?” has a short no-certificate we have proved claim of the theorem. For this purpose it suffices to guess some  $n_j : \beta_j$  (i.e. some justification assertion that appears negatively in  $a$ ) and show that every M-model that satisfies all the  $p_i : \alpha_i$ ’s, satisfies  $n_j : \beta_j$  too. Our guess will not only consist of the formula itself, but also of the way this formula is constructed from the  $p_i : \alpha_i$ ’s and from the constants that justify the axioms of J. In order to verify that our guess of the formula and its construction is correct we have to be able to access all the formulas that are justified by a given term in finite time. At first, it seems impossible to do this in finite time, since we have that some terms justify infinitely many formulas (in particular every constant justifies all the axiom instances, which are infinitely many). However, since J is axiomatized by finitely many axiom schemes we can use schematic variables for formulas and terms. This way we have that every constant justifies only finitely many axiom schemes. So, the short no-certificate can be guessed as follows: we non-deterministically choose some  $n_j : \beta_j$ . The term  $n_j$  is created by the connectives  $\cdot$  and  $+$  using a finite tree like the following one:



The above tree can be constructed in many ways but we guess one such that in the leaves there are terms of the form  $!^n c : \dots !c : c$  or some  $p_i$ ’s. Such a guess should be possible if the no-certificate exists. The fact that the tree is constructed in that way means,  $n_j : \beta_j$  is constructed by the axioms  $(+)$ ,  $(J)$ , the rule  $(AN!)$ , using the assumptions that every  $p_i$  satisfies every  $\alpha_i$ . We

assign to each of the tree's leaves an axiom scheme (if the leaf is of the form  $!^n c : \dots !: c : c$ ) or an  $\alpha_i$  (if the leaf is of the form  $p_i$ ). Then starting from the leaves (i.e. bottom-up) we unify the schematic formulas assigned to every tree node. If at some point the unification is impossible, then our guess is not correct. The bottom-up unification procedure ends when we construct a formula in the root. This formula has to be unifiable with  $\beta_j$ , otherwise the guess is again not correct. The formulas that we assigned to the leaves and the structure of the tree compose the short no-certificate. It can be shown that representing formulas as directed acyclic graphs and using Robinson's unification algorithm [8] we can verify that the unifications succeed in polynomial time. Hence the satisfiability for  $\text{cpnb}$ -formulas in logic  $\text{J}$  belongs to  $\text{coNP}$ . ■

Finally, we can present the known complexity bounds for  $\text{J}_{\text{SAT}}$ .

**Theorem 29.**  $\text{J}_{\text{SAT}}$  is  $\Sigma_2^{\text{P}}$ -complete.

*Proof.* Let  $\alpha \in \mathcal{L}_{\text{J}}$  be the formula that is tested for satisfiability. The upper bound follows by Kuznets's algorithm [20] which can be described by the following steps, using our notation:

1. Create a node with  $w \top \alpha$ . Apply the propositional rules for as long as possible. Non-deterministically choose a world path  $p_{w_{ij}}$ . This can be done in non-deterministic polynomial time.
2. Verify that  $B_{p_{w_{ij}}}$  is satisfiable using the  $\text{coNP}$ -algorithm of Theorem 28.

Observe that there is no rule that produces new worlds in the above algorithm. We have presented the algorithm using world signs in order to be consistent with our tableau notation. The lower bound follows by a result of Achilleos [1]. ■

### 5.2.2 Probabilistic Justification Logic

Let  $M$  be an  $\text{M}$ -model. Based on  $M$  we can define the evaluation  $v_M$  as follows:

$$\text{for every } \beta \in \mathcal{B}(\mathcal{L}_{\text{J}}), v_M(\beta) = \top \text{ if and only if } M \models \beta.$$

So, if we set  $\text{L} = \text{J}$ ,  $\mathcal{L} = \mathcal{L}_{\text{J}}$  and we define the evaluations as above, we can define the non-iterated probabilistic logic over  $\text{J}$ , which is the logic  $\text{PJ}$ . For the complexity of the satisfiability problem in  $\text{PJ}$ , we have the following corollary:

**Corollary 30.**  $\text{PJ}_{\text{SAT}}$  is  $\Sigma_2^{\text{P}}$ -complete.

*Proof.* The upper bound follows from Theorems 28 and 16. Since  $\text{PJ}$  is an extension of  $\text{J}$  and  $\text{J}_{\text{SAT}}$  is  $\Sigma_2^{\text{P}}$ -hard (Theorem 29) we get the lower bound. ■

Now we will present the iterated probabilistic justification logic  $\text{PPJ}$ . According to our previous definitions, in order to define the language of  $\text{PPJ}$ , which is called  $\mathcal{L}_{\text{PPJ}}$ , it suffices to define the basic formulas of  $\text{PPJ}$ . So, we

define  $\mathcal{B}(\mathcal{L}_{\text{PPJ}}) = \text{Prop} \cup \{t : A \mid A \in \mathcal{L}_{\text{PPJ}}\}$ . For the convenience of the reader we give the complete definition of  $\mathcal{L}_{\text{PPJ}}$ , i.e.

$$A ::= p \mid t : A \mid \neg A \mid A \wedge A \mid P_{\geq s}A,$$

where  $p \in \text{Prop}$  and  $s \in \mathbb{Q} \cap [0, 1]$ . We observe that the basic formulas of PPJ may contain random formulas of PPJ. So, the reader might think that the basic formulas do not have much simpler structure than the normal formulas of PPJ. However, the complex formulas of PPJ can appear only in the scope of justification terms. In PPJ, since there is no axiom that can draw a formula from the scope of a justification term (e.g.  $t : A \rightarrow A$ ), formulas that appear under the scope of a justification operator practically behave as atomic propositions. So, decidability and complexity of basic PPJ-formulas is much simpler to prove than decidability and complexity of random PPJ-formulas.

In order to define the PPJ-models we have to define evaluations for basic PPJ-formulas. Since basic PPJ-formulas resemble basic J-formulas, it makes sense to extend the definition of M-models in order to define evaluations for PPJ. So, as in the case of logic J we have to present the deductive system of PPJ first. This system is presented in Table 3. The axiomatization of PPJ is a combination of the axiomatization for  $\text{LPP}_1$  [28] and of the axiomatization for the basic justification logic J. Axiom (NN) corresponds to the fact that the probability of truthfulness of every formula is at least 0 (the acronym (NN) stands for non-negative). Observe that by substituting  $\neg A$  for  $A$  in (NN), we have  $P_{\geq 0} \neg A$ , which by our syntactical abbreviations is  $P_{\leq 1} A$ . Hence axiom (NN) also corresponds to the fact that the probability of truthfulness for every formula is at most 1. Axioms (L1) and (L2) describe some properties of inequalities (the L in (L1) and (L2) stands for less). Axioms (Add1) and (Add2) correspond to the additivity of probabilities for disjoint events (the Add in (Add1) and (Add2) stands for additivity). Rule (PN) is the probabilistic analogue of the necessitation rule in modal logics (hence the acronym (PN) stands for probabilist necessitation): if a formula is valid, then it has probability 1. Rule (ST) intuitively states that if the probability of a formula is arbitrary close to  $s$ , then it is at least  $s$ . Observe that the rule (ST) is infinitary in the sense that it has an infinite number of premises. It corresponds to the Archimedean property for the real numbers. The acronym (ST) stands for strengthening, since the statement of the result is stronger than the statement of the premises. Rule (ST) was introduced in [27, 32] so that strong completeness for probabilistic logics could be proved. We recall that a logical system is strongly complete if and only if every consistent set (finite or infinite) has a model. As it is shown in [27, 32], languages used for probabilistic logics are non-compact, so the proof of strong completeness is impossible without an infinitary rule.

So, now we can extend Definition 26 to the basic formulas of  $\mathcal{L}_{\text{PPJ}}$ . Recall that basic PPJ-formulas may contain iterated probabilistic operators under the scope of justification terms. This is the reason why we cannot use the standard M-models for basic PPJ-formulas. However since, as we mentioned before, PPJ-formulas under the scope of justification operators practically behave as atomic

Axioms:	
(P)	finitely many axiom schemata axiomatizing classical propositional logic in the language $\mathcal{L}_{\text{PPJ}}$
(NN)	$\vdash P_{\geq 0}A$
(L1)	$\vdash P_{\leq r}A \rightarrow P_{\leq s}A$ , where $s > r$
(L2)	$\vdash P_{< s}A \rightarrow P_{\leq s}A$
(Add1)	$\vdash P_{\geq r}A \wedge P_{\geq s}B \wedge P_{\geq 1}\neg(A \wedge B) \rightarrow P_{\geq \min(1, r+s)}(A \vee B)$
(Add2)	$\vdash P_{\leq r}A \wedge P_{\leq s}B \rightarrow P_{\leq r+s}(A \vee B)$ , where $r + s \leq 1$
(J)	$\vdash s : (A \rightarrow B) \rightarrow (t : A \rightarrow s \cdot t : B)$
(+)	$\vdash (s : A \vee t : A) \rightarrow s + t : A$
Rules:	
(MP)	if $T \vdash A$ and $T \vdash A \rightarrow B$ then $T \vdash B$
(PN)	if $\vdash A$ then $\vdash P_{\geq 1}A$
(ST)	if $T \vdash A \rightarrow P_{\geq s - \frac{1}{k}}B$ for every integer $k \geq \frac{1}{s}$ and $s > 0$ then $T \vdash A \rightarrow P_{\geq s}B$
(AN!)	$\vdash !^n c : !^{n-1}c : \dots : !c : c : A$ , where $c \in \text{Con}$ , $A$ is an instance of some PPJ-axiom and $n \in \mathbb{N}$

Table 3: The Deductive System PPJ

propositions the only difference between extended M-models and normal ones is that in the former we have the logic PPJ in the place where the later have the logic J.

**Definition 31** (Extended M-Model). An extended M-model is a pair  $\langle v, \mathcal{E} \rangle$ , where  $v : \text{Prop} \rightarrow \{\mathbf{T}, \mathbf{F}\}$  and  $\mathcal{E} : \text{Tm} \rightarrow \mathcal{P}(\mathcal{L}_{\text{PPJ}})$  such that for every  $s, t \in \text{Tm}$ , for  $c \in \text{Con}$  and  $A, B \in \mathcal{L}_{\text{PPJ}}$ , for  $C$  being an axiom instance of PPJ and  $n \in \mathbb{N}$  we have

1.  $(A \rightarrow B \in \mathcal{E}(s) \text{ and } A \in \mathcal{E}(t)) \implies B \in \mathcal{E}(s \cdot t)$  ;
2.  $\mathcal{E}(s) \cup \mathcal{E}(t) \subseteq \mathcal{E}(s + t)$  ;
3.  $!^{n-1}c : !^{n-2}c : \dots : !c : c : C \in \mathcal{E}(!^n c)$ .

We can define evaluations based on extended M-models in the same way as for the standard M-models. So a PPJ-model is a PPL-model where the evaluations are based on extended M-models. This completes the definition of semantics for PPJ.

Now we are ready to present the complexity bounds for  $\text{PPJ}_{\text{SAT}}$ .

**Theorem 32.** *The satisfiability problem for c<sub>pnb</sub>-formulas in logic PPJ belongs to coNP.*

*Proof.* We recall that c<sub>pnb</sub>-formulas in  $\mathcal{L}_{\text{PPJ}}$  are conjunctions of positive and negative atomic propositions and positive and negative formulas of the form  $t : A$ , where  $A \in \mathcal{L}_{\text{PPJ}}$ .

Since the c<sub>pnb</sub>-formulas in  $\mathcal{L}_{\text{PPJ}}$  resemble the c<sub>pnb</sub>-formulas in  $\mathcal{L}_{\text{J}}$  we will use a slight variation of the algorithm in Theorem 28 for deciding the satisfiability of c<sub>pnb</sub>-formulas. It is not difficult to observe that the algorithm of Theorem 28 does not depend on what the axioms of the logic are, as long as they are finitely many. Assume that  $a$  is the c<sub>pnb</sub>-formula of logic PPJ that we want to test for satisfiability. As in the proof of Theorem 28 we can choose a formula  $t : B$  that appears negatively in  $a$ , guess a tree that describes the construction of  $t$ , assign to the leaves of the tree PPJ-axioms and formulas and then verify that our guess is correct using unification. However, since the axioms of PPJ have different form than the axioms of J we have to modify the unification algorithm. Simple unification is not sufficient any more, since the axioms of PPJ come with linear conditions. In the rest of the proof we explain that the verification can be done in polynomial time by using a unification algorithm and by testing a linear system for satisfiability.

Whereas for  $\mathcal{L}_{\text{J}}$  we need two kinds of schematic variables (for terms and formulas), for  $\mathcal{L}_{\text{PPJ}}$  we need three kinds of schematic variables: for terms, formulas and rational numbers. Also, because of the side conditions that come with the axioms (L1) and (Add2) our schematic formulas should be paired with systems of linear inequalities. For example, the scheme (L1) should be represented by the schematic formula  $P_{\leq r}A \rightarrow P_{< s}A$  (with the schematic variables  $r$ ,  $s$ , and  $A$ )

together with the inequality  $r < s$ , whereas a scheme that is obtained by a conjunction of the schemata (L1) and (Add2) should be represented as

$$(P_{\leq r_1} A_1 \rightarrow P_{< s_1} A_1) \wedge (P_{\leq r_2} A_2 \wedge P_{< s_2} B_2 \rightarrow P_{< r_2 + s_2} (A_2 \vee B_2))$$

together with the inequalities

$$\{r_1 < s_1, r_2 + s_2 \leq 1\}.$$

We should not forget that the rational variables belong to  $\mathbb{Q} \cap [0, 1]$ . So we have to add constraints like  $0 \leq r \leq 1$ . Hence in addition to constructing unification equations we need to take care of the linear constraints. For instance, in order to unify the schemata  $P_{\geq r} A$  and  $P_{\geq s} B$  the algorithm has to unify  $A$  and  $B$ , and to equate  $r$  and  $s$ , i.e. it adds  $r = s$  to the linear system. At the end the verification algorithm will succeed only if the standard unification of formulas succeeds and the linear system is solvable.

Another complication are constraints of the form

$$l = \min(1, r + s) \tag{16}$$

that originate from the scheme (Add1). Obviously, Eq. (16) is not linear. However, we find that Eq. (16) has a solution if and only if one of the set of equations

$$\{l = r + s, r + s \leq 1\} \text{ or } \{l = 1, r + s > 1\}$$

has a solution. Thus whenever we come to an equation like (16) we can non-deterministically chose one of the equivalent set of equations and add it to the constructed linear system.

We conclude that we can guess a tree for  $t$  and also a linear system in non-deterministic polynomial time. We also find that the verification can be done in polynomial time, since testing a linear system for satisfiability can be done in polynomial time [14] and unification of formulas can be checked in polynomial time using Robinson's algorithm. So, as in the case of J we can show that the satisfiability problem for **cpnb**-formulas in PPJ has short no-certificates, i.e it belongs to **coNP**. ■

*Remark 33.* It might seem strange to the reader that the **cpnb**-formulas of J and PPJ have the same upper complexity bound. At first sight the PPJ **cpnb**-formulas seem more complex, since they may contain probabilistic operators (and iterations of them). However in the PPJ **cpnb**-formulas, the probabilistic operators, may occur only under the scope of justification terms. This means that the probabilistic operators cannot impose any conditions for satisfiability. For example in  $t : P_{\geq s} A$ , the formula  $P_{\geq s} A$  does not have to be satisfiable. So, probabilistic operators under the scope of justification operators, behave as atomic propositions. In particular they are more sophisticated than simple atomic propositions because they consist of rational numbers and formulas. It is not difficult to see, that the only impact that this has on the standard decidability procedure for the logic J is on the unification algorithm. That is why the biggest part of the proof for Theorem 32 is devoted on showing how the modified unification algorithm works and that it runs in polynomial time.

**Corollary 34.**  $\text{PPJ}_{\text{SAT}}$  is PSPACE-complete.

*Proof.* The upper bound follows from Theorems 32 and 19. The lower bound follows from Theorem 22. ■

## 6 Conclusion

We have presented upper and lower complexity bounds for the satisfiability problem in non-iterated and iterated probabilistic logics over any extension of classical propositional logic. The aforementioned bounds are parameterized on the complexity of satisfiability of conjunctions of positive and negative formulas that have neither a probabilistic nor a classical operator as their top-connectives. As an application we have shown how tight bounds for the complexity of satisfiability in non-iterated and iterated probabilistic logics over classical propositional logic and justification logic can be obtained. It is interesting that both for classical propositional logic and for the basic justification logic J adding non-nested probabilistic operators to the language does not increase the complexity of the satisfiability problem.

Now we present some directions for further research. The probabilistic logic of [9] allows iterations of some probabilistic operators, that are more complicated than the ones used in this paper. It would be interesting to check whether the tableau procedure of our paper is applicable in this logic. Another interesting question is the following: Rašković et al. [33] define a probabilistic logic over classical propositional logic, called  $\text{LPP}^{\text{S}}$ , using approximate conditional probabilities with the intention to model non-monotonic reasoning. The satisfiability problem for  $\text{LPP}^{\text{S}}$  is again reduced to solving linear systems. In [30] the logic of [33] is extended to a probabilistic logic with approximate conditional probabilities over justification logic. What are the complexity bounds for the satisfiability problem in the logics of [33] and [30]?

## References

- [1] A. Achilleos. Nexp-completeness and universal hardness results for justification logic. In L. D. Beklemishev and D. V. Musatov, editors, *Computer Science - Theory and Applications - 10th International Computer Science Symposium in Russia, CSR 2015, Listvyanka, Russia, July 13-17, 2015, Proceedings*, volume 9139 of *Lecture Notes in Computer Science*, pages 27–52. Springer, 2015.
- [2] S. Artemov and M. Fitting. Justification logic. In E. N. Zalta, editor, *The Stanford Encyclopedia of Philosophy*. Metaphysics Research Lab, Stanford University, winter 2016 edition, 2016.
- [3] S. N. Artemov. Operational modal logic. Technical Report MSI 95–29, Cornell University, Dec. 1995.

- [4] S. N. Artemov. Explicit provability and constructive semantics. *Bulletin of Symbolic Logic*, 7(1):1–36, 2001.
- [5] P. Blackburn, M. de Rijke, and Y. Venema. *Modal Logic*. Cambridge University Press, New York, NY, USA, 2001.
- [6] V. N. Brezhnev. On explicit counterparts of modal logics. Technical Report CFIS 2000–05, Cornell University, 2000.
- [7] V. Chvátal. *Linear programming*. W. H. Freeman and Company, New York, 1983.
- [8] J. Corbin and M. Bidoit. A Rehabilitation of Robinson’s Unification Algorithm. *Comptes Rendus de l’ Académie des Sciences. Serie I-Mathématique*, 296(5):279–282, 1983.
- [9] D. Doder, N. Savić, and Z. Ognjanović. A decidable multi-agent logic with iterations of upper and lower probability operators. In F. Ferrarotti and S. Woltran, editors, *Foundations of Information and Knowledge Systems - 10th International Symposium, FoIKS 2018, Budapest, Hungary, May 14-18, 2018, Proceedings*, volume 10833 of *Lecture Notes in Computer Science*, pages 170–185. Springer, 2018.
- [10] R. Fagin, J. Halpern, and N. Megiddo. A logic for reasoning about probabilities. *Information and Computation*, 87:78–128, 1990.
- [11] R. Fagin and J. Y. Halpern. Reasoning about knowledge and probability. *Journal of the ACM (JACM)*, 41(2):340–367, 1994.
- [12] G. Georgakopoulos, D. Kavvadias, and C. H. Papadimitriou. Probabilistic satisfiability. *Journal of complexity*, 4(1):1–11, 1988.
- [13] J. Y. Halpern and Y. Moses. A guide to completeness and complexity for modal logics of knowledge and belief. *Artif. Intell.*, 54(2):319–379, 1992.
- [14] N. Karmarkar. A new polynomial-time algorithm for linear programming. *Combinatorica*, 4(4):373–395, Dec 1984.
- [15] J. Keisler. Hyperfinite model theory. In R. O. Gandy and J. M. E. Hyland, editors, *Logic Colloquim 1976*, Lecture Notes in Computer Science, page 5–10. North-Holland, 1977.
- [16] I. Kokkinis. The complexity of non-iterated probabilistic justification logic. In M. Gyssens and G. R. Simari, editors, *Foundations of Information and Knowledge Systems - 9th International Symposium, FoIKS 2016, Linz, Austria, March 7-11, 2016. Proceedings*, volume 9616 of *Lecture Notes in Computer Science*, pages 292–310. Springer, 2016.
- [17] I. Kokkinis. The complexity of probabilistic justification logic. *CoRR*, abs/1708.04100, 2017.

- [18] I. Kokkinis, P. Maksimović, Z. Ognjanović, and T. Studer. First steps towards probabilistic justification logic. *Logic Journal of the IGPL*, 23(4):662–687, 2015.
- [19] I. Kokkinis, Z. Ognjanovic, and T. Studer. Probabilistic justification logic. In S. N. Artemov and A. Nerode, editors, *Logical Foundations of Computer Science - International Symposium, LFCS 2016, Deerfield Beach, FL, USA, January 4-7, 2016. Proceedings*, volume 9537 of *Lecture Notes in Computer Science*, pages 174–186. Springer, 2016.
- [20] R. Kuznets. On the complexity of explicit modal logics. In P. G. Clote and H. Schwichtenberg, editors, *Computer Science Logic, 14th International Workshop, CSL 2000, Annual Conference of the EACSL, Fischbachau, Germany, August 21–26, 2000, Proceedings*, volume 1862 of *Lecture Notes in Computer Science*, pages 371–383. Springer, 2000.
- [21] R. Kuznets. *Complexity Issues in Justification Logic*. PhD thesis, CUNY Graduate Center, May 2008.
- [22] R. Kuznets and T. Studer. Justifications, ontology, and conservativity. In T. Bolander, T. Braüner, S. Ghilardi, and L. Moss, editors, *Advances in Modal Logic, Volume 9*, pages 437–458. College Publications, 2012.
- [23] H. E. J. Kyburg. *Probability and the Logic of Rational Belief*. Wesleyan University Press, 1961.
- [24] G. W. F. von Leibniz. *Philosophical essays*. Hackett Publishing, 1989.
- [25] A. Mkrtychev. Models for the logic of proofs. In S. Adian and A. Nerode, editors, *Logical Foundations of Computer Science, 4th International Symposium, LFCS'97, Yaroslavl, Russia, July 6–12, 1997, Proceedings*, volume 1234 of *Lecture Notes in Computer Science*, pages 266–275. Springer, 1997.
- [26] N. Nilsson. Probabilistic logic. *Artificial Intelligence*, 28:71–87, 1986.
- [27] Z. Ognjanović and M. Rašković. Some first-order probability logics. *Theoretical Computer Science*, 247(1):191–212, 2000.
- [28] Z. Ognjanović, M. Rašković, and Z. Marković. Probability logics. *Zbornik radova, subseries “Logic in Computer Science”*, 12(20):35–111, 2009.
- [29] Z. Ognjanović, M. Rašković, and Z. Marković. *Probability Logics - Probability-Based Formalization of Uncertain Reasoning*. Springer, 2016.
- [30] Z. Ognjanović, N. Savić, and T. Studer. Justification logic with approximate conditional probabilities. In A. Baltag, J. Seligman, and T. Yamada, editors, *Logic, Rationality, and Interaction - 6th International Workshop, LORI 2017, Sapporo, Japan, September 11-14, 2017, Proceedings*, volume 10455 of *Lecture Notes in Computer Science*, pages 681–686. Springer, 2017.

- [31] C. H. Papadimitriou. *Computational Complexity*. Addison-Wesley, 1994.
- [32] M. Rašković and Z. Ognjanović. A first order probability logic- $LP_Q$ . *Publications de l'Institut Mathématique. Nouvelle Série*, 65:1–7, 1999.
- [33] M. Rašković, Z. Marković, and Z. Ognjanović. A logic with approximate conditional probabilities that can model default reasoning. *Int. J. Approx. Reasoning*, 49(1):52–66, 2008.