

# The Saukas-Song Selection Algorithm and Coarse Grained Parallel Sorting

Laurence Boxer \*

## Abstract

We analyze the running time of the Saukas-Song algorithm for selection on a coarse grained multicomputer without expressing the running time in terms of communication rounds. We derive sorting algorithms that are asymptotically optimal for restricted ranges of processors on coarse grained multicomputers.

Key words and phrases: selection problem, coarse grained multicomputer, mesh, PRAM

---

\*Department of Computer and Information Sciences, Niagara University, Niagara University, NY 14109, USA; and Department of Computer Science and Engineering, State University of New York at Buffalo. E-mail: boxer@niagara.edu

# 1 Introduction

The paper [10], by Saukas and Song, presents an efficient algorithm to solve the Selection Problem on coarse grained parallel computers. The analysis of the algorithm is presented in terms of the amount of time spent in local sequential operations and the number of communications rounds. In the current paper, we replace analysis of the number of communications rounds with an analysis of the running time of the entire algorithm. We also use the Saukas-Song algorithm to obtain algorithms for sorting on coarse grained parallel computers.

## 2 Preliminaries

### 2.1 Model of Computation

Material in this section is quoted or paraphrased from [6].

The *coarse grained multicomputer* model, or  $CGM(n, p)$ , considered in this paper, has  $p$  processors with  $\Omega(n/p)$  local memory apiece - i.e., each processor has  $\Omega(n/p)$  memory cells of  $\Theta(\log n)$  bits apiece. The processors may be connected to some (arbitrary) interconnection network (such as a mesh, hypercube, or fat tree) or may share global memory. A processor may exchange messages of  $O(\log n)$  bits with any immediate neighbor in constant time. In determining time complexities, we consider both local computation time and interprocessor communication time, in standard fashion. The term “coarse grained” means that the size  $\Omega(n/p)$  of each processor’s memory is “considerably larger” than  $\Theta(1)$ ; by convention, we assume  $n/p \geq p$  (equivalently,  $n \geq p^2$ ). Thus, each processor has at least

enough local memory to store the ID number of every other processor. For more information on this model and associated operations, see [7].

### 2.2 Terminology and notation

We say an array  $list[1 \dots n]$  is *evenly distributed* in a  $CGM(n, p)$  if each processor has  $\Theta(n/p)$  members of the array.

### 2.3 Data movement operations

In the literature of CGM algorithms, many papers, including [10], analyze an algorithm by combining the running time of sequential computations with the number of “communications rounds,” the latter in which data is communicated among the processors. A communications round is described in [10] as an operation in which each processor of a  $CGM(n, p)$  can exchange  $O(n/p)$  data with other processors.

However, this definition does not lead to a clear understanding of the asymptotic running time of a CGM algorithm. E.g., a communication round could require a processor to send  $\Theta(1)$  data to a neighboring processor, which can be done in  $\Theta(1)$  time; or, a communication round could require communication of  $\Theta(1)$  data between diametrically opposite processors of a linear array, which requires  $\Theta(p)$  time.

Further, there is a sense in which the notion of a communication round is not well defined. Consider again the example of communication of  $\Theta(1)$  data between diametrically opposite processors of a linear array. This could be regarded as a single communication round

according to the description of communication rounds given above; or as  $p-1$  communications rounds, in the  $i^{\text{th}}$  of which processor  $P_i$  sends  $\Theta(1)$  data to processor  $P_{i+1}$ ,  $1 \leq i < p$ .

Now that more is known about the running times of communications operations in CGM than when [10] appeared, we can fully analyze the running time of the algorithm. In the remainder of this section, we discuss running times of communications operations used in the Saukas-Song algorithm.

**Theorem 2.1.** [3] *A unit of data can be broadcast from one processor to all other processors of a CGM( $n, p$ ) in  $O(p)$  time.  $\square$*

Let  $S$  be a set of data values distributed, not necessarily evenly, among the processors of a parallel computer. A *gather* operation results in a copy of  $S$  being in a single processor  $P_i$ , and we say  $S$  has been gathered to  $P_i$  [3, 9]. We have the following.

**Theorem 2.2.** [3] *Let  $S$  be a nonempty set of  $N$  elementary data values distributed among the processors of  $G$ , a CGM( $n, p$ ), such that  $N = \Omega(p)$  and  $N = O(n/p)$ . Then  $S$  can be gathered to any processor of  $G$  in  $\Theta(N)$  time.  $\square$*

Let  $S$  be a set of data values distributed one per processor in a parallel computer. A *multinode broadcast* operation results in every processor having a copy of  $S$ .

**Theorem 2.3.** [3] *Let  $S$  be a set of elementary data distributed one per processor in a CGM( $n, p$ ). Then a multinode broadcast operation, at the end of which every processor has a copy of  $S$ , can be performed in  $O(p^2)$  time.*

Let  $X = \{x_j\}_{j=1}^n$  be a set of data values and let  $\circ$  be a binary operation on  $X$ . A *parallel prefix* operation computes all of

$$x_1, x_1 \circ x_2, \dots, x_1 \circ x_2 \circ \dots \circ x_n.$$

**Theorem 2.4.** [3] *Let  $X = \{x_j\}_{j=1}^n$  be a set of data values distributed  $\Theta(n/q)$  per processor in a CGM( $n, q$ ). Then the parallel prefix computation of*

$$x_1, x_1 \circ x_2, \dots, x_1 \circ x_2 \circ \dots \circ x_n.$$

*can be performed in  $\Theta(n/q)$  time. At the end of this algorithm, the processor that holds  $x_j$  also holds  $x_1 \circ \dots \circ x_j$ .  $\square$*

### 3 Analysis of the Saukas-Song algorithm

The algorithm of [10] is given in Figure 1. We will refer to the steps of the algorithm as labeled in this figure. For convenience, we will take  $c = 1$  in step (2).

ALGORITHM 1. CGM algorithm for obtaining the  $k$ th smallest element, assuming  $p$  processors each with local memory of size  $O(n/p)$ .

*Input:* Set  $A$  of  $n$  elements distributed among the  $p$  processors, each processor  $i$  with  $n_i = O(n/p)$  elements, and an integer  $k$ ,  $1 \leq k \leq n$ .

*Output:* An element  $a_i$  of  $A$  such that  $\text{rank}(a_i, A) = k$ .

- (1) Set  $N := n$
- (2) Repeat until  $N \leq n/(cp)$ 
  - (2.1) Each processor  $i$  computes the median  $m_i$  of its  $n_i$  elements
  - (2.2) Each processor  $i$  sends  $m_i$  and  $n_i$  to processor 1
  - (2.3) Processor 1 computes the weighted median  $M$
  - (2.4) Processor 1 broadcasts  $M$  to all other processors
  - (2.5) Each processor  $i$  computes  $l_i, e_i, g_i$ , respectively the numbers of its local elements less than, equal to, or greater than  $M$
  - (2.6) Each processor  $i$  sends  $l_i, e_i, g_i$  to processor 1
  - (2.7) Processor 1 computes  $L = \sum_{1 \leq i \leq p} l_i$ ,  $E = \sum_{1 \leq i \leq p} e_i$ ,  $G = \sum_{1 \leq i \leq p} g_i$ , respectively the total numbers of elements less than, equal to, or greater than  $M$
  - (2.8) Processor 1 broadcasts  $L, E, G$  to all other processors
  - (2.9) One of the following:
    - if  $L < k \leq L + E$  then return solution  $M$  and stop
    - if  $k \leq L$  then each processor  $i$  discards all but those elements less than  $M$  and set  $N := L$
    - if  $k > L + E$  then each processor  $i$  discards all but those elements greater than  $M$  and set  $N := G$  and  $k := k - (L + E)$
- (3) All the remaining  $N$  elements are sent to processor 1
- (4) Processor 1 solves the remaining problem sequentially

Figure 1: The Saukas-Song algorithm of [10]

**Theorem 3.1.** [10] *After each performance of the body of the loop in step (2), the number of elements remaining under consideration is reduced by at least one quarter.  $\square$*

**Corollary 3.2.** *The number of performances of the body of the loop in step (2) is  $O(\log p)$ .*

*Proof.* It follows from Theorem 3.1 that after  $k$  performances of the body of the loop, the number of elements remaining under consideration is at most  $(3/4)^k n$ . Since step (2) terminates in the worst case when the number of elements remaining under consideration is at most  $n/p$ , termination requires, in the worst case,  $(3/4)^k n \leq n/p$ , or  $p \leq (4/3)^k$ . The smallest integer  $k$  satisfying this inequality must therefore satisfy  $k = \Theta(\log p)$ . Since the loop could terminate after as little as 1 performance of its body, the assertion follows.  $\square$

**Theorem 3.3.** *The Saukas-Song algorithm for the Selection Problem runs in  $\Theta(\frac{n \log p}{p})$  time on a CGM( $n, p$ ) in the worst case. In the best case, the running time is  $\Theta(n/p)$ . We may assume that at the end of the algorithm, every processor has the solution to the Selection Problem.*

*Proof.* We give the following argument.

- Clearly, step (1) executes in  $\Theta(1)$  time.
- We analyze step (2) as follows.
  1. Step (2.1) is executed by a linear-time sequential algorithm [1, 8]. As Saukas and Song observed, our algorithm does not guarantee that the data being considered are evenly

distributed among the processors throughout the repetitions of the loop body. In the worst case, some processor could have  $\Theta(n/p)$  data in each iteration of the loop body. Therefore, this step executes in  $O(n/p)$  time.

2. Step (2.2) is performed by a gather operation. By Theorem 2.2, this can be done in  $O(p)$  time. In the worst case, the time required is  $\Theta(p)$ ; this is the case for an architecture such as a linear array of  $p$  processors.
3. Step (2.3) is performed in  $\Theta(p)$  time.
4. Step (2.4) is performed by a broadcast operation. By Theorem 2.1, this requires  $O(p)$  time.
5. Step (2.5) is performed by sequential semigroup (counting) operations performed by all processors in parallel, in linear time [8]. As noted above, in the worst case a processor could have  $\Theta(n/p)$  data in each iteration of the loop body. Therefore, this step executes in  $O(n/p)$  time.
6. Step (2.6) is performed by a gather operation. As above, this can be done in  $O(p)$  time. In the worst case, the time required is  $\Theta(p)$ ; this is the case for an architecture such as a linear array of  $p$  processors.
7. Step (2.7) is executed by semigroup operations in  $\Theta(p)$  time.
8. Step (2.8) is performed by a broadcast operation in  $O(p)$

time. In the worst case, as above, the time required is  $\Theta(p)$ .

9. In the worst case, Step (2.9) requires each processor  $P_i$  to discard  $O(n/p)$  data items. This can be done as follows. In parallel, each processor  $P_i$  rearranges its share of the data so that the undiscarded items are at the beginning of the segment of (a copy of) *list* stored in  $P_i$ , using a sequential prefix operation in  $O(n/p)$  time.

Thus, the time required for one performance of the body of the loop of step (2) is  $O(n/p + p) = O(n/p)$ . By Corollary 3.2, the loop executes its body  $O(\log p)$  times. Thus, the loop executes all performances of its body in  $O(\frac{n \log p}{p})$  time.

- Step (3) is performed by a gather operation. Since we now have  $N \leq n/p$ , this is done in  $O(n/p)$  time.
- Step (4) uses a linear time sequential algorithm to solve the problem in  $\Theta(N) = O(n/p)$  time.
- Additionally, processor 1 can broadcast its solution to all other processors. By Theorem 2.1, this requires  $O(p)$  time.

Thus, the algorithm uses  $O(\frac{n \log p}{p})$  time.

In the best case, the loop of step (2) executes its body once, when in step (2.9) it is found that  $L < k \leq L + E$ . In this case, step (2) executes in  $\Theta(n/p)$  time, and the algorithm executes in  $\Theta(n/p)$  time.

In the worst case, there is a processor  $P_j$  that has the  $n/p$  smallest *list* elements, or the  $n/p$  largest *list* elements. In this case,  $P_j$  has  $n/p$  elements during  $\Theta(\log p)$  performances of the body of the loop of step (2), so step (2) executes in  $\Theta(\frac{n \log p}{p})$  time, and therefore the algorithm executes in  $\Theta(\frac{n \log p}{p})$  time.  $\square$

## 4 Applications to sorting

### 4.1 Sorting on a general CGM

**Theorem 4.1.** *Given a list of  $n$  data evenly distributed among the processors of a  $CGM(n, p)$ , the list can be sorted in  $O(n \log p + \frac{n \log n}{p})$  time.*

*Proof.* For simplicity, we assume in the following that every processor  $P_i$  has  $n/p$  *list* entries. Consider the following algorithm for sorting  $list[1 \dots n]$ , evenly distributed in a  $CGM(n, p)$ .

1. In parallel, each processor  $P_i$  sorts its entries of *list*. The time required is  $\Theta(\frac{n \log n}{p})$ .
2. For  $i = 1$  to  $p - 1$ , compute the  $in/p$ -th smallest member  $s_i$  of the *list* and broadcast  $s_i$  to all processors. By Theorem 3.3, the running time of this step is  $O(n \log p)$ .
3. For elements of  $\{i\}_{i=1}^p$ , let  $S_i$  be a set of elements that eventually will be sent to  $P_i$ . The set  $S_i$  is computed as follows. (Note if it is known in advance that the *list* has no duplicate values, the steps discussed below for partitioning among the sets  $S_i$  multiple *list* values that equal some  $s_k$  can be omitted.)

- In parallel, each processor  $P_i$  initializes  $n_{i,j} = 0$  for  $1 \leq j \leq p$ . This requires  $\Theta(p)$  time.
  - In this step, we determine members of the  $S_i$  that do not equal any  $s_i$ . Let  $S_1$  be the set of at most  $n/p$  members of  $list$  that are less than  $s_1$ . For  $i \in \{2, \dots, p\}$ , let  $S_i = \{x \in list \mid s_{i-1} < x < s_i\}$ . In parallel, each processor  $P_i$  does the following. For each  $x \in list$  that is in  $P_i$ , assign  $x$  a tag with the value  $j$  if  $x \in S_j$ , and increment  $n_{i,j}$  by 1. This can be done for each  $x$  via binary search in  $O(\log(n/p)) = O(\log n)$  time. Therefore, this step requires  $O(\frac{n \log n}{p})$  time. At the end of this step,  $n_{i,j}$  is the number of  $list$  entries in  $P_i$  that, so far, have been tagged for  $S_j$ .
  - For  $1 \leq j \leq p$ , compute  $n_j = \sum_{i=1}^p n_{i,j}$ , the number of  $list$  entries tagged so far for  $S_j$ . Each such sum  $n_j$  can be computed by gathering the  $n_{i,j}$  to  $P_j$  in  $\Theta(p)$  time and computing a sequential total in  $P_j$  in  $\Theta(p)$  time; in an additional  $\Theta(p)$  time,  $n_j$  can be broadcast to all processors. Therefore, doing the above for all  $j$  requires  $\Theta(p^2) = O(n)$  time.
  - Since there may be multiple  $list$  entries that equal  $s_i$ , do the following.
    - For  $i = 1$  to  $p$ 
      - (a) In parallel, each processor  $P_j$  finds the first and last of its  $list$  entries  $x$ , respectively  $list_{u_j}$  and  $list_{v_j}$ , such that  $x = s_i$  and  $x$  was not previously tagged for some  $S_k$ . Note it may be that there are no such  $list$  values in  $P_j$ . Since the  $list$  entries in  $P_j$  are sorted, this can be achieved using binary searches in  $O(\log n)$  time.
      - (b) If  $i > 1$ , perform a parallel prefix operation to tag for  $S_i$  the first, at most,  $n/p - n_i$   $list$  members that are equal to  $s_{i-1}$  and were not previously tagged for some  $S_k$ , incrementing  $n_i$  by 1 for each member tagged for  $S_i$  in this step. Note the first and last values in each processor operated upon by parallel prefix can be found in  $\Theta(1)$  time from the indices  $u_j$  and  $v_j$ . Therefore, this parallel prefix can be performed in  $O(n/p)$  time, by Theorem 2.4. Note at the end of this step,  $n_i$  again is the number of  $list$  elements tagged for  $S_i$ .
      - (c) Perform a parallel prefix operation to tag for  $S_i$  the first  $n/p - n_i$   $list$  members that are equal to  $s_i$  and are not previously tagged. As above, this requires  $O(n/p)$  time.
- End For.
- One performance of the loop body requires  $O(n/p)$  time, so the loop requires  $O(n)$  time.
4. For  $i = 1$  to  $p$ , gather  $S_i$  (which is

now the set of *list* entries tagged  $i$  to the processor  $P_i$ . By Theorem 2.2, this takes  $\Theta(p \times n/p) = \Theta(n)$  time.

5. In parallel, each processor  $P_i$  sorts  $S_i$ . At the end of this step, the *list* is sorted. The time for this step is

$$\Theta((n/p) \log(n/p)) = \Theta\left(\frac{n \log n}{p}\right).$$

Thus, the running time of this algorithm is  $O(n \log p + \frac{n \log n}{p})$ .  $\square$

**Remark 4.2.** When  $\log p \leq \frac{\log n}{p}$ , or equivalently,  $p^p \leq n$ , the running time of this algorithm reduces to  $\Theta(\frac{n \log n}{p})$ , which is asymptotically optimal, since optimal time for sequential sorting is  $\Theta(n \log n)$ . The condition  $p^p \leq n$  is very common, e.g., for personal computers, laptops, smartphones, game machines, embedded systems, etc.  $\square$

**Remark 4.3.** When  $\log p \geq \frac{\log n}{p}$ , or equivalently,  $p^p \geq n$ , our algorithm's running time reduces to  $O(n \log p)$ . This is asymptotically faster than sequential sorting time, although it seems reasonable to hope for further improvement.  $\square$

## 4.2 Coarse grained sorting on a mesh with extra memory

In this section, we obtain an algorithm for sorting on a CGM with a mesh architecture and extra memory. Our algorithm is asymptotically faster than that of Theorem 4.1.

Since the rows and columns of a mesh are linear arrays, the following will be useful.

**Lemma 4.4.** *Suppose a CGM( $n, p$ ) is a linear array and has a list of  $n$  entries stored in its processors, not necessarily evenly distributed. Then the members of the list can be redistributed so that the list is evenly distributed among the processors, in  $O(n)$  time.*

*Proof.* This can be done by a rotation of the data through the processors, in which only excess data from processors with more than  $n/p$  entries is rotated, and a data value stops its participation in the rotation upon reaching a processor with less than  $n/p$  entries.  $\square$

In the following, we assume some extra memory, as the algorithm may have intermediate states in which the *list* is not evenly distributed.

**Theorem 4.5.** *Let a CGM( $np^{1/2}, p$ ) be a mesh with a list of  $n$  entries stored in its processors, evenly distributed. Then the list can be sorted in*

$$\Theta\left(\frac{n \log p}{p^{1/2}} + \frac{n \log n}{p}\right)$$

*time.*

*Proof.* For simplicity, we assume that the *list* items are all distinct. In the more general case, we can determine which members of the *list* go to any processor by accommodating duplicate values as in the proof of Theorem 3.3. We also assume that the processors are numbered in row-major order [8]. Consider the following algorithm.

1. For  $i = 1$  to  $p^{1/2}$ , compute the  $ip^{1/2}$ -th smallest *list* member  $t_i$  and broadcast  $t_i$  to all processors. By Theorem 3.3, this can be done in

$$\Theta(p^{1/2} \times \frac{n \log p}{p}) = \Theta(\frac{n \log p}{p^{1/2}})$$
 time.

2. The set  $R_i$  of *list* members that must be sent to the processors of row  $i$  is

$$R_1 = \{list_j \mid list_j \leq t_1\};$$

$$R_i = \{list_j \mid t_{i-1} < list_j \leq t_i\}$$

$$\text{for } 2 \leq i \leq p^{1/2}.$$

In parallel, all processors  $P_m$  determine, for each of their *list* members  $x$ , to which  $R_i$   $x$  belongs, by conducting binary searches for  $x$  among the values of  $\{t_i\}_{i=1}^{p^{1/2}}$ . This requires  $O(\frac{n \log n}{p})$  time.

3. In parallel, each column  $j$  of the mesh performs a column rotation of its *list* members so that if  $x$  is a *list* entry such that  $x \in R_i$ , then  $x$  finishes the rotation in  $P_{i,j}$ , the processor in row  $i$  and column  $j$ . In the worst case, for some  $i, j$  we have all  $n/p^{1/2}$  *list* entries of column  $j$  belonging to  $R_i$ . Thus, this step takes  $O(n/p^{1/2})$  time. At the end of this step, each *list* member is in the correct row of the mesh for our ordering of the data.
4. In a  $CGM(np^{1/2}, p)$ , each processor can hold  $\Omega(n/p^{1/2})$  data. This is necessary as, in the worst case, some processor has received all the  $n/p^{1/2}$  *list* entries of its column. In parallel, each row  $i$  of the mesh does the following.

- Redistribute the *list* entries of the row so that each processor  $P_{i,j}$  has  $n/p$  *list* members of  $R_i$ . The row has the  $n/p^{1/2}$  *list* entries, so this requires  $O(n/p^{1/2})$  time, by Lemma 4.4.

- For  $j = 1$  to  $p^{1/2}$ , compute the  $jp^{1/2}$ -th smallest *list* member  $u_{i,j}$  in row  $i$  and broadcast  $u_{i,j}$  to all processors of the row. By Theorem 3.3, this can be done in

$$O\left(p^{1/2} \times \frac{\frac{n}{p^{1/2}} \log p^{1/2}}{p^{1/2}}\right) =$$

$$O\left(\frac{n \log p}{p^{1/2}}\right) \text{ time.}$$

- Let  $U_{i,1}$  be the set of *list* members in  $R_i$  that are less than or equal to  $u_{i,1}$ , and let  $U_{i,j}$  be the set of *list* members in  $R_i$  that are greater than  $u_{i,j-1}$  and less than or equal to  $u_{i,j}$ . Perform a row rotation of the *list* members of row  $i$  so that a *list* member  $x$  that belongs to  $U_{i,j}$  stops its participation in the rotation upon reaching  $P_{i,j}$ . Since row  $i$  has  $n/p^{1/2}$  *list* members, the time required is  $O(n/p^{1/2})$ . At the end of this step, every *list* member is in the correct processor for the ordering of the *list*.

End parallel

5. In parallel, every processor  $P_{i,j}$  sorts its *list* members in

$$\Theta(n/p \log(n/p)) = \Theta\left(\frac{n \log n}{p}\right)$$

time. This completes the sort.

Clearly, the running time of the algorithm is  $\Theta\left(\frac{n \log p}{p^{1/2}} + \frac{n \log n}{p}\right)$ .  $\square$

Notice the following.

**Remark 4.6.** When  $\frac{\log p}{p^{1/2}} \leq \frac{\log n}{p}$ , or, equivalently,  $p^{p^{1/2}} \leq n$ , the running time of our algorithm reduces to optimal  $\Theta(\frac{n \log n}{p})$ , which is optimal.  $\square$

**Remark 4.7.** When  $\frac{\log p}{p^{1/2}} \geq \frac{\log n}{p}$ , or, equivalently,  $p^{p^{1/2}} \geq n$ , this algorithm's running time reduces to  $\Theta(\frac{n \log p}{p^{1/2}})$ , which is somewhat better than the running time for the non-optimal case for the general architecture discussed at Remark 4.3.  $\square$

**Corollary 4.8.** A CGM( $n, p$ ) with a PRAM architecture can sort  $n$  data in  $\Theta(\frac{n \log p}{p^{1/2}} + \frac{n \log n}{p})$  time.

*Proof.* A PRAM can execute the algorithm of Theorem 4.5 without need for the extra memory.  $\square$

## 5 Further remarks

We have given an asymptotic analysis of the running time of the Saukas-Song selection algorithm for coarse grained parallel computers. We have used this algorithm to obtain efficient algorithms for coarse grained parallel sorting.

There are many CGM algorithms in such papers as [7, 5, 6] for which running times are analyzed in terms of  $T_{sort}(n, p)$ , the time to sort  $\Theta(n)$  data on a CGM( $n, p$ ), where the expression  $T_{sort}(n, p)$  is used as an unevaluated primitive. For many of these algorithms, we can use results of this paper so that the running time of the algorithm can be expressed without using  $T_{sort}(n, p)$  as an unevaluated primitive.

One can find experimental results for the Saukas-Song selection algorithm in [10].

## References

- [1] M. Blum, R.W. Floyd, V. Pratt, R. L. Rivest, and R. E. Tarjan, Bounds for selection, *Journal of Computer and System Sciences* 7 (1973), 448-461.
- [2] L. Boxer, Efficient coarse grained permutation exchanges and matrix multiplication, *Parallel Processing Letters* 19 (3), 2009, 477-484.
- [3] L. Boxer and R. Miller, Coarse grained gather and scatter operations with applications, *Journal of Parallel and Distributed Computing* 64 (11) (2004), 1297-1310.
- [4] L. Boxer and R. Miller, Efficient Coarse Grained Data Distributions and String Pattern Matching, *International Journal of Information and Systems Sciences* 6 (4) (2010), 424-434.
- [5] L. Boxer, R. Miller, and A. Rau-Chaplin, Scalable parallel algorithms for lower envelopes with applications, *Journal of Parallel and Distributed Computing* 53 (1998), 91-118.
- [6] L. Boxer, R. Miller, and A. Rau-Chaplin, Scalable parallel algorithms for geometric pattern recognition, *Journal of Parallel and Distributed Computing* 58 (1999), 466-486.
- [7] F. Dehne, A. Fabri, and A. Rau-Chaplin, Scalable parallel geometric algorithms for multicomputers, *Int. Journal of Computational Geometry and Applications* 6 (1996), 379-400.

- [8] R. Miller and L. Boxer, *Algorithms Sequential and Parallel, A Unified Approach*, 3rd ed., Cengage Learning, Boston, 2013.
- [9] R. Miller and Q.F. Stout, *Parallel Algorithms for Regular Architectures: Meshes and Pyramids*, The MIT Press, Cambridge, MA, 1996.
- [10] E.L.G. Saukas and S.W. Song, A note on parallel selection on coarse-grained multicomputers, *Algorithmica* 24 (1999), 371380.