

# SOAR: Simultaneous Or-of-And Rules for Classification of Positive & Negative Classes

Elena Khusainova  
Yale University

Emily Dodwell  
AT&T Labs

Ritwik Mitra  
AT&T Labs

## ABSTRACT

Algorithmic decision making has proliferated and now impacts our daily lives in both mundane and consequential ways. Machine learning practitioners make use of a myriad of algorithms for predictive models in applications as diverse as movie recommendations, medical diagnoses, and parole recommendations without delving into the reasons driving specific predictive decisions. Machine learning algorithms in such applications are often chosen for their superior performance, however popular choices such as random forest and deep neural networks fail to provide an interpretable understanding of the model’s predictions. In recent years, rule-based algorithms have been used to address this issue. Wang et al. [26] presented an or-of-and (disjunctive normal form) based classification technique that allows for classification rule mining of a single class in a binary classification; this method is also shown to perform comparably to other modern algorithms. In this work, we extend this idea to provide classification rules for both classes simultaneously. That is, we provide a distinct set of rules for each of the positive and negative classes. In describing this approach, we also present a novel and complete taxonomy of classifications that clearly capture and quantify the inherent ambiguity of noisy binary classifications in the real world. We show that this approach leads to a more granular formulation of the likelihood model and a simulated annealing-based optimization achieves classification performance competitive with comparable techniques. We apply our method to synthetic and real world data sets for comparison with other related methods to demonstrate the utility of our contribution.

## 1 INTRODUCTION

The use of machine learning (ML) tools is ubiquitous in today’s world, with applications ranging from the purely technical, e.g. facial recognition or spam detection, to the biomedical (Shen et al. [22], Esteva et al. [10], Libbrecht and Noble [18]) and social sciences (Berk [1]); ML has found its way into virtually all aspects of modern life. However, as researchers and practitioners become accustomed to turning to ML methods for performing increasingly more complicated and high-impact tasks, good model fit and high predictive accuracy of ML tools, while desirable, are proving insufficient. There is a need for transparency in large-scale automated decisions to enable proper assignment of accountability for applications with important implications to human lives; see Varshney and Alemzadeh [24]. This need has found further validation in the European Union’s (EU) adoption of General Data Protection Regulation (GDPR) (see [7]), guidelines that address the collection, storage, processing, and use of personal data of EU residents. GDPR stipulates that in situations where personal data are processed for use in an automated decision mechanism, individuals should have

*the right to obtain human intervention, to express his or her point of view, to obtain an explanation of the decision reached after such assessment and to challenge the decision.*

This could potentially lead the way for wider adoption of and preference for interpretable, non-black-box models in certain domains. See also Goodman and Flaxman [14], Wachter et al. [25], for further discussion of legal implications regarding interpretability and explainability as stated in GDPR.

This need for understanding has spurred the development of Interpretable Machine Learning (IML), a sub-division of machine learning that focuses on discovering and making explicit the relationships between predictors and a specific outcome in a form understandable by humans. *Interpretability* in machine learning is a rapidly growing field<sup>1</sup>, and researchers have tried to achieve it in a variety of ways. Perhaps necessarily, it is an ambiguous term with ‘domain-specific’ implications (Rudin [21], Murdoch et al. [20], Doshi-Velez and Kim [9]). One approach to achieve interpretability has been to build black box models and assign explainability to their predictions post-hoc through various mechanisms; we refer to Guidotti et al. [15] for a detailed accounting and references. In this current work, we instead adopt IML to refer to that definition suggested by Murdoch et al. [20]:

*The use of machine-learning models for the extraction of relevant knowledge about domain relationships contained in data.*

The term *relevant* means that the insights obtained are useful for the chosen audience and problem domain. The interpretability that we are interested in is *model-based*, rather than *post hoc*, meaning that we do not seek new ways of deriving insights from existing methods, but rather creating a new algorithm that is inherently designed to be interpretable.

Given this increased need for transparency in situations where ML algorithms have potential for significant impact on human subjects, and in light of the distinction between explainable and interpretable models, we focus our attention on the latter with the evolution of rule-based classifiers that are inherently interpretable.

A widely-used class of IML tools is rule ensemble algorithms (Friedman and Popescu [12]). Rule-based algorithms are inherently interpretable as they fit the model with a set of rules that can be understood by a human. For example, the following may define the outcome of a customer’s choice regarding whether or not to buy a piece of clothing based on its color, size, and price:

If *color* is *blue* and *price* is *low* then *buy* = “yes”

If *color* is *red* and *size* is *M* and *price* is *high* then *buy* = “no”

<sup>1</sup>Google Scholar produces more than 5000 results for the search “Interpretable Machine Learning” for the period from January 2015 to April 2020 as opposed to less than 200 for all time before 2015.

If *size* is XXXS then *buy* = “yes”

Such rules enable us to see relationships between variables by expressing dependencies of the outcome variable on the predictors in a manner that can be easily comprehended.

The history of rule-based interpretable machine learning (especially rules of the above form) is rich, and the field is growing. Early instances of rule-based ML models may be found in Crama et al. [8] and Boros et al. [4] in the context of “logical analysis of data,” which aims to detect and group patterns that can correctly classify examples. Friedman and Fisher [11] introduced the Patient Rule Induction Method (PRIM), which identifies simple rules to define rectangular subregions of the input variable space that correspond to above- or below-average values of the output variable. Further extensions of PRIM have been studied in Goh and Rudin [13], where exact and approximate-yet-fast rule sets can be derived through mixed integer programming. Cohen [6] proposed a fast algorithm RIPPER<sub>k</sub> which creates a rule-based model by first growing a rule set and then repeatedly pruning it based on error-reducing criteria. We refer to Molnar [19] for a recent accounting of interpretable machine learning methods and further references because research in this field has evolved in various directions too numerous to note here in detail.

Relevant to our current work, Wang et al. [26] proposed a rule-based algorithm for binary classification called Bayesian Or’s of And’s (BOA), which represents a Bayesian framework to address the issue of model interpretability. As the name suggests, the algorithm requires a prior distribution on the set of possible rules that may serve as a proxy for professional opinion about the shape of the rule set. This algorithm results in one rule set that defines the positively classified observations, while the negative class is passively defined as its complement. The algorithm was created in the context of recommendation systems (Wang et al. [26]) for which the positive class is of primary interest.

However, in certain applications, obtaining a rule set for the negative class may be just as important as defining the positive class. Consider for example, a classification model that predicts whether a patient will have a drug-related adverse reaction (positive class) or not (negative class) given their medical history, including e.g. comorbidities, results of diagnostic tests, and prior prescribed medication. Such a model may enable safer administration of a newer drug when, for example, adverse effects of a treatment and its potential toxicity require further study and consideration. In this scenario, there is significant value for both the doctor and subject receiving the treatment to understand the combination of factors associated with non-occurrence of an adverse event (i.e. definition of the negative class) to inform safe treatment and motivate patient compliance. Furthermore, cases where rules associated with both an adverse event’s occurrence and non-occurrence are satisfied may indicate complicated interactions of multiple factors, which alerts both the doctor and patient to the potential for extenuating circumstances and enable closer monitoring. We address this important aspect of rule-based modeling directly in this work.

**Contribution.** In this paper we propose SOAR, **S**imultaneous **O**r-of-**A**nd **R**ules, an algorithm to identify rule sets for each of the positive and negative classes in a binary classification problem. The SOAR algorithm is an extension of the BOA algorithm. It treats

the positive and negative classes separately and produces a defined rule set for each, rather than creating rules for the positive class and assigning the complement to the negative class. We therefore take a direct approach through the Bayesian framework as proposed in Wang et al. [26] and describe a complete likelihood for both classes. We calculate the posterior likelihood through annealing (Van Laarhoven and Aarts [23]). A key advantage of this approach is that two rule sets allow for cases that may satisfy both or neither of them; we refer to such cases as “ambiguous”. We argue that for these ambiguous cases, insight into which of an observation’s traits help assign it to both the positive and negative classes (or neither) is important for interpretability. Recognizing this need for describing ambiguity, SOAR provides a complete *taxonomy* of classifications that identify conflicts when the same rules suggest different classes. This taxonomy is useful and important for real world applications which tend to be noisy and do not lend themselves to neat categorizations.

Our work is organized as follows: in Section 2, we present an implementation of the SOAR algorithm and discuss terminology and key notation as they appear throughout the remaining sections. We present a detailed description of our proposal and introduce the complete taxonomy of classifications in Section 3, as well as explain the algorithm for creating simultaneous rules. In Section 4, we validate our algorithm with one simulated and two real-word data sets. By comparing SOAR to algorithms such as BOA and random forest, we find that SOAR’s performance is comparable in predictive accuracy; by offering deeper insights provided by a rule set that explicitly defines the negative class, our algorithm provides increased descriptive accuracy.

## 2 PROBLEM SET UP

In this section we define the problem and the terminology we use. When possible we adopt notation and terminology from either Friedman and Popescu [12] or Wang et al. [26].

The algorithm is intended to address the standard binary classification problem. We assume that the data, denoted as  $X$ , consist of  $p$  categorical predictors and  $n$  observations. That is  $X := [X_{\cdot 1}, \dots, X_{\cdot p}]$ , with  $X_{\cdot i} \in \{0, 1\}^n$  for  $1 \leq i \leq p$ . Note, that  $X$  can be also expressed as  $X := [X_1, \dots, X_n]^T$ . When it does not cause confusion we will abandon dots in the notation and use  $\mathbf{x}_i = X_i$ , to refer to observations in the data. For simplicity of notation, we also say that  $X = \{\mathbf{x}_1, \dots, \mathbf{x}_n\}$ . Additionally, each observation belongs to one of two classes, labeled as 0 and 1, with labels stored in the variable of interest  $Y = [y_1, \dots, y_n] \in \{0, 1\}^n$ .

In order to define the form of the model to fit the data, we need to first define rules. Let function  $\mathbf{r} = \mathbf{r}(\mathbf{x})$  be a product of indicators:

$$\mathbf{r}(\mathbf{x}) = \prod_{i=1}^k \mathbb{1}\{\mathbf{x}[s_i] = x_i\}, \quad (2.1)$$

where  $\mathbf{x} \in X$ ,  $1 \leq s_i \leq p$  and values  $x_i$  belong to the range of corresponding predictors  $X_{\cdot s_i}$ ,  $i = 1, \dots, k$ . We say that any function of the form (2.1) is a *rule* or *pattern* of length  $k$ . For a set of rules  $R$  we say that

$$R(\mathbf{x}) = \begin{cases} 1 & \text{if there exists } \mathbf{r} \in R \text{ such that } \mathbf{r}(\mathbf{x}) = 1, \\ 0 & \text{otherwise} \end{cases} \quad (2.2)$$

and define

$$X_R := \{x \in X : R(x) = 1\}$$

to be the set of all observations that satisfy the rule set  $R$ .

The model we fit then takes form:

$$f(x) = \sum_{m=1}^M r_m(x),$$

where  $r_1, \dots, r_m$  are rules. This form of the model can be seen as a disjunction of conjunctions, or simply, Or-of-Ands (hence the name of the algorithm). If sets  $X^+$  and  $X^-$  are such that

$$\begin{aligned} X^+ &= \{x_i \in X : y_i = f(x_i) = 1\}, \\ X^- &= \{x_i \in X : y_i = f(x_i) = 0\}, \end{aligned}$$

that is,  $X^+$  and  $X^-$  consist of observations from positive and negative classes respectively, then the goal of the algorithm is to find rule sets  $R^+$  and  $R^-$  such that  $X_{R^+}$  and  $X_{R^-}$  are close (in terms of maximizing the posterior distribution, see Section 3.2) to  $X^+$  and  $X^-$  respectively.

### 3 SIMULTANEOUS OR-OF-AND RULES

In this section we present the construction of the prior and log-likelihood model and also introduce the new taxonomy to be used with simultaneous classification.

The main contribution of the SOAR algorithm is that instead of finding trends and patterns among just the positive observations, we do so simultaneously for each of the positive and negative classes.

#### 3.1 Taxonomy of classifications

Consider two rule sets  $R_*^+$  and  $R_*^-$  and the corresponding sets of observations  $X_{R_*^+}$  and  $X_{R_*^-}$ . We call cases in  $X_{R_*^+} \cap X_{R_*^-}$  *active ambiguous* and those in  $X \setminus (X_{R_*^+} \cup X_{R_*^-})$  *passive ambiguous*. Intuitively,  $R_*^+$  and  $R_*^-$  describe the characteristics of positive and negative sets respectively. Then active ambiguous refers to those cases that exhibit characteristics of both classes, while passive ambiguous are cases that do not exhibit characteristics of either class.

For cases in  $X_{R_*^+} \cap \overline{X_{R_*^-}}$  or  $X_{R_*^-} \cap \overline{X_{R_*^+}}$ , where  $\overline{X_{R_*^+}} := X \setminus X_{R_*^+}$  and  $\overline{X_{R_*^-}} := X \setminus X_{R_*^-}$ , we say that there is *consensus*. These represent cases that satisfy the positive class definition and not that of the negative class, or vice versa.

Table 1: Taxonomy

$\{y_i = 1 \mid R^+(x_i) = 1, R^-(x_i) = 0\}$	=	Consensus - True Positive	(CTP),
$\{y_i = 0 \mid R^+(x_i) = 1, R^-(x_i) = 0\}$	=	Consensus - False Positive	(CFP),
$\{y_i = 0 \mid R^+(x_i) = 0, R^-(x_i) = 1\}$	=	Consensus - True Negative	(CTN),
$\{y_i = 1 \mid R^+(x_i) = 0, R^-(x_i) = 1\}$	=	Consensus - False Negative	(CFN),
$\{y_i = 1 \mid R^+(x_i) = 1, R^-(x_i) = 1\}$	=	Active Ambiguous - Positive	(AAP),
$\{y_i = 0 \mid R^+(x_i) = 1, R^-(x_i) = 1\}$	=	Active Ambiguous - Negative	(AAN),
$\{y_i = 1 \mid R^+(x_i) = 0, R^-(x_i) = 0\}$	=	Passive Ambiguous - Positive	(PAP),
$\{y_i = 0 \mid R^+(x_i) = 0, R^-(x_i) = 0\}$	=	Passive Ambiguous - Negative	(PAN).

The complete taxonomy is presented in Table 1. For an observation  $x_i$  we can have one and only one of the eight possible scenarios. The first four cases are standard for classification problems, but the last four are slightly unusual. We allow the algorithm to

not give any prediction if there is uncertainty in the data which in turn highlights the inherent ambiguity. We argue that allowing such cases makes our method more appropriate in circumstances where the user would prefer a second opinion model, as our expanded taxonomy provides for this detailed look.

#### 3.2 Beta-Binomial prior and log-likelihood model

We now describe the prior distribution for the model and the model itself. The first step of the algorithm (described in Section 3.3) results in two pattern sets  $\mathcal{P}^+$  and  $\mathcal{P}^-$ , called *pattern pools*. The patterns in each of them satisfy three conditions:

- each pattern consists of no more than  $L$  literals, with  $L$  provided by the user;
- each pattern is frequent in the data. That is, there are more than a pre-specified threshold of observations that agree with the pattern;
- each patterns on its own has a strong relationship with the outcome variable (in terms of impurity score).

The prior is defined on the sets of all subsets of  $\mathcal{P}^+$  and  $\mathcal{P}^-$  in the following way:

- (1) For each  $l^+, l^- \in \{1, 2, \dots, L\}$  we simulate  $p_{l^+}^+$  and  $p_{l^-}^-$  such that

$$p_{l^+}^+ \sim \text{Beta}(\alpha_{l^+}^+, \beta_{l^+}^+) \text{ and } p_{l^-}^- \sim \text{Beta}(\alpha_{l^-}^-, \beta_{l^-}^-).$$

The parameters

$$\theta_{prior} = \{\alpha_1^+, \dots, \alpha_{L^+}^+, \alpha_1^-, \dots, \alpha_{L^-}^-, \beta_1^+, \dots, \beta_{L^+}^+, \beta_1^-, \dots, \beta_{L^-}^-\}$$

are user-specified.

- (2) Each pattern of length  $l^+$  (or  $l^-$ ) is selected from  $\mathcal{P}^+$  (or  $\mathcal{P}^-$ ) with probability  $p_{l^+}^+$  (or  $p_{l^-}^-$ ).

In subsequent discussions, we describe the prior on the positive and negative rules jointly as

$$\pi(R^+, R^- \mid \theta_{prior}).$$

With full control over parameters of the prior, the user can influence the shape of the outcome by limiting the maximal pattern length, favoring longer or shorter patterns, and affecting the size of each of the rule sets.

We next explicitly write the likelihood of the data given a model. The following likelihood parameters govern the probability that an observation is of a true positive (or negative) class when it satisfies the corresponding pattern sets:

$$\begin{aligned} \rho_A^+ &= \mathbb{P}(y_n = 1 \mid R^+(x_n) = 1, R^-(x_n) = 1), \\ \rho_A^- &= \mathbb{P}(y_n = 0 \mid R^+(x_n) = 0, R^-(x_n) = 0), \\ \rho_C^+ &= \mathbb{P}(y_n = 1 \mid R^+(x_n) = 1, R^-(x_n) = 0), \\ \rho_C^- &= \mathbb{P}(y_n = 0 \mid R^+(x_n) = 0, R^-(x_n) = 1). \end{aligned} \quad (3.1)$$

The prior for these four parameters are assigned as follows:

$$\begin{aligned} \rho_A^+ &\sim \text{Beta}(\alpha_A^+, \beta_A^+), \rho_A^- \sim \text{Beta}(\alpha_A^-, \beta_A^-), \\ \rho_C^+ &\sim \text{Beta}(\alpha_C^+, \beta_C^+), \rho_C^- \sim \text{Beta}(\alpha_C^-, \beta_C^-). \end{aligned}$$

As before, parameters  $\theta_{likelihood} = \{\alpha_A^+, \beta_A^+, \alpha_A^-, \beta_A^-, \alpha_C^+, \beta_C^+, \alpha_C^-, \beta_C^-\}$  are provided by the user. Denote  $\varrho = \{\rho_A^+, \rho_A^-, \rho_C^+, \rho_C^-\}$ ; then the log-likelihood of the data is given by:

$$\begin{aligned}
& \log \left( \mathbb{P}(\{\mathbf{x}_i, y_i\}_{i=1}^n \mid \mathbf{R}^+, \mathbf{R}^-, \boldsymbol{\rho}) \right) \\
&= \sum_{i=1}^n \left[ \left\{ y_i \mathbf{R}^+(\mathbf{x}_i)(1 - \mathbf{R}^-(\mathbf{x}_i)) \right\} \log \rho_C^+ \right. \\
&\quad + \left\{ (1 - y_i) \mathbf{R}^+(\mathbf{x}_i)(1 - \mathbf{R}^-(\mathbf{x}_i)) \right\} \log(1 - \rho_C^+) \\
&\quad + \left\{ (1 - y_i)(1 - \mathbf{R}^+(\mathbf{x}_i)) \mathbf{R}^-(\mathbf{x}_i) \right\} \log \rho_C^- \\
&\quad + \left\{ y_i(1 - \mathbf{R}^+(\mathbf{x}_i)) \mathbf{R}^-(\mathbf{x}_i) \right\} \log(1 - \rho_C^-) \\
&\quad + \left\{ y_i \mathbf{R}^+(\mathbf{x}_i) \mathbf{R}^-(\mathbf{x}_i) \right\} \log \rho_A^+ \\
&\quad + \left\{ (1 - y_i) \mathbf{R}^+(\mathbf{x}_i) \mathbf{R}^-(\mathbf{x}_i) \right\} \log(1 - \rho_A^+) \\
&\quad + \left\{ (1 - y_i)(1 - \mathbf{R}^+(\mathbf{x}_i))(1 - \mathbf{R}^-(\mathbf{x}_i)) \right\} \log \rho_A^- \\
&\quad \left. + \left\{ y_i(1 - \mathbf{R}^+(\mathbf{x}_i))(1 - \mathbf{R}^-(\mathbf{x}_i)) \right\} \log(1 - \rho_A^-) \right] \\
&= \text{CTP} \log(\rho_C^+) + \text{CFP} \log(1 - \rho_C^+) \\
&\quad + \text{CTN} \log(\rho_C^-) + \text{CFN} \log(1 - \rho_C^-) \\
&\quad + \text{AAP} \log(\rho_A^+) + \text{AAN} \log(1 - \rho_A^+) \\
&\quad + \text{PAN} \log(\rho_A^-) + \text{PAP} \log(1 - \rho_A^-), \tag{3.2}
\end{aligned}$$

where CTP, CFP, CTN, CFN, AAP, AAN, PAN, PAP are the counts of the corresponding cases. Here we have (with slight abuse of notation) used the empirical versions of the definitions defined in Table 1. Incorporating the prior structure for  $\boldsymbol{\rho}$ , we get

$$\begin{aligned}
& \mathbb{P}(\{\mathbf{x}_i, y_i\}_{i=1}^n \mid \mathbf{R}^+, \mathbf{R}^-, \boldsymbol{\theta}_{\text{likelihood}}) \\
&= \int_{\boldsymbol{\rho}} \left( \mathbb{P}(\{\mathbf{x}_i, y_i\}_{i=1}^n \mid \mathbf{R}^+, \mathbf{R}^-, \boldsymbol{\rho}) \right) \\
&\quad \times \text{Beta}(\alpha_A^+, \beta_A^+) \text{Beta}(\alpha_A^-, \beta_A^-) \text{Beta}(\alpha_C^-, \beta_C^-) \text{Beta}(\alpha_C^+, \beta_C^+) d\boldsymbol{\rho}. \\
&= \int_{\boldsymbol{\rho}} (\rho_C^+)^{\text{CTP}} (1 - \rho_C^+)^{\text{CFP}} (\rho_C^-)^{\text{CTN}} (1 - \rho_C^-)^{\text{CFN}} \\
&\quad \times (\rho_A^+)^{\text{AAP}} (1 - \rho_A^+)^{\text{AAN}} (\rho_A^-)^{\text{PAN}} (1 - \rho_A^-)^{\text{PAP}} \\
&\quad \times \text{Beta}(\alpha_A^+, \beta_A^+) \text{Beta}(\alpha_A^-, \beta_A^-) \text{Beta}(\alpha_C^-, \beta_C^-) \\
&\quad \times \text{Beta}(\alpha_C^+, \beta_C^+) d\rho_A^+ d\rho_A^- d\rho_C^+ d\rho_C^- \\
&= \left\{ \frac{\text{B}(\text{CTP} + \alpha_C^+, \text{CFP} + \beta_C^+)}{\text{B}(\alpha_C^+, \beta_C^+)} \right\} \times \left\{ \frac{\text{B}(\text{CTN} + \alpha_C^-, \text{CFN} + \beta_C^-)}{\text{B}(\alpha_C^-, \beta_C^-)} \right\} \\
&\quad \times \left\{ \frac{\text{B}(\text{AAP} + \alpha_A^+, \text{AAN} + \beta_A^+)}{\text{B}(\alpha_A^+, \beta_A^+)} \right\} \times \left\{ \frac{\text{B}(\text{PAN} + \beta_A^-, \text{PAP} + \alpha_A^-)}{\text{B}(\alpha_A^-, \beta_A^-)} \right\}, \tag{3.3}
\end{aligned}$$

where  $\text{B}(a, b) = \Gamma(a)\Gamma(b)/\Gamma(a+b)$ . The final posterior distribution for the rules and data is then given by:

$$\begin{aligned}
& \mathbb{P}(\{\mathbf{x}_i, y_i\}_{i=1}^n, \mathbf{R}^+, \mathbf{R}^- \mid \boldsymbol{\theta}_{\text{likelihood}}, \boldsymbol{\theta}_{\text{prior}}) \\
&\propto \mathbb{P}(\{\mathbf{x}_i, y_i\}_{i=1}^n \mid \mathbf{R}^+, \mathbf{R}^-, \boldsymbol{\theta}_{\text{likelihood}}) \times \pi(\mathbf{R}^+, \mathbf{R}^- \mid \boldsymbol{\theta}_{\text{prior}}). \tag{3.4}
\end{aligned}$$

The MAP (maximum *a posteriori*) estimator for these rules is then given by:

$$(\mathbf{R}_*^+, \mathbf{R}_*^-) := \underset{\mathbf{R}^+ \subseteq \mathcal{P}^+, \mathbf{R}^- \subseteq \mathcal{P}^-}{\text{argmax}} \mathbb{P}(\{\mathbf{x}_i, y_i\}_{i=1}^n, \mathbf{R}^+, \mathbf{R}^- \mid \boldsymbol{\theta}_{\text{likelihood}}, \boldsymbol{\theta}_{\text{prior}}). \tag{3.5}$$

### 3.3 Algorithm

The algorithm can be divided into three main steps:

- (1) Frequent pattern mining. The most frequent patterns are mined from the data using the scalable FPGrowth algorithm introduced by Han et al. [16] and implemented by Borgelt [3].

**REMARK 3.1.** *Note that frequent pattern mining (FPM) is agnostic of the positive or negative class membership of the observation. As such, one could run a single FPM on the whole dataset to get a set of frequent rules for both positive and negative classes. That is, at this stage the positive and negative pattern pools are identical.*

- (2) Pattern screening. The patterns mined in the previous step are ranked based on one of the following, user-chosen, impurity functions: conditional entropy or Gini index. The best ones form the final pattern pools of the size limited by the user.
- (3) Simulated annealing to find MAP (3.5). For details, see Algorithm 1.

Define

$$\text{Score}(\mathbf{R}^+, \mathbf{R}^-) = -\log \mathbb{P}(\{\mathbf{x}_i, y_i\}_{i=1}^n, \mathbf{R}^+, \mathbf{R}^- \mid \boldsymbol{\theta}_{\text{likelihood}}, \boldsymbol{\theta}_{\text{prior}}),$$

and the cooling schedule:

$$T(t) := \frac{T_0}{\log(1+t)},$$

where the initial temperature  $T_0$  is user-defined. Then the simulated annealing algorithm to find MAP solution is as shown in Algorithm 1.

**Algorithm 1** Simulated annealing for finding MAP

---

```

1: procedure SOAR(...)
2:    $R^+(0), R^-(0) \leftarrow$  initial rule sets
3:    $(R^+, R^-) \leftarrow (R^+(0), R^-(0))$ 
4:    $t \leftarrow 1$ 
5:   while  $t < iter_{max}$  do
6:      $x_t \leftarrow$  a randomly selected observation with incorrect prediction (based on  $(R^+, R^-)$ )
7:     if  $[y_i == 1]$  then
8:       if  $[R^+(x_i) == 1 \text{ AND } R^-(x_i) == 1]$  then  $R_{temp}^+ \leftarrow COVERLESS(R^-(t-1))$ 
9:       if  $[R^+(x_i) == 0 \text{ AND } R^-(x_i) == 0]$  then  $R_{temp}^+ \leftarrow COVERMORE(R^+(t-1))$ 
10:      if  $[R^+(x_i) == 0 \text{ AND } R^-(x_i) == 1]$  then
11:         $R_{temp}^+ \leftarrow \begin{cases} COVERLESS(R^-(t-1)) & \text{with prob } 0.5 \\ COVERMORE(R^+(t-1)) & \text{with prob } 0.5 \end{cases}$ 
12:      if  $[y_i == 0]$  then
13:        if  $[R^+(x_i) == 1 \text{ AND } R^-(x_i) == 1]$  then  $R_{temp}^+ \leftarrow COVERLESS(R^-(t-1))$ 
14:        if  $[R^+(x_i) == 0 \text{ AND } R^-(x_i) == 0]$  then  $R_{temp}^+ \leftarrow COVERMORE(R^+(t-1))$ 
15:        if  $[R^+(x_i) == 1 \text{ AND } R^-(x_i) == 0]$  then
16:           $R_{temp}^+ \leftarrow \begin{cases} COVERLESS(R^-(t-1)) & \text{with prob } 0.5 \\ COVERMORE(R^+(t-1)) & \text{with prob } 0.5 \end{cases}$ 
17:        if  $[Score(R_{temp}^+, R^+(t-1)) < Score(R^+, R^-)]$  then  $(R^+, R^-) \leftarrow (R_{temp}^+, R^+(t-1))$ .
18:         $\alpha \leftarrow \min \left\{ 1, \exp \left( -\frac{Score(R_{temp}^+, R^+(t-1)) - Score(R^+(t-1), R^-(t-1))}{T(t)} \right) \right\}$ 
19:         $R^\pm(t) \leftarrow \begin{cases} R_{temp}^+ & \text{with prob } \alpha \\ R^\pm(t-1) & \text{with prob } 1 - \alpha \end{cases}$ 
20:       $t \leftarrow t + 1$ 
21:   return  $(R^+, R^-)$ 

```

---

The procedures *COVERMORE* and *COVERLESS* used in the algorithm are the same as in Wang et al. [26]:

- *COVERMORE* ( $R, p$ ) With probability  $p$ , add a random pattern to  $R$  from the corresponding pool. Else, evaluate the objective  $Score()$  for all neighboring solutions where a pattern is added to  $R$  and choose the one with the best score.
- *COVERLESS* ( $R, p$ ) With probability  $p$ , remove a random pattern from  $R$ . Else, evaluate the objective  $Score()$  for all neighboring solutions where a pattern is removed from  $R$  and choose the one with the best score.

## 4 RESULTS

In this section we present the comparison of SOAR's performance to that of BOA by Wang et al. [26] and random forest [5]. We use three data sets to illustrate the benefits of our algorithms, as well as its difficulties:

- (1) Synthetic data manually generated to enable complete control over actual positive and negative rule sets.
- (2) The Adult data set (Kohavi [17]) extracted from the 1994 Census Bureau database, which contains socioeconomic information on  $\sim 32K$  adults.
- (3) Car data from (Bohanec and Rajkovic [2]) that represents evaluation of 1728 cars based on their characteristics.

For comparison of algorithm performance, we split the data randomly into training and test sets, train each model on the same training set, and compare model predictions on the same test set. Because SOAR allows for ambiguous classification (AAN, AAP, PAN, PAP), we differentiate such *ambiguous* cases from those that are *truly misclassified*, i.e. predicted incorrectly, by our algorithm

(CFP, CFN). For classical performance comparison we also include a forced prediction. That is, in the event that SOAR predicts an observation to be actively ambiguous, it is assigned to the class that has the longest rule it agrees with (unless the lengths are the same, in which case it stays ambiguous).

### 4.1 Synthetic data

We simulate a data set of 1000 observations with 5 binary predictors ( $x_1, x_2, x_3, x_4, x_5$ ) and a single binary outcome. Because there are  $2^5 = 32$  possible combinations of predictors under this scheme, this naturally results in duplicate rows in the data matrix, as we may expect in real world applications when different observations share the same characteristics. The following rules determine the true classification of each observation:

$$\begin{aligned}
 R_{truth}^+ &= \{(x_1, 0) \wedge (x_2, 1), \\
 &\quad (x_1, 1) \wedge (x_2, 1) \wedge (x_3, 0), \\
 &\quad (x_2, 0) \wedge (x_3, 0) \wedge (x_5, 1)\} \\
 R_{truth}^- &= \{(x_1, 1) \wedge (x_3, 1), \\
 &\quad (x_1, 0) \wedge (x_2, 0) \wedge (x_4, 0), \\
 &\quad (x_1, 1) \wedge (x_2, 0) \wedge (x_3, 0)\},
 \end{aligned}$$

Among the 1000 observations, 500 are classified as positive and 490 are classified as negative. The intersection between these two classes (that is, observations that satisfy both positive and negative rules) is 59, and the remaining 69 observations are neither positive nor negative. We assign those that satisfy both positive and negative rules to a final positive class with probability 0.05, and those that satisfy neither to a final positive class with probability 0.5. Table 2 summarizes the data.

Table 2: Assignment of true classes for creation of synthetic data.

Initial class	Count	Final class
positive only	441	positive
negative only	431	negative
both positive and negative	59	5% positive, 95% negative
neither	69	50% positive, 50% negative

We randomly split the data into a training set of 800 observations and a test set of the remaining 200 observations. Regarding interpretability, the patterns produced by SOAR algorithm are:

$$\begin{aligned}
 R^+ &= \{(x_2, 1), (x_3, 0) \wedge (x_5, 1)\} \\
 R^- &= \{(x_1, 1) \wedge (x_3, 1), (x_2, 0) \wedge (x_5, 0), \\
 &\quad (x_1, 1) \wedge (x_2, 0) \wedge (x_4, 1) \wedge (x_5, 1), \\
 &\quad (x_1, 1) \wedge (x_2, 0) \wedge (x_4, 0) \wedge (x_5, 1)\}
 \end{aligned}$$

Table 3: True class and predicted class for all  $2^5$  possible predictor combinations.

x1	x2	x3	x4	x5	Truth	Prediction
0	0	0	0	0	(0,1)	(0,1)
0	0	0	0	1	(1,0)	(1,0)
0	0	0	1	0	(0,0)	(0,1)*
0	0	0	1	1	(1,0)	(1,0)
0	0	1	0	0	(0,1)	(0,1)
0	0	1	0	1	(0,1)	(0,0)*
0	0	1	1	0	(0,0)	(0,1)*
0	0	1	1	1	(0,0)	(0,0)
0	1	0	0	0	(1,0)	(1,0)
0	1	0	0	1	(1,0)	(1,0)
0	1	0	1	0	(1,0)	(1,0)
0	1	0	1	1	(1,0)	(1,0)
0	1	1	0	0	(1,0)	(1,0)
0	1	1	0	1	(1,0)	(1,0)
0	1	1	1	0	(1,0)	(1,0)
0	1	1	1	1	(1,0)	(1,0)
1	0	0	0	0	(0,1)	(0,1)
1	0	0	0	1	(1,1)	(1,1)
1	0	0	1	0	(0,1)	(0,1)
1	0	0	1	1	(1,1)	(1,1)
1	0	1	0	0	(0,1)	(0,1)
1	0	1	0	1	(0,1)	(0,1)
1	0	1	1	0	(0,1)	(0,1)
1	0	1	1	1	(0,1)	(0,1)
1	1	0	0	0	(1,0)	(1,0)
1	1	0	0	1	(1,0)	(1,0)
1	1	0	1	0	(1,0)	(1,0)
1	1	0	1	1	(1,0)	(1,0)
1	1	1	0	0	(0,1)	(1,1)*
1	1	1	0	1	(0,1)	(1,1)*
1	1	1	1	0	(0,1)	(1,1)*
1	1	1	1	1	(0,1)	(1,1)*

Table 3 illustrates that the positive and negative classes defined by these rules are close to those defined by  $R^+_{truth}$  and  $R^-_{truth}$ ; predictor combinations for which the two pairs of rule sets disagree are marked with (\*). Because both positive and negative rule sets provide a determination as to whether or not they were satisfied, we capture the determination of each rule set for observation  $\mathbf{x}$  as a pair  $(r^+, r^-)$ , where  $r^+$  is the outcome of the positive rule set, and  $r^-$  is the outcome of the negative rule set. For example, an observation  $\mathbf{x} = [0, 0, 1, 0, 1]$  with true class  $(0, 1)$  and predicted class  $(0, 0)$  can be interpreted as

$$\begin{aligned} R^+_{truth}(\mathbf{x}) &= 0, & R^-_{truth}(\mathbf{x}) &= 1 \\ R^+(\mathbf{x}) &= 0, & R^-(\mathbf{x}) &= 0. \end{aligned}$$

The comparison of all three algorithms is presented in Table 4. While the overall misclassification rate is high for unforced SOAR, no observations are truly misclassified; that is, observations for which the algorithm’s prediction fails to match the true label ultimately represent “ambiguous” cases. Once we force our algorithm to make a prediction (SOAR-forced), the true misclassification rate stays remarkably low and the overall misclassification rate is competitive with random forest and BOA.

Table 4: Comparison of performance of SOAR, BOA and random forest on synthetic data.

	SOAR	SOAR (forced)	BOA	RF
truly misclassified	0	0.005	0.05	0.05
ambiguous	0.25	0.07	0	0

## 4.2 Adult data

The Adult data set (Kohavi [17]) is a Census Bureau data on the income of  $\sim 32\text{K}$  adults. The data has 14 categorical socioeconomic predictors and 1 binary outcome, indicating whether a person makes more than  $\$50\text{K}$  a year. The rules for classification are not known. The positive support (that is, people who make more than  $\$50\text{K}$ ) is  $\sim 8\text{K}$  observations, and the negative support is  $\sim 24\text{K}$  observations. We split the data into a training set with 25K observations and test set with  $\sim 7.5\text{K}$  observations. The rules produced by SOAR are as follows:

$$\begin{aligned} R^+ &= \{(\text{marital\_status}, \text{Married-civ-spouse}), \\ &\quad (\text{education\_num}, 15), \\ &\quad (\text{education}, \text{Masters}) \wedge (\text{sex}, \text{Male}) \wedge (\text{capital\_loss}, 0) \\ &\quad \wedge (\text{native\_country}, \text{United-States}), \\ &\quad (\text{occupation}, \text{Exec-managerial}) \wedge (\text{education}, \text{Bachelors}) \\ &\quad \wedge (\text{sex}, \text{Male}) \wedge (\text{capital\_loss}, 0)\} \\ R^- &= \{(\text{education\_num}, 9), \\ &\quad (\text{relationship}, \text{Own-child}), \\ &\quad (\text{occupation}, \text{Other-service}), \\ &\quad (\text{capital\_gain}, 0) \wedge (\text{capital\_loss}, 0), \\ &\quad (\text{occupation}, \text{Adm-clerical}) \wedge (\text{sex}, \text{Female}) \\ &\quad \wedge (\text{capital\_gain}, 0)\} \end{aligned} \quad (4.1)$$

SOAR predicts that people who are married, have achieved higher levels of education, and men who work in managerial positions make more money, while people with fewer years of education, and those who work in administrative or service jobs make less. These rules are intuitive based on what we know of income factors. The comparison between the three algorithms is presented in Table 5.

Table 5: Comparison of performances of SOAR, BOA and random forest using Adult data.

	SOAR	SOAR (forced)	BOA	RF
truly misclassified	0.034	0.174	0.297	0.159
ambiguous	0.432	0.044	0	0

As before, SOAR’s misclassification rate is very low, and the performance of SOAR-forced is superior to BOA. To illustrate the strength of the algorithm we show examples of ambiguous—both passive and active—cases in Table 6.

Table 6: Examples of cases from Adult data labeled as *ambiguous* by SOAR algorithm.

	education	ed_num	marital_status	occupation	relationship	race	sex	capital_loss	capital_gain	>50K
Active ambiguous	Masters	14	Married-civ-spouse	Other-service	Husband	White	Male	0	0	0
	Bachelors	13	Never-married	Exec-managerial	Own-child	White	Male	0	0	0
	Masters	14	Never-married	Sales	Own-child	Black	Male	0	0	0
Passive ambiguous	Bachelors	13	Never-married	Exec-managerial	Other-relative	White	Female	0	1	0
	10th	6	Never-married	Adm-clerical	Not-in-family	White	Female	1	0	0
	Masters	14	Divorced	Exec-managerial	Not-in-family	White	Male	0	1	1

From these examples and the rules (4.1), we immediately see that rule-based algorithms in general and SOAR in particular can be used to assess bias inherent in this data set. The characteristic (sex, Male) is present in two patterns for positive classification, and the first example of passive ambiguous classification (a woman with a managerial position and college education) is not labeled as positive.

To illustrate our taxonomy Table 7 presents the comparative results between BOA and SOAR.

Table 7: Comparison between traditional prediction classification for BOA and the newly proposed SOAR taxonomy using Adult data.

	CTP	CTN	CFN	CFP	AAN	AAP	PAN	PAP
TP	433	0	21	0	0	1234	0	39
TN	0	3525	0	0	16	0	45	0
FN	0	0	137	0	0	1	0	11
FP	0	68	0	118	1864	0	49	0

We see that both algorithms are better at detecting observations in the positive class. There are only 149 FN-cases for BOA and 158 CFN-cases for SOAR. Observations in the negative class prove more problematic for BOA, which has more than 2000 FP-cases; comparatively, SOAR classifies the majority of those same cases as ambiguous.

Table 8 presents the most common patterns that appear in final positive and negative rule sets in 100 runs of the algorithm.

Table 8: Most common rules for Adult data.

Classification	Rule	Frequency
Positive	(marital_status, Married-civ-spouse)	42
	(education_num, 15)	38
	(education, Prof-school)	37
Negative	(relationship, Own-child)	54
	(occupation, Other-service)	42
	(capital_gain, 0) $\wedge$ (capital_loss, 0)	41

These common patterns are consistent with those observed in the rules (4.1).

### 4.3 Car evaluation data

Car data from (Bohanec and Rajkovic [2]) represents evaluation of 1728 cars according to 6 categorical variables:

- **buyingPrice**: buying price of a car
- **maintainPrice**: maintenance price
- **doors**: number of doors
- **persons**: number of passengers
- **lugBoot**: size of a trunk
- **safety**: safety level

The outcome variable indicates whether the car was assessed as *not acceptable*, *acceptable*, *good* or *very good*. For the purpose of binary classification, we encode the *unacceptable* category as 0 and the three remaining categories as 1. The positive support is 518 observations and negative support is 1210 observations. We randomly split the data into a training set of 1200 observations and a test set of 528 observations. SOAR produces the following rules:

$$R^+ = \{(\text{buyingPrice, low}) \wedge (\text{persons, 4}) \wedge (\text{safety, high}),$$

$$(\text{buyingPrice, med}) \wedge (\text{persons, 4}) \wedge (\text{safety, high}),$$

$$(\text{maintainPrice, low}) \wedge (\text{persons, 4}) \wedge (\text{safety, high}),$$

$$(\text{maintainPrice, med}) \wedge (\text{persons, 4}) \wedge (\text{safety, high}),$$

$$(\text{maintainPrice, low}) \wedge (\text{persons, more}) \wedge (\text{safety, high})\}$$

$$R^- = \{(\text{persons, 2}),$$

$$(\text{safety, low}),$$

$$(\text{buyingPrice, high}) \wedge (\text{maintainPrice, vhigh}),$$

$$(\text{buyingPrice, vhigh}) \wedge (\text{maintainPrice, vhigh}),$$

$$(\text{buyingPrice, vhigh}) \wedge (\text{maintainPrice, high}),$$

$$(\text{doors, 2}) \wedge (\text{lugBoot, small})\}$$

Based on these rules, cars that are safe, spacious, and inexpensive (either in terms of buying or maintaining) are classified as *acceptable*, while small or expensive cars are classified as *unacceptable*. The comparison of all three algorithms is presented in Table 9. Again, we see that observations truly misclassified by SOAR and

Table 9: Comparison of performances of SOAR, BOA and random forest using car data.

	SOAR	SOAR (forced)	BOA	RF
truly misclassified	0.006	0.009	0.153	0.013
ambiguous	0.242	0.235	0	0

SOAR-forced are few, while ambiguous cases account for most instances of overall misclassification. We present examples in Table 10 to illustrate how our algorithm manages to provide useful insights even when it is uncertain.

Table 10: Examples of cases from car data labeled as *ambiguous* by SOAR algorithm.

SOAR	buyingPrice	maintainPrice	doors	persons	lugBoot	safety	class
Active ambiguous	vhigh	low	2	4	small	high	1
	vhigh	low	2	more	small	high	0
	high	low	2	more	small	high	0
	low	low	2	4	small	high	1
Passive ambiguous	vhigh	med	2	4	big	med	1
	low	low	3	more	med	med	1
	low	med	5more	more	big	high	1
	high	low	4	more	small	med	0

We see that active ambiguous cases are those cars that appear small (2 doors, small trunk), but are able to fit 4 or more people. Meanwhile, passive ambiguous cases are cars with medium safety (note that all rules for positive classification include literal (safety, high)), but they otherwise have low buying and maintenance prices and enough space, all of which we previously observed as associated with positive classification.

## 5 CONCLUSION

We have presented a new rule-based algorithm, Simultaneous OR-of-ANDs Rules (SOAR), that encompasses the advantages of the BOA algorithm (Wang et al. [26]), while expanding upon it to address situations that benefit from development of explicit rules for each of the positive and negative classes. Owing the Bayesian framework, as with BOA, SOAR allows for *professional opinion* to be incorporated into the model as a prior and returns the final model in the form of two sets of rules for positive and negative classification. This approach allows for *uncertain* classification and thereby improves predictive performance when the classification is *certain*, naturally decreasing true misclassification rate. Moreover, having two sets of classification rules allows SOAR to model patterns in both positive and negative classes which we capture through a taxonomy of ambiguity; this taxonomy recognizes the inherent nuance of real world applications and enables articulation and characterization of such instances.

There are several directions that SOAR can go from here. Future work includes building a scalable version of the algorithm and incorporating continuous variables in the model. Moreover, this work may be extended to multi-class classification problems where a more general taxonomy of ambiguity must be devised and incorporated into the SOAR likelihood framework.

## REFERENCES

- [1] Richard Berk. 2012. *Criminal justice forecasts of risk: A machine learning approach*. Springer Science & Business Media.
- [2] Marko Bohanec and Vladislav Rajkovic. 1988. Knowledge acquisition and explanation for multi-attribute decision making. In *8th Intl Workshop on Expert Systems and their Applications*. 59–78.
- [3] Christian Borgelt. 2005. An Implementation of the FP-growth Algorithm. In *Proceedings of the 1st international workshop on open source data mining: frequent pattern mining implementations*. 1–5.
- [4] Endre Boros, Peter L Hammer, Toshihide Ibaraki, Alexander Kogan, Eddy Mayoraz, and Ilya Muchnik. 2000. An implementation of logical analysis of data. *IEEE Transactions on Knowledge and Data Engineering* 12, 2 (2000), 292–306.
- [5] Leo Breiman. 2001. Random forests. *Machine learning* 45, 1 (2001), 5–32.
- [6] William W Cohen. 1995. Fast effective rule induction. In *Machine learning proceedings 1995*. Elsevier, 115–123.
- [7] Council of European Union. 2016. Reg (EU) 2016/679 of the European Parliament and of the Council of 27 April 2016 on the protection of natural persons with regard to the processing of personal data and on the free movement of such data, and repealing Dir 95/46/EC (General Data Protection Regulation) 2016. <https://eur-lex.europa.eu/eli/reg/2016/679/oj/eng>.
- [8] Yves Crama, Peter L Hammer, and Toshihide Ibaraki. 1988. Cause-effect relationships and partially defined Boolean functions. *Annals of Operations Research* 16, 1 (1988), 299–325.
- [9] Finale Doshi-Velez and Been Kim. 2017. Towards a rigorous science of interpretable machine learning. *arXiv preprint arXiv:1702.08608* (2017).
- [10] Andre Estevea, Brett Kuprel, Roberto A Novoa, Justin Ko, Susan M Swetter, Helen M Blau, and Sebastian Thrun. 2017. Dermatologist-level classification of skin cancer with deep neural networks. *Nature* 542, 7639 (2017), 115–118.
- [11] Jerome H Friedman and Nicholas I Fisher. 1999. Bump hunting in high-dimensional data. *Statistics and Computing* 9, 2 (1999), 123–143.
- [12] Jerome H Friedman and Bogdan E Popescu. 2008. Predictive learning via rule ensembles. *The Annals of Applied Statistics* 2, 3 (2008), 916–954.
- [13] Siong Thy Goh and Cynthia Rudin. 2014. Box drawings for learning with imbalanced data. In *Proceedings of the 20th ACM SIGKDD international conference on Knowledge discovery and data mining*. 333–342.
- [14] Bryce Goodman and Seth Flaxman. 2017. European Union regulations on algorithmic decision-making and a “right to explanation”. *AI magazine* 38, 3 (2017), 50–57.
- [15] Riccardo Guidotti, Anna Monreale, Salvatore Ruggieri, Franco Turini, Fosca Giannotti, and Dino Pedreschi. 2018. A survey of methods for explaining black box models. *ACM computing surveys (CSUR)* 51, 5 (2018), 1–42.
- [16] Jiawei Han, Jian Pei, and Yiwen Yin. 2000. Mining frequent patterns without candidate generation. *ACM sigmod record* 29, 2 (2000), 1–12.
- [17] Ron Kohavi. 1996. Scaling up the accuracy of naive-bayes classifiers: A decision-tree hybrid. In *Kdd*, Vol. 96. 202–207.
- [18] Maxwell W Libbrecht and William Stafford Noble. 2015. Machine learning applications in genetics and genomics. *Nature Reviews Genetics* 16, 6 (2015), 321–332.
- [19] Christoph Molnar. 2020. *Interpretable Machine Learning*. Lulu. com.
- [20] W James Murdoch, Chandan Singh, Karl Kumbier, Reza Abbasi-Asl, and Bin Yu. 2019. Interpretable machine learning: definitions, methods, and applications. *arXiv preprint arXiv:1901.04592* (2019).
- [21] Cynthia Rudin. 2019. Stop explaining black box machine learning models for high stakes decisions and use interpretable models instead. *Nature Machine Intelligence* 1, 5 (2019), 206–215.
- [22] Dinggang Shen, Guorong Wu, Daoqiang Zhang, Kenji Suzuki, Fei Wang, and Pingkun Yan. 2015. Machine learning in medical imaging. *Comp. Med. Imag. and Graph.* 41 (2015), 1–2.
- [23] Peter JM Van Laarhoven and Emile HL Aarts. 1987. Simulated annealing. In *Simulated annealing: Theory and applications*. Springer, 7–15.
- [24] Kush R Varshney and Homa Alemzadeh. 2017. On the safety of machine learning: Cyber-physical systems, decision sciences, and data products. *Big data* 5, 3 (2017), 246–255.
- [25] Sandra Wachter, Brent Mittelstadt, and Luciano Floridi. 2017. Why a Right to Explanation of Automated Decision-Making Does Not Exist in the General Data Protection Regulation. *International Data Privacy Law* 7, 2 (06 2017), 76–99.
- [26] Tong Wang, Cynthia Rudin, Finale Doshi, Yimin Liu, Erica Klampfl, and Perry MacNeille. 2015. *Bayesian or’s of and’s for interpretable classification with application to context aware recommender systems*. Technical Report. MIT, Tech. Rep., 2015, submitted.