

Against Membership Inference Attack: Pruning is All You Need

Yijue Wang¹, Chenghong Wang², Zigeng Wang¹, Shanglin Zhou¹, Hang Liu³,
Jinbo Bi¹, Caiwen Ding¹, Sanguthevar Rajasekaran^{1*}

¹University of Connecticut

²Duke University

³Stevens Institute of Technology

{yijue.wang, zigeng.wang, shanglin.zhou, jinbo.bi, caiwen.ding, sanguthevar.rajasekaran}@uconn.edu,
cw374d@duke.edu,
hang.liu@stevens.edu

Abstract

The large model size, high computational operations, and vulnerability against membership inference attack (MIA) have impeded deep learning or deep neural networks (DNNs) popularity, especially on mobile devices. To address the challenge, we envision that the weight pruning technique will help DNNs against MIA while reducing model storage and computational operation. In this work, we propose a pruning algorithm, and we show that the proposed algorithm can find a subnetwork that can prevent privacy leakage from MIA and achieves competitive accuracy with the original DNNs. We also verify our theoretical insights with experiments. Our experimental results illustrate that the attack accuracy using model compression is up to 13.6% and 10% lower than that of the baseline and Min-Max game, accordingly.

1 Introduction

Advances in Machine Learning (ML) have enabled high accuracy in classifications, recommendations, and natural language processing, etc [He *et al.*, 2016; Vaswani *et al.*, 2017; Pan *et al.*, 2020]. The success of modern deep neural networks (DNNs) is mainly dependent on the availability of advanced computing power and a large number of data. Machine-Learning-As-A-Service (MLaaS) [Ribeiro *et al.*, 2015] providers such as Amazon [Kurniawan, 2018], Microsoft [Gollob, 2015], and Google [Ravulavaru, 2018] have taken advantage of the aforementioned two availabilities. By providing black-box interfaces, MLaaS allows individuals or groups to upload data easily, leverage powerful large-scale DNNs, and deploy analytic services via pay-as-you-go or subscriptions using personal computers or mobile devices [Truex *et al.*, 2019].

However, there are two main challenges. (i) MLaaS raises privacy concerns on sensitive data such as patient treatment records. Even though the DNN model structures are in black-box, MLaaS can leak sensitive information about training

data used to build back-end models. For instance, membership inference attack (MIA) [Shokri *et al.*, 2017] is one of the critical inference attacks in exploiting the aforementioned vulnerability. By using MIA, the adversary monitors the distinctive behavior of back-end models by repeating sophisticated designed inference requests to further exploit information about the training data. (ii) DNN models are evolving fast in order to satisfy the diverse characteristics of broad applications. As the layers of DNNs get deeper and the model size of DNNs gets larger, the large computational operations and model size introduce substantial data movements, limiting their ability to provide a user-friendly experience on mobile devices [Krizhevsky *et al.*, 2012; Hinton *et al.*, 2012].

There are several mechanisms have been developed to address the MIA challenges. Differential privacy (DP), a major privacy-preserving mechanism against general Inference attack, which is based on adding noises into gradients or objective function of the training model, has been applied in different machine learning models [Abadi *et al.*, 2016; Zhang *et al.*, 2019; Rahman *et al.*, 2018]. Although the robustness of DP has been proven, the utility cost (e.g., creating indistinguishable non-membership datasets, calculating the bound for the function sensitivity) of DP is hard to be limited as acceptable since it imposes a significant accuracy loss for protecting complicated models as well as on high dimensional data when noise is considerable.

Another defense mechanism is game theory, e.g., Min-Max game [Nasr *et al.*, 2018], which guarantees the information privacy. The maximum gain of inference model is considered as a new regularization called *adversarial regularization* and will be minimized with the training model loss. Unfortunately, the Min-Max game introduces extra computational operations in addition to the classifier training process.

Finally, yet importantly, neither DP nor Min-Max game addresses the second challenge, i.e., large computational operations and model size in DNNs.

In this paper, to simultaneously address the two challenges, we develop our pruning algorithm that is optimized for the dual objectives of privacy and efficiency by finding a subnetwork from a sufficiently over-parameterized random network. We present the main contributions of our work as follows:

- To the best of our knowledge, this work is the first attempt

*Corresponding Author

to simultaneously address the challenges of large model size, high computational cost, and vulnerability against MIA on DNNs. We jointly formulate weight pruning and MIA as MIA-Pruning and provide an analytic solution strategy for the problem.

- We show that our pruning algorithm can find a subnetwork that can prevent the privacy leakage from MIA and achieves competitive accuracy with the original DNNs.
- We show that our pruning algorithm performs better than baseline (without defense and pruning) and Min-Max game, i.e., further reduces attack accuracy. We also investigate the combination of weight pruning and Min-Max game and show that the combination will further enhance DNN model privacy.

Experimental results show that our MIA-Pruning can help against MIA while simultaneously achieving model storage and computational complexity reduction within a very small accuracy loss. Our proposed method significantly outperforms DP on MIA. Since weight pruning reduces the number of parameters, the proposed MIA-Pruning enables faster DNN computation than prior works.

2 Related Work

2.1 Weight Pruning

State-of-the-art DNNs contain multiple cascaded layers and at least millions of parameters (i.e., weights) for the entire model [He *et al.*, 2016; Vaswani *et al.*, 2017]. Prior works have focused on developing DNN weight pruning algorithms such as weight pruning [Zhang *et al.*, 2018; Frankle and Carbin, 2018; Zhou *et al.*, 2019; Ramanujan *et al.*, 2020] (i.e., removing weights with specific dimensions or with any desired weight matrix shapes) utilizing different regularization techniques to explore sparsity. Blalock [Blalock *et al.*, 2020] introduced ShrinkBench for standardized evaluations of pruning methods.

2.2 Defense Mechanism against MIA

One defense direction is using game theory to protect privacy [Nasr *et al.*, 2018; Alvim *et al.*, 2017; Shokri, 2015; Shokri *et al.*, 2012]. Most of the game theory-based mechanisms minimize the privacy loss against the most potent attacker by converting the utility function into the Min-Max optimization problem.

[Nasr *et al.*, 2018] proposed a Min-Max game mechanism and formulated the gain of MIA as a new regularization, which is maximized while the classifier’s loss is minimized. We use it as a comparison with our experimental results.

DP is another major defense mechanism against MIA. There are multiple DP-based defense mechanisms [Chaudhuri *et al.*, 2011; Abadi *et al.*, 2016; Iyengar *et al.*, 2019], by adding noises into gradients or the objective function of the training model. However, the existing mechanisms would impose a significant accuracy loss for protecting complicated models as well as on high dimensional data when the noise parameter ϵ is large.

There are some other defense directions. For example, the model stacking [Salem *et al.*, 2018] mechanism made a combination of multiple classifier results to prevent the attacker




Figure 1: Illustrative diagram of using weight pruning against MIA.

from inferring a single target classifier. MemGuard mechanism [Jia *et al.*, 2019] randomly added noise on the target classifier prediction.

The existing defenses have at least one of the limitations: 1) they have typical extra computations, such as extra weight storage and noise calculations. That means these mechanisms introduce extra computational operations in addition to the training approaches. 2) they achieve privacy protection with significant utility loss.

3 MIA-Pruning: Problem Statement

In this work, we investigate the following question: *Will an effective DNN weight pruning technique help against MIA while simultaneously achieving model storage and computational complexity reduction?*

3.1 Problem Formulation

MIA

For the target machine learning model, we consider the classification model in this work. Let f denotes the target classification model, x denotes a data point, and $f(x)$ denotes the output of f on data x . $f(x)$ is a one-hot vector of probabilities of x belonging to k classes. We consider the MIA problems in a black-box condition, which means the adversary can not access the classification model’s parameters but can only observe the input and output of the classification model. We assume that the adversary has access to some data records from the training set and the predictions from the black-box DNN target model. Based on the difference between the model’s prediction on the training dataset and the non-training dataset, the adversary can determine whether a data record belongs to the model’s training dataset or not. Figure 1 shows an illustrative diagram of using weight pruning against MIA in DNNs. We use f_A to denote the adversarial inference model $f_A : x \times y \times f(x) \rightarrow [0, 1]$. f_A takes the feature of the data x , the label of the data y , and the prediction of classification model $f(x)$ as inputs. And f_A outputs the probability of data (x, y) belonging to the training set D or the non-training set D' . The probability distributions of samples in D and D' are P_D and $P_{D'}$, respectively. The gain function of the inference

model f_A given the classification model f can be written as:

$$G_f(f_A) = \mathbb{E}_{(x,y) \sim P_D} [\log(f_A(x, y, f(x)))] + \mathbb{E}_{(x,y) \sim P_{D'}} [\log(1 - f_A(x, y, f(x)))] \quad (1)$$

The first expectation computes the inference model’s accuracy in predicting training data (members), and the second expectation computes the accuracy of the inference model on predicting non-training data (non-members). The underline probability P_D and $P_{D'}$ is normally not known. The empirical gain can be calculated by simply sampling data from the training set and validation set.

MIA-Pruning against MIA

The objective is to build a defense system against MIA by pruning the model weights so that the model predictions for the training dataset and non-training dataset are not distinguishable. In this case, it becomes more difficult for the adversary to determine where an observed data record belongs to. Finally, the risk of membership privacy loss is reduced. Ideally, the adversary can only make a determination by random guess. At the same time, the classification accuracy of the model will not be or slightly be affected. In other words, the utility cost of defense (e.g., classification accuracy loss) is negligible.

Formally, the problem can be formulated as:

$$\begin{aligned} \underset{\{\mathbf{W}_i\}, \{\mathbf{b}_i\}}{\operatorname{argmin}} \quad & \mathcal{L}(f(\{\mathbf{W}_i\}, \{\mathbf{b}_i\}; x), y) \\ \text{s.t.} \quad & \mathbf{W}_i \in \{\mathbf{W}_i | \operatorname{card}(\mathbf{W}_i) \leq n_i\} \\ & \{n_i\} = \underset{\{n_i\}}{\operatorname{argmin}} \max_{f_A} G_f(\{\mathbf{W}_i\}, \{\mathbf{b}_i\})(f_A) \end{aligned} \quad (2)$$

where $\{\mathbf{W}_i\}$ and $\{\mathbf{b}_i\}$ are the weights and biases of each layer, and $\mathcal{L}(f(\{\mathbf{W}_i\}, \{\mathbf{b}_i\}; x), y)$ is the loss of the classification model. $\operatorname{card}(\mathbf{W}_i)$ is the cardinality of weights in each layer, which returns the number of non-zero weights. n_i is the desired number of non-zero weights for each layer, which regularizes the strength of compression.

MIA-Pruning & Min-Max Game against MIA

For the further step, we consider the combination of weight pruning and Min-Max game [Nasr *et al.*, 2018] to strengthen the defense efficiency against MIA, and the optimization objective would become:

$$\begin{aligned} \underset{\{\mathbf{W}_i\}, \{\mathbf{b}_i\}}{\operatorname{argmin}} \quad & \mathcal{L}(f(\{\mathbf{W}_i\}, \{\mathbf{b}_i\}; x), y) \\ & + \gamma \max_{f_A} G_f(f_A(f(\{\mathbf{W}_i\}, \{\mathbf{b}_i\}; x), y)) \\ \text{s.t.} \quad & \mathbf{W}_i \in \{\mathbf{W}_i | \operatorname{card}(\mathbf{W}_i) \leq n_i\} \\ & \{n_i\} = \underset{\{n_i\}}{\operatorname{argmin}} \max_{f_A} G_f(\{\mathbf{W}_i\}, \{\mathbf{b}_i\})(f_A) \end{aligned} \quad (3)$$

where γ is the weight of the maximum gain of the inference model. The difference between Equation 2 and 3 is that the loss in 3 when updating the classification model also includes the maximum possible inference gain given the current classification model. The problem of 2 and 3 can be written as Equation 14 in Appendix Section 2.

4 MIA-Pruning: Methodology

4.1 Solution Strategy

To find the optimal compression ratio or n_i , we set different n_i in a range and choose n_i that can achieve the minimum $G_f(f_A^*)$. For the Min-Max game, the minimization and maximization problems need to be solved jointly to reach an equilibrium point. As shown in algorithm 1, for a fixed classification model f , we use a subset of training data and non-training data to train the inference model f_A to find the best attack to f . Then for the current f_A , we minimize the loss in Equation 2 and 3 to find the most defensive model f against f_A . Note that for MIA-Pruning, the for-loop to update f_A is not needed. For an arbitrary f_A , it is easy to optimize it empirically by Stochastic Gradient Descent (SGD). However, it is difficult to solve the optimization problem of f . We modified the Alternating Direction Method of Multipliers (ADMM) [Zhang *et al.*, 2018] to solve it, of which the details can be found in Appendix Section 3.

4.2 Theoretical Analysis

Pruning Convergence Analysis

We suppose the target network $f(x)$ as:

$$f(x) = \mathbf{W}_n^f \sigma(\mathbf{W}_{n-1}^f \dots (\sigma(\mathbf{W}_1^f x))) \quad (4)$$

and we define the original network $g(x)$ as:

$$g(x) = \mathbf{W}_{2n}^g \sigma(\mathbf{W}_{2n-1}^g \dots \sigma(\mathbf{W}_1^g(x))) \quad (5)$$

where $\mathbf{W}_i^f, \mathbf{W}_j^g$ is the randomized weight matrix at i -th layer of f and j -th layer of $g(x)$. And $\sigma(\cdot)$ is the activation function.

A pruned network $\hat{g}(x)$ can be presented as :

$$\hat{g}(x) = (\mathbf{P}_{2n} \odot \mathbf{W}_{2n}^g) \sigma(\mathbf{P}_{2n-1} \odot \mathbf{W}_{2n-1}^g) \dots \sigma(\mathbf{P}_1 \odot \mathbf{W}_1^g(x)) \quad (6)$$

where \mathbf{P}_i is the pruning matrix in i -th layer.

Theorem 1. *For every network f defined in Eq. 11 with depth l and $\forall i \in \{1, 2, \dots, n\}$. Consider g defined in Eq.12 is a randomly initialized neural network with $2n$ layers, and width $\operatorname{poly}(d, n, m, 1/\epsilon, \log 1/\delta)$, where d is input size, n is number of layers in f , m is the maximum number of neurons in a layer. The weight initialization distribution belongs to uniform distribution in range $[-1, 1]$. Then with probability at least $1 - \delta$ there is a weight-pruned subnetwork \hat{g} of g such that:*

$$\sup_{x \in \mathcal{X}, \|\mathbf{W}\| \leq 1} \|f(x) - \hat{g}(x)\| \leq \epsilon \quad (7)$$

The full proof of Theorem 1 is in Appendix Section 1. Using Theorem 1, we know that for every bounded distribution and every target network with bounded weights, there is a subnetwork with the competitive accuracy of the original sufficiently over-parameterized neural networks.

Inference Model’s Gain Function Analysis

According to [Nasr *et al.*, 2018], we rewrite the gain function of the inference model in the form of probability distribution:

$$G_f(f_A) = \int_{x,y} [P_D(x, y) p_f(f(x)) \log(f_A(x, y, f(x)))] + P_{D'}(x, y) p'_f(f(x)) \log(1 - f_A(x, y, f(x)))] dx dy \quad (8)$$

Algorithm 1 The Process of MIA-Pruning

```
1: for  $\{n_i\}$  in  $(\{n_{min}\}, \{n_{max}\})$  do
2:   for  $epoch$  in  $epochs$  do
3:     for  $t$  in  $iterations$  do
4:       Get a random mini-batch  $S \subset D$ .
5:       Get a random mini-batch  $S' \subset D'$ .
6:       Update  $f_A$  to minimize  $-G_f(f_A)$  using SGD.
7:     end for
8:     Get a random mini-batch  $S'' \subset D, S'' \neq S$ .
9:     Update  $\{\mathbf{W}_i^t\}, \{\mathbf{b}_i^t\}$  to minimize Loss in Equation 2
10:    Prune weight by update  $\{\mathbf{W}_i^t\}$  to  $\{P_i^t \odot \mathbf{W}_i^t\}$ 
11:  end for
12:  OUTPUT  $(\{\mathbf{W}_i\}, \{\mathbf{b}_i\}, G_f(f_A))$ .
13: end for
14: OUTPUT  $(\{\mathbf{W}_i^*\}, \{\mathbf{b}_i^*\}, G_f^*(f_A)) = \min(G_f(f_A))$ .
```

where D is the training set and D' is the non-training set. p_f and p'_f are the probability distribution of the classification model f 's output for training data and non-training data.

For a given classification model f and data sampled from a known probability distribution, the optimal determination solution for the inference model f_A is [Goodfellow *et al.*, 2014; Nasr *et al.*, 2018]:

$$f_A^*(x, y, f(x)) = \frac{p_f(f(x))}{p_f(f(x)) + p'_f(f(x'))} \quad (9)$$

Therefore, by substituting f_A^* in the Equation 1, the gain function of f_A^* can be written as:

$$\begin{aligned} G_f(f_A^*) &= \mathbb{E}_{(x,y) \sim P_D} \left[\log \left(\frac{p_f(f(x))}{p_f(f(x)) + p'_f(f(x'))} \right) \right] \\ &\quad + \mathbb{E}_{(x,y) \sim P_{D'}} \left[\log \left(1 - \frac{p_f(f(x))}{p_f(f(x)) + p'_f(f(x'))} \right) \right] \\ &= -\log(4) + 2 \cdot JS(p_f(f(x)) || p'_f(f(x))) \end{aligned} \quad (10)$$

Where $JS(p_f(f(x)) || p'_f(f(x)))$ is the Jensen–Shannon divergence between the two distributions. Since $JS(p_f(f(x)) || p'_f(f(x)))$ is always non-negative and equals 0 if and only if $p_f(f(x)) = p'_f(f(x'))$, the global minimum value that $G_f(f_A^*)$ can possibly have is $-\log(4)$ if and only if $p_f(f(x)) = p'_f(f(x'))$ [Goodfellow *et al.*, 2014]. This means that the prediction of classification model f for both the training set and non-training set has the same probability distribution. In this case, the classification model can be totally protected from MIA, the inference model can only flip a coin to make the determination with the possibility of 0.5. We use d to represent the Jensen–Shannon divergence $JS(p_f(f(x)) || p'_f(f(x)))$ between the probability distributions of f 's outputs for the training set and non-training set. The larger d is, the higher the maximum gain of the reference model is. In other words, the more vulnerable the classification model is. Thus, any methods that can smaller d can have a defending effect against MIA. Intuitively, weight pruning can prevent over-fitting. Thus it will have a smaller d .

	Baseline		MIA-Pruning		Min-Max Game	
	Testing accuracy	Attack accuracy	Testing accuracy	Attack accuracy	Testing accuracy	Attack accuracy
MNIST-LeNet-5	99.3%	67.00%	99.39%	53.41%	98.98%	56.00%
CIFAR-10-VGG16	91.28%	61.99%	91.38%	59.02%	90.97%	60.35%
CIFAR-10-MobileNetV2	90.09%	62.75%	86.14%	58.98%	89.71%	57.91%
CIFAR-100-VGG16	64.84%	67.628%	66.93%	58.61%	65.71%	68.59%
CIFAR-100-MobileNetV2	64.14%	66.15%	57.72%	62.67%	63.36%	62.61%
CIFAR-100-ResNet-18	73.45%	69.85%	74.10%	63.50%	69.05%	71.78%

Table 1: Comparison of classification accuracy and membership attack accuracy on different image datasets between model baseline, MIA-Pruning, and Min-Max Game.

5 Evaluation

In this section, we apply MIA-Pruning to different classification models with various DNN structures, mainly from two perspectives: the defense performance of our model and the computation cost benefit we obtain.

5.1 Classification Model

To evaluate our proposed method, we apply MIA-Pruning on different DNN models, including LeNet-5, VGG16, MobileNetV2, ResNet-18, on different datasets (e.g., MNIST, CIFAR-10, CIFAR-100, ImageNet). We use LeNet-5 on MNIST dataset, and VGG-16, MobileNetV2 and ResNet-18 to classify CIFAR-10 and CIFAR-100 dataset. We also use MobileNetV2 and ResNet-18 models on the ImageNet dataset to show the scalability of our proposed method.

We set the plain training of the classification model, i.e., without adversary training or MIA-Pruning, as our baseline. We compare the classification accuracy of the classification (target) model and the attack accuracy of the inference (adversary) model between MIA-Pruning, Min-Max Game, and baseline. We also compare MIA-Pruning with the popular method DP on CIFAR-10 dataset. We followed the same architecture with the four layers CNN classification model in [Rahman *et al.*, 2018] and compare our results with the reported results in [Rahman *et al.*, 2018]. For MNIST datasets, we use LeNet-5 as the classification model and implement DP with the noise parameter ϵ as 6.28. The detailed setting of training can be found in Appendix Section 4.

5.2 Inference Attack Model

To compare with the Min-Max game, we use the same neural network as the inference attack model as in [Nasr *et al.*, 2018] for all experiments except CIFAR-10-CNN in Table 2. For CIFAR-10-CNN in Table 2, the inference attack model is the same as in [Rahman *et al.*, 2018] (see Appendix Section 5).

5.3 Evaluation Results on MIA-Pruning MNIST, CIFAR-10 and CIFAR-100

We compare weight pruning (using MIA-Pruning) and Min-Max game to investigate if weight pruning can constrain the maximum gain G of the inference model, i.e., further reduce attack accuracy. We provide the attack accuracy and testing accuracy of baseline (without defense and pruning),

	DP		MIA-Pruning	
	Testing accuracy	Attack accuracy	Testing accuracy	Attack accuracy
CIFAR-10-CNN	68.10%	58.30%	75.46%	57.36%
MNIST-LeNet-5	96.64%	78.54%	99.30%	53.41%

Table 2: Comparison of classification accuracy and membership attack accuracy between DP and MIA-Pruning.

	Baseline		MIA-Pruning	
	Testing accuracy	Attack accuracy	Testing accuracy	Attack accuracy
ImageNet-MobileNetV2	71.88%	66.90%	68.77%	64.79%
ImageNet-ResNet-18	69.76%	66.20%	69.30%	61.27%

Table 3: Comparison of classification accuracy and membership attack accuracy on ImageNet between model baseline and MIA-Pruning.

MIA-Pruning, and the Min-Max game as shown in Table 1. On MNIST, experimental results demonstrate that for LeNet-5, the attack accuracy using MIA-Pruning is 13.6% lower than the attack accuracy of baseline and is 2.6% lower than the attack accuracy of the Min-Max game. From the comparison between DP and MIA-Pruning shown in Table 2, MIA-Pruning achieves 25.13% lower attack accuracy than DP and with 2.66% higher testing accuracy of the classification model.

On CIFAR-10, the experimental results demonstrate that for VGG16, the attack accuracy using MIA-Pruning is 3% lower than the baseline attack accuracy and is 1.34% lower than the attack accuracy of the Min-Max Game. On the other hand, for MobileNetV2, the attack accuracy using MIA-Pruning is 3.77% lower than the baseline attack accuracy and is close to Min-Max game. As shown in Table 2, on a four-layers CNN [Rahman *et al.*, 2018], MIA-Pruning has 1% lower attack accuracy than DP, while MIA-Pruning has 7.36% higher testing accuracy of the classification model than DP.

On CIFAR-100, the experimental results demonstrate that for VGG16, the attack accuracy using MIA-Pruning is 9.1% lower than the baseline attack accuracy and is approximately 10% lower than the Min-Max game. On the other hand, for MobileNetV2, the attack accuracy using MIA-Pruning is 3.48% lower than the baseline attack accuracy and is close to the Min-Max Game.

The results indicate that using weight pruning can help against MIA, and weight pruning is more effective than using Min-Max Game. On the other hand, weight pruning has significantly less utility cost than DP. And our experiment also shows that DP is hard to achieve privacy-preserving with negligible utility loss. Also, based on the experiment in [Rahman *et al.*, 2018], to achieve the same level of attack accuracy, the test accuracy under the DP method is under 70% in the best case, 25% in the worst case on CIFAR-10 by different noise parameter ϵ . In addition, weight pruning brings another benefit shown in Table 4, i.e., we achieve 15.78X model size reduction for LeNet-5 on MNIST, at least 10.06X model size




Figure 2: Upper row: the classification loss along with epochs during training classification model. Lower row: membership attack accuracy during training the inference model gain the trained classification model. Classification models baseline, MIA-Pruning, and Min-Max game are shown in (a-c) respectively.




Figure 3: Distribution of weights in VGG16 trained on CIFAR-10 for (a) baseline, (b) MIA-Pruning, (c) Min-Max Game, and (d) MIA-Pruning & Min-Max.

reduction for on CIFAR-10/CIFAR-100 among VGG16, MobileNetV2, and ResNet-18, which is extremely helpful for deploying DNNs on mobile devices. Figure 3 (a)-(c) show the weight distributions in different classification models from baseline, MIA-Pruning, and Min-Max game. We can observe that the weights after pruning are much less than the baseline model and Min-Max game model (both without pruning).

Next, we investigate classification loss of baseline (without pruning and defense), MIA-Pruning, and Min-Max Game. Taking CIFAR-10-VGG16 as an example, Figure 2 shows the classification loss of baseline, MIA-Pruning, and Min-Max Game, respectively, in the upper row. The classification loss of MIA-Pruning converges rapidly in less than 20 epochs. In addition, it has the highest final classification loss when the model is fully trained. In other words, MIA-Pruning prevents overfitting instead of reducing the classification loss on training data arbitrarily low. We train the membership inference model based on the predicted outputs of the well-trained classification model. We plot the testing accuracy of membership

inference attack during the inference model training process in the lower row in Figure 2. The adversary attack accuracy is measured by averaging the adversary’s correct determination percentage among all adversary determination for the observed data records [Nasr *et al.*, 2018].

Data	Model	Weights (#)	Weights after pruning (#)	Weights reduction ratio
MNIST	LeNet	60 K	3.80 K	15.78 ×
CIFAR-10/100	VGG16	13.83 M	1.00 M	13.84 ×
	ResNet-18	11.17 M	1.06 M	10.54 ×
	MobileNetV2	3.46 M	0.34 M	10.06 ×
ImageNet	ResNet-18	11.17 M	3.47 M	3.37 ×
	MobileNetV2	3.46 M	1.06 M	3.27 ×

Table 4: weight pruning ratios for different classification networks.

	MIA-Pruning		MIA-Pruning & Min-Max	
	Testing accuracy	Attack accuracy	Testing accuracy	Attack accuracy
CIFAR-10-VGG16	91.38%	59.02%	89.19%	54.67%
CIFAR-100-VGG16	66.93%	58.61%	54.71%	57.65%
MNIST-LeNet-5	99.39%	53.41%	99.03%	54.00%

Table 5: Comparison of classification accuracy and membership attack accuracy between MIA-Pruning and MIA-Pruning & Min-Max.

ImageNet

The experimental results for ImageNet are shown in Table 3, which demonstrates that for MobileNetV2, the attack accuracy using MIA-Pruning is 2.11% lower than the baseline, then, for ResNet-18, the attack accuracy using pruning is approximately 5% lower than the baseline. The weight reduction ratio is 3.37 × for ResNet-18 and 3.27 × for MobileNetV2 compare with the baseline weights.

5.4 Evaluation Results on MIA-Pruning & Min-Max

The experimental result for the MIA-Pruning & Min-Max is showed in Table 5. The experiment results demonstrate that for CIFAR-10-VGG16, the attack accuracy of Pruning & Min-Max is 54.67%, which is 3.03% lower than the attack accuracy of MIA-Pruning. And for CIFAR-100-VGG16, the attack accuracy of pruning & Min-Max is 57.65%, which is 1% lower than the attack accuracy of MIA-Pruning. For MNIST-LeNet-5, the attack accuracy of pruning & Min-Max is close to the attack accuracy of MIA-Pruning. Figure 3 (d) shows the distribution of weights in classification models from MIA-Pruning & Min-Max. We can also observe that after pruning, the weights are much less than the baseline model.

5.5 MIA-Pruning Analysis

In general, for the same type of model, the more overfitting the model is, the more vulnerable it is to MIA. The least generic the distribution of training data is, the more information it leaks. MIA-Pruning achieves parameter sparsity by pruning non-critical weights, thus can potentially reduce the overfitting caused by over parameterization. Taking CIFAR-10-VGG16 as an example, we compare the prediction on training data and non-training data between baseline, MIA-Pruning, and Min-Max Game. The baseline

	Training accuracy	Testing accuracy	Attack accuracy
Baseline	99.66%	91.28%	61.99%
MIA-Pruning	99.22%	91.38%	59.02%
Min-Max Game	99.18%	90.97%	60.35%
MIA-Pruning&Min-Max	92.86%	89.19%	54.67%

Table 6: Comparison of classification accuracy on training and testing set and membership attack accuracy between model baseline, MIA-Pruning, Min-Max Game, and MIA-Pruning & Min-Max.

predicts the highest probability for the correct class in the training data. In other words, it has the highest prediction certainty, or it fits the training data best. However, the baseline has significantly lower prediction certainty on the testing data. The difference of prediction between the training data and testing data can be learned by the inference model to distinguish the membership. Since models with pruning or/and Min-Max Game reduce overfitting, they have lower prediction certainty on the training data, but similar to the prediction certainty on the testing data. The detail of pruning rate settings is in Appendix Section 6.

To summarize the difference of prediction between training and non-training data quantitatively, we show the MIA accuracy along with the difference of classification accuracy between training and non-training data for each class in CIFAR-10 in Table 6. The larger the training-non-training accuracy gap is, the higher the membership attack accuracy is.

6 Conclusion

In this work, we jointly formulate weight pruning and MIA as MIA-Pruning and provide an algorithm to solve the problem. We theoretically analyze and conclude that our proposed algorithm can protect the information privacy from MIA and achieves competitive accuracy with the original DNNs. And we evaluate our method on LeNet-5, VGG16, MobileNetV2, ResNet-18 on different datasets including MNIST, CIFAR-10, CIFAR-100, and ImageNet. From experimental results, we see weight pruning can significantly reduce the information leakage from MIA.

Our proposed method outperforms DP on MIA. Compared with our MIA-Pruning, our MIA-Pruning & Min-Max game can achieve the lowest attack accuracy so that it maximally enhance DNN model privacy. Thanks to the hardware-friendly characteristic of weight pruning (reducing weight storage and computational operation), our proposed MIA-Pruning is very helpful for deploying DNNs on mobile devices. We hope our proposed method will shed some light on the increasing membership privacy concerns when applying DNNs on user-sensitive data such as business and medical datasets on mobile devices.

Acknowledgements

This work has been supported in part by the following NSF grants: 1743418 and 1843025. This work originated from the course project of CSE5095 Advances in Deep Learning taught by Prof. Caiwen Ding. We also thank Dan Guo for many helpful discussions.

References

- [Abadi *et al.*, 2016] Martin Abadi, Andy Chu, Ian Goodfellow, H Brendan McMahan, Ilya Mironov, Kunal Talwar, and Li Zhang. Deep learning with differential privacy. In *Proceedings of the 2016 ACM SIGSAC conference on computer and communications security*, 2016.
- [Alvim *et al.*, 2017] Mário S Alvim, Konstantinos Chatzikokolakis, Yusuke Kawamoto, and Catuscia Palamidessi. Information leakage games. In *International Conference on Decision and Game Theory for Security*, pages 437–457. Springer, 2017.
- [Blalock *et al.*, 2020] Davis Blalock, Jose Javier Gonzalez Ortiz, Jonathan Frankle, and John Guttag. What is the state of neural network pruning? *arXiv preprint arXiv:2003.03033*, 2020.
- [Boyd *et al.*, 2011] Stephen Boyd, Neal Parikh, Eric Chu, Borja Peleato, and Jonathan Eckstein. Distributed optimization and statistical learning via the alternating direction method of multipliers. *Foundations and Trends® in Machine learning*, 3(1):1–122, 2011.
- [Chaudhuri *et al.*, 2011] Kamalika Chaudhuri, Claire Monteleoni, and Anand D Sarwate. Differentially private empirical risk minimization. *Journal of Machine Learning Research*, 12(Mar):1069–1109, 2011.
- [Frankle and Carbin, 2018] Jonathan Frankle and Michael Carbin. The lottery ticket hypothesis: Finding sparse, trainable neural networks. *arXiv preprint arXiv:1803.03635*, 2018.
- [Gollob, 2015] David Gollob. *Microsoft Azure-Planning, Deploying, and Managing Your Data Center in the.* Springer-verlag Berlin And Hei, 2015.
- [Goodfellow *et al.*, 2014] Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *Advances in neural information processing systems*, pages 2672–2680, 2014.
- [He *et al.*, 2016] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 770–778, 2016.
- [Hinton *et al.*, 2012] Geoffrey Hinton, Li Deng, Dong Yu, George E Dahl, Abdel-rahman Mohamed, Navdeep Jaitly, Andrew Senior, Vincent Vanhoucke, Patrick Nguyen, Tara N Sainath, and Brian Kingsbury. Deep neural networks for acoustic modeling in speech recognition: The shared views of four research groups. *IEEE Signal Processing Magazine*, 2012.
- [Hong *et al.*, 2016] Mingyi Hong, Zhi-Quan Luo, and Meisam Razaviyayn. Convergence analysis of alternating direction method of multipliers for a family of nonconvex problems. *SIAM Journal on Optimization*, 26(1):337–364, 2016.
- [Iyengar *et al.*, 2019] Roger Iyengar, Joseph P Near, Dawn Song, Om Thakkar, Abhradeep Thakurta, and Lun Wang. Towards practical differentially private convex optimization. In *2019 IEEE Symposium on Security and Privacy (SP)*. IEEE, 2019.
- [Jia *et al.*, 2019] Jinyuan Jia, Ahmed Salem, Michael Backes, Yang Zhang, and Neil Zhenqiang Gong. Memguard: Defending against black-box membership inference attacks via adversarial examples. In *Proceedings of the 2019 ACM SIGSAC Conference on Computer and Communications Security*, 2019.
- [Krizhevsky *et al.*, 2012] Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. In *Advances in neural information processing systems*, 2012.
- [Kurniawan, 2018] Agus Kurniawan. *Learning AWS IoT: Effectively manage connected devices on the AWS cloud using services such as AWS Greengrass, AWS button, predictive analytics and machine learning.* Packt Publishing Ltd, 2018.
- [Liu *et al.*, 2018] Sijia Liu, Jie Chen, Pin-Yu Chen, and Alfred Hero. Zeroth-order online alternating direction method of multipliers: Convergence analysis and applications. In *International Conference on Artificial Intelligence and Statistics*, pages 288–297, 2018.
- [Lueker, 1998] George S Lueker. Exponentially small bounds on the expected optimum of the partition and subset sum problems. *Random Structures & Algorithms*, 12(1):51–62, 1998.
- [Nasr *et al.*, 2018] Milad Nasr, Reza Shokri, and Amir Houmansadr. Machine learning with membership privacy using adversarial regularization. In *Proceedings of the 2018 ACM SIGSAC Conference on Computer and Communications Security*, pages 634–646, 2018.
- [Ouyang *et al.*, 2013] Hua Ouyang, Niao He, Long Tran, and Alexander Gray. Stochastic alternating direction method of multipliers. In *International Conference on Machine Learning*, pages 80–88, 2013.
- [Pan *et al.*, 2020] Haihong Pan, Zaijun Pang, Yaowei Wang, Yijue Wang, and Lin Chen. A new image recognition and classification method combining transfer learning algorithm and mobilenet model for welding defects. *IEEE Access*, 2020.
- [Rahman *et al.*, 2018] Md Atiqur Rahman, Tanzila Rahman, Robert Laganière, Noman Mohammed, and Yang Wang. Membership inference attack against differentially private deep learning model. *Transactions on Data Privacy*, 11(1):61–79, 2018.
- [Ramanujan *et al.*, 2020] Vivek Ramanujan, Mitchell Wortsman, Aniruddha Kembhavi, Ali Farhadi, and Mohammad Rastegari. What’s hidden in a randomly weighted neural network? In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 11893–11902, 2020.
- [Ravulavaru, 2018] Arvind Ravulavaru. *Google Cloud AI Services Quick Start Guide: Build Intelligent Applications with Google Cloud AI Services.* Packt Publishing Ltd, 2018.
- [Ribeiro *et al.*, 2015] Mauro Ribeiro, Katarina Grolinger, and Miriam AM Capretz. Mlaas: Machine learning as a service. In *2015 IEEE 14th International Conference on Machine Learning and Applications (ICMLA)*, pages 896–902. IEEE, 2015.
- [Salem *et al.*, 2018] Ahmed Salem, Yang Zhang, Mathias Humbert, Pascal Berrang, Mario Fritz, and Michael Backes. MI-leaks: Model and data independent membership inference attacks and defenses on machine learning models. *arXiv preprint arXiv:1806.01246*, 2018.
- [Shokri *et al.*, 2012] Reza Shokri, George Theodorakopoulos, Carmela Troncoso, Jean-Pierre Hubaux, and Jean-Yves Le Boudec. Protecting location privacy: optimal strategy against localization attacks. In *Proceedings of the 2012 ACM conference on Computer and communications security*, 2012.
- [Shokri *et al.*, 2017] Reza Shokri, Marco Stronati, Congzheng Song, and Vitaly Shmatikov. Membership inference attacks against machine learning models. In *2017 IEEE Symposium on Security and Privacy (SP)*, pages 3–18. IEEE, 2017.
- [Shokri, 2015] Reza Shokri. Privacy games: Optimal user-centric data obfuscation. *Proceedings on Privacy Enhancing Technologies*, 2015.

[Truex et al., 2019] Stacey Truex, Ling Liu, Mehmet Emre Gursoy, Lei Yu, and Wenqi Wei. Demystifying membership inference attacks in machine learning as a service. *IEEE Transactions on Services Computing*, 2019.

[Vaswani et al., 2017] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in neural information processing systems*, 2017.

[Zhang et al., 2018] Tianyun Zhang, Shaokai Ye, Kaiqi Zhang, Jian Tang, Wujie Wen, Makan Fardad, and Yanzhi Wang. A systematic dnn weight pruning framework using alternating direction method of multipliers. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pages 184–199, 2018.

[Zhang et al., 2019] Xueru Zhang, Chunan Huang, Mingyan Liu, Anna Stefanopoulou, and Tulga Ersal. Predictive cruise control with private vehicle-to-vehicle communication for improving fuel consumption and emissions. *IEEE Communications Magazine*, 2019.

[Zhou et al., 2019] Hattie Zhou, Janice Lan, Rosanne Liu, and Jason Yosinski. Deconstructing lottery tickets: Zeros, signs, and the supermask. In *Advances in Neural Information Processing Systems*, pages 3597–3607, 2019.

A Appendix

In the appendix, we first introduce the unified problem reformulation of MIA-Pruning, then describe the solution strategy for weight pruning, namely ADMM. We also included the details of experimental settings: the training of classification model, the inference attack model, and the pruning rate.

A.1 SECTION 1: The Proof of Theorem 1

Preliminaries and notations

In this part, we introduce some notations we will use in the following analysis. We define the target network $f(x)$ as:

$$f(x) = W_n^f \sigma(W_{n-1}^f \dots (\sigma(W_1^f x))) \quad (11)$$

and we define the original network $g(x)$ as:

$$g(x) = W_{2n}^g \sigma(W_{2n-1}^g \dots \sigma(W_1^g(x))) \quad (12)$$

where W_i^f, W_j^g is the randomized weight matrix at i -th layer of f and j -th layer of $g(x)$. And $\sigma(\cdot)$ is the activation function.

A pruned network $\hat{g}(x)$ can be presented as :

$$\hat{g}(x) = (P_{2n} \odot W_{2n}^g) \sigma(P_{2n-1} \odot W_{2n-1}^g) \dots \sigma(P_1 \odot W_1^g x) \quad (13)$$

Where P_l is the pruning matrix in l -th layer.

we analysis the objective from simple to complex. We will start from a pruning simple linear function with one variable. Then we consider about pruning a simple ReLU network. Furthermore, we analysis the pruning from a neuron and a layer. Finally, we give the analysis of our main objective.

Analysis on Simple linear Network

In this case, $f(x) = w \cdot x$, and $g(x) = \left(\sum_{i=1}^d w_i\right) x$.

Theorem 2. Let W_1^*, \dots, W_n^* belongs to i.i.d. Uniform distribution over $[-1, 1]$, where $n \geq C \log \frac{2}{\delta}$, where $\delta \leq$

$\min\{1, \epsilon\}$. Then, with probability at least $1 - \delta$, we have

$$\begin{aligned} & \exists S \subset \{1, 2, \dots, n\}, \forall W \in [-0.5, 0.5], \\ & \text{s.t. } \left| W - \sum_{i \in S} W_i^* \right| \leq \epsilon \end{aligned} \quad (14)$$

Lueker et al.[Lueker, 1998] proposed this theorem and have gave a proof.

Analysis on Simple ReLU Networks

In this case, $f(x) = w \cdot x$, $g(x) = \mathbf{u}\sigma(\mathbf{w}^g x)$. because σ is ReLU activation function, we have $w = \sigma(w) - \sigma(-w)$. So that the a single ReLU neuron can be written as:

$$x^* \mapsto \sigma(wx) = \sigma(\sigma(wx) - \sigma(-wx)) \quad (15)$$

On the other hand, this neuron can be present by a width m two layer network with a pruning matrix p^* for the first layer as:

$$x^* \mapsto \mathbf{u}\sigma(\mathbf{p} \odot \mathbf{w}^g x) \quad (16)$$

we define $\mathbf{w}^+ = \max\{\mathbf{0}, \mathbf{w}\}$, $\mathbf{w}^- = \min\{\mathbf{0}, \mathbf{w}\}$, $\mathbf{w}^+ + \mathbf{w}^- = \mathbf{w}^g$. Combine Eq. 15 and 16 we have:

$$x^* \mapsto \mathbf{u}\sigma(\mathbf{p} \odot \mathbf{w}^+ x) - \sigma(\mathbf{p} \odot -\mathbf{w}^- x) \quad (17)$$

Base on Theorem 2, when $n \geq C \log 4/\epsilon$, there exist a pattern of \mathbf{w} , such that, with probability $1 - \epsilon/2$,

$$\forall w^f \in [0, 1], \exists p \in [0, 1]^n, \text{s.t. } |w^f - \mathbf{u}\sigma(\mathbf{p} \odot \mathbf{w}^+)| < \epsilon/2 \quad (18)$$

Similarly, we have \mathbf{w} , such that, with probability $1 - \epsilon/2$,

$$\forall w^f \in [0, 1], \exists p \in [0, 1]^n, \text{s.t. } |w^f - \mathbf{u}\sigma(\mathbf{p} \odot \mathbf{w}^-)| < \epsilon/2 \quad (19)$$

so Consider Eq.18 and 19, we have:

$$\begin{aligned} & \sup |w^f x - \mathbf{u}\sigma(\mathbf{p} \odot \mathbf{w} x)| \\ & \leq |\sigma(w^f)x - \sigma(-w^f)x - \mathbf{u}\sigma(\mathbf{p} \odot \mathbf{w}^+ x) - \mathbf{u}\sigma(\mathbf{p} \odot \mathbf{w}^- x)| \\ & \leq \sup |\sigma(w^f)x - \mathbf{u}\sigma(\mathbf{p} \odot \mathbf{w}^+ x)| + \\ & \sup |\sigma(w^f)x - \mathbf{u}\sigma(\mathbf{p} \odot \mathbf{w}^- x)| \\ & \leq \epsilon/2 + \epsilon/2 \\ & \leq \epsilon \end{aligned} \quad (20)$$

A.2 Analysis on a Neuron

In this case, $f(x) = \mathbf{w}^f \mathbf{x}$, $g(x) = \mathbf{u}\sigma(\mathbf{w} \mathbf{x})$ and $\hat{g}(x) = \mathbf{u}\sigma(\mathbf{p} \odot \mathbf{w} \mathbf{x})$

$$\begin{aligned} & \sup |\mathbf{w}^f \mathbf{x} - \mathbf{u}\sigma(\mathbf{p} \odot \mathbf{w} \mathbf{x})| \\ & \leq \sup \left| \sum_{i=1}^m (w_i^f x_i - \mathbf{u}_i \sigma(\mathbf{p}_i \odot \mathbf{w}_i x_i)) \right| \\ & \leq \sup \sum_{i=1}^m |w_i^f x_i - \mathbf{u}_i \sigma(\mathbf{p}_i \odot \mathbf{w}_i x_i)| \\ & \leq \sum_{i=1}^m \sup |w_i^f x_i - \mathbf{u}_i \sigma(\mathbf{p}_i \odot \mathbf{w}_i x_i)| \\ & \leq m \cdot \frac{\epsilon}{m} \\ & \leq \epsilon \end{aligned} \quad (21)$$

A.3 Analysis on a Layer

In this case, $f(x) = \mathbf{W}^f \mathbf{x}$, and $g(x) = \mathbf{u} \sigma(\mathbf{W}^g \mathbf{x})$, and $\hat{g}(x) = \mathbf{u} \sigma(\mathbf{p} \odot \mathbf{W}^g \mathbf{x})$

$$\begin{aligned}
& \sup \left| \mathbf{W}^f \mathbf{x} - \mathbf{u} \sigma(\mathbf{p} \odot \mathbf{W}^g \mathbf{x}) \right| \\
& \leq \sup \left| \sum_{j=1}^k \sum_{i=1}^m \left(w_{j,i}^f x_i - \mathbf{u}_i \sigma(\mathbf{p}_{j,i} \odot w_{j,i}^g x_i) \right) \right| \\
& \leq \sup \sum_{j=1}^k \sum_{i=1}^m \left| w_{j,i}^f x_i - \mathbf{u}_i \sigma(\mathbf{p}_{j,i} \odot w_{j,i}^g x_i) \right| \quad (22) \\
& \leq \sum_{j=1}^k \sum_{i=1}^m \sup \left| w_{j,i}^f x_i - \mathbf{u}_i \sigma(\mathbf{p}_{j,i} \odot w_{j,i}^g x_i) \right| \\
& \leq k \cdot m \cdot \frac{\epsilon}{mk} \\
& \leq \epsilon
\end{aligned}$$

A.4 The analysis in general

For general case, $f(x)$ is defined as Eq.11, $g(x)$ is defined as Eq.12. so with the probability over $1 - \epsilon$, we have:

$$\begin{aligned}
& \sup \|f(x) - \hat{g}(x)\| \\
& = \left\| \mathbf{W}_n \mathbf{x}_n - \mathbf{P}_{2n} \odot \mathbf{W}_{2n}^g \mathbf{x}_n^g \sigma(\mathbf{P}_{2n-1} \odot \mathbf{x}_{2n-1}^g) \right\| \\
& \leq \left\| \mathbf{W}_n \mathbf{x}_n - \mathbf{W}_n \mathbf{x}_n^g \right\| + \\
& \left\| \mathbf{W}_n \mathbf{x}_n^g - \mathbf{P}_{2n} \odot \mathbf{W}_{2n}^g \mathbf{x}_n^g \sigma(\mathbf{P}_{2n-1} \odot \mathbf{x}_{2n-1}^g) \right\| \quad (23) \\
& \leq \left\| \mathbf{x}_n - \mathbf{x}_n^g \right\| + \\
& \left\| \mathbf{W}_n \mathbf{x}_n^g - \mathbf{P}_{2n} \odot \mathbf{W}_{2n}^g \mathbf{x}_n^g \sigma(\mathbf{P}_{2n-1} \odot \mathbf{x}_{2n-1}^g) \right\| \\
& \leq \epsilon/2 + \epsilon/2 \\
& \leq \epsilon
\end{aligned}$$

A.5 SECTION 2: Unified Problem Reformulation of MIA-pruning

Comparing Equation 2 and 3 in the main text, the optimization problem of MIA-Pruning can be considered as a special case of MIA-Pruning+Min-Max where $\gamma = 0$. Since n_i ranges from 0 to 1 and has a relatively smaller search space, we obtain the optimal n_i by simply iterating different sets of n_i and choosing the smallest $G_f(f_A^*)$. Therefore, we can rewrite the problem in a unified form and in an equivalent form without constrains:

$$\begin{aligned}
& \min_{\{\mathbf{W}_i\}, \{\mathbf{b}_i\}} \mathcal{L}(f(\{\mathbf{W}_i\}, \{\mathbf{b}_i\}; x), y) \\
& + \gamma \max_{f_A} G_f(f_A(f(\{\mathbf{W}_i\}, \{\mathbf{b}_i\}; x), y)) + \sum_{i=1}^N g_i(\mathbf{W}_i) \quad (24)
\end{aligned}$$

where $g_i(\mathbf{W}_i)$ is a indicator function of the constrain $\text{card}(\mathbf{W}_i) \leq n_i$. If $\text{card}(\mathbf{W}_i) \leq n_i$ holds, $g_i(\mathbf{W}_i) = 0$, otherwise $g_i(\mathbf{W}_i) = +\infty$.

B SECTION 3: Solution Strategy: ADMM

ADMM-based DNN weight pruning: Considering an optimization problem $\min_{\mathbf{x}} f(\mathbf{x})$ with combinatorial constraints,

which is difficult to solve directly using optimization tools [Zhang *et al.*, 2018]. By using ADMM [Boyd *et al.*, 2011], the $\min_{\mathbf{x}} f(\mathbf{x})$ problem can be decomposed into two subproblems on \mathbf{x} and \mathbf{z} (auxiliary variable), i.e., the first subproblem derives \mathbf{x} given \mathbf{z} : $\min_{\mathbf{x}} f(\mathbf{x}) + q_1(\mathbf{x}|\mathbf{z})$; the second subproblem derives \mathbf{z} given \mathbf{x} : $\min_{\mathbf{z}} I(\mathbf{z}) + q_2(\mathbf{z}|\mathbf{x})$. Both q_1 and q_2 are quadratic functions. In such way, the two subproblems could be solved separately and iteratively until convergence. Originally, ADMM is used to accelerate the convergence of convex optimization problems and enable distributed optimization, where the optimality and fast convergence rate have been proven [Ouyang *et al.*, 2013; Boyd *et al.*, 2011]. One special property of ADMM is that it can effectively deal with a subset of combinatorial constraints and yields optimal (or at least high quality) solutions [Hong *et al.*, 2016; Liu *et al.*, 2018]. The related constraints in DNN weight pruning belong to this subset of combinatorial constraints. Therefore ADMM is applicable to DNN mode compression.

In order to solve the constrained optimization problem, we use ADMM method to decompose it into simpler subproblems. First we rewrite the format of ADMM [Zhang *et al.*, 2018]:

$$\begin{aligned}
& \underset{\{\mathbf{W}_i\}, \{\mathbf{b}_i\}}{\text{argmin}} \quad \mathcal{L}(f(\{\mathbf{W}_i\}, \{\mathbf{b}_i\}; x), y) \\
& + \gamma \max_{f_A} G_f(f_A(f(\{\mathbf{W}_i\}, \{\mathbf{b}_i\}; x), y)) \quad (25) \\
& + \sum_{i=1}^N g_i(\mathbf{Z}_i) \\
& \text{s.t.} \quad \mathbf{W}_i = \mathbf{Z}_i, i = 1, \dots, N
\end{aligned}$$

For simplicity, we denote the first two parts of the minimization objective in the above equation as $\mathcal{L}_s(\{\mathbf{W}_i\}, \{\mathbf{b}_i\})$. The augmented Lagrangian solution for the above problem can be written as:

$$\begin{aligned}
& L_\lambda(\{\mathbf{W}_i\}, \{\mathbf{b}_i\}, \{\mathbf{Z}_i\}, \{\mathbf{U}_i\}) \\
& = \mathcal{L}_s(\{\mathbf{W}_i\}, \{\mathbf{b}_i\}) + \sum_{i=1}^N g_i(\mathbf{Z}_i) \quad (26) \\
& + \sum_{i=1}^N \frac{\lambda_i}{2} \left\| \mathbf{W}_i - \mathbf{Z}_i + \mathbf{U}_i \right\|_F^2 + \sum_{i=1}^N \frac{\lambda_i}{2} \left\| \mathbf{U}_i \right\|_F^2
\end{aligned}$$

where $\mathbf{U}_i = (1/\lambda_i)\mathbf{\Lambda}_i$. $\mathbf{\Lambda}_i$ is the Lagrange dual variable, λ_i is penalty parameters, and $\|\cdot\|_F^2$ is the Frobenius norm.

The ADMM process updates the parameters repeatedly as follows:

$$\begin{aligned}
& \{\mathbf{W}_i^{k+1}, \mathbf{b}_i^{k+1}\} = \underset{\{\mathbf{W}_i\}, \{\mathbf{b}_i\}}{\text{argmin}} L_\lambda(\{\mathbf{W}_i\}, \{\mathbf{b}_i\}, \{\mathbf{Z}_i^k\}, \{\mathbf{U}_i^k\}) \\
& \{\mathbf{Z}_i^{k+1}\} = \underset{\{\mathbf{Z}_i\}}{\text{argmin}} L_\lambda(\{\mathbf{W}_i^{k+1}\}, \{\mathbf{b}_i^{k+1}\}, \{\mathbf{Z}_i\}, \{\mathbf{U}_i^k\}) \quad (27a)
\end{aligned}$$

$$\{\mathbf{Z}_i^{k+1}\} = \underset{\{\mathbf{Z}_i\}}{\text{argmin}} L_\lambda(\{\mathbf{W}_i^{k+1}\}, \{\mathbf{b}_i^{k+1}\}, \{\mathbf{Z}_i\}, \{\mathbf{U}_i^k\}) \quad (27b)$$

$$\mathbf{U}_i^{k+1} = \mathbf{U}_i^k + \mathbf{W}_i^{k+1} - \mathbf{Z}_i^{k+1} \quad (27c)$$

The sub-problem of updating $\{\mathbf{W}_i, \mathbf{b}_i\}$ in Equation 27a is easy to solve:

$$\begin{aligned} \mathbf{W}_i^{k+1} &= \frac{\partial \mathcal{L}(\{\mathbf{W}_i\}, \{\mathbf{b}_i\}) + G_f(f_A^*)}{\partial \mathbf{W}_i} + \lambda_i(\mathbf{W}_i - \mathbf{Z}_i + \mathbf{U}_i) \\ \mathbf{b}_i^{k+1} &= \frac{\partial \mathcal{L}(\{\mathbf{W}_i\}, \{\mathbf{b}_i\}) + G_f(f_A^*)}{\partial \mathbf{b}_i} \end{aligned} \quad (28)$$

Since the loss of the classifier $\mathcal{L}(\{\mathbf{W}_i\}, \{\mathbf{b}_i\})$ is differentiable and $G_f(f_A^*)$ is also differentiable with respect to its input $f(\{\mathbf{W}_i\}, \{\mathbf{b}_i\}; x)$, the above equation has analytical solution.

The sub-problem of optimization \mathbf{Z}_i can be written as

$$\min_{\{\mathbf{Z}_i\}} \sum_{i=1}^N g_i(\mathbf{Z}_i) + \sum_{i=1}^N \frac{\lambda_i}{2} \|\mathbf{W}_i - \mathbf{Z}_i + \mathbf{U}_i\|_F^2 \quad (29)$$

where $g_i(\cdot)$ is the indicator function of whether the number of non-zero \mathbf{Z}_i smaller than n_i . Intuitively, the optimal $\{\mathbf{Z}_i\}$ is a sparse approximation of $\mathbf{W}_i + \mathbf{U}_i$. According to [Zhang *et al.*, 2018], the optimal solution for the above equation can be obtained by keeping the largest n_i element of $\mathbf{W}_i^{k+1} + \mathbf{U}_i^k$ and set the rest of small values to zero.

C SECTION 4: Classification Model

When training the classification model, the batch size is set as 64, and the training epoch is 300. The optimizer is Adam, and the learning rate is 0.05. For the MIA-Pruning, we pre-train the classification model for 200 epochs and then we follow the MIA-Pruning process shown in Algorithm 1 in the main text.

D SECTION 5: Inference Attack Model

The inference attack model is composed of three fully-connected sub neural networks in a hierarchical structure. The prediction vector $f(x)$ and the targeted label y are fed into two sub-networks in the first level in parallel, and the processed representations of the two sub-networks are then concatenated and fed into the third sub-network on the second level to make the final prediction. The architectures of the two sub-networks for processing $f(x)$ and y are [100, 1024, 512, 64] and [100, 512, 64], respectively. The architecture of the third sub-network is [256, 64, 1]. We use ReLU as the activation function for the whole network. The weights are initialized following $\mathcal{N}(0, 0.01)$. We use Adam optimizer with the learning rate 0.001. For CIFAR-10-CNN in Table 2 in the main text, the inference attack model consists of one fully-connected layer, the same as in [Rahman *et al.*, 2018]. For the training of the inference model in the Min-Max game (line 3-6 in Algorithm 1 in the main text), we use half of the training set and half of the testing set of the classification model as D and D' . The batch size is 64, and we set *iterations* to make it goes through roughly one epoch of the training data for the inference model for each epoch in line 2 in Algorithm 1 in the main text. We train the inference model using Adam optimizer with the learning rate as 0.00001. After training of the final classification model,

we retrain the inference model for 100 epochs using another D and D' sampled differently from the classification model’s training and validation set.

E SECTION 6: Pruning Rate in Experiment

In our experiment, we rank the weights based on the magnitude and prune a certain percentage of the smallest weights per layer by the following rules: 1) in the first layer, we prune 30%-40% 2) for the rest of the layers, we increase the percentage value from 50%-95%, depend on the depths and the structures of different DNN models. For example, on LeNet-5 model, the pruning rate for each layer is 40%, 90%, 93.75%, 93.75%, 93.75%. We also show the total prune amount and rate in table 4 in the main text.

F SECTION 7: Extra Experiment results

To summarize the difference of prediction between training and non-training data quantitatively, we plot the MIA accuracy along with the difference of classification accuracy between training and non-training data for each class in CIFAR-10 in Figure 4. We name such difference as training/non-training accuracy gap. As shown in Figure 4, there is a correlation between the train/non-training accuracy gap and the attack accuracy. The larger the training-non-training accuracy gap is, the higher the membership attack accuracy is. Among all the four methods, MIA-Pruning & Min-Max achieves the smallest train-test accuracy gap and lowest membership inference attack accuracy, therefore providing the highest privacy enhancement.




Figure 4: Attack accuracy versus training/non-training accuracy gap of VGG16 on CIFAR-10, which is defined as the difference of classification accuracy between training and non-training data.