

[[2, 10], [6, 6]]-equitable partitions of the 12-cube*

Denis S. Krotov

Abstract

We describe the computer-aided classification of equitable partitions of the 12-cube with quotient matrix $[[2, 10], [6, 6]]$, or, equivalently, simple orthogonal arrays $OA(1536, 12, 2, 7)$, or order-7 correlation-immune Boolean functions in 12 variables with 1536 ones (which completes the classification of unbalanced order-7 correlation-immune Boolean functions in 12 variables). We find that there are 103 equivalence classes of the considered objects, and there are only two almost- $OA(1536, 12, 2, 8)$ among them.

1 Introduction

The main result of the current work is completing the classification of unbalanced order-7 correlation-immune Boolean functions in 12 variables (equivalently, equitable 2-partitions of the 12-cube with asymmetric quotient matrix having an eigenvalue -4). We solve the case of functions with 1536 ones, finding 103 equivalence classes, while the functions with 1024 ones and with 1792 ones from the considered family were characterized in [9] (16 equivalence classes and 2 equivalence classes, respectively). Computationally, the classification considered in the current paper is harder than in [9]; it requires the subdivision of the classified family into three subfamilies, each of which is solved with a special modification of the algorithm, and still spends almost thirty CPU years. The classification [9] of functions with 1024 ones was much more easy and straightforward because of smaller number of ones, while the 1792-ones case was solved using the Fourier analysis, which required more analytical than computational work (the crucial fact for the success of the Fourier-based classification was that the average density $1792/2^{12} = 9/16$ of ones of the function was not a multiple of $1/8$, which is not true for the 1536-ones case).

The n -cube is a graph Q_n on the set $\{0, 1\}^n$ of binary n -tuples, where two n -tuples are adjacent if and only if they differ in exactly one position. A partition (C_0, C_1) of the vertex set of Q_n into two cells is called an *equitable 2-partition* (of Q_n) with *quotient* 2×2 matrix $S = (S_{ij})$ if for all $i, j \in \{0, 1\}$ any vertex of C_i has exactly S_{ij} neighbors in C_j . A (Boolean) function $f : \{0, 1\}^n \rightarrow \{0, 1\}$ is called *unbalanced* if the number of its ones is different from 0, 2^{n-1} , and 2^n . It is called *t -th order correlation immune* if the number of ones (equivalently, zeros) $(x_1, \dots, x_n) : f(x_1, \dots, x_n) = 1$ is statistically independent on the values of any t arguments. Fon-Der-Flaass [1] proved that the correlation-immunity order of an unbalanced Boolean function in n variables cannot exceed $2n/3 - 1$; moreover, any unbalanced Boolean function f of correlation-immunity order $2n/3 - 1$

*The work was funded by the Russian Science Foundation under grant 18-11-00136

corresponds to an equitable 2-partition of the n -cube Q_n with quotient matrix $[[a, b], [c, d]]$, where $a + b = c + d = n$, $a - c = -n/3$, and the number of ones of f is $2^n c / (b + c)$. Nowadays, there are three known families of quotient matrices corresponding to such functions: $[[0, 3T], [T, 2T]]$, $[[T, 5T], [3T, 3T]]$ (found in [11]), $[[3T, 9T], [7T, 5T]]$ (found in [3]). For each of the matrices $[[0, 3], [1, 2]]$, $[[1, 5], [3, 3]]$, and $[[0, 6], [2, 4]]$, a function is unique up to equivalence. Kirienko [7] found that there are exactly 2 inequivalent unbalanced Boolean functions in 9 variables attaining the bound on the order of correlation immunity (the corresponding quotient matrix is $[[0, 9], [3, 6]]$). Fon-Der-Flaass started the investigation of equitable 2-partitions of Q_{12} attaining the correlation-immunity bound: in [3], it was shown that equitable partitions with quotient matrix $[[1, 11], [5, 7]]$ do not exist, while equitable partitions with quotient matrix $[[3, 9], [7, 5]]$ were built. In [9], combining the theoretical and computational approaches equitable partitions with quotient matrices $[[0, 12], [4, 8]]$ and $[[3, 9], [7, 5]]$ were classified up to equivalence. The current work is aimed on the remaining case $[[2, 10], [6, 6]]$. This case is interesting

Throughout this paper, we use the notation $S = [[S_{++}, S_{+-}], [S_{-+}, S_{--}]] = [[2, 10], [6, 6]]$ and the term S -partition in the meaning “equitable partition of the 12-cube with quotient matrix S ”.

2 Classification

The general classification approach we use is similar to the one used in [8] for $[[0, 13], [3, 10]]$ -partitions of Q_{13} , which, in its turn, is a development of the algorithm used in [9] for $[[0, 12], [4, 8]]$ -partitions of Q_{12} . The description of the algorithm (in particular, the definition of local partitions) in the following two subsections slightly differs from that in [8] because we now have no zeros in the quotient. However, the main difference and originality of the current search is described in Subsection 2.3, where the class of all $[[2, 10], [6, 6]]$ -partitions is divided into three subclasses, according to containing special configurations in the partition. As shown preliminary experiments, without this subdivision, the classification would hardly be possible with modern computational possibilities.

Our goal is to classify the $[[2, 10], [6, 6]]$ -partitions of Q_{12} up to equivalence, so the definition of the equivalence plays a key role. Two subsets C and C' of $\{0, 1\}^n$ are *equivalent* if there is an automorphism π of the graph Q_n such that $\pi(C) = C'$. Two 2-partitions (C_+, C_-) and (C'_+, C'_-) of $\{0, 1\}^n$ are *equivalent* if C_+ is equivalent to C'_+ . (In this paper, we compare only equitable 2-partitions with the same asymmetric quotient matrix, so the first cell of one partition cannot be equivalent to the second cell of the other). An *automorphism* of a subset C of $\{0, 1\}^n$ (and of the partition $(C, \{0, 1\}^n \setminus C)$) is an automorphism π of Q_n such that $\pi(C) = C$. The set $\text{Aut}(C)$ of all automorphisms of C forms a group with respect to the composition, the *automorphism group* of C . The number of 2-partitions equivalent to a given 2-partition (C_+, C_-) is calculated as $|\text{Aut}(\{0, 1\}^n)| / |\text{Aut}(C_+)|$, where $\text{Aut}(\{0, 1\}^n)$ is the set of automorphisms of Q_n , $|\text{Aut}(\{0, 1\}^n)| = 2^n \cdot n!$.

2.1 Local partitions

For classification by exhaustive search, we use an approach based on the local properties of the equitable partitions. Say that the pair of disjoint sets P_+ , P_- of vertices of Q_{12} is an (r_0, r_1) -local partition (sometimes, we will omit the parameters (r_0, r_1)) if

- (I) $P_+ \cup P_-$ are the all words starting with 0 and having weight at most r_0 or starting with 1 and having weight at most r_1 ;
- (II) P_+ contains the all-zero word $\bar{0}$;
- (III) P_- contains 100000000000;
- (IV) the neighborhood of every vertex $\bar{v} = (v_1, \dots, v_{12})$ of weight less than r_{v_1} satisfies the local condition from the definition of an equitable partition with quotient matrix $[[2, 10], [6, 6]]$ (that is, if $\bar{v} \in P_+$ then \bar{v} has 2 neighbors in P_+ and 6 neighbors in P_- . if $\bar{v} \in P_-$ then the neighborhood has exactly 6 elements in P_+ and 6 in P_-);
- (V) Every vertex from P_+ has at most 2 neighbors in P_+ .

Two (r_0, r_1) -local partitions (P_+, P_-) and (P'_+, P'_-) are *equivalent* ((r_0, r_1) -equivalent) if there is a permutation of coordinates that fixes the first coordinate and sends P_+ to P'_+ .

By an r -local partition, we mean an (r, r) -local partition, but the equivalence for this notion is counted differently: Two r -local partitions (P_+, P_-) and (P'_+, P'_-) are *equivalent* (r -equivalent) if there is a permutation of coordinates that sends P_+ to P'_+ . So, equivalent (r, r) -local partitions are necessarily r -equivalent (equivalent as r -local partitions), but not vice versa.

The general approach is to classify all inequivalent (r_0, r_1) -local partitions subsequently for (r_0, r_1) equal $(2, 2)$, $(2, 3)$, $(3, 3)$, $(3, 4)$, $(4, 4)$, $(12, 12)$, where $(12, 12)$ corresponds to the complete equitable partitions. In an obvious way, every equitable partition (C, \bar{C}) such that $\bar{0} \in C$ includes a $(4, 4)$ -local partition $(P_+^{(4,4)}, P_-^{(4,4)})$, $P_+^{(4,4)} \subset C$ and $P_-^{(4,4)} \subset \bar{C}$, every $(4, 4)$ -local partition $(P_+^{(4,4)}, P_-^{(4,4)})$ includes a $(3, 4)$ -local partition $(P_+^{(3,4)}, P_-^{(3,4)})$, $P_+^{(3,4)} \subseteq P_+^{(4,4)}$ and $P_-^{(3,4)} \subseteq P_-^{(4,4)}$, and so on. So, the strategy is to reconstruct, in all possible ways, a (r_0, r_1) -local partition from each of the inequivalent $(r_0 - 1, r_1)$ -local or $(r_0, r_1 - 1)$ -local partitions, and then to choose and keep only inequivalent solutions, one representative for each equivalence class found. The details of the reconstruction are described in the next subsection (except the reconstruction from $(4, 4)$ to $(12, 12)$, which is straightforward from the correlation immunity), followed by Section 2.3, where we discuss how to reduce the amount of computations for the concrete quotient matrix $[[2, 12], [6, 6]]$.

2.2 A reconstruction step

Assume that we have a $(r_0 - 1, r_1)$ -local partition (P_+, P_-) (the case $(r_0, r_1 - 1)$ is considered similarly). To find all possible (r_0, r_1) -local partitions (R_+, R_-) that include it, we construct the following instance of the exact cover problem.

- Among all words \bar{x} of weight r_0 and starting from 0, we choose only those whose inclusion in the first cell does not contradict (V), for \bar{x} itself and for all its neighbors. Call them *candidates* (for the inclusion in $R_+ \setminus P_+$).
- Next, for each words \bar{v} of weight $r_0 - 1$ and starting from 0, we count the number $\alpha_{\bar{v}}$ of its neighbors to add to the first cell for (IV) to be satisfied. If $\bar{v} \in P_i$, $i \in \{+, -\}$, then $\alpha_{\bar{v}} = S_{i+} - \beta_{\bar{v}}$, where $\beta_{\bar{v}}$ is the number of neighbors of \bar{v} that are already in P_+ .
- We construct a 0, 1-matrix $M = (m_{\bar{x}, \bar{v}})$ whose rows are indexed by candidates, columns are indexed by the words of weight $r_0 - 1$ starting from 0, and $m_{\bar{x}, \bar{v}} = 1$ if and only if \bar{x}, \bar{v} are neighbors.
- Now, finding (r_0, r_1) -local continuation of (P_+, P_-) is equivalent to finding a set of rows of M whose sum is the row $(\alpha_{\bar{v}})$. This is an instance of the so-called exact multiple cover problem (multiple, because the coefficients $\alpha_{\bar{v}}$ can be larger than 1), and can be solved with an appropriate software; we use `libexact` [5].
- For each exact cover found, we form R_+ by adding the indices of the chosen rows to P_+ , while R_- is found as the complement of R_+ .

An important step, traditionally called the *isomorph rejection*, is choosing nonequivalent representatives from the set of all found solutions, intermediate or final. A standard technique to deal with equivalence, see [4, Sect. 3.3], is to represent sets (in our case, R_+) by graphs and use a software [10] recognizing the isomorphism of graphs. At this point, it is possible to make some partial *validation* of the intermediate results by double-counting the total number of found continuations (R_+, R_-) of (P_+, P_-) with the help of the orbit-stabilizer theorem, see [4, Sect. 10.2] for the general strategy. Here, we do not stop on details of the isomorph rejection and the validation, because they are the same as in [8], and focus on the improvements specific for the current parameters of equitable partitions.

2.3 How to reduce the amount of computation

In the case when $r_0 = r_1$, it is sufficient to continue calculation for a representative of every equivalence class of r -local partitions, $r := r_0 = r_1$ (we apply this strategy for $r = 2$). However, the choice of the representative becomes important if we want to make the experiment repeatable with the same intermediate numerical results: for different representatives of the same equivalence class E of r -local partitions, the number of $(r, r+1)$ -local continuations can be different, but it is the same for equivalent (r, r) -local partitions. So, for the subdivision $\{E_1, \dots, E_s\}$ of E into (r, r) -equivalence classes, we need to choose one (r, r) -equivalence class explicitly. For this reason, we require that the representative chosen for further calculation must have the minimum number of inequivalent $(r, r+1)$ -local continuations. If, with this condition, there is still more than one candidate (r, r) -equivalence class, then we choose the one with the minimum number of inequivalent $(r+1, r+1)$ -local continuations, then $(r+1, r+2)$, and so on. This approach implies that we produce some redundant computation (to make the choice, we need to find the $(r, r+1)$ -local continuations for each subclass E_1, \dots, E_s , and sometimes need to find the $(r+1, r+1)$ -local

continuations for more than one of them, while only one of them is used for the classification), but makes the choice explicit and the experiment completely repeatable. It reduces the total number of calculations when s is large (up to 10); we essentially use this approach in Section 2.4.

The general algorithm described above works faster than the similar the algorithm based on r -local partitions only, but still very heavy for the considered parameters, without taking into account the specific properties of the classified partitions. To make the classification doable, we distinguish the following subfamilies of the family of all $[[2, 10], [6, 6]]$ -equitable partitions of the 12-cube.

We say that a $[[2, 10], [6, 6]]$ -equitable (local) partition (C_+, C_-) of Q_{12} is *square* if there are four vertices of C_+ that induce a square subgraph of Q_{12} (for square local partitions, we additionally require one of these vertices to be the all-zero word). A $[[2, 10], [6, 6]]$ -equitable (local) partition (C_+, C_-) is *square-free* if there are no four vertices of C_+ inducing a square subgraph of Q_{12} .

We say that a $[[2, 10], [6, 6]]$ -equitable partition (C_+, C_-) of Q_{12} is *heavy* (*light*) if there is (there is no) a subgraph of Q_{12} isomorphic to the cube Q_3 and having at least 5 five vertices from C_+ .

The classification is divided into the following three stages; each stage is considered in a separate subsection below. At stage one, we classify the square partitions. Stage two deals with heavy partitions, and its main result is that all heavy $[[2, 10], [6, 6]]$ -equitable partitions of Q_{12} are square. Stage three is the classification of the square-free partitions; by the results of the second stage they are all light.

2.4 The square partitions

Up to equivalence, any square S -partition or square local partition contains the four words $\bar{0} = 0\dots000$, $\bar{e}_{12} = 0\dots001$, $\bar{e}_{11} = 0\dots010$, $\bar{e}_{11} + \bar{e}_{12} = 0\dots011$ in its first cell.

Lemma 1. *There are 66462606 2-local partitions (C_+, C_-) with $\bar{0}$, \bar{e}_{12} , \bar{e}_{11} , $\bar{e}_{11} + \bar{e}_{12} \in C_+$, which are partitioned into 60 2-equivalence classes or 286 $(2, 2)$ -equivalence classes.*

Proof. Assume that we have a 2-local partition (C_+, C_-) with $\bar{0}$, \bar{e}_{12} , \bar{e}_{11} , $\bar{e}_{11} + \bar{e}_{12} \in C_+$. Every weight-2 word from C_+ is adjacent to exactly two words from $\bar{e}_1, \dots, \bar{e}_{10}$. On the other hand, every word from $\bar{e}_1, \dots, \bar{e}_{10}$ has exactly 5 weight-2 neighbors in C_+ (totally $S_{-,+} = 6$ neighbors in C_+ , but one of them is $\bar{0}$). Clearly, this incidence structure corresponds to a 5-regular graph on the 10 vertices $\bar{e}_1, \dots, \bar{e}_{10}$. It is easy to see that this correspondence with the class of 5-regular graphs of order 10 is one-to-one; moreover, two graphs are isomorphic if and only if the corresponding 2-local partitions are equivalent. The number of 5-regular graphs on 10 labelled vertices is 66462606, see <http://oeis.org/A059441>, and the number of their isomorphism classes is 60, see <http://oeis.org/A006821>. The number of $(2, 2)$ -equivalence classes is counted computationally; it equals the number of vertex orbits summed over the 60 non-isomorphic 5-regular graphs of order 10 (equivalently, the number of non-isomorphic 5-regular graphs of order 10 with one marked vertex, which corresponds to the first coordinate of the $(2, 2)$ -local partition). \square

Next, realizing the strategy described in Section 2.3, we choose 60 representatives of $(2, 2)$ -local partitions, and for each of them find all non-equivalent $(2, 3)$ -local, $(3, 3)$ -local, $(3, 4)$ -local, $(4, 4)$ -local, and finally S -partitions. The local partitions that continue the chosen 60 representatives will be called *leading*, in contrast to the local partitions that continue the rest $286 - 60$ $(2, 2)$ -equivalence classes. Up to equivalence, we have the following numbers of square partitions:

- there are 37141023 (few CPU days) square $(2, 3)$ -local partitions, 4979729 of them are leading;
- there are 659276500 square $(3, 3)$ -local partitions, 94275707 (736 CPU days) of them are leading; there are 65945212 3-local partitions (comparing 94275707 and 65945212, we see that applying the strategy described in Section 2.3 can reduce the number of further calculation by factor about 1.4; it was decided not to implement this improvement);
- there are 16535880038 (1795 CPU days) leading square $(3, 4)$ -local partitions;
- there are 3111 square $(4, 4)$ -local partitions, 667 (2322 CPU days) of them are leading; there are 429 square 4-local partitions, and all of them continue to S -partitions;
- there are 77 square S -partitions.

2.5 The heavy partitions

Define the $(1, 2)$ -local partition (B_+, B_-) where $B_+ = \{\bar{e}_1 + \bar{e}_2, \bar{e}_2, \bar{0}, \bar{e}_3, \bar{e}_3 + \bar{e}_1, \bar{e}_1 + \bar{e}_4, \bar{e}_1 + \bar{e}_5, \bar{e}_1 + \bar{e}_6\}$.

Lemma 2. *Every heavy S -partition is equivalent to a partition continuing the $(1, 2)$ -local partition (B_+, B_-) .*

Proof. (i) It is easy to observe that if C is a vertex set of Q_3 of cardinality at least 5 and such that the induced subgraph has no vertices of degree more than two, then C induces either a 5-path or a 6-cycle, being equivalent to either

$$\{110, 010, 000, 001, 101\} \quad \text{or} \quad \{110, 010, 000, 001, 101, 111\},$$

respectively.

(ii) Let (C_+, C_-) be a heavy S -partition. Without loss of generality, According to the definition of heavy S -partition, we can assume without loss of generality that the 8 vertices ending by 9 zeros include at least 5 vertices from C_+ . From (i) we see that these vertices are 110 000000000, 010 000000000, 000 000000000, 001 000000000, 101 000000000, and may be 111 000000000. It remains to note that the first cell of the corresponding $(1, 2)$ -local partition contains the first 5 of these vertices and 3 more neighbors of 100000000000, which are 100100000000, 100010000000, and 100001000000, up to coordinate permutation. \square

In contrast to the other subcases, in this section we choose the $(1, 3)$ -local partitions for the next step of the classification instead of $(2, 2)$ -local partitions. Up to equivalence, we have the following number of partitions containing $\bar{e}_1 + \bar{e}_2, \bar{e}_2, \bar{0}, \bar{e}_3, \bar{e}_3 + \bar{e}_1$:

- there are 178 (2, 2)-local partitions (2-local partitions);
- there are 953730 (1 CPU minute) (2, 3)-local partitions;
- there are 815364 (30 CPU days) (3, 3)-local partitions (3-local partitions); up to this step, all local partitions are square-free;
- there are 2325257827 (3, 4)-local partitions, 560234770 (14 CPU days) of them are square-free;
- there are 54 (4, 4)-local partitions (4-local partitions), all of them continue to S -partitions, 0 (7 CPU days) of them are square-free;
- there are 17 heavy S -partitions, none of them is square-free (17 CPU days).

Remark 1. In the considered case, the r -equivalence coincides with the (r, r) -equivalence because the first coordinate is special and cannot be permuted with any other.

Finally, we have established the following fact, which essentially simplifies the next-section classification of the square-free S -partitions.

Lemma 3. *All square-free S -partitions are light.*

Remark 2. To validate Lemma 3, it was sufficient to consider only square-free partitions. The numbers of partitions without the square-free condition provided above are based on early computations, which occur to be redundant. The CPU time was not kept; it is essentially smaller than that for the step in the previous section, and it is surely possible to save some time if consider only light square partitions in Section 2.4. In any case, the largest part of computation is described in the next section.

2.6 The square-free partitions

Lemma 4. *Every square-free S -partition is equivalent to a partition containing $\bar{e}_1 + \bar{e}_2$, \bar{e}_2 , $\bar{0}$, \bar{e}_3 , and $\bar{e}_3 + \bar{e}_4$, in its first cell C_+ .*

Proof. Without loss of generality, we can assume that $\bar{0}$ belongs to C_+ , and its two neighbors in C_+ are \bar{e}_2 and \bar{e}_3 . The word $\bar{e}_2 + \bar{e}_3$ is not in C_0 because the partition is square-free. Hence, the second C_+ -neighbor of \bar{e}_2 is $\bar{e}_i + \bar{e}_2$, where $i \neq 2, 3$. We can assume $i = 1$. Similarly, the second C_+ -neighbor of \bar{e}_2 is $\bar{e}_3 + \bar{e}_j$, where j is not 2 or 3. Additionally, j is not 1, because the partition is not light otherwise, contradicting Lemma 3. So, we can assume $j = 4$. \square

Based on the lemma above, we will search for only local partitions having $\bar{e}_1 + \bar{e}_2$, \bar{e}_2 , $\bar{0}$, \bar{e}_3 , and $\bar{e}_3 + \bar{e}_4$, in the first cell. Among such partitions,

- there are 1786 equivalence classes of (2, 2)-local partitions, 1010 equivalence classes of 2-local partitions.

Realizing the strategy described in Section 2.3, we can choose 1010 representatives of (2, 2)-local partitions, and for each of them find all non-equivalent (2, 3)-local, (3, 3)-local, (3, 4)-local, (4, 4)-local, and finally S -partitions. The local partitions that continue the chosen 1010 representatives are called *leading*. Up to equivalence, we have the following numbers of square-free partitions:

- there are 226841305 (few CPU days) square-free (2, 3)-local partitions, 77868835 of them are light, 38039061 of them are leading;
- there are 166399852 light square-free (3, 3)-local partitions, 96211116 (1500 CPU days) of them are leading; there are 83210833 3-local partitions (again, comparing 96211116 and 83210833, we find unreasonable applying the strategy of Section 2.3 for $r = 3$);
- there are 23752571733 light square-free (3, 4)-local partitions 14937782031 of them (2328 CPU days) are leading;
- there are 923 light square-free (4, 4)-local partitions, 663 (1306 CPU days) of them are leading; there are 490 light square-free 4-local partitions, 312 of them are completable to square-free S -partitions (the other are also completable to S -partitions, but with squares);
- there are 26 square-free S -partitions.

3 Results and properties

As we see in Sections 2.4–2.6, there are 103 nonequivalent $[[2, 10], [6, 6]]$ -partitions, 77 of them have squares in the first cell, while the remaining 26 are square-free. In this section, we discuss properties of the found equitable partitions.

3.1 Cycle length

The first cell of a $[[2, 10], [6, 6]]$ -partition induce a disjoint union of cycles in Q_n . These cycles can be of different lengths, the possible values are 4, 8, 10, 12, 16, 18, 20, 24, 28, 30, 32, 36, 40, 44, 48, 52, 60, 88, 120. The following partitions have only one cycle length:

#1: 4^{384} (i.e., 384 cycles of length 4);
 #101, #102, #103: 8^{192} ; #91, #93, #94, #95: 24^{64} ;
 #78, #79, #80, #81, #82, #83, #84, #85, #86, #87, #90, #92: 48^{32} .

The other partitions without a square in the first cell:

#88, #89, #96, #97, #99, #100: $8^{64}16^{64}$; #98: $8^{64}32^{32}$.

Only one partition has more than five different cycle lengths:

#60: $4^{32}18^820^{32}30^836^460^4$.

Two partitions have cycles of the maximum length:

#69, #71: $4^{64}40^8120^8$.

Note that the cycle formula does not reflect other parameters such as the number of cycles that are not translations of each other, the number of different directions in a cycle, the diameter of a cycle; these parameters can vary over partitions with the same cycle formula.

3.2 Automorphisms

The order of the automorphism group of a partition from the considered class can possess the values 8 (#64, #65), 16, 32, 64, 128, 160 (#69, #71), 256, 384 (#19), 512, 640 (#73, #74), 768 (#95), 1024, 2048, 2560 (#33), 3072, 4096, 8192 (#15, #102), 12288 (#103), 16384 (#8, #12), 24576 (#101), 32768 (#3), 983040 (#1). The number of translational automorphisms (i.e., the number of

periods \bar{x} : $C_+ + \bar{x} = C_+$) can be 4, 8, 16, 32 (#2, #12, #13, #15, #28), 64 (#3, #8, #101), 128 (#1). The only partitions that have odd-weight (with odd, 5 or 7, number of ones) periods are #41, #43, #74. The cell C_+ is partitioned into orbits under the action of $\text{Aut}(C_+)$; the following partitions have small number of the orbits: #1, #101 (1 orbit), #16, #95, #103 (2 orbits), #3, #8, #12, #32, #88, #102 (3 orbits), #15, #20, #28, #30, #33, #96, #97 (4 orbits). A notable partition is #95: the first cell is divided into only two orbits, while the induced cycles are of length 24.

3.3 Good orthogonal arrays and Fourier coefficients

A multiset C of tuples from $\{0, 1\}^n$ is called a *binary orthogonal array* of strength t , $\text{OA}(|C|, n, 2, t)$, if every $(n - t)$ -subcube of Q_n has exactly $|C|/2^t$ elements of C , taking into account the multiplicities. If there are no elements of multiplicity more than one (i.e., C can be treated as an ordinary set), the orthogonal array is called *simple*. In other words, a simple $\text{OA}(M, n, 2, t)$ is a subset of $\{0, 1\}^n$ of size M whose characteristic function is correlation immune of order t . In particular, $[[2, 10], [6, 6]]$ -partitions correspond to simple $\text{OA}(1536, 12, 2, 7)$. By the bound in [6] (see [1] for the simple case), an array of cardinality less than 2^{n-1} has strength at most $2n/3 - 1$ (for $n = 12$, at most 7). So, among orthogonal arrays of strength 7 and size less than 2048, there are no orthogonal arrays of strength 8. It is natural to ask which of them better approximate orthogonal arrays of strength 8. We will say that C is an *almost orthogonal array* of strength $t + 1$, $\text{OA}(|C|, n, 2, t+)$, if it is $\text{OA}(|C|, n, 2, t)$ and every $(n - t - 1)$ -subcube of Q_n has exactly $|C|/2^{t+1} - 1$, $|C|/2^{t+1}$, or $|C|/2^{t+1} + 1$ elements of C . From [9], we know that there are two simple $\text{OA}(1792, 12, 2, 7)$ and both of them are $\text{OA}(1792, 12, 2, 7+)$. From current computations, we find that there are 103 simple $\text{OA}(1536, 12, 2, 7)$ and only two of them, #81 and #82 (with 32 cycles of length 48), are $\text{OA}(1536, 12, 2, 7+)$. Also, from data in [9], we find that among the 16 $\text{OA}(1024, 12, 2, 7)$, there is only one $\text{OA}(1024, 12, 2, 7+)$, number 16.

The Fourier decomposition of a real-valued function $f : \{0, 1\}^n \rightarrow \mathbb{R}$ is the representation in the form

$$f(\bar{x}) = \sum_{\bar{y} \in \{0, 1\}^n} \hat{f}(\bar{y})(-1)^{\bar{y} \cdot \bar{x}},$$

where $\bar{y} \cdot \bar{x}$ is the *inner product* defined as $(y_1, \dots, y_n) \cdot (x_1, \dots, x_n) = y_1x_1 + \dots + y_nx_n$, and $\hat{f}(\bar{y})$ are the *Fourier coefficients* defined uniquely for each f (indeed, the functions $\chi_{\bar{y}}(\bar{x}) = (-1)^{\bar{y} \cdot \bar{x}}$, $\bar{y} \in \{0, 1\}^n$, form an orthogonal basis of the space of all real-valued functions on $\{0, 1\}^n$). The function \hat{f} is called the *Fourier transform* of f . For an equitable S -partition (C_+, C_-) , it is convenient to consider the Fourier transform \hat{f}_{C_+, C_-} of

$$f_{C_+, C_-}(\bar{x}) = \begin{cases} S_{+-} & \text{if } \bar{x} \in C_+ \\ -S_{-+} & \text{if } \bar{x} \in C_- \end{cases}.$$

It is known that

- (a) $\hat{f}_{C_+, C_-}(\bar{y}) = 0$ unless \bar{y} has exactly $(b + c)/2$ ones;

(b) if \bar{y} has exactly $(b+c)/2$ ones, then

$$\hat{f}_{C_+, C_-}(\bar{y}) = 2^{(S_{+-} + S_{-+})/2 - n} \sum_{\bar{x} \perp \bar{y}} f_{C_+, C_-}(\bar{x}),$$

where $\bar{x} \perp \bar{y}$ means that \bar{x} and \bar{y} have no ones in the same position;

(c) in particular, every Fourier coefficient is a multiple of $2^{(S_{+-} + S_{-+})/2 - n} (S_{+-} + S_{-+})$;

(d) $\sum_{\bar{y} \in \{0,1\}^n} (\hat{f}_{C_+, C_-}(\bar{y}))^2 = S_{+-} S_{-+}$.

It follows from (c) and (d) that the Fourier transform of every $[[2, 10], [6, 6]]$ -partition is integer and the sum of the squares of all coefficients is 60. In fact, the possible values of coefficients are $0, \pm 1, \pm 2$. It can be seen from (b) that the partitions with all Fourier coefficients in $\{0, 1, -1\}$ (60 non-zero coefficients in total) correspond to OA(1536, 12, 2, 7+) (equivalence classes #81 and #82); i.e., for these partitions, every 4-subcube has 11, 12, or 13 elements of the first cell. There are four inequivalent partitions with the Fourier coefficients in $\{0, 2, -2\}$ (15 non-zero coefficients), #1, #3, #8, and #101; for these partitions, every 4-subcube has 10, 12, or 14 elements of the first cell. For the partitions from the other 98 equivalence classes, each value from 10 to 14 is realized in some 4-subcube.

3.4 Known constructions

The partitions #1, #3, #15, and #103 (cycle formulas $4^{384}, 4^{256}8^{64}, 4^{128}8^{128}, 8^{192}$, respectively) are obtained from the unique $[[1, 5], [3, 3]]$ -partition (P_+, P_-) by the constructions

$$C_i = \{(\bar{x}, \bar{y}) \mid \bar{x} + \bar{y} \in P_i\},$$

where the addition is coordinatewise over \mathbb{Z}_2 for #1, by pairs of coordinates over \mathbb{Z}_4 for #103 (binary pairs are treated as elements of \mathbb{Z}_4 , via the map $00 \rightarrow 0, 01 \rightarrow 1, 11 \rightarrow 2, 10 \rightarrow 3$), and of mixed $\mathbb{Z}_2\mathbb{Z}_4$ type for #3 and #15 (one or two pairs of coordinates are treated as elements of \mathbb{Z}_4 , while the remaining 4 or 2 coordinates are treated as elements of \mathbb{Z}_2).

The next construction is described here without some technical details, which can be found in [2] and [12]. $[[2, 10], [6, 6]]$ -partitions can be constructed in the following way. At first, we take a $[[2, 1], [3, 0]]$ -partition (A_+, A_-) , say $A_- = \{000, 111\}$; note that A_+ can be partitioned into 3 edges of the 3-cube. Defining $B_+ = \{(\bar{x}, \bar{y}) \mid \bar{x} + \bar{y} \in A_+\}$ (with the coordinatewise binary addition), we get a $[[4, 2], [6, 0]]$ -partition (B_+, B_-) , where B_+ can be partitioned into twelve quadruples Q_1, \dots, Q_{12} inducing 2-subcubes of the 6-cube. The next step is a special case of the construction in [2, Sect. 3], with the additional possibility to switch some subsets observed in [12]. Applying the doubling construction again results in a $[[8, 4], [12, 0]]$ -partition (C_+, C_-) , where C_+ can be split into C'_+ and C''_+ to form a $[[2, 6, 4], [6, 2, 4], [6, 6, 0]]$ -partition (C'_+, C''_+, C_-) . There are many ways to split: each set $\{(\bar{x}, \bar{y}) \mid \bar{x} + \bar{y} \in Q_i\}$ is divided into two subsets Q'_i and Q''_i according to the formula in [2], but, as noted in [12], for each i we are free to choose which of Q'_i, Q''_i is included in C'_+ and which in C''_+ . So, we can get 2^{12} different $[[2, 6, 4], [6, 2, 4], [6, 6, 0]]$ -partitions (C'_+, C''_+, C_-) . It is straightforward from the quotient matrix that for each of them, $(C'_+, C''_+ \cup$

C_-) is a $[[2, 10], [6, 6]]$ -partition. In such a way, we get 8 equivalence classes of $[[2, 10], [6, 6]]$ -partitions, #1, #2, #3, #5, #7, #8, #16, and #101. With some accuracy, this switching approach can be combined with varying the addition as in the previous paragraph, but this possibility was not yet developed.

For #1, #73 (cycle formula $4^{64}20^{16}60^{16}$), #74 ($4^{64}10^{16}20^830^{16}60^8$), the first cell of a partition can be obtained as the projection (puncturing) of the first cell of the unique $[[0, 13], [3, 10]]$ -partition (the construction is given in [2], the uniqueness is established in [8]) in one of the directions (one direction corresponds to #1, six directions to #73, and six to #74).

A List of partitions

Below, we list representatives of all 103 equivalence classes of equitable $[[2, 10], [6, 6]]$ -partitions. It would take unreasonably much space to list each partition completely. We use some easy-to-recover form, representing each partition (C_+ , C_-) by the characteristic function χ_{C_+} of the first cell, restricted by the weight-4 words only. The values of this function on the words of weight 3 (similarly, weight 2, weight 1, and 0) can be easily reconstructed by the following rule: if a weight-3 words has at most 2 weight-4 neighbors in C_+ , then it belongs to C_+ , otherwise it is in C_- . The values on each word x of weight $w = 5$ (then, 6, 7, ..., 12) can be found using the correlation immunity of χ_{C_+} : the number of ones in the set $\{y \mid y \preceq x\}$ is $\frac{6}{10+6} \cdot 2^w$. The list of values on the 495 weight-4 words, listed in the lexicographic ordering 000000001111, 000000010111, ..., 111100000000, is represented in the hexadecimal form, each symbol corresponding to 4 binary values, except the first symbol of the sequence, which corresponds to 3 binary values (note that the first value can be 0, representatives No 75, 76, 77).

The representatives listed below are lexicographically ordered in the following manner: for each partition, we order the first cell lexicographically, forming a tuple from 1536 words; then, such lists are compared in the lexicographical way. Each equivalence class is represented by the lexicographically first partition, and all 103 representatives of different classes are ordered as well. In particular, the first 77 contain 0...0, 0...01, 0...010, 0...011, forming a square, and the last 26, square-free, contain 0...0, 0...01, 0...010, 0...0101, 0...01010. Note that the lexicographic order between functions on the whole 12-cube is not kept after restricting by the weight-4 words only; that is why the list of sequences below does not look ordered.

1. 7321c79e3c79e384ce1ffe00000000061ffe0000000007099cc3200001f807f00810e670c30e670c20600001f807f00810e670c30e670c207099cc321819
2. 7321c79e3c79e384ce1ffe00000000061ffe00000000070aad45200001f807f00810d568a30e670c20600001f807f00810e670c30d568a2070aad4521819
3. 7321c79e3c79e384ce1ffe00000000061ffe00000000070e670c200001f807f0081099cc330e670c20600001f807f00810e670c3099cc32070e670c21819
4. 7321c79e3c79e384ce1ffe00000000061ffe00000000070e670c200001f807f00810aad4530d568a20600001f807f00810d568a30aad452070e670c21819
5. 7321c79e3c79e384ce1ffe00000000061f801f800000830aad452007e00007f00050d568a30e670c20600001f807f00810e670c30d568a20b0aad4521419
6. 7321c79e3c79e384ce1ffe00000000061f801f800000830aad452007e00007

- f00050e670c30d568a20600001f807f00810d568a30e670c20b0aad4521419
7. 7321c79e3c79e384ce1f801f800000821f801f800000830aad452007e00007f00050d568a30e670c20a007e00007f00050e670c30d568a20b0aad4521415
 8. 7321c79e3c79e384ce1f801f800000821f801f800000830e670c2007e00007f0005099cc330e670c20a007e00007f00050e670c3099cc320b0e670c21415
 9. 7321c79e3c79e384ce1f801f800000821f801f800000830e670c2007e00007f00050aad4530d568a20a007e00007f00050d568a30aad4520b0e670c21415
 10. 7321c79e3c79e384ce1f801f800000821f8000007f00030aad452007e1f800000850d568a30e670c20a007e00007f00050e670c30d568a20d0aad4521215
 11. 7321c79e3c79e384ce1f801f800000821f8000007f00030aad452007e1f800000850e670c30d568a20a007e00007f00050d568a30e670c20d0aad4521215
 12. 7321c79e3c79e384ce1f801f800000821f8000007f00030e670c2007e1f800000850e670c3099cc320a007e00007f0005099cc330e670c20d0e670c21215
 13. 7321c79e3c79e3fc001f801099c000821f801f800000e10e641c2007e0000613385f800c330e6700782007e00007f00610e642c3099cc300f0e6700b8416
 14. 7321c79e3c79e3fc001f801099c000821f8000007f00610e641c2007e1f800000e10e642c3099cc300e007e0000613385f800c330e67007850e6700b8216
 15. 73218f9f18f9f184ce8ffc40000000a8ffc40000000b38670c200001ce079c081099ca2b38670c20600001ce079c08138670c3099ca2a0738670c22829
 16. 7312cb5e3c7ad348ce1ffe0000000061f801f800000830aad452007e00007f00050d568a30e670c20600001f807f00810e670c30d568a20b0aad4521419
 17. 7312cb5e3c7ad348ce1ffe0000000061f801f800000830aad452007e00007f00050e670c30d568a20600001f807f00810d568a30e670c20b0aad4521419
 18. 7312cb5e3c7ad348ce1ffe0000000061f801f800000830b35862007e00007f00050e670c30cce4920600001f807f00810cce4930e670c20b0b358621419
 19. 7312cb5e3c7ad348ce1ffe0000000061f8000007f00030b35862007e1f800000850e670c30cce4920600001f807f00810cce4930e670c20d0b358621219
 20. 7312cb5e3c7ad348ce1f8000007f00021f8000007f00030e670c2007e1f800000850aad4530d568a20c007e1f800000850d568a30aad4520d0e670c21213
 21. 7312cb5e3c7ad348ce1f8000007f00021f8000007f00030e670c2007e1f800000850b358630cce4920c007e1f800000850cce4930b358620d0e670c21213
 22. 7301c79e3c79e3fc021fc00099c000c01f809f802000410e45146107e00004133a1f800c330c6700f82007f10003f00210e243c2099cc330b0a6628b8494
 23. 7301c79e3c79e3000205d49a987530041fc01f800000e10e26086107e00007f00610a6608a099cc328c1a2b1581ab03820000c330e451438b0c652439512
 24. 7301c79e3c79e3000205d49a987530041fc000007f00610e26086107e1f800000e10a6608a099cc328c1a2b1581ab03820000c330e451438d0c652439312
 25. 7301c79e3c79e300021fc01f800000e01f811099ff00030e241c2107e00007f0060099cc330a642c30c007e9f802133850e470060000c338b0c6700a9394
 26. 7301c79e3c79e300021fc01f800000e01f811f802133830e27006107e00007f0060099cc330a6700b0a007e9099ff00050e441c20000c338b0c642c29594
 27. 733fc79e0c79e0fc0010fe00180030641f81909980000308643ca00420001ff0361f99c0010e043c78400019f80213381086720ff800c33830e0710f9188
 28. 733fc79e0c79e0fc0010801f980030e01f81909980000308643ca00420001ff0361f99c0010e043c788007f8000213305086720ff800c33830e0710f9184
 29. 733fc79e0c79e0fc0010801f980030e01f818000213303086720e00420001ff0361f99c0010e0710f88007f909980000508643cbf800c33830e043c79184
 30. 733fc79e0c79e0000010fe1f980030641f818000213307086700e00421f81bf03e0019c0010e071079200019099ff000308642cbf800c33850e043c39988
 31. 733fc79e0c79e0000010801f980030e41f819581b53003086518a00420001f

f0363f99c0010e0518b88007f9a982b030508662460000c33930e06247918c
32. 733fc79e0c79e0000010801f980030e41f819f80213303086700e00420001f
f0363f99c0010e0700f88007f9099bf000508643c20000c33930e043c3918c
33. 733fc79e0c79e0000000c01f9840306400c000183f30e5f99c00015179a81b
503030a2608f0a26383881a2b9581ab03030c4504f0c45343880000c339592
34. 733fc79e0c79e0000000c01f9840306400c000183f30e5f99c000152b9581b
503030a4508f0a45383881a179a81ab03030c2604f0c26343880000c339592
35. 733fc79e0c79e0000000c01f9840306405e995983530050a4508e10020001b
f03e3f99c0010a45383881a179a81ab03030c2604e0000c338d0c263439192
36. 733fc79e0c79e0000000c01f980030e400c000187f3065f99c000152b9581b
503030a452870a4518b881a179a81ab03030c2614b0c26247880000c339394
37. 733fc79e0c79e0000000c01f980030e405e995983530050a4528610020001f
f0363f99c0010a4518b881a179a81ab03030c2614a0000c338b0c262479194
38. 733fc79e0c79e0000000c01f980030e41f819581b530030c2518a10020001f
f0363f99c0010a4518b88007f9a982b03050a462460000c338b0c262479194
39. 733fc79e08f98cac0c8f8c1a9800000210801f980110a301662ca00420001f
9c2a3380a2c7f99c00188007f80003530095818a33086728a8b0e0718a8d90
40. 733fc79e08f98cac0c8f8c000035300210801f980110a3016728a00420001f
9c2a3380b18bf99c00188007f9a980000095818a3308662ca8b0e062c68d90
41. 733f8f98c863ec84cc833e1f800000088f8c00003f0009099892a108000887
92c8738830cb01672c21c00421ce141018706170c7380b1c21bf99c0019188
42. 733f8f98c863ec84cc833e00003f00088f8c1f80000009099892a108000887
92c8738832c301670ca1c00421ce141018706171c3380b0c61bf99c0019188
43. 733f8f98c863ecac0c833e1a980000088f8c0000353009581892a108000887
92ca338822cb016728a8c00421ce14101a306162c7380b18a8bf99c0019188
44. 733f8f98c863ecac0c833e00003530088f8c1a98000009581892a108000887
92ca3388328b01662ca8c00421ce14101a3061718b380a2c68bf99c0019188
45. 733f8f98c863ecfc00833e00002133088f8c1099800009f80092a108000887
92ce1388320f01643cb8400421ce14101e1061710f38083c783f99c0019188
46. 733f8f98c861f084cc837d9f80000088f8c00003f000b099882a108000887
9200738e70cb01672c21c00421ce160c18608170c7380b1c01ff99c0c80188
47. 733f8f98c861f084cc837d80003f00088f8c1f8000000b099882a108000887
9200738e72c301670ca1c00421ce160c18608171c3380b0c41ff99c0c80188
48. 733f8f98c861f0ac0c837d9a980000088f8c000035300b581882a108000887
9202338e62cb016728a8c00421ce160c1a208162c7380b1888ff99c0c80188
49. 733f8f98c861f0ac0c837d80003530088f8c1a9800000b581882a108000887
9202338e728b01662ca8c00421ce160c1a2081718b380a2c48ff99c0c80188
50. 733f8f98c861f0fc00837d80002133088f8c109980000bf80082a108000887
9206138e720f01643cb8400421ce160c1e0081710f38083c587f99c0c80188
51. 733ec198c8f9807c008f8c1f00213318108e3f88411001016700e007f90896
0cc0e0800a07c900ac9920cc2400179c203380b10d010f2cd89380c5c18784
52. 733ec198c863e07c00833e1f00213318108e2008792c05388320c1f8190896
0cc0e080090bc904ac1860cc25f81410101061700f010f1cd9138085c58b84
53. 733e8fd8c863e00300830190897f0c0e833e000021330df800922108e3c807
92c640184a01388300f940cc25f8181010138045c5061710f83010f0cd8d90
54. 733e8fd8c861f00000837c006021330c830190897f000bf860b22108e3c807
9206138e320e0184aca000cc25f81a0c1e2081000f38045c18b010f0c9998c
55. 72388fb8c863f9c3083c20ce14001808301800621318bf8141248f8e10988
000093008bc7f80092b8210b24088392061309c2c9388720b8301643cb8984
56. 72388fb8c863f9c003083c20ce17f018083019f8621318a00141248f8e10988

- 0000b3008bc3f80082b8a10b24088392065309c2c1388700b9301643cb8984
57. 72388fb8c8600cfc3083c20ce1400182837f800621318bf8140248f8e1098b
f00093008bc4000092b8610b240883920e1309c2c9388320b8301643c38994
 58. 72388fbfc863fce03083c20060c001e283018c80213191f8140268f8010988
70009f810b03306091f8810b24088392061309c2c9388720b8301643cb8984
 59. 62118e3f18e29103008afe34d000ca8094f0438611228f356001c83803c667
f006110a4a46380401292950088a0ffc08c3800a0330645438528549a02d43
 60. 62118e3f18e29103008a8034d03fca8094f0438611228f356401483fe3c664
0006110a4a46380001a92950088a0ffc08c3800b0130645438528548a22d43
 61. 62118e3f18e29103008a8034d03fca8094f0438611228f356401483803c667
f006110a4b44380401292957e88a0c0c08c3800a03306054b8528548a22d43
 62. 62118e3f18a78100308afe34d000ac809c5243e011228f365001c83803c667
f006110a4a4a38040128a950088a0ffc08a3800a0336046438528549a02d43
 63. 62118e3f18a78100308a8034d03fac809c5243e011228f365401483fe3c664
0006110a4a4a380001a8a950088a0ffc08a3800b0136046438528548a22d43
 64. 62118e2918fc0164009f80956071998094f0489147000b3061192807e2ae56
844923800025356464b82807e336038cce0291522438646024d180242a3601
 65. 62118e2918fc0164009f80336038cce094f0489147000a3864502807e95607
19980291522530612924c807e2ae56844931802427356464a0038000283783
 66. 62118e2918fd9100009faa20656842a294f0489147000b356074a804c3fe03
8cce1184802638646020080549fe07190c838000233065093822924a283a4d
 67. 62118e2918fd9100009fcc206038cce094f0489147000a3860702802a3fe56
842a31848027356464a0080549fe07190c82924a2330650924c38000283b83
 68. 62018e18386193800095fe20a01530449fea25e1a0c8a3011538a80d49ac07
f008932662c23000cc2049a411fe66b048a306003238400440a0c24a22787a
 69. 62388e38c8e3fcff30908e2c901920008380006621110f30e422c83b390894
000093084acb800b23828cc2438080c181310f309f81012d8930145c78582
 70. 62388e38c8e3fcff30908e2c901920008381800621118b308722a83b210890
0c00d30e4b09f80092b848cc243e0c00101310c2cdf8141258330107c78982
 71. 62388e38c8e3fc0330908e2c9019200483801fe621110f30e402c83b390897
f00093084ac20000b23928cc2438080c183310f309f81002d8930145c3858a
 72. 62388e38c8e3fc0330908e2c9019200483819f8621118b308702a83b210893
fc00d30e4b00000092b948cc243e0c00103310c2cdf8140258330107c3898a
 73. 62388e3fc8ff8ce330908e2c90001c80803203e021120df90022c83819088d
900113084acb3060727828cc24000870163310f305361401f91f8149038588
 74. 62388e3fc8ff8c643090b24388001000800f9c60211191f90722a83c22060d
9020330942cd300f027828c801090a6cc0b31647ca3800a1e01f810b01898c
 75. 3301823cfd29824c869709ff8020000812fa1cd6228c060d0304a17d200829
1a2073e2b087019808c03c32830003f000c990c82618a92c01f86221c21c9c
 76. 3301823cfd29824c869709f0003f000812fa1cd6228c060d012c217d200829
1a2073e2a1c3019808c05c3283f8020000c990c82618ab0481f86230861c9a
 77. 3301823cfd2982fc009709e990e0000812fa1cd6228c600d0034a17d200829
1a2613e28387019808c03c328300013218df80082618a920d87862210f849c
 78. 485264169968264a1300f3fe56080501a1e1051618a8175b012189383e2502
ec501a848985000128627d122832294c10f0001287a848984335b01218464d
 79. 485264169968264a1300f3fe56080501a1e1051618a8175b012189383e2502
ec5010001287a84898427d122832294c10fa8489850001286335b01218464d
 80. 4912341699682c489300f9fcd6080501a1b0514618a2475b012189389e0d02
ec501a81a185000128627d12881a294c10f0001287a81a184335b01218464d
 81. 4912341699682c489300f9fcd6080501a1b0514618a247a81a1849389e0d02

ec5015b01219000128627d12881a294c10f00012875b0121833a81a184464d
82. 4912341699682c489300f9fcd6080501a1b0514618a247a81a1849389e0d02
ec50100012875b0121827d12881a294c10f5b01219000128633a81a184464d
83. 4982341699682c419300fbb96080501a1b2130618a2475b01418938ba2902
ec50185161850001486179921813256810f00014878516184335b01418464d
84. 4982341699682c419300fbb96080501a1b2130618a2478516184938ba2902
ec5015b014190001486179921813256810f00014875b01418338516184464d
85. 4982341699690c099300fbb96080029a1b2130618a2c35b01418938ba2902
ec02985161830001486179905883256810f00280878512384335b280184a4d
86. 4990309699690c099300fb1ebe080029a1961a0618a2c38512382938b02b82
ec0295b2801900280861b9905883256818b00280875b280183385123824a4d
87. 4990309699690c099300fb1ebe080029a1961a0618a2c38512382938b02b82
ec02900280875b280181b9905883256818b5b2801900280863385123824a4d
88. 405a00024240005a03a1915de5fc2a61a1915de5fc2a610040045dbdd88e08
4752c990460300400443bdbdd88e084752d004004499046023b00400444e4f
89. 405a00024240005a03a1915f35f98a61a1915f35f98a610040045dbdd8a308
1d52c990460300400443bdbdd8a3081d52d004004499046023b00400444e4f
90. 4186345689690c099308fabe86480029a1b2130618a2c35b01418d383a210a
ec02905568830001486179905883256810f00280878512384335b280184a4d
91. 64da6010c308065b2704921e843d436097df828405430110a545588050d907
6c1a5855088705016001d8bf5010e500227050160185508861710a54543847
92. 64da6010c308065b2704921e843d436097df828405430110a545588050d907
6c1a5050160185508861d8bf5010e500227855088705016001710a54543847
93. 64da6010c228145b2720905e843d436097df828407028102a945588050d907
6c1a5855088705016001d8bf5010e500227050160185508861710a54543847
94. 64da6010c068305b2720905e8438e36097df828402a28102a944dc3f1810e5
002272801601a8508862788050d9076c1a9855088705016001d10a5243847
95. 64da44128148225b2704921c5438e36097df805400e301a850887c0018d907
6c1a910a524d28016002dc3f1810e50022b280160110a524c27a8508863847
96. 402d3647c3647ccb31dead6044008823ad5ee022004445680400380000990f
2cc015090d47a090e8a63800019661321815091137a09223a65966030e8911
97. 400024168168240003a4df9d45103ed1a4df9d45103ed10001083de8b8169f
65428990c109000108237de8b8169f654290001082990c1083700010824e4f
98. 401e3647c3647ccb31dec6044008823b4dee022004444f00400380000990f
2cc015090d47a090e8a63800019661321815091137a09223a65966030e8911
99. 401234d20349304803df7d801e00c367bf7d801e00c367680000180019c967
9c2e0408c30f8888000678001938e67c1e11910000211430e6768032c560e1
100. 401234d20349304803df7d801e00c367bf7d801e00c367680000180019c967
9c2e14888000808c30e678001938e67c1e0111430f29100006768032c560e1
101. 4012049200492048039f807fe600cc9b9f807fe600cc9b6800001807e60667
fcc1c900430f68000006b807e60667fcc1d6800000900430e6b68000007475
102. 4012049200492048039f807fe600cc9b9f807fe600cc9b6800001807e60667
fcc1c600430f98000006b807e60667fcc1d9800000600430e6b68000007475
103. 403f0492c0492cff31897e6006000c059fa460600c003f8073cd800009007
fcc196980f096818f040580001fe6120099698023d681813c03fe6030e1008

References

- [1] D. G. Fon-Der-Flaass. A bound on correlation immunity. *Sib. Èlektron. Mat. Izv.*, 4:133–135, 2007. Online: <http://mi.mathnet.ru/eng/semr149>.
- [2] D. G. Fon-Der-Flaass. Perfect 2-colorings of a hypercube. *Sib. Math. J.*, 48(4):740–745, 2007. DOI: 10.1007/s11202-007-0075-4 translated from *Sib. Mat. Zh.* 48(4) (2007), 923-930.
- [3] D. G. Fon-Der-Flaass. Perfect colorings of the 12-cube that attain the bound on correlation immunity. *Sib. Èlektron. Mat. Izv.*, 4:292–295, 2007. In Russian. English translation: <https://arxiv.org/abs/1403.8091>.
- [4] P. Kaski and P. R. J. Östergård. *Classification Algorithms for Codes and Designs*, volume 15 of *Algorithms Comput. Math.* Springer, Berlin, 2006. DOI: 10.1007/3-540-28991-7.
- [5] P. Kaski and O. Pottonen. libexact user’s guide, version 1.0. Technical Report 2008-1, Helsinki Institute for Information Technology HIIT, 2008.
- [6] A. V. Khalyavin. Estimates of the capacity of orthogonal arrays of large strength. *Mosc. Univ. Math. Bull.*, 65(3):130–131, 2010. DOI: 10.3103/S0027132210030101.
- [7] D. Kirienko. On new infinite family of high order correlation immune unbalanced Boolean functions. In *Proceedings 2002 IEEE International Symposium on Information Theory, Lausanne, Switzerland, June 30 – July 5, 2002*, page 465. IEEE, 2002. DOI: 10.1109/ISIT.2002.1023737.
- [8] D. S. Krotov. On the OA(1536,13,2,7) and related orthogonal arrays. *Discrete Math.*, 343:111659/1–11, 2020. DOI: 10.1016/j.disc.2019.111659.
- [9] D. S. Krotov and K. V. Vorob’ev. On unbalanced Boolean functions with best correlation immunity. *Electr. J. Comb.*, 27(1):#P1.45(1–24), 2020. DOI: 10.37236/8557.
- [10] B. D. McKay and A. Piperno. Practical graph isomorphism, II. *J. Symb. Comput.*, 60:94–112, 2014. DOI: 10.1016/j.jsc.2013.09.003.
- [11] Yu. Tarannikov. On resilient Boolean functions with maximal possible nonlinearity. Cryptology ePrint Archive 2000/005, 2000. <https://eprint.iacr.org/2000/005>.
- [12] K. V. Vorobev and D. G. Fon-Der-Flaass. On perfect 2-colorings of the hypercube. *Sib. Èlektron. Mat. Izv.*, 7:65–75, 2010. In Russian, with English abstract.