

DEAAN: DISENTANGLED EMBEDDING AND ADVERSARIAL ADAPTATION NETWORK FOR ROBUST SPEAKER REPRESENTATION LEARNING

Mufan Sang, Wei Xia, John H.L. Hansen

Center for Robust Speech Systems, The University of Texas at Dallas, TX, USA

{mufan.sang, wei.xia, john.hansen}@utdallas.edu

ABSTRACT

Despite speaker verification has achieved significant performance improvement with the development of deep neural networks, domain mismatch is still a challenging problem in this field. In this study, we propose a novel framework to disentangle speaker-related and domain-specific features and apply domain adaptation on the speaker-related feature space solely. Instead of performing domain adaptation directly on the feature space where domain information is not removed, using disentanglement can efficiently boost adaptation performance. To be specific, our model’s input speech from the source and target domains is first encoded into different latent feature spaces. The adversarial domain adaptation is conducted on the shared speaker-related feature space to encourage the property of domain-invariance. Further, we minimize the mutual information between speaker-related and domain-specific features for both domains to enforce the disentanglement. Experimental results on the VOICES dataset demonstrate that our proposed framework can effectively generate more speaker-discriminative and domain-invariant speaker representations with a relative 20.3% reduction of EER compared to the original ResNet-based system.

Index Terms— Speaker verification, embedding disentangling, adversarial domain adaptation

1. INTRODUCTION

The task of speaker verification (SV) is to identify the true characteristics of the speaker from audio streams and to accept or discard the identity claimed by the speaker [1]. As the previous state-of-the-art method, i-vector has been far surpassed by current neural network-based deep speaker embedding systems [2, 3, 4, 5, 6]. Among them, x-vector and ResNet-based architectures are most widely used. Although current deep speaker systems trained on a large amount of labeled data can extract speaker-discriminative and robust speaker embeddings, their performance may still degrade significantly when deployed to new unseen domains [7]. It is caused by the domain mismatch between training and unseen test data. Deep speaker embedding networks can improve the generalization ability with large-scale in-domain datasets. In practice, however, it might be very costly or even impossible to collect sufficient data annotations.

Many extrinsic factors can lead to performance degradation, such as channel mismatch, language, environmental noise, and room reverberation. To alleviate this problem, numerous robust speaker verification systems have been proposed. One approach used in [5, 7] is to improve the robustness of speaker verification systems with data augmentation by adding noise, music, and reverberant speech. However, data augmentation has its constraint that it can only provide specific acoustic variations.

The goal of domain adaptation (DA) is to reduce mismatch across domains. It has been performed on the back-end level, input-level, and embedding-level. For back-end level, PLDA can be adapted with unlabeled in-domain data on its mean and covariance matrix. For input-level, models usually can be adapted by training with enhanced [8] or domain-translated [9] input features. For adaptation at embedding-level, it often targets at minimizing certain distances between source and target domains to align them in the same embedding space, such as cosine distance [10], mean squared error (MSE) [11], and maximum mean discrepancy (MMD) [12]. However, this method usually requires parallel or artificial simulated data, which cannot generalize well to real-world scenarios.

Recently, adversarial learning becomes a popular approach to adapt speaker representations. For instance, [13, 14] explored domain adversarial learning to learn domain-invariant and speaker-discriminative representations. Similar ideas are also applied in [15, 16, 17], but these systems need more extra noise labels or environment labels, which are hard to obtain in real-world scenarios. However, these DA methods have a common limitation that they implement the adaptation typically on the feature space, which encodes speaker-related and speaker-unrelated factors collectively. Therefore, the adaptation on feature space is unavoidably interfered with the speaker-independent factors, even leading to negative transfer [18]. Although [19] introduced their study on speaker representation disentangling with Voxceleb datasets, the cross-dataset adaptation with disentangling is still an open question to investigate.

In this work, we propose a novel framework Disentangled Embedding and Adversarial Adaptation Network (DEAAN), aiming for the cross-domain speaker verification problem by disentangling speaker-related and the undesired domain-specific features. Unlike previous methods treating adaptation and disentangling separately, we incorporate both of them into our framework and train them jointly. In this way, domain adaptation can be operated more effectively on the speaker-related space without the interference of domain-specific features. Accordingly, the proposed framework aims to encode the source and target inputs into three latent feature spaces by the corresponding shared speaker-related encoder and two domain-specific encoders, as shown in Figure 1. The shared speaker-related space contains speaker-related features across domains. The source and target domain-specific feature spaces capture domain-specific features only. Meanwhile, a domain adversarial loss is applied to encourage the encoder to produce domain-invariant features. To guarantee the disentanglement, we propose to minimize the mutual information between disentangled speaker-related features and domain-specific features in both domains. Our proposed approach makes disentangling and adaptation mutually benefit each other. The disentangled feature enables the adaptation to concentrate on speaker-related features exclusively, and adaptation correspondingly




Fig. 1: Overview of the proposed Disentangled Embedding and Adversarial Adaptation Network

enhances the disentangling with a more domain-invariant encoder. We evaluate our proposed framework on a far-field dataset Voices Obscured in Complex Environmental Settings (VOICES) [20]. Experimental results show that our framework can significantly improve speaker verification performance using the same backbone structure as the ResNet-based system utilized in this study.

In Sec. 2, we describe the details of our proposed DEAAN framework. Data description and detailed experiment settings, results and discussions are reported in Sec. 3 and 4. Finally, we conclude our work in Sec. 5.

2. DISENTANGLED EMBEDDING AND ADVERSARIAL ADAPTATION NETWORK

In this section, we introduce our proposed approach of DEAAN with the goal of obtaining robust disentangled speaker embeddings which contain only speaker-related information. To make the speaker embedding robust to domain variations, we collectively consider the adversarial domain adaptation and representation disentanglement to decouple domain-invariant speaker representations from input speech signals. Therefore, our framework incorporates disentanglement and adversarial domain adaptation to extract speaker-related and domain-invariant speaker representations.

The entire model architecture of DEAAN is illustrated in Figure 1. It can be mainly concluded as two modules: 1) disentanglement, and 2) domain adaptation. To be specific, disentanglement module consists of following components: a shared speaker frame-level feature extractor (referred as backbone G), a speaker-related encoder E_{id} , two domain-specific encoders E_{ds} and E_{dt} , a domain discriminator D_{dom} , two speaker identity classifiers C_s for source domain, and C_t for target domain, and a decoder R . The adaptation module consists of an adversarial domain discriminator D_{adv} .

For the backbone, we use a ResNet34 architecture. As shown in Figure 1, the extractor G extracts frame-level latent features \mathbf{f}_G from input features. The three encoders E_{id} , E_{ds} , E_{dt} aim to disentangle the frame-level latent features into speaker-related features and domain-specific features with speaker identity labels. The decoder R is responsible for reconstructing the original input feature (\mathbf{x}_s or \mathbf{x}_t) from a fusion of speaker-related and domain-specific feature. In

order to promote the disentanglement, we minimize the mutual information between disentangled features to decrease their dependency. The adversarial domain discriminator D_{adv} is trained to align the distributions of speaker-related features \mathbf{f}_{id} across source and target domains. With the adversarial training strategy, our proposed adaptation network can effectively extract robust and domain-invariant speaker features.

2.1. Speaker embedding network backbone

In this work, we use the ResNet34 with self-attentive pooling (SAP) [6] as our original speaker recognition system. This speaker embedding network can encode variable length of utterance into a fix-length speaker representation. This system is trained using cross-entropy (CE) as the speaker identity loss. Meanwhile, we use the ResNet34 only as our backbone G for DEAAN to extract frame-level latent features.

2.2. Embedding disentanglement

Although the original speaker recognition system above can extract discriminative speaker embeddings, there are still some speaker-unrelated information entangled in the feature space. To decouple the speaker-related features from embeddings, we enforce the shared encoder E_{id} to encode speaker-related information from speaker embeddings across domains, and encourage the two separated domain-specific encoders to capture their speaker-unrelated domain-specific features. As depicted in Figure 1, given a source input and a target input, the speaker-related feature for source \mathbf{f}_{id}^s and target \mathbf{f}_{id}^t going through speaker classifiers C_s and C_t are expected to preserve the strong speaker discriminative power with the speaker identity loss,

$$L_{id} = \mathbb{E} \left[- \sum_{i=1}^I y_i^s \log C_s(\mathbf{f}_{id}^s)_i \right] + \mathbb{E} \left[- \sum_{j=1}^J y_j^t \log C_t(\mathbf{f}_{id}^t)_j \right] \quad (1)$$

Where y_i^s and y_j^t denotes the class of the i -th sample in source domain and the j -th sample in target domain.

To ensure domain-specific features are disentangled by the two encoders E_{ds} and E_{dt} properly, a shared domain discriminator D_{dom} is applied to discriminate the domain-specific feature \mathbf{f}_{dom}^s or \mathbf{f}_{dom}^t based on their domain membership (source or target). D_{dom} is trained by minimizing the following binary cross-entropy (BCE) loss function,

$$L_{dom} = \mathbb{E} [-\log D_{dom}(\mathbf{f}_{dom}^s)] + \mathbb{E} [-\log D_{dom}(1 - \mathbf{f}_{dom}^t)] \quad (2)$$

Disentangled embeddings are expected to preserve information of the original input, thus the decoder R is required to reconstruct the original inputs \mathbf{x}_s and \mathbf{x}_t in source and target domains from the fusion of $(\mathbf{f}_{id}^s, \mathbf{f}_{dom}^s)$ and $(\mathbf{f}_{id}^t, \mathbf{f}_{dom}^t)$, respectively. This can be achieved by minimizing the distance between reconstructed input and original input. We utilize L_2 distance as the distance metric, the reconstruction loss function is formulated as,

$$L_R = \mathbb{E} [\|R(\mathbf{f}_{id}^s, \mathbf{f}_{dom}^s) - \mathbf{x}_s\|_2^2] + \mathbb{E} [\|R(\mathbf{f}_{id}^t, \mathbf{f}_{dom}^t) - \mathbf{x}_t\|_2^2] \quad (3)$$

In this way, disentangled embeddings are enforced to retain more information of original inputs.

2.3. Mutual information minimization

To achieve better disentanglement performance, we minimize the mutual information between speaker-related and domain-specific features on source and target domains. Theoretically, mutual information is represented as the Kullback-Leibler (KL) divergence between the joint distribution \mathbb{P}_{XZ} (referred as \mathbb{J}) and the product of marginals $\mathbb{P}_X \otimes \mathbb{P}_Z$ (referred as \mathbb{M}) of two random variables X and Z . In [21], a mutual information neural estimation (MINE) was proposed to estimate the mutual information for high dimensional continuous variables based on a deep learning architecture. With the Donsker-Varadhan representation [22], mutual information can be estimated as,

$$\mathcal{I}_\Theta(X; Z) = D_{KL}(\mathbb{J} \parallel \mathbb{M}) = \sup_{\theta \in \Theta} \mathbb{E}_J [T_\theta] - \log(\mathbb{E}_M [e^{T_\theta}]) \quad (4)$$

Where $T_\theta : \mathcal{X} \times \mathcal{Z} \rightarrow \mathbb{R}$ denotes a neural network parameterized by θ in the equation. Mutual information between continuous random variables can be estimated by maximizing the above equation. Considering we primarily concern minimizing mutual information instead of its detailed value, we propose to apply an alternative MINE which is more stable based on the Jensen-Shannon divergence (JSD) [23]. The Equation 4 can be alternatively formulated as,

$$\mathcal{I}_\Theta(X; Z) = \mathbb{E}_J [-\text{sp}(-T_\theta)] - \mathbb{E}_M [\text{sp}(T_\theta)] \quad (5)$$

Where $\text{sp}(z) = \log(1 + e^z)$ represents a softplus function.

The information overlap between $(\mathbf{f}_{id}^s, \mathbf{f}_{dom}^s)$ as well as $(\mathbf{f}_{id}^t, \mathbf{f}_{dom}^t)$ can be minimized by minimizing their mutual information. Thus, we achieve embedding disentanglement by playing a min-max game. First, MINE (referred as M) is trained to estimate mutual information between pairs of features $(\mathbf{f}_{id}^s, \mathbf{f}_{dom}^s)$, and $(\mathbf{f}_{id}^t, \mathbf{f}_{dom}^t)$ by maximizing \mathcal{I}_Θ in Equation 5. Meanwhile, encoders are trained to produce speaker-related and domain-specific features with minimum mutual information. Thus, we define the corresponding loss as,

$$L_{MI} = \min_{E_{id}, E_{ds}, E_{dt}} \max_M \sum_{i=1}^N \mathcal{I}_\Theta((\mathbf{f}_{id})_i; (\mathbf{f}_{dom})_i) \quad (6)$$

Where \mathbf{f}_{id} and \mathbf{f}_{dom} represent $(\mathbf{f}_{id}^s$ or $\mathbf{f}_{id}^t)$ and $(\mathbf{f}_{dom}^s$ or $\mathbf{f}_{dom}^t)$. A gradient reversal layer (GRL) [24] is adopted to play the min-max game for this objective function.

2.4. Adversarial domain alignment

In embedding disentanglement, we apply the strategy that shares the weights for the backbone extractor and speaker-related encoder between source and target domains. But this strategy cannot ensure that the speaker-related features are properly adapted and have similar distribution across domains. To encourage the characteristic of domain-invariant for disentangled speaker-related features, we exploit an adversarial domain discriminator D_{adv} which aims to distinguish the domain of speaker-related features \mathbf{f}_{id}^s and \mathbf{f}_{id}^t . On the other hand, the encoder E_{id} learns to confuse the D_{adv} and generates speaker-related features which cannot be differentiated by the discriminator. The adversarial loss can be presented as,

$$L_{adv} = \mathbb{E} [\log D_{adv}(\mathbf{f}_{id}^s) + \log(1 - D_{adv}(\mathbf{f}_{id}^t))] + \mathbb{E} [\log D_{adv}(\mathbf{f}_{id}^t) + \log(1 - D_{adv}(\mathbf{f}_{id}^s))] \quad (7)$$

With this designed mechanism, the shared encoder E_{id} is able to extract domain-invariant and speaker-related features.

2.5. Overall optimization

In summary, the overall objective function of DEEAN is a weighed sum of all loss functions above represented as,

$$L_{DEEAN} = L_{id} + \lambda_{dom} L_{dom} + \lambda_{adv} L_{adv} + \lambda_R L_R + \lambda_{MI} L_{MI} \quad (8)$$

Where λ_{dom} , λ_{adv} , λ_R , and λ_{MI} are hyper-parameters to control the weight for each composition. In our experiments, they are set as: $\lambda_{dom} = 0.5$, $\lambda_{adv} = 0.5$, $\lambda_R = 0.2$, and $\lambda_{MI} = 0.2$.

3. EXPERIMENTAL SETTING

3.1. Datasets

3.1.1. Source domain data

We use the development set of Voxceleb1 and Voxceleb2 (refer to as Vox1-dev and Vox2-dev) which were collected ‘‘in the wild’’ [25, 26] as our source domain data. The former contains 148642 utterances from 1211 speakers, and the latter one comprises of around 1 million utterances from 5994 speakers. We do not use any data augmentation strategies in experiments.

3.1.2. Target domain data

For target domain, we use the Voices Obscured in Complex Environmental Settings (VOICES) Challenge 2019 corpus [20] which is challenging with speech recorded by various distance far-field microphones in different noisy rooms. The corpus consists of development set (refer to as VOICES-dev) with 15904 utterances from 196 speakers, and evaluation set (refer to as VOICES-eval) with 11392 utterances from more challenging recording conditions. Our proposed DEEAN is evaluated on the VOICES-eval set with 3.6 million trials. We report the system performance with two evaluation metrics: Equal Error Rate (EER) and minimum Detection Cost Function (DCF) with $P_{target} = 0.01$.

Table 1: Speaker verification results on the VOICES evaluation set with different adaptation methods.

System	Train set	EER (%)	minDCF
ResNet34-SAP	Vox1+Vox2	7.52	0.532
ResNet34-SAP-FT	Vox1+Vox2 +VOICES-dev	6.54	0.458
Peri [27]	Vox1+Vox2	9.07	N/A
ADSAN+MINE [28]	Vox1+Vox2+Aug +VOICES-dev	6.76	0.599
Our proposed DEEAN	Vox1+Vox2 +VOICES-dev	5.21	0.394

3.2. Feature extraction and ResNet-based models training

For all systems, 64-dimensional log-mel filter bank energies are extracted with a frame-length of 25 ms at a 10 ms shift. We apply mean-normalization over a sliding window of up to 3 seconds, and Kaldi energy-based VAD is used to remove silence frames.

We use the ResNet34 with self-attentive pooling (SAP) method trained by the CE loss function as the original system. It is trained on the Vox1-dev and Vox2-dev without any data augmentation. For each training step, we randomly make a chunk of 300 to 800 frames of each utterance to keep samples in each minibatch sharing the same frame length.

Based on the pre-trained ResNet34-SAP model, we fine-tune it on the VOICES-dev with the replaced new last classification layer and all other layers (referred as ResNet34-SAP-FT). Same settings for input and loss function as the above system are adopted during fine-tuning. We evaluate the fine-tuned model on the VOICES-eval.

3.3. DEEAN implementation details

For our proposed architecture, we use the Vox1-dev and Vox2-dev as the source domain data and development set of VOICES as the target domain data to train the DEEAN. We exploit a ResNet34 as the backbone to extract the frame-level features. The shared speaker-related encoder and two domain-specific encoders share the same structure which consists of one SAP layer and two fully-connected layers. The decoder R reconstructs the original input feature through three fully-connected layers and nine transposed convolution layers [29] with batch normalization.

For training, we use the SGD optimizer with a learning rate of $1e-4$ and momentum of 0.9 to optimize the adversarial domain discriminator. Adam optimizer is applied with an initial learning rate of $1e-4$ decreasing by 5% every 5 epochs to train other parts. We train the model adversarially with the procedure similar in [30]. Different from the ResNet34-SAP system and the fine-tuned one ResNet34-SAP-FT, we use a shorter fixed length input with 384 frames randomly cropped from each utterance to train our DEEAN. The backend comprises of LDA for reducing the embedding dimension to 200, centering, length normalization, and a Gaussian PLDA.

4. RESULTS AND DISCUSSIONS

We investigate the performance of our DEEAN architecture and compare it with the ResNet34-SAP and the fine-tuned ResNet34-SAP-FT.

Table 1 shows system performance on the VOICES-eval. Methods [27, 28] are recently proposed adversarial training architectures for speaker representation learning. As shown in the Table, although the proposed DEEAN is trained with shorter input (384 frames)




Fig. 2: t-SNE plots of extracted embeddings for 8 speakers: (a) Speaker embeddings extracted from the ResNet34-SAP-FT. (b) speaker-related features extracted from DEEAN. (c) domain-specific features extracted from DEEAN

and use the same frame-level extractor as the ResNet34-SAP and ResNet34-SAP-FT, it outperforms both of them significantly with a relative 30.7% and 20.3% reduction in EER, and 25.9% and 13.9% reduction in minDCF, respectively. With the best performance produced by DEEAN in Table 1, it meets our assumption that the incorporation of our proposed adversarial domain adaptation and embedding disentanglement can effectively improve the speaker verification performance. With the same classification loss and even shorter length of input, the results demonstrate that our model can generate more speaker-discriminative and domain-invariant speaker embeddings even in challenging environments.

To visualize the effectiveness and disentanglement performance of the proposed model, we use the t-distributed Stochastic Neighbor Embedding (t-SNE) plots to illustrate the performance improvement in Figure 2. Speakers are randomly chosen from target domain. Figure 2 (a) is the visualization of embeddings extracted from the ResNet34-SAP-FT, Figure 2 (b) represents speaker-related features f_{id} extracted from DEEAN, and Figure 3 (c) shows the corresponding domain-specific features. As shown in Figure 2 (a), it can be observed that the identity clusters are not compact enough (e.g., blue cluster) and even contain small separated clusters in each identity. It may can be explained that some recorded speech segments share similar or same noise in the room and far-field conditions, but the entire recording process was conducted with various channels and noise variabilities. Compared to the ResNet34-SAP-FT, the speaker-related features extracted by our proposed model are denser for same identity and the gap caused by domain or channel mismatch is diminished. Moreover, domain-specific features shown in Figure 3 (c) are distributed uniformly in the feature space and independent to speaker identities. Therefore, the above results indicates that our proposed method can effectively generate discriminative and domain-invariant speaker-related features.

5. CONCLUSIONS

In this paper, we propose a novel speaker embedding framework that disentangles speaker-related and domain-specific features and performs domain adaptation on the speaker-related feature space without detailed mismatch information by adversarial training. By introducing a mutual information neural estimator and adversarial domain adaptation, DEEAN can effectively adapt speaker embeddings across domains without domain-related interference. Our approach incorporates representation disentanglement and adversarial domain adaptation together, which enable them to mutually benefit each other. Experimental results demonstrate that our approach can produce more speaker-discriminative and domain-invariant features to improve the speaker verification performance in challenging environments compared to the original and fine-tuned systems with using the same backbone structure.

6. REFERENCES

- [1] John HL Hansen and Taufiq Hasan, “Speaker recognition by machines and humans: A tutorial review,” *IEEE Signal processing magazine*, vol. 32, no. 6, pp. 74–99, 2015.
- [2] Chunlei Zhang and Kazuhito Koishida, “End-to-end text-independent speaker verification with triplet loss on short utterances,” in *Interspeech*, 2017, pp. 1487–1491.
- [3] Wei Xia and John HL Hansen, “Speaker representation learning using global context guided channel and time-frequency transformations,” *Proc. Interspeech 2020*, pp. 3226–3230, 2020.
- [4] Li Wan, Quan Wang, Alan Papir, and Ignacio Lopez Moreno, “Generalized end-to-end loss for speaker verification,” in *ICASSP*, 2018, pp. 4879–4883.
- [5] David Snyder, Daniel Garcia-Romero, Gregory Sell, Daniel Povey, and Sanjeev Khudanpur, “X-vectors: Robust dnn embeddings for speaker recognition,” in *ICASSP*, 2018, pp. 5329–5333.
- [6] Weicheng Cai, Jinkun Chen, and Ming Li, “Exploring the encoding layer and loss function in end-to-end speaker and language recognition system,” in *Proc. Odyssey 2018 The Speaker and Language Recognition Workshop*, 2018, pp. 74–81.
- [7] Jesús Villalba, Nanxin Chen, David Snyder, Daniel Garcia-Romero, Alan McCree, Gregory Sell, Jonas Borgstrom, Fred Richardson, Suwon Shon, François Grondin, et al., “State-of-the-art speaker recognition for telephone and video speech: The jhu-mit submission for nist sre18.,” in *Interspeech*, 2019, pp. 1488–1492.
- [8] Yanpei Shi, Qiang Huang, and Thomas Hain, “Robust speaker recognition using speech enhancement and attention model,” in *Proc. Odyssey 2020 The Speaker and Language Recognition Workshop*, 2020, pp. 451–458.
- [9] Phani Sankar Nidadavolu, Saurabh Kataria, Jesús Villalba, and Najim Dehak, “Low-resource domain adaptation for speaker recognition using cycle-gans,” in *ASRU*, 2019, pp. 710–717.
- [10] Mufan Sang, Wei Xia, and John HL Hansen, “Open-set short utterance forensic speaker verification using teacher-student network with explicit inductive bias,” *Proc. Interspeech 2020*, pp. 2262–2266, 2020.
- [11] Danwei Cai, Weicheng Cai, and Ming Li, “Within-sample variability-invariant loss for robust speaker recognition under noisy environments,” in *ICASSP*, 2020, pp. 6469–6473.
- [12] Weiwei Lin, Man-Mai Mak, Na Li, Dan Su, and Dong Yu, “Multi-level deep neural network adaptation for speaker verification using mmd and consistency regularization,” in *ICASSP*, 2020, pp. 6839–6843.
- [13] Qing Wang, Wei Rao, Sining Sun, Leib Xie, Eng Siong Chng, and Haizhou Li, “Unsupervised domain adaptation via domain adversarial training for speaker recognition,” in *ICASSP*, 2018, pp. 4889–4893.
- [14] Wei Xia, Jing Huang, and John HL Hansen, “Cross-lingual text-independent speaker verification using unsupervised adversarial discriminative domain adaptation,” in *ICASSP*, 2019, pp. 5816–5820.
- [15] Jianfeng Zhou, Tao Jiang, Lin Li, Qingyang Hong, Zhe Wang, and Bingyin Xia, “Training multi-task adversarial network for extracting noise-robust speaker embedding,” in *ICASSP*, 2019, pp. 6196–6200.
- [16] Zhong Meng, Yong Zhao, Jinyu Li, and Yifan Gong, “Adversarial speaker verification,” in *ICASSP*, 2019, pp. 6216–6220.
- [17] Zhuoyi Wang, Yigong Wang, Yu Lin, Evan Delord, and Khan Latifur, “Few-sample and adversarial representation learning for continual stream mining,” in *Proceedings of The Web Conference*, 2020, pp. 718–728.
- [18] Sinno Jialin Pan and Qiang Yang, “A survey on transfer learning,” *IEEE Transactions on knowledge and data engineering*, vol. 22, no. 10, pp. 1345–1359, 2009.
- [19] Yoohwan Kwon, Soo-Whan Chung, and Hong-Goo Kang, “Intra-class variation reduction of speaker representation in disentanglement framework,” *Proc. Interspeech 2020*, pp. 3231–3235, 2020.
- [20] Colleen Richey, Maria A Barrios, Zeb Armstrong, Chris Bartels, Horacio Franco, Martin Graciarena, Aaron Lawson, Mahesh Kumar Nandwana, Allen Stauffer, Julien van Hout, et al., “Voices obscured in complex environmental settings (voices) corpus,” *arXiv preprint arXiv:1804.05053*, 2018.
- [21] Mohamed Ishmael Belghazi, Aristide Baratin, Sai Rajeshwar, Sherjil Ozair, Yoshua Bengio, Aaron Courville, and Devon Hjelm, “Mutual information neural estimation,” in *International Conference on Machine Learning*, 2018, pp. 531–540.
- [22] Monroe D Donsker and SR Srinivasa Varadhan, “Asymptotic evaluation of certain markov process expectations for large time. iv,” *Communications on Pure and Applied Mathematics*, vol. 36, no. 2, pp. 183–212, 1983.
- [23] Sebastian Nowozin, Botond Cseke, and Ryota Tomioka, “fgan: Training generative neural samplers using variational divergence minimization,” in *Advances in neural information processing systems*, 2016, pp. 271–279.
- [24] Yaroslav Ganin, Evgeniya Ustinova, Hana Ajakan, Pascal Germain, Hugo Larochelle, François Laviolette, Mario Marchand, and Victor Lempitsky, “Domain-adversarial training of neural networks,” *The Journal of Machine Learning Research*, vol. 17, no. 1, pp. 2096–2030, 2016.
- [25] Arsha Nagrani, Joon Son Chung, and Andrew Zisserman, “Voxceleb: A large-scale speaker identification dataset,” *Proc. Interspeech 2017*, pp. 2616–2620, 2017.
- [26] Joon Son Chung, Arsha Nagrani, and Andrew Zisserman, “Voxceleb2: Deep speaker recognition,” *Proc. Interspeech 2018*, pp. 1086–1090, 2018.
- [27] Raghuveer Peri, Monisankha Pal, Arindam Jati, Krishna Somandepalli, and Shrikanth Narayanan, “Robust speaker recognition using unsupervised adversarial invariance,” in *ICASSP*, 2020, pp. 6614–6618.
- [28] Lu Yi and Man Wai Mak, “Adversarial separation and adaptation network for far-field speaker verification,” *Proc. Interspeech 2020*, pp. 4298–4302, 2020.
- [29] Alec Radford, Luke Metz, and Soumith Chintala, “Unsupervised representation learning with deep convolutional generative adversarial networks,” *arXiv preprint arXiv:1511.06434*, 2015.
- [30] Hsin-Ying Lee, Hung-Yu Tseng, Qi Mao, Jia-Bin Huang, Yuding Lu, Maneesh Singh, and Ming-Hsuan Yang, “Drit++: Diverse image-to-image translation via disentangled representations,” *International Journal of Computer Vision*, pp. 1–16, 2020.