

Game-Theoretic Models of Moral and Other-Regarding Agents

Gabriel Istrate *

January 10, 2022

Abstract

We investigate Kantian equilibria in finite normal form games, a class of non-Nashian, morally motivated courses of action that was recently proposed in the economics literature. We highlight a number of problems with such equilibria, including computational intractability, a high price of miscoordination, and expensive/problematic extension to general normal form games. We point out that such a proper generalization will likely involve the concept of *program equilibrium*. Finally we propose some general, intuitive, computationally tractable, other-regarding equilibria related to Kantian equilibria, as well as a class of courses of action that interpolates between purely self-regarding and Kantian behavior.

Keywords: game theory; moral agents; Kantian equilibria; program equilibria; tractability.

1 Introduction

Game Theory is widely regarded as the main conceptual foundation of strategic behavior. The promise behind its explosive development (at the crossroads of Economics and Computer Science) is that of understanding the dynamics of human agents and societies and, equally importantly, of guiding the engineering of artificial agents, ultimately capable of realistic, human-like, courses of action. Yet, it is clear that the main models of Game Theory, primarily based on the self-interested, rational actor model, and exemplified by the concept of Nash equilibria, are not realistic representations of the richness of human interactions. Concepts such as *bounded rationality* [Sim97], and the limitations they impose on the computational complexity of agents' cognitive models [vRBKW19] can certainly account for some of this difference. But this is hardly the only possible explanation: People behave differently from ideal economic agents not because they would be irrational [Ari10], but because many instances of human interactions are cooperative, rather than competitive [Tom09], guided by social

*West University of Timișoara, Timișoara, Romania. email:gabrielstrate@acm.org

norms such as *reciprocity*, *fairness* and *inequity-aversion* [BG13], often involving *networked minds*, rather than utility maximization performed in isolation [Gin16], guided by moral considerations [Tom16] or by other behaviors that are not purely self-regarding, including *altruism* [HS13] and *spite* [CK08, CM16].

Moral considerations (should) interact substantially with game theory: indeed, the latter field has been used to propose a reconstruction of moral philosophy [Bin94, B⁺94, Bin05]; conversely, some philosophers have gone as far as to claim that we need a *moral equilibrium theory* [Tal98]. Whether that's true or not, it is a fact that *homo economicus*, the Nash optimizer of economics, is increasingly complemented by a rich emerging typology of human behavior [Gin20], that also contains (in Gintis's words) "*homo socialis*, the other-regarding agent who cares about fairness, reciprocity, and the well-being of others, and *homo moralis* [¹] ... the Aristotelian bearer of nonconsequentialist character virtues" [²]. These claims are well-documented experimentally: for instance, Fischbacher et al. [FGF01] investigated the percent of people having self-regarding preferences in a public goods game, showing that it is in the range of 30-40%, while the remaining were either other-regarding or moral agents.

Insofar as artificial agents (will) interact with humans, such concerns are highly relevant to the design of multiagent systems as well. Similar ideas have, indeed, been expressed before: to give just a couple of examples, in [Kam13] a challenge was made "to cure robot autism". To accomplish this one would need (according to [Kam13]) to "build better *socially-capable robots* by relying on general *social intelligence* building blocks, built into the brains of robots, rather than grafted on per mission". Rong and Halpern [HR10, RH13] have investigated some interesting "cooperative equilibria". Closer to the present, in their prize-winning Blue-Sky paper from AAMAS'20 Dignum and Dignum [DD20] explicitly note that, for multiagent systems purposes, agent rationality is not sufficient to model human behavior, "which is based on split second decisions, on habits, on social conventions and power structures". Such non-self-regarding behaviors call for game-theoretic formalizations: A standard approach (e.g. [FS99]) is to encode moral/other-regarding considerations as *externalities* into agents' perceived utilities, that may lead them away from straightforward maximization of their material payoffs. However, such a specification leaves out other important ingredients, e.g. epistemic preconditions on acting.

The requirement of implementation in computational agents imposes specific constraints on the target game-theoretic concepts: to be efficiently implementable, such concepts should at least be: (1) *expressive*, i.e. indicative of realistic behavior of human agents in sufficiently typical situations (2) *cognitively plausible*: models should not be justifiable in terms of expensive epistemic assumptions (the way common knowledge of rationality can be used to justify

¹since our agents are not necessarily human, we will use alternate names such as "moral agent" for this type of behavior.

²Gintis proposes a taxonomy of behavior with three distinct types of preferences: *self-regarding*, *other regarding* and *universalist*; a further relevant distinction is between so-called *private* and *public personas*, that leads to further types of behavior such as *homo Parochialis*, *homo Universalis* and *homo Vertus*. See [Gin20] for further details.

Nash equilibria [AB95]); (3) *tractable*: equilibria of proposed models should be easy to specify formally, in a way that translates to efficient implementations. They should also be tractable, since boundedly rational agents are assumed to often display them.

The purpose of this paper is to contribute to the emerging literature on non-Nashian, morally inspired game theoretic concepts and, equally important, to bring its concerns and methods to the attention of the algorithmic game theory and multiagent systems communities in Artificial Intelligence. We are inspired by what we believe is one of the most intriguing classes of equilibrium concepts that can be seen as morally grounded: *Kantian (a.k.a. Hofstadter) equilibria*. This notion emerged from two separate lines of research converging on an identical mathematical definition, but justifying it, however, from two very different perspectives: *superrationality* [Hof85, Fou20] and *Kantian optimization*, respectively [Roe19].

The common framework (crisply developed, so far, for symmetric coordination games) only considers as relevant the action profiles where all agents choose *the same course of action*, choosing the action x that, if played by everyone, maximizes agents' (identical) utility functions. This choice has been justified from two very different epistemic (and moral) positions: first, *superrationality* assumes that if rationality constrains an agent to choose a specific course of action x , then the same reasoning compels **all** agents (at least in the case of symmetric games, when all agents are positionally indistinguishable from the original agent) to also choose x . To cite Hofstadter: "If reasoning dictates an answer, then everyone should independently come to that answer. Seeing this fact is itself the critical step in the reasoning toward the correct answer [...]". Though superrationality does away with the assumption of counterfactual independence of Nash equilibria, it is otherwise compatible with a particular version of homo economicus that requires some very strong assumptions on agent rationality (see [Fou20] for a discussion).

In contrast, *Kantian optimization* justifies the limitation to symmetric profiles in a very different manner: developing early ideas of Laffont [Laf75], Roemer [Roe10] suggested that agents often ignore the potential for action of the other players, acting instead according to the *Kantian categorical imperative* [Sed08] "act only according to that maxim whereby you can, at the same time, will that it should become a universal law", that is, choose a course of action that, if adopted by every agent, would bring all agents the highest payoff. One way to formalize this idea, employed e.g. in [AW13], is to decouple the *material payoffs* agents receive in a game from their (perceived) utility, which is the one they maximize in order to select the course of action. Specifically, assume the given agent i plays strategy x against action profile y . We will assume that the material payoff the agent receives is $\pi_i(x, y)$. On the other hand the utility the agent uses to evaluate playing x may not be equal to $\pi_i(x, y)$ and may (in extreme cases) have in fact nothing to do with y at all! In particular, the utility of a Kantian agent i playing x against action profile y is

$$u_i(x, \mathbf{y}) = \pi_i(x, \bar{x}_{-i}), \tag{1}$$

where \bar{x}_{-i} is the action profile where all agents other than i play action x as well. In other words, the agent evaluates the desirability of action x in isolation from the potential actions of the other players, as if choosing strategy x could somehow "magically" determine the other players to adopt the same strategy [3]. An alternate interpretation is that $\pi(x, \bar{x}_{-i})$ measures the extent to which action x is "the morally best course of action". Such a behavior is cognitively plausible: people often informally justify their choices in this way.

The questions we attempt to start answering in this paper are:

1. Do (mixed) Kantian equilibria, perhaps suitably extended to general games, satisfy the requirements outlined above ?
2. (How) can one naturally extend the existing definition of (mixed) Kantian equilibria to general games ?
3. If the answer to question 1 is negative: Can we, alternatively, define notions of other-regarding equilibria that satisfy them ?
4. Finally: in real life agents display a continuum of behaviors between selfish and Kantian. (How) can we formalize this ?

The outline of the paper is as follows: In Section 2 we review some basic notions. In Section 3 we obtain some further results on (and highlight some limitations of) Kantian equilibria: first of all, we point out that finding a mixed Kantian equilibrium is computationally intractable even for two-player symmetric games (Theorem 2). Second, multiple Kantian equilibria may exist, and lack of coordination on the same equilibrium may be detrimental to players, even with all of them playing a common linear combination of Kantian actions. In Subsections 4.1 to 4.4 we discuss the problem of extending Kantian equilibria to non-symmetric games. We highlight problems of existing proposals, and give an alternative one based on the concept of program equilibria. As such, our proposal inherits the problems of this concept. Given these problems, in Section 5 we propose several other-regarding equilibria [4]. We show (Theorem 5) that these equilibria can be computed efficiently, then (Theorem 6) that they are indeed Kantian equilibria (according to our generalized definition), and that they yield Kantian equilibria for symmetric coordination games. Finally, in Section 6 we relax the assumption that the agents are other-regarding: in the framework we propose agents have a degree of greed, zero for Kantian agents, infinite for Nashian agents. We show (Theorem 8) how our definition applies to Prisoners' Dilemma.

³Frank [Fra04] refers to this as *voodoo causation*. Elster [Els17] argues that Kantian optimization seems to be rooted in a form of *magical thinking*, "causing agents to act on the belief (or act as if they believed) that they can have a causal influence on outcomes that are effectively outside their control".

⁴Generally self-regarding and moral behavior are not regarded as equivalent; counterexamples exist, [Ran64]; however, it's fair to say that such positions are controversial, and somewhat marginal. In contrast, moral and other-regarding behaviors are more closely related, with other-regarding behavior often a consequence of moral play.

2 Preliminaries

We assume knowledge of basic results of game theory at the level of a textbook such as, e.g. [OR94], in particular with concepts such as normal form games, best response strategy, and mixed (Nash) equilibria. All the games G we consider are normal form and, unless mentioned otherwise, have identical action sets Act_G for all players. Given a finite set S , we will define $\Delta(S)$ to be the set of probability distributions on s . Elements of $\Delta(S)$ are functions $c : S \rightarrow [0, 1]$ satisfying $\sum_{i \in S} c(i) = 1$. $\Delta^n := \Delta(\{1, 2, \dots, n\})$ is, geometrically, a $(n - 1)$ -dimensional simplex. When G is a normal-form game and k a player in the game we will denote by Δ_G^k the set of mixed actions available to player k , identified with some simplex Δ^n with a suitable dimension. We will occasionally drop k from the notation and simply write Δ_G instead when the player is clear from the context, or when all agents have the same action set.

Given vectors $x = (x_1, \dots, x_n)$ and $y = (y_1, \dots, y_n)$, we say that x *dominates* y iff $x_i \geq y_i$ for all $i = 1, \dots, n$. The domination is *strict* if at least one inequality is. When comparing (mixed) action profiles \mathbf{a} and \mathbf{b} , the domination relation may apply to the vectors of agent utilities $(u_1(\mathbf{a}), \dots, u_n(\mathbf{a}))$ and $(u_1(\mathbf{b}), \dots, u_n(\mathbf{b}))$, respectively. Action profiles that are strictly dominated may be assumed not to occur in game play. A stronger form of rationality is *individual rationality*. We refrain from giving a formal definition (referring, e.g., to [Fou20]), but in a nutshell individual rationality discards those action profiles in which some agent gets a utility lower than what he could guarantee for itself independently of other players.

A game with identical action sets is *diagonal* if every pure action profile is dominated by some profile on the diagonal, i.e. the set of action profiles where all players play the same action. A particular class of diagonal games are *coordination games*, those where all player utilities are zero outside of the diagonal. Such a game is *symmetric* if, additionally, agent utilities are identical for all action profiles on the diagonal.

Definition 1. *Let G be a symmetric game. A Kantian (Hofstadter) equilibrium (action) is a pure strategy x^{opt} that maximizes the material payoff of the agent, should everyone play similarly. Formally $x^{opt} = \operatorname{argmax}[\pi(x, x, \dots, x) : x \in Act_G]$. A Kantian agent will play, of course, a Kantian action to maximize its utility.*

Example 1. *One of the original applications of Kantian equilibria was Prisoners' Dilemma, whose payoff matrix we reproduce in Figure 1 a. Kantian equilibria provide an elegant solution to the paradox. Indeed, while the unique Nash equilibrium is (D, D) , Kantian agents will coordinate on action profile (C, C) , as jointly selecting action C is giving them a higher payoff than D .*

Kantian equilibria are easiest to justify for symmetric diagonal games, since in this case Kantian equilibria dominate all other action profiles, and can be properly seen as "best course of action for all". There are symmetric (nondiagonal) games, though, where no pure strategy Kantian equilibrium is adequate,

| | | | |
|----------|---|----------|------|
| | | Player 2 | |
| | | C | D |
| Player 1 | C | 2, 2 | 0, 3 |
| | D | 3, 0 | 1, 1 |

| | | | |
|----------|---|----------|------|
| | | Player 2 | |
| | | B | S |
| Player 1 | B | 2, 1 | 0, 0 |
| | S | 0, 0 | 1, 2 |

Figure 1: a. Prisoners' Dilemma. b. Bach or Stravinsky.

and which seem to compel us to considering mixed-strategy Kantian equilibria. A convincing example is Hofstadter's "Platonia's Dilemma" [Hof85], a special case of the *market entry games* of Selten and Güth [SG82]:

Definition 2. *n* agents (say, $n = 20$) are offered to win a prize. Agents may choose to send their name to a referee. An agent wins the prize if and only if it is **the only one submitting their name**: if zero or at least two agents send their names then noone wins anything.

It is easy to see that both pure strategies, sending/not sending their name, are equally bad if adopted by all agents: they get zero payoff. A better option is to allow independent randomization:

Definition 3. Given a game G with identical actions, a **mixed Kantian agent** will choose a mixed strategy $X^{OPT} \in \Delta_G$ that maximizes its expected utility, should everyone play X . For two-player symmetric games with game matrix A

$$X^{OPT} = \operatorname{argmax}\{y^T Ay : y \in \Delta_G\} \tag{2}$$

The mixed Kantian equilibrium in Platonia Dilemma is given by the following:

Lemma 1. *The probabilistic strategy where each agent independently submits their name with probability p , so that the expected number of agents submitting their name is 1, brings an expected profit to every agent equal to $p(1-p)^{n-1}$. This quantity is maximized for $p = \frac{1}{n}$. Thus the strategy with $p = \frac{1}{n}$ is a mixed Kantian equilibrium.*

Proof. Let $f(p) = p(1-p)^{n-1}$. $f'(p) = (1-p)^{n-1} - (n-1)p(1-p)^{n-2} = (1-p)^{n-2}(1-np)$, so f is increasing on $[0, 1/n]$ and decreasing on $[1/n, 1]$. \square

3 Limitations of Kantian Equilibria

We next note some properties of Kantian equilibria. They are mostly negative: finding a mixed Kantian equilibrium is intractable. Also, Kantian equilibria are vulnerable to miscoordination.

3.1 The Computational Complexity of Mixed Kantian Equilibria

First we make an easy observation concerning the computational complexity of mixed Kantian equilibria in symmetric two player games. To our knowledge this has not been discussed before. A simple note: such equilibria are guaranteed to exist, since the $(n - 1)$ -dimensional simplex of mixed strategies is a compact set and the common utility function is continuous.

Finding a mixed Kantian equilibrium is easy in symmetric coordination games, as all such equilibria coincide with pure Kantian equilibria.

Theorem 1. *Consider a symmetric coordination game. Then mixed Kantian equilibria coincide with pure Kantian equilibria. Consequently one can compute mixed Kantian equilibria in polynomial time.*

Proof. $E[p] = \sum_{i,j} a_{i,j} p_i p_j \leq \max_{a_{i,i}} \sum_{i,j} p_i p_j = \max_{a_{i,i}} (\sum_k p_k)^2 = \max_{a_{i,i}} a_{i,i}$. \square

Note that the Platonia Dilemma game with $n = 2$ shows that the result is not true for general symmetric games. This is no coincidence: as soon as we move beyond two-player symmetric coordination games, finding (or merely detecting) the optimal mixed strategy becomes in fact intractable:

Theorem 2. *The following problem is NP-hard:*

INPUT: A two-player symmetric game G , and an aspiration level $r \in \mathbb{Q}$.

TO DECIDE: Is there a mixed strategy profile $x = (x_1, \dots, x_N)$ such that the utility of every player under mixed action $x_1 a_1 + x_2 a_2 + \dots + x_m a_m$ is at least r ?

Proof. An easy restatement of the problem of detecting a mixed Kantian equilibrium $x = (x_1, \dots, x_N)$ is the following continuous quadratic optimization problem:

$$\begin{cases} \max(x^T A x) \\ x_1 + \dots + x_N = 1 \\ x_1, \dots, x_N \geq 0. \end{cases} \quad (3)$$

This is a problem that has been called [Bom98] *the standard quadratic optimization problem*, and has been investigated substantially in the global optimization literature (see e.g. [Bom97]). A beautiful result due to Motzkin and Straus [MS65] can be restated as claiming that for symmetric games whose payoff matrix is the adjacency matrix of a graph g , if f is the optimum of problem (3) then $\frac{1}{1-f}$ is the size of the maximum clique in g . Deciding whether such a restricted game has a Kantian equilibrium with payoff at least r is equivalent to deciding whether the maximum clique in the associated graph has size at least $\frac{1}{1-r}$. This latter problem is, of course, NP-complete. \square

| | | | | |
|----------|---|----------|------|------|
| | | Player 2 | | |
| | | C | D | E |
| Player 1 | C | 5, 5 | 3, 6 | 1, 2 |
| | D | 6, 3 | 4, 4 | 6, 3 |
| | E | 2, 1 | 3, 6 | 5, 5 |

| | | | |
|----------|---|----------|------|
| | | Player 2 | |
| | | B | S |
| Player 1 | B | 6, 1 | 0, 0 |
| | S | 0, 0 | 3, 2 |

Figure 2: a. A game with multiple Kantian equilibria. b. Modified Bach or Stravinsky.

3.2 Multiple Equilibria and miscoordination

Optimal diagonal action profiles may fail to be unique. If the agents are not communicating (and no implicit coordination mechanisms are acting, e.g., one of the action profiles being a *focal point*, such as in the Hi-Lo game from [Bac06]), agents may reach a suboptimal action profile due to their lack of coordination on the same optimal action: Consider, indeed, the game in Figure 2. In this game (C, C) and (E, E) are equally good pure (and mixed) Kantian equilibria. But if one player plays C and the other plays E the resulting outcomes are the worst possible for both of them, being dominated by every single possible strategy profile ! Randomizing among Kantian actions might not help either: miscoordination impacts even scenarios with a "Kantian" flavor, where players, lacking a "focal" Kantian equilibrium to coordinate on, play a joint mixed strategy formed of Kantian actions only. We quantify the degradation in performance in such a scenario as follows:

Definition 4. For a symmetric game G with strictly positive payoffs let NC be the set of mixed action profiles whose individual strategies in their support are all Kantian actions. The price of miscoordination of G is the ratio

$$p(G) = \sup_{a \in NC} \frac{u_i(X^{OPT})}{u_i(a)}. \quad (4)$$

Because of the game symmetry the definition above does not depend on the particular choice of player i .

The following result shows that the price of miscoordination can be arbitrarily large, and that its magnitude may be influenced by the the number of pure Kantian equilibria:

Theorem 3. Let G be a symmetric diagonal game with $k \geq 2$ players and $r \geq 1$ pure Kantian actions. Then the price of miscoordination of G is in the range $[1, r^{k-1}]$. Both bounds are tight and can be reached when players choose a Kantian action uniformly at random.

Proof. The price of miscoordination is insensitive to dividing all utilities by the same factor λ , so w.l.o.g. one may assume that the utilities agent receive on pure Kantian equilibrium profiles is 1. For the mixed action \mathbf{a} where players play

the r Kantian actions (w.l.o.g. $1, 2, \dots, r$) with probabilities p_1, p_2, \dots, p_r (which add up to 1), its expected utility is $E[u_i(\mathbf{a})] = \sum u_i(i_1, i_2, \dots, i_k) \cdot p_{i_1} p_{i_2} \dots p_{i_k} \geq \sum_{i=1}^r p_i^k \geq r \cdot \frac{1}{r^k} = \frac{1}{r^{k-1}}$, by Jensen’s inequality. The upper bound is obtained when off-diagonal action profiles formed of Kantian actions only have utilities equal to 0. As for the lower bound, for diagonal games by domination we have $u_i(i_1, i_2, \dots, i_k) \leq 1$, so $E[u_i(\mathbf{a})] = \sum u_i(i_1, i_2, \dots, i_k) \cdot p_{i_1} p_{i_2} \dots p_{i_k} \leq \sum p_{i_1} p_{i_2} \dots p_{i_k} = (p_1 + p_2 + \dots + p_r)^k = 1$. A game realizing the lower bound is the one where agent utilities on all pure action profiles are equal to 1. \square

4 Generalizing Kantian Equilibria

The definition of Kantian equilibria makes the most sense in symmetric coordination games. A natural problem is to extend it to more general settings. In this section we review three such possible extensions and argue that they are not appropriate. We then give what we believe is a general (but unfortunately ineffective) definition of Kantian equilibria, as symmetric *program equilibria*.

4.1 Hofstadter equilibria in general games

Since we are looking to extend the definition of Kantian optimization from symmetric coordination to general games, we first note that such extensions exist under the other paradigm employed to define Kantian equilibria, superrationality: Kant-Hofstadter equilibria have recently been extended to non-symmetric games in [Fou20]. The so-called *perfectly transparent equilibrium* (PTE) relies on the iterated elimination of strategies that are not individually rational. For games without ties, that is those where an agent is never indifferent between two action profiles, Fourny proves that at most one action payoff can be a PTE. These facts suggest that one should at least consider PTE as candidates for the extension of Kantian equilibria. Unfortunately, they seem rather unsuitable. The following are some objections against PTE:

1. A first objection is epistemic complexity: PTE require knowledge of rationality in *all possible worlds*, which is stronger than common knowledge. Also, Beard and Bail [BB94] have experimentally shown that people do not always adequately perform even two levels of iterated elimination of dominated strategies (for a review of the experimental literature see Chapter 12 of [Dha16]). The elimination process leading to a unique PTE is at least equally (if not more) cognitively expensive, since each round is based on a more complicated type of rationality assumption (individual rationality versus domination), also employing multiple rounds. Thus PTE are implausible from a bounded rationality perspective.
2. A second problem of PTE is that they do not alleviate the problem of multiple equilibria and miscoordination: Fourny [Fou20] acknowledges this problem, and only defines PTE for games without ties, for which this issue does not exist.

3. A final, and most daunting, objection against PTE is that *they produce problematic predictions*: in the game in Fig. 3 (see [BDS19]), for instance, the unique PTE is (C, C) . However, (C, C) is dominated by both (C, S) and (S, C) (and convex combinations thereof) hence it is difficult to justify C as "the action that is best for all".

4.2 Berge Equilibria

Berge (or Berge-Zhukovsky) equilibria are another class of cooperative equilibria. Originally defined in Berge's monograph [Ber57], they were studied in the Soviet Union [Zhu85, ZK17], while remaining relatively obscure, until recently, in the English-language literature. Formally, an action profile $x^* = (x_1^*, x_2^*, \dots, x_n^*)$ is a *Berge equilibrium* if for every player i and every partial profile x^{-i} , $u_i(x_i^*, x^{-i}) \leq u_i(x^*)$. In other words, the partial profile chosen by all but one of the agents is optimal for the remaining agent, given its chosen action.

Kantian equilibria of symmetric coordination games coincide with Berge equilibria. One could naturally hope that this extends to general games. But this is not the case: Even though Berge equilibria are an intriguing concept, worthy of further investigations, sadly they are inappropriate as extensions of Kantian equilibria. First, there are three-player games [PBF19] admitting no mixed-strategy Berge equilibria, and deciding the existence of mixed-strategy Berge equilibria is NP-complete [NC18]. For two-player games Berge equilibria correspond [CKMT11] to the Nash equilibria of a modified games. In particular the seminal existence theorem for mixed Nash equilibria guarantees the existence of Berge equilibria in this case. Second, Berge equilibria capture indeed one aspect of the Kantian categorical imperative, that of players choosing a course of action that is "best for everyone". But *they fail to explicitly capture the other one, that of all players doing, in some sense, "the same thing"*. They are also vulnerable to miscoordination: an example is the game Bach or Stravinsky ([OR94], see Figure 1 b.). Here the two agents may agree that they should choose the same action, but don't necessarily agree on *which one*. Nor is the "obvious" mixed strategy $\frac{1}{2}C + \frac{1}{2}S$ a suitable alternative. While it is the unique Berge equilibrium, it is **not** a Kantian equilibrium: the expected player payoff, $\frac{3}{4}$, is inferior to what they would get under either of (C, C) or (S, S) !

4.3 Correlated equilibria

The problem with the previous mixed strategy profile arose from miscoordination. A conclusion is that one may need to give up the assumption that players are choosing their actions independently, and assume, instead, some form of *team reasoning* [Bac06] based on *correlated strategy profiles*, and perhaps, some version of *correlated equilibria* [Aum74]. Such a choice could seem natural at first: Gintis [Gin09, Gin10] convincingly argues that correlated equilibria are more natural than Nash equilibria, and can model a wide variety of social phenomena, including social norms. Also [GZ89], unlike Nash equilibria, computing

correlated equilibria is tractable. Many of the examples of other-regarding game-playing we give in this paper can, indeed, be modeled with correlated equilibria. However, the mathematical definition of correlated equilibria (see e.g. [SLB09]) does not directly address the issue of "the two agents doing the same thing". Also, since all Nash equilibria are correlated equilibria, *some symmetric games have correlated equilibria that can hardly be intuitively classified as "Kantian"*. This is the case of the game *chicken* [OR94], whose two Nash equilibria corresponding to one player yielding to the other one are also correlated equilibria [PR08]. This example also shows that simply eliminating strictly dominated equilibria does not help, since it would not eliminate these "bad" equilibria.

4.4 Kantian Program Equilibria

We propose next a definition that formalizes (a generalization of) the Kantian imperative in a substantially more transparent way.

Let us continue with the example of the Bach or Stravinsky game. Intuitively, agents would perhaps agree that the following **protocol** could be called Kantian, in that it is symmetric and both players would benefit if they both followed it: flip a fair coin; if it comes out *heads*, they (both) play *C*, else they play *D*.

As described, the protocol requires the centralized choice of a random bit, but it could easily be implemented in a distributed manner by making each of the two agents flip a (fair) coin and taking their XOR. The implementation of the protocol (given as Algorithm 4.1) is parameterized by an *agent ID* $i \in \{1, 2\}$ (not needed in this particular case) and vector $(myb, otherb)$ of random bit choices, one for each player, and shared between players.

Algorithm 4.1: BOS($i :: ID, myb :: BIT, otherb :: BIT$)

```

Randomly choose a bit  $myb \in \{0, 1\}$ 
communicate  $mybit$  to the other player as its  $otherb$ .
if [ $myb \oplus otherb == 0$ ]
  then play  $C$ 
  else play  $D$ 

```

An even more dramatic case is that of the game from Figure 3 a., where the best outcomes are not symmetric. As seen before, in these cases it even seems irrational for the agents to play symmetric action profiles, since these action profiles are dominated by all the other action profiles ! Rather, it is plausible that agents would agree that they need to **anticoordinate**, but they have different preferences for the joint action profile to coordinate upon. A solution to this problem is to choose a random anti-coordinated profile, that is jointly play what could be denoted $\frac{1}{2}(C, S) + \frac{1}{2}(S, C)$. As in the previous example, this course of action can be implemented by the two agents in a distributed manner, by

jointly playing according to the protocol in Algorithm 4.2. In this example, in addition to the extra bit *otherb* communicated by the other player, the protocol of each agent makes explicit use of the agents' own *id*, $i \in \{1, 2\}$.

| | | | | | |
|-------|---|----------|----------|-------|------|
| | | Pl. 2 | | Pl. 2 | |
| | | C | S | C | D |
| Pl. 1 | C | 10, 10 | 100, 200 | 10, 1 | 0, 0 |
| | S | 200, 100 | 6, 6D | 0, 0 | 4, 2 |

Figure 3: a. An anti-coordination game. b. Modified BoS.

Algorithm 4.2: ANTICOORD($i :: ID, myb :: BIT, otherb :: BIT$)

Randomly choose a bit $myb \in \{0, 1\}$
communicate myb to the other player as its $otherb$.
if $myb \oplus otherb \equiv i \pmod{2}$ then play C
else play S

The intuitive conclusions of these two examples are simple: even in non-symmetric games there may exist coordinated **protocols** that could properly be called "Kantian". To formalize this idea we will connect Kantian optimization to **program equilibria** [How88, Ten04] (see also [For09, KKLS10, vdHWW13, LFY⁺14, BCF⁺14, Cri19, Oes19]). Briefly, to every finite game in normal form one associates an extended game. Actions in this game correspond to players choosing *programs* P . Agents' programs have access to own and other players' program sources, and can act on them. An instruction, $DO(x)$, with x a mixed strategy profile, allows the agent to sample actions from x . The full semantics of program equilibria is a slight variant (modified according to the remarks below) of the one for program equilibria in the Appendix of [Ten04]. For lack of space we defer a full presentation to the journal version of this paper. A couple of technical points are, however, in order:

- The model in [Ten04] does not allow explicit random choices, other than the ones encoded via $DO(\cdot)$ instructions. We do. However, to enforce symmetric behavior we will essentially *disallow private randomness*: all agents' random choices will be shared through *input variables* (another feature missing from the model in [Ten04]). For the same reason, game payoffs will not be "hard-coded" into the program, but given via "oracle calls", with parameters agent id and strategy profiles. Finally, the Kantian imperative motivates the assumption that *players should have the same action sets*.
- The information exchanged by the agents may be numerical, but we will assume it "cannot mix" with numerical data considered internally in the program. In particular we cannot compute probabilities based on such information, we cannot compare an ID (or expression based on ID's) against

a probability, etc. An easy way to implement such a restriction is to assume that input variables (including ID) are *typed*, and ID types (or of any other shared information) cannot be added/multiplied with/compared with real numbers, unless real themselves. Of course, there is no restriction against adding, multiplying, comparing pieces of input data when their types support these operations. If we didn't have such a restriction then we could implement some "weird" mixed action profiles by "symmetric" programs, with agents using their ID's to compute different probabilities, etc.

- All agents know their own ID and can individualize the information they sent to other agents, but shouldn't be able to infer the source of any other information, in order to make the protocol symmetric. This introduces a problem with the syntax of program equilibria for more than two players: the symmetric Kantian program should not depend on the identity of variables whose values are set by the other agents. One solution to this problem is to assume the existence of a special kind of agent called *mediator* [MT09]. This agent receives the information from all agents, and sends to each i the multisets of *aggregated data received from other agents*. This will allow us to force notation, as in Algorithm 4.3 below, writing b_1, b_2, \dots, b_n for the arguments of the algorithm, even though, strictly speaking agent i 's program only knows which b_i is its own and which ones are not.
- Just as for Prisoners' Dilemma [Ten04, MT09], a Kantian agent playing program P can make sure it is not taken advantage upon by the other players, either alone, as in [Ten04], by reading other players' programs (players are translucent [CH15, HP18]) and only playing P when all do, or with the help of a *mediator*. In this latter case, the mediator implements on behalf of all players the following protocol: if all agents follow P then the mediator will simulate P on behalf of the agent; otherwise it will play in a Nashian way.

These considerations finally allow us to propose the following

Definition 5. *Given a game G with identical actions sets for all players, a Kantian (program) equilibrium in G is a probability distribution p on the action profiles of G that:*

- a. p has its support on the set of undominated strategies.
- b. p is implemented by a symmetric program equilibrium.
- c. there exists no probability distribution q with properties a. and b. such that the vector of expected utilities $(E[u_i(q)])$ strictly dominates the vector $(E[u_i(p)])$.

Point a. encodes the simple rationality condition for mixed equilibria. Point b. and c. embody a generalized implementation of the Kantian categorical imperative: point b. encodes the constraint of symmetric behavior, while point c. encodes the fact that implementing p is "the best action" for all players.

Example 2. *Definition 5 allows players to obtain a better expected payoff in Hofstadter's Platonian's Dilemma than the mixed strategy equilibrium, implementing the following informal strategy (Algorithm 4.3): a random agent submits its name, all other don't.*

Theorem 4. *The action profile implemented by Algorithm 4.3 is a Kantian program equilibrium for the Platonica Dilemma game.*

Proof. Points a. and b. from the definition of Kantian program equilibria are clear, the only one that merits a discussion is point c.

The expected utility of each player under Algorithm 4.3 is equal to $1/n$. Since the sum of utilities of all players under a particular set of random choices is equal to 1, no vector of expected utilities can strictly dominate the vector $(1/n, 1/n, \dots, 1/n)$ of expected utilities for the Algorithm. \square

Algorithm 4.3: CHOOSE-WINNER(i, b_1, b_2, \dots, b_n)

```

Randomly choose an integer  $b_i \in \mathbb{Z}_n$ 
if  $[\sum_{j=1}^n b_j \equiv i \pmod{n}]$ 
  then submit  $i$ 
  else don't submit anything.

```

5 Some computationally efficient other-regarding equilibria

As defined in the previous section, Kantian program equilibria for games with identical action sets inherit the problems of program equilibria, and display some new ones. Among them:

- *fragility* (see e.g. [Oes19]): (Kantian) program equilibria are sensitive to the precise specification of programs: do we insist that all agents use syntactically identical programs, or just ones that "do the same thing" ? See [LFY+14, vdHWW13] for some attempted solutions for program equilibria that could be adapted to our setting.
- *lack of generality*: Definition 5 it is only applicable to games with identical action sets. To further generalize it one would need to specify what it means for two agents to "take the same course of action". One possibility is to define such a notion explicitly. This is what Roemer attempted, for instance, by defining *multiplicative Kantian equilibria*, where two players taking the same action (in his setting by a real number, a *production level*) meant multiplying their production level by the same amount.
- *lack of predictive power*: when some of the agents win more than the other ones, what does a mixed strategy profile being "best for all agents" even mean ? As we will see below, there are multiple courses of action that are Kantian program equilibria according to Definition 5, giving different answers to the previous question.

- *lack of efficient computational mechanisms for finding Kantian program equilibria.*

Given these objections, and with the tractability constraints outlined in the introduction in mind, we propose in the sequel a more modest approach: Rather than seeking a general definition of Kantian equilibria we propose instead not one, but *several* notions of other-regarding equilibria. **They all correspond intuitively to real-life situations, are general, tractable, and have implementations satisfying Definition 5.** Some of them were independently suggested in [Kor16], others are first introduced here:

Definition 6. *A Rawlsian equilibrium is a probability distribution over undominated profiles that maximizes the egalitarian social welfare [CEL⁺06] (i.e. the expected utility of the worst-off player) and is strictly dominated by no other profile with this property. Rawlsian equilibria implement the idea of justice as fairness [Raw01].*

Example 3. *We modify the BoS example by tripling the payoffs of player 1, so that it wins more than the other player: perhaps player 1 is a classical music lover, that gets a higher utility than the other player by going, together with its partner, to any of the two concerts. Then (S,S) is the (unique) Rawlsian equilibrium. Choosing such an equilibrium is an example of altruistic behavior from player 1, since it maximizes the payoff of its non-music-lover partner.*

Definition 7. *A Bentham-Harsányi equilibrium is a probability distribution over undominated profiles maximizing the sum of expected payoffs. See [Har55] for a philosophical motivation.*

Definition 8. *A best-off equilibrium is a probability distribution over undominated profiles maximizing the largest expected payoff, and is strictly dominated by no profile with this property.*

Example 4. *In Example 3 (B,B) is the unique Bentham-Harsányi equilibrium, as well as the unique best-off equilibrium.*

Although a best-off equilibrium does not seem "fair", there exist real-life situations that elicit behavior suggestive of such an equilibrium: one such example is, for instance, members of a couple making sacrifices for their more successful partner (or for a child).

So far the equilibrium notions we introduced were implicitly assuming that player utility is given by material payoffs. Sometimes the frustration a player may feel is not expressed in absolute utility terms, but in counterfactual ones, by comparing the actual outcome with all other possible ones. There are many ways to measure frustration. The following notion quantifies the extent to which a given profile is worse for the given player than a random profile.

Definition 9. *The percentile index of a profile a for player i is the percentage of pure action profiles that would get i a strictly better payoff than a . We exclude dominated profiles from the computation of the index. Players with the smallest expected utility have percentile index 0 in Rawlsian equilibria, while for best-off equilibria the same is true for players with the largest expected gains.*

Example 5. We modify the BoS example as shown in Figure 3 b. Then percentile indices of undominated profiles are $(0, 100)$ for profile (C, C) , and $(100, 0)$ for profile (D, D) , respectively.

Definition 10. A Rawlsian percentile equilibrium is a profile minimizing the largest expected percentile index among all players, and is strictly dominated by no profile with this property.

Example 6. In Example 5, profile $\frac{1}{2}(C, C) + \frac{1}{2}(D, D)$ is a Rawlsian percentile equilibrium. Player 1 gets average utility 7 while player 2 gets average utility $\frac{3}{2}$.

The previous definition used a rather cognitively sophisticated notion of agent "happiness". An even simpler alternative is:

Definition 11. The natural expectation point of player i is the median (over all undominated pure strategy profiles) payoff it receives. If there are two medians then the average value is taken. A player is happy in a pure strategy profile a iff its payoff is larger or equal than its natural expectation point and unhappy otherwise.

An aspiration equilibrium is a mixed strategy profile that minimizes the largest probability of unhappiness among all players and is strictly dominated by no other profile with this property.

Example 7. Take a coordination game with payoffs $(C, C) \rightarrow (10, 1)$, $(D, D) \rightarrow (9, 2)$, $(E, E) \rightarrow (8, 3)$, $(F, F) \rightarrow (4, 7)$. The natural expectation points of players are $\frac{9+8}{2} = 8.5$ and $\frac{2+3}{2} = 2.5$, respectively. The first player is happy on (C, C) and (D, D) , the second on (E, E) , (F, F) . Consequently on $\frac{1}{4}(C, C) + \frac{1}{4}(D, D) + \frac{1}{4}(E, E) + \frac{1}{4}(F, F)$ the two players are happy 50% of the time and no mixed action profile can do any better, so the profile is an aspiration equilibrium.

Unlike Kantian ones, the equilibria we defined are tractable:

Theorem 5. Rawlsian, Rawlsian percentile, Bentham-Harsányi, best-off, aspiration equilibria always exist, and can be found by solving a sequence of linear programs (hence in polynomial time in the number of players plus the number of undominated action profiles).

Proof. In all cases we will enforce undomination using the following simple idea: suppose we have found a set of candidate equilibria that have all desired properties except domination. Maximizing social welfare over the candidate equilibria will give us the desired equilibrium, since the profile maximizing social welfare among candidates cannot be strictly dominated by any other one.

Indeed, let P_1, P_2, \dots, P_m be the undominated profiles and, for every P_j and player i , let $p_{i,j}$ be the utility player i gets from profile P_j . To find a Rawlsian equilibrium we first solve the LP (5). This computes the egalitarian social welfare z^* . Now solve system (6). This yields a profile (x_1^*, \dots, x_m^*) which, by our observation, is a Rawlsian equilibrium. The same programs with a different semantics for $p_{i,j}$ as the percentile of P_j among undominated profiles from the point of view of i , computes Rawlsian percentile equilibria.

$$\begin{cases} \max(z) \\ p_{i,1}x_1 + \dots + p_{i,m}x_m \geq z, i = 1, \dots, n \\ x_1 + \dots + x_m = 1 \\ x_i \geq 0. \end{cases} \quad (5)$$

$$\begin{cases} \max(\sum_{i=1}^n p_{i,j}x_j) \\ p_{i,1}x_1 + \dots + p_{i,m}x_m \geq z^*, i = 1, \dots, n \\ x_1 + \dots + x_m = 1 \\ x_i \geq 0. \end{cases} \quad (6)$$

As for Bentham-Harsányi equilibria, we directly solve

$$\begin{cases} \max(\sum_{j=1}^m (\sum_{i=1}^n p_{i,j})x_j) \\ x_1 + \dots + x_m = 1 \\ x_i \geq 0. \end{cases} \quad (7)$$

For aspiration equilibria we first solve the program

$$\begin{cases} \min(z) \\ \sum_{k \in U_i} x_k \leq z, i = 1, \dots, n \\ x_1 + \dots + x_m = 1 \\ x_i \geq 0. \end{cases}$$

where U_k denotes action profiles making j unhappy to find the smallest agent probability of unhappiness. We then maximize (using another LP) social welfare over agents realizing the minimum. For best-off equilibrium the algorithm is somewhat more complicated: first, for every player $i = 1, \dots, n$ the program (8) yields the largest payoff y_i^* player i could get. If $y_j^* = \max(y_i^* : i = 1, \dots, n)$ is the global optimum then the program (9) finds the largest social welfare when agent j reaches its optimal value. Maximizing the social welfare over all such optimal j 's gives the best-off equilibrium.

$$\begin{cases} \max(\sum_{j=1}^m p_{i,j}x_j) \\ x_1 + \dots + x_m = 1 \\ x_i \geq 0. \end{cases} \quad (8)$$

$$\begin{cases} \max(\sum_{j=1}^m (\sum_{i=1}^n p_{i,j})x_j) \\ x_1 + \dots + x_m = 1 \\ \sum_{k=1}^m p_{j,k}x_k = y_j^* \\ x_i \geq 0. \end{cases} \quad (9)$$

□

Theorem 6. *Rawlsian, Bentham-Harsányi, best-off, Rawlsian percentile, aspiration equilibria are all Kantian program equilibria.*

Proof Sketch. We sketch the proof for Bentham-Harsányi equilibria only, the details for the other type of equilibria are entirely similar, and deferred to the journal version. It is clear that all the agents could independently compute the optimum solution to the LP problem (7) and then act accordingly. The problem is that, to make the equilibrium Kantian, one needs to "synchronize" the independent executions of the LP-solving program. This can be accomplished by (a). agents agreeing on a random permutation $x_{\sigma(1)}, \dots, x_{\sigma(n)}$ of the variables. (b). then independently solving the LP by implementing the same algorithm, and (c). Jointly sampling a pure action according to the computed solution. For point (b). one needs to choose an algorithm that acts deterministically given a concrete instance and variable ordering $(x_{\sigma(1)}, \dots, x_{\sigma(n)})$. For instance, one could choose the simplex algorithm with deterministic pivoting rules (e.g. Bland's rule, etc.) that are guaranteed to complete. Point (c). can be easily achieved by each agent choosing a random real in $[0,1]$, computing s , the sum of these numbers (mod 1), and using s to (jointly) sample a pure action according to the computed probabilities. It remains to show how to implement point (a) in a "symmetric" way. This is easy: to generate $\sigma(1)$ agent i chooses a random sample $X_{i,1} \in \mathbb{Z}_n$ and we let $\sigma(1) = 1 + \oplus_{i=1}^n X_{i,1}$. To generate $\sigma(k)$: agent i chooses a random sample $X_{i,k} \in \mathbb{Z}_{n-k}$ and we let $\tau(k) = \oplus_{i=1}^n X_{i,k}$. Define $\sigma(k)$ as the $(\tau(k)+1)$ 'th integer in $1, 2, \dots, n$ not equal to one of $\sigma(1), \sigma(2), \dots, \sigma(k-1)$. \square

We call an equilibrium point *extremal* if it cannot be written as a non-trivial convex combination of other (similar) equilibria. We next show that extremal self-regarding equilibria generalize Kantian pure equilibria. Extremality is needed, since our equilibria are closed under convex combinations but Kantian ones are not. Because of Thm. 2 no similar connection is likely for mixed Kantian equilibria:

Theorem 7. *In symmetric diagonal games Rawlsian, Bentham-Harsányi, best-off, Rawlsian percentile, aspiration equilibria coincide with convex combinations of Kantian pure equilibria.*

Proof Sketch. Because of domination only pure action profiles on the diagonal need to be considered. By symmetry, optimizing the worst-off utility or the social welfare over mixed profiles with diagonal pure strategies in the support is equivalent to maximizing the best-off utility, which implies that all pure action profiles in the support of Rawlsian (Bentham-Harsányi, best-off) equilibria are Kantian. The converse is easily seen to be true. A similar argument works for Rawlsian percentile and aspiration equilibria. \square

6 Agents with bounded greed

So far we have assumed that people are other-regarding. In reality people are not unrestricted optimizers, nor are they perfect Kantian moralists. Alger and

Weibull [AW13] attempted to interpolate between utilitarian agents and Kantian ones, by defining *homo moralis* to be an agent whose utility has the form $u_i(x, y) = (1 - k)\pi(x, y) + k\pi(x, x)$, where $k \in [0, 1]$ is the so-called *degree of morality* of the agent. They showed that evolutionary models with assortative mixing and incomplete information favor a particular kind of *homo moralis*, those whose degree of morality coincides with the degree of assortativity of the matching process. Interesting as this result is, it has some weaknesses. For instance [AW13], *homo moralis* behaves like *homo economicus* in Prisoners' Dilemma and all constant-sum games when $k \neq 1$. In other words, agent behavior is not sensitive to the degree of morality, as long as the agent is not Kantian.

We give (for symmetric games, but the idea can be extended to Kantian program equilibria) a definition with the same overall intention, but capturing a slightly different agent behavior:

Definition 12. *Let $\lambda \in [1, \infty]$. An agent is called λ -utilitarian if, for every action profile (a_i, b) , its utility $u_i(a_i, b)$ is:*

- $\pi_i(a_i, (\bar{a}_i)_{-i})$ if a_i is a Kantian action.
- 0 if a_i is not Kantian and $\pi_i(a_i, b) \leq \lambda \cdot \pi_i(X^{OPT})$,
- $\pi_i(a, b)$ if a_i is not Kantian and $\pi_i(a_i, b) \leq \lambda \cdot \pi_i(X^{OPT})$.

*In other words, a λ -utilitarian agent prefers to deviate from its Kantian action X^{OPT} **only** if the utility it obtains as a consequence of this action would be more than λ times larger. The number $\frac{1}{\lambda-1}$ will be called the greed index of agent i . The agent is called bounded greed when its greed index is finite. Purely utilitarian agents have infinite greed. Kantian agents have greed index zero.*

The next result gives an empirically plausible way that bounded greed agents behave differently from utilitarian/Kantian ones:

Theorem 8. *All pure action profiles in Prisoners' Dilemma are Nash equilibria of agents with varying degrees of greed.*

Proof. Bounded-greed agents still coordinate on the Kantian equilibrium (C, C) as long as both their greed indices are < 2 (i.e. they would need at least a twofold increase in payoff to deviate). If one of them has greed index < 2 and the other one has greed index ≥ 2 , then the latter one will defect. If both agents have greed indices ≥ 2 , then they will coordinate, just as if utilitarian agents would do, on the Nash equilibrium (D, D) . \square

7 Conclusions

Our main contribution is bringing Kantian equilibria (and related concepts) to the attention of agent community, showing that this notion is theoretically interesting, but that the road to implementable behaviors goes through less general equilibrium concepts.

Many of the notions we introduced, on the other hand, including Kantian program equilibria and bounded greed agents, are interesting and deserve further study. So does the connection between correlated equilibria and Kantian program equilibria: in many of the examples that we gave Kantian program equilibria were simply "fair" convex combinations of correlated equilibria.

Finally, many open problems remain: Can we find algorithms for our other-regarding equilibria that bypass the need for solving multiple LP's ? Is the problem from Theorem 2 NP-complete (i.e. in NP) ? What is the appropriate notion of equilibrium for bounded greed agents ? What is its computational complexity ?

References

- [AB95] Robert Aumann and Adam Brandenburger. Epistemic conditions for Nash equilibrium. *Econometrica: Journal of the Econometric Society*, pages 1161–1180, 1995.
- [Ari10] Dan Ariely. *Predictably irrational*. Harper, 2010.
- [Aum74] Robert J Aumann. Subjectivity and correlation in randomized strategies. *Journal of mathematical Economics*, 1(1):67–96, 1974.
- [AW13] Ingela Alger and Jörgen W Weibull. Homo moralis - preference evolution under incomplete information and assortative matching. *Econometrica*, 81(6):2269–2302, 2013.
- [B+94] Kenneth George Binmore et al. *Game theory and the social contract: just playing*, volume 2. M.I.T. Press, 1994.
- [Bac06] Michael Bacharach. *Beyond individual choice: teams and frames in game theory*. Princeton University Press, 2006.
- [BB94] T Randolph Beard and Richard O Beil. Do people rely on the self-interested maximization of others? an experimental test. *Management Science*, 40(2):252–262, 1994.
- [BCF⁺14] Mihaly Barasz, Paul Christiano, Benja Fallenstein, Marcello Herreshoff, Patrick LaVictoire, and Eliezer Yudkowsky. Robust cooperation in the prisoner’s dilemma: Program equilibrium via provability logic. *arXiv preprint arXiv:1401.5577*, 2014.
- [BDS19] Antoni Bosch-Domènech and Joaquim Silvestre. Experiment-inspired comments on John Roemer’s theory of cooperation. *Review of Social Economy*, 77(1):69–89, 2019.
- [Ber57] Claude Berge. *Théorie générale des jeux à n personnes*, volume 138. Gauthier-Villars Paris, 1957.
- [BG13] Samuel Bowles and Herbert Gintis. *A cooperative species: Human reciprocity and its evolution*. Princeton University Press, 2013.
- [Bin94] Ken G Binmore. *Game theory and the social contract: playing fair*. M.I.T. Press, 1994.
- [Bin05] K.G. Binmore. *Natural justice*. Oxford University Press, USA, 2005.
- [Bom97] Immanuel M Bomze. Evolution towards the maximum clique. *Journal of Global Optimization*, 10(2):143–164, 1997.
- [Bom98] Immanuel M Bomze. On standard quadratic optimization problems. *Journal of Global Optimization*, 13(4):369–387, 1998.

- [CEL⁺06] Y Chevalere, U Endriss, J Lang, PE Dunne, M Lemaitre, N Maudet, J Padget, S Phelps, JA Rodriguez-Aguilar, P Sousa, et al. Issues in multiagent resource allocation. *Informatica*, 30, 2006.
- [CH15] Valerio Capraro and Joseph Y Halpern. Translucent players: Explaining cooperative behavior in social dilemmas. In *Proceedings of the 15th conference on Theoretical Aspects of Rationality and Knowledge*, 2015.
- [CK08] Po-An Chen and David Kempe. Altruism, selfishness, and spite in traffic routing. In *Proceedings of the 9th ACM conference on Electronic commerce*, pages 140–149, 2008.
- [CKMT11] Andrew M Colman, Tom W Körner, Olivier Musy, and Tarik Tazdaït. Mutual support in games: Some properties of berge equilibria. *Journal of Mathematical Psychology*, 55(2):166–175, 2011.
- [CM16] Jing Chen and Silvio Micali. Auction revenue in the general spiteful-utility model. In *Proceedings of the 2016 ACM Conference on Innovations in Theoretical Computer Science*, pages 201–211, 2016.
- [Cri19] Andrew Critch. A parametric, resource-bounded generalization of löb’s theorem, and a robust cooperation criterion for open-source game theory. *The Journal of Symbolic Logic*, pages 1–15, 2019.
- [DD20] Virginia Dignum and Frank Dignum. Agents are dead. long live agents! In *Proceedings of the 19th International Conference on Autonomous Agents and MultiAgent Systems*, pages 1701–1705, 2020.
- [Dha16] Sanjit Dhami. *The foundations of behavioral economic analysis*. Oxford University Press, 2016.
- [Els17] Jon Elster. On seeing and being seen. *Social choice and welfare*, 49(3-4):721–734, 2017.
- [FGF01] Urs Fischbacher, Simon Gächter, and Ernst Fehr. Are people conditionally cooperative? evidence from a public goods experiment. *Economics letters*, 71(3):397–404, 2001.
- [For09] Lance Fortnow. Program equilibria and discounted computation time. In *Proceedings of the 12th Conference on Theoretical Aspects of Rationality and Knowledge*, pages 128–133, 2009.
- [Fou20] Ghislain Fourny. Perfect prediction in normal form: Superrational thinking extended to non-symmetric games. *Journal of Mathematical Psychology*, 96:102332, 2020.

- [Fra04] Robert H Frank. *What Price the Moral High Ground? Ethical Dilemmas in Competitive Environments*. Princeton University Press, 2004.
- [FS99] E. Fehr and K.M. Schmidt. A theory of fairness, competition, and cooperation. *The Quarterly Journal of Economics*, 114(3):817, 1999.
- [Gin09] H. Gintis. *The bounds of reason: game theory and the unification of the behavioral sciences*. Princeton University Press, 2009.
- [Gin10] Herbert Gintis. Social norms as choreography. *politics, philosophy & economics*, 9(3):251–264, 2010.
- [Gin16] Herbert Gintis. *Individuality and entanglement: the moral and material bases of social life*. Princeton University Press, 2016.
- [Gin20] Herbert Gintis. A typology of human morality. *Manuscript on authors' webpage, forthcoming in Journal of Economic Behavior and Organization*, 2020.
- [GZ89] Itzhak Gilboa and Eitan Zemel. Nash and correlated equilibria: Some complexity considerations. *Games and Economic Behavior*, 1(1):80–93, 1989.
- [Har55] John C Harsanyi. Cardinal welfare, individualistic ethics, and interpersonal comparisons of utility. *Journal of political economy*, 63(4):309–321, 1955.
- [Hof85] Douglas Hofstadter. Dilemmas for superrational thinkers, leading up to a luring lottery. In *Metamagical Themas: Questing for the Essence of Mind and Pattern*. Basic Books, 1985.
- [How88] John V Howard. Cooperation in the prisoner’s dilemma. *Theory and Decision*, 24(3):203, 1988.
- [HP18] Joseph Y Halpern and Rafael Pass. Game theory with translucent players. *International Journal of Game Theory*, 47(3):949–976, 2018.
- [HR10] Joseph Y Halpern and Nan Rong. Cooperative equilibrium. In *Proceedings of the 9th International Conference on Autonomous Agents and Multiagent Systems: volume 1-Volume 1*, pages 1465–1466, 2010.
- [HS13] Martin Hoefer and Alexander Skopalik. Altruism in atomic congestion games. *ACM Transactions on Economics and Computation (TEAC)*, 1(4):1–21, 2013.
- [Kam13] Gal A Kaminka. Curing robot autism: a challenge. In *AAMAS*, pages 801–804, 2013.

- [KKLS10] Adam Tauman Kalai, Ehud Kalai, Ehud Lehrer, and Dov Samet. A commitment folk theorem. *Games and Economic Behavior*, 69(1):127–137, 2010.
- [Kor16] Ioannis Kordonis. A model for partial Kantian cooperation. *arXiv preprint arXiv:1609.01921*, 2016.
- [Laf75] Jean-Jacques Laffont. Macroeconomic constraints, economic efficiency and ethics: An introduction to kantian economics. *Economica*, 42(168):430–437, 1975.
- [LFY⁺14] Patrick LaVictoire, Benja Fallenstein, Eliezer Yudkowsky, Mihaly Barasz, Paul Christiano, and Marcello Herreshoff. Program equilibrium in the prisoner’s dilemma via löb’s theorem. In *Workshops at the Twenty-Eighth AAAI Conference on Artificial Intelligence*, 2014.
- [MS65] Theodore S Motzkin and Ernst G Straus. Maxima for graphs and a new proof of a theorem of turán. *Canadian Journal of Mathematics*, 17:533–540, 1965.
- [MT09] Dov Monderer and Moshe Tennenholtz. Strong mediated equilibrium. *Artificial Intelligence*, 173(1):180–195, 2009.
- [NC18] Ahmad Nahhas and HW Corley. The computational complexity of finding a mixed berge equilibrium for ak-person noncooperative game in normal form. *International Game Theory Review*, 20(04):1850010, 2018.
- [Oes19] Caspar Oesterheld. Robust program equilibrium. *Theory and Decision*, 86(1):143–159, 2019.
- [OR94] M. Osborne and A. Rubinstein. *A Course in Game Theory*. M.I.T. Press, 1994.
- [PBF19] Jarosław Pykacz, Paweł Bytner, and Piotr Frackiewicz. Example of a finite game with no Berge equilibria at all. *Games*, 10(1):7, 2019.
- [PR08] Christos H Papadimitriou and Tim Roughgarden. Computing correlated equilibria in multi-player games. *Journal of the ACM (JACM)*, 55(3):1–29, 2008.
- [Ran64] Ayn Rand. *The virtue of selfishness*. Penguin, 1964.
- [Raw01] John Rawls. *Justice as fairness: A restatement*. Harvard University Press, 2001.

- [RH13] Nan Rong and Joseph Y Halpern. Towards a deeper understanding of cooperative equilibrium: characterization and complexity. In *Proceedings of the 2013 international conference on Autonomous agents and multi-agent systems*, pages 319–326, 2013.
- [Roe10] John E Roemer. Kantian equilibrium. *Scandinavian Journal of Economics*, 112(1):1–24, 2010.
- [Roe19] John E Roemer. *How We Cooperate: A Theory of Kantian Optimization*. Yale University Press, 2019.
- [Sed08] Sally Sedgwick. *Kant’s groundwork of the metaphysics of morals: an introduction*. Cambridge University Press, 2008.
- [SG82] Reinhard Selten and Werner Güth. Equilibrium point selection in a class of market entry games. In *Games, economic dynamics, and time series analysis*, pages 101–116. Springer, 1982.
- [Sim97] Herbert Alexander Simon. *Models of bounded rationality: Empirically grounded economic reason*, volume 3. MIT press, 1997.
- [SLB09] Y. Shoham and K. Leyton-Brown. *Multiagent systems: Algorithmic, game-theoretic, and logical foundations*. Cambridge University Press, 2009.
- [Tal98] William J Talbott. Why we need a moral equilibrium theory. In P. Danielson, editor, *Modeling Rationality, Morality and Evolution*. Oxford University Press, 1998.
- [Ten04] Moshe Tennenholtz. Program equilibrium. *Games and Economic Behavior*, 49(2):363–373, 2004.
- [Tom09] Michael Tomasello. *Why we cooperate*. MIT press, 2009.
- [Tom16] Michael Tomasello. *A natural history of human morality*. Harvard University Press, 2016.
- [vdHWW13] Wiebe van der Hoek, Cees Witteveen, and Michael Wooldridge. Program equilibrium—a program reasoning approach. *International Journal of Game Theory*, 42(3):639–671, 2013.
- [vRBKW19] Iris van Rooij, Mark Blokpoel, Johan Kwisthout, and Todd Wareham. *Cognition and intractability: A guide to classical and parameterized complexity analysis*. Cambridge University Press, 2019.
- [Zhu85] Vladislav I Zhukovskii. Some problems of non-antagonistic differential games. *Matematicheskie metody v issledovanii operacij*, pages 103–195, 1985.
- [ZK17] Vladislav I Zhukovskiy and Konstantin N Kudryavtsev. Mathematical foundations of the golden rule. i. static case. *Automation and Remote Control*, 78(10):1920–1940, 2017.