
Cutoff stability under distributional constraints with an application to summer internship matching*

Haris Aziz · Anton Baychkov · Péter Biró

Received: date / Accepted: date

Abstract We introduce a new two-sided stable matching problem that describes the summer internship matching practice of an Australian university. The model is a case between two models of Kamada and Kojima on matchings with distributional constraints. We study three solution concepts, the strong and weak stability concepts proposed by Kamada and Kojima, and a new one in between the two, called cutoff stability. Kamada and Kojima showed that a strongly stable matching may not exist in their most restricted model with disjoint regional quotas. Our first result is that checking its existence is NP-hard. We then show that a cutoff stable matching exists not just for the summer internship problem but also for the general matching model with arbitrary heredity constraints. We present an algorithm to compute a cutoff stable matching and show that it runs in polynomial time in our special case of summer internship model. However, we also show that finding a maximum size cutoff stable matching is NP-hard, but we provide a Mixed Integer Linear Program formulation for this optimisation problem.

Keywords stable matching, distributional constraints, cutoff scores, NP-hardness, integer programming

1 Introduction

Centralized two-sided matching market algorithms have received immense success in several application domains, including matching students to schools,

* This paper is the extension of our conference paper [Aziz et al., 2020]. The main addition is Section 5 on our new solution concept of cutoff stability and an algorithm to achieve it.

Haris Aziz
UNSW Sydney and Data61 CSIRO, Australia
E-mail: haziz@cse.unsw.edu.au

Anton Baychkov
University of Sydney, Australia
E-mail: abay3963@uni.sydney.edu.au

Péter Biró
Centre for Economic and Regional Studies, Hungary
E-mail: peter.biro@krtk.mta.hu

residents to hospitals, and projects to workers.¹ We present a novel matching market model that we refer to as the summer internship matching market. The model captures the matching of student applicants to projects proposed by supervisors in an internship program. A distinctive feature of the model is that in order for an applicant to be assigned to any project, a certain amount of money needs to be contributed from the project supervisors' funds.

Our problem is inspired by summer intern research programs in Australia. It is common for undergraduate students to undertake research projects over the summer. Each project is supervised by one or more members of the faculty, with many offering multiple projects. Even though the projects may be discounted by contributions from the faculty, supervisors are often required to contribute to the funding of these positions, from their personal research budget. Alternatively, they could be constrained by the amount of time they can allocate to supervision. These supervisor-side constraints mean that not all projects can be funded.

Just as the standard hospital resident matching models do not just apply to the matching of doctors to hospitals [Roth, 2008], our model also does not just apply to matching of student interns. It applies to any two-sided matching model in which very widely applicable budget requirements and budget constraints are involved. For example, our problem also models hiring scenario in which different teams have their own budgets and they want to hire employees. Certain employee roles could sit across various teams. In that case, multiple teams can pool in their money to fund joint positions.

The budget constraints that we consider lead to interesting research challenges. Firstly, applying standard matching algorithms such as the Deferred Acceptance Algorithm does not work as it do not deal with complex feasibility constraints. More critically, as we will discuss, there may exist no feasible matching that satisfies stability as considered in seminal papers on matching (see, e.g., Gale and Shapley [1962b] and Abdulkadiroğlu and Sönmez [2003a]).

1.1 Contributions

In this paper, we formalize the summer internship problem with budgets, abbreviated as SIP. It falls within the class of models that matches applicants, projects, and supervisors. The main characteristic of our problem is that supervisors have budgets that they can spread across their projects. Our model is more general than the widely-used hospital-resident matching model in which the hospitals are partitioned into regions and regions have upper capacities [Kamada and Kojima, 2015], a model that we abbreviate as REG. On the other hand, our model is a special case of the matching model under distributional constraints of Kamada and Kojima [2017b], where the feasibility of a matching is monotone in the number of applicants matched, the property called *heredity* by Goto et al. [2017], that we abbreviate as HER.

First, we study the concept of strong stability proposed in Kamada and Kojima [2015], where the authors showed that such solution may not exist for REG. Here we prove that the problem of checking the

¹ For an overview of real-life matching markets, please see <http://www.matching-in-practice.eu>, and a recent survey [Biró, 2017].

existence of a strongly stable matching is NP-hard for REG (and thus also for any settings that contain REG as a special case, such as SIP and HER).

Then we study weak stability, also introduced in Kamada and Kojima [2015] for REG and then studied in Kamada and Kojima [2017b] for HER. In the conference version of our paper [Aziz et al., 2020] we provided a strongly polynomial algorithm for computing a weakly stable matching for our intermediate SIP model, based on the algorithm of Kamada and Kojima [2017b] for HER. Our algorithm uses as an oracle an algorithm based on network flows to repeatedly check whether a given matching is feasible or not. In this extended version of our conference paper, we strengthen this result by presenting a general algorithm that returns a matching satisfying cutoff stability. Fair matchings are exactly those matchings that can be induced by a set of cutoff scores. Meanwhile, cutoff stable matchings are those that are induced by minimal cutoffs, i.e., where the decrease of any cutoff would make the induced matching infeasible. We show that cutoff stability is an intermediate notion between weak and strong stability, and the computation of a cutoff stable matching is always possible with our algorithm for HER. Since HER covers many well-studied settings including refugee matching (see, e.g., [Aziz et al., 2018, Delacrétaz et al., 2016]), our result has wide-applicability.² We apply the algorithm in the context of SIP and show that it can be implemented to run in polynomial time. However, we also show that finding a maximum size cutoff stable matching is NP-hard even for REG (implying that is also NP-hard for SIP and HER). However, we formulate a Mixed Integer Linear Program (MILP) for finding such an optimal solution for SIP. Many of our general structural results for the HER model. Unless specified otherwise, we will assume that our formal statements apply to HER.

Finally, we provide a normative criterion for egalitarian ex-post allocation of supervisor funding among projects, and a polynomial-time algorithm to find an egalitarian allocation. Combined with our polynomial-time algorithm for finding a weakly stable matching, we present a compelling approach for finding a desirable solution for the summer internship problem that appeals to both stability and fairness requirements.

1.2 Related Work

The literature on two-sided matching was inspired by the seminal paper of Gale and Shapley [1962a] who considered matching markets that match students to schools and hospitals to residents. The paper has spawned richer matching models and resulted in new algorithmic work (see, e.g., Manlove [2013]). Our work is an extension of these models and falls in the general umbrella of matching markets with various kinds of distributions constraints (see, e.g., Aziz et al. [2018], Kamada and Kojima [2017a], Fragiadakis et al. [2016], Fragiadakis and Troyan [2017], Kurata et al. [2017]).

Our concept of budget-feasibility is a type of feasibility constraint, as defined by Kamada and Kojima [2017b] and thus our problem falls under the

² See, for example, the discussion by Kamada and Kojima [2020] who point out that even intra-project heredity constraints capture problems including college admissions with students with disabilities; refugee match, and daycare allocation.

umbrella of matching under feasibility constraints. Thus, the notions of strong and weak stability studied by Kamada and Kojima [2017b] also apply in our model. In our paper, we focus on computational results such as establishing NP-completeness or polynomial-time solvability of stable matchings. Our model also has the additional dimension of budget allocations for which we explore fairness concepts as well as algorithms to divide the budget in an egalitarian manner. We also propose an intermediate concept called cutoff stability and prove that it can be achieved for the general matching model with arbitrary heredity constraints. Cutoff stability is a new notion for the HER model, though similar notions have been studied for different stable matching models, such as the choice function model of Fleiner and Jankó [2014]. Our concept of cutoff stability defined for general feasibility constraints is similar in spirit to the within-type envy-freeness concept of Echenique and Yenmez [2015] in the context of school choice with affirmative action.

Goto et al. [2017] also considered two-sided matching under general feasibility constraints that satisfy the heredity property. Their main contribution is proposing an algorithm called Adaptive Deferred Acceptance that satisfies strategy-proofness, non-wastefulness, and a fairness property (that is weaker than the weak stability concept of Kamada and Kojima [2017b] and hence also cutoff stability). Kamada and Kojima [2020] also consider heredity constraints that apply to individual schools/hospitals.

Our model bears some similarities with the hospital-resident matching problem with regional constraints [Kamada and Kojima, 2015, Biro et al., 2010, Goto et al., 2016, Aziz et al., 2019, Kamada and Kojima, 2018]. In these region-based problems, at most a certain number of students can be selected from given regions. On the other hand, in the summer internship problem, a supervisor's budget is divisible and can be spread partially over all of her projects. If the regions are disjoint (as studied by Kamada and Kojima [2015]), then the region-based model is a special case of our model. The general setting with region constraints has not seen many positive results, and the more constrained hierarchical regions as studied by Goto et al. [2016] and Kamada and Kojima [2018] can neither replicate, nor be replicated by a set of supervisors. In particular, the concept of stability with regional priorities proposed by Kamada and Kojima [2018] cannot be directly applied to our setting. Our concept of cutoff stability is an alternative intermediate notion of stability and it can be applied to a wider range of settings (those subsumed under the HER model).

Abraham et al. [2007] considered a different model for student-project allocation. Notable differences in their model include: (1) no project has multiple supervisors, (2) each supervisor has a universal priority list over students which is not project specific, and (3) a supervisor has a rigid capacity constraint for the number of projects to supervise. Our model allows supervisors to explore more efficient outcomes by pooling in their budgets to host a student. The universal priority list of each supervisor makes the model of Abraham et al. [2007] much more restricted and different from our model.

Two other recent models are similar to our setting. Goto et al. [2017] introduce the Student-Project-Room matching problem. Rooms are indivisible, and at most one room can be allocated to each project. Ismaili et al. [2018] extend this to a more general Student-Project-Resource allocation problem. Resources

are still indivisible, but there is no longer a restriction imposed on the number of resources that can be allocated to each project. Our model is distinct from both of these, as it allows the resources (in our case, supervisor budgets) to be divisible. This divisibility allows for better computational results. For instance, verifying the feasibility of a matching, and finding a weakly stable (and thus non-wasteful) matching can be done in polynomial time.

There is also work on matching with budget constraints (see, e.g., Kawase and Iwasaki [2017, 2018], Ismaili et al. [2019]). The models considered in these papers are different in several respects. For example, hospitals have additive utilities and each hospital gives monetary compensation to doctors.

Regarding the LP descriptions and IP techniques for two-sided stable matching problems, Baïou and Balinski [2000] gave the first description on the stable admissions polytope. Integer programming techniques have been used later for college admissions with special features [Ágoston et al., 2016], stable project allocation under distributional constraints [Ágoston et al., 2018], the hospital–resident problem with couples [Biró et al., 2014], and ties [Kwanashie and Manlove, 2014, Delorme et al., 2019].

2 Preliminaries

First, we introduce our summer internship matching model (SIP), we show that the checking the feasibility of a matching is polynomial time tractable, and finally we also show the relation of our model to the REG and HER models of Kamada and Kojima described in Kamada and Kojima [2015] and Kamada and Kojima [2017b], respectively.

2.1 Model

Let A be a finite set of applicants, and P a finite set of projects. Each applicant $a \in A$ has a strict preference list \succ_a that ranks the subset of projects that a finds acceptable. Each project $p \in P$ has a preference list \succ_p over the subset of applicants that p finds acceptable, and a maximum capacity c_p .

Furthermore, let S denote the set of project supervisors. Each supervisor $s \in S$ has a list of projects P_s that they supervise, and is endowed with a budget (e.g. quantity of funds) q_s that they can allocate among those projects. We assume that these budgets are infinitely divisible and that each applicant requires one unit of funding. Further, we assume that these endowments are publicly known, and thus supervisors cannot strategise by misreporting their budgets. Additionally, denote the list of supervisors for project p by S_p .

We say that an applicant $a \in A$ is matched to project $p \in P$ if $(a, p) \in M$. A **matching** M is a subset of $A \times P$ that satisfies the following conditions:

- Each applicant is matched to at most one project (for all $a \in A$, $|\{(a, p) \in M : p \in P\}| \leq 1$), and a finds the project they are matched to acceptable.
- The number of applicants matched to any project does not exceed that project’s capacity (for all $p \in P$, $|\{(a, p) \in M : a \in A\}| \leq c_p$), and p finds all applicants matched to it acceptable.

We use $M(a)$ to refer to the project that applicant a is matched to ($M(a) = \emptyset$ if a is unmatched). Meanwhile, $M(p)$ denotes the set of applicants matched to p .

Let $x_{s,p}$ be the amount of funds a supervisor s allocates to project p . We call a matching M **feasible** (or supervisor-feasible) if there exists a set $\{x_{s,p}\}_{s \in S, p \in P_s}$ that satisfies the following conditions:

- $x_{s,p} \geq 0$ for all $s \in S, p \in P_s$
- Every project receives one unit of funding for each applicant matched to it: $\sum_{s \in S_p} x_{s,p} = |M(p)|$ for all $p \in P$
- Supervisors do not exceed their endowment: $\sum_{p \in P_s} x_{s,p} \leq q_s$ for all $s \in S$

We call any set $\{x_{s,p}\}_{s \in S, p \in P_s}$ that satisfies the above conditions for matching M a **feasible funding allocation**. The mathematical model presented exactly captures the student research internship program in our university: each supervisor can be part of multiple internship project proposals but does not necessarily have the funding to contribute to all of them.

Example 1 (Summer Internship Problem) Consider the following instance of the summer internship problem with 2 applicants 2 supervisors, and 2 projects.

$$\begin{array}{lll}
 A = \{a_1, a_2\} & \succ_{a_1}: p_2, p_1 & \succ_{a_2}: p_1, p_2 \\
 P = \{p_1, p_2\} & \succ_{p_1}: a_1, a_2 & \succ_{p_2}: a_2, a_1 \\
 S = \{s_1, s_2\} & P_{s_1} = \{p_1, p_2\} & P_{s_2} = \{p_2\} \\
 q_{s_1} = 0.7 & q_{s_2} = 0.5 & c_{p_1} = c_{p_2} = 1
 \end{array}$$

The only three feasible matchings are the empty matching and the two matchings in which some applicant is matched to project p_2 . The reason no one can be matched to project p_1 is that p_1 has a sole supervisor s_1 who does not have sufficient funding to fund p_1 . On the other hand, the combined funding of s_1 and s_2 is more than 1 for project p_2 so p_2 can be funded. A feasible funding allocation x is where s_1 contributed half of the budget of project p_1 and s_2 contributes the rest: $x_{s_1, p_2} = 0.5, x_{s_2, p_2} = 0.5$.

2.2 Checking Feasibility of a Matching

We show that checking feasibility of a matching in our model can be done efficiently by reducing the question to a network flow problem.³ Define the **funding flow graph** G_M associated with a matching M as follows:

- $V(G_M) = \{s^*\} \cup S \cup P \cup \{t^*\}$, where s^* is the source, and t^* is the sink
- Arcs (s, p) , for all supervisor-project pairs where $p \in P_s$ with capacity ∞
- Arcs (s^*, s) , for all $s \in S$, each with capacity q_s
- Arcs (p, t^*) , for all $p \in P$, each with capacity $|M(p)|$

Theorem 1 *The feasibility of a matching can be checked in polynomial time $O((\max\{|S|, |P|\})^3)$ for the summer-internship problem.*

³ For an overview of network flows, see Ahuja et al. [1993].

Proof Our first claim is that a matching M is feasible if and only if G_M admits a feasible s^* - t^* flow of size $|M|$.

Suppose M is feasible. Define a flow f on G_M as follows:

- $f(s,p) = x_{s,p}, \forall s \in S, p \in P_s$
- $f(s^*,s) = \sum_{p \in P_s} x_{s,p}, \forall s \in S$
- $f(p,t^*) = \sum_{s \in S_p} x_{s,p}, \forall p \in P$

It is easy to see that this is a feasible flow of size $|M|$. Now suppose that G_M admits a feasible flow f of size $|M|$. Set $x_{s,p} = f(s,p), \forall s \in S, p \in P_s$. We can then show that this $\{x_{s,p}\}$ satisfies the conditions of feasibility.

Now that we have established the claim, we use the fact that the maximum flow problem can be solved in $O(V^3)$ time, using for instance, the algorithm proposed by Malhotra et al. [1962]. $V(G_M) = |S| + |P| + 2$ and, given a matching M , G_M can be constructed in $O((|S| + |P|)^2)$ time. We can check whether M is feasible in $O(\max\{|S|, |P|\}^3)$ time by computing a maximum flow and verifying whether it equals $|M|$. \square

Note that by the integer property of the network flow problem, if all the capacities of the supervisors are integer and the flow is feasible then an integer funding allocation exists.

2.3 Connection with the models by Kamada and Kojima

Our model satisfies the heredity property of Kamada and Kojima [2017b] and Goto et al. [2017], that says that if a matching is feasible then it remains feasible if the numbers of applicants matched to each project weakly decreases. More formally, their matching model under distributional constraints that satisfy heredity (HER), can be represented by a **feasibility function** $f: \mathcal{M} \rightarrow \{0,1\}$ that satisfies the following condition:

- $f(\emptyset) = 1$ and, for any two matchings M and M' , if $|M'(p)| \leq |M(p)| \forall p \in P$ then $f(M) = 1 \Rightarrow f(M') = 1$.

A matching M is feasible if and only if $f(M) = 1$. Note that the feasibility constraints are ‘anonymous’ in the sense that they do not depend on the identity of the applicants matched but only on their quantity.

Kamada and Kojima [2015] studied a basic model with regional upper quotas, where the regions form a partition of the set of hospitals (REG). We can represent this in our model by replacing each region with a supervisor, endowed with a budget equal to that region’s capacity, and supervising a set of projects that correspond to the hospitals in that region.

Thus, REG is a special case of SIP, and SIP is a special case of HER. Therefore, every hardness result for REG implies the same hardness result for SIP and HER, and any easiness result for HER implies the same result for SIP, and an easiness result for SIP also holds for REG.

2.4 Fair matchings and cutoff scores

We say that matching M is *fair*, if for every pair $(a,p) \notin M$, $p \succ_a M(a)$ implies that $a' \succ_p a$ for every $a' \in M(p)$.⁴ This is a basic property for both strong and weak stability by Kamada and Kojima [2017b], and so also for our intermediate notion of cutoff stability.

In the classical Gale-Shapley model [Gale and Shapley, 1962a] a matching is stable if and only if it is fair and non-wasteful, where *non-wastefulness* means that there exists no project p with unfilled capacity and applicant a where $p \succ_a M(a)$. In our context we can define different non-wastefulness notions leading to weak and strong stability and a new intermediate stability concept, called cutoff stability. We will define and analyze these stability concepts in Sections 3, 4 and 5, respectively.

The concept of cutoff scores is closely related to fair matchings. Let $d: P \rightarrow [0, 1, \dots, |A| + 1]$ be the cutoff score function, where $d(p)$ is the *cutoff* at project p . Without loss of generality we assume that each project p assigns a score to each applicant a in accordance with its preference list, that is a has score $|A| - k + 1$ if she is ranked k th by project p . Given cutoff scores d , applicant we say that a is *admissible* to project p if her score achieves the cutoff. Cutoff scores d *induce* matching M , if every applicant is matched to the best project of her preference where she is admissible.⁵ The following observation is well-known (see, e.g. Lemma 3 in Fleiner and Jankó [2014]), for completeness we give a short proof.

Proposition 1 *A matching is fair if and only if it is induced by some cutoff scores.*

Proof A matching induced by cutoffs is always fair by definition, since $p \succ_a M(a)$ implies that a could not reach the cutoff score at p so everyone assigned to p has a higher rank than her. In the other direction let M be a fair matching. For every project p we set the cutoff $d(p)$ to be equal to the score of the lowest ranked applicant in $M(p)$. It is easy to see that d induces M . \square

In the following sections we will consider the strong and weak stability concepts of Kamada and Kojima [2017b], and subsequently introduce our new solution concept of cutoff stability.

3 Strong Stability

An applicant-project pair (a,p) is a **blocking pair** for matching M if:

- applicant a prefers project p to the project they are currently matched to: $p \succ_a M(a)$, and
- either:
 - p is under capacity and finds a acceptable: $|M(p)| < c_p$ and $a \succ_p \emptyset$; or

⁴ In the school choice literature this property is also called as *justified envy-freeness*, see, e.g., Abdulkadiroğlu and Sönmez [2003b].

⁵ In fact, in many college admission schemes only the cutoff scores are announced, the induced matchings are obvious for the participants involved, see, e.g. the cases of Hungary [Ágoston et al., 2016] and Australia [Artemov et al., 2017] and [Guillen et al., 2020].

- p prefers a to one of its currently matched applicants: $\exists a' \in M(p)$ such that $a \succ_p a'$

Definition 1 (Strong Stability) We call a matching M strongly stable if for any blocking pair (a,p) for matching M , the following two conditions are satisfied:

- $a' \succ_p a$ for all applicants $a' \in M(p)$
- The matching $M' = (M \cup \{(a,p)\}) \setminus \{(a, M(a))\}$ is not feasible.

The first condition implies that we only allow the existence of blocking pairs involving a project p that is under its maximum capacity c_p . The second condition implies that even if slot is free at project p , adding applicant a to project p will result in a distributional constraint being violated so that $M' = (M \cup \{(a,p)\}) \setminus \{(a, M(a))\}$ is not feasible. Thus, we allow blocking pairs that cannot be satisfied without violating our feasibility constraint to exist in a strongly stable matching.

Alternatively, we can define strong stability in terms of fairness and strong non-wastefulness, as follows. We say that matching M is *strongly non-wasteful* if for every pair $(a,p) \notin M$, $p \succ_a M(a)$ implies that $(M \cup \{(a,p)\}) \setminus \{(a, M(a))\}$ is not feasible or project p is at capacity. It is easy to see that M is strongly stable if and only if it is fair and strongly non-wasteful.

Our first observation is that for our problem, a strongly stable matching does not exist. This follows from the observation that our model is more general than the hospital resident setting with disjoint regions [Kamada and Kojima, 2015]. We provide an adaptation of an example (Example 1) of Kamada and Kojima [2017b] for the sake of completeness.

Example 2 (A strongly stable matching does not necessarily exist for the summer internship problem)

Consider the following instance of the summer internship problem:

$$\begin{array}{lll} A = \{a_1, a_2\} & \succ_{a_1}: p_2, p_1 & \succ_{a_2}: p_1, p_2 \\ P = \{p_1, p_2\} & \succ_{p_1}: a_1, a_2 & \succ_{p_2}: a_2, a_1 \\ S = \{s\} & P_s = \{p_1, p_2\} & q_s = c_{p_1} = c_{p_2} = 1 \end{array}$$

It is easy to see that $|M| \leq 1$. If both applicants are unmatched then (a_1, p_1) forms a blocking pair. Suppose without loss of generality that a_1 is matched in the stable matching. If $M = \{(a_1, p_1)\}$ then (a_1, p_2) is a blocking pair that does not satisfy the second condition of strong stability. If $M = \{(a_1, p_2)\}$ then (a_2, p_2) is a blocking pair that does not satisfy the first condition of strong stability. Thus, every feasible matching admits a blocking pair that is not permitted under strong stability, and is therefore not strongly stable.

Below we show that the problem of deciding the existence of a strongly stable matching is NP-complete. We reduce for Restricted MAX-SMTI, the problem of deciding whether there exists a complete stable matching for the stable marriage problem with incomplete lists and ties under the restriction that the preferences of the men are strict, and the preference list of each woman is either strict or consists solely of a tie of length two [Manlove et al., 2002]. First, we introduce an instance that will serve as the core of the construction imitating an indifferent woman.

Example 3 (An instance with two strongly stable matchings, covering different agents) The instance consists of a preference cycle involving four applicants and four projects as follows.

$$\begin{array}{ll}
A = \{a_1, a_2, a_3, a_4\} & \\
\succ_{a_1}: p_2, p_1 & \succ_{a_2}: p_3, p_2 \\
\succ_{a_3}: p_4, p_3 & \succ_{a_4}: p_1, p_4 \\
P = \{p_1, p_2, p_3, p_4\} & \\
\succ_{p_1}: a_1, a_4 & \succ_{p_2}: a_2, a_1 \\
\succ_{p_3}: a_3, a_2 & \succ_{p_4}: a_4, a_3 \\
S = \{s_1, s_2, s_3\} & P_{s_1} = \{p_1, p_3\} \\
P_{s_2} = \{p_2\} & P_{s_3} = \{p_4\} \\
q_{s_1} = q_{s_2} = q_{s_3} = 1 & c_{p_1} = c_{p_2} = c_{p_3} = c_{p_4} = 1
\end{array}$$

One can check that there are two strongly stable matchings: $M_1 =$

$\{(a_1, p_1), (a_2, p_2), (a_4, p_4)\}$ and $M_2 = \{(a_2, p_2), (a_3, p_3), (a_4, p_4)\}$. First, let us show the stability of M_1 (the argument is similar for M_2 by symmetry). The only blocking pairs for M_1 are (a_2, p_3) and (a_3, p_3) , but adding any of these pairs to M_1 would make the matching infeasible. To show that M_1 and M_2 are the only strongly stable matchings we observe first that a_2 has to be matched to p_2 , and a_4 has to be matched to p_4 by symmetric reasons (so we prove only the former fact). Note that a_2 cannot be unmatched, as she would block the matching with p_2 . Suppose now for a contradiction that a_2 is matched to p_3 . Then p_1 must be unfilled by feasibility, thus a_4 has to be matched to p_4 and a_3 remains unmatched and so forms a blocking pair with p_3 , a contradiction. So we showed that (a_2, p_2) and (a_4, p_4) must be contained in any strongly stable matching. Finally we shall note that both p_1 and p_3 cannot remain unfilled, as (a_4, p_1) would form a blocking pair. Therefore, in a strongly stable matching we must also have either (a_1, p_1) or (a_3, p_3) , resulting in M_1 and M_2 , respectively.

Note that this example also shows that the Rural Hospitals' Theorem of Roth [1986] does not hold for strongly stable matchings, which says that always the same applicants are matched in every stable solution in a many-to-one college admissions problem. Actually, the same two matchings are also the only weakly stable matchings, and thus the only cutoff stable matchings, by the same argument.

Using the example as a gadget, we will show that deciding whether an instance of our problem has a strongly stable solution is an NP-complete problem.

Theorem 2 *For the Summer Internship Problem (SIP), checking the existence of a strongly stable matching is NP-complete, even if all the supervisors have capacity one and each is responsible for at most two distinct projects.*

Proof Given a solution, we can check whether it is strongly stable by considering each potential blocking pair in polynomial time, so the problem is in NP. For proving NP-hardness, we reduce from the special version of the MAX-SMTI problem [Manlove et al., 2002]. Here, we are given an instance of a stable marriage problem with incomplete lists and ties, where $U = \{u_1, u_2, \dots, u_n\}$ is the set of men, each having a strict preference list over the women acceptable for him, and $W = W^s \cup W^t$ is the set of women, where $W^s = \{w_1, \dots, w_k\}$ are

the women with strict preference lists and $W^t = \{w_{k+1}, \dots, w_n\}$ are the women, where each has a single tie of length two in her preference list (i.e., she finds two men acceptable, and she is indifferent between them). A matching is said to be weakly stable if it is not blocked by a pair where both parties strictly prefer each other to their current partners. Let us denote the restricted instance of SMTI by I , where the problem of deciding the existence of a complete weakly stable matching is NP-complete [Manlove et al., 2002].

We construct the corresponding internship problem I' as follows. For every man u_i we create a project p_i with a single supervisor s_i each with capacity one. We denote this set of projects by P^u . For every woman in $w_j \in W^s$ we create an applicant a_j , and we denote this set of applicants by A^s . Here the preference list of a_j over the projects in I' is identical to the preference list of w_j over the men in I . Now, for each woman $w_j \in W^t$, we introduce a gadget G^j that is identical to the instance in Example 3, so let G^j be constructed as follows.

$$\begin{aligned}
A^j &= \{a_1^j, a_2^j, a_3^j, a_4^j\} \\
&\succ_{a_1^j}: p_2^j, p_1^j && \succ_{a_2^j}: p_3^j, p_2^j \\
&\succ_{a_3^j}: p_4^j, p_3^j && \succ_{a_4^j}: p_1^j, p_4^j \\
P^j &= \{p_1^j, p_2^j, p_3^j, p_4^j\} \\
&\succ_{p_1^j}: a_1^j, a_4^j && \succ_{p_2^j}: a_2^j, a_1^j \\
&\succ_{p_3^j}: a_3^j, a_2^j && \succ_{p_4^j}: a_4^j, a_3^j \\
S &= \{s_1^j, s_2^j, s_3^j\} && P_{s_1^j} = \{p_1^j, p_3^j\} \\
P_{s_2^j} &= \{p_2^j\} && P_{s_3^j} = \{p_4^j\} \\
q_{s_1^j} &= q_{s_2^j} = q_{s_3^j} = 1 && c_{p_1^j} = c_{p_2^j} = c_{p_3^j} = c_{p_4^j} = 1
\end{aligned}$$

Furthermore, if $w_j \in W^t$ had preference list $[u_{i_1}, u_{i_2}]$ then we append p_{i_1} to the end of the preference list of a_1^j and we append p_{i_2} to the end of the preference list of a_3^j . Likewise, we adjust the preference list of $p_i \in P^u$ as follows: for every $w_j \in W^s$, we replace w_j with a_j , whilst if $w_j \in W^t$ then we replace w_j with either a_1^j or a_3^j according to whether u_i was the first or the second man in the tie of w_j . Finally, we add a gadget G^* , which is a copy of the unsolvable instance in Example 2, together with an additional applicant a^* who accepts one of the projects, say p^* , in G^* . Let a^* be the most preferred applicant by the projects in G^* , so including this applicant in G^* will turn the instance solvable by assigning a^* to p^* and leaving the other applicants in G^* unmatched. To link $G^* \cup a^*$ with the rest of I' we put all the projects in P^u ahead of p^* in the preference list of a^* and we also append a^* to the end of the preference list of each $p_j \in P^u$.

We will show that I has a complete weakly stable matching if and only if I' has a strongly stable matching. Let us suppose first that M is a complete stable matching of I , we construct a strongly stable matching M' of I' as follows. For every $(u_i, w_j) \in M$, where $w_j \in W^s$ we simply add the corresponding pair (p_i, a_j) to M' . Suppose now that $(u_i, w_j) \in M$, where $w_j \in W^t$ and u_i is the first man in the single tie of w_j , so p_i is linked with a_1^j in I' . Let then include (p_i, a_1^j) in M' , together with the corresponding strongly stable matching M_2 of G^j that leaves

a_1^j unmatched, namely $M_2^j = \{(a_2^j, p_2^j), (a_3^j, p_3^j), (a_4^j, p_4^j)\}$. Similarly, if u_i is the second man in the tie of w_j , then we include (p_i, a_3^j) in M' , together with the corresponding strongly stable matching M_1 of G^j that leaves a_3^j unmatched, namely $M_1^j = \{(a_1^j, p_1^j), (a_2^j, p_2^j), (a_4^j, p_4^j)\}$. Finally, we add (a^*, p^*) to M' . The strong stability of M' is implied by the following reasons. Observe first that a^* cannot block with any project in P^u , since all of these projects are assigned with better applicants. The matching in gadget G^* is also stable internally, as well as in each gadget G^j . Finally, the weak stability of M implies the lack of the blocking pairs of form (a_j, p_i) for M' , where $a_j \in A^s$ and $p_i \in P^u$.

In the other direction, let us assume that M' is a strongly stable matching for I' and we construct a complete weakly stable matching M for I as follows. First, we note that a^* must be matched to p^* in M' , as otherwise the separated gadget G^* would cause instability. But if a^* is matched to p^* then each project $p_i \in P^u$ must be assigned to an applicant better than a^* . Now, if $(p_i, a_j) \in M'$ for $a_j \in A^s$ then we add (u_i, w_j) to M (where $w_j \in W^s$), and if (p_i, a_1^j) or (p_i, a_3^j) belongs to M' then we add (u_i, w_j) to M (where $w_j \in W^t$). It is obvious that M is a complete matching in I , its weak stability is implied by the strong stability of M' as follows. Suppose for a contradiction that a pair (u_i, w_j) would be blocking for M (where $w_j \in W^s$), then the corresponding pair (p_i, a_j) would also block M' , a contradiction. This completes the proof. \square

Our hardness result is strong because it holds for a very restricted setting and also implies NP-completeness for the setting of Kamada and Kojima [2015] that concerns disjoint regions (REG), even if at most two hospitals belong to each region. The complexity of existence of strongly stable matching was also an open problem for the model of Kamada and Kojima [2015].⁶

Corollary 1 *For REG, checking the existence of a strongly stable matching is NP-complete.*

Furthermore, this case can also occur when one hospital has a common upper quota for two different types of jobs, e.g., daytime and night shifts, or surgical and medical internship positions. Another motivating example is the Hungarian college admission scheme, where students can be admitted to a programme under two contracts, state-funded and privately-funded, and there is a common upper bound on them [Biro et al., 2010].

4 Weak Stability

In view of the non-existence and NP-completeness of checking the existence of strongly stable matchings, one can consider a weaker stability criterion. Kamada and Kojima [2017b] proposed a weak stability concept for a setting that does not concern budgets but which has an abstract feasibility indicator function for any given matching. We present the definition in our terminology of applicants and projects.

⁶ Most of the computational hardness results for distributional constraints concern overlapping regions (see, e.g. Goto et al. [2016]).

Definition 2 (Weak Stability) We call a matching M weakly stable if for any blocking pair (a,p) for matching M , the following two conditions are satisfied.

- $a' \succ_p a$ for all applicants $a' \in M(p)$
- $M \cup \{(a,p)\}$ is not feasible.

Note the similarity in the definition of strong stability and weak stability. The only difference is that in the second condition, applicant a can have two contracts: one with project $M(a)$ and another with the project p she is blocking with. One way to see this is that in order for applicant a to block with p , it must sign the contract with p before it opts to annul its match with project $M(a)$. We call any blocking pair that satisfies these condition **permitted under weak stability**. Note that due to the second condition, any empty matching need not be weakly stable.

Alternatively, we can also define weak stability in terms of fairness and weak non-wastefulness. We say that matching M is *weakly non-wasteful* if for every pair $(a,p) \notin M$, $\succ_a M(a)$ implies that $M \cup \{(a,p)\}$ is not feasible or project p is at capacity. It is easy to see that M is weakly stable if and only if it is fair and weakly non-wasteful, for a short proof see Proposition 1 in Kamada and Kojima [2017b].

We say that p is *unconstrained* for a feasible matching M if for any $(a,p) \notin M$, $M \cup \{(a,p)\}$ remains feasible, i.e., when one more applicant can be added to project p by keeping the solution feasible.

Proposition 2 *A matching M is weakly stable if and only if it is induced by cutoff scores d such that for every unconstrained project p , $d(p)=0$.*

Proof Following Proposition 1, we only need to show that the condition of every unconstrained project having zero cutoff is equivalent to weak non-wastefulness. Suppose first that M is weakly non-wasteful. This means that there cannot exist an unconstrained project p and an applicant a such that $p \succ_a M(a)$, so indeed for all unconstrained project we can set the cutoff to be zero, and for the constrained projects we just set the cutoff to be equal to the score of lowest ranked applicant assigned. In the other direction, if we have cutoff scores satisfying that every unconstrained project has cutoff score zero, then there cannot exist an applicant a such that $p \succ_a M(a)$ for an unconstrained project p . \square

In the conference version of our paper [Aziz et al., 2020] we presented a polynomial-time algorithm that always returns a weakly stable matching based on the algorithm by Kamada and Kojima [2017b] (Appendix B.3 [Kamada and Kojima, 2017b]) In this extended version of our conference paper, we strengthen this result by showing that a so-called cutoff stable matching can also be computed efficiently for SIP, by designing an algorithm that also works for HER.

5 Cutoff stability

In this section, we discuss cutoff stability that applies to any matching problem with feasibility constraints.

We say that M is *cutoff non-wasteful* if M is non-wasteful and for every pair $(a,p) \notin M$, $p \succ_a M(a)$ implies that either

- $M \cup \{(a,p) \setminus (a,M(a))\}$ is not feasible, or
- there exists another applicant $a' \notin M(p)$, such that $a' \succ_p a$, $p \succ_{a'} M(a')$ and $(M \cup \{(a',p)\}) \setminus \{(a',M(a'))\}$ is not feasible, or
- project p is at capacity

We say a matching is *cutoff stable* if it is fair and cutoff non-wasteful.

We also define the notion of a matching induced by minimal cutoff scores, as explored by Fleiner and Jankó [2014] in a model without distributional constraints, and by Biró and Kiselgof [2015] for a college admission model with ties. Let d^{-p} denote the cutoff scores after decreasing the cutoff of p by one, and keeping the other cutoffs the same, i.e., $d^{-p}(p) = d(p) - 1$, and $d^{-p}(p') = d(p')$ for every $p' \neq p$. We say that cutoffs d are *minimal* if we cannot decrease the cutoff score of any project without making the induced matching infeasible. More formally for every project p , either $d(p) = 0$ or the matching induced by d^{-p} , which we call M^{-d} , is not feasible.

Proposition 3 *A matching is cutoff stable if and only if it is induced by minimal cutoff scores.*

Proof Due to Proposition 1, we only need to show that the minimality of the cutoff score is equivalent to cutoff non-wastefulness. Suppose first that matching M is induced by minimal cutoff scores d , which means that for any project p , if $d(p) > 0$ then d^{-p} is not feasible. Consider project p with $d(p) > 0$ and let a be the applicant who is assigned a score of $d^{-p}(p)$ by project p . M^{-p} , the matching induced d^{-p} , is not feasible which means $M^{-p} \neq M$. Therefore, $M^{-p} = (M \cup \{(a,p)\}) \setminus \{(a,M(a))\}$ and thus $p \succ_a M(a)$, which in turn means that a is the highest ranked applicant who forms a blocking pair with p . Thus, the induced matching M is cutoff non-wasteful. Now suppose that M is a cutoff stable matching and let d be some cutoff scores that induce M which are minimal in that sense that no smaller cutoff scores can induce M . Consider project p with $d(p) > 0$. The matching M^{-p} induced by d^{-p} must be different from M . Since M is cutoff non-wasteful, M^{-p} must be infeasible for every project p with $d(p) > 0$ and thus cutoffs d are minimal. \square

We can show the natural correspondence in between the three solution concepts as follows.

Proposition 4 *Every strongly stable matching is cutoff stable, and every cutoff stable matching is weakly stable.*

Proof By definition, strong non-wastefulness implies cutoff non-wastefulness, and cutoff non-wastefulness implies weak non-wastefulness. \square

Furthermore, these notions do not coincide, as illustrated in the following example.

Example 4 (An instance where the sets of strongly stable, cutoff stable and weakly stable matchings are distinct)

$$\begin{array}{lll}
 A = \{a_1, a_2, a_3\} & & \\
 \succ_{a_1}: p_1, p_2, p_3 & \succ_{a_2}: p_2, p_1 & \succ_{a_3}: p_3 \\
 P = \{p_1, p_2, p_3\} & c_{p_1} = c_{p_2} = c_{p_3} = 1 & \\
 \succ_{p_1}: a_2, a_1 & \succ_{p_2}: a_1, a_2 & \succ_{p_3}: a_1, a_3 \\
 S = \{s\} & P_s = \{p_1, p_2, p_3\} & q_s = 2
 \end{array}$$

Due to the supervisor capacity every feasible matching has size at most two, and any matching of size fewer than two is weakly wasteful. Thus, all the relevant matchings for weak, cutoff and strong stability have size two, so we consider all the matchings of size two below. $M_1 = \{(a_1, p_1), (a_2, p_2)\}$ and $M_2 = \{(a_1, p_2), (a_2, p_1)\}$ are strongly stable.

$M_3 = \{(a_1, p_2), (a_3, p_3)\}$ is not strongly stable, due to blocking pair (a_1, p_1) . However, M_3 is cutoff stable, since $a_2 \succ_{p_1} a_1$ and $M_3 \cup \{(a_2, p_1)\}$ is not feasible.

$M_4 = \{(a_1, p_3), (a_2, p_1)\}$ is not cutoff stable, due to blocking pairs (a_1, p_2) and (a_2, p_2) . However, M_3 is weakly stable as adding an applicant to a_2 results in an infeasible matching. All other matchings of size two are not fair or not feasible.

Note that for the classical college admission model these notions are equivalent to stability as formulated by Gale and Shapley [1962a]. Further theoretical findings about cutoff scores for this basic model are discussed by Azevedo and Leshno [2016].

5.1 Algorithm for computing a cutoff stable matching

We present an algorithm (Algorithm 1) that shows the existence of a cutoff stable matching for every instance of HER, and can compute a cutoff stable matching for an instance of SIP in strongly polynomial-time. Algorithm 1 has similarities with the algorithm proposed by Kamada and Kojima [2017b] which finds a weakly stable matching for HER. In contrast to the algorithm of Kamada and Kojima [2017b], we do not explicitly work with a set of blocking of pairs, but with cutoff scores. Furthermore, a blocking pair (a, p) was satisfied in Kamada and Kojima [2017b] whenever the new matching $M \cup \{(a, p)\}$ stayed feasible, leading to a weakly stable solution in the end, whilst we satisfy a blocking pair (a, p) if $(M \cup \{(a, p)\}) \setminus \{(a, M(a))\}$ stay feasible, leading to a cutoff stable matching. Algorithm 1 can also be viewed as a modified version of the Fleiner-Jankó score-decreasing algorithm (see subsection 4.3 in Fleiner and Jankó [2014]). Whereas Fleiner and Jankó [2014] do not consider distributional constraints, our goal is to achieve stability properties under general heredity constraints. Finally, in independent and recent work, Kamada and Kojima [2020] consider a fixed-point approach based on cutoffs. However, their heredity constraints apply to individual hospitals/projects and cannot capture SIP or regional constraints.

The idea of Algorithm 1 is simple. We start with maximum cutoffs that induce the empty matching and then we gradually decrease them until we can no longer do so without making the induced matching infeasible. Note

that for the classical college admission problem this process is equivalent to the college proposing Gale-Shapley algorithm [Gale and Shapley, 1962a], that was observed in the Turkish college admission practice [Balinski and Sönmez, 1999], and also in the Hungarian college admission scheme [Biró and Kiselgof, 2015] in a more general form, as ties have been present in the rankings.

Input: lists \succ_p for all $p \in P$ and \succ_a for all $a \in A$; feasibility function f ; project order $P^* = (p_1, \dots, p_k)$
Output: Matching M and corresponding cutoffs d_M
1: Initialize M to empty and $d_M(p) = |A| + 1$ for every project p .
2: **while** Cutoff d_M are not minimal **do**
3: Locate the first p_j in the list P^* such that M^{-p_j} is feasible.
4: Let $M = M^{-p_j}$ and $d_M = d_M^{-p_j}$.

Algorithm 2: Algorithm for matching with heredity constraints.

Theorem 3 *A cutoff stable matching always exists for a matching problem under any set of distributional constraints that can be represented by a feasibility function, i.e., for the HER model. Algorithm 1 produces one such matching.*

Proof Note that M remains feasible and also fair during the algorithm since it is induced by cutoffs. The final matching is cutoff stable, due to Proposition 3, since the algorithm terminates when the cutoffs are minimal. \square

We remark here that the argument for Theorem 3 does not require projects to be selected in the order P^* .

The next theorem shows that as long as the feasibility of a matching can be tested in polynomial time, Algorithm 1 runs in polynomial time.

Theorem 4 *Suppose checking $f(w)$ takes t time. Then, the running time of Algorithm 1 is $O(|A||P|^2t)$.*

Proof We decrease the cutoffs in at most $(|A|+1)|P|$ rounds. In every round we potentially need to check the matching induced by decrementing the cutoff of each of $|P|$ projects. To do this for project p_j , we compute matching M^{-p_j} from the current matching M , by simply comparing whether the newly admitted applicant a_i with score $d_M^{-p_j}$ from p_j prefers p_j to her current match $M(a_i)$, and if so, whether the new matching $(M \cup \{(a_i, p_j)\}) \setminus \{(a_i, M(a_i))\}$ is feasible. By assuming that checking the feasibility of a matching takes t time, the overall run time of the algorithm is $O(|A||P|^2t)$. \square

We note that Algorithm 1 can be applied to the summer internship problem where the feasibility function is based on the supervisor budgets. Therefore, for the summer internship problem a cutoff stable matching exists. Furthermore, from Theorem 1 we know that the feasibility of a matching can be checked in polynomial time, and thus a cutoff stable matching can be found in polynomial time.

Additionally, using the cutoff-decreasing algorithm we can find a natural relationship between weakly stable and cutoff stable matchings.

Proposition 5 *Every weakly stable matching that is not cutoff stable is Pareto-dominated by a cutoff stable matching for the applicants.*

Proof Let M be a weakly stable matching that is not cutoff stable. Since M is fair, it can be induced by cutoff scores, but these cutoff scores are not minimal, since M is not cutoff stable. Therefore, we can gradually decrease these cutoff scores as described in the cutoff decreasing process until we reach a cutoff stable matching M' . Note that M' Pareto-dominates M since decreasing cutoff scores can only make the applicants better off, and every change in the matching means a strict improvement for at least one applicant. \square

Although Algorithm 1 satisfies cutoff stability, it also has some drawbacks. Next we establish some properties of the algorithm.

Theorem 5 *The following properties hold for Algorithm 1.*

1. *Algorithm 1 is not strategyproof for the applicants.*
2. *Algorithm 1 does not always find a strongly stable matching whenever one exists.*
3. *Changing the order of projects ordered after p by P^* can change p 's allocation.*
4. *There exist cutoff stable matchings that cannot be produced as a result of Algorithm 1 by changing the project order P^* .*

Proof We prove each of the statements separately.

1. Consider the following instance.

$$\begin{array}{lll} A = \{a_1, a_2\} & \succ_{a_1}: p_2, p_1 & \succ_{a_2}: p_2 \\ P = \{p_1, p_2\} & \succ_{p_1}: a_2, a_1 & \succ_{p_2}: a_2, a_1 \\ S = \{s\} & P_s = \{p_1, p_2\} & q_s = c_{p_1} = c_{p_2} = 1 \end{array}$$

If we set $P^* = (p_1, p_2)$ then the algorithm outputs $M = \{(a_1, p_1)\}$. However, if a_2 were to modify their preferences to $\succ_{a_2}: p_2, p_1$, then the algorithm will output $M = \{(a_2, p_2)\}$, which is preferred by a_2 . Thus, the algorithm is not strategy-proof for applicants.

2. For the example above, since (a_2, p_2) is the only strongly stable matching, the algorithm does not find the strongly stable matching when one exists.
3. Consider the following instance.

$$\begin{array}{lll} A = \{a_1, a_2, a_3\} & & \\ \succ_{a_1}: p_2, p_1 & \succ_{a_2}: p_1, p_2 & \succ_{a_3}: p_3 \\ P = \{p_1, p_2, p_3\} & & \\ \succ_{p_1}: a_1, a_2 & \succ_{p_2}: a_2, a_1 & \succ_{p_3}: a_3 \\ S = \{s\} & P_s = P & \\ c_{p_1} = c_{p_3} = 1 & c_{p_2} = 2 & q_s = 2 \end{array}$$

Setting $P^* = (p_1, p_2, p_3)$, the algorithm terminates in the matching $M = \{(a_1, p_2), (a_2, p_1)\}$. However, if we set $P^* = \{p_1, p_3, p_2\}$, a_1 gets matched to p_1 and then a_3 gets matched to p_3 . At this point $C_{p_2} = \emptyset$ since

$$f(\{(a_1, p_1), (a_3, p_3), (a_2, p_2)\}) = 0$$

, so the algorithm terminates with matching $M = \{(a_1, p_1), (a_3, p_3)\}$. This shows that changing the order of projects ordered after p by P^* can change p 's allocation.

4. This is a consequence of the project-proposing nature of the algorithm. Consider the following instance.

$$\begin{array}{lll}
A = \{a_1, a_2\} & \succ_{a_1}: p_1, p_2 & \succ_{a_2}: p_2, p_1 \\
P = \{p_1, p_2\} & \succ_{p_1}: a_2, a_1 & \succ_{p_2}: a_1, a_2 \\
S = \{s\} & P_s = P & \\
c_{p_1} = c_{p_2} = 1 & q_s = 2 &
\end{array}$$

Both possible project orders produce $M = \{(a_2, p_1), (a_1, p_2)\}$, but the matching $M = \{(a_1, p_1), (a_2, p_2)\}$ is also cutoff stable. Thus, there exist weakly stable matchings that cannot be produced by the algorithm.

This completes the proof. \square

Since the examples above contain exactly one supervisor, Theorem 5 also applies to REG and any setting that contains REG as a special case.

5.2 Finding a maximum size cutoff stable matching

First, we show that this problem is NP-hard for the REG model by reducing it from MAX-SMTI. Then we provide a mixed integer linear programming formulation.

In the proof we will use a gadget equivalent to the problem in Example 2, where we have no strongly stable matching, but we have two cutoff stable matchings, namely $\{a_1, p_1\}$ and $\{a_2, p_2\}$.

Theorem 6 *Finding a maximum size cutoff stable matching for regional quotas is NP-hard.*

Proof We reduce again from the special version of the MAX-SMTI problem [Manlove et al., 2002]. Suppose that we have an instance I of MAX-SMTI. We will create an instance I' of SIP, such that the maximum size of the cutoff stable in I' is the same as the maximum size weakly stable matching in I . For I we use the same notation of $W = W^s \cup W^t$ to denote the set of women with strict preferences and with a single tie, respectively, and let U denote the set of men. Every men in I will be replaced by an applicant in I' with essentially the same preferences. Now, every woman in $w_j \in W^s$ will be replaced with a single project p_j with identical preferences. For every woman $w_j \in W^t$ we create two projects, p_j^1 and p_j^2 that will correspond to the projects in Example 2. If u_i and u_k were the two men in the single tie of w_j in I then let the two corresponding applicants a_i and a_k complete the instance of Example 2. So the preference lists of the projects are $\succ_{p_j^1}: a_i, a_k$ and $\succ_{p_j^2}: a_k, a_i$, whilst a_i will have p_j^2 and p_j^1 in her list with preference for the former, and a_k will also have them both with opposite preferences. For the reduction we have to show that if M is a weakly stable matching in I then there is a corresponding cutoff stable matching M' in I' with the same size, and vica versa. The correspondence between the matchings is as follows.

- for every $w_j \in W^s$ and $u_i \in U$, $(u_i, w_j) \in M \iff (a_i, p_j) \in M'$
- for every $w_j \in W^t$ and $u_i \in U$, where u_i is the first man in the tie of w_j , $(u_i, w_j) \in M \iff (a_i, p_j^1) \in M'$
- for every $w_j \in W^t$ and $u_k \in U$, where u_k is the second man in the tie of w_j , $(u_k, w_j) \in M \iff (a_k, p_j^2) \in M'$

We can observe that the sizes of M and M' are the same. \square

Note that since MAX-SMTI is not approximable within a factor of $21/19$ unless $P = NP$ [Halldórsson et al., 2007], due to the one-to-one relation of the sizes of the matchings in our reduction, the same inapproximability result applies for our problem as well. Furthermore, we also note that the very same result applies for weak stability, since for Example 2 the cutoff stable matchings are the same as the weakly stable matchings, and so the very same reduction works also to show the NP-hardness of the problem of finding a maximum size weakly stable matching.

MILP-formulation

The mixed integer linear program will have three main parts. The first set of constraints describe the feasibility of the funding allocation. The matching in between applicants and projects are described with (0-1) binary variables defined for every mutually acceptable applicant-project pair, as follows, let $y_{a,p} = 1 \iff (a,p) \in M$. Let $x_{s,p}$ be a non-negative continuous variable denoting the funding for project p provided by supervisor s . The following three sets of conditions ensures the feasibility of the solution.

$$\text{Applicant-feasibility: } \sum_{p \in P} y_{a,p} \leq 1 \text{ for each } a \in A \quad (1)$$

$$\text{Project-feasibility: } \sum_{a \in A} y_{a,p} = \sum_{s \in S} x_{s,p} \text{ for each } p \in P \quad (2)$$

$$\text{Applicant-feasibility: } \sum_{p \in P} x_{s,p} \leq q_s \text{ for each } s \in S \quad (3)$$

The second set of constraints will describe the fairness of the matching by means of cutoff scores. Let $z_{a,p}$ be the score of applicant a at project p , a given constant integer in the interval $[0, |A|]$. For every project p , let $d(p)$ be an integer variable in the range of $[0, |A| + 1]$ denoting the cutoff of project p . We can link the cutoff scores with the induced matching M by the following set of constraints, as also used in Ágoston et al. [2016] and Delorme et al. [2019].

$$d(p) \leq (1 - y_{a,p})(|A| + 1) + z_{a,p} \text{ for each } (a,p) \quad (4)$$

The above constraint enforces that if an applicant is assigned to a project then she reached the cutoff there.

$$z_{a,p} + 1 \leq d(p) + \left(\sum_{p' \succeq_a p} y_{a,p'} \right) \cdot (|A| + 1) \text{ for each } (a,p) \quad (5)$$

This constraint implies that if the applicant is rejected from project p , so she is not admitted there and nor to any better project of her preference (in which case the sum term is zero on the right hand side), then the cutoff must be higher at p than her score there. These two sets of conditions together imply that every student is admitted to her most preferred project where she achieved the cutoff, which means that we get the matching induced by the cutoffs.

For ensuring cutoff stability we have to provide cutoff non-wastefulness by enforcing that the cutoffs are minimal. This can be achieved by simply minimizing the sum of the cutoff scores in the objective function of the MILP. To see this we just need to observe that if the matching would not be cutoff minimal, so we could decrease some of the cutoffs by keeping the solution feasible, but then the solution was not optimal with respect to this objective function.

Finally, if we want to maximize the number of applicants matched in the cutoff stable solution then we can use the following combined objective function, where W is a large enough constant.

$$\max \sum_{a \in A, p \in P} W \cdot y_{a,p} - \sum_{p \in P} d(p) \quad (6)$$

This completes the MILP for finding a maximum size cutoff stable matching.

6 Egalitarian Budget Allocations

Given a feasible matching M , there can exist multiple ways to allocate supervisor budgets among projects to fund all applicants matched to them. Our goal is to find a method for the fairest such allocation. We have chosen to deal with fairness post-match, in order to find a solution that does not constrain the set of feasible matchings.

For each supervisor $s \in S$, and each project they supervise $p \in P_s$ set $0 < t_{s,p} \leq 1$ such that, for each $p \in P$, $\sum_{s \in S_p} t_{s,p} = 1$. Call this the normative ‘target’ - how much we would want s to contribute to the funding of any applicant matched to p . For instance, if we would ideally want the supervisors of any given project to contribute equally to its funding, we would set: $t_{s,p} = \frac{|M(p)|}{|S_p|} \quad \forall p \in P, s \in S_p$. However, given a feasible matching M , some supervisors may lack sufficient funding to reach these targets. Therefore, we seek to find a funding allocation that is closest to the target allocations. In order to define closest, we consider specific lexicographic comparisons. Let $X = \{x_{s,p}\}_{s \in S, p \in P_s}$ be a feasible funding allocation for matching M . Denote by ϕ_X the vector corresponding to the weakly decreasing ordering of the set: $\left\{ \frac{x_{s,p}}{t_{s,p}} \right\}_{s \in S, p \in P_s}$. Denote by Φ_M the set of such vectors corresponding to all feasible funding allocations for matching M .

The **egalitarian feasible funding allocation** for matching M is the funding allocation corresponding to $\phi^* \in \Phi_M$ such that for all $\phi \in \Phi_M$, $\phi^* \prec_{lex} \phi$, where \prec_{lex} refers to the well-known lexicographic order. This is exactly equivalent to finding the leximin optimum of the following set: $\left\{ \frac{-x_{s,p}}{t_{s,p}} \right\}_{s \in S, p \in P_s}$. The egalitarian feasible funding allocation can be achieved via Algorithm 3, which runs a series of linear programs.

Theorem 7 *Given a feasible matching, the egalitarian funding allocation can be computed in time $O(|S|^2|P|^2)LP(O(|S| \cdot |P|))$, where LP refers to the running time of the linear programming algorithm used.*

Proof The algorithm solves a series of linear programs with $O(|S| \cdot |P|)$ constraints. The while loop iterates at most $|T| \leq |S||P|$ times, as the algorithm adds

Input: $T = \{(s,p) | s \in S, p \in P_s\}$, $q_s \forall s \in S$ and $\{t_{s,p} | (s,p) \in T\}$.
Output: Funding allocation x

- 1: $T_{tight} \leftarrow \emptyset$
- 2: **while** $T_{tight} \neq T$ **do**
- 3: Minimise the maximal component of $\left\{ \frac{x_{s,p}}{t_{s,p}} | (s,p) \in T \right\}$ that is not yet tight by solving the following LP:

$$\begin{aligned} \lambda^* &\leftarrow \text{Min } \lambda \text{ s.t.} \\ x_{s,p} &\geq 0 \quad \forall (s,p) \in T \\ \sum_{s \in S_p} x_{s,p} &= |T(p)| \quad \forall p \in P \\ \sum_{p \in P_s} x_{s,p} &\leq q_s \quad \forall s \in S \\ \frac{x_{s,p}}{t_{s,p}} &\leq \lambda \quad \forall (s,p) \in T \setminus T_{tight} \\ \frac{x_{s,p}}{t_{s,p}} &= \lambda_{s,p} \quad \forall (s,p) \in T_{tight} \end{aligned}$$
- 4: **for** $(s,p)^* \in T \setminus T_{tight}$ **do**
- 5: Determine whether the constraint corresponding to $(s,p)^*$ is tight by solving the following Auxiliary LP:

$$\begin{aligned} \epsilon^* &\leftarrow \text{Max } \epsilon \quad \text{s.t.} \\ x_{s,p} &\geq 0 \quad \forall (s,p) \in T \\ \sum_{s \in S_p} x_{s,p} &= |T(p)| \quad \forall p \in P \\ \sum_{p \in P_s} x_{s,p} &\leq q_s \quad \forall s \in S \\ \frac{x_{s,p}}{t_{s,p}} &\leq \lambda^* \quad \forall (s,p) \in T \setminus T_{tight} \setminus \{(s,p)^*\} \\ \frac{x_{s,p}}{t_{s,p}} &= \lambda_{s,p} \quad \forall (s,p) \in T_{tight} \\ \frac{x_{s,p}}{t_{s,p}} + \epsilon &\leq \lambda^* \quad \text{for } (s,p) = (s,p)^* \end{aligned}$$
- 6: **if** $\epsilon^* = 0$ **then**
- 7: Add $(s,p)^*$ to T_{tight}
- 8: $\lambda_{s,p} \leftarrow \lambda^*$
- 9: **return** $\{\lambda_{s,p} | (s,p) \in T\}$

Algorithm 3: Computing an egalitarian funding allocation for a given feasible matching

at least one element to the set T_{tight} in every iteration. The for loop also iterates at most $|T|$ times. Thus, the overall complexity is $O(|S|^2|P|^2)LP(O(|S| \cdot |P|))$, where LP refers to the running time of the linear programming algorithm used. Since linear programs can be solved in polynomial time, the egalitarian funding allocation can also be computed in polynomial time. \square

7 Conclusion

We presented a novel matching model that captures many real-world scenarios. For the model, we presented a compelling solution that is polynomial-time and satisfies stability and fairness properties. Our central algorithm computes a cutoff stable matching even for the general matching model with heredity constraints. Hence, it applies to many applications such as refugee matching that involve heredity constraints.

Several directions and problems arise as a result of our study. Our approach to finding a fair budget allocation was to first compute a cutoff stable matching and then find an egalitarian budget allocation. It will be interesting to explore a fair outcome that is fairest in some global sense across all weakly stable matchings. We showed that the algorithm we consider is not strategyproof for applicants. It is open whether there exists an algorithm that is strategyproof and satisfies weak stability or cutoff stability.

Acknowledgments

Aziz gratefully acknowledges support from Defence Science and Technology (DST). Baychkov's work was supported by the CSIRO undergraduate vacation scholarship program, and he extends many thanks to Haris Aziz and Gavin Walker for their invaluable mentorship. Biró is supported by the Hungarian Scientific Research Fund, OTKA, Grant No. K128611.

References

- A. Abdulkadiroğlu and T. Sönmez. School choice: A mechanism design approach. *American Economic Review*, 93(3):729–747, 2003a.
- A. Abdulkadiroğlu and T. Sönmez. School choice: A mechanism design approach. *American Economic Review*, 93(3):729–747, 2003b.
- D. J. Abraham, R. W. Irving, and D. Manlove. Two algorithms for the student-project allocation problem. *J. Discrete Algorithms*, 5(1):73–90, 2007.
- K. C. Ágoston, P. Biró, and I. McBride. Integer programming methods for special college admissions problems. *Journal of Combinatorial Optimization*, 32(4):1371–1399, 2016.
- K. C. Ágoston, P. Biró, and R. Szántó. Stable project allocation under distributional constraints. *Operations Research Perspectives*, 5:59–68, 2018.
- R. K. Ahuja, T. L. Magnanti, and J. B. Orlin. *Network Flows: Theory, Algorithms, and Applications*. Prentice Hall, 1993.
- G. Artemov, Y.-K. Che, and Y. He. Strategic ‘mistakes’: Implications for market design research. *Work. Pap., Melbourne Univ., Melbourne, Aust*, 2017.
- E. M. Azevedo and J. D. Leshno. A supply and demand framework for two-sided matching markets. *Journal of Political Economy*, 124(5):1235–1268, 2016.
- H. Aziz, J. Chen, S. Gaspers, and Z. Sun. Stability and pareto optimality in refugee allocation matchings. In *Proc. of 17th AAMAS Conference*, pages 964–972, 2018.
- H. Aziz, S. Gaspers, Z. Sun, and T. Walsh. From matching with diversity constraints to matching with regional quotas. In *Proc. of 18th AAMAS Conference*, pages 377–385, 2019.
- H. Aziz, A. Baychkov, and P. Biró. Summer internship matching with funding constraints. In *Proc. of 19th AAMAS Conference*, pages 97–104, 2020.
- M. Baïou and M. Balinski. The stable admissions polytope. *Mathematical Programming*, 87(3):427–439, 2000.
- M. Balinski and T. Sönmez. A tale of two mechanisms: Student placement. *Journal of Economic theory*, 84(1):73–94, 1999.
- P. Biró. Applications of matching models under preferences. In *Trends in Computational Social Choice*, pages 345–373. AI Access Foundation, 2017.

- P. Biró and S. Kiselgof. College admissions with stable score-limits. *Central European Journal of Operations Research*, 23(4):727–741, 2015.
- P. Biro, T. Fleiner, R. W. Irving, and D. F. Manlove. The college admissions problem with lower and common quotas. *Theoretical Computer Science*, 411(34–36):3136–3153, 2010.
- P. Biró, D. F. Manlove, and I. McBride. The hospitals/residents problem with couples: Complexity and integer programming models. In *International Symposium on Experimental Algorithms*, pages 10–21. Springer, 2014.
- D. Delacrétaz, S. D. Kominers, and A. Teytelboym. Refugee resettlement. 2016.
- M. Delorme, S. García, J. Gondzio, J. Kalcsics, D. Manlove, and W. Pettersson. Mathematical models for stable matching problems with ties and incomplete lists. *European Journal of Operational Research*, 277(2):426–441, 2019.
- F. Echenique and M. B. Yenmez. How to control controlled school choice. *American Economic Review*, 105(8):2679–94, August 2015.
- T. Fleiner and Z. Jankó. Choice function-based two-sided markets: stability, lattice property, path independence and algorithms. *Algorithms*, 7(1):32–59, 2014.
- D. Fragiadakis and P. Troyan. Improving matching under hard distributional constraints. *Theoretical Economics*, 12(2):863–908, 2017.
- D. Fragiadakis, A. Iwasaki, P. Troyan, S. Ueda, and M. Yokoo. Strategyproof matching with minimum quotas. *ACM Transactions on Economics and Computation*, 4(1):1–40, 2016.
- D. Gale and L. S. Shapley. College admissions and the stability of marriage. *The American Mathematical Monthly*, 69(1):9–15, 1962a.
- D. Gale and L. S. Shapley. College admissions and the stability of marriage. *The American Mathematical Monthly*, 69(1):9–15, 1962b.
- M. Goto, A. Iwasaki, Y. Kawasaki, R. Kurata, Y. Yasuda, and M. Yokoo. Strategyproof matching with regional minimum and maximum quotas. *Artificial intelligence*, 235:40–57, 2016.
- M. Goto, F. Kojima, R. Kurata, A. Tamura, and M. Yokoo. Designing matching mechanisms under general distributional constraints. *American Economic Journal: Microeconomics*, 9(2):226–262, 2017.
- P. Guillen, O. Kesten, A. Kiefer, and M. Melatos. A field evaluation of a matching mechanism: University applicant behaviour in australia. Technical report, 2020.
- M. M. Halldórsson, K. Iwama, S. Miyazaki, and H. Yanagisawa. Improved approximation results for the stable marriage problem. *ACM Transactions on Algorithms (TALG)*, 3(3):30–es, 2007.
- A. Ismaili, T. Yamaguchi, and M. Yokoo. Student-project-resource allocation: Complexity of the symmetric case. In *PRIMA 2018: Principles and Practice of Multi-Agent Systems*, pages 226–241. Springer Verlag, 2018.
- A. Ismaili, N. Hamada, Y. Zhang, T. Suzuki, and M. Yokoo. Weighted matching markets with budget constraints. *J. Artif. Intell. Res.*, 65:393–421, 2019.
- Y. Kamada and F. Kojima. Efficient matching under distributional constraints: Theory and applications. *American Economic Review*, 105(1):67–99, 2015.
- Y. Kamada and F. Kojima. Recent developments in matching with constraints. *The American Economic Review*, 107(5):200–204, 2017a.
- Y. Kamada and F. Kojima. Stability concepts in matching under distributional constraints. *Journal of Economic Theory*, 168:107–142, 2017b.
- Y. Kamada and F. Kojima. Stability and strategy-proofness for matching with constraints: A necessary and sufficient condition. *Theoretical Economics*, 13(2):761–793, 2018.
- Y. Kamada and F. Kojima. Fair matching under constraints: Theory and applications. June 2020.
- Y. Kawase and A. Iwasaki. Near-feasible stable matchings with budget constraints. In *Proceedings of the Twenty-Sixth International Joint Conference on Artificial Intelligence, IJCAI-17*, pages 242–248, 2017.
- Y. Kawase and A. Iwasaki. Approximately stable matchings with budget constraints. In *Proceedings of the Thirty-Second AAAI Conference on Artificial Intelligence, (AAAI-18)*, pages 1113–1120, 2018.
- R. Kurata, N. Hamada, A. Iwasaki, and M. Yokoo. Controlled school choice with soft bounds and overlapping types. *Journal of Artificial Intelligence Research*, 58:153–184, 2017.
- A. Kwanashie and D. F. Manlove. An integer programming approach to the hospitals/residents problem with ties. In *Operations Research Proceedings 2013*, pages 263–269. Springer, 2014.
- V. Malhotra, M. P. Kumar, and S. N. Maheshwari. An $O(|V|^3)$ algorithm for finding maximum flows in networks. *Information Processing Letters*, 7(6):277–278, 1962.

- D. F. Manlove. *Algorithmics of Matching Under Preferences*. World Scientific Publishing Company, 2013.
- D. F. Manlove, R. W. Irving, K. Iwama, S. Miyazaki, and Y. Morita. Hard variants of stable marriage. *Theoretical Computer Science*, 276(1–2):261–279, 2002.
- A. E. Roth. On the allocation of residents to rural hospitals: a general property of two-sided matching markets. *Econometrica: Journal of the Econometric Society*, pages 425–427, 1986.
- A. E. Roth. Deferred acceptance algorithms: history, theory, practice, and open questions. *International Journal of Game Theory*, 36:537–569, 2008.