

# A Survey on Stance Detection for Mis- and Disinformation Identification

Momchil Hardalov<sup>1,2\*</sup>, Arnav Arora<sup>1,3</sup>, Preslav Nakov<sup>1,4</sup> and Isabelle Augenstein<sup>1,3</sup>

<sup>1</sup>CheckStep Research

<sup>2</sup>Sofia University “St. Kliment Ohridski”, Bulgaria

<sup>3</sup>University of Copenhagen, Denmark

<sup>4</sup>Qatar Computing Research Institute, HBKU, Doha, Qatar  
{momchil, arnav, preslav.nakov, isabelle}@checkstep.com

## Abstract

Detecting attitudes expressed in texts, also known as *stance detection*, has become an important task for the detection of false information online, be it misinformation (unintentionally false) or disinformation (intentionally false, spread deliberately with malicious intent). Stance detection has been framed in different ways, including: (a) as a component of fact-checking, rumour detection, and detecting previously fact-checked claims; or (b) as a task in its own right. While there have been prior efforts to contrast stance detection with other related social media tasks such as argumentation mining and sentiment analysis, there is no survey examining the relationship between stance detection and mis- and disinformation detection from a holistic viewpoint, which is the focus of this survey. We review and analyse existing work in this area, before discussing lessons learnt and future challenges.

## 1 Introduction

In the past decade, there has been a rapid growth in popularity of social media platforms such as Facebook, Twitter, Reddit and Parler.<sup>1</sup> Moreover, controversial events such as Brexit and the US presidential election, as well as the emergence of the COVID-19 pandemic that brought an infodemic [Alam et al., 2020] with it. This, in turn, has led to a flood of dubious content, both in mainstream media and online, raising yet another red flag reminding us of the ever growing need for effective detection of mis- and disinformation.

In this work, we examine the relationship between automatically detecting false information online – including fact-checking, detecting fake news, rumors, and hoaxes – and the core underlying Natural Language Processing (NLP) task needed to achieve this, namely stance detection. Therein, we consider both the phenomena of mis- and disinformation. The latter two differ by the underlying intention of disinformation to do harm. This is illustrated in the definitions of

these notions by Claire Wardle from First Draft,<sup>2</sup> *misinformation* is “*unintentional mistakes such as inaccurate photo captions, dates, statistics, translations, or when satire is taken seriously.*”, and *disinformation* is “*fabricated or deliberately manipulated audio/visual context, and also intentionally created conspiracy theories or rumours.*”. While the intent to do harm is very important, it is also very hard to prove. Thus, the vast majority of work has focused on factuality, thus treating misinformation and disinformation as part of the same problem: spread of false information (regardless of whether this is done with harmful intent). This is also the approach we will adopt in this survey.

Detecting and aggregating the expressed stances towards a piece of information can be a powerful tool for a variety of tasks like understanding ideological debates [Hasan and Ng, 2014], gathering different frames of a particular issue [Shurafa et al., 2020] or determining leanings of different media outlets [Stefanov et al., 2020]. The task of stance detection has been studied from different angles, e.g., in political debates [Habernal et al., 2018], for fact-checking [Thorne et al., 2018], or regarding new products [Somasundaran and Wiebe, 2009]. Further, different types of text have been studied, including social media posts [Zubiaga et al., 2016a] and news articles [Pomerleau and Rao, 2017]. Finally, stances expressed by different actors have been considered, such as politicians [Johnson and Goldwasser, 2016], journalists [Hanselowski et al., 2019], users on the web [Derczynski et al., 2017].

There have been a couple of recent surveys related to stance detection. Zubiaga et al. [2018a] present a survey on rumour veracity prediction, where they discussed stance as a component of the rumour verification pipeline, and Küçük and Can [2020] give a holistic view on the stance detection task in general.

However, there is no existing overview of how different formulations of the task play a role in the detection of false information. This could be as a standalone task – to gather stances of users or texts towards a claim (to aid in the fact-checking process or studying misinformation), or as a component of an automated system which uses stance as features

\*Contact Author

<sup>1</sup><https://www.digitalinformationworld.com/2021/02/social-media-platforms-peak-points.html>

<sup>2</sup><http://firstdraftnews.org/wp-content/uploads/2018/07/Types-of-Information-Disorder-Venn-Diagram.png>

Dataset	Source(s)	Target	Context	Evidence	#Instances	Task
<b>English Datasets</b>						
<i>Rumour Has It</i> [Qazvinian et al., 2011]		Topic	Tweet		10K	Rumours
<i>PHEME</i> [Zubiaga et al., 2016a]		Claim	Tweet		7.5K	Rumours
<i>Emergent</i> [Ferreira and Vlachos, 2016]		Headline	Article*		2.6K	Rumours
<i>FNC-1</i> [Pomerleau and Rao, 2017]		Headline	Article		75K	Fake news
<i>RumourEval '17</i> [Derczynski et al., 2017]		Implicit <sup>‡</sup>	Tweet		7.1K	Rumours
<i>FEVER</i> [Thorne et al., 2018]		Claim	Facts		185K	Fact-checking
<i>Snopes</i> [Hanselowski et al., 2019]	Snopes	Claim	Snippets		19.5K	Fact-checking
<i>RumourEval '19</i> [Gorrell et al., 2019]		Implicit <sup>‡</sup>	Post		8.5K	Rumours
<i>COVIDLies</i> [Hossain et al., 2020]		Claim	Tweet		6.8K	Misconceptions
<i>TabFact</i> [Chen et al., 2020]		Statement	WikiTable		118K	Fact-checking
<b>Non-English Datasets</b>						
<i>Arabic</i> [Baly et al., 2018]		Claim	Document		3K	Fact-checking
<i>DAST (Danish)</i> [Lillie et al., 2019]		Submission	Comment		3K	Rumour
<i>Croatian</i> [Bošnjak and Karan, 2019]		Title	Comment		0.9K	Claim verifiability
<i>Arabic</i> [Khouja, 2020]		Claim	Title		3.8K	Claim verification

Table 1: Key characteristics of the stance detection datasets for mis- and disinformation detection. #Instances denotes dataset size as a whole; the numbers are in thousands (K) and are rounded to the hundreds. \*the article’s body is summarised. †the stance is expressed towards a topic, which is not present in the data. Sources: Twitter, News, Wikipedia, Reddit. Evidence: Single, Multiple, Thread.

for determining veracity. With this survey, we aim to bridge this gap, present some emerging trends from this space and discuss the challenges ahead.

## 2 What is Stance?

In order to understand the task of stance detection, we first provide definitions of stance and the stance-taking process. Biber and Finegan (1988) define stance as the expression of a speaker’s standpoint and judgement towards a given proposition. Further, Du Bois (2007) define stance as “A public act by a social actor, achieved dialogically through overt communicative means, of simultaneously evaluating objects, positioning subjects (self and others), and aligning with other subjects, with respect to any salient dimension of the sociocultural field”, showing that the stance-taking process is affected not only by one’s personal opinion, but also by other external factors such as cultural norms, roles in the institution of the family, etc. For the purpose of this survey, we adopt the general definition of stance detection from Küçük and Can [2020]: “for an input in the form of a piece of text and a target pair, stance detection is a classification problem where the stance of the author of the text is sought in the form of a category label from this set: Favor, Against, Neither. Occasionally, the category label of Neutral is also added to the set of stance categories [Mohammad et al., 2016], and the target may or may not be explicitly mentioned in the text [Augenstein et al., 2016a; Mohammad et al., 2016]. Note that the stance detection definitions and the label inventories vary somewhat dependent on the target application (see Section 3).

Finally, stance detection can be distinguished from several other closely related NLP tasks: (i) *Biased Language Detection*, where the existence of an inclination or tendency towards a particular perspective within a text is explored;

(ii) *Emotion Recognition*, where the goal is to recognise emotions such as *love, anger, sadness, etc.* in the text; (iii) *Perspective Identification*, which aims to find the point-of-view of the author (e.g., Democrat vs. Republican) and the target is always explicit; (iv) *Sarcasm Detection*, where the interest is in satirical or ironic pieces of text, which are often written with the intent of ridicule or mockery; (v) *Sentiment Analysis*, which determines the polarity of a piece of text.

## 3 Stance and Factuality

In this section, we discuss the different aspects of mis- and disinformation identification, where stance detection has been successfully applied, i.e., fake news detection, rumour verification and debunking, misconception identification, and fact-checking, both as a task on its own or as a component of a pipeline. In Table 1, we provide an overview of the key characteristics of the available datasets for each task. There, we include the *source* from which the data is collected, the *target* towards which the stance is expressed in the provided *context*. Further, we show the type of evidence: *Single* is a single document/fact, *Multiple* is multiple pieces of text evidence, often facts or documents, *Thread* is a (conversational) sequence of posts or a discussion. The final column is the type of the target *Task*.

### 3.1 Fact-Checking as Stance Detection

As stance detection is the core task within fact-checking, prior work has studied it in isolated, artificial task settings – predicting the stance towards one or several documents.

#### Fact-Checking with One Evidence Document

Pomerleau and Rao [2017] organised the first Fake News Challenge<sup>3</sup> (FNC-1) with the aim of automatically detecting fake news. The goal was to detect the relatedness of a news

<sup>3</sup><http://www.fakenewschallenge.org/>

article’s body to a headline (possibly from another news article), based on the stance that the former takes regarding the latter. The possible categories are *positive*, *negative*, *discuss* and *unrelated*. This is a standalone task, as it provides annotations only for the stance, and omits the actual “truth labels”; however, the system can be further integrated as a component of a fact-checking system. The motivation behind creating a stance detection instead of a full-blown fact-checking task was that with a successful stance detection model, a human fact-checker would be able to enter a claim or a headline and instantly retrieve the top articles which agree, disagree, or discuss the claim/headline in question. They could then look at the arguments for and against the claim, and use their human judgment and reasoning skills to assess the validity of the claim in question. Such a tool would enable human fact-checkers to be fast and effective.

**Fact-Checking with Multiple Evidence Documents** The FEVER [Thorne et al., 2018; Thorne et al., 2019] shared task was introduced in 2018 and extended in 2019, with the goal of assessing the veracity of a claim based on a set of supporting statements from Wikipedia. However, claims can be composite and can contain multiple (contradicting) statements, thus making multi-hop reasoning a required skill for solving the task. The authors offered claim–evidence pairs annotated into three categories: *SUPPORTED*, *REFUTED*, and *NO ENOUGH INFO*. The last category includes claims which are either too general or too specific, and thereby cannot be supported or refuted by the available information in Wikipedia. This kind of setup may help fact-checkers to understand the decisions that the models made in their assessment of the veracity of a claim, or can navigate a human to the final judgement. The second edition (2019) of the task evaluated how robust the models are with respect to adversarial attacks, where the participants were tasked with building new examples to “break” the existing models, and then to propose “fixes” in order to improve the system robustness to such attacks.

Hanselowski et al. [2019] presented a task constructed from manually fact-checked claims on the Snopes<sup>4</sup> fact-checking portal. For this task, a model has to predict the stance of evidence sentences from articles written by journalists towards claims. In contrast to FEVER, the task does not require multi-hop reasoning.

Chen et al. [2020] focused on verifying claims using tabular data. The TabFact dataset was generated by human annotators who created positive and negative statements about Wikipedia tables. Solving the task requires two different forms of reasoning in the statement: (i) linguistic, i.e., semantic-level understanding, and (ii) symbolic, i.e., execution on the tables’ structure.

### 3.2 Stance as a (Mis-/Dis-)information Detection Component

Fully automated systems can assist in gauging the extent, and studying the spread, of false information being propagated online. Hence, in contrast to the previously discussed applications of stance detection – as a stand-alone system for iden-

tification of mis- and disinformation, here we review its potency to serve as a component in a larger automated pipeline.

**Rumors** Stance detection can further be used for rumour detection and debunking, where the stance of the crowd, the media, or other sources towards a claim is used to determine the veracity of a currently circulating story or a report of uncertain or doubtful factuality. More formally, *for a pair of a textual input and a rumour expressed as text, stance classification means to determine the position of the text towards the rumour as a category label from the set Support, Deny, Query, Comment.*

This setup has been widely explored in the context of microblogs and social media. Qazvinian et al. [2011] started with five rumours and classified the user’s stance into five categories: *endorse*, *deny*, *unrelated*, *question*, *neutral*. This work is one of the first to demonstrate the feasibility of this task formulation; however, its limited size and the focus on assessing stance of single posts presented significant challenges in building real-world systems. Zubiaga et al. [2016a] took the task further by analysing how people orient to and spread rumours on social media based on conversational threads. The study included rumour threads associated with nine newsworthy events, and users’ stance before and after the rumours were confirmed or denied. Dungs et al. [2018] continued this line of research, but focused on the effectiveness of the stance to predict the veracity of the rumours. Hartmann et al. [2019] explored the flow of (dis-)information on Twitter after the MH17 Plane Crash.

Recently, RumourEval [Derczynski et al., 2017; Gorrell et al., 2019] was held as a sequence of shared tasks for automated claim validation. The work aimed to identify and to handle rumours based on user reactions and ensuing conversations in social media. The tasks offered annotations for both stance and veracity. Both the 2017 and 2019 competitions were similar in spirit: the 2019 one extended the task with more tweets and also Reddit posts. This work showed the importance of modeling the discourse around a story instead of drawing conclusions based on a single post.

Ferreira and Vlachos [2016] focused on debunking rumours based on news articles as part of the Emergent<sup>5</sup> project. They collected a set of claims and news articles from rumour sites with annotations both for stance and for veracity, done by journalists. The goal was to leverage the stance of a news article (summarized into a single sentence) regarding the claim as one of the components used to determine its overall veracity. A downside of this approach is the need of summarisation in contrast to FNC-1 [Pomerleau and Rao, 2017], where entire news articles were used.

**Misconceptions** Hossain et al. [2020] explored detection of misinformation related to COVID, based on a set of known misconceptions listed in Wikipedia<sup>6</sup>. In particular, they evaluated the veracity of a tweet depending on whether it *agrees*, *disagrees*, or has *no stance* with respect to a subset of misconceptions most relevant to it. This may allow fact-checkers to

<sup>4</sup><https://www.snopes.com/>

<sup>5</sup><http://www.emergent.info/>

<sup>6</sup>[https://en.wikipedia.org/wiki/COVID-19\\_misinformation](https://en.wikipedia.org/wiki/COVID-19_misinformation)

assess the veracity of dubious content in a convenient way by evaluate the stance of a claim regarding an already checked stories, known misconceptions, and facts.

**Media profiling** Another appealing aspect of stance detection for fact-checking is media profiling. Stefanov et al. [2020] explored the feasibility of an unsupervised approach for identifying the political leanings of media outlets and influential people on Twitter based on their stance on controversial topics. They built clusters of users around core vocal ones based on their behaviour on Twitter such as retweeting, using the procedure proposed by Darwish et al. [2020]. This is an important step towards understanding media biases.

The reliability of news media sources has been automatically estimated based on their stance with respect to known manually fact-checked claims, without access to gold labels for the overall medium-level factuality of reporting [Mukherjee and Weikum, 2015; Popat et al., 2017; Popat et al., 2018]. The assumption is that reliable media agree with true claims and disagree with false ones, while for unreliable media, the situation is reversed. The trustworthiness of Web sources has also been studied from a Data Analytics perspective. For instance, Dong et al [2015] proposed that a trustworthy source is one that contains very few false claims.

**Multiple languages** Existing work for languages other than English is scarce. All of the aforementioned research has focused only or primarily on English. Nevertheless, interest in stance detection for other languages has started to emerge. Baly et al. [2018] integrated stance detection and fact-checking for Arabic. Khouja [2020] proposed a dataset for Arabic which matches the FEVER [Thorne et al., 2018] setup. Lillie et al. [2019] collected data for stance and for veracity from Danish Reddit threads, annotated using the (S)upport, (D)eny, (Q)uery, (C)omment schema proposed by Zubiaga et al. [2016a]. Bošnjak and Karan [2019] worked on stance detection, claim verification, and sentiment analysis of comments on articles in Croatian news.

## 4 Methods

**Stance Detection (Single Task)** Here, we discuss approaches for stance detection in the context of mis- and disinformation detection without including extra tasks or data. One line of research is the Fake News Challenge [Pomerleau and Rao, 2017] setting. During the competition, the teams mostly developed the models with rich hand-crafted features such as words, word embeddings, and sentiment lexica [Riedel et al., 2017; Hanselowski et al., 2018]. Hanselowski et al. [2018] showed that the most important group of features are lexical ones, followed by features from topic models, while sentiment analysis did not help. Ghanem et al. [2018] used lexical cue words. More recently, Slovikovskaya and Attardi [2020] explored the effectiveness of different types of transfer learning with pre-trained Transformer models, significantly surpassing the results from previous approaches. Furthermore, Guderlei and Aßenmacher [2020] showed the robustness of these models to batch size, learning rate, sequence length,

and freezing for FNC. The most important hyper-parameter turned out to be the learning rate, while freezing more layers did not help. Mohtarami et al. [2018] worked on mitigating the effects of irrelevant and noisy information on memory networks by learning a similarity matrix and a stance filtering component applied at inference time. Moreover, they made a small step towards explaining the stance of a given claim by extracting meaningful snippets from evidence documents. Memory networks have also shown to be effective in a cross-lingual setting [Mohtarami et al., 2019]. Other noteworthy approaches include combining bags of words with variational autoencoders [Augenstein et al., 2016b], and using bidirectional conditional encoding when modeling the interaction between the claim and the target [Augenstein et al., 2016a].

The top-performing systems on FEVER [Yoneda et al., 2018; Nie et al., 2019] adopted a state-of-the-art LSTM-based model for natural language inference, namely enhanced sequential inference model (ESIM) [Chen et al., 2017]. Nie et al. [2019] proposed a neural semantic matching network, which came first in the competition. They incorporated additional information such as page view frequency and WordNet features in addition to using pre-trained contextualized embeddings. More recent approaches have used bi-directional attention [Li et al., 2018], a GPT language model [Malon, 2018] and graph neural networks [Zhou et al., 2019; Atanasov et al., 2019]. Another notable idea is to use pre-trained language models as fact-checkers based on a masked language modelling objective [Lee et al., 2020].

**Threaded Stance** Another setting where stance detection can be applied to detect mis- and disinformation is in conversational threads [Zubiaga et al., 2016a; Derczynski et al., 2017; Gorrell et al., 2019]. In contrast to the single task setup which ignores or does not provide additional context, here, important knowledge can be gained from the structure of the user interactions within conversational threads. A common characteristic of the proposed methods is to use tree-like structured models. Zubiaga et al. [2016b] explored Linear-Chain and Tree CRFs fed with posts encoded with lexicon-based, content formatting, punctuation, and tweet formatting features. Kumar and Carley [2019] replaced the CRFs with Binarised Constituency Tree LSTMs, and used pre-trained embeddings to encode the tweets. More recently, Tree [Ma and Gao, 2020] and Hierarchical [Yu et al., 2020] Transformers were proposed combining both post- and thread-level representations for rumour debunking. Kochkina et al. [2017] split the conversations into branches, and then modeled each branch using branched-LSTM and hand-crafted features. Li et al. [2020] deviated from this structure by proposing modeling the conversations as a graph. Tian et al. [2020] showed that pre-training on stance data helps build better representations for threaded tweets for downstream rumour detection. Li et al. [2019a] used an ensemble model for stance with features similar to those in [Kochkina et al., 2017], which they further combined with user credibility information, conversation structure, and other content-related features to predict the veracity of the rumour. Zubiaga et al. [2018b] chained four different sequen-

tial classifiers that showed state-of-the-art results on conversational threads. Li et al. [2019b] also leveraged user credibility features in addition to other tweet-related features. Finally, the stance of a post might not be expressed directly towards the root of the thread, and thus the preceding posts must be also taken into account [Gorrell et al., 2019].

**Multi-Dataset Learning** Mixing data from different domains and sources can improve the robustness and the ability of the models to generalise. However, setups which combine both mis- and disinformation identification with stance detection, outlined in Section 3, vary in their annotation and labeling schemes, making the combination of different datasets a challenging task.

Earlier approaches focused only on the pre-training of models on multiple tasks, e.g., Fang et al. [2019] achieved state-of-the-art results on FNC-1 by fine-tuning the model on multiple tasks such as question answering, natural language inference, etc., which are weakly related to stance detection.

Recently, Schiller et al. [2020] proposed a stance detection benchmark to evaluate the robustness of stance models, including some of the factuality-related datasets. They leveraged a pre-trained multi-task deep neural network (MT-DNN) model and continued its training on all datasets simultaneously using multi-task learning, showing sizeable improvements over strong baselines trained on single datasets.

**Systems** Popat et al. [2018] proposed CredEye<sup>7</sup>, a system for automatic credibility assessment. It takes a claim as an input and analyses its credibility by considering relevant articles from the Web. The underlying approach [Popat et al., 2017] combines the predicted stance of the articles regarding the claim with linguistic features to obtain a credibility score.

Nadeem et al. [2019] developed FAKTA, an system for automatic end-to-end fact-checking of claims. It retrieves relevant articles from Wikipedia and selected media sources, which are used for verification. FAKTA uses a stance detection model, trained in a FEVER setting, to predict the stance and to obtain entailed spans. These predictions, combined with linguistic analysis, are used to provide both document- and sentence-level explanations and a factuality score.

Wen et al. [2018] worked on cross-lingual cross-platform rumour verification. They included multimodal content from fake and from real posts with images or videos shared on Twitter. For this purpose, they collected supporting documents from two search engines, Google and Baidu, which they then used for veracity evaluation. They considered posts in two languages, English and Chinese. However, they trained the stance model on English data (FNC-1) using pre-trained multilingual sentence embeddings, and is further used cross-platform features for training a neural network model.

Nguyen et al. [2020] proposed the Factual News Graph (FANG) model, which models the social context for fake news detection. In particular, FANG uses the stance of user comments with respect to the target news article, and in addition also temporal information, user-user interactions, article-source interactions, and source reliability information.

Zubiaga et al. [2018a] considered a four-step tracking process as a pipeline for rumour resolution: (1) *rumour detection*, which, given a stream of claims, determines whether they are worth verifying or they do not contain a rumour; (2) *rumour tracking* for finding relevant information about the rumour using social media posts, sentence descriptions, and keywords; (3) *stance classification* to collect stances towards that rumour; and (4) *veracity classification* to aggregate the information from the tracking component, the collected stances, and optionally other relevant information about sources, users metadata, etc., to obtain a predicted truth value for the rumour. Possible methods which can be applied at each step in the pipeline are discussed in more detail in [Zubiaga et al., 2018a].

## 5 Lessons Learnt and Challenges

**Integration** People question false information more and tend to affirm true information [Mendoza et al., 2010], and thus, stance can play a vital role for verifying dubious content. We argue that a tighter integration between stance and fact-checking is needed. Stance can be expressed in different forms, e.g., news articles, user posts, sentences in Wikipedia, and Wiki tables, among others. All of these can guide human fact-checkers through the process of fact verification, and can point them to relevant evidence, which can help them to make informed decisions pertaining to the factuality of a claim. Moreover, the wisdom of the crowd can be a powerful instrument in the fight against mis- and disinformation, although it should be noted that vocal minorities can derail public discourse. Nevertheless, these risks can be mitigated by taking into account the credibility of the user or of the information source, which can be done automatically or with the help of human fact-checkers.

**Explainability** is an important aspect in stance detection research, especially in the context of its application to mis- and disinformation detection. Moreover, explainability is a crucial step towards adopting fully automated fact-checking. In terms of previous work, FEVER 2.0 [Thorne et al., 2019] may be viewed as a step towards obtaining such explanations. Specifically, there have been efforts to identify adversarial triggers, which offer explanations of vulnerabilities at the model level [Atanasova et al., 2020b]. However, FEVER is artificially created and is limited to Wikipedia, which may not reflect real-world settings. To mitigate this, explanation by professional journalists can be found on fact-checking websites, and can be further combined with stance detection components in an automated system. A step in this direction is [Atanasova et al., 2020a], who generated natural language explanations for claims from PolitiFact given gold evidence document summaries by journalists. Other existing systems [Popat et al., 2017; Popat et al., 2018; Nadeem et al., 2019] offer explanations to a more limited extent, highlighting span overlaps between the target text and the evidence documents. Overall, a more holistic and realistic setting for generating explanations of how fact-checking models arrived at its prediction is still needed.

**Dataset Sizes** Another major limitation is the size of existing stance detection datasets. The vast majority of such

<sup>7</sup><https://gate.d5.mpi-inf.mpg.de/credeye/>

datasets contain at most a few thousand examples. Contrasted with the related task of Natural Language Inference, where datasets such as SNLI of more than half a million samples have been collected, this is far from optimal. Nevertheless, recent advances in transfer learning and the release of large pre-trained models such as ELMo, GPT\*, BERT, and RoBERTa have eased the efforts to train well-performing systems on smaller datasets. Furthermore, GPT-3 showed a remarkable success in few-shot learning, but at the expense of training a billion parameter model. Recent research showed that smaller models can also be good few-shot learners [Rethmeier and Augenstein, 2020].

**Dataset Biases** An additional challenge is that existing datasets also have certain potentially undesirable biases. Datasets constructed from naturally occurring data in fact-checking portals, such as Augenstein et al. [2019] exhibit a long-tail distribution when it comes to which entities are mentioned in the claims. Moreover, due to the nature of which claims are deemed to be worthy for fact-checking, some entities can be mentioned in claims with predominantly one veracity class. This, in turn, could yield biased models and biased decisions when such models are put in practical use. Another option is to use artificially constructed datasets such as FEVER, which are also biased as the way the claims and the evidence statements are expressed is not representative of naturally occurring claims, and it is likely that the types of claims are not reflective of check-worthy claims either [Wright and Augenstein, 2020]. As biases in datasets are unavoidable, it might instead be worth noting what the intended application for them is [Waseem et al., 2020].

**Granular Stance** As research in stance detection has evolved, so has the definition of the task and the label inventories. As shown in Section 3, the labels can vary based on the use case and the setting they’re used in. Much of the literature adopt a variant of the *Favour, Against, Neither* labels, or an extended schema such as *(S)upport, (Q)uery, (D)eny (C)omment* [Mohammad et al., 2016], however that is not enough to accurately assessing stance, as it would need ascertaining the strength with which the target is supported or refuted. In case of neutral, detecting whether that is the case because of conflicting arguments or because of truly neutral stance is another challenge.

**Modelling Context** Modelling the context stance is expressed in is a particularly important, yet challenging task. In many cases, it is important to consider the background of the stance-taker as well as the characteristics of the targeted object. In particular, in the context of social media, one can provide information about the users such as their previous activity, other users they interact most with, the threads in which they discuss a particular topic, or even their interests [Zubiaga et al., 2016a; Gorrell et al., 2019; Li et al., 2019b]. The context of stance expressed through news articles is related to the features of the media outlets, like sources of funding, previously known biases, or credibility [Darwish et al., 2020; Stefanov et al., 2020]. When using contextual information about the object, factual information about the real world, and the time of posting are all important to consider. Incorporat-

ing those into a stance detection pipeline, while challenging, paves the way towards a robust detection process.

## 6 Future Trends

**Multimodality** Spreading mis- and disinformation through multiple modalities is becoming increasingly popular. One such example of this are *DeepFakes*, i.e., synthetically created images or videos, in which (usually) the face of one person is replaced with another person’s. Another such example are information propagation techniques such as *memetic warfare*, i.e., the use of memes for information warfare. Both DeepFakes and memetic warfare require the modelling of not only text, but also of other modalities. Some work in this area is on fake news detection for images [Nakamura et al., 2020], claim verification for images [Zlatkova et al., 2019], or searching for fact-checked information to alleviate the spread of fake news [Vo and Lee, 2020].

**Data Mixing** As we previously discussed (see Section 3), task definitions and label inventories vary between different applications of stance detection for mis- and disinformation detection. This is not specific to this context, but it is a known challenge in stance detection [Küçük and Can, 2020], as discussed in [Schiller et al., 2020]. Nevertheless, large-scale studies of approaches that aim to leverage the relationships between the label inventories, or the similarity between datasets are still to come. One promising direction is the use of label embeddings [Augenstein et al., 2018], as they offer a convenient way to learn the interaction between disjoint label sets that carry semantic relations.

**Weighing Stances** When evaluating the factuality of a piece of information, the nuance in the strength of the expressed stance by an actor is another indicator that should be taken into consideration in the decision-making process. In practice, this can be subjective, which is why annotations for the strength of agreement are scarce. Moreover, a complex system should weigh sources based on their known biases and trustfulness.

**Multilinguality** Finally, we argue for the importance for fact-checking systems to be language-agnostic for several reasons: (i) the content in question may originate from a text piece in various languages; (ii) the evidence or the stance may not be expressed in the same language, in turn (iii) posing a challenge for fact-checkers, who might not be native speakers of the language considered. This is an important challenge and an emerging trend not only in stance detection, but in NLP in general. Currently, only a handful of datasets for factuality and stance cover languages other than English [Baly et al., 2018; Bošnjak and Karan, 2019; Lillie et al., 2019; Khouja, 2020]. While they are a good start, they are small in size, and do not offer a truly cross-lingual setup. Only recently, Vamvas and Sennrich [2020] introduced a cross-lingual setup with three languages for stance in debates.

## 7 Conclusion

We surveyed the current state-of-the-art in stance detection for mis- and disinformation detection. We explored applications of stance for detecting fake news, verifying and debunking rumours, identifying misconceptions, and fact-checking. Furthermore, we discussed existing approaches used in different aspects of the aforementioned tasks. We also identified several vital challenges which need to be addressed in order to make substantial progress, such as the integration of stance in fully- or semi-automated systems. Finally, we outlined promising future trends in the field of stance detection for mis- and disinformation detection.

## References

- [Alam et al., 2020] F. Alam et al. Fighting the COVID-19 infodemic in social media: a holistic perspective and a call to arms. *arXiv:2007.07996*, 2020.
- [Atanasov et al., 2019] A. Atanasov et al. Predicting the role of political trolls in social media. In *CoNLL*, 2019.
- [Atanasova et al., 2020a] P. Atanasova et al. Generating fact checking explanations. In *ACL*, 2020.
- [Atanasova et al., 2020b] P. Atanasova et al. Generating label cohesive and well-formed adversarial claims. In *EMNLP*, 2020.
- [Augenstein et al., 2016a] Augenstein et al. Stance detection with bidirectional conditional encoding. In *EMNLP*, 2016.
- [Augenstein et al., 2016b] I. Augenstein et al. USFD at SemEval-2016 task 6: Any-target stance detection on Twitter with autoencoders. In *SemEval*, 2016.
- [Augenstein et al., 2018] I. Augenstein et al. Multi-task learning of pairwise sequence classification tasks over disparate label spaces. In *NAACL-HLT*, 2018.
- [Augenstein et al., 2019] I. Augenstein et al. MultiFC: A real-world multi-domain dataset for evidence-based fact checking of claims. In *EMNLP-IJCNLP*, 2019.
- [Baly et al., 2018] Baly et al. Integrating stance detection and fact checking in a unified corpus. In *NAACL-HLT*, 2018.
- [Biber and Finegan, 1988] Biber and Finegan. Adverbial stance types in english. *Discourse Processes*, 11(1), 1988.
- [Bošnjak and Karan, 2019] M. Bošnjak and M. Karan. Data set for stance and sentiment analysis from user comments on Croatian news. In *BSNLP*, 2019.
- [Chen et al., 2017] Q. and Chen et al. Enhanced LSTM for natural language inference. In *ACL*, 2017.
- [Chen et al., 2020] W. Chen et al. TabFact: A large-scale dataset for table-based fact verification. In *ICLR*, 2020.
- [Darwish et al., 2020] K. Darwish et al. Unsupervised user stance detection on twitter. In *ICWSM*, 2020.
- [Derczynski et al., 2017] L. Derczynski et al. SemEval-2017 task 8: RumourEval: Determining rumour veracity and support for rumours. In *SemEval*, 2017.
- [Dong et al., 2015] Dong et al. Knowledge-based trust: Estimating the trustworthiness of web sources. *VLDB*, 2015.
- [Du Bois, 2007] Du Bois. The stance triangle. *Stancetaking in discourse: Subjectivity, evaluation, interaction*, 2007.
- [Dungs et al., 2018] S. Dungs et al. Can rumour stance alone predict veracity? In *COLING*, 2018.
- [Fang et al., 2019] W. Fang et al. Neural multi-task learning for stance prediction. In *FEVER*, 2019.
- [Ferreira and Vlachos, 2016] W. Ferreira and A. Vlachos. Emergent: a novel data-set for stance classification. In *NAACL-HLT*, 2016.
- [Ghanem et al., 2018] Ghanem et al. Stance detection in fake news a combined feature representation. In *FEVER*, 2018.
- [Gorrell et al., 2019] G. Gorrell et al. SemEval-2019 task 7: RumourEval, determining rumour veracity and support for rumours. In *SemEval*, 2019.
- [Guderlei and Aßenmacher, 2020] Maike Guderlei and Matthias Aßenmacher. Evaluating unsupervised representation learning for detecting stances of fake news. In *COLING*, 2020.
- [Habernal et al., 2018] I. Habernal et al. The argument reasoning comprehension task: Identification and reconstruction of implicit warrants. In *NAACL-HLT*, 2018.
- [Hanselowski et al., 2018] A. Hanselowski et al. A retrospective analysis of the fake news challenge stance-detection task. In *COLING*, 2018.
- [Hanselowski et al., 2019] A. Hanselowski et al. A richly annotated corpus for different tasks in automated fact-checking. In *CoNLL*, 2019.
- [Hartmann et al., 2019] M. Hartmann et al. Mapping (dis-)information flow about the MH17 plane crash. In *NLP4IF*, 2019.
- [Hasan and Ng, 2014] K. Hasan and V. Ng. Why are You Taking this Stance? Identifying and Classifying Reasons in Ideological Debates. In *EMNLP*, 2014.
- [Hossain et al., 2020] T. Hossain et al. COVIDLies: Detecting COVID-19 misinformation on social media. In *NLP-COVID19*, 2020.
- [Johnson and Goldwasser, 2016] K. Johnson and D. Goldwasser. “All I know about politics is what I read in Twitter”: Weakly supervised models for extracting politicians’ stances from Twitter. In *COLING*, 2016.
- [Khouja, 2020] J. Khouja. Stance prediction and claim verification: An Arabic perspective. In *FEVER*, 2020.
- [Kochkina et al., 2017] Kochkina et al. Turing at SemEval-2017 task 8: Sequential approach to rumour stance classification with branch-LSTM. In *SemEval*, 2017.
- [Küçük and Can, 2020] D. Küçük and F. Can. Stance detection: A survey. *ACM Comput. Surv.*, 53(1), 2020.
- [Kumar and Carley, 2019] S. Kumar and K. Carley. Tree LSTMs with convolution units to predict stance and rumor veracity in social media conversations. In *ACL*, 2019.

- [Lee et al., 2020] N. Lee et al. Language models as fact checkers? In *FEVER*, 2020.
- [Li et al., 2018] S. Li et al. An end-to-end multi-task learning model for fact checking. In *FEVER*, 2018.
- [Li et al., 2019a] Li et al. eventAI at SemEval-2019 task 7: Rumor detection on social media by exploiting content, user credibility and propagation information. 2019.
- [Li et al., 2019b] Q. Li et al. Rumor detection by exploiting user credibility information, attention and multi-task learning. In *ACL*, 2019.
- [Li et al., 2020] J. Li et al. Exploiting microblog conversation structures to detect rumors. In *COLING*, 2020.
- [Lillie et al., 2019] Anders Edelbo Lillie et al. Joint rumour stance and veracity prediction. In *NoDaLiDa*, 2019.
- [Ma and Gao, 2020] J. Ma and W. Gao. Debunking rumors on Twitter with tree transformer. In *COLING*, 2020.
- [Malon, 2018] Christopher Malon. Team Papelote: Transformer networks at FEVER. In *FEVER*, 2018.
- [Mendoza et al., 2010] M. Mendoza et al. Twitter under crisis: Can we trust what we RT? In *SOMA*, 2010.
- [Mohammad et al., 2016] S. Mohammad et al. SemEval-2016 task 6: Detecting stance in tweets. In *SemEval*, 2016.
- [Mohtarami et al., 2018] M. Mohtarami et al. Automatic stance detection using end-to-end memory networks. In *NAACL-HLT*, 2018.
- [Mohtarami et al., 2019] Mohtarami et al. Contrastive language adaptation for cross-lingual stance detection. In *EMNLP*, 2019.
- [Mukherjee and Weikum, 2015] S. Mukherjee and G. Weikum. Leveraging joint interactions for credibility analysis in news communities. In *CIKM*, 2015.
- [Nadeem et al., 2019] Nadeem et al. FAKTA: An automatic end-to-end fact checking system. In *NAACL-HLT*, 2019.
- [Nakamura et al., 2020] K. Nakamura et al. Fakeddit: A new multimodal benchmark dataset for fine-grained fake news detection. In *LREC*, 2020.
- [Nguyen et al., 2020] V. Nguyen et al. FANG: Leveraging social context for fake news detection using graph representation. In *CIKM*, 2020.
- [Nie et al., 2019] Y. Nie et al. Combining fact extraction and verification with neural semantic matching networks. In *AAAI*, 2019.
- [Pomerleau and Rao, 2017] D. Pomerleau and D. Rao. Fake news challenge stage 1 (FNC-I): Stance detection, 2017.
- [Popat et al., 2017] K. Popat et al. Where the truth lies: Explaining the credibility of emerging claims on the Web and social media. In *WWW*, 2017.
- [Popat et al., 2018] K. Popat et al. CredEye: A credibility lens for analyzing and explaining misinformation. In *WWW*, 2018.
- [Qazvinian et al., 2011] Qazvinian et al. Rumor has it: Identifying misinformation in microblogs. In *EMNLP*, 2011.
- [Rethmeier and Augenstein, 2020] N. Rethmeier and I. Augenstein. Long-tail zero and few-shot learning via contrastive pretraining on and for small data. *arXiv:2010.01061*, 2020.
- [Riedel et al., 2017] B. Riedel et al. A simple but tough-to-beat baseline for the Fake News Challenge stance detection task. *ArXiv:1707.03264*, 2017.
- [Schiller et al., 2020] B. Schiller et al. Stance detection benchmark: How robust is your stance detection? *arXiv:2001.01565*, 2020.
- [Shurafa et al., 2020] C. Shurafa et al. Political framing: US COVID19 blame game. In *SocInfo*, 2020.
- [Slovikovskaya and Attardi, 2020] Slovikovskaya and Attardi. Transfer learning from transformers to fake news challenge stance detection (FNC-1) task. In *LREC*, 2020.
- [Somasundaran and Wiebe, 2009] S. Somasundaran and J. Wiebe. Recognizing stances in online debates. In *ACL-AFNLP*, 2009.
- [Stefanov et al., 2020] P. Stefanov et al. Predicting the topical stance and political leaning of media using tweets. In *ACL*, 2020.
- [Thorne et al., 2018] J. Thorne et al. FEVER: a large-scale dataset for fact extraction and VERification. In *NAACL-HLT*, 2018.
- [Thorne et al., 2019] J. Thorne et al. The FEVER2.0 shared task. In *FEVER*, 2019.
- [Tian et al., 2020] L. Tian et al. Early detection of rumours on twitter via stance transfer learning. In *ECIR*, 2020.
- [Vamvas and Sennrich, 2020] J. Vamvas and R. Sennrich. X-Stance: A multilingual multi-target dataset for stance detection. In *SwissText-KONVENS*, 2020.
- [Vo and Lee, 2020] N. Vo and K. Lee. Where are the facts? searching for fact-checked information to alleviate the spread of fake news. In *EMNLP*, 2020.
- [Waseem et al., 2020] Z. Waseem et al. Disembodied machine learning: On the illusion of objectivity in NLP. *arXiv:2101.11974*, 2020.
- [Wen et al., 2018] W. Wen et al. Cross-lingual cross-platform rumor verification pivoting on multimedia content. In *EMNLP*, 2018.
- [Wright and Augenstein, 2020] D. Wright and I. Augenstein. Claim check-worthiness detection as positive unlabelled learning. In *EMNLP Findings*, 2020.
- [Yoneda et al., 2018] T. Yoneda et al. UCL machine reading group: Four factor framework for fact finding (HexaF). In *FEVER*, 2018.
- [Yu et al., 2020] J. Yu et al. Coupled hierarchical Transformer for stance-aware rumor verification in social media conversations. In *EMNLP*, 2020.
- [Zhou et al., 2019] J. Zhou et al. GEAR: Graph-based evidence aggregating and reasoning for fact verification. In *ACL*, 2019.



- [Zlatkova et al., 2019] D. Zlatkova et al. Fact-checking meets fauxtography: Verifying claims about images. In *EMNLP-IJCNLP*, 2019.
- [Zubiaga et al., 2016a] A. Zubiaga et al. Analysing how people orient to and spread rumours in social media by looking at conversational threads. *PLOS ONE*, 11(3), 2016.
- [Zubiaga et al., 2016b] A. Zubiaga et al. Stance classification in rumours as a sequential task exploiting the tree structure of social media conversations. In *COLING*, 2016.
- [Zubiaga et al., 2018a] A. Zubiaga et al. Detection and resolution of rumours in social media: A survey. *ACM Comput. Surv.*, 51(2), 2018.
- [Zubiaga et al., 2018b] A. Zubiaga et al. Discourse-aware rumour stance classification in social media using sequential classifiers. *Inf. Process. Manage.*, 54(2), 2018.