

Self-stabilizing Multivalued Consensus in Asynchronous Crash-prone Systems

(preliminary version)

Oskar Lundström Michel Raynal Elad M. Schiller

December 14, 2021

The problem of multivalued consensus is fundamental in the area of fault-tolerant distributed computing since it abstracts a very broad set of agreement problems in which processes have to uniformly decide on a specific value $v \in V$, where $|V| \geq 2$. Existing solutions (that tolerate process failures) reduce the multivalued consensus problem to the one of binary consensus, *e.g.*, Mostéfaoui-Raynal-Tronel and Zhang-Chen.

Our study aims at the design of an even more reliable solution. We do so through the lenses of *self-stabilization*—a very strong notion of fault-tolerance. In addition to node and communication failures, self-stabilizing algorithms can recover after the occurrence of *arbitrary transient-faults*; these faults represent any violation of the assumptions according to which the system was designed to operate (as long as the algorithm code stays intact).

This work proposes the first (to the best of our knowledge) self-stabilizing algorithm for multivalued consensus for asynchronous message-passing systems prone to process failures and arbitrary transient-faults. Our solution is also the first (to the best of our knowledge) to support wait-freedom. Moreover, using piggybacking techniques, our solution can invoke n binary consensus objects concurrently. Thus, the proposed self-stabilizing solution can terminate using fewer binary consensus objects than earlier non-self-stabilizing solutions by Mostéfaoui, Raynal, and Tronel, which uses an unbounded number of binary consensus objects, or Zhang and Chen, which is not wait-free.

1 Introduction

We propose, to the best of our knowledge, the first self-stabilizing, non-blocking, and memory-bounded implementation of *multivalued consensus* objects for asynchronous message-passing systems whose nodes may crash.

1.1 Background and motivation

Fault-tolerant distributed applications span over many domains in the area of banking, transports, tourism, production, commerce, to name a few. The implementations of these applications use message-passing systems and require fault-tolerance. The task of designing and

verifying these systems is known to be very hard, because the joint presence of failures and asynchrony creates uncertainties about the application state (from the process’s point of view). *E.g.*, Fischer, Lynch, and Paterson [23] demonstrated that, in any asynchronous message-passing system, it takes no more than one process crash to prevent the system from achieving consensus deterministically.

Our focal application is the emulation of finite-state machines. For the sake of consistency maintenance, all emulating processes need to apply identical sequences of state transitions. This can be done by dividing the problem into two: (i) propagation of user input to all emulating processes, and (ii) letting each emulating process execute identical sequences of state transitions. Uniform reliable broadcast [26, 41] can solve Problem (i). This work focuses on Problem (ii) since it is the core problem. *I.e.*, all processes need to agree on a common value according to which all emulating processes execute their state transitions. The consensus problem generalizes problem (ii) and requires each process to propose a value, and all non-crashed processes to reach a common decision that one of them had proposed. There is a rich literature on fault-tolerant consensus. This work advances the state of the art by offering a greater set of failures that can be tolerated.

1.2 Problem definition and scope

The definition of the consensus problem appears in Definition 1.1. This work studies the multivalued version of the problem in which there are at least two values that can be proposed. Note that there is another version of the problem in which this set includes exactly two values, and referred to as binary consensus. Existing solutions for the multivalued consensus (as well as the proposed one) often use binary consensus algorithms. We present the relation among the problems mentioned above in Figure 1.

Definition 1.1 (Consensus) *Every process p_i has to propose a value $v_i \in V$ via an invocation of the $\text{propose}_i(v_i)$ operation, where V is a finite set of values. Let Alg be an algorithm that solves consensus. Alg has to satisfy safety (i.e., validity, integrity, and agreement) and liveness (i.e., termination).*

- **Validity.** *Suppose that v is decided. Then some process had invoked $\text{propose}(v)$.*
- **Termination.** *All non-faulty processes decide.*
- **Agreement.** *No two processes decide different values.*
- **Integrity.** *No process decides more than once.*

1.3 Fault Model

We consider an asynchronous message-passing system that has no guarantees on communication delays (except that they are finite) and the algorithm cannot explicitly access the local clock. Our fault model includes (i) crashes of less than half of the processes, and (ii) communication failures, such as packet omission, duplication, and reordering.

In addition to the failures captured in our model, we also aim to recover from *arbitrary transient-faults*, i.e., any temporary violation of assumptions according to which the system and network were designed to operate, *e.g.*, the corruption of control variables, such as the program counter, packet payload, and indices, *e.g.*, sequence numbers, which are responsible for the correct operation of the studied system, as well as operational assumptions, such as that

at least a majority of nodes never fail. Since the occurrence of these failures can be arbitrarily combined, it follows that these transient-faults can alter the system state in unpredictable ways. In particular, when modeling the system, we assume that these violations bring the system to an arbitrary state from which a *self-stabilizing algorithm* should recover the system after the occurrence of the last transient-fault. The system is guaranteed to satisfy the task requirements, *e.g.*, Definition 1.1, after this recovery period. Our design criteria also support wait-freedom, which requires all operations to terminate within a bounded number of algorithm steps. Wait-freedom is important since it assures starvation-freedom even in the presence of failures since all operations terminate (as long as the process that invoked them does not crash).

1.4 Related Work

The celebrated Paxos algorithm [28] circumvents the impossibility by Fischer, Lynch, and Paterson [23], from now on FLP, by assuming that failed computers can be detected by unreliable failure detectors [10]. Paxos has inspired many veins of research, *e.g.*, [44] and references therein. We, however, follow the family of abstractions by Raynal [41] due to its clear presentation that is easy to grasp. Also, the studied algorithm does not consider failure detectors. Instead, it assumes the availability of binary consensus objects, which uses the weakest failure detector, see Raynal [41].

1.4.1 Non-self-stabilizing solutions

Mostéfaoui, Raynal, and Tronel [36], from now on MRT, reduce multivalued consensus to binary consensus via a crash-tolerant block-free algorithm. MRT uses an unbounded number of invocations of binary consensus objects and at most one uniform reliable broadcast (URB) per process. Zhang and Chen [46] proposed an algorithm for multivalued consensus that uses only x instances, where x is the number of bits it takes to represent any value in V ; the domain of proposable values.

Our self-stabilizing solution is wait-free since termination is achieved within at most n invocations of binary consensus objects and at most one uniform reliable broadcast [32] (URB) operation per process, where n is the number of processes in the system. However, each such URB invocation needs to be repeated until the consensus object is deactivated by the invoking algorithm. This is due to a well-known impossibility [14, Chapter 2.3], which says that self-stabilizing systems cannot terminate and stop sending messages. Note that it is easy to trade the broadcast repetition rate with the speed of recovery from transient-faults.

Afek *et al.* [1] showed that binary and multivalued versions of the k -simultaneous consensus task are wait-free equivalent. Here, the k -simultaneous consensus is required to let each process to participate at the same time in k independent consensus instances until it decides in any one of them.

Our study focuses on deterministic solutions and does not consider probabilistic approaches, such as [4, 22, 31]. It is worth mentioning that Byzantine fault-tolerant multivalued consensus algorithms [11, 12, 35, 43] have applications to Blockchain [34]. Our fault model does not include Byzantine failures, instead, we consider arbitrary transient-faults.

1.4.2 Self-stabilizing solutions

We follow the design criteria of self-stabilization, which Dijkstra [13] proposed. A detailed pretension of self-stabilization was provided by Dolev [14] and Altisen *et al.* [3]. Consensus was sparsely studied in the context of self-stabilization. Blanchard *et al.* [7] presented the first

distributed applications
automata emulation (Algorithm 4)
total-order delivery (Algorithm 3)
multivalued consensus (Algorithm 2)
binary consensus
uniform reliable broadcast

Figure 1: The studied problems of binary consensus (in bold font) and their context

solution in the context of self-stabilization. They presented a practically-self-stabilizing version of Paxos [28], which was the first (non-self-stabilizing) solution to the area of fault-tolerant message-passing systems. The studied solution is part of a more advanced and efficient protocol suite (Figure 1). We note that practically-self-stabilizing systems, as defined by Alon *et al.* [2] and clarified by Salem and Schiller [42], do not satisfy Dijkstra’s requirements, *i.e.*, practically-self-stabilizing systems do not guarantee recovery within a finite time after the occurrence of transient-faults. We base our self-stabilizing multivalued consensus on the self-stabilizing binary consensus by Lundström, Raynal, and Schiller [33], which is the first self-stabilizing solution to the binary consensus problem that recovers within a bounded time.

We propose, to the best of our knowledge, the first self-stabilizing solution for the multivalued version of the problem. As an application, we offer, to the best of our knowledge, the first self-stabilizing algorithm for (uniform reliable broadcast with) total order delivery. It is based on the self-stabilizing uniform reliable broadcast with FIFO delivery by Lundström, Raynal, and Schiller [32]. Our solution can facilitate the self-stabilizing emulation of state-machine replication. Dolev *et al.* [15] proposed the first practically-self-stabilizing emulation of state-machine replication, which has a similar task to one in Figure 1. However, Dolev *et al.*’s solution does not guarantee recovery within a finite time since it does not follow Dijkstra’s criterion. Moreover, it is based on virtual synchrony by Birman and Joseph [6], where the one in Figure 1 considers censuses.

Georgiou, Lundström, and Schiller studied the trade-off between non-blocking and wait-free solutions for self-stabilizing atomic snapshot objects [24]. We study a similar trade-off for a different problem.

More generally, in the context of self-stabilization there are algorithms for group communications [19–21], consensus in shared-memory systems [18], wireless communications [27, 29, 30, 37–40], software defined networks [8, 9], virtual infrastructure for mobile nodes [16, 17, 45], to name a few.

1.5 Our contribution

We present a fundamental module for dependable distributed systems: a self-stabilizing wait-free algorithm for multivalued consensus for asynchronous message-passing systems that are prone to crash failures. To the best of our knowledge, we are the first to provide a wait-free solution for multivalued consensus that tolerates a broad fault model *i.e.*, crashes, communication failures, *e.g.*, packet omission, duplication, and reordering as well as arbitrary transient-faults using a bounded amount of resources. The latter models any violation of the assumptions according to which the system was designed to operate (as long as the algorithm code stays intact).

Our wait-free solution achieves (multivalued) consensus within n invocations of binary consensus instances that can run either sequentially or concurrently, where n is the number of processes. Besides, our concurrent version can piggyback the binary consensus messages and terminate within the time that it takes to complete one uniform reliable broadcast (URB) and one binary consensus. This is also the time it takes the system to recover after the occurrence of the last transient-fault.

As an application, this technical report offers a total order extension to the self-stabilizing FIFO URB service by Lundström, Raynal, and Schiller [32]. That self-stabilizing solution uses three multivalued consensus objects and stabilizes within a constant time. The technical report also explains how to enhance this solution to a self-stabilizing emulator of a replicated state machine.

1.6 Organization

We state our system settings in Section 3. The task specifications and solution organization appear in Section 2. Section 4 includes a brief overview of the studied algorithm by Mostéfaoui, Raynal, and Tronel [36] that has led to the proposed solution. Our self-stabilizing algorithm for consensus multivalued object is proposed in Section 5. The correctness proof appears in Section 6. We present an application to the proposed algorithm in Section 7, which is a self-stabilizing total order uniform reliable broadcast. We conclude in Section 8 and explain how to extend the proposed application to serve as an emulator for state-machine replication.

2 Task Specifications and Solution Organization

The proposed solution is tailored for the protocol suite presented in Figure 1. Thus, before we specify how all these tasks are organized into one solution, we list the external building blocks and define the studied tasks.

2.1 External Building-Blocks: Uniform Reliable Broadcast

2.1.1 Binary consensus objects

T_{binCon} denotes the task of binary and multivalued consensus, which Definition 1.1 specifies. We assume the availability of self-stabilizing binary consensus objects, such as the one by Lundström, Raynal, and Schiller [33]. As in Definition 1.1, the proposed and decided values have to be from the V domain (of proposable values). For clarity sake, we distinguish the invocation of binary and multivalued consensus. That is, for a given binary consensus object BC , the operation $BC.\text{binPropose}(v)$ invokes the binary consensus on $v \in V = \{\text{True}, \text{False}\}$. (Traditionally, the result of binary consensus is either 0 or 1, but we rename them.)

2.1.2 First-in first-out uniform reliable broadcast (FIFO-URB)

The task T_{URB} of Uniform reliable broadcast (URB) [26] considers an operation for URB broadcasting of message m and an event of URB delivery of message m . The requirements include URB-validity, *i.e.*, there is no spontaneous creation or alteration of URB messages, URB-integrity, *i.e.*, there is no duplication of URB messages, as well as URB-termination, *i.e.*, if the broadcasting node is non-faulty, or if at least one receiver URB-delivers a message, then all non-failing nodes URB-deliver that message. Note that the URB-termination property considers

both faulty and non-faulty receivers. This is the reason why this type of reliable broadcast is named *uniform*.

The task of FIFO-URB, denoted by $T_{\text{TO-URB}}$, requires, in addition to the above URB requirements, *i.e.*, URB-validity, URB-integrity, and URB-termination, that all messages that come from the same sender are delivered in the same order in which their sender has sent them; but there are no constraints regarding messages that arrive from different senders.

The proposed solution assumes the availability of a self-stabilizing uniform reliable broadcast (URB) [32]. We also assume that the operation for URB broadcasting message m returns a transmission descriptor, $txDes$, which is the unique message identifier. Moreover, the predicate $\text{hasTerminated}(txDes)$ holds whenever the sender knows that all non-failing nodes in the system have delivered m . The implementation of $\text{hasTerminated}(txDes)$ can just test that all trusted receivers have acknowledged the arrival of the message with identifier $txDes$. The solution in [32] can facilitate the implementation of $\text{hasTerminated}()$ since the self-stabilizing algorithm in [32] considers such messages as 'obsolete' messages and lets the garbage collector remove them.

2.2 Task specifications

We specify the studied tasks.

2.2.1 Total order URB (TO-URB)

The task of total order URB, denoted by $T_{\text{TO-URB}}$, requires the total order delivery requirement, in addition to URB-validity, URB-integrity, and URB-termination. The total order delivery requirement says that if a node calls $\text{toDeliver}(m)$ and later $\text{toDeliver}(m')$, then no node $\text{toDeliver}(m')$ before $\text{toDeliver}(m)$.

2.2.2 Binary and multivalued consensus objects

T_{mulCon} denotes the task of multivalued consensus, which Definition 1.1 specifies. As in Definition 1.1, the proposed and decided values have to be from the V domain (of proposable values), where $|V| > 2$. The operation $\text{propose}(v)$ invokes the multivalued consensus on $v \in V$.

2.3 Solution organization

We consider multivalued consensus objects that use an array, $BC[]$, of n binary consensus objects, such as the one by [41, Chapter 17], where $n = |\mathcal{P}|$ is the number of nodes in the system. The proposed algorithm considers a single multivalued consensus object, denoted by O .

The proposed application, which is a TO-URB solution, considers an array, $CS[]$, of M multivalued consensus objects, where $M \in \mathbb{Z}^+$ is a predefined constant. Our solution for TO-URB uses $M = 3$ (Section 7). Each object is uniquely identified using a single sequence number. The proposed algorithm assumes that the multivalued consensus object O is stored at $CS[s \bmod M]$. Whenever an operation is invoked or a message is sent, the sequence number s is attached as a procedure parameter, and respectively, a message field (although the code of the proposed algorithm does not show this). We note that in case the proposed application runs out of sequence numbers, a global restart mechanism can be invoked, such as the one in [24, Section 5]. The function $\text{test}(s)$ is used to assert consistency of the sequence number s . The function returns **False** whenever inconsistency is detected. Our TO-URB solution exemplifies an implementation of $\text{test}()$. We assume that all underlying algorithms invoke $\text{test}(s)$ whenever

the object $CS[s \bmod M]$ or $CS[s \bmod M].BC[k] : p_k \in \mathcal{P}$ is accessed, an operation is invoked, or a message (that is associated with s) arrives (although the code of the proposed algorithm does not show this). (The term underlying algorithm refers to both the proposed algorithm for multivalued consensus as well as the one for binary consensus.) If object $CS[s \bmod M]$ is found to be inconsistent, it is simply deactivated by assigning \perp to $CS[s \bmod M]$. Also, inconsistent operation invocations and arriving messages are simply ignored.

Definition 1.1 considers the $\text{propose}(v)$ operation, but it does not specify how the decided value is retrieved. We clarify that it can be either via the returned value of the $\text{propose}(v)$ (or $\text{binPropose}(v)$) operation (as in algorithm [25]) or via the returned value of the $\text{result}()$ operation (as in the proposed solution). But, if $p_i \in \mathcal{P}$ is yet to have access to the decided value, $\text{result}_i()$ returns \perp . Otherwise, the decided value is returned. Specifically, for the case of $\text{propose}(v)$, the parameter s should be used when calling $\text{result}_i(s)$ and for the case of $\text{binPropose}(v)$, also the parameter $k : p_k \in \mathcal{P}$ should be used when calling $\text{result}_i(s, k)$.

We clarify that, in the absence of transient-faults, $\text{result}_i(s)$ and $\text{result}_i(s, k)$ always return either \perp or the decided value. Thus, we solve the problem specified by Definition 1.1. The studied algorithm [25] was not designed to deal with transient-faults. As we explain in Section 4.2, transient-faults can cause the studied algorithm to violate Definition 1.1's requirements without providing any indication to the invoking algorithm. After the occurrence of a transient-fault, the proposed solution allows $\text{result}_i(s)$ to provide such indication to the invoking algorithm via the return of the *transient error* symbol Ψ . Section 5.2.2 brings the details and Algorithm 4 exemplifies the indication handling.

3 System settings

We consider an asynchronous message-passing system that has no guarantees on the communication delay. Moreover, there is no notion of global (or universal) clocks and the algorithm cannot explicitly access the local clock (or timeout mechanisms). The system consists of a set, $\mathcal{P} = \{p_0, \dots, p_{n-1}\}$, of n crash-prone nodes (or processors) with unique identifiers. Due to an impossibility [14, Chapter 3.2], we assume that any pair of nodes $p_i, p_j \in \mathcal{P}$ have access to a bidirectional communication channel, $\text{channel}_{j,i}$, that, at any time, has at most $\text{channelCapacity} \in \mathbb{N}$ packets on transit from p_j to p_i .

In the *interleaving model* [14], the node's program is a sequence of (*atomic*) *steps*. Each step starts with an internal computation and finishes with a single communication operation, *i.e.*, a message *send* or *receive*. The *state*, s_i , of node $p_i \in \mathcal{P}$ includes all of p_i 's variables and $\text{channel}_{j,i}$. The term *system state* (or configuration) refers to the tuple $c = (s_1, s_2, \dots, s_n)$. We define an *execution* (or *run*) $R = c[0], a[0], c[1], a[1], \dots$ as an alternating sequence of system states $c[x]$ and (atomic) steps $a[x]$, such that each $c[x+1]$, except for the starting one, $c[0]$, is obtained from $c[x]$ by the execution of step $a[x]$ that some processor takes. The set of *legal executions* (*LE*) refers to all the executions in which the requirements of the task T hold.

3.1 The fault model and self-stabilization

Failures are environment steps rather than algorithm steps.

3.1.1 Benign failures

When the occurrence of a failure cannot cause the system execution to lose legality, *i.e.*, to leave *LE*, we refer to that failure as a benign one. The system is prone to *crash failures*, in which

nodes stop taking steps forever. We assume that at most $t < n/2$ node may crash. We denote by *Correct* the set of indices of processors that never crash. We consider solutions that are oriented towards asynchronous message-passing systems and thus they are oblivious to the time in which the packets arrive and depart. Also, the communication channels are prone to packet failures, such as omission, duplication, reordering. However, if p_i sends a message infinitely often to p_j , node p_j receives that message infinitely often. We refer to the latter as the *fair communication* assumption. We assume that any message can reside in a communication channel only for a finite period (before it is delivered or lost). The length of that period is unbounded since we assume no bound on transmission delays. In other words, our communication model formally excludes messages that it takes an infinite time to deliver or loss them; but to say that it takes an infinite time to deliver a given message means that this message is lost.

3.1.2 Arbitrary transient-faults

We consider any violation of the assumptions according to which the system was designed to operate. We refer to these violations and deviations as *arbitrary transient-faults* and assume that they can corrupt the system state arbitrarily (while keeping the program code intact). The occurrence of an arbitrary transient-fault is rare. Thus, our model assumes that the last arbitrary transient-fault occurs before the system execution starts [14]. Also, it leaves the system to start in an arbitrary state.

3.1.3 Dijkstra's self-stabilization criterion

An algorithm is *self-stabilizing* with respect to the task of LE , when every (unbounded) execution R of the algorithm reaches within a finite period a suffix $R_{legal} \in LE$ that is legal. That is, Dijkstra [13] requires that $\forall R : \exists R' : R = R' \circ R_{legal} \wedge R_{legal} \in LE \wedge |R'| \in \mathbb{Z}^+$, where the operator \circ denotes that $R = R' \circ R''$ concatenates R' with R'' . The complexity measure of self-stabilizing systems, called *stabilization time*, is the time it takes the system to recover after the occurrence of the last transient-fault, *i.e.*, $|R'|$. The studied and proposed solutions allow nodes to interact and share information via binary consensus objects and uniform reliable broadcast (URB). Thus, we measure the stabilization time as the number of accesses to these primitives plus the number of URB accesses.

4 Background: Non-self-stabilizing Non-blocking Multivalued Consensus

We review in sections 4.1 and 4.2 a non-self-stabilizing non-blocking algorithm for multivalued consensus by Mostéfaoui, Raynal, and Tronel [36], which uses an unbounded number of binary consensus objects.

4.1 Algorithm 1: non-self-stabilizing multivalued consensus

The non-self-stabilizing solution in Algorithm 1 is the basis for its self-stabilizing variation in Algorithm 2. For the sake of a simple presentation, the line numbers of Algorithm 2 continues the ones of Algorithm 1. The operation `propose(v)` (line 5) invokes an instance of a multivalued consensus object. Algorithm 1 uses a uniform reliable broadcast (URB) [41] for letting any $p_i \in \mathcal{P}$ disseminate its proposed value v_i (line 7). Each $p_j \in \mathcal{P}$ that delivers this proposal, stores this value in `proposalj[i]`. Also, $p_k \in \mathcal{P}$ can concurrently broadcast its proposal, v_k , which p_j

Algorithm 1: Non-self-stabilizing non-blocking multivalued consensus using an unbounded number of binary consensus instances; code for p_i

```

1 local variables:
2  $proposals[0, \dots, n-1]$  ;           /* array of the received proposals */
3  $k$  ;                               /* the round counter */
4  $BC[0, \dots, n-1]$  ;             /* binary consensus objects (unbounded list) */
5 operation propose( $v$ ) begin
6    $(proposals, BC) \leftarrow ([\perp, \dots, \perp], [\perp, \dots, \perp])$ ;
7   urbBroadcast PROPOSAL( $v$ );
8   while ( $k \leftarrow 0$ ; True;  $k \leftarrow k + 1$ ) do
9     if  $BC[k].binPropose((proposals[k \bmod n] \neq \perp))$  then
10      wait( $proposals[k \bmod n] \neq \perp$ );
11      return ( $proposals[k \bmod n]$ );
12 upon urbDelivered PROPOSAL( $v$ ) from  $p_j$  do { $proposals[j] \leftarrow v$ ;}

```

stores in $proposal_j[k]$. Therefore, Algorithm 1 needs to decide which entry in $proposal_j[]$ the $propose(v)$ operation should return. This decision is coordinated via an unbounded global array $BC[0], BC[1], \dots$, of binary consensus objects.

Algorithm 1 starts by URB-broadcasting p_i 's proposed value, v_i (line 7). This broadcast assures that all correct nodes receive identical sets of messages (Section 2.1.2). Also, the set of delivered messages must include every message URB-broadcast by any correct node. The arrival of PROPOSAL(v) from p_j , informs p_i about p_j 's proposal, and thus, p_i stores v_j in $proposal_i[j]$ (line 12).

Following the proposal broadcast, Algorithm 1 proceeds in asynchronous rounds. The variable k stores the round counter (lines 3 and 8). Once p_i decides, it leaves the loop by returning the value of $proposal_i[x_i]$ (line 11), where $x_i = k_i \bmod n$. In other words, $x_i \in \{0, \dots, n-1\}$ is the identifier of the node that has broadcast the proposal stored in $proposal_i[x_i]$.

As mentioned, the selection of x_i is facilitated via the unbounded array, $BC[]$, of binary consensus objects. Since all correct nodes eventually receive the same set of broadcasts, p_i proposes $proposal_i[x] \neq \perp$ to the k_i -th object, $BC[k_i]$ (line 9). *I.e.*, p_i proposes True on the k_i -th round if, and only if, it received p_{x_i} 's proposal.

Algorithm 1 continues to the next round whenever $BC[k_i]$ decides False. Otherwise, p_i decides the value, $proposal_i[x_i]$, proposed by p_{x_i} . Due to asynchrony, p_i might need to wait until p_{x_i} 's broadcast was URB-delivered (line 10). However, if any node proposed to decide v_{x_i} , it must be the case that $proposal_i[x_i]$ was delivered to the node that has proposed True at $BC[k_i]$. Therefore, eventually, p_i is guaranteed to URB-deliver v_{x_i} and stores it at $proposal_i[x_i]$. For this reason, Algorithm 1 does not block forever in line 10 and the decided value is eventually returned in line 11.

4.2 Executing Algorithm 1 in the presence of transient-faults

Before describing Algorithm 2, we review the main challenges that one faces when transferring Algorithm 1 to an algorithm that can recover after the concurrence of transient-faults.

- (a) Upon $\text{propose}(v)$, uniform reliable broadcast $\langle v \rangle$.
- (b) By URB-termination, eventually, there is $p_j \in \mathcal{P}$ and round k' , such that p_j 's message arrived at all non-faulty processors, *i.e.*, $\forall \ell \in \text{Correct} \implies \text{proposals}_\ell[j] \neq \perp$.
- (c) For $k \in \{0, 1, 2, \dots\}$, p_i invokes $BC[k].\text{binPropose}(\text{proposals}[k \bmod n] \neq \perp)$.
- (d) By BC-termination and stage (b), eventually, the k_{\min} -th binary consensus objects is the first to decide **True** while all x -th objects decide **False**, where $x \in \{0, 1, 2, k_{\min}-1\}$.
- (e) Due to URB-termination, eventually, $\text{proposals}[k_{\min} \bmod n]$ includes a non- \perp value.
- (f) Then, return $\text{proposals}[k_{\min} \bmod n]$ as the decided value.

Figure 2: High-level stages in the execution of Algorithm 1; code for p_i

4.2.1 Use of an unbounded number of binary objects

Self-stabilizing systems can only use a bounded amount of memory [14]. This is because, in practice, computer systems can use only a finite amount of memory. However, a single transient-fault can set every counter (or data-structure) to its maximum value (respectively, exhaust the memory capacity of the data-structure).

4.2.2 Corrupted round number counter

In the context of self-stabilization, one cannot simply rely on counter k (line 3) to count the number of asynchronous rounds. This is because a single transient-fault can set the value of k to zero. It can also alter the state of every $BC[k]_{k \in \{0, \dots, z\} \wedge z \in \mathbb{Z}^+}$, such that a call to $\text{propose}()$ returns **False**, where z can be practically infinite, say $z = 2^{64} - 1$. In this case, the system will have to iterate for 2^{64} times before a fresh binary consensus object is reached.

4.2.3 Corrupted program counter

A transient-fault can set the program counter of every $p_j \in \mathcal{P}$ to skip over the broadcast in line 7 and to point to line 8. If this happens, then validity or termination can be violated. Therefore, there is a need to repeat the transmission of v_i in order to make sure that at least one proposal is known to all correct processors.

4.2.4 A corrupted array of binary objects

Transient faults can corrupt binary objects in the array $BC[]$. Specifically, since the array $BC[]$ should include only a bounded number of binary consensus objects, a transient-fault can change the state of all objects in $BC[]$ to encode ‘decide **False**’. In this case, Algorithm 1 cannot finish the multivalued consensus.

5 The Proposed Solution: Self-stabilizing Wait-free Multivalued Consensus

This section presents a new self-stabilizing algorithm for multivalued consensus that is wait-free and uses n binary consensus objects and n self-stabilizing uniform reliable broadcasts (URBs) [32]. The correctness proof appears in Section 6.

- (a) Upon `propose(v)`, uniform reliable broadcast $\langle v \rangle$.
- (b) Wait until `hasTerminated()` says that $\langle v \rangle$ arrived at all non-faulty processors.
- (c) For $k \in \{0, \dots, n-1\}$, p_i invokes `BC[k].binPropose(proposals[k mod n] $\neq \perp$)`.
- (d) By BC-termination and stage (b), eventually, the k_{\min} -th binary consensus objects is the first to decide `True` while all x -th objects decide `False`, where $x \in \{0, 1, 2, k_{\min}-1\}$.
- (e) Due to URB-termination, eventually, `proposals[kmin mod n]` includes a non- \perp value.
- (f) Then, return `proposals[kmin mod n]` as the decided value.

Figure 3: A bounded alternative to Figure 2; code for p_i

5.1 The algorithm idea

We sketch the key notions that are needed for Algorithm 2 by addressing the challenges raised in Section 4.2.

5.1.1 Using a bounded number of binary objects

We explain how Algorithm 2 can use only at most n binary consensus objects. Figure 2 is a high-level description of Algorithm 2's execution and Figure 3 shows how this process can be revised. The key differences between figures 2 and 3 appear in the boxed text of Figure 3. Specifically, Figure 3 waits until p_i 's broadcast has terminated in line (b). At that point in time, p_i knows that all non-faulty processors have received its message. Only then does p_i allow itself to propose values via the array of binary objects. This means that no processor starts proposing any binary value before there is at least one index $k \in \{0, \dots, n-1\}$ for which `proposalsj[k] $\neq \perp$` , where p_j is any node that has not failed. This means that, regardless of who is going to invoke the k -th binary consensus object, only the value `True` can be proposed. For this reason, there is no need to use more than n binary consensus values until at least one of them decides `True`, cf. line (c) in Figure 3.

5.1.2 Dealing with corrupted round number counter

Using the object values in `BC[]`, Algorithm 2 calculates $k()$, which returns the current round number. This way, a transient-fault cannot create inconsistencies between $k()$'s value and `BC[]`.

In detail, for an active multivalued consensus object O , *i.e.*, $O \neq \perp$, we say that the binary consensus object $O.BC[k]$ is active when $O.BC[k] \neq \perp$. Algorithm 2 calculates $k()$ (line 19) by counting the number of active binary consensus objects that have terminated and the decided value is `False`. We restrict this counting to consider only the entries `BC[k]`, such that $k = 0$ or $\forall k' < k : BC[k']$ is an active binary consensus objects that have terminated and the decided value is `False`. This is defined by the set $\mathbf{K} = (\{k \in S(n-1) : O.BC[k] \neq \perp \wedge O.BC[k].result(k) = \text{False}\})$, where $S(x) = \{0, \dots, x\}$ is the set of all integers between zero and x . This way, the value of $k()$ is simply $\max(\{-1\} \cup \{x \in S(n-1) : (S(x) \cap \mathbf{K}) = S(x)\})$. Note that the value of -1 is used to indicate that there are no active binary objects in `BC[]` that have terminated with a decided value of `False`, *i.e.*, $\mathbf{K} = \emptyset$.

5.1.3 Dealing with a corrupted program counter

As explained in Section 4.2.3, there is a need to repeat the transmission of v_i in order to make sure that at least one proposal is known to all correct processors. Specifically, after $\text{propose}_i(v_i)$'s invocation, $p_i \in \mathcal{P}$ need to store v_i and broadcasts v_i repeatedly due to a well-known impossibility [14, Chapter 2.3]. Note that there is an easy way to trade the broadcast repetition rate with the recovery speed from transient-faults. Also, once the first broadcast has terminated, all correct processors $p_i \in \mathcal{P}$ are ready to decide by proposing $\text{binPropose}_i(k, \text{proposals}_i[k] \neq \perp)$ for any $p_k \in \mathcal{P}$, see steps (b) and (c) in Figure 3.

5.1.4 Dealing with a corrupted array of binary objects

Algorithm 2 uses only n binary consensus objects. Due to the challenge in Section 4.2.4, we explain how to deal with the case in which a transient-fault changes the state of all objects in $BC[]$ to encode 'decide False'. In this case, the algorithm cannot satisfy the requirements of the multivalued consensus task (Definition 1.1). Therefore, our solution identifies such situations and informs the invoking algorithm via the return of the *transient error* symbol Ψ .

5.2 Algorithm description

5.2.1 The $\text{propose}(v)$ operation and variables

The operation $\text{propose}(v)$ activates a multivalued object by initializing its fields (line 20). These are the proposed value, v , the array, $\text{proposals}[]$, of received proposals, where $\text{proposals}[j]$ stores the value received from $p_j \in \mathcal{P}$. Moreover, $BC[]$ is the array of binary consensus objects, where the active object $BC[j]$ determines whether the value in $\text{proposals}[j]$ should be the decided value. Also, txDes is the transmission descriptor (initialized with \perp), and oneTerm is a boolean that indicates that at least one transmission has completed, which is initialized with False. Note that only v has its (immutable) value initialized in line 20 to its final value. The other fields are initialized to \perp or an array of \perp values; their values can change later on.

5.2.2 The $\text{result}()$ operation

Algorithm 2 allows retrieving the decided value via $\text{result}()$ (line 21). As long as the multivalued consensus object is not active (line 22), or there is no decision yet (line 24), the operation returns \perp . As explained in Section 5.1.3, Algorithm 2 might enter an error state. In this case, $\text{result}()$ returns Ψ (lines 23 and 25). The only case that is left (the else clause of line 25) is when there is a binary consensus object $O.BC[k]$ and a matching $O.\text{proposals}[k] \neq \perp$, where $k = k()$. Here, due to the definition of $k()$ (line 19), for any $k' \in \{0, \dots, k-1\}$ the decided value of $O.BC[k']$ is False and $O.BC[k]$ decides True. Thus, $\text{result}_i()$ returns the value of $O.\text{proposals}[k]$.

5.2.3 The do-forever loop

As explained above, Algorithm 2 has to make sure that the proposed value, v , arrives at all processors and records in oneTerm the fact that at least once transmission has arrived. To that end, in line 27, p_i tests the predicate $(\text{txDes} \neq \perp \wedge \text{hasTerminated}(\text{txDes}))$ and makes sure that the transmission descriptor, txDes , refers to an active broadcast, *i.e.*, txDes stores a descriptor that has not terminated (cf. $\text{hasTerminated}()$'s definition in Section 2.1.2). In detail, whenever $x.\text{txDes} \neq \perp$ holds, $\text{hasTerminated}_i(\text{txDes})$ holds eventually (URB-termination). Thus, the if-statement condition in line 27 holds eventually and p_i URB-broadcast PROPOSAL(v) (line 29)

Algorithm 2: Self-stabilizing non-blocking multivalued consensus; p_i 's code

```
13 variables: /* initialization is optional in the context of
    self-stabilization */
14  $v$ ; /* local decision estimates */
15  $proposals[0, \dots, n-1]$ ; /* array of arriving proposals */
16  $BC[0, \dots, n-1]$ ; /* array of  $n$  binary consensus objects */
17  $txDes$ ; /* URB transmission descriptor for decision sharing */
18  $oneTerm$ ; /* true once at least one broadcast termination occurred */
19 macro  $k() = \max(\{-1\} \cup \{x \in S(n-1) : (S(x) \cap K) = S(x)\})$ : where  $S(x) =$ 
     $\{0, \dots, x\}$  and  $K = (\{k \in S(n-1) : O.BC[k] \neq \perp \wedge O.BC[k].result(k) = \text{False}\})$ ;
    /*  $k()$  is the max consecutive  $BC[]$  entry index with the decision False */
20 operation  $propose(v)$  do if  $v \neq \perp \wedge O = \perp$  then
     $O.(v, proposals, BC, txDes, oneTerm) \leftarrow (v, [\perp, \dots, \perp], [\perp, \dots, \perp], \perp, \text{False})$ ;
21 operation  $result()$  begin
22   if  $O = \perp$  then return  $\perp$ ;
23   else if  $O.v = \perp \vee k \geq n-1$  then return  $\Psi$  where  $k = k()$ ;
24   else if  $BC[k+1] = \perp \vee BC[k+1].result(k+1) \neq \text{True}$  then return  $\perp$ ;
25   else if  $x = \perp$  then return  $\Psi$  else return  $x$  where  $x = O.proposals[k+1]$ ;
26 do forever foreach  $O \neq \perp$  with  $O$ 's fields  $v, proposals, BC,$  and  $txDes$  do
27   if  $(v \neq \perp \wedge (txDes = \perp \vee \text{hasTerminated}(txDes)))$  then
28      $oneTerm \leftarrow oneTerm \vee (txDes \neq \perp \wedge \text{hasTerminated}(txDes))$ ;
29      $txDes \leftarrow \text{urbBroadcast PROPOSAL}(v)$ 
    /* use either lines 30 to 31 or lines 32 to 33 */
30   if  $oneTerm \wedge k < n-1 \wedge BC[k+1] = \perp \wedge (k=-1 \vee BC[k].result(k) \neq \perp)$  then
31      $\text{binPropose}(k+1, proposals[k+1] \neq \perp)$  where  $k = k()$ 
32   if  $oneTerm \wedge \exists \ell : BC[\ell] = \perp$  then /* invoke BC objects concurrently */
33     for each  $k \in \{0, \dots, n-1\} : BC[k] = \perp$  do  $\text{binPropose}(k, proposals[k+1] \neq \perp)$ 
34 upon  $\text{PROPOSAL}(vJ)$  urbDelivered from  $p_j$  begin
35   if  $vJ \neq \perp$  then
36     if  $O \neq \perp \wedge O.proposals[j] = \perp$  then  $O.proposals[j] \leftarrow vJ$ ;
37     else if  $O = \perp$  then  $(O.(v, proposals, BC, txDes),$ 
     $O.proposals[j]) \leftarrow ((sJ, vJ, [\perp, \dots, \perp], [\perp, \dots, \perp], \perp), vJ)$ ;
```

after checking that $v \neq \perp$ (line 27). Note that p_i records the fact that at least one transmission was completed by assigning True to $oneTerm$ (line 28).

Upon the URB-delivery of p_i 's $\text{PROPOSAL}(vJ)$ at $p_j \in \mathcal{P}$, processor p_j considers the following two cases. If O is an active object, p_j merely checks whether $O.proposals[i]$ needs to be updated with vJ (line 36). Otherwise, O is initialized with vJ as the proposed value (line 37) similarly to line 20.

Going back to the sender side, Algorithm 2 uses either lines 30 to 31, which sequentially access the array, $BC[]$, of binary consensus objects, or lines 32 to 33, which simply access all binary objects concurrently. In both methods, processor p_i makes sure that at least one broadcast was

completed, *i.e.*, $oneTerm = \text{True}$ (lines 28, 30 and 32). When following the sequential method (lines 30 to 31), the aim is to invoke binary consensus by calling $\text{binPropose}(k+1, \text{proposals}[k+1] \neq \perp)$ (line 31), where $k = k_i()$. This can only happen when the $(k+1)$ -th object in $BC[]$ is not active, *i.e.*, $BC[k+1] = \perp$ and $BC[k+1]$ is either the first in $BC[]$, *i.e.*, $k = -1$ or $BC[k]$ has terminated, *i.e.*, $BC[k].\text{result}_i(k) \neq \perp$ (line 30).

The advantage of the sequential access method over the concurrent one is that it is more conservative with respect to the number of consensus objects that are being used since once the decision is True , there is no need to use more objects. The concurrent access method, marked in the boxed lines, encourages to piggyback of the messages related to binary concurrent objects. This is most relevant when every message (of binary consensus) can carry the data-loads of n proposals. In this case, the concurrent access method is both simpler and faster than the sequential one.

6 Correctness of Algorithm 2

Theorems 6.1 and 6.6 show that Algorithm 2 implements a self-stabilizing multivalued consensus. Definition 6.1 is used by Theorem 6.1. As explained in Section 2.3, for the sake of a simple presentation, we make the following assumptions. Let R be an Algorithm 2's execution, $p_i \in \mathcal{P}$, and O_i a multivalued consensus object.

Definition 6.1 (Consistent multivalued consensus object) *Let R be an Algorithm 2's execution and O_i a multivalued consensus object, where $p_i \in \mathcal{P}$. Suppose either (i) $O_i = \perp$ is inactive or that (ii) $O_i \neq \perp$ is active, $O_i.v \neq \perp \wedge (k < n - 1) \wedge ((BC[k+1] = \perp \vee BC[k+1].\text{result}(k+1) = \perp \vee (BC[k+1].\text{result}(k+1) = \text{True} \wedge O_i.\text{proposals}[k+1] \neq \perp))$), where $k = k_i()$. In either case, we say that O_i is consistent in c .*

Theorem 6.1 shows recovery from arbitrary transient-faults.

Theorem 6.1 (Convergence) *Let R be an Algorithm 2's execution. Suppose that there exists a correct processor $p_j \in \mathcal{P} : j \in \text{Correct}$, such that throughout R it holds that $O_j \neq \perp$ is an active multivalued consensus object. Moreover, suppose that any correct processor $p_i \in \mathcal{P} : i \in \text{Correct}$ calls $\text{result}_i()$ infinitely often in R . Within n invocations of binary consensus, (i) the system reaches a state $c \in R$ after which $\text{result}_i() \neq \perp$ holds. Specifically, (ii) O_i is either consistent (Definition of 6.1) or eventually reports the occurrence of a transient-fault, *i.e.*, $\text{result}_i() = \Psi$.*

Proof of Theorem 6.1 Lemmas 6.2 and 6.5 implies the proof.

Lemma 6.2 *Invariant (i) holds, *i.e.*, $\text{result}_i() \neq \perp$ holds in c .*

Proof of Lemma 6.1 Suppose, towards a contradiction, that c does not exist. Specifically, let R' be the longest prefix of R that includes no more than n invocations of binary consensus. The proof of Invariant (i) needs to show that the system reaches a contradiction by showing that $c \in R'$. To that end, arguments (1) to (3), as well as claims 6.3 to 6.4, show the needed contradiction.

Argument (1) implies that it is enough to show that the if-statement in line 24 cannot hold eventually.

Argument (1) *The if-statement conditions in lines 22, 23, and 25 do not hold for p_j throughout R .* By the theorem assumption that $O_j \neq \perp$ is an active multivalued consensus object throughout R , we know that the if-statement condition in line 22 cannot hold. Moreover, by the

assumption that c does not exist, we know that the if-statement conditions in lines 23 and 25 do not hold for any (correct) p_i throughout R .

Argument (2) *The invariant $O_j.v \neq \perp$ holds throughout R .* Since the if-statement condition in line 23 does not hold, $O_j.v \neq \perp$ holds in R 's starting system state. Moreover, only lines 20, 36, and 37 change the value of $O_j.v$ but this happens only after testing that the assigned value is not \perp (lines 20 and 35).

Argument (3) *R has a suffix in which all correct processors $p_i \in \mathcal{P}$ are active.* Since p_j is active and $O_j.v \neq \perp$ holds throughout R , the if-statement condition in line 27 holds eventually since either $txDes = \perp$ or $\text{hasTerminated}(txDes)$ holds eventually due to the URB-termination property. By line 29, p_j broadcasts the $\langle v \rangle$ message to all correct processors p_i . By the URB-termination property, p_i receives $\langle v \rangle$ and by lines 36 to 37, processor p_i is active.

Argument (4) $\forall i, j \in \text{Correct} : O_i.\text{proposals}[j] \neq \perp \wedge O_i.txDes \neq \perp \wedge O_i.\text{oneTerm} = \text{True}$ holds eventually. By URB-termination, $\text{hasTerminated}(O_i.txDes)$ holds eventually. Once that happens, the if-statement condition in line 27 holds (due to arguments (2) and (3)) and $O_i.txDes = \perp$ cannot hold (line 29). By Argument (2), $O_i.v \neq \perp$. Thus, p_i eventually URB-broadcasts $\text{PROPOSAL}(O_i.v)$. Once p_i self-delivers this message, line 36 assigns v to $O_i.\text{proposals}[i]$ due to the assumption that $O_i \neq \perp$ throughout R . We can now repeat the reasoning that $\text{hasTerminated}(O_i.txDes)$ holds eventually and thus the if-statement condition in line 27 hold. Thus, $O_i.\text{oneTerm} = \text{False}$ does not hold eventually (line 28). By Argument (3), the same holds for p_j . Specifically, p_j eventually URB-broadcasts $\text{PROPOSAL}(O_j.v)$. Once p_i URB-delivers this message from p_j , p_i 's state can possibly change, even in the case that $O_i \neq \perp$, cf. lines 36 and 37.

Claim 6.3 *The if-statement condition in lines 30 and 32 can only hold at most n times for any $p_i \in \mathcal{P} : i \in \text{Correct}$.*

Proof of Claim 6.1 The if-statement condition in line 32 can only hold at most once due to line 33. Thus, the rest of the proof focuses on line 31.

By the proof of Argument (4), eventually, the system reaches a state, $c' \in R$, in which $O_i.txDes \neq \perp \wedge O_i.\text{proposals}[j] \neq \perp \wedge O_i.\text{oneTerm} = \text{True}$ holds. Note that the if-statement condition in line 30 holds whenever $k = -1$. Arguments (5) and (6) assumes that $k > -1$ and consider the cases in which $O_i.BC[k+1] \neq \perp$ holds and does not hold, respectively, where $k = k()$. Argument (7) shows that the if-statement condition in line 30 can hold at most n times.

Argument (5) *Suppose that $k > -1 \wedge O_i.BC[k+1] \neq \perp$ holds. Eventually, either $k_i() < n-1$ does not hold or the if-statement condition in line 30 holds. $BC[k+1].\text{result}_i(k+1) \neq \perp$ holds eventually due to the termination property of binary consensus objects.*

In case $BC[k+1].\text{result}_i(k+1) = \text{True}$, we know that $\text{result}_i() \neq \perp$ holds due to the definition of $k()$ (line 19). However, this implies a contradiction with the assumption made at the start of this lemma's proof.

In case $BC[k+1].\text{result}_i(k+1) = \text{False}$ holds, the if-statement condition in line 30 holds in c' if $k+1 < n-1$ and $O_i.BC[k+1] = \perp$. In case the former predicate holds and the latter does not, we can repeat the reasoning above for at most n times until either the former does not hold or both predicates hold. In either case, the proof of the argument is done.

Argument (6) *Suppose that $k > -1 \wedge O_i.BC[k+1] = \perp$ holds. Eventually, either $k_i() < n-1$ does not hold or the if-statement condition in line 30 holds. The if-statement condition in line 30 holds if $BC[k].\text{result}_i(k) \neq \perp$ holds. Since $k > -1$, the reasoning in the proof of*

Argument (5), which shows that $BC[k+1].\text{result}_i(k+1) \neq \perp$ holds, can be used for showing that $BC[k].\text{result}_i(k) \neq \perp$ holds eventually.

Argument (7) *Within n invocations of $\text{binPropose}_i()$, the if-statement condition in line 30 does not hold.* Suppose that the if-statement condition in line 30 holds. In line 31, p_i invokes the operation $\text{binPropose}_i(k+1, O_i.\text{proposals}[k+1] \neq \perp)$ of the $(k+1)$ -th binary consensus object. This invocation changes p_i 's state, such that $O_i.BC[k+1] = \perp$ does not hold any longer (because the $\text{binPropose}_i()$ operation initializes the state of $O_i.BC[k+1]$). Since $BC[]$ has n entries, there could be at most n such invocations until the system reaches $c'' \in R$, after which the if-statement condition in line 30 cannot hold. $\square_{\text{Claim 6.3}}$

Claim 6.4 *Once the if-statement condition in line 30 (or 32) does not hold, also the if-statement condition in line 24 does not hold.*

Proof of Claim 6.1 Since if-statement condition in line 30 does not hold, we know that $BC_i[k+1] = \perp$ does not hold, see Argument (5) of Claim 6.3. In the case of line 32, the same holds in a straight forward manner. By BC-termination, $BC[k+1].\text{result}_i(k+1) \neq \perp$ holds eventually. Since $\forall p_x \in \mathcal{P} : O_i.BC[x] \neq \perp \wedge BC[x].\text{result}_i(x) = \text{False}$ implies a contradiction with Argument (1), we know that $BC_i[k+1].\text{result}(k+1) \neq \text{True}$ cannot hold. $\square_{\text{Claim 6.4}}$

$\square_{\text{Lemma 6.5}}$

Lemma 6.5 *Invariant (ii) holds, i.e., O_i is either consistent or $\text{result}_i() = \Psi$.*

Proof of Lemma 6.1 Recall that the theorem assumes that O_i is an active object throughout R . The argument is implied by Definition 6.1 and lines 22 to 25.

In detail, line 22 handles the case in which $O_i = \perp$. Suppose that $O_i \neq \perp$ is active, which indicates that an inconsistent was detected. Line 23 handles the case in which $O_i.v \neq \perp \wedge k < n-1$ does not hold by returning Ψ , where $k = \kappa_i()$, which indicates that an inconsistent was detected. Line 24 allows the case in which $BC[k+1] = \perp \vee BC[k+1].\text{result}(k+1) = \perp$ (note that the case of $BC[k+1].\text{result}(k+1) = \text{False}$ does not exist due to the definition of $k()$ in line 19). This case is allowed since it is consistent, see Definition 6.1. Line 25 handles the case in which $(BC[k+1].\text{result}(k+1) = \text{True} \wedge O_i.\text{proposals}[k+1] \neq \perp)$ does not hold by returning Ψ , which indicates that an inconsistent was detected. $\square_{\text{Lemma 6.5}}$ $\square_{\text{Theorem 6.1}}$

Definition 6.2 is used by Theorem 6.6.

Definition 6.2 (Complete execution with respect to propose() invocations) *Let R be an execution of Algorithm 2 that starts in $c \in R$. We say that c is completely free of PROPOSAL(-) messages if (i) the communication channels do not include PROPOSAL(-) messages, and (ii) for any non-failing $p_i \in \mathcal{P}$, there is no active multivalued consensus object $O_i = \perp$ in c . Let $c_s \in R$ be the system state that is: (a) completely free of PROPOSAL(-), and (b) it appears in R immediately before a step that includes p_i 's invocation of propose(-) (lines 20) in which O_i becomes active (rather than due to the arrival of a PROPOSAL(-) message in lines 35 to 37). In this case, we say that p_i 's invocation is authentic. Suppose that p_i sends a PROPOSAL(-) message after c_s . In this case, we say that PROPOSAL(-) is an authentic message transmission. An arrival of PROPOSAL(-) to $p_j \in \mathcal{P}$ (lines 20) is said to be authentic if it is due to an authentic message transmission. Suppose that p_j activates $O_j = CS_j[s]$ (line 37) due to an authentic arrival (rather than an invocation of the propose(-) operation). In this case, we also say that p_j 's invocation is authentic. We complete the definitions of authentic transmissions, arrivals, and invocations by applying the transitive closures of them. Suppose that any invocation in R*

of $\text{propose}_k(-) : p_k \in \mathcal{P}$ is authentic as well as the transmission and reception of $\text{PROPOSAL}(-)$ messages from or to p_k . In this case, we say that R is authentic.

Theorem 6.6 shows that Algorithm 2 satisfies the task requirements (Section 2.2).

Theorem 6.6 (Closure) *Let R be an authentic execution of Algorithm 2. The system demonstrates in R the construction of a multivalued consensus object.*

Proof of Theorem 6.6 Validity holds since only the user input is stored in the field v (line 20), which is then URB-broadcast (line 29), stored in the relevant entry of proposals (lines 36 to 37), and returned as the decided value (line 25). Moreover, any value in v can be traced back to an invocation of $\text{propose}(v)$ since R is authentic.

Lemma 6.7 demonstrates termination and agreement.

Lemma 6.7 *Let $a_i \in R$ be the first step in R that includes an invocation, say, by $p_i \in \mathcal{P}$ of $\text{propose}_i(v_i)$. Suppose that $v_i \neq \perp$ holds in any system state of R . There exists $v \notin \{\perp, \Psi\}$, such that for every correct $p_j \in \mathcal{P}$ it holds that $\text{result}_j()$ returns v within n invocations of binary consensus.*

Proof of Lemma 6.6 Arguments (1) to (7) imply the proof.

Argument (1) $O_i.(v, \text{proposals}, BC, txDes, oneTerm) = (v, [\perp, \dots, \perp], [\perp, \dots, \perp], \perp, \text{False})$ holds immediately after a_i . We show that the if-statement condition in line 20 holds immediately before a_i . Recall the theorem assumption that $v_i \neq \perp$ holds in R . By the assumption that R is authentic, we know that $O_i = \perp$ holds immediately before a_i . Therefore, p_i assigns $(v_i, [\perp, \dots, \perp], [\perp, \dots, \perp], \perp, \text{False})$ to $O_i.(v_i, \text{proposals}_i, BC_i, txDes_i, oneTerm_i)$ (line 20).

Argument (2) *Eventually* $\text{PROPOSAL}(v_i)$ messages are URB broadcast and $oneTerm_i$ holds. By URB-termination, $\text{hasTerminated}(O_i.txDes)$ does not hold eventually. Since $O_i.v \neq \perp$ (by the lemma assumption), the if-statement condition in line 27 holds and p_i URB-broadcasts $\text{PROPOSAL}(O_i.v)$. By applying again the same argument, the assignment in line 28 makes sure that $oneTerm_i = \text{True}$.

Argument (3) *For any $p_x \in \mathcal{P} : x \in \text{Correct}$, eventually $O_x.\text{proposals}[i] \neq \perp$ and $O_x.\text{proposals}[x] \neq \perp$ hold.* By URB-termination, every correct processor, p_x , eventually URB-delivers Argument (2)'s $\text{PROPOSAL}(v_i)$ message. By the assumption that $v_i \neq \perp$ holds in any system state of R , the if-statement condition in line 35 holds (even if p_x has invoked $\text{propose}_x(v_x)$ before this URB delivery).

In case there was no earlier invocation of $\text{propose}_x(v_x)$, the assignment $O_x.v \leftarrow v_i$ occurs due to line 37 (otherwise, a similar assignment occurs due to line 36). Moreover, due to the reasons that cause p_i URB broadcasts in Argument (2), also p_x URB broadcasts $\text{PROPOSAL}(v' \neq \perp)$ messages. Upon the URB delivery of p_x message to itself, the $O_x.\text{proposals}[x] \leftarrow v' \neq \perp$ assignment occurs (line 36). (Note that this time, the if-statement condition in line 36 must hold since $O_x \neq \perp$.)

Argument (4) *The if-statement condition in lines 30 and 32 hold eventually.* Since $oneTerm_i$ holds eventually (Argument (2)), the if-statement condition in line 32 holds eventually. Also, the fact that $O_x.\text{proposals}[x] \neq \perp$ (Argument (3)) and URB-termination imply that eventually, in p_x 's do-forever loop, the if-statement condition in line 30 holds. In detail, since R is an authentic execution, $k = -1 \wedge BC[k+1] = \perp$ holds in R 's second state, where $k = k_x()$.

Let $S(z) = \{0, \dots, z\}$. The proof of Argument (5) shows $\exists y \in S(n-1), \forall x \in \text{Correct}, p_x$ invokes $\text{binPropose}_x()$ at most y times and it observes that $O_x.BC[k] \neq \perp : k \in S(y-1)$.

Argument (5) *The Termination property holds.* By line 33, the if-statement condition in line 32 can hold at most once. The if-statement condition in line 30 cannot hold for more than n times due to the $(k < n-1)$ clause. Thus, the termination property is implied.

Let $r(j) = [x(0), \dots, x(n-1)] : x(k) = BC_j[k].\text{result}(k)$ and $S = \{[\perp, \dots, \perp], [\dots, \text{False}, \perp, \dots, \perp], [\dots, \text{False}, \text{True}, \perp, \dots, \perp], [\dots, \text{False}, \text{True}]\}$. For the case of using lines 30 to 31, the proof of Argument (6) shows $\forall p_j \in \mathcal{P} : r(j) \in S$, *i.e.*, sequential invocation of `binPropose()`.

Argument (6) *For the case of using lines 30 to 31, $r(j) \in S$ holds.* Due to lines 19 and 30 as well as the agreement property of binary consensus objects and the fact that R is authentic, we know that eventually, all non-failing nodes must observe the same results from their consensus objects. Specifically for the case of lines 30 to 31, it holds that $\forall p_j \in \mathcal{P} : r(j) = r_s$. Also, at any time, $r(j)$ can only include a finite number (perhaps empty but with no more than $n-1$) of `False` values that are followed by at most one `True` value and the only \perp -values (if space is left), *i.e.*, $r(j) \in S$.

Argument (7) *The Agreement property holds.*

Since no $p_j \in \mathcal{P}$ invokes `binProposej(k_j+1 , $O_x.\text{proposals}[k_j+1] \neq \perp$)` (lines 30 and 32), before it had assured the safe URB delivery of $O_x.\text{txDes}$'s transmission, we know that eventually, at least one element of $r(j)$ is `True`. Thus, by the agreement property of binary consensus, every p_x eventually calculates the same value of $k_j()$, such that $BC[k_j()].\text{result}_x(k_j() + 1) = \text{True}$. This implies the agreement property since `resultx()` returns $O_x.\text{proposals}[k_j()+1]$ for any non-failing $p_x \in \mathcal{P}$ (line 25). $\square_{\text{Lemma 6.7}}$

Lemma 6.8 demonstrates the property of integrity.

Lemma 6.8 *Suppose that $\exists v' \notin \{\perp, \Psi\} : \exists p_j \in \mathcal{P} : \exists c' \in R : \text{result}_j() = v'$ in c' . $\nexists c'' \in R : \text{result}_j() = v''$ in c'' , such that $v' \neq v''$.*

Proof of Lemma 6.6 The proof is by contradiction. Suppose that $c'' \in R$ exists and, without the loss of generality, c' appears before c'' in R . Since R is authentic and $c' \in R$ exists, then there is a $p_k \in \mathcal{P} : k \in S(n-1)$, such that for any $p_j \in \mathcal{P}$, there is a system state c'_j that appears in R not after c' in which for any $k' \in S(n-1)$ it holds that $BC[k'].\text{result}_j(k') = \text{False}$ for the case of $k' < k$ and $BC[k].\text{result}_j(k') = \text{True}$ for the case of $k' = k$. This is due the definition of $k()$ (line 19). Note that in any system state that follows c'_j , the value of $k = k_j()$ does not change due to the integrity of binary consensus objects. Therefore, `resultj()` must return the value of $O_j.\text{proposal}[k]$ in any system state that follows c'_j . Since line 36 does not allow any change in the value of $O_j.\text{proposal}[k]$ between c' and c'' , it holds that $v' = v''$. Thus, the proof reached a contradiction and the lemma is true. $\square_{\text{Lemma 6.8}}$ $\square_{\text{Theorem 6.6}}$

7 Application: Self-stabilizing Total-order Message Delivery using Multivalued Consensus

We exemplify the use of Algorithm 2 by implementing the task total order uniform reliable broadcast (TO-URB), which we specified in Section 2.2.1. We describe our implementation before bringing the correctness proof.

7.1 Refinement of the system settings

Our self-stabilizing total order message delivery implementation (Algorithm 3) provides the `toBroadcast(m)` operation (line 44). It uses a self-stabilizing URB with FIFO-order delivery,

Algorithm 3: Self-stabilizing TO-URB via consensus; code for $p_i \in \mathcal{P}$

```
38 notations:  $x \text{ opr}_3 y \equiv (x \text{ opr } y) \bmod 3 : \text{opr} \in \{-, +\}$ ;  
39 constants and variables:  $\delta \in \mathbb{Z}^+$  max number of messages after which is delivery is  
    enforced;  $CS[0..2] = [\perp, \dots, \perp]$  array of multivalued consensus objects;  $obsS = 0$   
    highest obsolete sequence number  
40 macro  $S() = \{CS[k].seq : CS[k] \neq \perp\}_{k \in \{0, \dots, 2\}}$ ;  
41 macro  $getSeq()$  do return  $\max(\{obsS\} \cup S());$   
42 macro  $test(s)$  do return  $(s \in (S() \cup \{getSeq() + 1\}))$ ;  
43 macro  $\Delta()$  do return  $((\text{allHaveTerminated}() \wedge 0 < \ell) \vee \delta \leq \ell)$  where  
     $(x, y, \ell) = (\text{minReady}(), \text{maxReady}(), \sum_{p_k \in \mathcal{P}} (y[k] - x[k]))$ ;  
44 operation  $toBroadcast(m)$  do  $\text{fifoURB}(toURB(m))$ ;  
45 do forever begin  
46   if  
     $(\exists k \in \{0, \dots, 2\} : CS[k] \neq \perp \wedge CS[k].seq \bmod 3 \neq k) \vee (S() \neq \emptyset \wedge (obsS > \max S() \vee$   
     $\max S() - \min S() > 1))$  then  $CS \leftarrow [\perp, \dots, \perp]$  ;  
47    $sn \leftarrow sn + 1$ ;  
48   repeat  
49     foreach  $p_j \in \mathcal{P}$  do  $\text{send SYNC}(sn)$  to  $p_j$ ;  
50     until  $\text{SYNCack}(sn, \bullet)$  received from all  $p_j : j \in \text{trusted}$ ;  
51     let  $(allReady, maxSeq, allSeq) = (\text{entrywise-min}\{x\}_{(\bullet, x) \in X},$   
     $\max\{x\}_{(-, x, \bullet) \in X, \cup_{(-, x, y, -) \in X} \{x, y\}}$  where  $X$  is the set of messages received in  
    line 50;  
52     let  $(x, y, z) = (obsS, getSeq(), maxSeq)$ ;  
53     if  $\neg(x+1=y=z \vee x=y=z \vee x=y=z-1)$  then  
54        $obsS \leftarrow \max\{x, y, z\}$   
55     foreach  $k \in \{0, \dots, 2\} \setminus (\{x \bmod 3 : x < y\} \cup \{y \bmod 3\} \cup \{z+31 : |allSeq| = 1\})$   
    do  $CS[k] \leftarrow \perp$ ;  
56     if  $(|allSeq| = 1 \wedge \Delta())$  then  
57        $CS[maxSeq+31].propose(maxSeq+1, allReady)$   
58     if  $obsS+1 = getSeq() \wedge x \neq \perp \wedge x.result() \neq \perp$  where  $x = CS[(obsS+31)]$  then  
59       if  $x.result() \neq \Psi$  then  
60         foreach  $m \in \text{bulkRead}(x.result())$  do  $toDeliver(m)$   
61        $obsS \leftarrow obsS + 1$   
62 upon  $\text{SYNC}(snJ)$  arrival from  $p_j$  do  
     $\text{send SYNCack}(snJ, getSeq(), obsS, maxReady())$  to  $p_j$ ;
```

such as the one by Lundström, Raynal, and Schiller [32], to broadcast the protocol message, $toURB(msg)$. As before, the line numbers of Algorithm 3 continues the ones of Algorithm 2.

The proposed solution assumes that the FIFO-URB module has interface functions that facilitate the aggregation of protocol messages before their delivery. For example, we assume that the interface function $\text{allHaveTerminated}_i()$ returns **True** whenever there are no active URB transmissions sent by $p_i \in \mathcal{P}$. Also, given $p_i \in \mathcal{P}$, the functions $\text{readyMin}_i()$ and $\text{readyMax}_i()$ return each a vector, $r_i[0, \dots, n-1]$, such that for any $p_j \in \mathcal{P}$, the entry $r_i[j]$ holds the lowest,

and respectively, highest FIFO-delivery sequence number that is ready to be FIFO-delivered. These FIFO-delivery sequence numbers are the unique indices that the senders attach to the URB messages. Also, the function $\text{bulkRead}_i(r_{\max})$ returns immediately after system state c a determinately ordered sequence, sqnc_i , that includes all the messages between r_{\min} and r_{\max} , such that $r_{\min} = \text{readyMin}_i()$ in c , as well as r_{\max} , is a vector that is entry-wise greater or equal to r_{\min} and entry-wise smaller or equal $r = \text{readyMax}_i()$ in c .

Algorithm 3 assumes access to a self-stabilizing perfect failure detector, such as the one by Beauquier and Kekkonen-Moneta [5]. The local set, trusted_i , includes the indices of the nodes that p_i 's failure detector trusts. We follow Assumption 7.1 for the sake of a simple presentation.

Assumption 7.1 *Any sent message arrives or is lost within $\mathcal{O}(1)$ asynchronous cycles. Any URB message arrives within $\mathcal{O}(1)$ asynchronous cycles [32]. Each active multivalued consensus object decides within $\mathcal{O}(1)$ asynchronous cycles [33].*

7.2 Algorithm description

The algorithm idea uses the fact that sqnc_i is deterministically ordered. Namely, if all nodes $p_j \in \mathcal{P}$ share the same sequence r_1, r_2, \dots when calling $\text{bulkRead}_j(r_x) : x \in \mathbb{Z}^+$, the studied task is reduced to invoking the event of $\text{toDeliver}(m)$ for every $m \in \text{bulkRead}(r_x)$. To that end, Algorithm 3 queries all nodes about the messages that are ready to be delivered (lines 47 to 51), validates the consistency of the control variables (line 46 and lines 54 to 55), agree on the current value of r_x (lines 56 to 57), and delivers the ready messages (lines 58 to 61). We discuss in detail each part after describing the local constant, variables, and macros; sn the query number.

7.2.1 Constant, variables, and macros

The constant M defines the number of multivalued consensus objects that Algorithm 3 needs to use. The proof shows that, at any time during a legal execution, Algorithm 3 uses at most two active objects at a time and one more object that is always non-active. The array $CS[0..2]$ holds all the multivalued consensus objects that Algorithm 3 uses. Algorithm 3 uses $CS[]$ cyclically.

Algorithm 3 aims at aggregating URB messages and delivering them only when all transmission activities have terminated. To that end, it uses the $\text{allHaveTerminated}()$ function (Section 7.1). Since the number of such transmissions is unbounded, there is a need to stop aggregating after some predefined number of transmissions that we call δ . The variable obsS points to the highest obsolete sequence number; the one that was already delivered locally. The variable sn stores the number of the next query. As mentioned in Section 2.2, whenever Algorithm 3 runs out of query numbers, a global restart mechanism is invoked, such as the one in [24, Section 5]. Thus, it is possible to have bounded query numbers.

The macro $S()$ returns the set of sequence numbers used by the active multivalued consensus objects. The macro $\text{getSeq}()$ returns the locally maximum sequence number. The macro $\text{test}(s)$ returns True whenever the sequence number s is used by an active or is greater by one than $\text{getSeq}()$. The macro $\Delta()$ facilitates the decision about whether to invoke a new consensus. It returns True if there are non-delivered messages but no on-going transmissions. It also returns True when the number of ready to be delivered messages exceeds δ (regardless of the presence of active URB transmissions).

7.2.2 Querying (lines 47 to 51)

Algorithm 3 uses a simple synchronization query mechanism. Each query instance is associated with a unique sequence number that is stored in the variable sn and incremented in line 47. Line 49 broadcasts the synchronization query repeatedly until a reply is received from every trusted node. The query response (line 62) includes the correspondent's (local) maximum sequence number stored by any multivalued consensus object (that the macro $\text{getSeq}()$ retrieves), the maximum obsolete sequence number (that its respective multivalued consensus object is no longer needed), and the latest value returned from $\text{readyMax}_i()$. Using these responses, line 50 aggregates the query results and store them in minReady , maxSeq , and allSeq . The vector minReady includes the entry-wise minimum (per sender) FIFO-URB messages that are ready to be delivered at all nodes. Also, maxSeq is the maximum known sequence number. And, the set allSeq includes all the collected maximum sequence numbers and obsolete sequence numbers.

7.2.3 Consistency assertion and stale information removal (line 46 and lines 54 to 55)

Line 46 makes sure that $CS[k].seq$, when taken its remainder from the division by M , equals to k . It also tests that the local obsolete sequence number, obsS , is not greater than the largest sequence number. Besides, the gap between the maximum and the minimum sequence number cannot be greater than one. Line 54 verifies that obsS , $\text{getSeq}()$, and maxSeq follow a consistent pattern. Line 55 removes stale information by deactivating any obsolete multivalued consensus object.

7.2.4 Repeated agreement (lines 56 to 57)

The if-statement condition in line 56 tests whether all trusted nodes in the system share the same sequence number. This happens when all trusted nodes $p_j \in \mathcal{P}$ have $\text{obsS}_j = \text{getSeq}_j()$. Line 56 also checks whether $\Delta()$ indicates that it is the time to deliver a batch of messages. If this is the case, then line 57 proposes to agree on the value of allReady .

7.2.5 Message delivery (lines 58 to 61)

The delivery of the next message batch becomes possible the multivalued consensus object has terminated (line 58). Before the actual delivery (line 60), there is a need to check that no error was reported (line 60) due to conditions that appear at line 23 of Algorithm 2. In any case, obsS is incremented (line 61) so that even if an error occurred, the object is ready for recycling.

7.3 Correctness of Algorithm 3

Theorem 7.2 uses Definition 7.1.

Definition 7.1 (Consistent states and legal executions) *Let c be a system state and $p_i \in \mathcal{P}$ be any processor in the system. Suppose that in c , it holds that (i) $\forall k \in \{0, \dots, 2\} : CS_i[k] = \perp \vee CS_i[k].seq \bmod 3 = k$ and either $S = \emptyset \wedge \text{obsS}_i \in \mathbb{Z}^+$ or $S \neq \emptyset \wedge (\text{obsS}_i \leq \max S \wedge \max S - \min S \leq 1)$, where $S = \{CS_i[k].seq : CS_i[k] \neq \perp\}_{k \in \{0, \dots, 2\}}$ and $\text{getSeq}_i()$ returns $seq = \max(\{\text{obsS}_i\} \cup S)$. Moreover, (ii.a) sn_i 's value is greater equal to any sn_J field in the message $\text{SYNC}(sn_J)$ in a communication channel from p_i as well as $\text{SYNCack}(sn_J, \bullet)$ message in a communication channel to p_i . And (ii.b) $\text{obsS}_i \leq \text{getSeq}_i() \leq \text{obsS}_i + 1$. In this case, we say that c is consistent concerning Algorithm 3.*

Suppose that R is an execution of Algorithm 3, such that every $c \in R$ is consistent. In addition, (iii.a) suppose that if `toBroadcast()` is not invoked during R nor do any FIFO-broadcast becomes available for delivery, then pred holds throughout R , where $\text{pred} \equiv \exists z \in \mathbb{Z}^+ : \forall k \in \text{Correct} : \text{getSeq}_k() = z \wedge \text{maxSeq}_k = z \wedge \text{obsS}_k = z \wedge \text{allSeq}_k = \{z\}$. Furthermore, (iii.b) suppose that if `toBroadcast()` is invoked during R infinitely often, then pred holds infinitely often. In this case, we say that R is legal.

Theorem 7.2 *Within $\mathcal{O}(1)$ asynchronous cycles, Algorithm 3's execution is legal.*

Proof of Theorem 7.2 Due to line 46, Definition 7.1's Invariant (i) holds after p_i first complete iteration of Algorithm 3's do-forever loop (lines 45 to 61). Lemma 7.3 shows Invariant (ii.a). Line 54 implies Invariant (ii.b). Lemma 7.5 shows invariant (iii).

Lemma 7.3 *Invariant (ii.a) holds.*

Proof of Lemma 7.2 Only line 47 modifies sn_i 's value, *i.e.*, by increasing the value of sn_i . The rest of the proof is implied by Assumption 7.1, which says that all messages that appear in the communication channels in R 's starting system state are either delivered or lost within $\mathcal{O}(1)$ asynchronous cycles. $\square_{\text{Lemma 7.3}}$

We observe from the code of Algorithm 2 that once invariants (i) and (ii) hold, they are not violated. Thus, the rest of the proof assumes that invariants (i) and (ii) hold in every system state of R . Lemma 7.4 is needed for the proof of Lemma 7.5.

Lemma 7.4 *Every complete iteration of the do-forever loop (lines 45 to 61) allows the collection of $M_{sn_i} = \{(sn_i, s_k, o_k, r_k)\}_{k \in \text{trusted}_i}$, such that $s_k = \text{seq}_k, o_k = \text{obsS}_k$, and $r_k = \text{readyMax}_k()$ in the system state c_k , where $c_i^{\text{line } \ell} \in R : \ell \in \{47, 50\}$ is the system state when p_i executed line ℓ with sn_i and c_k appears between $c_i^{\text{line } 47}$ and $c_i^{\text{line } 50}$ when p_k executed line 62 on the arrival of `SYNC($sn_j = sn_i$)`. Moreover, minReady_i (line 50) is entry-wise smaller equal to every $\text{readyMax}_k()$ in $c_i^{\text{line } 50}$, maxSeq_i is greater equal than every seq_k in $c_i^{\text{line } 47}$, and allSeq_i includes the union $\cup_{k \in \text{trusted}_i} aS_k$, where $aS_k = \{\text{obsS}_k, \text{seq}_k\}$ in c_k .*

Proof of Lemma 7.2 Since invariants (ii.a) holds, the increment of sn_i (line 47) creates a sequence number that is (associated with p_i and) greater than all other associated sequence numbers in the system. With this unique sequence number, the repeat-until loop (lines 49 to 50) gets a fresh collection of $M_{sn_i} = \{(sn_i, s_k, o_k, r_k)\}_{k \in \text{trusted}_i}$. Note that this loop cannot block due to the end-condition (line 50), which considers only the trusted nodes in the system. The rest of the proof is implied directly by lines 47, 50, and 62. $\square_{\text{Lemma 7.4}}$

Lemma 7.5 *Within $\mathcal{O}(1)$ asynchronous cycles, $R = R' \circ R''$ reaches a suffix, R'' , in which invariants (iii.a) and (iii.b) hold.*

Proof of Lemma 7.2 Argument (1) Invariant (iii.a) holds. By the assumption that no FIFO-broadcast becomes ready during R , it holds that the if-statement condition in line 56 does not hold during R . By Assumption 7.1, all active multivalued consensus objects have terminated with $\mathcal{O}(1)$ asynchronous cycles. Therefore, within $\mathcal{O}(1)$ asynchronous cycles, the if-statement condition in line 60 cannot hold. Due to Lemma 7.4, maxSeq_i is greater equal to $\text{getSeq}_k() : k \in \text{Correct}_i$. Due to the if-statement line 53 and line 55, within $\mathcal{O}(1)$ asynchronous cycles, line 55 deactivates any multivalued consensus object, $O_{i:p_i \in \mathcal{P}, x \in \{0, \dots, 2\}} = CS_i[x]$ for which $O_{i,x}.seq < \text{maxSeq}_i - 1$. By using Assumption 7.1 again, any re-activated multivalued

Algorithm 4: Self-stabilizing emulation of a replicated state-machine; code for $p_i \in \mathcal{P}$

Same code as in lines 38 to 44.

```
52 do forever begin
    Same code as in lines 46 to 55.
62 if ( $|allSeq| = 1 \wedge \Delta_i()$ ) then
63    $CS[obsS_i + 3 \ 1].propose(maxSeq + 1, (state = getState(), msg = maxReady()))$ 
64 if  $obsS_i + 1 = getSeq_i() \wedge x \neq \perp \wedge x.result() \neq \perp$  where  $x = CS[(obsS_i + 3 \ 1)]$  then
65   if  $x.result() \neq \Psi$  then
66      $setState(x.result().state);$            foreach  $m \in bulkRead(x.result().msg)$  do
         $toDeliver(m)$                        Same code as in lines 61 to 62.
```

consensus object has to terminate with $\mathcal{O}(1)$ asynchronous cycles. Thus, the above implies that the state of all multivalued consensus objects, active or not, do not change and that $maxSeq_i = getSeq_k() : k \in Correct_i$.

We show that $obsS_i = getSeq_i()$ holds within $\mathcal{O}(1)$ asynchronous cycles. By Invariant (ii.b), we know that either $obsS_i + 1 = getSeq_i()$ or $obsS_i = getSeq_i()$. Suppose that $obsS_i + 1 = getSeq_i()$ holds. Due to the definition of $getSeq_i()$ as well as lines 46 and 55, $x_i \neq \perp$, where $x_i = CS_i[(obsS_i + 3 \ 1)]$ (line 58). By Assumption 7.1, within $\mathcal{O}(1)$ asynchronous cycles, the multivalued consensus object x_i terminates. Thus, the if-statement condition in line 58 holds and line 61 increments $obsS_i$ once. Therefore, $obsS_i = getSeq_i()$ within $\mathcal{O}(1)$ asynchronous cycles.

Since $maxSeq_i = getSeq_k() = obsS_k : k \in Correct_i$, then $allSeq_k = \{z\}$, where $z = maxSeq_i = getSeq_k() = obsS_k : k \in Correct_i$. Thus, *pred* holds.

Argument (2) *Invariant (iii.b) holds.* We note that $\Delta_i()$ holds infinitely often by the assumption that $toBroadcast()$ is invoked during R infinitely often and the URB-termination property. We show that the if-statement condition in line 56 holds within $\mathcal{O}(1)$ asynchronous cycles once $\Delta_i()$ holds. Suppose, towards a contradiction, that $|allSeq| = 1$ does not hold for a period longer than $\mathcal{O}(1)$ asynchronous cycles. Then, the then-statement in line 57 is not executed for a period longer than $\mathcal{O}(1)$ asynchronous cycles. By the proof of Argument (1), *pred* holds within $\mathcal{O}(1)$ asynchronous cycles. Thus, the if-statement condition in line 56 holds within $\mathcal{O}(1)$ asynchronous cycles. In other words, Invariant (iii.b) holds. $\square_{Lemma\ 7.5}$

$\square_{Theorem\ 7.2}$

8 Discussion

We showed how a non-self-stabilizing algorithm for multivalued consensus by Mostéfaoui, Raynal, and Tronel [36] can become one that recovers from transient-faults. Interestingly, our solution is both wait-free and incurs a bounded number of binary consensus invocations whereas earlier work either uses an unbounded number of binary consensus objects [36] or is blocking [46]. Therefore, we present a more attractive transformation technique than the studied algorithm (regardless of the presence or absence of transient-faults).

As an application, we showed a self-stabilizing total-order message delivery. As an enhancement to this application, Algorithm 4 explains how to construct a self-stabilizing emulator for state-machine replication. Line 63 of Algorithm 4 proposes to agree on both on the automaton state, which is retrieved by $getState()$, and the bulk of FIFO-URB messages, as in line 57 of

Algorithm 3. Line 66 of Algorithm 4 uses `setState()` for updating the automaton state using the agreed state.

References

- [1] Yehuda Afek, Eli Gafni, Sergio Rajsbaum, Michel Raynal, and Corentin Travers. The k -simultaneous consensus problem. *Distributed Comput.*, 22(3):185–195, 2010.
- [2] Noga Alon, Hagit Attiya, Shlomi Dolev, Swan Dubois, Maria Potop-Butucaru, and Sébastien Tixeuil. Practically stabilizing SWMR atomic memory in message-passing systems. *J. Comput. Syst. Sci.*, 81(4):692–701, 2015.
- [3] Karine Altisen, Stéphane Devismes, Swan Dubois, and Franck Petit. *Introduction to Distributed Self-Stabilizing Algorithms*. Synthesis Lectures on Distributed Computing Theory. Morgan & Claypool Publishers, 2019.
- [4] Arta Babae and Moez Draief. Distributed multivalued consensus. *Comput. J.*, 57(8):1132–1140, 2014.
- [5] Joffroy Beauquier and Synnöve Kekkonen-Moneta. Fault-tolerance and self-stabilization: impossibility results and solutions using self-stabilizing failure detectors. *Int. J. Systems Science*, 28(11):1177–1187, 1997.
- [6] Kenneth P. Birman and Thomas A. Joseph. Reliable communication in the presence of failures. *ACM Trans. Comput. Syst.*, 5(1):47–76, 1987.
- [7] Peva Blanchard, Shlomi Dolev, Joffroy Beauquier, and Sylvie Delaët. Practically self-stabilizing Paxos replicated state-machine. In *NETYS*, volume 8593 of *LNCS*, pages 99–121. Springer, 2014.
- [8] Marco Canini, Iosif Salem, Liron Schiff, Elad Michael Schiller, and Stefan Schmid. A self-organizing distributed and in-band SDN control plane. In Kisung Lee and Ling Liu, editors, *37th IEEE International Conference on Distributed Computing Systems, ICDCS 2017, Atlanta, GA, USA, June 5-8, 2017*, pages 2656–2657. IEEE Computer Society, 2017.
- [9] Marco Canini, Iosif Salem, Liron Schiff, Elad Michael Schiller, and Stefan Schmid. Renaissance: A self-stabilizing distributed SDN control plane. In *38th IEEE International Conference on Distributed Computing Systems, ICDCS 2018, Vienna, Austria, July 2-6, 2018*, pages 233–243. IEEE Computer Society, 2018.
- [10] Tushar Deepak Chandra and Sam Toueg. Unreliable failure detectors for reliable distributed systems. *J. ACM*, 43(2):225–267, 1996.
- [11] Miguel Correia, Nuno Ferreira Neves, and Paulo Veríssimo. From consensus to atomic broadcast: Time-free Byzantine-resistant protocols without signatures. *Comput. J.*, 49(1):82–96, 2006.
- [12] Tyler Crain, Vincent Gramoli, Mikel Larrea, and Michel Raynal. DBFT: efficient leaderless Byzantine consensus and its application to blockchains. In *17th IEEE International Symposium on Network Computing and Applications, NCA*, pages 1–8, 2018.

- [13] Edsger W. Dijkstra. Self-stabilizing systems in spite of distributed control. *Commun. ACM*, 17(11):643–644, 1974.
- [14] Shlomi Dolev. *Self-Stabilization*. MIT Press, 2000.
- [15] Shlomi Dolev, Chryssis Georgiou, Ioannis Marcoullis, and Elad Michael Schiller. Practically-self-stabilizing virtual synchrony. *J. Comput. Syst. Sci.*, 96:50–73, 2018.
- [16] Shlomi Dolev, Seth Gilbert, Nancy A. Lynch, Elad Schiller, Alexander A. Shvartsman, and Jennifer L. Welch. Virtual mobile nodes for mobile ad hoc networks. In Rachid Guerraoui, editor, *Distributed Computing, 18th International Conference, DISC 2004, Amsterdam, The Netherlands, October 4-7, 2004, Proceedings*, volume 3274 of *Lecture Notes in Computer Science*, pages 230–244. Springer, 2004.
- [17] Shlomi Dolev, Seth Gilbert, Elad Schiller, Alexander A. Shvartsman, and Jennifer L. Welch. Autonomous virtual mobile nodes. In Suman Banerjee and Samrat Ganguly, editors, *Proceedings of the DIALM-POMC Joint Workshop on Foundations of Mobile Computing, Cologne, Germany, September 2, 2005*, pages 62–69. ACM, 2005.
- [18] Shlomi Dolev, Ronen I. Kat, and Elad Michael Schiller. When consensus meets self-stabilization. *J. Comput. Syst. Sci.*, 76(8):884–900, 2010.
- [19] Shlomi Dolev and Elad Schiller. Communication adaptive self-stabilizing group membership service. *IEEE Trans. Parallel Distributed Syst.*, 14(7):709–720, 2003.
- [20] Shlomi Dolev and Elad Schiller. Self-stabilizing group communication in directed networks. *Acta Informatica*, 40(9):609–636, 2004.
- [21] Shlomi Dolev, Elad Schiller, and Jennifer L. Welch. Random walk for self-stabilizing group communication in ad hoc networks. *IEEE Trans. Mob. Comput.*, 5(7):893–905, 2006.
- [22] Paul D. Ezhilchelvan, Achour Mostéfaoui, and Michel Raynal. Randomized multivalued consensus. In *Object-Oriented Real-Time Distributed Computing (ISORC 2001)*, pages 195–200, 2001.
- [23] Michael J. Fischer, Nancy A. Lynch, and Mike Paterson. Impossibility of distributed consensus with one faulty process. *J. ACM*, 32(2):374–382, 1985.
- [24] Chryssis Georgiou, Oskar Lundström, and Elad Michael Schiller. Self-stabilizing snapshot objects for asynchronous failure-prone networked systems. In *Networked Systems, NETYS*, pages 113–130, 2019.
- [25] Rachid Guerraoui and Michel Raynal. The information structure of indulgent consensus. *IEEE Trans. Computers*, 53(4):453–466, 2004.
- [26] Vassos Hadzilacos and Sam Toueg. A modular approach to fault-tolerant broadcasts and related problems. Technical report, Cornell Univ., Ithaca, NY, 1994.
- [27] Jaap-Henk Hoepman, Andreas Larsson, Elad Michael Schiller, and Philippas Tsigas. Secure and self-stabilizing clock synchronization in sensor networks. *Theor. Comput. Sci.*, 412(40):5631–5647, 2011.
- [28] Leslie Lamport. The part-time parliament. *ACM Trans. Comput. Syst.*, 16(2):133–169, 1998.

- [29] Pierre Leone and Elad Schiller. Self-stabilizing TDMA algorithms for dynamic wireless ad hoc networks. *Int. J. Distributed Sens. Networks*, 9, 2013.
- [30] Pierre Leone and Elad Michael Schiller. Interacting urns processes for clustering of large-scale networks of tiny artifacts. *Int. J. Distributed Sens. Networks*, 6(1), 2010.
- [31] Guanfeng Liang and Nitin H. Vaidya. Error-free multi-valued consensus with Byzantine failures. In *ACM Principles of Distributed Computing, PODC*, pages 11–20, 2011.
- [32] Oskar Lundström, Michel Raynal, and Elad M. Schiller. Self-stabilizing uniform reliable broadcast. In *Networked Systems and CoRR abs/2001.03244*, 2020.
- [33] Oskar Lundström, Michel Raynal, and Elad Michael Schiller. Self-stabilizing indulgent zero-degrading binary consensus. In *22nd Distributed Computing and Networking ICDCN*, pages 1–1, 2021.
- [34] Achour Mostéfaoui and Michel Raynal. Signature-free asynchronous Byzantine systems: From multivalued to binary consensus with $t < n/3$, $o(n^2)$ messages, and constant time. In *Structural Information and Communication Complexity, SIROCCO*, pages 194–208, 2015.
- [35] Achour Mostéfaoui and Michel Raynal. Signature-free asynchronous Byzantine systems: from multivalued to binary consensus with $t < n/3$, $o(n^2)$ messages, and constant time. *Acta Informatica*, 54(5):501–520, 2017.
- [36] Achour Mostéfaoui, Michel Raynal, and Frederic Tronel. From binary consensus to multivalued consensus in asynchronous message-passing systems. *Inf. Process. Lett.*, 73(5-6):207–212, 2000.
- [37] Mohamed Mustafa, Marina Papatriantafidou, Elad Michael Schiller, Amir Tohidi, and Philippos Tsigas. Autonomous TDMA alignment for vanets. In *Proceedings of the 76th IEEE Vehicular Technology Conference, VTC Fall 2012, Quebec City, QC, Canada, September 3-6, 2012*, pages 1–5. IEEE, 2012.
- [38] Thomas Petig, Elad Schiller, and Philippos Tsigas. Self-stabilizing TDMA algorithms for wireless ad-hoc networks without external reference. In *13th Annual Mediterranean Ad Hoc Networking Workshop, MED-HOC-NET 2014, Piran, Slovenia, June 2-4, 2014*, pages 87–94. IEEE, 2014.
- [39] Thomas Petig, Elad Michael Schiller, and Philippos Tsigas. Self-stabilizing TDMA algorithms for wireless ad-hoc networks without external reference. In Teruo Higashino, Yoshiaki Katayama, Toshimitsu Masuzawa, Maria Potop-Butucaru, and Masafumi Yamashita, editors, *Stabilization, Safety, and Security of Distributed Systems - 15th International Symposium, SSS 2013, Osaka, Japan, November 13-16, 2013. Proceedings*, volume 8255 of *Lecture Notes in Computer Science*, pages 354–356. Springer, 2013.
- [40] Oscar Morales Ponce, Elad Michael Schiller, and Paolo Falcone. How to stop disagreeing and start cooperating in the presence of asymmetric packet loss. *Sensors*, 18(4):1287, 2018.
- [41] Michel Raynal. *Fault-Tolerant Message-Passing Distributed Systems - An Algorithmic Approach*. Springer, 2018.

- [42] Iosif Salem and Elad Michael Schiller. Practically-self-stabilizing vector clocks in the absence of execution fairness. In Andreas Podelski and François Taïani, editors, *Networked Systems - 6th International Conference, NETYS 2018, Essaouira, Morocco, May 9-11, 2018, Revised Selected Papers*, volume 11028 of *Lecture Notes in Computer Science*, pages 318–333. Springer, 2018.
- [43] Lewis Tseng. Recent results on fault-tolerant consensus in message-passing networks. In *Structural Information and Communication Complexity, SIROCCO*, pages 92–108, 2016.
- [44] Robbert van Renesse and Deniz Altinbuken. Paxos made moderately complex. *ACM Comput. Surv.*, 47(3):42:1–42:36, 2015.
- [45] Axel Wegener, Elad Michael Schiller, Horst Hellbrück, Sándor P. Fekete, and Stefan Fischer. Hovering data clouds: A decentralized and self-organizing information system. In Hermann de Meer and James P. G. Sterbenz, editors, *Self-Organizing Systems, First International Workshop, IWSOS 2006, and Third International Workshop on New Trends in Network Architectures and Services, EuroNGI 2006, Passau, Germany, September 18-20, 2006, Proceedings*, volume 4124 of *Lecture Notes in Computer Science*, pages 243–247. Springer, 2006.
- [46] Jialin Zhang and Wei Chen. Bounded cost algorithms for multivalued consensus using binary consensus instances. *Inf. Process. Lett.*, 109(17):1005–1009, 2009.