

Flavours of Sequential Information Flow

Ezio Bartocci   

Technische Universität Wien, Vienna, Austria

Thomas Ferrère  



Imagination Technologies, Kings Langley, UK

Thomas A. Henzinger   

IST Austria, Klosterneuburg, Austria

Dejan Nickovic  

AIT Austrian Institute of Technology, Vienna, Austria

Ana Oliveira da Costa  

Technische Universität Wien, Vienna, Austria

Abstract

Information-flow policies prescribe which information is available to a given user or subsystem. We study the problem of specifying such properties in reactive systems, which may require dynamic changes in information-flow restrictions between their states. We formalize several flavours of *sequential information-flow*, which cover different assumptions about the semantic relation between multiple observations of a system. Information-flow specification falls into the category of *hyperproperties*. We define different variants of sequential information-flow specification using a first-order logic with both trace quantifiers and temporal quantifiers called Hypertrace Logic. We prove that HyperLTL, equivalent to a subset of Hypertrace Logic with restricted quantifier prefixes, cannot specify the majority of the studied two-state independence variants. For our results, we introduce a notion of equivalence between sets of traces that cannot be distinguished by certain classes of formulas in Hypertrace Logic. This presents a new approach to proving inexpressiveness results for logics such as HyperLTL.

2012 ACM Subject Classification Security and privacy → Logic and verification

Keywords and phrases Hyperproperties, Sequential Information-flow, Expressiveness

Digital Object Identifier 10.4230/LIPIcs..2021.

Funding *Ana Oliveira da Costa*: This work was supported by the Austrian FWF project W1255-N23

1 Introduction

Information-flow policies specify restrictions on what information can be shared within components of a system or its users. Information that must be kept secret may be deduced by combining multiple observations of the non-secret behavior of the system. For this reason, properties that characterize information-flow policies are often not properties of a single trace, but rather properties of sets of traces, that is, *hyperproperties* [5].

A basic concept for specifying information flows can be found in the notion of *independence* [12, 5], defined as a binary relation between observable variables of a system. We say that y is independent of x , denoted by $ind(x, y)$, to specify that no information can flow from x to y . Over a given set of traces, the independence relation $ind(x, y)$ is captured by the formula $\forall \pi \forall \pi' \exists \pi'' x_\pi = x_{\pi''} \wedge y_{\pi'} = y_{\pi''}$, where π denotes an observation of the system and x_π the value x observed in π . We introduce *two-state independence*, a simple, yet fundamental sequential information-flow requirement. It can be used for instance to capture *declassification* [18], a process in which previously secret information is allowed to be released. Given x, y, z and *state* variables, the two-state independence is stated as follows: “The value



© E. Bartocci and T. Ferrère and T. A. Henzinger and D. Nickovic and A. Oliveira da Costa; licensed under Creative Commons License CC-BY 4.0

Leibniz International Proceedings in Informatics

LIPICs Schloss Dagstuhl – Leibniz-Zentrum für Informatik, Dagstuhl Publishing, Germany

■ **Algorithm 1** Program \mathcal{P} for two-state independence.

```

1  state := 0;
2  do
3    if (state = 0) then
4      | input(c1, state in {0, 1});
5    end
6    input(c0, x in {0, 1});
7    if (state = 0) then
8      | z := x; y = default;
9    else
10   | y := x; z = default;
11  end
12  output(c2, y);
13  output(c3, z);
14 while True;

```

■ **Table 1** A set of traces T observed from the inputs and outputs of \mathcal{P} , with *default* = 0, where white cells denote that *state* = 0 and gray cells denote that *state* = 1.

	Time											
	0			1			2			3		
	x	y	z	x	y	z	x	y	z	x	y	z
τ_1	0	0	0	1	1	0	1	1	0	1	1	0
τ_2	1	0	1	1	1	0	1	1	0	1	1	0
τ_3	1	0	1	1	0	1	0	0	0	0	0	0
τ_4	0	0	0	1	0	1	0	0	0	1	1	0

of y is independent from the value of x until *state* changes, and from then on the value of z is independent from the value of x .”

The program \mathcal{P} , shown in Algorithm 1, intuitively satisfies a two-state independence property between x , y and z . The program starts in the initial state (*state* = 0) and in every subsequent step, the next state is non-deterministically assigned via the channel c_1 . Once \mathcal{P} changes from *state* = 0 to *state* = 1, it remains in that state forever. The value of x is non-deterministically assigned via channel c_0 regardless of the current state. When in state 0, \mathcal{P} assigns x to z and a default value to y . When in state 1, \mathcal{P} assigns y to z and a default value to z . Note that the default value can be 0, 1 or a non-deterministic boolean value set at the start of the program execution. The program finally exposes y and z via channels c_2 and c_3 , respectively. Program \mathcal{P} satisfies the two-state independence requirement by ensuring that $ind(x, y)$ holds in the first state, and that $ind(x, z)$ holds in the second state. Table 1 shows a set of traces observed from the input/output interface of \mathcal{P} and that are consistent with the two-state independence requirement. The first two traces, τ_1 and τ_2 , transition to the second state at time 1, while τ_3 and τ_4 transition at time 2 and 3, respectively. Then, for the second state of the specification (i.e. after *state* = 1), we need to compare the observations at time 1 of τ_1 and τ_2 with observations at time 2 and 3 of τ_3 and τ_4 , respectively.

Table 1 illustrates one possible way to observe the program \mathcal{P} . However, the observation of program executions may not be uniquely defined. For example, an observer may have the ability to access the internal program memory, while another observer may only observe its input/output interface. The power of observer has a significant impact on the specification of information flow requirements.

In this paper, we study multiple flavours of sequential information flow, according to our assumptions about the observer. We focus on the two-state independence requirement as the simplest hyperproperty that exposes the main features of sequential information flow.

Logical specification of sequential information flow (and other hyperproperties) requires (implicit or explicit) quantification over time and traces. We refer to this family of linear-time specification languages as *hyperlogics*. We introduce Hypertrace Logic, a two-sorted first-order logic that allows us to express and compare a rich variety of sequential hyperproperties and specification languages for hyperproperties.

We identify two natural interpretations of two-state independence, based on *point* and *segment* semantics. In point semantics, an observation at a given execution point is inde-

pendent from observations at all other execution points. Segment semantics relates entire segments of observations, where each segment is aligned with a specification state. We also identify three types of state transition actions, *synchronous*, *asynchronous* and *hidden*. For example, the set of traces T shown in Table 1 has an asynchronous action and satisfies a two-state independence under the segments semantics, with $ind(x, y)$ and $ind(x, z)$ interpreted over segments of traces associated to states 0 and 1 respectively. Every combination of independence interpretation and action type defines a different assumption about program observations. We provide a mathematical definition using Hypertrace Logic of the two-state independence for each such combination.

We then study the expressiveness of all the presented two-state independence flavours with respect to HyperLTL, the de-facto standard for specifying, analysing and model-checking hyperproperties. We show that HyperLTL cannot express the majority of the studied two-state independence variants. Our results emphasize the important role that the order of time and trace quantifiers play in hyperproperties and in addition highlight the need to explore, also noted independently in [3, 1], more asynchronous variants of hyperlogics.

The contributions of this paper can be summarized as follows:

- We investigate multiple flavours of sequential information flow through a generic first-order formalism, which relieves us of the burden of specific syntactic choices.
- We present a comprehensive expressiveness study of the simplest sequential information-flow property—namely, two-state independence—with respect to first-order fragments and the popular HyperLTL formalism.
- We devise a new systematic technique to prove that logics such as HyperLTL cannot express a given property. This proof strategy is of independent interest and can be used in other expressiveness proofs.

2 First Order Logic for Trace Sets

We define a two-sorted first-order logic to formalize the hyperproperties we are interested in. We extend the first-order logic of linear order with equality, FO[<] [13], with a trace sort \mathbb{T} . As we are interested in discrete linear-time, we interpret FO[<] with the theory of natural numbers. Under this theory, FO[<] is expressively equivalent to LTL [13, 11].

Let X be a finite set of propositional variables. We denote by $v(x)$ a *valuation* (partial mapping) of variables $x \in X$ to boolean values, $v : X \rightarrow \{0, 1\}$, and by \mathbb{V}_X the set of all valuations over X . The *domain* of a valuation v is denoted as $X(v)$ and its *size* is defined by the size of its domain, i.e. $|v| = |X(v)|$. Given a sequence of propositional variables (x_0, \dots, x_n) , we write a valuation v over it as a boolean string $v(x_0) \dots v(x_n)$. We denote by $v[x \mapsto b]$ the update of valuation v with x being assigned the boolean b . The *composition of two valuations* v and v' is defined as $v \otimes v' = v[x_1 \mapsto v'(x_1)] \dots [x_n \mapsto v'(x_n)]$, where $\{x_1, \dots, x_n\} = X(v')$.

A trace τ over X is a sequence of valuations in \mathbb{V}_X . We refer to X as the *alphabet* of τ . The set of all *infinite traces* (over X) is denoted by \mathbb{V}_X^ω and the set of all *finite traces* is denoted by \mathbb{V}_X^* . For a finite trace $\tau = v_0 v_1 \dots v_n$, its *length* is defined as $|\tau| = n + 1$ and $|\tau| = \omega$ for an infinite trace. The *composition of traces* $\tau = v_0 v_1 \dots$ and $\tau' = v'_0 v'_1 \dots$ is defined as $\tau \otimes \tau' = (v_0 \otimes v'_0)(v_1 \otimes v'_1) \dots$. Given a trace $\tau = v_0 v_1 \dots$ and an index $i < |\tau|$, we use the following indexing notation: $\tau[i] = v_i$, $\tau[i \dots] = v_i v_{i+1} \dots$, and $\tau[\dots i] = v_0 v_1 \dots v_{i-1}$. For $j \geq |\tau|$ we adopt the following convention: $\tau[j \dots]$ is the empty trace and $\tau[\dots j] = \tau$.

A *trace property* T over a set of propositional variables X is a set of infinite traces over X , that is, $T \subseteq \mathbb{V}_X^\omega$. The set $\mathbb{T} = 2^{\mathbb{V}_X^\omega}$ defines the *set of all trace properties*. A system S is

XX:4 Flavours of Sequential Information Flow

characterized by the observable behavior for each of its executions, which are represented as traces. Hence a system is defined by a set of traces. A *hyperproperty* characterizes a set of systems, and defines a set of sets of traces $\mathbf{T} \subseteq 2^{\mathbb{V}_X^\omega} = \mathbb{T}$.

LTL is a propositional linear-time temporal logic [17]. Its formulas, φ , are defined by the grammar: $\varphi ::= a \mid \neg\varphi \mid \varphi \vee \varphi \mid \mathbf{X}\varphi \mid \varphi \mathbf{U}\varphi$, where $a \in X$ is a propositional variable and *next*, \mathbf{X} , and *until*, \mathbf{U} , are temporal modalities. LTL formulas are interpreted over infinite traces. The satisfaction relation, for a given trace $\tau \in \mathbb{V}_X^\omega$, is defined inductively over LTL formulas as follows:

$$\begin{aligned} \tau \models a &\text{ iff } \tau[0](a) = 1; \tau \models \neg\psi &\text{ iff } \tau \not\models \psi; \tau \models \psi_1 \vee \psi_2 &\text{ iff } \tau \models \psi_1 \text{ or } \tau \models \psi_2; \tau \models \mathbf{X}\psi &\text{ iff } \tau[1\dots] \models \psi; \\ \tau \models \psi_1 \mathbf{U}\psi_2 &\text{ iff there exists } 0 \leq j : \tau[j\dots] \models \psi_2 &\text{ and for all } 0 \leq j' < j : \tau[j'\dots] \models \psi_1. \end{aligned}$$

The temporal operators *globally*, \mathbf{G} , and *eventually*, \mathbf{F} are defined as customary, with $\mathbf{G}\psi \equiv \psi \mathbf{U}\text{false}$ and $\mathbf{F}\psi \equiv \text{true} \mathbf{U}\psi$.

2.1 Hypertrace Logic

Hypertrace Logic, denoted $\text{FO}[\langle, \mathbb{T}]$, is a two-sorted first-order logic with equality and the signature $\{\langle\} \cup \{P_a \mid a \in X\} \cup \{def\}$, where X is a set of propositional variables. It includes the trace sort \mathbb{T} and time sort \mathbb{N} . All the predicates are binary and they have the following signatures: $\langle : \mathbb{N} \times \mathbb{N}$ and $P_a, def : \mathbb{T} \times \mathbb{N}$, for all $a \in X$. The predicate \langle is interpreted over the theory of natural numbers, while the other predicates are uninterpreted.

The first-order logic of linear order, $\text{FO}[\langle]$, allows only monadic predicates, aside from the interpreted binary predicate \langle . We extend it to specify hyperproperties by allowing binary predicates P_a for each propositional variable a and a binary predicate def . Given a set of traces, we interpret P_a with all pairs of traces and time positions where a holds. The predicate def holds for all positions that are within the length of a given trace. This enables us to reason about both finite and infinite traces.

Given a set of traces T , we define the structure \overline{T} with domain $T \cup \mathbb{N}$ by letting, for all $a \in X$, $P_a = \{(\tau, k) \mid \tau \in T, k \in \mathbb{N} \text{ and } \tau[k](a) = 1\}$ and $def = \{(\tau, k) \mid \tau \in T, k \in \mathbb{N} \text{ and } 0 \leq k < |\tau|\}$. A set of traces T is a model of a formula $\varphi \in \text{FO}[\langle, \mathbb{T}]$, denoted $T \models_{\mathbb{T}} \varphi$, when \overline{T} models φ under the classical first-order semantics. From now on, we refer to P_a as a and omit the subscript \mathbb{T} in $\models_{\mathbb{T}}$ whenever it is clear from the context. The *set of sets of traces generated by a hypertrace formula* φ is $\llbracket \varphi \rrbracket = \{T \mid T \models_{\mathbb{T}} \varphi\}$. We also equip Hypertrace Logic with a *point interpretation* defined as $\llbracket \varphi \rrbracket_{point} = \{T[0]T[1]\dots \mid T \models_{\mathbb{T}} \varphi\}$, where $T[i] = \{\tau[i] \mid \tau \in T\}$.

► **Example 1.** Consider the set of traces $T = \{00(11)^\omega, 10(00)^\omega\}$ with valuations over (x, y) . Its point interpretation is $\{00, 10\}(\{11, 00\})^\omega$.

2.2 Trace-prefixed Hypertrace Logic

Trace-prefixed Hypertrace Logic, $\mathbf{T}\text{-FO}[\langle, \mathbb{T}]$, is a fragment of Hypertrace Logic in which all trace quantifiers are at the beginning of the formula. Its formulas, $\varphi \in \mathbf{T}\text{-FO}[\langle, \mathbb{T}]$, are defined by the following grammar: $\varphi ::= \forall\pi \varphi \mid \neg\varphi \mid \psi$ with $\psi ::= \forall i \psi \mid \psi \vee \psi \mid \neg\psi \mid i < i \mid i = i \mid a(\pi, i)$, where $\pi \in \mathcal{V}$ is a trace variable, i is a time variable and $a \in X$ a propositional variable.

$\mathbf{T}\text{-FO}[\langle, \mathbb{T}]$ is expressively equivalent to HyperLTL [4] interpreted over sets of infinite traces. HyperLTL extends LTL by adding quantifiers over traces. Its syntax is defined by the following grammar, where \mathcal{V} is a set of trace variables, $a \in X$ and $\pi \in \mathcal{V}$: $\psi ::= \exists\pi \psi \mid \forall\pi \psi \mid \varphi$ with $\varphi ::= a_\pi \mid \neg\varphi \mid \varphi \vee \varphi \mid \mathbf{X}\varphi \mid \varphi \mathbf{U}\varphi$. A trace assignment, $\Pi_T : \mathcal{V} \rightarrow T$, is a partial function that assigns traces from T to trace variables in \mathcal{V} . We denote by $\Pi_T[\pi \mapsto \tau]$ the

trace assignment in which π is mapped to τ and otherwise identical to Π_T . The satisfaction relation for HyperLTL formulas is defined inductively as follows:

- $(\Pi_T, i) \models_H \exists \pi \psi$ iff there exists $\tau \in T : (\Pi_T[\pi \mapsto \tau], i) \models_H \psi$;
- $(\Pi_T, i) \models_H \forall \pi \psi$ iff for all $\tau \in T : (\Pi_T[\pi \mapsto \tau], i) \models_H \psi$;
- $(\Pi_T, i) \models_H a_\pi$ iff $\Pi_T(\pi)[i](a) = 1$;
- $(\Pi_T, i) \models_H \neg \psi$ iff $(\Pi_T, i) \not\models_H \psi$;
- $(\Pi_T, i) \models_H \psi_1 \vee \psi_2$ iff $(\Pi_T, i) \models_H \psi_1$ or $(\Pi_T, i) \models_H \psi_2$;
- $(\Pi_T, i) \models_H \mathbf{X} \psi$ iff $(\Pi_T, i+1) \models_H \psi$;
- $(\Pi_T, i) \models_H \psi_1 \mathbf{U} \psi_2$ iff there exists $i \leq j : (\Pi_T, j) \models_H \psi_2$ and for all $i \leq j' < j : (\Pi_T, j') \models_H \psi_1$.

A set of traces T is a *model* of a HyperLTL formula φ , denoted by $T \models_H \varphi$, iff there exists a mapping Π_T s.t. $(\Pi_T, 0) \models_H \varphi$. A formula is closed when all occurrences of trace variables are in the scope of a quantifier. For all closed formulas (sentences) φ , $T \models_H \varphi$ iff $(\Pi_T^\emptyset, 0) \models_H \varphi$, where Π_T^\emptyset is the empty assignment. We may omit the subscript H in \models_H whenever it is clear from the context.

► **Definition 2.** Let T be a set of traces and $\Pi_T : \mathcal{V} \rightarrow T$ be a partial function assigning traces in T to variables in \mathcal{V} . We introduce the following notions:

- The set of trace variables assigned in Π_T is $\mathcal{V}(\Pi_T) = \{\pi \mid \Pi_T(\pi) \text{ is defined}\}$;
- This size of Π_T is $|\Pi_T| = |\mathcal{V}(\Pi_T)|$;
- The flattening of Π_T is $\langle \Pi_T \rangle[i](a_\pi) = \Pi_T(\pi)[i](a)$.

Note that a quantifier-free HyperLTL formula φ with trace variables in \mathcal{V} and alphabet X is also an LTL formula over the alphabet $\{a_\pi \mid a \in X, \pi \in \mathcal{V}\}$.

► **Example 3.** Let $T = \{0^\omega, 1^\omega\}$ be a set of traces over $\{a\}$. Consider, the assignment Π_T s.t. $\Pi_T(\pi) = 0^\omega$ and $\Pi_T(\pi') = 1^\omega$. Then, $\langle \Pi_T \rangle$ defines the trace $(01)^\omega$ over $(a_\pi, a_{\pi'})$.

► **Proposition 4.** Let φ be a quantifier-free HyperLTL formula. For all $i \in \mathbb{N}$, all set of traces T and all of its trace assignments Π_T , $(\Pi_T, i) \models_H \varphi$ iff $\langle \Pi_T \rangle[i \dots] \models \varphi$.

► **Proposition 5.** For all HyperLTL sentences φ_H there exists a trace-prefixed hypertrace sentence φ s.t. for all sets of infinite traces $T \subseteq \mathbb{V}_X^\omega$, $T \models_H \varphi_H$ iff $T \models_{\mathbb{T}} \varphi$. For all trace-prefixed hypertrace sentences φ there exists a HyperLTL sentence φ_H s.t. for all sets of infinite traces $T \subseteq \mathbb{V}_X^\omega$, $T \models_H \varphi_H$ iff $T \models_{\mathbb{T}} \varphi$.

Proof. The translation from HyperLTL formulas to an equivalent trace-prefixed hypertrace formula works as follows. We keep the trace quantifiers as they are and we use the translation from LTL to FO[<] introduced in [11] to translate the quantifier-free part. Then, we apply the following change in the quantifier-free part: $P_a(\pi, i) = P_{a_\pi}(i)$. Let us call this translation tr_H . It follows from structural induction on HyperLTL formulas that for all sets of traces and their assignments they satisfy an HyperLTL formula iff they satisfy its translation to trace-prefixed hypertrace formula. This follows from the result by Gabbay et al. in [11] and Proposition 4 for the base case of this induction. Hence for all HyperLTL formulas φ_H there exists the trace-prefixed hypertrace formula $\text{tr}_H(\varphi_H)$ s.t. $T \models_H \varphi_H$ iff $T \models_{\mathbb{T}} \text{tr}_H(\varphi_H)$.

The translation from trace-prefixed hypertrace formulas to HyperLTL is similar. We use instead the translation from FO[<] to LTL from [11]. ◀

2.3 Time-prefixed Hypertrace Logic

Time-prefixed Hypertrace Logic, $\text{<-FO}[\text{<, T}]$, restricts the syntax of Hypertrace Logic to have all time constraints defined before trace quantifiers. Its formulas, $\varphi \in \text{<-FO}[\text{<, T}]$, are defined by the following grammar: $\varphi := \forall i \varphi \mid \neg \varphi \mid i < i \mid i = i \mid \varphi \vee \varphi \mid \psi$ with $\psi := \forall \pi \psi \mid \psi \vee \psi \mid \neg \psi \mid a(\pi, i)$, where $\pi \in \mathcal{V}$ is a trace variable, i is a time variable and $a \in X$ a propositional variable.

Globally Hypertrace logic, $\mathbf{G}\text{-FO}[\text{<, T}]$, is a syntactic fragment of Time-prefixed Hypertrace logic in which all formulas start with a universal time quantifier followed by a formula that can only have trace quantifiers. Then, $\varphi \in \mathbf{G}\text{-FO}[\text{<, T}]$ iff $\varphi = \forall i \psi_i$ where ψ_i is defined by the following grammar: $\psi_i := \forall \pi \psi_i \mid \psi_i \vee \psi_i \mid \neg \psi_i \mid a(\pi, i) \mid \text{def}(\pi, i)$.

For a formula $\psi(i)$ without time quantifiers and whose only free time variable is i , we also define as a convenience its satisfaction w.r.t. sets of valuations $M = \{v_0, v_1, \dots\}$ as follows:

$$\{v_0, v_1, \dots\} \models_{\mathbb{T}} \psi(i) \text{ iff for } T = \{v_0^\omega, v_1^\omega, \dots\}, \bar{T} \models \forall i \psi(i).$$

Globally Hypertrace Logic can be used to specify relations between traces of a system that must be satisfied in each of their time points independently. We use it later to specify the *point semantics* of independence.

We prove below that if an hyperproperty can be expressed with globally hypertrace logic then it can be characterized by a set of sets of valuations \mathbf{M} . We denote the set with all sequences of elements of \mathbf{M} by \mathbf{M}^ω . In this formal language context, we interpret sets of valuations as letters. Consider for instance the set $\mathbf{M} = \{\{00, 01\}, \{11\}\}$ with valuations over (x, y) . Then, $\{00, 11\} \{11\} \{00, 11\}^\omega \in \mathbf{M}^\omega$ while $\{00\}^\omega \notin \mathbf{M}^\omega$.

► **Theorem 6.** *Let X be a finite set of propositional variables and $\mathbf{T} \subseteq 2^{\mathbb{V}^X}$ be a hyperproperty. If there exists a globally hypertrace formula $\varphi \in \mathbf{G}\text{-FO}[\text{<, T}]$ that generates the same set of sets of traces as the hyperproperty, $\mathbf{T} = \llbracket \varphi \rrbracket$, then there exists a set of sets of valuations $\mathbf{M} \subseteq 2^{\mathbb{V}^X}$ that generates the point-wise interpretation of the hyperproperty, $\{T[0]T[1] \dots \mid T \in \mathbf{T}\} = \mathbf{M}^\omega$, where $T[i] = \{\tau[i] \mid \tau \in T\}$.*

3 Two-state Local Independence

We are interested in specifying the following property:

The value of y is independent from the value of x until state changes, and from then on the value of z is independent from the value of x .

Independence requirements relate observable values from multiple system executions by requiring that for any pair of traces there exists a third that interleaves the first two. However, there is some freedom in how to combine and compare a pair of traces. In this work, we assume observations to be synchronous concerning the states of the specification. We can then compare observations either point-wise, with *point semantics*, or as a whole, with *segment semantics*. As independence requirements may be evaluated over sets with traces of different length, we compare a pair of traces with different size by matching their values up to the common length. This enables us to capture dependencies between variables in systems where executions may stop at different points. We could choose to compare only traces of the same size, this would not affect our results.

► **Definition 7.** *Two variables, x and y , are point independent, denoted by $\text{ind}_{\text{point}}(x, y)$, iff:*

$$\forall i \forall \pi \forall \pi' \exists \pi_3 \left(\text{def}(\pi, i) \wedge \text{def}(\pi', i) \rightarrow \left(\text{def}(\pi_3, i) \wedge (x(\pi, i) \leftrightarrow x(\pi_3, i)) \wedge (y(\pi', i) \leftrightarrow y(\pi_3, i)) \right) \right).$$

■ **Table 2** Trace-prefixed Hypertrace Logic expressiveness for different variants of the two-state local independence property. For the two-state independence under point semantics and synchronous action, we prove in Theorem 27 that it cannot be expressed by HyperLTL formulas with only a Globally operator.

Independence Semantics	Action Timing		
	<i>Sync</i>	<i>Async</i>	<i>Hidden</i>
<i>Point</i>	No? [Thm. 27]	No [Thm. 34]	No [Thm. 34]
<i>Segment</i>	Yes [Thm. 29]	No [Thm. 34]	No [Thm. 34]

Two variables, x and y , are segment independent, denoted by $ind_{seg}(x, y)$, iff:

$$\forall \pi \forall \pi' \exists \pi_{\exists} \forall i (def(\pi, i) \wedge def(\pi', i)) \rightarrow (def(\pi_{\exists}, i) \wedge (x(\pi, i) \leftrightarrow x(\pi_{\exists}, i)) \wedge (y(\pi', i) \leftrightarrow y(\pi_{\exists}, i))).$$

We need to distinguish between observations from the first and the second logical state of the observed system. For this, we define a slicing operator over sets of traces that returns all its elements prefixes (or suffixes) before (after) a given propositional variable holds for the first time.

► **Definition 8.** Let a be a propositional variable. The abbreviation, $min(\pi, a, i)$, stands for $a(\pi, i) \wedge \forall j a(\pi, j) \rightarrow i \leq j$. Given a set of traces T , we define its slicing w.r.t. a , as follows:

$$T[a..] = \{\tau[k..] \mid \tau \in T, k \in \mathbb{N}, min(\tau, a, k)\} \text{ and } T[...a] = \{\tau[..k] \mid \tau \in T, k \in \mathbb{N}, min(\tau, a, k)\}.$$

Remark that we only keep traces in which a holds at least once. The property that a holds at least once in every trace can be verified separately.

► **Example 9.** Consider the set of traces $T = \{00^\omega, 01(10)^\omega\}$ in which the valuations are over (a, x) . Then, $T[...a] = \{(00)^\omega, 01\}$ and $T[a..] = \{(10)^\omega\}$.

The action that triggers the change of state may occur at the same time point for all observations, be *synchronous*, or at any time, be *asynchronous*.

► **Definition 10.** Let a be a boolean variable that is true when the state changes. Two-state independence is defined according to the possible action type, *sync*, *async* or *hidden*, and w.r.t. an independence interpretation $ind \in \{ind_{point}, ind_{seg}\}$.

Asynchronous Action: $\mathbf{T}_{ind}^{async} = \{T \mid T[...a] \models ind(x, y) \text{ and } T[a..] \models ind(x, z)\}$.

Synchronous Action: $\mathbf{T}_{ind}^{sync} = \{T \mid T \in \mathbf{T}_{ind}^{async} \text{ and } T \models \exists i \forall \pi min(\pi, a, i)\}$.

Hidden Action: $\mathbf{T}_{ind}^{hidden} = \{T|_a \mid \exists a T[...a] \models ind(x, y) \text{ and } T[a..] \models ind(x, z)\}$, where $T|_a$ is the same set of traces as T except for the assignments of a that are removed.

We note that in the case that we cannot observe the action, we do not make any assumption on whether the actual underlying action is synchronous and do not impose any further restriction on it.

4 Expressiveness

In this section, we explore which variations of two-state local independence can be specified using Trace-prefixed Hypertrace Logic, which is expressible equivalent to HyperLTL. We summarize our results in Table 2.

4.1 Indistinguishable Trace Sets

We introduce notions of indistinguishability between sets of traces for both the time-prefixed and the trace-prefixed fragments of Hypertrace Logic. We start by defining an equivalence between sets of traces for HyperLTL, which is expressively equivalent to the trace-prefixed fragment for sets with infinite traces. The number of trace quantifiers in a HyperLTL sentence defines how many traces can be compared in the requirement defined by the quantifier-free part. Recall that for quantifier-free formulas, HyperLTL satisfaction is reduced to LTL satisfaction, with assignments flattened to traces. We propose an equivalence notion for HyperLTL models that lifts equivalence between traces relative to a given class of LTL formulas to sets of traces. An example of such LTL equivalence is the stuttering equivalence between traces for the class of LTL formulas defined only with until modalities.

► **Definition 11.** *Let \mathbb{C} be a class of LTL formulas. We say that $\approx_{\mathbb{C}}$ is an equivalence on traces for formulas in \mathbb{C} when $\approx_{\mathbb{C}}$ is an equivalence relation and for all LTL formulas $\varphi \in \mathbb{C}$ and traces $\tau \approx_{\mathbb{C}} \tau'$, $\tau \models \varphi$ iff $\tau' \models \varphi$.*

We extend classes of LTL formulas to classes of HyperLTL formulas based on their syntax, enabling us to characterize certain temporal aspects of HyperLTL.

► **Definition 12.** *Let \mathbb{C} be a class of LTL formulas \mathbb{C} and let $\varphi = Q_0\pi_0 \dots Q_n\pi_n\psi$ be a HyperLTL formula with ψ being quantifier-free and $Q_i \in \{\forall, \exists\}$, with $0 \leq i \leq n$. Then, φ is in the HyperLTL extension of \mathbb{C} , denoted $\varphi \in 2^{\mathbb{C}}$, iff $\psi \in \mathbb{C}$.*

Given an equivalence on traces for LTL formulas in a class \mathbb{C} , we extend it to HyperLTL formulas with k quantifiers followed by a temporal formula in \mathbb{C} by requiring a bijective translation between sets of traces that preserves $\approx_{\mathbb{C}}$, for all assignments of size k .

► **Definition 13.** *Let $k \in \mathbb{N}$ and \mathbb{C} be a class of LTL formulas, with $\approx_{\mathbb{C}}$ an equivalence on traces for formulas in \mathbb{C} . Two sets of traces T and T' are (k, \mathbb{C}) -equivalent, denoted by $T \approx_{(k, \mathbb{C})} T'$, iff there exists a bijective and total function $f : T \rightarrow T'$, such that for all assignments over T and T' of size k , Π_T and $\Pi_{T'}$, we have: $\langle \Pi_T \rangle \approx_{\mathbb{C}} \langle f(\Pi_T) \rangle$ and $\langle \Pi_{T'} \rangle \approx_{\mathbb{C}} \langle f^{-1}(\Pi_{T'}) \rangle$. We let $f(\Pi)(\pi) = f(\Pi(\pi))$, if $\pi \in \mathcal{V}(\Pi)$ and, otherwise, undefined.*

► **Theorem 14.** *Let \mathbb{C} be a class of LTL formulas and $\approx_{\mathbb{C}}$ an equivalence on traces for formulas in \mathbb{C} . For all HyperLTL sentences with quantifier-free part in the class \mathbb{C} , $\varphi \in 2^{\mathbb{C}}$, and for all two set of traces that are (k, \mathbb{C}) -equivalent, $T \approx_{(|\mathcal{V}(\varphi)|, \mathbb{C})} T'$, then, $T \models \varphi$ iff $T' \models \varphi$.*

Proof. Follows from the application of Lemma 15 below. ◀

► **Lemma 15.** *Let \mathbb{C} be a class of LTL formulas. For all HyperLTL formulas in the HyperLTL extension of \mathbb{C} , $\varphi \in 2^{\mathbb{C}}$, and all sets of traces T and T' that are $(|\mathcal{V}(\varphi)|, \mathbb{C})$ -equivalent, $T \approx_{(|\mathcal{V}(\varphi)|, \mathbb{C})} T'$, then for all functions $f : T \rightarrow T'$ witnessing the equivalence and all assignments Π_T and $\Pi_{T'}$ over T and T' , respectively, only with assignments to the set of free variables in φ , $\mathcal{V}(\Pi_T) = \mathcal{V}(\Pi_{T'}) = \text{free}(\varphi)$:*

$$(\Pi_T, 0) \models \varphi \text{ iff } (f(\Pi_T), 0) \models \varphi; \text{ and } (\Pi_{T'}, 0) \models \varphi \text{ iff } (f^{-1}(\Pi_{T'}), 0) \models \varphi.$$

Proof. We proceed by structural induction on HyperLTL formulas in the extension of the LTL class \mathbb{C} . The base case follows from $\approx_{\mathbb{C}}$ being an equivalence on traces for formulas in \mathbb{C} and Proposition 4. We only treat the induction case for $\forall\pi \varphi$ and $\exists\pi \varphi$, the full proof is in appendix.

Assume by induction hypothesis (IH) that the statement holds for arbitrary $\varphi \in 2^{\mathbb{C}}$. Assume that (i) $T \approx_{(|\mathcal{V}(\forall\pi \varphi)|, \mathbb{C})} T'$. Note that, wlog we can assume that quantifiers bind a variable already occurring in φ , i.e. $|\mathcal{V}(\forall\pi \varphi)| = |\mathcal{V}(\varphi)|$. Then, (i') $T \approx_{(|\mathcal{V}(\varphi)|, \mathbb{C})} T'$, and it has the same witnesses as assumption (i). Let $f: T \rightarrow T'$ be a function that witnesses (i). Now, consider arbitrary Π_T and $\Pi_{T'}$, over T and T' , s.t. $\mathcal{V}(\Pi_T) = \mathcal{V}(\Pi_{T'}) = \text{free}(\forall\pi \varphi) = \text{free}(\varphi) \setminus \{\pi\}$. We prove next that, if $(\Pi_T, 0) \models \forall\pi \varphi$ then $(f(\Pi_T), 0) \models \forall\pi \varphi$.

Assume that $(\Pi_T, 0) \models \forall\pi \varphi$, then (\star) for all $\tau \in T: (\Pi_T[\pi \mapsto \tau], 0) \models \varphi$. By Definition 13, $\mathcal{V}(f(\Pi_T)) = \mathcal{V}(\Pi_T)$. Thus, $\mathcal{V}(f(\Pi_T)[\pi \mapsto \tau']) = \mathcal{V}(\Pi_T) \cup \{\pi\} = \text{free}(\varphi)$. We can apply the (IH), because $T \approx_{(|\mathcal{V}(\varphi)|, \mathbb{C})} T'$, f witnesses it, and for all $\tau \in T$ then $\Pi_T[\pi \mapsto \tau]$ is an assignment over T . So, for all $\tau \in T: (f(\Pi_T[\pi \mapsto \tau]), 0) \models \varphi$.

Assume towards a contradiction that $(f(\Pi_T), 0) \not\models \forall\pi \varphi$. Then, there exists $\tau' \in T'$ s.t. $(f(\Pi_T)[\pi \mapsto \tau'], 0) \not\models \varphi$. We can apply the (IH), because $\mathcal{V}(f(\Pi_T)[\pi \mapsto \tau']) = \text{free}(\varphi)$, (i') with f being one of its witnesses, and for all $\tau' \in T'$ then $f(\Pi_T)[\pi \mapsto \tau']$ is an assignment over T' . Hence there exists $\tau' \in T'$ s.t. $(f^{-1}(f(\Pi_T)[\pi \mapsto \tau']), 0) \not\models \varphi$. Then, by Definition 13, there exists $\tau' \in T'$ s.t. $(f^{-1}(f(\Pi_T)[\pi \mapsto \tau']), 0) \not\models \varphi$. As f is a bijective function, $(f^{-1}(f(\Pi_T))) = \Pi_T$, and so there exists $\tau' \in T'$ s.t. $(\Pi_T[\pi \mapsto f^{-1}(\tau')], 0) \not\models \varphi$. And this is equivalent to, there exists $\tau' \in T'$ s.t. $\tau = f^{-1}(\tau')$ and $(\Pi_T[\pi \mapsto \tau], 0) \not\models \varphi$. Given that f is a surjective function, then there exists $\tau \in T: (\Pi_T[\pi \mapsto \tau], 0) \not\models \varphi$. This contradicts (\star) .

We prove now that if $(\Pi_T, 0) \models \exists\pi \varphi$ then $(f(\Pi_T), 0) \models \exists\pi \varphi$. Assume that $(\Pi_T, 0) \models \exists\pi \varphi$, then there exists $\tau \in T$ s.t. $(\Pi_T[\pi \mapsto \tau], 0) \models \varphi$. By Definition 13, $\mathcal{V}(f(\Pi_T)) = \mathcal{V}(\Pi_T)$, and thus $\mathcal{V}(f(\Pi_T)[\pi \mapsto \tau']) = \mathcal{V}(\Pi_T) \cup \{\pi\} = \text{free}(\varphi)$. Then, we can apply the (IH), because $T \approx_{(|\mathcal{V}(\varphi)|, \mathbb{C})} T'$ with f being one of its witnesses, and for all $\tau \in T$ then $\Pi_T[\pi \mapsto \tau]$ is an assignment over T . So, there exists $\tau \in T$ s.t. $(f(\Pi_T[\pi \mapsto \tau]), 0) \models \varphi$. By Definition 13 and f being a total function, then there exists $\tau \in T, \tau' = f(\tau)$ and $(f(\Pi_T)[\pi \mapsto \tau'], 0) \models \varphi$. Hence there exists $\tau' \in T': (f(\Pi_T)[\pi \mapsto \tau'], 0) \models \varphi$, and so $(f(\Pi_T), 0) \models \exists\pi \varphi$. ◀

► **Remark 16.** The other direction of the implication in Theorem 14 does not hold. Consider the two set of traces below with valuations over (x) : $T = \{1010^\omega\}$ and $T' = \{10010^\omega, 100010^\omega\}$. The sets have different cardinality, so there is no k and \mathbb{C} for each they are (k, \mathbb{C}) -equivalent. However they are indistinguishable for all HyperLTL formulas with one trace quantifier and only until modalities, because the traces in T' are stutter-equivalent to the trace in T .

Next we introduce some notions of equivalence over traces that are used later in our results. We start by defining *Globally LTL*, \mathbb{G} , a LTL class with all formulas that have Globally, \mathbf{G} , as the topmost and unique modal operator. Then, $\mathbb{G} = \{\mathbf{G}\psi \mid \psi \text{ is a propositional formula}\}$.

► **Definition 17.** Two traces τ and τ' are $\approx_{\mathbb{G}}$ equivalent iff $\{\tau[i] \mid i \in \mathbb{N}\} = \{\tau'[j] \mid j \in \mathbb{N}\}$.

► **Proposition 18.** For all all two traces τ and τ' , $\tau \approx_{\mathbb{G}} \tau'$ iff, for all $\varphi \in \mathbb{G}$, $\tau \models \varphi$ iff $\tau' \models \varphi$.

The class \mathbb{X}^n is the class of LTL formulas with up to n nesting of the \mathbf{X} operator. In [15], the authors introduce the notion of a letter being n -redundant in a trace. A letter is n -redundant if it is repeated for at least n consecutive times. Then, two traces are n -stutter equivalent if they are equal up to the deletion of n -redundant letters. The following Proposition 20 is a direct consequence of the results in [15].

► **Definition 19** ([15]). A valuation at a time point i in a trace τ is n -redundant iff $\tau[i] = \tau[i+j]$ for all $1 \leq j \leq n+1$. For all $n \in \mathbb{N}$ we define the relation $<_n$ over finite or infinite traces, as follows: $\tau <_n \tau'$ iff τ can be obtained from τ' by deleting a n -redundant valuation. The relation \approx_n is the least equivalence over the set of all finite or infinite traces containing $<_n$. Then, the traces τ and τ' are n -stutter equivalent iff $\tau \approx_n \tau'$.

► **Proposition 20** ([15]). *For all formulas $\varphi \in \mathbb{X}^n$, if $\tau \approx_n \tau'$, then $\tau \models \varphi$ iff $\tau' \models \varphi$.*

We introduce a notion of indistinguishable sets of trace for time-prefixed Hypertrace logic. Consider a time-prefixed formula that quantifies over k time points. Then, two sets of traces are k -point equivalent if for each possible k -tuple of time points there is a bijective translation between the sets of traces that makes them indistinguishable in the times of that tuple.

► **Definition 21.** *Two sets of traces, T and T' , are k -point equivalent, denoted by $T \approx_k^{point} T'$, iff for all k -tuples of time positions, $(i_1, \dots, i_k) \in \mathbb{N}^k$, there exists a bijective and total function $f : T \rightarrow T'$ s.t. for all $\tau \in T$ we have $\tau[i_j] = f(\tau)[i_j]$ and for all $\tau' \in T'$ we have $\tau'[i_j] = f^{-1}(\tau')[i_j]$, with $1 \leq j \leq k$.*

► **Theorem 22.** *For all time-prefixed Hypertrace sentences $\varphi \in <-FO[<, \mathbb{T}]$ and all sets of traces, T and T' , that are $|\mathcal{I}(\varphi)|$ -point equivalent, $T \approx_{|\mathcal{I}(\varphi)|}^{point} T'$, where $|\mathcal{I}(\varphi)|$ is the number of time variables in φ , then $T \models \varphi$ iff $T' \models \varphi$.*

4.2 Point Semantics

The point semantics interpretation of independence considers each time point independently. Recall from Definition 7 that $ind_{point}(x, y)$ is defined as:

$$\forall i \forall \pi \forall \pi' \exists \pi_{\exists} \left(def(\pi, i) \wedge def(\pi', i) \right) \rightarrow \left(def(\pi_{\exists}, i) \wedge (x(\pi, i) \leftrightarrow x(\pi_{\exists}, i)) \wedge (y(\pi', i) \leftrightarrow y(\pi_{\exists}, i)) \right).$$

Globally HyperLTL is the extension of Globally LTL with trace quantifiers. We start by proving that no Globally HyperLTL formula can express *one-state independence with point semantics*, $\mathbf{T}_{point}^1 = \llbracket ind_{point}(x, y) \rrbracket$. Note that $ind_{point}(x, y)$ is a Globally Hypertrace formula.

First, we define two families of models parameterized by a natural number s.t. one of them satisfies the one-state independence with point semantics while the other does not satisfy it. The parameter in the models guarantees that given a HyperLTL with n quantifiers there are enough traces in the models to prevent HyperLTL from distinguishing them. We exploit the fact that while evaluating a HyperLTL formula we can compare simultaneously at most the same number of traces as the number of quantifiers. Then, we prove that no Globally HyperLTL formula can distinguish between the two types of models. To prove this result, we show that there exists a (k, \mathbb{G}) -equivalence between the models, where $\approx_{\mathbb{G}}$ is an equivalence over traces for Globally LTL formulas.

► **Definition 23.** *We define below set of sets of traces T_n^{point} and $T'_n{}^{point}$, for $n \in \mathbb{N}$ and with valuations over (x, y) :*

$$E_n = \{(11)^{n+2}(00)^\omega\} \cup \bigcup_{0 \leq j < n} \{(00)^j 10 (00)^\omega, (00)^j 01 (00)^\omega\};$$

$$T_n^{point} = E_n \cup \{(00)^n 10 10 (00)^\omega, (00)^n 01 01 (00)^\omega\}; \text{ and}$$

$$T'_n{}^{point} = E_n \cup \{(00)^n 10 00 (00)^\omega, (00)^n 01 00 (00)^\omega\}.$$

► **Example 24.** For $n = 1$, we get the following sets of traces:

$$\begin{array}{l} T_1^{point} = \{11 11 11 (00)^\omega, \\ \quad 10 00 00 (00)^\omega, \\ \quad 01 00 00 (00)^\omega, \\ \quad 00 10 10 (00)^\omega, \\ \quad 00 01 01 (00)^\omega\} \end{array} \qquad \begin{array}{l} T'_1{}^{point} = \{11 11 11 (00)^\omega, \\ \quad 10 00 00 (00)^\omega, \\ \quad 01 00 00 (00)^\omega, \\ \quad 00 10 00 (00)^\omega, \\ \quad 00 01 00 (00)^\omega\} \end{array}$$

The set T_1^{point} satisfies the condition that x is independent of y because at all time points we have all possible combinations of observations for x and y . However, T_1^{point} does not satisfy the requirement, because at time 2 we are missing traces with valuations 10 and 01 in (x, y) . Globally HyperLTL formulas with only one trace quantifier cannot distinguish between these sets of traces.

► **Lemma 25.** $T_n^{point} \in \mathbf{T}_{point}^1$ and $T_n^{point} \notin \mathbf{T}_{point}^1$.

► **Lemma 26.** For all $n \in \mathbb{N}$, $T_n^{point} \approx_{(n, \mathbb{G})} T_n^{point}$.

► **Theorem 27.** For all Globally HyperLTL formulas $\varphi \in 2^{\mathbb{G}}$, $\llbracket \varphi \rrbracket \neq \mathbf{T}_{point}^{sync}$.

Proof. By Lemma 25, Lemma 26 and Theorem 14, it follows that for all HyperLTL formulas in the class extending globally LTL, $\varphi \in 2^{\mathbb{G}}$, $\llbracket \varphi \rrbracket \neq \mathbf{T}_{point}^1$. Assume towards a contradiction that there exists a Globally HyperLTL formula φ s.t. $\llbracket \varphi \rrbracket = \mathbf{T}_{point}^{sync}$. Then, we define $\varphi_y = \varphi[z \mapsto y]$ where $[z \mapsto y]$ substitutes all occurrence of z by y . Then, $\llbracket \varphi_y \rrbracket = \mathbf{T}_{point}^1$. This is a contradiction, and so for all Globally HyperLTL formulas φ , $\llbracket \varphi \rrbracket \neq \mathbf{T}_{point}^{sync}$. ◀

We conjecture that this result extends to all HyperLTL formulas. Globally hypertrace formulas enforce a requirement over all time points that must be satisfied independently by them. Intuitively, such properties can be only expressed with HyperLTL formulas that are equivalent to a globally HyperLTL formula.

It is not surprising that time-prefixed hypertrace formulas can express two-state independence under point semantics with synchronous action. We conjecture that this is the only variant it can express.

► **Theorem 28.** Consider the following time-prefixed hypertrace formula:

$$\begin{aligned} \varphi_{time}^{sync} \stackrel{def}{=} & \exists j \forall i < j \forall k \leq j \forall \pi \forall \pi' \exists \pi_{\exists} \\ & (\neg a(\pi, i) \wedge \neg a(\pi', i) \wedge (x(\pi, i) \leftrightarrow x(\pi_{\exists}, i)) \wedge (y(\pi', i) \leftrightarrow y(\pi_{\exists}, i))) \wedge \\ & (a(\pi, j) \wedge a(\pi', j) \wedge (x(\pi, k) \leftrightarrow x(\pi'_{\exists}, k)) \wedge (z(\pi', k) \leftrightarrow z(\pi'_{\exists}, k))) \end{aligned}$$

Then, $\llbracket \varphi_{time}^{sync} \rrbracket = \mathbf{T}_{point}^{sync}$.

4.3 Segment Semantics

The segment semantics of independence compares between whole observations of a state in a system. Recall from Definition 7 that $ind_{seg}(x, y)$ is defined as:

$$\forall \pi \forall \pi' \exists \pi_{\exists} \forall i (def(\pi, i) \wedge def(\pi', i)) \rightarrow (def(\pi_{\exists}, i) \wedge (x(\pi, i) \leftrightarrow x(\pi_{\exists}, i)) \wedge (y(\pi', i) \leftrightarrow y(\pi_{\exists}, i))).$$

We prove that HyperLTL can express the two-state segments independence with synchronous action, while both asynchronous and hidden action are not expressible.

The intuitive HyperLTL formula for the two-state segments independence entails that the action is synchronous. So, we already cannot expect to rely on the proposition a to slice our traces accurately, when the action is asynchronous. To prove that HyperLTL cannot express the property in this scenario, we exploit the fact that we need to compare arbitrarily distant time points from different observations.

► **Theorem 29.** Consider the following HyperLTL formula:

$$\varphi_{seg}^{sync} \stackrel{def}{=} \forall \pi \forall \pi' \exists \pi_{\exists} \exists \pi'_{\exists} (\neg a_{\pi} \wedge \neg a_{\pi'} \wedge x_{\pi} = x_{\pi_{\exists}} \wedge y_{\pi'} = y_{\pi'_{\exists}}) \mathbf{U} (a_{\pi} \wedge a_{\pi'} \wedge \square (x_{\pi} = x_{\pi_{\exists}} \wedge z_{\pi'} = z_{\pi'_{\exists}}))$$

Then, $\llbracket \varphi_{seg}^{sync} \rrbracket = \mathbf{T}_{seg}^{sync}$.

XX:12 Flavours of Sequential Information Flow

We now examine the case of an asynchronous action. Like in the previous section for point semantics, we start by defining a family of models s.t. one of the families satisfies the two-state independence property while the other does not. The difficulty in expressing the asynchronous action is the arbitrary distance between time points we want to compare. Thus, we create the models to guarantee that there are not enough *next* operators to encode this distance. Then, the second family is the same as the first except for the position $2n + 1$ that is deleted. This position will coincide with a global (across all sets in the set of traces) n -stuttering in the first family. Thus, it is not surprising that instances of these families, for a given $n \in \mathbb{N}$, are (k, \mathbb{X}^n) -equivalent, for any number of trace quantifiers k .

► **Definition 30.** *The sets of sets of traces $T_n^{async} = \{t_1, t_2, t_3, t_4\}$ and $T_n^{rasync} = \{t'_1, t'_2, t'_3, t'_4\}$, for $n \in \mathbb{N}$, with valuations over (a, x, y, z) are defined by letting*

$$\begin{aligned} \tau_0 &= 1110 (1000)^{n+4} (1001)^{n+4} 1111 (1001)^{n+4} (1000)^{n+4}, \\ \tau_1 &= 1111 (1001)^{n+4} (1000)^{n+4} 1110 (1000)^{n+4} (1001)^{n+4}, \\ t_1 &= 0000 \tau_1 (1001)^\omega, \quad t_2 = 0010 \tau_1 (1001)^{n+4} (1111)^\omega, \\ t_3 &= (0000)^{n+4} \tau_0 (1001)^\omega, \quad t_4 = (0010)^{n+4} \tau_0 (1111)^\omega, \\ t'_i &= t_i[0]t_i[1] \dots t_i[2n+10]t_i[2n+12] \dots \text{ for } 1 \leq i \leq 4. \end{aligned}$$

► **Lemma 31.** *For all assignments $\Pi_{T_n^{async}}$ over T_n^{async} , the valuation at $2n+11$ is n -redundant in the trace $\langle \Pi_{T_n^{async}} \rangle$.*

It is clear, that all sets of traces that are models under the segments semantics are models under the point semantics, as well. Then, $\mathbf{T}_{seg}^{async} \subseteq \mathbf{T}_{point}^{async}$.

► **Lemma 32.** *$T_n^{async} \in \mathbf{T}_{seg}^{async}$, $T_n^{rasync} \notin \mathbf{T}_{point}^{async}$ and $T_n^{rasync}|_a \notin \mathbf{T}_{point}^{hidden}$.*

We remark that the set of traces T_n^{async} satisfies the two-state independence even when the segment interpretation of independence compares only pairs of traces of the same length.

► **Lemma 33.** *For all $n \in \mathbb{N}$, $k \in \mathbb{N}$ and HyperLTL formulas $\varphi \in \mathbb{X}^n$, $T_n^{async} \approx_{(k, \mathbb{X}^n)} T_n^{rasync}$ and $T_n^{async}|_a \approx_{(k, \mathbb{X}^n)} T_n^{rasync}|_a$.*

Proof. Consider arbitrary $n \in \mathbb{N}$ and $k \in \mathbb{N}$. We define the witness function $f : T_n^{async} \rightarrow T_n^{rasync}$ as $f(t_i) = t'_i$, with $1 \leq i \leq 4$. Clearly, it is both bijective and total. Let $\Pi_{T_n^{async}}$ be an arbitrary assignment over T_n^{async} s.t. $|\Pi_{T_n^{async}}| = k$. We prove in Lemma 31 that the letter at $2n + 11$ in $\langle \Pi_{T_n^{async}} \rangle$ is n -redundant. By definition of T_n^{rasync} , $\langle f(\Pi_{T_n^{async}}) \rangle$ is the same as $\langle \Pi_{T_n^{async}} \rangle$ except for the valuation at $2n + 11$ that is deleted. Then, $\langle \Pi_{T_n^{async}} \rangle \approx_{\mathbb{X}^n} \langle f(\Pi_{T_n^{async}}) \rangle$. We prove analogously that for all assignments over T_n^{rasync} , $\Pi_{T_n^{rasync}}$, with size k , $\langle \Pi_{T_n^{rasync}} \rangle \approx_{\mathbb{X}^n} \langle f^{-1}(\Pi_{T_n^{rasync}}) \rangle$. Hence $T_n^{async} \approx_{(k, \mathbb{X}^n)} T_n^{rasync}$. We use the same witness function to prove that $T_n^{async}|_a \approx_{(k, \mathbb{X}^n)} T_n^{rasync}|_a$. Note, as $T_n^{async}|_a$ is the same as T_n^{async} except for the valuations of a that are removed, then Lemma 31 holds for $T_n^{async}|_a$, as well. ◀

► **Theorem 34.** *For all HyperLTL sentences φ : $\llbracket \varphi \rrbracket \neq \mathbf{T}_{point}^{async}$, $\llbracket \varphi \rrbracket \neq \mathbf{T}_{seg}^{async}$, $\llbracket \varphi \rrbracket \neq \mathbf{T}_{point}^{hidden}$ and $\llbracket \varphi \rrbracket \neq \mathbf{T}_{seg}^{hidden}$.*

Proof. From $\mathbf{T}_{seg}^{async} \subseteq \mathbf{T}_{point}^{async}$ and Lemma 32, it follows that:

- $T_n^{async} \in \mathbf{T}_{seg}^{async}$ and $T_n^{rasync} \notin \mathbf{T}_{seg}^{async}$; and
- $T_n^{async} \in \mathbf{T}_{point}^{async}$ and $T_n^{rasync} \notin \mathbf{T}_{point}^{async}$.

Let φ be a closed HyperLTL formulas and let n be the number of its nested next operators. Then, $\varphi \in 2^{\mathbb{X}^n}$ and there exists $k \in \mathbb{N}$ equal to the number of variables in φ . So, it follows from Lemma 33 and Theorem 14 that $T_n^{async} \in \llbracket \varphi \rrbracket$ iff $T_n'^{async} \in \llbracket \varphi \rrbracket$. Hence for all HyperLTL sentences $\llbracket \varphi \rrbracket \neq \mathbf{T}_{point}^{async}$ and $\llbracket \varphi \rrbracket \neq \mathbf{T}_{seg}^{async}$.

As $T_n^{async}|_a$ is the same as T_n^{async} , except for the valuations of a that were removed, then $T_n^{async}|_a \in \mathbf{T}_{seg}^{hidden}$ and $T_n^{async}|_a \in \mathbf{T}_{point}^{hidden}$. By Lemma 32, $T_n'^{async}|_a \notin \mathbf{T}_{point}^{hidden}$ and so it follows that $T_n'^{async}|_a \notin \mathbf{T}_{seg}^{hidden}$. As in the previous case, from Lemma 33 and Theorem 14, it follows that for all HyperLTL formulas $\llbracket \varphi \rrbracket \neq \mathbf{T}_{point}^{hidden}$ and $\llbracket \varphi \rrbracket \neq \mathbf{T}_{seg}^{hidden}$. ◀

5 Related Work

Linear-time hyperlogics support the comparison between traces from a given set. Trace properties, often specified in LTL [17], are not expressive enough to specify such relations [16, 5]. The seminal work of Clarkson and Schneider [5] introduces the concept of *hyperproperties* as sets of trace properties.

Different extensions to LTL have been proposed to reason about security properties that often require comparing multiple executions of a system. Well-known examples are the epistemic temporal logic (ETL) [8], which extends LTL with the *epistemic modal operator for knowledge*; and SecLTL [7], which introduces the *hide* modality. As an attempt to define a unifying logic for hyperproperties, Clarkson et al. introduce HyperLTL [4], which extends LTL with explicit quantification over traces.

The hide operator in SecLTL considers all alternative outcomes from the current time. For this reason, in [4] the authors argue that there is a SecLTL formula that can distinguish between some systems with different computations paths but the same set of traces. In the same paper, they prove that HyperLTL subsumes ETL. Their proof relies on the possibility to quantify over propositional variables that are not part of the system that generates a given set of traces. Later they updated the definition of HyperLTL to not allow such quantification. This extension to HyperLTL, with quantification over propositional variables, is introduced in [6] as HyperQPTL and proven to be strictly more expressive than HyperLTL.

Bozzelli et al. prove, in [2], that CTL* extended with trace quantifiers (HyperCTL*) and with the knowledge operator (KCTL*) have incomparable expressive power. These results extend to HyperLTL and ETL, as well, as they are both subsumed by the respective CTL* extension. They start by proving that no ETL formula can specify that in a given set of traces two traces only differ at a time point, which can be specified in HyperLTL. Their result explores the fact that trace quantification in ETL is implicit, as the only way to compare different traces is with the knowledge operator. Later, they prove that HyperLTL cannot express bounded termination. This result relies on the fact that, for all HyperLTL formulas, time quantifiers are always dependent on the trace quantifiers. The latter property can be specified in ETL.

In contrast to the extensions to LTL discussed above, in [14], Krebs et al. propose to reinterpret LTL under *team semantics*. Team semantics works with sets of assignments, referred to as *teams*. The authors introduce synchronous and asynchronous semantics. Similar to how we specify two-state independence, their semantics differ on how they slice the set of traces while interpreting the time operators. Synchronous semantics requires the time to be global, while in the asynchronous case time is local to each trace. They show that HyperLTL and LTL under team semantics and synchronous entailment have incomparable expressive power.

Previous negative expressivity results about HyperLTL in the literature refer to the

property used in the proof by Bozzelli et al. in [2]. Their proof defines an equivalence relation for a specific family of models to show that no HyperCTL* can distinguish them. To the best of our knowledge, only Finkbeiner and Rabe [9] identify an equivalence relation over sets of traces that are not distinguishable by HyperLTL formulas. Similar to LTL, HyperLTL cannot distinguish between systems that generate the same set of traces.

In [10], the authors propose to extend $FO[<]$ to hyperproperties by adding the equal-level predicate E and denote this extension as $FO[<, E]$. In this approach, time positions are labeled by traces and the predicate E is intended to relate the same time positions occurring in different traces. They prove in the same paper that $FO[<, E]$ is more expressive than HyperLTL. They then define HyperFO by distinguishing quantifiers over initial positions (equivalent to trace quantifiers in HyperLTL) from time quantifiers (ordinary temporal operators in HyperLTL). Finally, they prove that HyperFO and HyperLTL are expressively equivalent.

At the time of the submission we became aware of two accepted (not yet published) papers [3, 1] that address the problem of expressing asynchronous variants of information-flow security properties. In both submissions the authors introduce extensions of HyperLTL to address different approaches to deal with asynchronicity. These papers confirm that the need for a framework enabling a systematic investigation of information-flow properties under different assumptions is of timely importance. While these works focus on the asynchronicity of system events and on the decidability of the corresponding model-checking problems, we instead consider the (a-)synchronicity (and observability) of specification events under two information-flow semantics and investigate the corresponding expressiveness problems. For example, in the two-state independence property, the state transition does not (necessarily) refer to a system transition but *specifies* a change in the dependency graph between variables.

6 Conclusion

In this paper, we studied the formal specification of sequential information-flow hyperproperties, especially the paradigmatic hyperproperty of two-state independence. We formalized several flavours of sequential information-flow using Hypertrace Logic, a first-order logic with trace and time quantifiers. We introduced a new proof technique for reasoning about the expressiveness of linear-time specification formalisms for hyperproperties such as HyperLTL. In particular, we showed that several natural flavours of sequential information flow cannot be expressed in HyperLTL due to the fixed order of its quantifiers.

The results in this paper indicate the need to study more asynchronous classes of hyperlogics. These findings seem to be corroborated by very recent works [3, 1] on asynchronous and context HyperLTL. We plan to study also the expressiveness of these formalisms with respect to sequential information flow.

References

- 1 Jan Baumeister, Norine Coenen, Borzoo Bonakdarpour, Bernd Finkbeiner, and César Sanchez. A temporal logic for asynchronous hyperproperties. In *To appear in the Proc. of CAV 2021*, 2021.
- 2 Laura Bozzelli, Bastien Maubert, and Sophie Pinchinat. Unifying hyper and epistemic temporal logics. In *International Conference on Foundations of Software Science and Computation Structures*, pages 167–182. Springer, 2015.
- 3 Laura Bozzelli, Adriano Peron, and César Sanchez. Asynchronous extensions of hyperLTL. In *To appear in the Proc. of LICS 2021*, 2021.

- 4 Michael R. Clarkson, Bernd Finkbeiner, Masoud Koleini, Kristopher K. Micinski, Markus N. Rabe, and César Sánchez. Temporal logics for hyperproperties. In *Proc. of POST 2014: the Third International Conference on Principles of Security and Trust*, volume 8414 of *Lecture Notes in Computer Science*, pages 265–284. Springer, 2014. doi:10.1007/978-3-642-54792-8.
- 5 Michael R. Clarkson and Fred B. Schneider. Hyperproperties. *Journal of Computer Security*, 18(6):1157–1210, 2010. doi:10.3233/JCS-2009-0393.
- 6 Norine Coenen, Bernd Finkbeiner, Christopher Hahn, and Jana Hofmann. The hierarchy of hyperlogics. In *2019 34th Annual ACM/IEEE Symposium on Logic in Computer Science (LICS)*, pages 1–13. IEEE, 2019.
- 7 Rayna Dimitrova, Bernd Finkbeiner, Máté Kovács, Markus N Rabe, and Helmut Seidl. Model checking information flow in reactive systems. In *International Workshop on Verification, Model Checking, and Abstract Interpretation*, pages 169–185. Springer, 2012.
- 8 Ronald Fagin, Yoram Moses, Joseph Y Halpern, and Moshe Y Vardi. *Reasoning about knowledge*. MIT Press, 1995.
- 9 Bernd Finkbeiner and Markus N Rabe. The linear-hyper-branching spectrum of temporal logics. *Inf. Technol.*, 56(6):273–279, 2014.
- 10 Bernd Finkbeiner and Martin Zimmermann. The first-order logic of hyperproperties. In *34th Symposium on Theoretical Aspects of Computer Science*, 2017.
- 11 Dov Gabbay, Amir Pnueli, Saharon Shelah, and Jonathan Stavi. On the temporal analysis of fairness. In *Proceedings of the 7th ACM SIGPLAN-SIGACT symposium on Principles of programming languages*, pages 163–173, 1980.
- 12 Erich Grädel and Jouko Väänänen. Dependence and independence. *Studia Logica*, 101(2):399–410, 2013.
- 13 Hans Kamp. *Tense Logic and the Theory of Linear Order*. PhD thesis, UCLA, 1968.
- 14 A Krebs, A Meier, J Virtema, and M Zimmermann. Team semantics for the specification and verification of hyperproperties. *Leibniz International Proceedings in Informatics, LIPIcs*, 117, 2018.
- 15 Antonín Kučera and Jan Strejček. The stuttering principle revisited. *Acta Informatica*, 41(7-8):415–434, 2005.
- 16 John McLean. A general theory of composition for a class of “possibilistic” properties. *IEEE Transactions on Software Engineering*, 22(1):53–67, 1996.
- 17 Amir Pnueli. The temporal logic of programs. In *Proc. of FOCS77: the 18th Annual Symposium on Foundations of Computer Science*, pages 46–57. IEEE Computer Society, 1977. doi:10.1109/SFCS.1977.32.
- 18 Andrei Sabelfeld and David Sands. Declassification: Dimensions and principles. *Journal of Computer Security*, 17(5):517–548, 2009.

A Globally Hypertrace Logic

A.1 Theorem 6

Let X be a finite set of propositional variables and $\mathbf{T} \subseteq 2^{\mathbb{V}^x}$ be a hyperproperty. If there exists a globally hypertrace formula $\varphi \in \mathbf{G}\text{-FO}[\langle, \mathbb{T} \rangle]$ that generates the same set of sets of traces as the hyperproperty, $\mathbf{T} = \llbracket \varphi \rrbracket$, then there exists a set of sets of valuations $\mathbf{M} \subseteq 2^{\mathbb{V}^x}$ that generates the point-wise interpretation of the hyperproperty, $\{T[0]T[1]\dots \mid T \in \mathbf{T}\} = \mathbf{M}^\omega$, where $T[i] = \{\tau[i] \mid \tau \in T\}$.

Proof. Consider an arbitrary finite set of propositional variables X and $\mathbf{T} \subseteq 2^{\mathbb{V}^x}$. Assume that there exists $\varphi \in \mathbf{G}\text{-FO}[\langle, \mathbb{T} \rangle]$ s.t. $(\star) \mathbf{T} = \{T \mid T \models \varphi\}$. By definition of $\mathbf{G}\text{-FO}[\langle, \mathbb{T} \rangle]$, $\varphi = \forall i \psi(i)$. Let $\mathbf{M}_\varphi = \{T[n] \mid T \models \varphi \text{ and } n \in \mathbb{N}\}$. Clearly, $\mathbf{M}_\varphi \subseteq 2^{\mathbb{V}^x}$. As X is finite, all elements of \mathbf{M}_φ are finite. Additionally, there is only a finite number of valuations over X , so \mathbf{M}_φ is a finite set, too.

First, we prove $\{T[0]T[1]\dots \mid T \in \mathbf{T}\} \subseteq \mathbf{M}_\varphi^\omega$. Consider an arbitrary $T \in \mathbf{T}$. By our assumption (\star) , $T \models \varphi$. Then, by definition of \mathbf{M}_φ , $\{T[0], T[1], \dots\} \subseteq \mathbf{M}_\varphi$. Hence $T[0]T[1]\dots \in \mathbf{M}_\varphi^\omega$.

Now, we prove $\mathbf{M}_\varphi^\omega \subseteq \{T[0]T[1]\dots \mid T \in \mathbf{T}\}$. Consider arbitrary $M = M_0M_1\dots$ s.t. $M \in \mathbf{M}_\varphi^\omega$. Then, $\{M_0, M_1, \dots\} \subseteq \mathbf{M}_\varphi$ and, by definition of \mathbf{M}_φ , for all $j \in \mathbb{N}$, $(\star\star)$ there exists $T \models \varphi$ and $j' \in \mathbb{N}$ s.t. $M_j = T[j']$. Next we define a set of traces s.t. $T_M[0]T_M[1]\dots = M$ and $T_M \in \mathbf{T}$. Wlog, as \mathbf{M}_φ is finite, $\mathbf{M}_\varphi = \{M_0, \dots, M_n\}$. For all $M_i = \{m_0, \dots, m_j\} \in \mathbf{M}$, we use $M_i[l] = m_l$ with $0 \leq l \leq j$. The set of traces T_M is defined below:

$$T_M = \{\tau_k \mid 0 \leq k < \|\mathbf{M}_\varphi\| \text{ and } j \in \mathbb{N} : \tau_k[j] = M_j[k \bmod \|\mathbf{M}_\varphi\|]\}.$$

By our assumption (\star) , $T_M \in \mathbf{T}$ iff $T_M \models \forall i \psi(i)$. By definition of satisfaction for FOL, $T_M \models \varphi$ iff for all $j \in \mathbb{N}$, $T_M[j] \models \psi(i)$. Consider an arbitrary $j \in \mathbb{N}$. Given that there exists $k = \|\mathbf{M}\|$ traces, for all $M \in \mathbf{M}_\varphi$ we have $k \leq |M|$. Then, by $\tau_k[j] = M_j[k \bmod \|\mathbf{M}_\varphi\|]$ used in the definition of T_M , it follows that $T_M[j] = M_j$ (i.e. all valuations in M_j occur at least once at time j in T_M and there is nothing else there). So, by $(\star\star)$, there exists T and $j' \in \mathbb{N}$ s.t. $T[j'] \models \psi(i)$ and $T[j'] = M_j = T_M[j]$. Hence $T_M \in \mathbf{T}$. \blacktriangleleft

B Expressiveness

B.1 Lemma 15

Let \mathbb{C} be a class of LTL formulas. For all HyperLTL formulas in the HyperLTL extension of \mathbb{C} , $\varphi \in 2^{\mathbb{C}}$, and all sets of traces T and T' that are $(\mathcal{V}(\varphi), \mathbb{C})$ -equivalent, $T \approx_{(\mathcal{V}(\varphi), \mathbb{C})} T'$, then for all functions $f : T \rightarrow T'$ witnessing the equivalence and all assignments Π_T and $\Pi_{T'}$ over T and T' , respectively, only with assignments to the set of free variables in φ , $\mathcal{V}(\Pi_T) = \mathcal{V}(\Pi_{T'}) = \text{free}(\varphi)$: $(\Pi_T, 0) \models \varphi$ iff $(f(\Pi_T), 0) \models \varphi$; and $(\Pi_{T'}, 0) \models \varphi$ iff $(f^{-1}(\Pi_{T'}), 0) \models \varphi$.

Proof. We prove this statement by structural induction on HyperLTL formulas on a class $2^{\mathbb{C}}$. The class \mathbb{C} affects only the quantifier-free part of the formula.

Quantifier-free $\varphi \in 2^{\mathbb{C}}$: Then, $\text{free}(\varphi) = \mathcal{V}(\varphi)$. Additionally, φ can be interpreted as an LTL formula over the set of propositional variables $X_{\mathcal{V}(\varphi)}$ with $\varphi \in \mathbb{C}$. Consider arbitrary set of traces s.t. $T \approx_{(\mathcal{V}(\varphi), \mathbb{C})} T'$ with f being a function that witnesses it. Now, consider an arbitrary Π_T and $\Pi_{T'}$ over T' and T , respectively, s.t. $\mathcal{V}(\Pi_T) = \mathcal{V}(\Pi_{T'}) = \text{free}(\varphi)$. By definition of $\approx_{(\mathcal{V}(\varphi), \mathbb{C})}$, $\langle \Pi_T \rangle \approx_{\mathbb{C}} \langle f(\Pi_T) \rangle$ and, by definition of $\approx_{\mathbb{C}}$: $(\star) \langle \Pi_T \rangle \models$

φ iff $\langle f(\Pi_T) \rangle \models \varphi$. By Proposition 4, $(\Pi_T, 0) \models \varphi$ iff $\langle \Pi_T \rangle [0 \dots] \models \varphi$; and $(f(\Pi_T), 0) \models \varphi$ iff $\langle f(\Pi_T) \rangle [0 \dots] \models \varphi$. Thus, $(\Pi_T, 0) \models \varphi$ iff $(f(\Pi_T), 0) \models \varphi$.

Analogously, $(\Pi_{T'}, 0) \models \varphi$ iff $(\langle f^{-1}(\Pi_{T'}) \rangle, 0) \models \varphi$.

Induction case $\forall \pi \varphi$: Assume by induction hypothesis (IH) that the statement holds for arbitrary $\varphi \in 2^{\mathcal{C}}$. Assume that (i) $T \approx_{(|\mathcal{V}(\forall \pi \varphi)|, \mathcal{C})} T'$. Note that, wlog we can assume that quantifiers bind a variable already occurring in φ , i.e. $|\mathcal{V}(\forall \pi \varphi)| = |\mathcal{V}(\varphi)|$. Then, (i') $T \approx_{(|\mathcal{V}(\varphi)|, \mathcal{C})} T'$, and it has the same witnesses as assumption (i).

Let $f : T \rightarrow T'$ be a function that witnesses (i). Now, consider arbitrary Π_T and $\Pi_{T'}$, over T and T' , s.t. $\mathcal{V}(\Pi_T) = \mathcal{V}(\Pi_{T'}) = \text{free}(\forall \pi \varphi) = \text{free}(\varphi) \setminus \{\pi\}$.

We prove next that: $(\Pi_T, 0) \models \forall \pi \varphi$ iff $(f(\Pi_T), 0) \models \forall \pi \varphi$. We start with the \Rightarrow -direction of the statement. Assume that $(\Pi_T, 0) \models \forall \pi \varphi$, then by HyperLTL satisfaction: (\star) for all $\tau \in T : (\Pi_T[\pi \mapsto \tau], 0) \models \varphi$. By Definition 13, $\mathcal{V}(f(\Pi_T)) = \mathcal{V}(\Pi_T)$. Thus, $\mathcal{V}(f(\Pi_T)[\pi \mapsto \tau']) = \mathcal{V}(\Pi_T) \cup \{\pi\} = \text{free}(\varphi)$. We can apply the (IH), because $T \approx_{(|\mathcal{V}(\varphi)|, \mathcal{C})} T'$, f witnesses it, and for all $\tau \in T$ then $\Pi_T[\pi \mapsto \tau]$ is an assignment over T . So, it follows: for all $\tau \in T : (f(\Pi_T[\pi \mapsto \tau]), 0) \models \varphi$.

Assume towards a contradiction that $(f(\Pi_T), 0) \not\models \forall \pi \varphi$. Then, by definition of HyperLTL satisfaction: there exists $\tau' \in T' : (f(\Pi_T)[\pi \mapsto \tau'], 0) \not\models \varphi$. We can apply the (IH), because $\mathcal{V}(f(\Pi_T)[\pi \mapsto \tau']) = \text{free}(\varphi)$, (i') with f being one of its witnesses, and for all $\tau' \in T'$ the $f(\Pi_T)[\pi \mapsto \tau']$ is an assignment over T' . So, it follows:

$$\text{there exists } \tau' \in T' : (f^{-1}(f(\Pi_T)[\pi \mapsto \tau']), 0) \not\models \varphi.$$

And by Definition 13: there exists $\tau' \in T' : (f^{-1}(f(\Pi_T)[\pi \mapsto \tau']), 0) \not\models \varphi$. As f is a bijective function, $(f^{-1}(f(\Pi_T))) = \Pi_T$, and so: there exists $\tau' \in T' : (\Pi_T[\pi \mapsto f^{-1}(\tau')], 0) \not\models \varphi$. And this is equivalent to:

$$\text{there exists } \tau' \in T' : \tau = f^{-1}(\tau') \text{ and } (\Pi_T[\pi \mapsto \tau], 0) \not\models \varphi.$$

Given that f is a surjective function, then: there exists $\tau \in T : (\Pi_T[\pi \mapsto \tau], 0) \not\models \varphi$. This contradicts (\star) . So, the \Rightarrow -direction holds.

We now prove the \Leftarrow -direction by contra-position.

Assume that $(\Pi_T, 0) \not\models \forall \pi \varphi$, then by HyperLTL satisfaction: there exists $\tau \in T : (\Pi_T[\pi \mapsto \tau], 0) \not\models \varphi$. We can apply now the (IH), because $\mathcal{V}(f(\Pi_T)[\pi \mapsto \tau']) = \text{free}(\varphi)$, (i') with f being one of its witnesses, and for all $\tau \in T$ the $\Pi_T[\pi \mapsto \tau]$ is an assignment over T . Then, it follows: there exists $\tau \in T : (f(\Pi_T[\pi \mapsto \tau]), 0) \not\models \varphi$. By Definition 13: there exists $\tau \in T : \tau' = f(\tau)$ and $(f(\Pi_T)[\pi \mapsto \tau']), 0) \not\models \varphi$. By f being surjective, it follows: there exists $\tau' \in T' : (f(\Pi_T)[\pi \mapsto \tau']), 0) \not\models \varphi$. And by Definition of HyperLTL satisfaction: $(f(\Pi_T), 0) \not\models \forall \pi \varphi$. Thus, the \Leftarrow -direction of the statement holds, as well.

Hence $(\Pi_T, 0) \models \forall \pi \varphi$ iff $(f(\Pi_T), 0) \models \forall \pi \varphi$.

Now, we prove $(\Pi_{T'}, 0) \models \forall \pi \varphi$ iff $(f^{-1}(\Pi_{T'}), 0) \models \forall \pi \varphi$. We start with the \Rightarrow -direction of the statement.

Like in the previous case, we assume that $(\Pi_{T'}, 0) \models \forall \pi \varphi$, and then we assume towards a contradiction that $(f^{-1}(\Pi_{T'}), 0) \not\models \forall \pi \varphi$. The proof is analogous to the previous case up to the point that we infer:

$$\text{there exists } \tau \in T : \tau' = f(\tau) \text{ and } (\Pi_{T'}[\pi \mapsto \tau'], 0) \not\models \varphi.$$

Then, by f being total we get:

$$\text{there exists } \tau' \in T' : (\Pi_{T'}[\pi \mapsto \tau'], 0) \not\models \varphi.$$

XX:18 Flavours of Sequential Information Flow

And this contradicts the assumption that $(\Pi_{T'}, i) \models \forall \pi \varphi$.

The \Leftarrow -direction is analogous to the previous case, as well, up to the point that we infer:

there exists $\tau' \in T' : \tau = f(\tau')$ and $(f^{-1}(\Pi_T)[\pi \mapsto \tau]), 0 \not\models \varphi$.

Then, by f being total we infer:

there exists $\tau \in T : (f^{-1}(\Pi_T)[\pi \mapsto \tau]), 0 \not\models \varphi$.

So, $f^{-1}(\Pi_T), 0 \not\models \forall \pi \varphi$. Hence the \Leftarrow -direction holds.

Induction case $\exists \pi \varphi$: Assume by induction hypothesis (IH) that the statement holds for arbitrary $\varphi \in 2^{\mathcal{C}}$.

We assume that $(i) T \approx_{(|\mathcal{V}(\exists \pi \varphi)|, \mathcal{C})} T'$. Note that, wlog we can assume that quantifiers bind a variable already occurring in φ , i.e. $|\mathcal{V}(\exists \pi \varphi)| = |\mathcal{V}(\varphi)|$. So, $(i') T \approx_{(|\mathcal{V}(\varphi)|, \mathcal{C})} T'$, and it has the same witnesses as assumption (i) .

Let $f : T \rightarrow T'$ be a function that witnesses (i) . Now, consider arbitrary Π_T and $\Pi_{T'}$, over T and T' , s.t. $\mathcal{V}(\Pi_T) = \mathcal{V}(\Pi_{T'}) = \text{free}(\exists \pi \varphi) = \text{free}(\varphi) \setminus \{\pi\}$.

We prove: $(\Pi_T, 0) \models \exists \pi \varphi$ iff $(f(\Pi_T), 0) \models \exists \pi \varphi$.

We start with the \Rightarrow -direction of the statement.

Assume that $(\Pi_T, 0) \models \exists \pi \varphi$, then by HyperLTL satisfaction:

there exists $\tau \in T : (\Pi_T[\pi \mapsto \tau], 0) \models \varphi$.

By Definition 13, $\mathcal{V}(f(\Pi_T)) = \mathcal{V}(\Pi_T)$, and thus $\mathcal{V}(f(\Pi_T)[\pi \mapsto \tau']) = \mathcal{V}(\Pi_T) \cup \{\pi\} = \text{free}(\varphi)$. Then, we can apply the (IH), because $T \approx_{(|\mathcal{V}(\varphi)|, \mathcal{C})} T'$ with f being one of its witnesses, and for all $\tau \in T$ the $\Pi_T[\pi \mapsto \tau]$ is an assignment over T . So, we get:

there exists $\tau \in T : (f(\Pi_T[\pi \mapsto \tau]), 0) \models \varphi$.

By Definition 13,

there exists $\tau \in T, \tau' = f(\tau)$ and $(f(\Pi_T)[\pi \mapsto \tau'], 0) \models \varphi$.

Then, by f being a total function:

there exists $\tau' \in T' : (f(\Pi_T)[\pi \mapsto \tau'], 0) \models \varphi$.

Hence by HyperLTL satisfaction definition: $(f(\Pi_T), 0) \models \exists \pi \varphi$.

We now prove the \Leftarrow -direction of the statement.

Assume that $(f(\Pi_T), 0) \models \exists \pi \varphi$, then by HyperLTL satisfaction:

there exists $\tau \in T : (f(\Pi_T[\pi \mapsto \tau]), 0) \models \varphi$.

By Definition 13, $\mathcal{V}(\Pi_T) = \mathcal{V}(f(\Pi_T))$, and thus $\mathcal{V}(\Pi_T[\pi \mapsto \tau']) = \mathcal{V}(f(\Pi_T)) \cup \{\pi\} = \text{free}(\varphi)$. Then, we can apply the (IH), because $T \approx_{(|\mathcal{V}(\varphi)|, \mathcal{C})} T'$ with f being one of its witnesses, and for all $\tau \in T$ the $f(\Pi_T[\pi \mapsto \tau])$ is an assignment over T' . So, we get:

there exists $\tau \in T : (\Pi_T[\pi \mapsto \tau], 0) \models \varphi$.

And by HyperLTL satisfaction definition, $(\Pi_T, 0) \models \exists \pi \varphi$.

We prove: $(\Pi_{T'}, 0) \models \exists \pi \varphi$ iff $(f^{-1}(\Pi_{T'}), 0) \models \exists \pi \varphi$.

We start with the \Rightarrow -direction of the statement. It is analogous to the previous case, up to the point that we infer: there exists $\tau' \in T' : \tau = f^{-1}(\tau')$ and $(f^{-1}(\Pi_{T'})[\pi \mapsto \tau], 0) \models \varphi$. Then, by f being surjective we get:

there exists $\tau \in T : (f^{-1}(\Pi_{T'})[\pi \mapsto \tau], 0) \models \varphi$.

Hence by HyperLTL satisfaction definition: $(f^{-1}(\Pi_{T'}), 0) \models \exists \pi \varphi$.

The \Leftarrow -direction is analogous to the previous case. ◀

B.2 Proposition 18

For all all two traces τ and τ' , $\tau \approx_{\mathbb{G}} \tau'$ iff, for all $\varphi \in \mathbb{G}$, $\tau \models \varphi$ iff $\tau' \models \varphi$.

Proof. Consider arbitrary traces τ and τ' .

\Rightarrow : Assume that $\tau \approx_{\mathbb{G}} \tau'$. Consider an arbitrary $\varphi \in \mathbb{G}$, so $\varphi = \mathbf{G}\psi$ where ψ is a propositional formula. Then, $\tau \not\models \varphi$ iff there exists $i \in \mathbb{N}$ s.t. $\tau[i] \not\models \psi$. And this is equivalent to, there exists $v \in \{\tau[i] \mid i \in \mathbb{N}\}$ s.t. $v \not\models \psi$. By $\tau \approx_{\mathbb{G}} \tau'$, $v \in \{\tau[i] \mid i \in \mathbb{N}\}$ iff $v \in \{\tau'[j] \mid j \in \mathbb{N}\}$. Then from an analogous reasoning, the former is equivalent to $\tau' \not\models \varphi$.

\Leftarrow : Assume that for all $\varphi \in \mathbb{G}$ we have (\star) $\tau \models \varphi$ iff $\tau' \models \varphi$. Now, assume towards a contradiction that $\tau \not\approx_{\mathbb{G}} \tau'$. Consider first the case that there exists $i \in \mathbb{N}$ s.t. $\tau[i] \notin \{\tau'[j] \mid j \in \mathbb{N}\}$. This contradicts (\star) , because it entails that there exists $\varphi \in \mathbb{G}$ with $\varphi = \mathbf{G}\psi$ s.t. $\tau[i] \models \psi$ and for all $j \in \mathbb{N}$ $\tau'[j] \not\models \psi$. The case that there exists $j \in \mathbb{N}$ s.t. $\tau'[j] \notin \{\tau[i] \mid i \in \mathbb{N}\}$ is analogous. \blacktriangleleft

B.3 Theorem 22

For all time-prefixed Hypertrace sentences $\varphi \in \text{-FO}[\langle, \mathbb{T}]$ and all sets of traces, T and T' , that are $|\mathcal{I}(\varphi)|$ -point equivalent, $T \approx_{|\mathcal{I}(\varphi)|}^{\text{point}} T'$, where $|\mathcal{I}(\varphi)|$ is the number of time variables in φ , then $T \models \varphi$ iff $T' \models \varphi$.

Proof. We evaluate time-prefixed formulas as in FOL with sorts. We denote by $(\Pi_{\mathbb{N}}, \Pi_T)$ a pair with the assignments for variables over the sort time and the sort of traces, respectively. Wlog, we can assume that the variables can be identified by the position they are quantified. Then, given a k -point equivalence and an assignment over time, $\Pi_{\mathbb{N}}$ that has assignments for the variables $\mathcal{I}(\Pi_{\mathbb{N}}) = \{\pi_1, \dots, \pi_n\}$ with $n \leq k$, then there exists a witness function for the tuple (π_1, \dots, π_n) which we denote by $f_{\Pi_{\mathbb{N}}}$. We prove the theorem by proving the following lemma first:

For all time-prefixed Hypertrace formulas $\varphi \in \text{-FO}[\langle, \mathbb{T}]$ and all sets of traces, T and T' , that are $|\mathcal{I}(\varphi)|$ -point equivalent, $T \approx_{|\mathcal{I}(\varphi)|}^{\text{point}} T'$, where $|\mathcal{I}(\varphi)|$ is the number of time variables in φ , then for all time assignments $\Pi_{\mathbb{N}}$, and for all trace assignments Π_T and $\Pi_{T'}$, which are over $\text{free}(\varphi)$, we have: $(\Pi_{\mathbb{N}}, \Pi_T) \models \varphi$ iff $(\Pi_{\mathbb{N}}, f_{\Pi_{\mathbb{N}}}(\Pi_T)) \models \varphi$; and $(\Pi_{\mathbb{N}}, \Pi_{T'}) \models \varphi$ iff $(\Pi_{\mathbb{N}}, f_{\Pi_{\mathbb{N}}}^{-1}(\Pi_{T'})) \models \varphi$;

We prove this lemma by structural induction on time-prefixed formulas. The induction step for the time prefix part is trivial, as the assignment over time variables in both sides of the implication is the same. For the trace quantifier part, the proof is analogous to Lemma 15. The only difference is the base case, that follows from the definition of k -point equivalence. \blacktriangleleft

B.4 Point Semantics

B.4.1 Lemma 25

$T_n^{\text{point}} \in \mathbf{T}_{\text{point}}^1$ and $T_n'^{\text{point}} \notin \mathbf{T}_{\text{point}}^1$.

Proof. $T \in \mathbf{T}_{\text{point}}^1$ iff for all $i \in \mathbb{N}$:

$$T[i] \in \{M \mid M \models (x(\pi, i) \leftrightarrow x(\pi_{\exists}, i)) \wedge (y(\pi', i) \leftrightarrow y(\pi_{\exists}, i))\}$$

Consider arbitrary $n \in \mathbb{N}$. We represent the valuations in (x, y) .

For all $n+1 < i$, $T_n^{\text{point}}[i] = T_n'^{\text{point}}[i] = \{00\}$.

For all $i < n+1$, $T_n^{\text{point}}[i] = T_n'^{\text{point}}[i] = \{00, 01, 10, 11\}$.

XX:20 Flavours of Sequential Information Flow

As $T_n^{point}[n+1] = \{00, 01, 10, 11\}$, then $T_n^{point} \in \mathbf{T}_{point}^1$. And, as $T_n^{point}[n+1] = \{10, 00\}$, then $T_n^{point} \notin \mathbf{T}_{point}^1$. ◀

B.4.2 Theorem 28

Consider the following time-prefixed hypertrace formula:

$$\begin{aligned} \varphi_{time}^{sync} \stackrel{def}{=} & \exists j \forall i < j \forall k \leq j \forall \pi \forall \pi' \exists \pi_{\exists} \\ & (\neg a(\pi, i) \wedge \neg a(\pi', i) \wedge (x(\pi, i) \leftrightarrow x(\pi_{\exists}, i)) \wedge (y(\pi', i) \leftrightarrow y(\pi_{\exists}, i))) \wedge \\ & (a(\pi, j) \wedge a(\pi', j) \wedge (x(\pi, k) \leftrightarrow x(\pi'_{\exists}, k)) \wedge (z(\pi', k) \leftrightarrow z(\pi'_{\exists}, k))) \end{aligned}$$

Then, $\llbracket \varphi_{time}^{sync} \rrbracket = \mathbf{T}_{point}^{sync}$.

Proof. Note that $T \models \varphi_{time}^{sync}$ iff $T \models \exists j \forall i < j \forall \pi \neg a(\pi, i) \wedge a(\pi, j)$. Thus, it only includes sets of traces with synchronous action.

Additionally, for all T that have synchronous action:

$$\begin{aligned} T \models \varphi_{time}^{sync} \text{ iff } T \models & \exists j \forall i < j \forall \pi \forall \pi' \exists \pi_{\exists} \\ & (\neg a(\pi, i) \wedge \neg a(\pi', i) \wedge (x(\pi, i) \leftrightarrow x(\pi_{\exists}, i)) \wedge (y(\pi', i) \leftrightarrow y(\pi_{\exists}, i))) \wedge a(\pi, j) \\ & \text{and} \\ & T \models \exists j \forall k \leq j \forall \pi \forall \pi' \exists \pi_{\exists} \\ & a(\pi, j) \wedge a(\pi', j) \wedge (x(\pi, k) \leftrightarrow x(\pi'_{\exists}, k)) \wedge (z(\pi', k) \leftrightarrow z(\pi'_{\exists}, k)) \\ \text{iff } T[\dots a] \models & \forall i \forall \pi \forall \pi' \exists \pi_{\exists} (def(\pi, i) \wedge def(\pi', i)) \rightarrow \\ & (def(\pi_{\exists}, i) \wedge (x(\pi, i) \leftrightarrow x(\pi_{\exists}, i)) \wedge (y(\pi', i) \leftrightarrow y(\pi_{\exists}, i))) \\ & \text{and} \\ T[a\dots] \models & \forall k \forall \pi \forall \pi' \exists \pi_{\exists} (def(\pi, k) \wedge def(\pi', k)) \rightarrow \\ & (def(\pi_{\exists}, k) \wedge (x(\pi, k) \leftrightarrow x(\pi_{\exists}, k)) \wedge (z(\pi', k) \leftrightarrow z(\pi_{\exists}, k))). \end{aligned}$$

B.4.3 Lemma 26

For all $n \in \mathbb{N}$, $T_n^{point} \approx_{(n, \mathbb{G})} T_n^{point}$.

Proof. Consider arbitrary $n \in \mathbb{N}$. We define the witness function $f_n : T_n^{point} \rightarrow T_n^{point}$ below:

$$f_n(\tau) = \begin{cases} (00)^n 10 00^\omega & \text{if } \tau = (00)^n 10 10 00^\omega \\ (00)^n 01 00^\omega & \text{if } \tau = (00)^n 01 01 00^\omega \\ \tau & \text{otherwise.} \end{cases}$$

Clearly, this function is both bijective and total.

By definition of f_n and T_n^{point} , then for all assignments of size n over it, $\Pi_{T_n^{point}}$:

- (a) for all $i \neq n+1$, $\langle \Pi_{T_n^{point}} \rangle[i] = \langle f_n(\Pi_{T_n^{point}}) \rangle[i]$; and
- (b) for all $\pi \in \mathcal{V}$, if $\Pi_{T_n^{point}}(\pi) \notin \{(00)^n 10 10 00^\omega, (00)^n 01 01 00^\omega\}$, then $\Pi_{T_n^{point}}(\pi) = f_n(\Pi_{T_n^{point}}(\pi))$.

Analogously for all assignments over T_n^{point} of size n and f^{-1} .

It follows from the definition of T_n^{point} , that for all assignments of size $m < n$ over T_n^{point} , $\Pi_{T_n^{point}}^m$, there exists $0 \leq k < n$ s.t. for all $\pi \in \mathcal{V}$, $\Pi_{T_n^{point}}^m(\pi) \notin \{(00)^k 10 00^\omega, (00)^k 01 00^\omega\}$.

Then, $(\circ) \Pi_{T_n^{point}}^m[k] \in \{\{11\}, \{00\}, \{11, 00\}\}$, because the only way to get valuations 10 and 10 at time k is with the missing traces.

Consider arbitrary $n \in \mathbb{N}$ and assignment over T_n^{point} of size n , $\Pi_{T_n^{point}}$. If for all $\pi \in \mathcal{V}$, $\Pi_{T_n^{point}}(\pi) \notin \{(00)^n 10 10 00^\omega, (00)^n 01 01 00^\omega\}$, then by (b), for all $i \in \mathbb{N}$, $\langle f_n(\Pi_{T_n^{point}}) \rangle[i] = \langle \Pi_{T_n^{point}} \rangle[i]$. Now we assume that there exists $Y = \{\pi_0, \dots, \pi_l\}$, with $0 \leq l < n$ s.t. $\Pi_{T_n^{point}}(\pi) \in \{(00)^n 10 10 00^\omega, (00)^n 01 01 00^\omega\}$, with $\pi \in Y$, and for all $\pi \notin Y$, $\Pi_{T_n^{point}}(\pi) \notin \{(00)^n 10 10 00^\omega, (00)^n 01 01 00^\omega\}$. We can prove from (\circ) that there exists k s.t. $\langle \Pi_{T_n^{point}|Y} \rangle[n+1] = \langle \Pi_{T_n^{point}|Y} \rangle[k]$, where $\Pi_{T_n^{point}|Y}$ is $\Pi_{T_n^{point}}$ without the assignments to the variables in Y . Moreover, it follows as well, that for all $\pi \in Y$, $\langle \Pi_{T_n^{point}} \rangle[k] = 00$, and so there exists k s.t. $\langle f_n(\Pi_{T_n^{point}}) \rangle[n+1] = \langle \Pi_{T_n^{point}} \rangle[k]$. Thus, (\star) for all assignments over T_n^{point} of size n , $\Pi_{T_n^{point}}$ and all $i \in \mathbb{N}$ there exists $j \in \mathbb{N}$ s.t. $\langle f_n(\Pi_{T_n^{point}}) \rangle[i] = \langle \Pi_{T_n^{point}} \rangle[j]$.

By $\langle \Pi_{T_n^{point}} \rangle[n+1] = \langle f_n(\Pi_{T_n^{point}}) \rangle[n]$ and (a), then $(\star\star)$ for all assignments of size n over T_n^{point} , $\Pi_{T_n^{point}}$ and for all $i \in \mathbb{N}$ there exists $j \in \mathbb{N}$ s.t. $\langle \Pi_{T_n^{point}} \rangle[i] = \langle f_n(\Pi_{T_n^{point}}) \rangle[j]$.

By (\star) and $(\star\star)$, for all assignments of size n over T_n^{point} , $\Pi_{T_n^{point}}$, we have $\langle \Pi_{T_n^{point}} \rangle[i] \approx_{\mathbb{G}} \langle f_n(\Pi_{T_n^{point}}) \rangle[j]$.

We prove analogously that for all assignments of size n over T_n^{point} , $\Pi_{T_n^{point}}$, we have $\langle \Pi_{T_n^{point}} \rangle[i] \approx_{\mathbb{G}} \langle f_n^{-1}(\Pi_{T_n^{point}}) \rangle[j]$. \blacktriangleleft

B.4.4 Lemma 26

For all $n \in \mathbb{N}$, $T_n^{point} \approx_{(n, \mathbb{G})} T_n^{point}$.

Proof. Consider arbitrary $n \in \mathbb{N}$. We define the witness function $f_n : T_n^{point} \rightarrow T_n^{point}$ below:

$$f_n(\tau) = \begin{cases} (00)^n 10 (00)^\omega & \text{if } \tau = (00)^n 10 10 (00)^\omega \\ (00)^n 01 (00)^\omega & \text{if } \tau = (00)^n 01 01 (00)^\omega \\ \tau & \text{otherwise.} \end{cases}$$

Clearly, this function is both bijective and total.

We need to prove that for all assignments over T_n^{point} and T_n^{point} of size k , $\Pi_{T_n^{point}}$ and $\Pi_{T_n^{point}}$, we have: $\langle \Pi_{T_n^{point}} \rangle \approx_{\mathbb{G}} \langle f(\Pi_{T_n^{point}}) \rangle$ and $\langle \Pi_{T_n^{point}} \rangle \approx_{\mathbb{G}} \langle f^{-1}(\Pi_{T_n^{point}}) \rangle$. Recall that $\langle \Pi_{T_n^{point}} \rangle \approx_{\mathbb{G}} \langle f(\Pi_{T_n^{point}}) \rangle$ iff $\{\langle \Pi_{T_n^{point}} \rangle[i] \mid i \in \mathbb{N}\} = \{\langle f(\Pi_{T_n^{point}}) \rangle[j] \mid j \in \mathbb{N}\}$.

The interesting case is the time $n+1$ for assignments to the traces that are different in T_n^{point} and T_n^{point} . We show below that for all assignment over T_n^{point} of size n , there exists a time k that has the same valuations in the flattened assignment at time $n+1$.

Consider an arbitrary $n \in \mathbb{N}$ and assignment over T_n^{point} of size n , $\Pi_{T_n^{point}}$. Assume there exists $Y = \{\pi_0, \dots, \pi_l\}$, with $0 \leq l < n$ s.t. $\Pi_{T_n^{point}}(\pi) \in \{(00)^n 10 10 (00)^\omega, (00)^n 01 01 (00)^\omega\}$, with $\pi \in Y$, and for all $\pi \notin Y$, $\Pi_{T_n^{point}}(\pi) \notin \{(00)^n 10 10 (00)^\omega, (00)^n 01 01 (00)^\omega\}$.

For all assignments of size $m < n$ over T_n^{point} , $\Pi_{T_n^{point}}^m$, there exists $0 \leq k < n$ s.t. for all $\pi \in \mathcal{V}$, $\Pi_{T_n^{point}}^m(\pi) \notin \{(00)^k 10 (00)^\omega, (00)^k 01 (00)^\omega\}$. Note that we have n possible combinations for such pairings. Then, $(\bullet) \Pi_{T_n^{point}}^m[k] \in \{\{11\}, \{00\}, \{11, 00\}\}$, because the only way to get valuations 10 and 10 at time k is with the missing traces. Then, there exists k s.t. $\langle \Pi_{T_n^{point}|Y} \rangle[n+1] = \langle \Pi_{T_n^{point}|Y} \rangle[k]$, where $\Pi_{T_n^{point}|Y}$ is $\Pi_{T_n^{point}}$ without the assignments to the variables in Y . Moreover, it follows as well, that for all $\pi \in Y$, $\langle \Pi_{T_n^{point}} \rangle[k] = 00$. So, there exists k s.t. $\langle f_n(\Pi_{T_n^{point}}) \rangle[n+1] = \langle \Pi_{T_n^{point}} \rangle[k]$. Thus, (\star) for all assignments over T_n^{point} of size n , $\Pi_{T_n^{point}}$ and all $i \in \mathbb{N}$ there exists $j \in \mathbb{N}$ s.t. $\langle f_n(\Pi_{T_n^{point}}) \rangle[i] = \langle \Pi_{T_n^{point}} \rangle[j]$. \blacktriangleleft

B.5 Segment Semantics

B.5.1 Theorem 29

Consider the following HyperLTL formula:

$$\varphi_{seg}^{sync} \stackrel{def}{=} \forall \pi \forall \pi' \exists \pi_{\exists} \exists \pi'_{\exists} (-a_{\pi} \wedge \neg a_{\pi'} \wedge x_{\pi} = x_{\pi_{\exists}} \wedge y_{\pi'} = y_{\pi'_{\exists}}) \mathbf{U} (a_{\pi} \wedge a_{\pi'} \wedge \Box (x_{\pi} = x_{\pi_{\exists}} \wedge z_{\pi'} = z_{\pi'_{\exists}}))$$

Then, $\llbracket \varphi_{seg}^{sync} \rrbracket = \mathbf{T}_{seg}^{sync}$.

Proof. Note that $x(\pi, i) \leftrightarrow x(\pi_{\exists}, i)$ in Hypertrace Logic corresponds to $x_{\pi} = x_{\pi_{\exists}}$ in HyperLTL. By Definition 10, $T \in \mathbf{T}_{seg}^{sync}$ iff: (i) $T \models \exists i \forall \pi \min(\tau, a, i)$; (ii) $T[\dots a] \models ind_{seg}(x, y)$; and (iii) $T[a\dots] \models ind_{seg}(x, z)$. Then, by HyperLTL satisfaction, for all set of traces T :

$$\begin{aligned} T \models \varphi_{seg}^{sync} &\text{ iff} \\ T \models \forall \pi \forall \pi' (-a_{\pi} \wedge \neg a_{\pi'}) \mathbf{U} (a_{\pi} \wedge a_{\pi'}), \\ T \models \forall \pi \forall \pi' \exists \pi_{\exists} (-a_{\pi} \wedge \neg a_{\pi'} \wedge x_{\pi} = x_{\pi_{\exists}} \wedge y_{\pi'} = y_{\pi'_{\exists}}) \mathbf{U} (a_{\pi} \wedge a_{\pi'}), \text{ and} \\ T \models \forall \pi \forall \pi' \exists \pi'_{\exists} (-a_{\pi} \wedge \neg a_{\pi'}) \mathbf{U} (a_{\pi} \wedge a_{\pi'} \wedge \Box (x_{\pi} = x_{\pi_{\exists}} \wedge z_{\pi'} = z_{\pi'_{\exists}})). \end{aligned}$$

We can prove, by satisfaction for HyperLTL and Hypertrace Logic formulas, that:

$$T \models_H \forall \pi \forall \pi' (-a_{\pi} \wedge \neg a_{\pi'}) \mathbf{U} (a_{\pi} \wedge a_{\pi'}) \text{ iff } T \models \exists i \forall \pi a(\pi, i) \wedge \forall 0 \leq j < i \neg a(\pi, j)$$

Hence $\llbracket \varphi_{seg}^{sync} \rrbracket = \mathbf{T}_{seg}^{sync}$. ◀

B.5.2 Lemma 32

$$T_n^{async} \in \mathbf{T}_{seg}^{async}, T_n^{rasync} \notin \mathbf{T}_{point}^{async} \text{ and } T_n^{rasync}|_a \notin \mathbf{T}_{point}^{hidden}.$$

Proof. We start by proving $T_n^{async} \in \mathbf{T}_{seg}^{async}$.

First, we prove that $T_n^{async}[\dots a] \models ind_{seg}(x, y)$. By definition of slicing of sets of traces:

$$T_n^{async}[\dots a] = \{0000, 0010, (0000)^{n+4}, (0010)^{n+4}\}.$$

Then, by Definition 7, $T_n^{async}[\dots a] \models ind_{seg}(x, y)$ holds because we can choose $\pi_{\exists} = \pi'$.

Now, we prove that $T_n^{async}[a\dots] \models ind_{seg}(x, z)$. By definition of slicing of sets of traces, $T_n^{async}[a\dots] = \{\tau_0(1000)^{\omega}, \tau_1(1000)^{\omega}, \tau_0(1110)^{\omega}, \tau_1(1000)^{n+4}(1110)^{\omega}\}$, where τ_0 and τ_1 are as in Definition 30. Then, as in the previous case, we can choose $\pi_{\exists} = \pi'$ to show that $T_n^{async}[a\dots] \models ind_{seg}(x, z)$ holds.

We prove now that $T_n^{rasync} \notin \mathbf{T}_{point}^{async}$.

We show that $T_n^{rasync}[\dots a] \not\models ind_{point}(x, z)$. By Definition 30 and definition of slicing:

$$\begin{aligned} t'_1[a\dots] &= t_1[1]t_1[2] \dots t_1[2n+10]t_1[2n+12] \dots \\ &= \tau_1[0]\tau_1[1] \dots \tau_1[2n+9]\tau_1[2n+11] \dots \\ &= t'_2[a\dots] \\ t'_3[a\dots] &= t_3[n+4]t_3[n+5] \dots t_3[2n+10]t_3[2n+12] \dots \\ &= \tau_0[0]\tau_1[1] \dots \tau_0[n+6]\tau_0[n+8] \dots \\ &= t'_4[a\dots] \end{aligned}$$

Note that, $2n+10 - (n+4) = n+6$.

Note that (\star) $(t'_1[a\dots])[2n+9] = (t'_2[a\dots])[2n+9] = 1000$ and $(t'_3[a\dots])[2n+9] = (t'_4[a\dots])[2n+9] = 1111$. If we chose $i = 2n+9$, $\pi = t'_3$ and $\pi' = t'_1$, then there should exist

a trace $t_{\exists} \in T_n'^{async}$ s.t. $(t_{\exists}[a\dots])[2n+9](x) = (t'_3[a\dots])[2n+9](x) = 1$ and $(t_{\exists}[a\dots])[2n+9](z) = (t'_1[a\dots])[2n+9](z) = 0$. However, by (*) we know that there is not such trace in $T_n'^{async}$. Hence $T_n'^{async} \not\subseteq \mathbf{T}_{point}^{async}$.

The set of set of traces $T_n'^{async}|_a$ is the set $T_n'^{async}$ where all valuations of a are removed. We need to prove that there is no extension of $T_n'^{async}|_a$ with (possibly new) valuations in a that makes it an element of $\mathbf{T}_{point}^{hidden}$. We will abstract the extension of $T_n'^{async}|_a$ by defining a function $g: T_n'^{async}|_a \rightarrow \mathbb{N}$ that given a set of traces in $T_n'^{async}|_a$ returns the index where a first holds. We then redefine the slicing operator to slice w.r.t. this function, as follows: $T[\dots g] = \{\tau[\dots g(\tau)] \mid \tau \in T\}$.

We refer to the elements of $T_n'^{async}|_a$ by the same names as in the definition of $T_n'^{async}$. By construction of $T_n'^{async}|_a$, the function g needs to guarantee the following conditions for $T[\dots g] \models \text{ind}_{point}(x, y)$ to hold: $g(t'_1) \leq 5n+23$ and $g(t'_3) \leq 5n+23$, because $t'_1[5n+23] = 000 = t'_3[5n+23]$ and $t'_2[4n+23] = 111 = t'_4[5n+23]$. So, we are missing valuations 10 and 01 in (x, y) , to prove the independence of y w.r.t. x .

If $g(t'_1) = g(t'_2) = g(t'_3) = g(t'_4) = 1$, then $T[g\dots] \not\models \text{ind}_{point}(x, z)$, because $T_n'^{async}|_a[1] = \{000, 010, 111\}$ and so we are missing the valuation 01 in (x, z) .

We proceed by case analysis.

Case $g(t'_3) = g(t'_4) = 1$: We show below the first $n+4$ steps of the slice of t'_3 and t'_4 :

$$\begin{aligned}\tau'_3[1\dots n+4] &= (000)^{n+3} 110 \\ \tau'_4[1\dots n+4] &= (010)^{n+3} 110\end{aligned}$$

To find a compatible slicing of t'_1 and t'_2 we need it to satisfy the following:

- for the first $n+3$ we can only have the valuation 00 in (x, z) , as there is no time point where we can get at the same time 10 and 11;
- at the $n+4$ we cannot have 01 as it is not possible with only one trace left cover all the valuations missing (00 and 11).

Then, the time $n+7$ is the only slicing of t'_1 and t'_2 that satisfies this conditions and guarantees that x is independent of z for the first $n+4$ elements of the slicing suffix, as we show below:

$$\begin{aligned}\tau'_1[n+7\dots 2n+10] &= (000)^{n+3} 110 \\ \tau'_2[n+7\dots 2n+10] &= (000)^{n+3} 110 \\ \tau'_3[1\dots n+4] &= (000)^{n+3} 110 \\ \tau'_4[1\dots n+4] &= (010)^{n+3} 110\end{aligned}$$

However, if $g(t'_1) = g(t'_2) = n+7$, then $\tau'_1[4n+20] = \tau'_2[4n+20] = 000$ while $\tau'_3[3n+13] = \tau'_4[3n+13] = 111$. So, we are missing valuations 01 and 10 in (x, z) . Hence, for $g(t'_3) = g(t'_4) = n+7$, $T[g\dots] \not\models \text{ind}_{point}(x, z)$. So, $g(t'_3) = g(t'_4) > 1$.

Case $g(t'_1) = g(t'_2) > 1$: As $g(t'_3) = g(t'_4) > 1$, then the prefix of a slicing with $g(t'_1) = g(t'_2) > 1$ does not satisfy $\text{ind}_{point}(x, y)$. Note that $t'_1[1] = t'_2[1] = 111$ while $t'_3[1] = 000$ and $t'_4[1] = 010$, so we are missing the valuation 10 in (x, y) . Hence $g(t'_1) = g(t'_2) = 1$.

Case $1 < g(t'_3) \leq 5n+23$ and $1 < g(t'_4) \leq 5n+23$: If $g(t'_3) < n+4$ and $g(t'_4) < n+4$, then we will be missing the assignment 01 in (x, z) . If $g(t'_3) = n+4 = g(t'_4)$, then we know from the case with visible action that the property does not hold. If $n+4 < g(t'_3) < 2n+9$ and $n+4 < g(t'_4) < 2n+9$, then we will be missing the assignment 01 in (x, z) . If either $g(t'_3) = 2n+9$, then $g(t'_4)[2n+9\dots(2n+9)+3n+12] = 111$ while $g(t'_1)[1\dots 3n+13] = 000$ and we will be missing the assignment 10 on (x, z) . Then, $g(t'_3) \neq 2n+9$ because the suffix of the

trace starts with 000, so there will be not enough traces to cover for observation 111. The same reasoning holds for the next 3 positions. The next $2n + 9$ positions cover the deleted letter from t'_1 and t'_2 , while the deleted letter from t'_3 and t'_4 happens in a earlier part of the trace. So, the position $2n + 11$ of t'_1 and t'_2 , with assignment 110, will miss the assignment 11 on (x, z) . Note that at that point in the slice of t'_3 and t'_4 z is constantly 1. ◀

B.5.3 Lemma 31.

For all assignments Π over T_n^{async} , the valuation at $2n + 11$ is n -redundant in the trace $\langle \Pi \rangle$.

Proof. We prove this by induction on the size of trace assignments Π over T_n^{async} .

Base case $|\Pi| = 1$: Wlog, let $\mathcal{V}(\Pi) = \{\pi\}$ for some $\pi \in \mathcal{V}$.

If $\Pi(\pi) \in \{t_1, t_2\}$, then at $2n + 11$ we have the block $(1001)^{n+4}$. Hence $t_1[2n + 11] = t_1[2n + 11 + j]$ for all $1 \leq j \leq n + 1$.

If $\Pi(\pi) \in \{t_3, t_4\}$, then at $2n + 10$ we have the block $(1000)^{n+4}$. Hence $t_2[2n + 11] = t_1[2n + 11 + j]$ for all $1 \leq j \leq n + 1$.

Inductive case: Assume as induction hypothesis (IH) that the statement holds for all assignments of size k .

Consider an arbitrary assignment Π_{k+1} with size $k + 1$. Then, there exists an assignment Π_k with size k s.t. $\Pi_{k+1} = \Pi_k[\pi \mapsto \tau]$ and $\Pi_k(\pi)$ is undefined, for some $\pi \in \mathcal{V}$ and $\tau \in T_n^{async}$. By (IH), the valuation at position $2n + 11$ in $\langle \Pi_k \rangle$ is n -redundant. As argued in the base case, the letter at position $2n + 11$ for all $\tau \in T_n^{async}$ is n -redundant, as well.

As $\Pi_k(\pi)$ is undefined, then $\langle \Pi_{k+1}[\pi \mapsto \tau] \rangle = \langle \Pi_k \rangle \otimes \langle \Pi^\emptyset[\pi \mapsto \tau] \rangle$ where \otimes is the composition of traces. Then, by the $2n + 1$ letter being n -redundant in both $\langle \Pi_k \rangle$ and τ , it follows that the letter at $2n + 11$ in $\langle \Pi_{k+1}[\pi \mapsto \tau] \rangle$ is n -redundant, as well. ◀