
Meta-Cal: Well-controlled Post-hoc Calibration by Ranking

Xingchen Ma¹ Matthew B. Blaschko¹

Abstract

In many applications, it is desirable that a classifier not only makes accurate predictions, but also outputs calibrated probabilities. However, many existing classifiers, especially deep neural network classifiers, tend not to be calibrated. Post-hoc calibration is a technique to recalibrate a model, and its goal is to learn a calibration map. Existing approaches mostly focus on constructing calibration maps with low calibration errors. Contrary to these methods, we study post-hoc calibration for multi-class classification under constraints, as a calibrator with a low calibration error does not necessarily mean it is useful in practice. In this paper, we introduce two practical constraints to be taken into consideration. We then present Meta-Cal, which is built from a base calibrator and a ranking model. Under some mild assumptions, two high-probability bounds are given with respect to these constraints. Empirical results on CIFAR-10, CIFAR-100 and ImageNet and a range of popular network architectures show our proposed method significantly outperforms the current state of the art for post-hoc multi-class classification calibration.¹

1. Introduction

Recent advances in machine learning have resulted in very high accuracy in many classification tasks. In the context of computer vision, there has been a steady increase in top-1 accuracy on ImageNet (Russakovsky et al., 2015) since AlexNet (Krizhevsky et al., 2012). While highly accurate models are desirable in general, in some applications, we want that the output of a classifier is a calibrated posterior probability. This is especially important in cost-sensitive classification tasks, such as medical diagnosis (Ma et al., 2017) and autonomous driving (Chen et al., 2015).

¹ESAT-PSI, KU Leuven, Belgium. Correspondence to: Xingchen Ma <xingchen.ma@esat.kuleuven.be>.

¹Code is available at <https://github.com/maxc01/metacal>

The goal of classification calibration is to obtain a probabilistic model that has low calibration error. A formal definition of calibration error will be given in Section 3. To achieve this objective, one can design models with intrinsically low calibration errors. These models (Wilson et al., 2016; Pereyra et al., 2017; Lakshminarayanan et al., 2016; Malinin & Gales, 2018; Miliotis et al., 2018; Maddox et al., 2019) are usually developed with a Bayesian nature and tend to be expensive to train and make inferences. On the other end of the spectrum, a post-hoc calibration method transforms outputs of an existing classification model into well-calibrated predictions by learning a trainable post-processing step. Given the design difficulties and computational burdens of the former approach, we focus on post-hoc multi-class calibration in this paper.

Among the existing literature on post-hoc calibration, some methods (Zhang et al., 2020; Guo et al., 2017; Ding et al., 2020; Patel et al., 2020) seek calibration maps that preserve classification accuracy, while some other works (Wenger et al., 2020; Kull et al., 2019) focus more on calibration error without explicitly enforcing accuracy-preservation. Compared with the latter, there is no potential accuracy drop in the former, but its family of calibration maps is less flexible. We will formalize the limitation of such a family by giving a lower bound of its calibration error in Proposition 2. In this work, we try to get the best of both worlds by combining an existing calibration model with a bipartite ranking model, and we call our proposed post-hoc calibration method *Meta-Cal*.

Similar to previous works (Wenger et al., 2020; Kull et al., 2019), Meta-Cal does not preserve the overall accuracy. However, in contrast with these methods, Meta-Cal has full control over two practical constraints: (i) the miscoverage rate and (ii) coverage accuracy. Their definitions are given in Section 4. If the base calibration model used to construct Meta-Cal preserves the overall accuracy, it is guaranteed that Meta-Cal has an improved calibration error bound over this base calibrator.

The main contributions of this paper are: (i) We develop a post-hoc calibration method for multi-class classification that augments a base calibration method and improves its calibration performance. (ii) We investigate two practical constraints that should be considered when developing post-

hoc calibration methods that do not preserve accuracy of the original classifier. (iii) We show how these constraints are incorporated in constructing our proposed calibrator and we present theoretical guarantees on these constraints. (iv) We show the effectiveness of our proposed approach and validate our theoretical claims through a series of empirical experiments.

In the next section, we briefly review post-hoc calibration methods for classification and bipartite ranking models. Necessary background, notation and assumptions that will be used in this paper are given in Section 3. In Section 4, we describe our proposed method, Meta-Cal. Two practical constraints that should be considered together with calibration are discussed in Section 4.1 and Section 4.2 respectively. Empirical results are presented in Section 5. Finally, we conclude in Section 6.

2. Related Work

Post-hoc Calibration of Classifiers: Platt scaling (Platt, 1999; Lin et al., 2007) is proposed to learn a calibration transformation to map the outputs of a binary SVM into posterior probabilities. Extensions of Platt scaling for multi-class calibration include temperature scaling (Guo et al., 2017), ensemble temperature scaling (Zhang et al., 2020) and local temperature scaling (Ding et al., 2020). Different from the parametric approach adopted by Platt scaling, histogram binning (Zadrozny & Elkan, 2001) is a non-parametric post-hoc calibration method in binary settings. Two popular refinements of histogram binning are isotonic regression (Zadrozny & Elkan, 2002) and Bayesian binning into quantiles (Naeini et al., 2015). Beta calibration (Kull et al., 2017) is motivated by noticing that Platt scaling assumes scores of each class are Gaussian distributed, however, this assumption is not satisfied for many probabilistic classifiers. To handle this assumption violation, Beta calibration assumes Beta distribution of scores within each class. For multi-class classification, Dirichlet calibration (Kull et al., 2019) is proposed as an extension of Beta calibration. More recently, a Gaussian Process based calibration method (Wenger et al., 2020) is proposed.

Bipartite Ranking: The problem of bipartite ranking has been studied for a long time. In bipartite ranking, one wants to compare or rank two different objects and decide which one is better. Burges et al. (2005) use a neural network to model a ranking function and trains this network by gradient decent methods. Cl emen on et al. (2008) define a statistical framework for such ranking problems and provide some consistency results. Narasimhan & Agarwal (2013) investigate the relationship between binary classification and bipartite ranking. Our work is closely related to Narasimhan & Agarwal (2013) and we rely on the theoretical results presented there to construct a binary class probability esti-

mation (CPE) model from a ranking model.

Selective Classification: Selective classification is a technique that augments a classifier with a reject option and its essence is the trade-off between coverage and accuracy. El-Yaniv & Wiener (2010) lay the foundation for selective classification by characterizing the theoretical and practical boundaries of risk-coverage trade-offs. Geifman & El-Yaniv (2017) apply selective classification to deep neural networks. While the starting point of our work is to make improvements in post-hoc classification calibration under several practical constraints, it turns out that techniques present in this work can also be used in selective classification. Geifman & El-Yaniv (2017) present a one-sided and tight high-probability risk bound. In our work, we give a high probability bound for miscoverage rate and a high probability bound for coverage accuracy. It should be noted that the definitions of risk and coverage in our setting are different from these two metrics defined in the context of selective classification (El-Yaniv & Wiener, 2010; Geifman & El-Yaniv, 2017), thus these bounds are not directly comparable.

3. Problem Formulation

In this section, we summarize some necessary background, notation and assumptions that will be used throughout this paper. Let \mathcal{X} be the input space and $\mathcal{Y} = [k] = \{1, \dots, k\}$ be the label space in multi-class classification. We denote the $(k-1)$ -simplex by $\Delta^k := \{(p_1, \dots, p_k) \mid \sum_{i \in [k]} p_i = 1, p_i \in [0, 1]\}$. Suppose we are given a probabilistic classifier $f : \mathcal{X} \rightarrow \Delta^k$ and this classifier is trained on an i.i.d. data set following a joint distribution $\mathbb{P}(X, Y)$ on $\mathcal{X} \times \mathcal{Y}$. Let the random variable X take values in input space \mathcal{X} , $Z = (Z_1, \dots, Z_k)$ be the output of f applied to X , $\hat{Z} = \max_{i \in [k]} Z_i$ be the confidence score and $\hat{Y} = \arg \max_{i \in [k]} Z_i$ be the prediction of X . Whenever there is a tie, it is broken uniformly at random. To measure the level of calibration, following Naeini et al. (2015); Kumar et al. (2019); Wenger et al. (2020), the calibration error is defined in Definition 1.

Definition 1 (Calibration error). The L_p calibration error of f with $p \geq 1$ is:

$$\text{CE}_p(f) = \mathbb{E} \left[\left| \mathbb{E} \left(\mathbb{1}(Y = \hat{Y}) \mid \hat{Z} \right) - \hat{Z} \right|^p \right]^{1/p}, \quad (1)$$

where the expectation is taken with respect to $\mathbb{P}(X, Y)$.

If the calibration error of a model f is zero, we say f is perfectly calibrated. In practice, $\text{CE}_p(\cdot)$ is unobservable since it depends on the unknown joint distribution $\mathbb{P}(X, Y)$. To empirically estimate the calibration error based on a finite data set, prior works apply a fixed binning scheme $B \in \mathcal{B}$, where \mathcal{B} is the family of binning schemes, on values of \hat{Z}

and calculate the difference between the accuracy and the average of confidence scores in every bin. An example family for a binning scheme is a partition of the interval $[0, 1]$. When $p = 1$, the calibration error is also known as *expected calibration error* (ECE) (Guo et al., 2017) and an empirical estimator based on B is denoted by $\widehat{\text{ECE}}_B$. Although it is known that $\widehat{\text{ECE}}_B$ is a biased estimation (Kumar et al., 2019; Zhang et al., 2020) of ECE and its magnitude can be hard to interpret, in this work, we use this binned estimator to measure the level of calibration due to its simplicity and popularity. We note our high probability bounds for miscoverage rate and coverage accuracy do not depend on ECE and its estimator.

In the post-hoc calibration problem, one wants to find a function that transforms the outputs of f to make the final model better calibrated. Formally, a calibration map is a function $g : \Delta^k \rightarrow \Delta^k$. The goal is to learn a mapping $g \in \mathcal{G}$ on a finite calibration data set $\{(x_i, y_i)\}_{i=1}^n$ that is drawn i.i.d. from the joint distribution $\mathbb{P}(X, Y)$ so that the composition $g \circ f$ has a small calibration error, where \mathcal{G} is the calibration family.

In the problem of bipartite ranking, we want to find a ranking model $h : \mathcal{X} \rightarrow \mathbb{R}$ that ranks positive examples and negative ones so that the positive examples have higher scores with a high probability. Formally, one wants to minimize the following *ranking risk* (Narasimhan & Agarwal, 2013; Cl  men  on et al., 2008):

$$L(f) = \mathbb{P}((\epsilon - \epsilon') \cdot (h(X) - h(X'))),$$

where $(X, \epsilon), (X', \epsilon')$ are i.i.d. pairs taking values in $\mathcal{X} \times \{-1, +1\}$. The ranking risk is the probability that h ranks two randomly drawn pairs incorrectly (Cl  men  on et al., 2008). In this paper, if not stated otherwise, the random variable ϵ is a sign variable used to indicate whether X is correctly classified or not by f , that is, $\epsilon = 2 \cdot \mathbb{1}(Y \neq \hat{Y}) - 1$. In general, a bipartite ranking model is learnt using a consistent pairwise surrogate loss, such as exponential loss or logistic loss (Gao & Zhou, 2014).

In the following, we list some assumptions that will be used in Section 4.

Assumption 1. Denote the marginal distribution of X taking values in \mathcal{X} by $\mathbb{P}(X)$. The induced distribution of $h(X)$ is continuous.

Assumption 2. Let $h : \mathcal{X} \rightarrow [a, b]$ (where $a, b \in \mathbb{R}, a < b$) be any bounded-range ranking model. $\eta_h(s) = \mathbb{P}(\epsilon = 1 | h(x) = s)$ is square-integrable w.r.t. the induced density of $h(X)$.

4. Meta-Cal

In the following section, we start by showing the family of accuracy-preserving calibration maps has an inherent

limitation (Proposition 2) and this motivates us to combine a bipartite ranking model with an existing calibration model. Then we demonstrate that models with low calibration errors alone do not necessarily mean they are practical. Post-hoc calibration should be considered together with other factors. In this work, we investigate two useful constraints in Section 4.1 and Section 4.2, respectively: Miscoverage rate control and coverage accuracy control.

Proposition 2 (Lower bound of ECE). Define \mathcal{G}_a as the family of accuracy-preserving calibration maps, that is,

$$\mathcal{G}_a = \{g \in \mathcal{G} : \arg \max_{i \in [k]} f(X)_i = \arg \max_{i \in [k]} g(f(X))_i\}.$$

Then for all $g \in \mathcal{G}_a$

$$\sup_{B \in \mathcal{B}} \widehat{\text{ECE}}_B(g \circ f) > \frac{1 - \hat{\pi}_0}{k}, \quad (2)$$

where $\hat{\pi}_0$ is the empirical accuracy of f on a finite data set. Further we can show $\forall B \in \mathcal{B}, \forall g \in \mathcal{G}$,

$$\text{ECE}(g \circ f) \geq \widehat{\text{ECE}}_B(g \circ f). \quad (3)$$

All proofs are provided in ?? and we only describe a sketch of the proof here. The first step is to find the supremum of the binned estimator $\widehat{\text{ECE}}_B(g \circ f)$ across all calibration maps $g \in \mathcal{G}_a$ and all binning schemes $B \in \mathcal{B}$. This is achieved using Minkowski’s inequality. The second step is showing this supremum is lower bounded by $(1 - \hat{\pi}_0)/k$ by applying the Cauchy-Schwarz inequality. Unless f is perfectly accurate, $(1 - \hat{\pi}_0)/k$ will be strictly positive. The last step is already given in Kumar et al. (2019) by applying Jensen’s inequality. We note bounding $\widehat{\text{ECE}}_B(g \circ f)$ instead of its supremum makes little sense here since it is easy to construct a trivial $g \in \mathcal{G}_a$ and a binning scheme B such that $\widehat{\text{ECE}}_B(g \circ f)$ is exactly zero. In ??, we give such a trivial construction. Proposition 2 makes it clear that an accuracy-preserving calibration has an inherent limitation. Even given the label information, such a calibration map cannot perfectly calibrate a classifier. To avoid potential confusion, we emphasize here the empirical estimator of ECE measures the top-label calibration error instead of the calibration error w.r.t. a fixed class.

In the following proposition, we show if a post-hoc calibration map is allowed to change the accuracy of the original classifier, it can achieve perfect calibration with the aid of a binary classifier.

Proposition 3 (Optimal calibration map). Suppose realizations of $X | Y \neq \hat{Y}$ with positive labels and realizations of $X | Y = \hat{Y}$ with negative labels are separable and we are given a perfect binary classifier $\phi^* : \mathcal{X} \rightarrow \{-1, +1\}$ that is able to classify these two sets. For a new observation $x \sim X$, an optimal calibration map $g^* \in \mathcal{G}$ that minimizes

$\sup_{B \in \mathcal{B}, g \in \mathcal{G}} \widehat{\text{ECE}}_B(g \circ f)$ can be constructed using the following rules:

- if $\phi^*(x) = -1$, we let $\max_{i \in [k]} g^*(x)_i = 1$
- if $\phi^*(x) = +1$, we let $\max_{i \in [k]} g^*(x)_i = \frac{1}{k}$

Proof. The optimality of g^* follows directly from the proof steps of Proposition 2. \square

We note $g^* \notin \mathcal{G}_a$, since the used tie-breaking strategy is random at uniform, thus g^* does not preserve the accuracy after the above calibration. It is straightforward to check the constructed g^* in Proposition 3 has zero calibration error, that is $\text{ECE}(g^* \circ f) = \sup_{B \in \mathcal{B}} \widehat{\text{ECE}}_B(g^* \circ f) = 0$.

However, it is unlikely that a perfect binary classifier can be obtained in practice and classification errors will occur when $\phi(X) \neq 2 \cdot \mathbb{1}(Y \neq \hat{Y}) - 1$. We denote the Type I error (false positive error) and Type II error (false negative error) of ϕ by $R_0(\phi)$ and $R_1(\phi)$ respectively. In the following, we define the *miscoverage rate* and *coverage accuracy* of a calibration map g constructed using the rules in Proposition 3. These two constraints will be used in the final calibration map.

Definition 4 (Miscoverage rate). The miscoverage rate $F_0(g)$ of g constructed using the rules in Proposition 3 is defined to be the Type I error of the binary classifier ϕ associated with g .

Definition 5 (Coverage accuracy). The coverage accuracy $F_1(g)$ of g constructed using the rules in Proposition 3 is defined to be the precision of the binary classifier ϕ associated with g .

The miscoverage rate of g is the proportion of instances whose predictions are no longer correct after the calibration to instances whose predictions are originally correct before the calibration. The coverage accuracy of g is the accuracy among covered instances (i.e. those instances classified as negative by the binary classifier) after the calibration. The correspondence between the Type I error (precision) of a binary classifier and the miscoverage rate (coverage accuracy) of a calibration map is due to the construction rules in Proposition 3.

Proposition 6. *Using the construction rules in Proposition 3, we can estimate the expected calibration error of g on a finite data set:*

$$\sup_{B \in \mathcal{B}} \widehat{\text{ECE}}_B(g \circ f) = \hat{R}_1(\phi) \cdot (1 - \hat{\pi}_0),$$

where $\hat{R}_1(\phi)$ is the empirical Type II error of ϕ which is trained following Proposition 3, g is constructed using the rules in Proposition 3 and $\hat{\pi}_0$ is the empirical accuracy of f on this finite data set.

Under the above settings, it is easy to construct trivial calibration maps with low calibration errors and we describe two such constructions:

High miscoverage rate: From Proposition 6, we build a binary classifier with a low Type II error and a potentially high Type I error, thus the miscoverage rate is also potentially high. Such a binary classifier is always possible. For example, we can select a small portion among negative instances and relabel the remaining instances as positive.

Low coverage accuracy: Regardless of the input, we let the output of a calibration map to be the marginal class distribution. The calibration error of this calibration map is equal to 0, but its coverage accuracy is low and equal to the proportion of the largest class.

Obviously, the above two constructions are not useful in practice and we should consider a post-hoc calibration map either with a low miscoverage rate or with a high coverage accuracy. An intuitive example demonstrating the usefulness these two constraints is an automated decision model with human-in-the-loop (HIL). In such a model, on one hand, it is desirable that human interaction is as minimal as possible (low miscoverage rate). On the other hand, we hope this model can make accurate and reliable decisions (high coverage accuracy). We now describe how to construct a calibration map with a controlled miscoverage rate or a controlled coverage accuracy.

4.1. Miscoverage Rate Control

To control the miscoverage rate of our proposed calibration method, we need to construct a suitable binary classifier with a controlled Type I error. Such a classifier can be built using the following steps. Given a finite calibration data set $\{(x_i, y_i)\}_{i=1}^n$ that is drawn i.i.d. from the joint distribution $\mathbb{P}(X, Y)$ on $\mathcal{X} \times \mathcal{Y}$, we first create a binary classification data set $\{(x_i, 2 \cdot \mathbb{1}(y_i \neq \hat{y}_i) - 1)\}_{i=1}^n$, where $\hat{y}_i = \arg \max_{i \in [k]} f(x_i)$. Without loss of generality, we suppose the first n_1 inputs have negative labels and the last n_2 inputs have positive labels, where $n = n_1 + n_2$. Then we compute ranking scores on first n_1 inputs using a ranking model h and denote these ranking scores as $\{r_i\}_{i=1}^{n_1}$, where $r_i = h(x_i)$. Given a miscoverage rate tolerance α , the desired binary classifier is constructed by $\hat{\phi}(x) = 2 \cdot \mathbb{1}(h(x) > r_{(v)}) - 1$, where $v = \lceil (n_1 + 1)(1 - \alpha) \rceil$, $r_{(v)}$ is the v -th order statistic of $\{r_i\}_{i=1}^{n_1}$, that is, $r_{(1)} < \dots < r_{(n_1)}$. We note here $\mathbb{P}(r_i = r_j) = 0, \forall i, j \in [n_1]$ under Assumption 1. In Proposition 7, we show the Type I error of this constructed binary classifier is well-controlled, thus the miscoverage rate of our calibration method is also well-controlled.

Proposition 7 (Miscoverage rate control). *Under Assumption 1, given a finite test data set of size m that is i.i.d. drawn from $\mathbb{P}(X, Y)$, the empirical miscoverage rate $\hat{F}_0(g)$*

of g on D is well-controlled:

$$\begin{aligned} \mathbb{P}\left(\left|\hat{F}_0(g) - F_0(g)\right| \geq t\right) &\approx \mathbb{P}\left(|R_0 - F_0(g)| \geq t\right) \quad (4) \\ &\leq 2 \exp\left(-\frac{t^2}{2\sigma^2}\right), \end{aligned}$$

where $F_0(g)$ is the population miscoverage rate of g , the random variable R_0 has a Normal distribution $\mathcal{N}(F_0(g), \sigma^2)$, $\sigma^2 = F_0(g)(1 - F_0(g))/m_1$, $m_1 \leq m$ is the number of samples whose predictions are correct.

Further, we have (Tong et al., 2018):

$$\mathbb{P}(F_0(g) > \alpha) = \sum_{j=v}^{n_1} \binom{n_1}{j} (1-\alpha)^j \alpha^{n_1-j}, \quad (5)$$

where $v = \lceil (n_1 + 1)(1 - \alpha) \rceil$.

Equation (5) is given in Tong et al. (2018) and we adapt it here for our purpose. Essentially it means the population miscoverage rate is smaller than the predefined miscoverage rate tolerance with a high probability. A rough estimation of the miscoverage rate of g is $\lfloor (1+n)\alpha \rfloor / (1+n_1) \leq \alpha$. Although the miscoverage rate of our constructed calibration map can be well-controlled using the above constructed binary classifier, there is no such a guarantee that the Type II error of $\hat{\phi}$ is also well-controlled. Combining the results shown in Proposition 6, it can be seen that the empirical ECE depends solely on $\hat{R}_1(\hat{\phi})$, since $\hat{\pi}_0$ is a constant given a finite data set. Thus we cannot make sure the empirical calibration error is small if we keep using the construction rules shown in Proposition 3.

A simple refinement to the above issue is to utilize a separate calibration model $g_m \in \mathcal{G}$ and the updated construction rules for a calibration map are listed in the following:

- (i) if $\hat{\phi}(x) = -1$, we let $g(x) = g_m(x)$,
- (ii) if $\hat{\phi}(x) = +1$, we let $\max_{i \in [k]} g(x)_i = \frac{1}{k}$.

Now it is clear why we call our post-hoc calibration approach *Meta-Cal*, since our calibrator is built from a base calibration map. The rationality of the above updated rules is shown in Proposition 8.

Proposition 8 (Lower bound of Meta-Cal). *Suppose the base calibration map $g_m \in \mathcal{G}_a$ and g is constructed using the above updated rules, then:*

$$\sup_{B \in \mathcal{B}} \widehat{\text{ECE}}_B(g \circ f) > w \frac{1 - \hat{\pi}_0}{k}, \quad (6)$$

where $w = (1 - \hat{R}_0(\hat{\phi}))\hat{\pi}_0 + \hat{R}_1(\hat{\phi})(1 - \hat{\pi}_0) < 1$, $\hat{R}_0(\hat{\phi})$ and $\hat{R}_1(\hat{\phi})$ are empirical Type I error and Type II error of $\hat{\phi}$ respectively, $\hat{\pi}_0$ is the empirical accuracy of f on a finite data set.

It can be seen from Proposition 8 that Meta-Cal can construct a calibration map from a accuracy-preserving base calibrator with an improved calibration error lower bound. At the same time, its miscoverage rate is well-controlled. In Section 5, we empirically show that Meta-Cal outperforms other competing methods in terms of the empirical estimation of ECE. Algorithm 1 sketches the construction of Meta-Cal under a miscoverage rate constraint. For details of this construction, please see the first paragraph of Section 4.1.

Algorithm 1 Meta-Cal (miscoverage control)

- 1: **Input:** Training data set $\{(x_i, y_i)\}_{i=1}^n$, miscoverage rate tolerance α , base calibration model g_m , ranking model h .
 - 2: **Output:** Binary classifier $\hat{\phi}$, Meta-Cal calibration model g .
 - 3: Partition the training data set randomly into two parts. The first part has only negative ($\hat{Y} = Y$) samples. The second part contains both negative and positive samples ($\hat{Y} \neq Y$).
 - 4: Compute ranking scores on the first part using the ranking model h . Compute threshold r^* based on α .
 - 5: Construct a binary classifier $\hat{\phi}$ based on r^* .
 - 6: Train a base calibration model g_m using samples whose scores are smaller than r^* among the second part.
 - 7: Construct the final calibration map g using updated rules.
-

4.2. Coverage Accuracy Control

In some applications, we are more interested in controlling the coverage accuracy of a calibration map instead of the miscoverage rate. A practical example is a quality assurance (QA) system. The following two properties are desirable: (i) for products accepted by the QA system, their quality requirements are satisfied with high confidence, and (ii) the QA system does not perform unnecessary rejection. The first point corresponds to the coverage accuracy of a calibration map and the second point corresponds to the miscoverage rate.

To construct a calibration map with a controlled coverage accuracy, a suitable binary classifier is needed. It will be convenient to introduce the concept of a calibrated binary CPE model (Narasimhan & Agarwal, 2013). We note a calibrated binary CPE model is different from a perfectly calibrated model (Definition 1) in the binary setting.

Definition 9 (Calibrated binary CPE model (Narasimhan & Agarwal, 2013)). A binary class probability estimation (CPE) model $\hat{\eta} : \mathcal{X} \rightarrow [0, 1]$ is said to be calibrated w.r.t. a probability $\mathbb{P}(X, \epsilon)$ on $\mathcal{X} \times \{-1, +1\}$ if:

$$\mathbb{P}(\epsilon = 1 \mid \hat{\eta}(x) = u) = u, \forall u \in \text{range}(\hat{\eta})$$

where $\text{range}(\hat{\eta})$ denotes the range of $\hat{\eta}$.

Before we state our bound for the coverage accuracy, we present two existence propositions.

Proposition 10 (Existence of a monotonically increasing CPE transformation). *Under Assumptions 1 and 2, let $h : \mathcal{X} \rightarrow [a, b]$ (where $a, b \in \mathbb{R}$, $a < b$) be any bounded-range ranking model. There exists a monotonically increasing function $t : \mathbb{R} \rightarrow [0, 1]$ such that $t \circ h$ resulting from composing t and h is a calibrated binary CPE model.*

Proof. The existence of such a monotonically increasing CPE transformation directly follows by combining the results of Narasimhan & Agarwal (2013, Lemma 13) and Narasimhan & Agarwal (2013, Definition 12). \square

Proposition 11 (Existence of a monotonically decreasing coverage accuracy transformation). *Under Assumptions 1 and 2, let $h : \mathcal{X} \rightarrow [a, b]$ (where $a, b \in \mathbb{R}$, $a < b$) be any bounded-range ranking model. There exists a monotonically decreasing function $l : \mathbb{R} \rightarrow [0, 1]$ such that $l(s)$ is the coverage accuracy of a calibration map g which is constructed using the binary classifier $\hat{\phi}(x) = 2 \cdot \mathbb{1}(h(x) > s) - 1$.*

Proof. From Proposition 10, there exists a monotonically increasing t such that $t \circ h$ is a calibrated binary CPE model. Let $\mathcal{E}_h(s) = \mathbb{P}(\epsilon = 1 \mid h(x) < s)$, since t is monotonically increasing, we have:

$$\mathcal{E}_h(s) = \mathbb{P}(\epsilon = 1 \mid t(h(x)) < t(s)).$$

Because $t \circ h$ is a calibrated binary CPE model, using Definition 9, we further have:

$$\mathcal{E}_h(s) = \int_c^{t(s)} u du = \frac{1}{2} t(s)^2 - \text{constant}$$

where c is a constant.

From Definition 5, the desired coverage accuracy transformation is:

$$l(s) = 1 - \mathcal{E}_h(s) = \text{constant} - \frac{1}{2} t(s)^2.$$

Since $t(s) \geq 0, \forall s \in \mathbb{R}$ and $t(\cdot)$ is a monotonically increasing function, it is obvious that l is a monotonically decreasing function. From the definition of $\mathcal{E}_h(s)$, the binary classifier that is used to construct g is exactly $\hat{\phi}(x) = 2 \cdot \mathbb{1}(h(x) > s) - 1$. \square

Based on the above two existence propositions, we describe a bound for the empirical coverage accuracy in Proposition 12.

Algorithm 2 Meta-Cal (coverage accuracy control)

- 1: **Input:** Training data set $\{(x_i, y_i)\}_{i=1}^n$, desired coverage accuracy β , base calibration model g_m , ranking model h .
 - 2: **Output:** Binary classifier $\hat{\phi}$, Meta-Cal calibration model g .
 - 3: Randomly split the training data set into two parts.
 - 4: Estimate the coverage accuracy transformation \hat{l} on the first part.
 - 5: Compute a threshold $r^* = \hat{l}^{-1}(\beta)$ based on the estimated \hat{l} and β .
 - 6: Construct a binary classifier $\hat{\phi}$ based on r^* .
 - 7: Train a base calibration model g_m using samples among the second part whose scores are smaller than r^* .
 - 8: Construct the final calibration map g using updated rules.
-

Proposition 12 (Coverage accuracy control). *Under Assumptions 1 and 2, the empirical coverage accuracy $\hat{F}_1(g)$ of g on a finite test data set of size m that is drawn i.i.d. from $\mathbb{P}(X, Y)$ is well-controlled:*

$$\begin{aligned} \mathbb{P}\left(\left|\hat{F}_1(g) - \beta\right| \geq t\right) &\approx \mathbb{P}\left(|R_1 - \beta| \geq t\right) \\ &\leq 2 \exp\left(-\frac{m_1 t^2}{2\beta(1-\beta)}\right), \end{aligned} \quad (7)$$

where β is the desired coverage accuracy, the random variable R_1 has a Normal distribution $\mathcal{N}\left(\beta, \frac{\beta(1-\beta)}{m_1}\right)$, and $m_1 \leq m$ is the number of samples whose ranking scores are smaller than $l^{-1}(\beta)$ in the test data set.

Further, the desired binary classifier is:

$$\hat{\phi}(x) = 2 \cdot \mathbb{1}(h(x) > l^{-1}(\beta)) - 1. \quad (8)$$

It should be noted that among all calibration maps whose coverage accuracy is higher than β , the calibration map constructed using the binary classifier in Equation (8) has the smallest miscoverage rate. In the following, we describe how to estimate the monotonically decreasing function l in practice. Given a finite calibration data set $\{(x_i, y_i)\}_{i=1}^n$ that is drawn i.i.d. from the joint distribution $\mathbb{P}(X, Y)$ on $\mathcal{X} \times \mathcal{Y}$: Firstly the ranking scores $\{r_i\}_{i=1}^n$, where $r_i = h(x_i)$, are computed using our ranking model h . Then a set of bins $\{I_1, \dots, I_b\}$ to partition $\{r_i\}_{i=1}^n$ is constructed through uniform mass binning (Zadrozny & Elkan, 2001). For a given $j \in \{1, \dots, b\}$, let $l_j^{(s)}$ and $l_j^{(a)}$ denote the average of ranking scores on I_j and f 's accuracy on $\{I_1, \dots, I_j\}$ respectively. Finally a decreasing isotonic regression model is fitted on $\{(l_j^{(s)}, l_j^{(a)})\}_{j=1}^b$ and the fitted model is an estimation of l . Algorithm 2 sketches the construction of Meta-Cal under the coverage accuracy constraint.

Table 1. ECE comparison. *Uncal*, *TS*, *ETS*, *GPC*, *MetaMis*, *MetaAcc* denote no-calibration, temperature scaling, ensemble temperature scaling, Gaussian Process calibration, Meta-Cal under miscoverage rate constraint and Meta-Cal under coverage accuracy constraint respectively. Reported values are the average of 40 independent runs. All standard errors are less than $5e - 4$.

Dataset	Network	Acc	Uncal	TS	ETS	GPC	MetaMis	MetaAcc
CIFAR10	DenseNet40	0.9242	0.05105	0.00510	0.00567	0.00634	0.00434	0.00355
	ResNet110	0.9356	0.04475	0.00781	0.00809	0.00684	0.00391	0.00441
	ResNet110SD	0.9404	0.04022	0.00439	0.00509	0.00364	0.00350	0.00315
	WideResNet32	0.9393	0.04396	0.00706	0.00712	0.00684	0.00485	0.00532
CIFAR100	DenseNet40	0.7000	0.21107	0.01067	0.01104	0.01298	0.01093	0.00793
	ResNet110	0.7148	0.18182	0.02037	0.02130	0.01348	0.01815	0.01441
	ResNet110SD	0.7283	0.15496	0.01043	0.01057	0.01265	0.01109	0.00733
	WideResNet32	0.7382	0.18425	0.01332	0.01351	0.00993	0.01332	0.01189
ImageNet	DenseNet161	0.7705	0.05531	0.02053	0.02064	NA	0.01388	0.01248
	ResNet152	0.7620	0.06290	0.02023	0.02004	NA	0.01360	0.01138

5. Experiments

In this section, we present empirical results on a set of multi-class classifiers. Firstly, we compare our proposed Meta-Cal described in Section 4 with several baselines. Then we validate the two constraints investigated in this work are well satisfied in Section 5.2.

5.1. Calibrating Neural Networks

In this section, we compare our approach with other methods of post-hoc multi-class calibration. Following previous works (Guo et al., 2017; Kull et al., 2019; Zhang et al., 2020; Wenger et al., 2020), we report calibration results on several neural network classifiers trained on CIFAR-10, CIFAR-100 (Krizhevsky, 2009) and ImageNet (Deng et al., 2009). For CIFAR-10 and CIFAR-100, the following networks are used: DenseNet (Huang et al., 2016a), ResNet (He et al., 2015), ResNet with stochastic depth (Huang et al., 2016b), WideResNet (Zagoruyko & Komodakis, 2016). 45000 out of 60000 images are used for training these classifiers. The remaining 15000 images are held out for training and evaluating post-hoc calibration methods. The training details are given in ???. These 15000 samples are randomly split into 5000/10000 samples to train and evaluate a post-hoc calibration method. For ImageNet, we use pre-trained DenseNet-161 and ResNet-152 from PyTorch (Paszke et al., 2019). 50000 images in the validation set are used for training and evaluating post-hoc calibration methods. To train and test a calibration map, we randomly split these samples into 25000/25000 images.

The following post-hoc algorithms are used for comparison: temperature scaling (Guo et al., 2017), ensemble tempera-

ture scaling (Zhang et al., 2020), Gaussian Process calibration (Wenger et al., 2020). The Dirichlet calibration (Kull et al., 2019) is not included in our empirical comparison, since on the neural network classifiers we considered in this paper, its performance is consistently worse than other methods (Zhang et al., 2020).

To construct a calibration map using our proposed Meta-Cal, firstly we need to decide which base calibrator to use. Throughout the experimental part of this paper, we use temperature scaling since: (i) it is the most computationally efficient approach among the above baselines, and (ii) it can be seen from Proposition 8 that Meta-Cal augments the performance of temperature scaling, since it is an accuracy-preserving calibration map. Secondly a ranking model is required to construct a desired binary classifier based on different constraints. In this paper, we define the ranking model as the entropy of the output of an uncalibrated probabilistic classifier, that is, given $X \in \mathcal{X}$, we define $h(X) = -\sum_{i \in [k]} f(X)_i \log f(X)_i$. An alternative way is to learn a ranking model using a consistent ranking algorithm (Cl emen on et al., 2008) on a separate data set. A potential advantage of this approach is the constructed binary classifier has a lower Type II error, thus from Proposition 6, the worst-case estimation of expected calibration error can be improved. A disadvantage of this approach is a separate data set is required to learn a ranking model and this effectively means we have less samples to train a calibration model.

The experimental configurations specific to our proposed approach are as follows. For Meta-Cal under the miscoverage rate constraint, we set the miscoverage rate tolerance to be




Figure 1. Empirical miscoverage rate. The error bars show ± 2 standard deviation of 40 independent runs. The desired miscoverage rates for CIFAR-10, CIFAR-100 and ImageNet are all set to be 0.05.




Figure 2. Empirical coverage accuracy. The error bars show ± 2 standard deviation of 40 independent runs. The desired coverage accuracy for CIFAR-10, CIFAR-100 and ImageNet are set to be 0.97, 0.87 and 0.85, respectively.

0.05 for all neural network classifiers and all data sets used in the experiments. For Meta-Cal under the coverage accuracy constraint, we set the desired coverage accuracy to be 0.97, 0.87, 0.85 for CIFAR-10, CIFAR-100 and ImageNet, respectively. For reference, the original accuracy for each configuration is shown in the third column in Table 1. In both settings, we randomly select 1/10 samples (up to 500 samples) from the calibration data set to construct a binary classifier or estimate the coverage accuracy transformation function.

The comparison results of different calibration methods are shown in Table 1. The empirical ECE are estimated with 15 equal-width bins and ECE values reported in Table 1 are the average of 40 independent runs. Since GPC does not converge on ImageNet, its results on ImageNet are marked as NA in Table 1.

From Table 1, it can be seen that our proposed method Meta-Cal performs much better w.r.t. the empirical ECE in almost all configurations. It should be noted that Table 1 should be interpreted in a careful way, since our proposed method works in a novel setting, that is, post-hoc calibration under constraints. Essentially, we can interpret the improved calibration is due to the miscoverage price we pay. It is worth noting that after calibration, GPC has an around 0.2% accuracy drop in ResNet110 and ResNet110SD on CIFAR-10 data set. It is possible that GPC is trading off accuracy for calibration in an implicit and uncontrolled way.

5.2. Verifying Constraints

In this section, we empirically verify whether constraints of miscoverage rate and coverage accuracy are satisfied. The purpose of this section is to support our theoretical claims in Section 4.1 and Section 4.2.

The error bar plot in Figure 1 depicts ± 2 standard deviations of the empirical miscoverage rate over 40 independent runs. It can be seen from Figure 1 that the miscoverage rate is well-controlled given a miscoverage rate tolerance equal to 0.05. In Figure 2, the ± 2 standard deviation of the empirical coverage accuracy is illustrated. Given the desired coverage accuracies are set to be 0.97, 0.87 and 0.85 for CIFAR-10, CIFAR-100 and ImageNet, respectively, it can be seen that the coverage accuracy is well-controlled.

6. Conclusion

In this work, we propose Meta-Cal: a post-hoc calibration method for multi-class classification under practical constraints, including miscoverage rate constraints and coverage accuracy constraints. Our proposed approach can augment an accuracy-preserving calibration map and improve its calibration performance. Contrary to post-hoc calibration methods that cannot preserve accuracy, our approach has full control over coverage accuracy. A series of theoretical results are given to show the validity of Meta-Cal. Empirical results on a range of neural network classifiers on several popular computer vision data sets show our approach is able

to improve an existing calibration method.

References

- Burges, C., Shaked, T., Renshaw, E., Lazier, A., Deeds, M., Hamilton, N., and Hullender, G. Learning to rank using gradient descent. In *Proceedings of the 22nd International Conference on Machine Learning, ICML '05*, pp. 89–96, New York, NY, USA, August 2005. Association for Computing Machinery. ISBN 978-1-59593-180-1. doi: 10.1145/1102351.1102363.
- Chen, C., Seff, A., Kornhauser, A., and Xiao, J. Deep-Driving: Learning Affordance for Direct Perception in Autonomous Driving. In *2015 IEEE International Conference on Computer Vision (ICCV)*, pp. 2722–2730, December 2015. doi: 10.1109/ICCV.2015.312.
- Cléménçon, S., Lugosi, G., and Vayatis, N. Ranking and Empirical Minimization of U-statistics. *Annals of Statistics*, 36(2):844–874, April 2008. ISSN 0090-5364, 2168-8966. doi: 10.1214/009052607000000910.
- Deng, J., Dong, W., Socher, R., Li, L.-J., Li, K., and Fei-Fei, L. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pp. 248–255. Ieee, 2009.
- Ding, Z., Han, X., Liu, P., and Niethammer, M. Local Temperature Scaling for Probability Calibration. *arXiv:2008.05105 [cs]*, August 2020.
- El-Yaniv, R. and Wiener, Y. On the Foundations of Noise-free Selective Classification. *Journal of Machine Learning Research*, 11(53):1605–1641, 2010.
- Gao, W. and Zhou, Z.-H. On the Consistency of AUC Pairwise Optimization. *arXiv:1208.0645 [cs, stat]*, July 2014.
- Geifman, Y. and El-Yaniv, R. Selective Classification for Deep Neural Networks. *arXiv:1705.08500 [cs]*, June 2017.
- Guo, C., Pleiss, G., Sun, Y., and Weinberger, K. Q. On Calibration of Modern Neural Networks. In *Proceedings of the 34th International Conference on Machine Learning - Volume 70, ICML'17*, pp. 1321–1330. JMLR.org, 2017.
- He, K., Zhang, X., Ren, S., and Sun, J. Deep Residual Learning for Image Recognition. *arXiv:1512.03385 [cs]*, December 2015.
- Huang, G., Liu, Z., Weinberger, K. Q., and van der Maaten, L. Densely Connected Convolutional Networks. *arXiv:1608.06993 [cs]*, August 2016a.
- Huang, G., Sun, Y., Liu, Z., Sedra, D., and Weinberger, K. Q. Deep Networks with Stochastic Depth. In Leibe, B., Matas, J., Sebe, N., and Welling, M. (eds.), *Computer Vision – ECCV 2016*, Lecture Notes in Computer Science, pp. 646–661, Cham, 2016b. Springer International Publishing. ISBN 978-3-319-46493-0. doi: 10.1007/978-3-319-46493-0_39.
- Krizhevsky, A. Learning multiple layers of features from tiny images. Technical report, 2009.
- Krizhevsky, A., Sutskever, I., and Hinton, G. E. ImageNet Classification with Deep Convolutional Neural Networks. In Pereira, F., Burges, C. J. C., Bottou, L., and Weinberger, K. Q. (eds.), *Advances in Neural Information Processing Systems 25*, pp. 1097–1105. Curran Associates, Inc., 2012.
- Kull, M., Filho, T. S., and Flach, P. Beta calibration: A well-founded and easily implemented improvement on logistic calibration for binary classifiers. In *Artificial Intelligence and Statistics*, pp. 623–631. PMLR, April 2017.
- Kull, M., Perello Nieto, M., Kängsepp, M., Silva Filho, T., Song, H., and Flach, P. Beyond temperature scaling: Obtaining well-calibrated multi-class probabilities with Dirichlet calibration. In Wallach, H., Larochelle, H., Beygelzimer, A., d\textquotessingle Alché-Buc, F., Fox, E., and Garnett, R. (eds.), *Advances in Neural Information Processing Systems 32*, pp. 12316–12326. Curran Associates, Inc., 2019.
- Kumar, A., Liang, P. S., and Ma, T. Verified Uncertainty Calibration. In Wallach, H., Larochelle, H., Beygelzimer, A., d\textquotessingle Alché-Buc, F., Fox, E., and Garnett, R. (eds.), *Advances in Neural Information Processing Systems 32*, pp. 3792–3803. Curran Associates, Inc., 2019.
- Lakshminarayanan, B., Pritzel, A., and Blundell, C. Simple and Scalable Predictive Uncertainty Estimation using Deep Ensembles. *arXiv:1612.01474 [cs, stat]*, December 2016.
- Lin, H.-T., Lin, C.-J., and Weng, R. C. A note on Platt’s probabilistic outputs for support vector machines. *Machine Learning*, 68(3):267–276, October 2007. ISSN 1573-0565. doi: 10.1007/s10994-007-5018-6.
- Ma, X., Huang, D., Wang, Y., and Wang, Y. Cost-Sensitive Two-Stage Depression Prediction Using Dynamic Visual Clues. In Lai, S.-H., Lepetit, V., Nishino, K., and Sato, Y. (eds.), *Computer Vision – ACCV 2016*, Lecture Notes in Computer Science, pp. 338–351, Cham, 2017. Springer International Publishing. ISBN 978-3-319-54184-6. doi: 10.1007/978-3-319-54184-6_21.

- Maddox, W., Garipov, T., Izmailov, P., Vetrov, D., and Wilson, A. G. A Simple Baseline for Bayesian Uncertainty in Deep Learning. *arXiv:1902.02476 [cs, stat]*, December 2019.
- Malinin, A. and Gales, M. Predictive Uncertainty Estimation via Prior Networks. In Bengio, S., Wallach, H., Larochelle, H., Grauman, K., Cesa-Bianchi, N., and Garnett, R. (eds.), *Advances in Neural Information Processing Systems 31*, pp. 7047–7058. Curran Associates, Inc., 2018.
- Milios, D., Camoriano, R., Michiardi, P., Rosasco, L., and Filippone, M. Dirichlet-based Gaussian Processes for Large-scale Calibrated Classification. In Bengio, S., Wallach, H., Larochelle, H., Grauman, K., Cesa-Bianchi, N., and Garnett, R. (eds.), *Advances in Neural Information Processing Systems 31*, pp. 6005–6015. Curran Associates, Inc., 2018.
- Naeni, M. P., Cooper, G. F., and Hauskrecht, M. Obtaining well calibrated probabilities using bayesian binning. In *Proceedings of the Twenty-Ninth AAAI Conference on Artificial Intelligence*, AAAI’15, pp. 2901–2907, Austin, Texas, January 2015. AAAI Press. ISBN 978-0-262-51129-2.
- Narasimhan, H. and Agarwal, S. On the Relationship Between Binary Classification, Bipartite Ranking, and Binary Class Probability Estimation. *Advances in Neural Information Processing Systems*, 26:2913–2921, 2013.
- Paszke, A., Gross, S., Massa, F., Lerer, A., Bradbury, J., Chanan, G., Killeen, T., Lin, Z., Gimelshein, N., Antiga, L., Desmaison, A., Kopf, A., Yang, E., DeVito, Z., Raison, M., Tejani, A., Chilamkurthy, S., Steiner, B., Fang, L., Bai, J., and Chintala, S. Pytorch: An imperative style, high-performance deep learning library. In *Advances in Neural Information Processing Systems 32*, pp. 8024–8035. Curran Associates, Inc., 2019.
- Patel, K., Beluch, W., Yang, B., Pfeiffer, M., and Zhang, D. Multi-Class Uncertainty Calibration via Mutual Information Maximization-based Binning. *arXiv:2006.13092 [cs, stat]*, September 2020.
- Pereyra, G., Tucker, G., Chorowski, J., Kaiser, Ł., and Hinton, G. Regularizing Neural Networks by Penalizing Confident Output Distributions. *arXiv:1701.06548 [cs]*, January 2017.
- Platt, J. C. Probabilistic Outputs for Support Vector Machines and Comparisons to Regularized Likelihood Methods. In *Advances in Large Margin Classifiers*, pp. 61–74. MIT Press, 1999.
- Russakovsky, O., Deng, J., Su, H., Krause, J., Satheesh, S., Ma, S., Huang, Z., Karpathy, A., Khosla, A., Bernstein, M., Berg, A. C., and Fei-Fei, L. ImageNet Large Scale Visual Recognition Challenge. *International Journal of Computer Vision*, 115(3):211–252, December 2015. ISSN 1573-1405. doi: 10.1007/s11263-015-0816-y.
- Tong, X., Feng, Y., and Li, J. J. Neyman-Pearson classification algorithms and NP receiver operating characteristics. *Science Advances*, 4(2), February 2018. ISSN 2375-2548. doi: 10.1126/sciadv.aao1659.
- Wenger, J., Kjellström, H., and Triebel, R. Non-Parametric Calibration for Classification. In *International Conference on Artificial Intelligence and Statistics*, pp. 178–190, June 2020.
- Wilson, A. G., Hu, Z., Salakhutdinov, R., and Xing, E. P. Stochastic Variational Deep Kernel Learning. *arXiv:1611.00336 [cs, stat]*, November 2016.
- Zadrozny, B. and Elkan, C. Obtaining calibrated probability estimates from decision trees and naive Bayesian classifiers. In *Proceedings of the Eighteenth International Conference on Machine Learning*, ICML ’01, pp. 609–616, San Francisco, CA, USA, June 2001. Morgan Kaufmann Publishers Inc. ISBN 978-1-55860-778-1.
- Zadrozny, B. and Elkan, C. Transforming classifier scores into accurate multiclass probability estimates. In *Proceedings of the Eighth ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, KDD ’02, pp. 694–699, New York, NY, USA, July 2002. Association for Computing Machinery. ISBN 978-1-58113-567-1. doi: 10.1145/775047.775151.
- Zagoruyko, S. and Komodakis, N. Wide Residual Networks. *arXiv:1605.07146 [cs]*, May 2016.
- Zhang, J., Kailkhura, B., and Han, T. Y.-J. Mix-n-Match: Ensemble and Compositional Methods for Uncertainty Calibration in Deep Learning. *arXiv:2003.07329 [cs, stat]*, June 2020.

A. Proofs of Theoretical Results

In this section, we give proofs of propositions in the main paper.

Proof of Proposition 2. For a given $g \in \mathcal{G}_a$, the first step is to find the supremum of the binned estimator $\widehat{\text{ECE}}_B(g \circ f)$ across all binning schemes $B \in \mathcal{B}$. Let $B = \{I_1, \dots, I_b\}$, on the j -th bin I_j ,

$$\begin{aligned} & \left| \frac{1}{n_j} \sum_{i=1}^{n_j} \mathbb{1}(Y_{j,i} = \widehat{Y}_{j,i}) - \frac{1}{n_j} \sum_{i=1}^{n_j} \widehat{Z}_{j,i} \right| \\ & \leq \frac{1}{n_j} \sum_{i=1}^{n_j} \left| \mathbb{1}(Y_{j,i} = \widehat{Y}_{j,i}) - \widehat{Z}_{j,i} \right|, \end{aligned}$$

where n_j is the number of samples falling into I_j , $Y_{j,i}, \widehat{Y}_{j,i}, \widehat{Z}_{j,i}$ are the i -th label, the i -th prediction and the i -th confidence score in the i -th bin respectively. This implies that to maximize the binned estimator, I_j can be further divided into n_j sub-partitions so that each sub-partition contains exactly one sample. Let B^* denotes this implied binning scheme. Then we find the lower bound of $\widehat{\text{ECE}}_{B^*}(g \circ f)$. For the i -th sample in I_j , if $Y_{j,i} = \widehat{Y}_{j,i}$, we have $\left| \mathbb{1}(Y_{j,i} = \widehat{Y}_{j,i}) - \widehat{Z}_{j,i} \right| \geq 0$. If $Y_{j,i} \neq \widehat{Y}_{j,i}$, since $g \in \mathcal{G}_a$, we have $\left| \mathbb{1}(Y_{j,i} = \widehat{Y}_{j,i}) - \widehat{Z}_{j,i} \right| > 1/k$. Let $n_{j,1}$ be the number of wrongly classified samples in I_j , then:

$$\frac{1}{n_j} \sum_{i=1}^{n_j} \left| \mathbb{1}(Y_{j,i} = \widehat{Y}_{j,i}) - \widehat{Z}_{j,i} \right| > \frac{n_{j,1}}{n_j k}.$$

Since the above inequality holds for every bin, then:

$$\begin{aligned} \sup_{B \in \mathcal{B}} \widehat{\text{ECE}}_B(g \circ f) &= \widehat{\text{ECE}}_{B^*}(g \circ f) \\ &> \sum_{j=1}^b \frac{n_j}{n} \frac{n_{j,1}}{n_j k} = \frac{1 - \hat{\pi}_0}{k}, \end{aligned}$$

where $\hat{\pi}_0$ is the empirical accuracy of f . \square

Proof of Proposition 6. Using the construction rules described in Proposition 3, for any $B \in \mathcal{B}$, we have:

$$\begin{aligned} \widehat{\text{ECE}}_B(g \circ f) &= \left[(1 - \hat{R}_0(\phi)) \cdot \hat{\pi}_0 + \hat{R}_1(\phi) \cdot \hat{\pi}_1 \right] \\ &\quad \cdot \left| 1 - \frac{(1 - \hat{R}_0(\phi)) \cdot \hat{\pi}_0}{(1 - \hat{R}_0(\phi)) \cdot \hat{\pi}_0 + \hat{R}_1(\phi) \cdot \hat{\pi}_1} \right| \\ &\quad + \left[\hat{R}_0(\phi) \hat{\pi}_0 + (1 - \hat{R}_1(\phi)) \hat{\pi}_1 \right] \cdot \left| \frac{1}{k} - \frac{1}{k} \right| \\ &= \hat{R}_1(\phi) (1 - \hat{\pi}_0). \end{aligned}$$

Since the above equality holds for $\forall B \in \mathcal{B}$, it also holds for B^* , which is defined in the proof of Proposition 2. \square

Proof of Proposition 7. Under Assumption 1, from the definition of the miscoverage rate in Definition 4, we have:

$$\left(\mathbb{1}(h(X) > r_{(v)}) \mid Y = \widehat{Y} \right) \sim \text{Bern}(F_0(g)),$$

where $F_0(g)$ is the population miscoverage rate of g , $v = \lceil (n_1 + 1)(1 - \alpha) \rceil$, $r_{(v)}$ is the v -th order statistic of $\{r_i\}_{i=1}^{n_1}$. Without loss of generality, we suppose the first m_1 inputs have negative labels and the last m_2 inputs have positive labels, where $m = m_1 + m_2$. Then the empirical miscoverage rate is:

$$\widehat{F}_0(g) = \frac{1}{m_1} \sum_{i=1}^{m_1} \mathbb{1}(h(x_i) > r_{(v)}).$$

Thus $m_1 \widehat{F}_0(g)$ follows a Binomial distribution, that is, $m_1 \widehat{F}_0(g) \sim \text{Binom}(m_1, F_0(g))$. For large m_1 , we can approximate it by $\mathcal{N}(m_1 F_0(g), m_1 F_0(g)(1 - F_0(g)))$ using the central limit theorem. Let R_0 be a random variable following a Normal distribution $\mathcal{N}(F_0(g), \sigma^2)$, where $\sigma^2 = F_0(g)(1 - F_0(g))/m_1$. Applying the Chernoff bound for a Gaussian variable:

$$\mathbb{P}(|R_0 - F_0(g)| \geq t) \leq 2 \exp\left(-\frac{t^2}{2\sigma^2}\right).$$

Combining the above results finishes the proof of Proposition 7. \square

Proof of Proposition 8. This follows directly from Proposition 2. \square

Proof of Proposition 12. Under Assumptions 1 and 2, from the definition of coverage accuracy in Definition 5 and Proposition 11, we have:

$$\left(\mathbb{1}(Y = \widehat{Y}) \mid h(X) < l^{-1}(\beta) \right) \sim \text{Bern}(\beta).$$

Without loss of generality, we suppose ranking scores of the first $m_1 \leq m$ inputs are smaller than $l^{-1}(\beta)$. The empirical coverage accuracy is:

$$\widehat{F}_1(g) = \frac{1}{m_1} \sum_{i=1}^{m_1} \mathbb{1}(y_i = \hat{y}_i).$$

Thus $m_1 \widehat{F}_1(g)$ follows a Binomial distribution and can be approximated by a Gaussian distribution for large m_1 . The remaining proof is similar to the proof of Proposition 7. \square

B. A Trivial Construction

In this section, we show bounding $\widehat{\text{ECE}}_B(g \circ f)$ instead of its supremum makes little sense by giving a trivial construction. Suppose we are to evaluate the binned estimator on 4 samples and their predicted confidence scores,

predictions, targets are $\{0.6, 0.7, 0.8, 0.81\}$, $\{0, 0, 0, 0\}$, $\{0, 0, 0, 1\}$ respectively. Let the binning scheme be the interval $B = [0, 1]$, we can construct an accuracy-preserving calibration map:

$$g(x) = \begin{cases} 0.9 & , \text{ if } x = 0.81 \\ x & , \text{ otherwise.} \end{cases}$$

The binned estimator using such a calibration map on this data set is 0. Obviously, this calibration map is not practical.

C. Training Details

To train networks on CIFAR-10 and CIFAR-100, we use stochastic gradient descent with momentum (0.9) using mini-batches of 128 samples for 200 epochs. We also add an L2-weight decay regularization term, which is set to be 0.0001. The start learning rate is set to be 0.1 and is decreased to 0.01 and 0.001 in the beginning of the 80-th epoch and 150-th epoch respectively. Horizontal flipping and cropping are used as data augmentation.