

# Level-rank duality of $SU(2)_k$ Chern-Simons theory, and of hypergraph and magic states

---

**Howard J. Schnitzer**

*Martin Fisher School of Physics, Brandeis University, Waltham, Massachusetts 02453, USA*

*E-mail:* [schnitzr@brandeis.edu](mailto:schnitzr@brandeis.edu)

ABSTRACT: The level-rank duality of  $SU(2)_k$  Chern-Simons theory is discussed, and applied to graph, hypergraph, and magic states.

# 1 Introduction

Level-rank duality of Chern-Simons theory and WZW theories has a long history, [1–6] with many applications. It generally involves transposition of the Young tableaux of the representations for a pair of theories, linked by the duality. However, in general level-rank duality is not a one-to-one map between the tableaux of the two theories. For example,  $SU(2)_3$  has four states, while  $SU(3)_2$  has six. However, using cominimal equivalent or simple current maps relating states, [5] a one-to-one map of the representations is possible. Note that  $SU(2)_3/\mathbb{Z}_3$  and  $SU(3)_2/\mathbb{Z}_2$  have just two states related one-to-one by transposition of the respective Young tableaux. The generalization of this theme is central to this paper.

It is the purpose of this paper to discuss the level-rank duality of  $SU(2)_k$  and its relationship to  $SU(k)_2$ . The generalized Pauli group can be defined for each side of the duality, which can then be used to construct graph and hypergraph states for the level-rank pairs. Since a sub-set of hypergraph states describe magic states, level-rank duals of magic states also results.

## 2 Level-rank dualities of $SU(2)_k$

The integral representations of  $SU(2)_k$  Chern-Simons theory can be described by a single-row Young tableau with  $0 \leq k$  boxes, while that of  $SU(k)_2$  is described by a Young tableau with two columns,  $l_1$  and  $l_2$ , where  $l_1 \geq l_2$ , and  $l_1$  ranges from 0 to  $k - 1$ . Thus,  $SU(2)_k$  has  $k + 1$  states, while  $SU(k)_2$  has  $\frac{1}{2}k(k + 1)$  states. Therefore a transpose map between the representations of  $SU(2)_k$  and  $\widetilde{SU}(k)_2$  is not one-to-one, where  $\widetilde{SU}$  indicates the transpose of the Young tableau. However, making use of the orbits of cominimal maps or equivalently simple current maps, [5] one can obtain level-rank dual maps which are one-to-one for the Young tableaux. The two cases that we focus on are

$$SU(2)_{2k} = \widetilde{SU}(2k)_2/\mathbb{Z}_k \tag{2.1}$$

which has  $2k + 1$  states, and

$$SU(2)_{2k+1}/\mathbb{Z}_2 = \widetilde{SU}(2k + 1)_2/\mathbb{Z}_{2k+1} \tag{2.2}$$

which has  $k + 1$  states. In the next subsection we consider the generalized Pauli group for these two cases.

## 2.1 Generalized Pauli group

The qudit Pauli group for a  $d$ -dimensional system, for both  $d$  odd and even, is described by Farinholt [7]. One defines the operators

$$X = \sum_{x \in \mathbb{Z}_d} |x+1\rangle\langle x| \quad (2.3)$$

and

$$Z = \sum_{x \in \mathbb{Z}_d} \omega^x |x\rangle\langle x| \quad (2.4)$$

where  $\omega = \exp\left(\frac{2\pi i}{d}\right)$  is a primitive root of unity. We focus on  $d$ -odd for simplicity for the dual pairs (2.1) and (2.2). For the dual pairs of (2.1),  $d$  is odd for any integer  $k$ . However, for (2.2),  $d$  odd requires  $k$  even.

With these restrictions, the operators  $X$  and  $Z$  are defined for the level-rank dual pairs (2.1) and (2.2). Given the level-rank dual pairs (2.1) and (2.2), and the restriction to  $d$  odd, identify  $X = \tilde{X}$  and  $Z = \tilde{Z}$  for the Pauli operators of both sides of (2.1) and (2.2). Thus the dual pairs of  $X = \tilde{X}$  and  $Z = \tilde{Z}$  enables one to define level-rank dual pairs of graphs and hypergraph states, which we consider in the next sub-section.

## 2.2 Graph and hypergraph states

**Graph states** There are many equivalent constructions of graph states [8–12]. We follow arxiv:1612.06418 for a definition of qudit graph states. The multigraph is  $G = (V, E)$ , with vertices  $V$  and edges  $E$ , where an edge has multiplicity  $m_e \in \mathbb{Z}_d$ . To  $G$  associate a state  $|G\rangle$  such that to each vertex  $i \in V$ , there is a local state

$$|+\rangle = |p_0\rangle = \frac{1}{\sqrt{d}} \sum_{q=0}^{d-1} |q\rangle \quad (2.5)$$

Define

$$\begin{aligned} S^*|0\rangle &= \frac{1}{\sqrt{d}} \sum_{q=0}^{d-1} |q\rangle \\ &= |+\rangle = |p_0\rangle. \end{aligned} \quad (2.6)$$

To each edge  $e = \{i, j\}$  apply the unitary

$$Z_e^{m_e} = \sum_{q_i=0}^{d-1} |q_i\rangle\langle q_i| \otimes (Z_j^{m_e})^{q_i} \quad (2.7)$$

to the state

$$|+\rangle^V = \bigotimes_{i \in V} |+\rangle_i \quad (2.8)$$

The graph state is

$$|G\rangle = \prod_{e \in E} Z_e^{m_e} |+\rangle^V \quad (2.9)$$

$$= \prod_{e \in E} Z_e^{m_e} \bigotimes_{i \in V} |+\rangle_i \quad (2.10)$$

Every stabilizer state is LC equivalent to a graph state, while the Clifford group enables conversion between different multigraphs [8–12].

**Hypergraph states** We again follow arxiv:1612.06418 for the construction of qudit multi-hypergraph states. Given a multi-hypergraph  $H = (V, E)$ , associate a quantum state  $|H\rangle$ , with  $m_e \in \mathbb{Z}_d$  the multiplicity of the hyperedge  $e$ . To each vertex  $i \in V$ , associate a local state

$$|+\rangle = \frac{1}{\sqrt{d}} \sum_{q=0}^{d-1} |q\rangle \quad (2.11)$$

To each hyperedge  $e \in E$ , with multiplicity  $m_e$ , apply the controlled unitary  $Z_e^{m_e}$  to the state

$$|+\rangle^V = \bigotimes_{i \in V} |+\rangle_i \quad (2.12)$$

The hypergraph state is

$$|H\rangle = \prod_{e \in E} Z_e^{m_e} |+\rangle^V \quad (2.13)$$

and the elementary hypergraph state is

$$|H\rangle = \sum_{q=0}^{d-1} |q\rangle \langle q| \otimes \left( Z_{e \setminus \{1\}}^{m_e} \right)^q |+\rangle^V \quad (2.14)$$

For  $d$  prime, all  $n$ -elementary hypergraph states are equivalent under SLOCC.

Hypergraph and graph states admit a representation in terms of Boolean functions,

$$|H\rangle = \sum_{q=0}^{d-1} \omega^{f(q)} |q\rangle \quad (2.15)$$

with  $f : \mathbb{Z}_d^n \rightarrow \mathbb{Z}_d$ , where

$$f(x) = \sum_{\substack{i_1, \dots, i_k \in V \\ \{i_1, \dots, i_k\} \in E}} x_{i_1} \cdots x_{i_k} \quad (2.16)$$

For graph states,  $f(x)$  is quadratic, i.e.

$$f(x) = \sum_{\substack{i_1, i_2 \in V \\ \{i_1, i_2\} \in E}} x_{i_1} x_{i_2} \quad (2.17)$$

while for  $f(x)$  cubic or higher,  $|H\rangle$  is a hypergraph state. Therefore, for quadratic  $f(x)$ , one has a representation of stabilizer states, up to LC equivalence. For  $f(x)$  cubic or higher,  $|H\rangle$  represents hypergraph states which contain “magic” states. Examples of magic states are the CCZ state and Toffoli states, constructed from appropriate gates. Thus

$$\text{CCZ}|x_1 x_2 x_3\rangle = \omega^{x_1 x_2 x_3} |x_1 x_2 x_3\rangle \quad (2.18)$$

with

$$|\text{CCZ}\rangle = \text{CCZ}|+\otimes^3\rangle \quad (2.19)$$

as an example of a magic hypergraph state. Similarly

$$|\text{Toff}\rangle = \text{Toff}|+\otimes^3\rangle \quad (2.20)$$

Explicitly,

$$\text{Toff}|i, j, k\rangle = |i, j, ij + k, \text{ mod } d\rangle \quad (2.21)$$

### 2.3 Level-rank duality

The level-rank duality of the Pauli operators  $X, \tilde{X}, Z, \tilde{Z}$  in 2.1 allows one to express the graph and hypergraph states (2.7), (2.9), (2.10), (2.13), (2.14) as the level-rank duals of graph and hypergraph states for  $SU(2)_{2k}$  and for  $SU(2)_{2k+1}/\mathbb{Z}_2$  ( $k$  even). Since the hypergraph states contain magic states, there is a one-to-one map between such magic states and their level-rank duals.

It has been shown, using level-rank duality, that a universal topological quantum computer based on Chern-Simons theory for  $SU(2)_2$  [13] also implies an analogous universal quantum computer based on  $SU(3)_2$  [14]. However, this result depends on the level-rank duality of the Jones representation of the braid group, which differs from the duality discussed in this paper.

## Acknowledgments

We thank Jonathan Harper and Isaac Cohen-Abbo for their help in preparing the manuscript.

## References

- [1] S.G. Naculich and H.J. Schnitzer, *Duality relations between  $SU(N)_k$  and  $SU(k)_N$  WZW models and their braid matrices*, *Physics Letters B* **244** (1990) 235.
- [2] S.G. Naculich and H.J. Schnitzer, *Duality between  $SU(N)_k$  and  $SU(k)_N$  WZW models*, *Nuclear Physics B* **347** (1990) 687.
- [3] A. Kuniba and T. Nakanishi, *in Proc. Int. Coll. on modern quantum field theory, Bombay*, 1990.
- [4] S. Naculich, H. Riggs and H. Schnitzer, *Group-level duality in WZW models and Chern-Simons theory*, *Physics Letters B* **246** (1990) 417.
- [5] E.J. Mlawer, S.G. Naculich, H.A. Riggs and H.J. Schnitzer, *Group-Level duality of WZW Fusion Coefficients and Chern-Simons Link Observables*, *Nuclear Physics B* **352** (1991) 863.
- [6] S.G. Naculich, H.A. Riggs and H.J. Schnitzer, *Simple-Current Symmetries, Rank Level Duality, and Linear Skein Relations for Chern-Simons graphs*, *Nucl. Phys. B* **394** (1993) 445 [[hep-th/9205082](#)].
- [7] J.M. Farinholt, *An Ideal Characterization of the Clifford operators*, *Journal of Physics A: Mathematical and Theoretical* **47** (2014) 305303 [[1307.5087](#)].
- [8] F.E.S. Steinhoff, C. Ritz, N.I. Miklin and O. Gühne, *Qudit hypergraph states*, *Physical Review A* **95** (2017) [[1612.06418](#)].
- [9] M. Englbrecht and B. Kraus, *Symmetries and entanglement of Stabilizer states*, *Physical Review A* **101** (2020) [[2001.07106](#)].
- [10] Z.-W. Liu and A. Winter, *Many-body quantum magic*, [[2010.13817](#)].
- [11] M. Rossi, M. Huber, D. Bruß and C. Macchiavello, *Quantum hypergraph states*, *New Journal of Physics* **15** (2013) 113022 [[1211.5554](#)].
- [12] M. Hein, W. Dür, J. Eisert, R. Raussendorf, M. Van den Nest and H.J. Briegel, *Entanglement in Graph States and its Applications*, *arXiv e-prints* (2006) quant [[quant-ph/0602096](#)].
- [13] M. Freedman, M. Larsen and Z. Wang, *A modular functor which is universal for quantum computation*, *arXiv e-prints* (2000) quant [[quant-ph/0001108](#)].
- [14] H.J. Schnitzer, *Level-rank duality for a universal topological quantum computer*, [[1811.11861](#)].