

# Provably Efficient Representation Learning in Low-rank Markov Decision Processes

Weitong Zhang<sup>\*†</sup> Jiafan He<sup>\*‡</sup> Dongruo Zhou<sup>§</sup> Amy Zhang<sup>¶</sup> Quanquan Gu<sup>||</sup>

## Abstract

The success of deep reinforcement learning (DRL) is due to the power of learning a representation that is suitable for the underlying exploration and exploitation task. However, existing provable reinforcement learning algorithms with linear function approximation often assume the feature representation is known and fixed. In order to understand how representation learning can improve the efficiency of RL, we study representation learning for a class of low-rank Markov Decision Processes (MDPs) where the transition kernel can be represented in a bilinear form. We propose a provably efficient algorithm called ReLEX that can simultaneously learn the representation and perform exploration. We show that ReLEX always performs no worse than a state-of-the-art algorithm without representation learning, and will be strictly better in terms of sample efficiency if the function class of representations enjoys a certain mild “coverage” property over the whole state-action space.

## 1 Introduction

Reinforcement Learning (RL) has achieved impressive results in game-playing (Mnih et al., 2013), robotics (Kober et al., 2013), and many other tasks. However, most of the current RL tasks are challenging due to large state-action spaces that make traditional tabular methods intractable. Instead, function approximation methods can be applied to tackle this challenge. In this scheme, the state-action pairs are compressed to provide some compact *representations* that leverage underlying structure in the MDP, and therefore allowing the algorithm to generalize to unseen states.

In modern approaches, deep neural networks are often used as feature extractors to generate these representations. Since different feature extractors powered by different pretrained neural networks can be used, various representations are generated to encode the same state-action pair. However, how to utilize different representations in different scenarios is not well addressed in literature. Nonetheless, this task is crucial in robotics: A robot is usually equipped with different types of

---

\*Equal Contribution

<sup>†</sup>Department of Computer Science, University of California, Los Angeles, CA 90095, USA; e-mail: wt.zhang@ucla.edu

<sup>‡</sup>Department of Computer Science, University of California, Los Angeles, CA 90095, USA; e-mail: jiafanhe19@ucla.edu

<sup>§</sup>Department of Computer Science, University of California, Los Angeles, CA 90095, USA; e-mail: drzhou@cs.ucla.edu

<sup>¶</sup>Department of Electrical Engineering and Computer Science, University of California, Berkeley and Facebook AI Research; e-mail: amyzhang@fb.com

<sup>||</sup>Department of Computer Science, University of California, Los Angeles, CA 90095, USA; e-mail: qgu@cs.ucla.edu

sensors working through different physical phenomena (de Bruin et al., 2018), like accelerometers, magnetic sensors, or laser sensors. These sensors are all estimating the current state of the robot and providing a representation of the current state as the output. However, the accuracy and robustness of these sensors are varying in different states. Thus an intelligent system should always utilize the most accurate and robust sensor in different states to achieve the best performance. However, current theoretical literature on representation learning (Jiang et al., 2017; Agarwal et al., 2020; Modi et al., 2021) only address how to learn the *correct* representation but fail to show what a *good* representation is and how the algorithm benefits from this property. These issues in practice and lack of supporting theory yield the following question:

*Can representation learning provably improve sample efficiency in RL?*

In this paper, we answer the above question affirmatively by considering a class of low-rank Markov Decision Processes (MDPs) (Yang and Wang, 2020), where the transition kernel  $\mathbb{P}(s'|s, a)$  can be interpreted as a bilinear form of the feature vector  $\phi(s, a)$ , unknown matrix  $\mathbf{M}^*$  and feature vector  $\psi(s')$ . We propose an algorithm called ReLEX which can adapt to the best representation in a representation function class in different scenarios. Our contributions can be further formalized in below:

- We provably show the advantage of representation learning by showing that we can achieve an improved regret bound if the representation function class has good coverage for all state-action pairs.
- We propose a new algorithm called ReLEX which leverages the power of representation learning. We show that theoretically ReLEX performs no worse than the state-of-the-art algorithm without representation learning, and will have strictly better sample efficiency in some scenarios.
- Our analysis is based on several innovative techniques. We extend the diversity condition in linear contextual bandits to finite time-horizon MDP and provide a bound on the distribution mismatch of the state distribution caused by the sub-optimal policy in terms of the summation of the suboptimality gap. We believe both results are new and of independent interest.

**Notation.** Scalars and constants are denoted by lower and upper case letters, respectively. Vectors are denoted by lower case bold face letters  $\mathbf{x}$ , and matrices by upper case bold face letters  $\mathbf{A}$ . We denote by  $[k]$  the set  $\{1, 2, \dots, k\}$  for positive integers  $k$ . For two non-negative sequence  $\{a_n\}, \{b_n\}$ ,  $a_n = \mathcal{O}(b_n)$  means that there exists a positive constant  $C$  such that  $a_n \leq Cb_n$ , and we use  $\tilde{\mathcal{O}}(\cdot)$  to hide the log factor in  $\mathcal{O}(\cdot)$  except for the episode number  $k$ . We denote by  $\|\cdot\|_2$  the Euclidean norm of vectors and the spectral norm of matrices, and by  $\|\cdot\|_F$  the Frobenius norm of a matrix. We denote the Loewner ordering between two symmetric matrix as  $\mathbf{A} \succeq \mathbf{B}$  is equivalent to  $\mathbf{A} - \mathbf{B} \succeq \mathbf{0}$ . For vector  $\mathbf{x} \in \mathbb{R}^d$ , we denote by  $\mathbf{x}_{[i]}$  the  $i$ -th element of  $\mathbf{x}$ , for matrix  $\mathbf{A} \in \mathbb{R}^{d \times d}$ , we denote by  $\mathbf{A}_{[ii]}$  as the  $i$ -th diagonal elements.

## 2 Related Work

**Reinforcement Learning with Linear Function Approximation.** A large body of literature regarding learning MDP with linear function approximation has emerged recently. Those works can be roughly divided by their assumptions on MDPs: The first one is called Linear MDP (Yang

and Wang, 2019; Jin et al., 2020), where the representation function is built on the state action pair  $\phi(s, a)$ . Under this assumption, Jin et al. (2020) proposed the LSVI-UCB algorithm achieving  $\tilde{\mathcal{O}}(\sqrt{d^3 H^3 T})$  problem independent regret bound and  $\tilde{\mathcal{O}}(d^3 H^5 \text{gap}_{\min}^{-1} \log(T))$  problem dependent regret bound due to He et al. (2021). Here  $\text{gap}_{\min}$  is the minimal sub-optimality gap,  $d$  is the dimension and  $H$  is the time-horizon. Several similar MDP assumptions are studied in the literature: for instance, Jiang et al. (2017) studied a larger class of MDPs with low Bellman rank and proposed an algorithm with polynomial sample complexity. Low inherent Bellman error assumption is proposed by Zanette et al. (2020) and allows a better  $\mathcal{O}(dH\sqrt{T})$  regret by considering a global planning oracle. Yang and Wang (2020) considered the bilinear structure of the MDP kernel as a special case of the Linear MDP, and achieved an  $\tilde{\mathcal{O}}(H^2 d\sqrt{T})$  problem-independent regret bound. The second linear function approximation assumption is called Linear Mixture MDP (Modi et al., 2020; Ayoub et al., 2020; Zhou et al., 2021b) where the transition kernel of MDP is a linear function  $\phi(s, a, s')$  of the ‘state-action-next state’ triplet. Under this setting, Jia et al. (2020); Ayoub et al. (2020) proposed UCRL-VTR achieving  $\mathcal{O}(d\sqrt{H^3 T})$  problem independent bound for episodic MDP, while He et al. (2021) showed an  $\tilde{\mathcal{O}}(d^2 H^5 \text{gap}_{\min}^{-1} \log^3(T))$  problem dependent regret bound for the same algorithm. Zhou et al. (2021b) studied infinite horizon MDP with discounted reward setting and proposed UCLK algorithm to achieve  $\tilde{\mathcal{O}}(d\sqrt{T}(1-\gamma)^2)$  regret. Most recently, Zhou et al. (2021a) proposed nearly minimax optimal algorithms for learning Linear Mixture MDPs in both finite and infinite horizon settings. However, these works all assume a single representation and do not depend on the quality of the representation as long as it can well approximate the value function. Thus, what a good representation is and what improvement this good representation can bring is still an open question.

**Representation Learning in Reinforcement Learning.** Learning good representations in reinforcement learning enjoys a long history. State aggregation (Michael and Jordan, 1995; Dean and Givan, 1997; Ravindran and Barto, 2002; Abel et al., 2016) is one of the earliest methods for aggregating different states and generating a compressed representation for those states. With the fast development of deep learning methods, deep neural networks have been widely applied to provide good representations in different settings in practice (Diuk et al., 2008; Stooke et al., 2020; Yang et al., 2020). Several theoretical works (Du et al., 2019; Misra et al., 2020; Foster et al., 2020b) have also been proposed under the Block MDP setting where the dynamics are governed by a discrete latent state space and those algorithms are decoding the latent state space from the observations. Du et al. (2020) showed that for all value-based, model-based, and policy-based learning, having good approximate representations for Q-function, transition kernel or optimal Q-function is all insufficient for efficient learning and can still lead to an exponential sample complexity unless the quality of this approximation passes certain thresholds. Several representation learning algorithms have been proposed under this linear function approximation setting, Jiang et al. (2017) proposed a model-free algorithm called OLIVE which can select the correct representation from a representation function class and their algorithm is improved by Modi et al. (2021) by proposing the algorithm MOFFLE which is computationally efficient. On the other hand, Agarwal et al. (2020) proposed the model-based algorithm, FLAMBE, which can also find the correct representation from the representation function class. However, these works only address how to select the ‘correct’ representation, but fail to address how to learn a ‘good’ representation.

**Model Selection and Representation Learning in Contextual Bandits.** Since contextual bandits can be viewed as a special case of MDPs, our work is also related to some previous works on model selection in contextual bandits. The first line of work runs a multi-armed bandit at a high level while each arm corresponds to a low level contextual bandit algorithm. Following this line, [Odalric and Munos \(2011\)](#) used a variant of EXP4 ([Auer et al., 2002](#)) as the master algorithm while the EXP3 or UCB algorithm ([Auer et al., 2002](#)) serves as the base algorithm. This result is improved by CORRAL ([Agarwal et al., 2017](#)), which uses the online mirror descent framework and modifies the base algorithm to be compatible with the master. [Pacchiano et al. \(2020b\)](#) introduced a generic smoothing wrapper that can be directly applied to the base algorithms without modification. [Abbasi-Yadkori et al. \(2020\)](#) proposed a regret balancing strategy and showed that given the regret bound for the optimal base algorithm as an input, their algorithm can achieve a regret that is close to the regret of the optimal base algorithm. Following that, [Pacchiano et al. \(2020a\)](#) relaxed the requirement in [Abbasi-Yadkori et al. \(2020\)](#) by knowing each base algorithm comes with a candidate regret bound that may or may not hold during all rounds. Despite this progress, how to get the optimal regret guarantee for the general contextual learning problem remains an open question ([Foster et al., 2020a](#)). Besides those general model selection algorithms, recent works are focusing on representation learning under several different structures, thus different representations can be used at different rounds in the algorithm. [Foster et al. \(2019\)](#) studied model selection by considering a sequence of feature maps with increasing dimensions where the losses are linear in one of these feature maps. They proposed an algorithm that adaptively learns the optimal feature map, whose regret is independent of the maximum dimension. [Chatterji et al. \(2020\)](#) studied the hidden simple multi-armed bandit structure where the rewards are independent of the contextual information. [Ghosh et al. \(2021\)](#) considered a nested linear contextual bandit problem where the algorithm treats the norm bound or dimension of the weight vector in the linear model as the complexity of the problem and adaptively finds the true complexity for the given dataset. Most recently, [Papini et al. \(2021\)](#) proposed an algorithm, LEADER, that leverages good representations in linear contextual bandits. While being related, extending these algorithms and results from bandits to RL is highly nontrivial.

### 3 Preliminaries

We consider the time-inhomogeneous episodic Markov Decision Processes (MDP) denoted by  $\mathcal{M}(\mathcal{S}, \mathcal{A}, H, \{r_h\}_{h=1}^H, \{\mathbb{P}_h\}_{h=1}^H)$ . Here,  $\mathcal{S}$  is the state space,  $\mathcal{A}$  is the finite action space,  $H$  is the length of each episode,  $r_h : \mathcal{S} \times \mathcal{A} \mapsto [0, 1]$  is the reward function at step  $h$ , and  $\mathbb{P}_h(s'|s, a)$  denotes the probability for state  $s$  to transfer to state  $s'$  with action  $a$  at step  $h$ . We further assume the initial state  $s_1$  is randomly sampled from distribution  $\rho$ .

Given the MDP, we consider the *deterministic* policy  $\pi = \{\pi_h\}_{h=1}^H$  as a sequence of functions where  $\pi_h : \mathcal{S} \mapsto \mathcal{A}$  maps a state  $s$  to an action  $a$ . For each state-action pair  $(s, a) \in \mathcal{S} \times \mathcal{A}$  at time-step  $h$ , given the policy  $\pi$ , we denote the Q-function and value function as follows:

$$Q_h^\pi(s, a) = r_h(s, a) + \mathbb{E} \left[ \sum_{h'=h+1}^H r_{h'}(s_{h'}, \pi_{h'}(s_{h'})) \right], \quad V_h^\pi(s) = Q_h^\pi(s, \pi_h(s)),$$

where  $s_h = s, a_h = a$  and for all  $h' \in [h, H]$ , the distribution of  $s_{h'+1}$  is given by  $\mathbb{P}_{h'}(s_{h'}, a_{h'})$ . Both  $Q_h^\pi(s, a)$  and  $V_h^\pi(s)$  are bounded in  $[0, H]$  by definition. We further define the optimal value function

as  $V_h^*(s) := \sup_{\pi} V_h^{\pi}(s)$  and the optimal Q-function as  $Q_h^*(s, a) := \sup_{\pi} Q_h^{\pi}(s, a)$ . The optimal policy is denoted by  $\pi_h^*(s) := \operatorname{argmax}_{\pi} V_h^{\pi}(s)$  and we assume the optimal policy function  $\pi^*$  is unique.

For simplicity, for any function  $V : \mathcal{S} \mapsto \mathbb{R}$ , we denote  $[\mathbb{P}_h V](s, a) = \mathbb{E}_{s' \sim \mathbb{P}_h(s'|s, a)} V(s')$ . With this notation, we have the following Bellman equation as well as the Bellman optimality equation:

$$Q_h^{\pi}(s, a) = r_h(s, a) + [\mathbb{P}_h V_{h+1}^{\pi}](s, a), \quad Q_h^*(s, a) = r_h(s, a) + [\mathbb{P}_h V_{h+1}^*](s, a), \quad (3.1)$$

where  $V_{H+1}^*$  and  $V_{H+1}^{\pi}$  is set to be zero for any state  $s$  and policy  $\pi$ .

We consider learning the MDP structure in an *online* manner. That is to say, the algorithm runs for  $K$  episodes while for each  $k \in [K]$ , it first determines a policy  $\pi^k = \{\pi_h^k\}_{h=1}^H$  using the knowledge it has collected from the environment. Then the agent follows the policy and the dynamic of the MDP. In detail, for each step  $h \in [H]$ , the agent first observes the state  $s_h^k$ , chooses an action  $a_h^k$  by the policy  $\pi_h^k$  and then transits to the next state  $s_{h+1}^k$  generated by the MDP and receives the reward  $r_{h+1}^k$ . The *total regret* for the first  $K$  episodes  $\operatorname{Regret}(K)$  is defined as

$$\operatorname{Regret}(K) = \sum_{k=1}^K V_1^*(s_1^k) - V_1^{\pi^k}(s_1^k).$$

In this paper, we are interested in proving a problem-dependent regret bound. To achieve this, we need the following strictly positive minimal sub-optimality gap assumption (Simchowitz and Jamieson, 2019; Yang et al., 2021; He et al., 2021).

**Assumption 3.1.** Assume  $\operatorname{gap}_{\min} > 0$ , where

$$\operatorname{gap}_{\min} := \inf_{h, s, a} \{\operatorname{gap}_h(s, a) : \operatorname{gap}_h(s, a) \neq 0\}, \quad \operatorname{gap}_h(s, a) := V_h^*(s) - Q_h^*(s, a). \quad (3.2)$$

We consider the bilinear MDPs in Yang and Wang (2020), where the probability transition kernel is a bi-linear function of the feature vectors.

**Definition 3.2** (Bilinear MDPs, Yang and Wang 2020). For each state-action-state triple  $(s, a, s') \in \mathcal{S} \times \mathcal{A} \times \mathcal{S}$ , vectors  $\phi(s, a) \in \mathbb{R}^d$ ,  $\psi(s') \in \mathbb{R}^{d'}$  are known as the feature vectors. There exists an unknown matrix  $\mathbf{M}_h^* \in \mathbb{R}^{d \times d'}$  for all  $h \in [H]$  such that  $\mathbb{P}_h(s'|s, a) = \phi^{\top}(s, a) \mathbf{M}_h^* \psi(s')$ . We denote  $\mathbf{K}_{\psi} = \sum_{s \in \mathcal{S}} \psi(s) \psi^{\top}(s)$  which is assumed to be invertible. Let  $\Psi = (\psi(s_1), \psi(s_2), \dots, \psi(s_{|S|}))^{\top} \in \mathbb{R}^{|S| \times d'}$  be the matrix of all  $\psi$  features. We assume that for all  $h \in [H]$ ,  $\|\mathbf{M}_h^*\|_F^2 \leq C_{\mathbf{M}} d$ , for all  $(s, a) \in \mathcal{S} \times \mathcal{A}$ ,  $\|\phi(s, a)\|_2^2 \leq C_{\phi} d$ , and for all  $\mathbf{v} \in \mathbb{R}^{|S|}$ ,  $\|\Psi^{\top} \mathbf{v}\|_2 \leq C_{\psi} \|\mathbf{v}\|_{\infty}$  and  $\|\Psi \mathbf{K}_{\psi}^{-1}\|_{2, \infty} \leq C'_{\psi}$ , where  $C_{\mathbf{M}}, C_{\phi}, C_{\psi}$  and  $C'_{\psi}$  are all positive constants.

The bilinear MDP in Definition 3.2 is a special case of the low-rank MDP/Linear MDP. In the general low-rank MDP setting (Yang and Wang, 2019; Jin et al., 2020), one assumes  $\mathbb{P}_h(s'|s, a) = \langle \phi(s, a), \theta_h(s') \rangle$  where  $\theta_h(s')$  is a  $d$ -dimensional unknown measure. Instead, we parameterize  $\theta_h(s')$  with the product of an unknown matrix  $\mathbf{M}_h^*$  and feature vector  $\psi(s')$ . Furthermore, the Linear MDP assumes the reward function is also a linear function over feature mapping  $\phi(s, a)$ , while here we assume the reward function is known for the simplicity of presentation. As pointed out in Yang and Wang (2020), this could be easily replaced by assuming the reward function is also a linear function of representation  $\phi(s, a)$  by adding a step of the optimistic reward function estimation like LinUCB (Chu et al., 2011) without changing the analysis a lot.

Given the linear function representation of the MDP structure, we consider learning the good representation  $\phi(s, a)$  for different state-action pairs in the representation function class  $\Phi$ . We

make the following assumption on the representation function class  $\Phi$  in order to implicitly provide good representations for all possible state-action pairs.

**Assumption 3.3.** A representation function class  $\Phi$  is admissible if every  $\phi \in \Phi$  satisfies Definition 3.2 with different dimension  $d_\phi$ , parameter  $\mathbf{M}_{h,\phi}^*$  and constant  $C_\phi$ . Define  $\Lambda_{h,\phi}$  as

$$\Lambda_{h,\phi} = \mathbb{E}_{s_h} \left[ \phi(s_h, \pi_h^*(s_h)) \phi^\top(s_h, \pi_h^*(s_h)) \right] \in \mathbb{R}^{d_\phi \times d_\phi},$$

where the distribution of  $s_h$  at time-step  $h$  is defined by  $s_1 \sim \rho$  and  $s_{i+1} \sim \mathbb{P}_i(\cdot | s_i, \pi_i^*(s_i))$  for all  $i \in [h-1]$ . Then for all  $\phi \in \Phi$ , there exists an absolute positive constant  $\sigma_\phi > 0$  such that for all  $h \in [H]$ , the minimum non-zero eigenvalue for  $\Lambda_{h,\phi}$  is no smaller than  $\sigma_\phi$ . Let  $\mathcal{Z}_{h,\phi} = \{(s, a) \in \mathcal{S} \times \mathcal{A} | \phi(s, a) \in \text{Im}(\Lambda_{h,\phi})\}$  be the state-action pair whose representation  $\phi$  belongs to the column space of  $\Lambda_{h,\phi}$ , we assume that for all  $h \in [H]$ ,  $\mathcal{S} \times \mathcal{A} \subseteq \bigcup_{\phi \in \Phi} \mathcal{Z}_{h,\phi}$ .

**Remark 3.4.** Several related assumptions, usually referred to as *diversity assumptions*, have been made to lower bound the minimum eigenvalue of the term  $\phi\phi^\top$ , which is comprehensively discussed in Papini et al. (2021). We extend the assumption from linear bandit to the reinforcement learning setting, where the distribution of the state at time-step  $h$  is defined by the optimal policy. We note that a similar but strictly stronger assumption, called ‘uniformly excited features’ has been made by Wei et al. (2021) in the infinite time-horizon average reward MDP setting. There, they assume  $\Lambda$  is strictly positive definite for *all* possible policies  $\pi$ . In contrast, here we only need  $\Lambda$  to be strictly positive for the distribution induced by the *optimal* policy. Thus, our assumption is strictly weaker than theirs. This also implies that the states which rarely show up in the optimal policy do not affect the quality of the representation too much.

## 4 Proposed Algorithm

In this section, we propose the *Representation Learning for EXploration and EXploitation* (ReLEX) algorithm to learn a good representation among all possible representations in a finite representation function class  $\Phi$ . As shown in Algorithm 1, it maintains a different parameter estimation for each individual representation function  $\phi \in \Phi$ . For each representation function  $\phi$ , consider the following expression under Definition 3.2,

$$\begin{aligned} \left[ \mathbb{P}_h \psi(\cdot) \mathbf{K}_\psi^{-1} \right] (s, a) &= \sum_{s' \in \mathcal{S}} \mathbb{P}_h(s' | s, a) \psi^\top(s') \mathbf{K}_\psi^{-1} \\ &= \sum_{s' \in \mathcal{S}} \phi^\top(s, a) \mathbf{M}_{h,\phi}^* \psi(s') \psi^\top(s') \mathbf{K}_\psi^{-1} \\ &= \phi^\top(s, a) \mathbf{M}_{h,\phi}^*, \end{aligned}$$

where the last equality utilizes the fact that  $\mathbf{K}_\psi = \sum_{s' \in \mathcal{S}} \psi(s') \psi^\top(s')$ . Thus, the estimation of  $\mathbf{M}_{h,\phi}^*$  can be obtained from the following ridge regression problem analytically given the sampled triples  $\{s_h^j, a_h^j, s_{h+1}^j\}_{j=1}^{k-1}$  in Line 5 in Algorithm 1.

After getting estimation  $\mathbf{M}_{h,\phi}^k$ , the algorithm can recursively estimate the Q-function starting from  $Q_{H+1} = 0$ . Given we can compute the estimated value function  $V_{h+1}^k$  and denote  $\mathbf{v}_{h+1}^k =$

$(V_{h+1}^k(S_1), \dots, V_{h+1}^k(S_{|S|}))^\top \in \mathbb{R}^{|S|}$ , from the Bellman equation, the Q function at step  $h$  can be written as

$$Q_{h,\phi}^k(s, a) = r(s, a) + [\mathbb{P}_h V_{h+1}^k](s, a) = r(s, a) + \sum_{s' \in \mathcal{S}} \phi^\top(s, a) \mathbf{M}_{h,\phi}^k \psi(s') V_{h+1}^k(s').$$

Given the definition of  $\Psi$ , the optimistic estimation of the Q-function is provided in [Yang and Wang \(2020\)](#) by adding a confidence radius  $\Gamma_{h,\phi}(s, a)$

$$Q_{h,\phi}^k(s, a) = r(s, a) + \sum_{s' \in \mathcal{S}} \phi^\top(s, a) \mathbf{M}_{h,\phi}^k \psi(s') V_{h+1}^k(s') + \Gamma_{h,\phi}^k(s, a), \quad (4.1)$$

$$\Gamma_{h,\phi}^k(s, a) = C_\psi H \sqrt{\beta_{k,\phi} \phi^\top(s, a) (\mathbf{U}_{h,\phi}^k)^{-1} \phi(s, a)},$$

where the covariance matrix  $\mathbf{U}_{h,\phi}^k$  is calculated in Line 6 and  $\beta_{k,\phi}$  is the confidence parameter. Therefore, we have built the upper confidence bound for the  $Q_h^k(s, a)$  for each representation  $\phi \in \Phi$ . As a result, we can utilize the tightest available upper confidence bound for the Q-function estimation and by the greedy policy, the value function  $V_h^k$  is defined in Line 9.

Compared with the original algorithm in [Yang and Wang \(2020\)](#), our algorithm can learn different representations for different state-action pairs. By selecting the tightest upper confidence bound, our algorithm can leverage the representation power which only provides good embedding for some state-action pairs. That is, if a representation can provide very accurate estimation for certain state-action pairs while having poor performance for others, our algorithm can adaptively select that representation for those accurate state-action pairs and discard this representation otherwise. As a result, our algorithm enjoys a performance gain compared with running the algorithm by [Yang and Wang \(2020\)](#) using a single representation. This explains the benefit of representation learning for reinforcement learning.

---

**Algorithm 1** Representation Learning for EXploration and EXploitation (ReLEX)

---

```

1: for episodes  $k = 1, \dots, K$  do
2:   Received the initial state  $s_1^k$ .
3:   for step  $h = H, \dots, 1$  do
4:     for representation  $\phi \in \Phi$  do
5:       Calculate  $\mathbf{M}_{h,\phi}^k = \operatorname{argmin}_{\mathbf{M}} \sum_{j=1}^{k-1} \|\psi(s_{h+1}^j) \mathbf{K}_\psi^{-1} - \phi(s_h^j, a_h^j) \mathbf{M}\|_2^2 + \|\mathbf{M}\|_F^2$ 
6:       Calculate  $\mathbf{U}_{h,\phi}^k = \mathbf{I} + \sum_{j=1}^{k-1} \phi(s_h^j, a_h^j) \phi^\top(s_h^j, a_h^j)$ 
7:       Calculate  $Q_{h,\phi}^k(s, a)$  as of (4.1)
8:     end for
9:     Set  $Q_h^k(s, a) = \min_{\phi \in \Phi} \{Q_{h,\phi}^k(s, a)\}$ ,  $V_h^k(s) = \min\{\max_a Q_h^k(s, a), H\}$ 
10:  end for
11:  for step  $h = 1, \dots, H$  do
12:    Take action  $a_h^k \leftarrow \operatorname{argmax}_a Q_h^k(s_h^k, a)$  and receive next state  $s_{h+1}^k$ 
13:  end for
14: end for

```

---

## 5 Main Results

We will provide the regret bound for ReLEX in this section.

**Theorem 5.1.** Under Assumptions 3.1 and 3.3, set  $\beta_{k,\phi} = c(C_{\mathbf{M}} + C'_{\psi})^2 d_{\phi} \log(kHC_{\phi}|\Phi|/\delta)$  in Algorithm 1, where  $c$  is an absolute positive constant, then with probability at least  $1 - 5\delta$ , there exists a threshold

$$k^* = \max_{\phi \in \Phi} \{\text{poly}(d_{\phi}, \sigma_{\phi}^{-1}, H, \log(|\Phi|/\delta), \text{gap}_{\min}^{-1}, C_{\phi}, C_{\psi}, C_{\mathbf{M}}, C'_{\psi})\} \quad (5.1)$$

independent from episode number  $k$ , the regret for the first  $k$  episodes is upper bounded by

$$\begin{aligned} & \text{Regret}(k) \\ & \leq \min_{\phi \in \Phi} \left\{ \frac{128C_{\psi}^2 H^5 d_{\phi}^2 c(C_{\mathbf{M}} + C'_{\psi})^2 \log(\min\{k, k^*\}HC_{\phi}|\Phi|/\delta) \log(1 + C_{\phi} \min\{k, k^*\}d_{\phi})}{\text{gap}_{\min}} \right\} \\ & \quad + \frac{96H^4 \log(2 \min\{k, k^*\}(1 + \log(H/\text{gap}_{\min}))|\Phi|/\delta)}{\text{gap}_{\min}} \\ & \quad + \frac{16}{3} H^2 \log(((1 + \log(H \min\{k, k^*\})) \min\{k, k^*\})^2 |\Phi|/\delta) + 2. \end{aligned}$$

**Remark 5.2.** It is easy to verify that the regret bound shows a phase transition when the episode number  $k$  increases. First, when  $k \leq k^*$ , the regret is upper bounded by  $\tilde{\mathcal{O}}(d^2 H^5 \log(k) \text{gap}_{\min}^{-1})$ , which is exactly the logarithmic regret bound given by Lemma 6.3. However, when  $k \geq k^*$ , the regret bound is  $\tilde{\mathcal{O}}(d^2 H^5 \log(k^*) \text{gap}_{\min}^{-1})$ . Since the  $k^*$  is independent from  $k$  by (5.1), the regret bound turns out to be a problem-dependent constant regret bound which no longer grows as the total number of episode  $k$  increases. This result is well aligned with our intuition: once we have a fixed strictly positive sub-optimality gap, at the first few episodes, the regret might grow. However, when the agent collects enough data, an efficient learner can learn the environment well and thus will no longer introduce any additional sub-optimality to the regret.

**Remark 5.3.** If Assumption 3.3 does not hold, then  $k^* = \infty$ . In this case,  $\min\{k, k^*\} = k$ , and our regret bound degenerates to the gap-dependent regret bound. Similar bounds have been proved in He et al. (2021) for both linear MDPs and linear mixture MDPs. Our bound has the same dependency in  $H, \text{gap}_{\min}$  and episode number  $k$ . However, in terms of  $d$ , instead of  $\mathcal{O}(d^3)$  dependency for linear MDP, ours has  $\mathcal{O}(d^2)$  dependency, and is the same as that for linear mixture MDPs. This difference stems from estimating the MDP parameter  $\mathbf{M}_{h,\phi}^*$ , which is similar to that in UCRL-VTR (Ayoub et al., 2020) algorithm for learning linear mixture MDPs. As a comparison, the LSVI-UCB (Jin et al., 2020) algorithm for learning linear MDPs estimates the parameter for Q-function, which will introduce additional dependency on  $d$  due to covering-based argument. Also, it is easy to verify that, ignoring the logarithmic factor  $\log(|\Phi|)$ , our regret based on representation learning is always no worse than the regret achieved by using a single representation.

**Remark 5.4.** We notice that there is additional  $\log(|\Phi|)$  dependency in our regret bound, which is the cost of the representation learning. Such a  $\log(|\Phi|)$  result is non-trivial since directly concatenating those  $|\Phi|$  representations will lead to a regret bound polynomial in  $|\Phi|$  (Modi et al., 2020). Furthermore, such a  $\log(|\Phi|)$  dependency makes it possible to extend our result to some infinite representation function class with bounded statistical complexity (Agarwal et al., 2020). Also, when  $|\Phi| = 1$  which means there is only one representation function, Assumption 3.3 provides a criterion for a ‘good representation’ and such a ‘good representation’ can improve the problem-dependent regret bound from  $\mathcal{O}(\log(k))$  to a constant regret bound.

## 6 Proof Outline

In this section we will give the key technical lemmas and the proof sketch for Theorem 5.1. We defer the full proof of these lemmas to Appendix B.

First, we need to define a “good event” which happens with high probability, that the estimation  $\mathbf{M}_h^k$  is close to the target  $\mathbf{M}_h^*$ . This definition was originally introduced in Yang and Wang (2020).

**Lemma 6.1** (Lemma 15, Yang and Wang (2020)). Define the following event as  $\mathcal{E}_\phi^k$ ,

$$\mathcal{E}_\phi^k = \left\{ \text{tr} \left[ (\mathbf{M}_{h,\phi}^j - \mathbf{M}_{h,\phi}^*)^\top \mathbf{U}_{h,\phi}^j (\mathbf{M}_{h,\phi}^j - \mathbf{M}_{h,\phi}^*) \right] \leq \beta_{j,\phi}, \forall j \leq k, \forall h \in [H] \right\}.$$

With  $\beta_{k,\phi} = c(C_M + C_\psi^2)d_\phi \log(kHC_\phi/\delta)$  for some absolute constant  $c > 0$ , we have  $\Pr(\mathcal{E}_\phi^K) \geq 1 - \delta$  for all  $\phi \in \Phi$ .

**Remark 6.2.** The proof of Lemma 6.1 remains the same since the regression does not depend on the policy  $\pi$ . We also make the dependency of  $\delta$  explicit in  $\beta_{k,\phi}$ , which can be inferred from the proof of Lemma 15 in Yang and Wang (2020).

The next lemma shows a problem-dependent regret bound for the bilinear MDP in Definition 3.2.

**Lemma 6.3.** Under Assumption 3.1, setting parameter  $\beta_{k,\phi}$  as in Theorem 5.1. Then suppose  $\mathcal{E}_\phi^K$  holds for all  $\phi \in \Phi$ . Then with probability at least  $1 - 3\delta$ , the regret for the very first  $k \in [K]$  episodes is controlled by

$$\begin{aligned} \text{Regret}(k) \leq \min_{\phi \in \Phi} & \left\{ \frac{128C_\psi^2 H^5 d_\phi \beta_{k,\phi} \log(1 + C_\phi k d_\phi)}{\text{gap}_{\min}} \right\} \\ & + \frac{96H^4 \log(2k(1 + \log(H/\text{gap}_{\min})))|\Phi|/\delta}{\text{gap}_{\min}} \\ & + \frac{16}{3} H^2 \log(((1 + \log(Hk))k^2|\Phi|/\delta) + 2), \end{aligned} \quad (6.1)$$

while the sub-optimality gap for each  $h$  is controlled by

$$\begin{aligned} \sum_{i=1}^k (V_h^*(s_h^i) - Q_h^*(s_h^i, a_h^i)) \leq \min_{\phi \in \Phi} & \left\{ \frac{64C_\psi^2 H^4 d_\phi \beta_{k,\phi} \log(1 + C_\phi k d_\phi)}{\text{gap}_{\min}} \right. \\ & \left. + \frac{48H^3 \log(2k|\Phi|(1 + \log(H/\text{gap}_{\min})/\delta))}{\text{gap}_{\min}} \right\}. \end{aligned} \quad (6.2)$$

It is easy to verify that when there is only one representation function in  $\Phi$  (let  $d = d_\phi$  for simplicity), Lemma 6.3 yields an  $\mathcal{O}(H^5 d^2 \log(k/\delta) \text{gap}_{\min}^{-1})$  problem-dependent bound. Comparing our result with He et al. (2021), ours matches the problem-dependent bound for Linear Mixture MDP  $\mathcal{O}(H^5 d^2 \log(k/\delta) \text{gap}_{\min}^{-1})$  and is better than the problem-dependent bound for Linear MDP  $\mathcal{O}(H^5 d^3 \log(k/\delta) \text{gap}_{\min}^{-1})$  by a factor  $d$ . This improvement comes from the bilinear MDP structure in Definition 3.2. Moreover, it is obvious that when  $|\Phi| > 1$ , Algorithm 1 can achieve regret no worse than any possible regret achieved by a single representation, with an additional  $\log(|\Phi|)$  factor. Lemma 6.3 also suggests an  $\mathcal{O}(H^4 d^2 \log(k/\delta) \text{gap}_{\min}^{-1})$  bound for the summation of the sub-optimality gap. Based on that, the next lemma shows that the “covariance matrix”  $\mathbf{U}_{h,\phi}^k$  is almost linearly growing with respect to  $k$  given Assumption 3.3.

**Lemma 6.4.** Under Assumptions 3.1 and 3.3, with probability at least  $1 - \delta$ , we have for all  $k \in [K], h \in [H], \phi \in \Phi$ ,

$$\begin{aligned} \mathbf{U}_{h,\phi}^k &\succeq (k-1)\mathbf{\Lambda}_{h,\phi} - \iota \mathbf{I}_{d_\phi}, \\ \iota &= \frac{C_\phi d_\phi}{\text{gap}_{\min}} \sum_{i=1}^h \sum_{j=1}^{k-1} \text{gap}_i(s_i^j, a_i^j) + C_\phi d_\phi \sqrt{32H(k-1) \log(d_\phi |\Phi| Hk(k+1)/\delta)} - 1. \end{aligned}$$

Compared with Lemma 9 in Papini et al. (2021) which shows a similar result for linear contextual bandits, the proof of Lemma 6.4 is more challenging: The distribution of  $s_h$  is induced by the optimal policy  $\pi^*$  in Assumption 3.3 but we can only use the estimated policy  $\pi^k$  to sample  $s_h$ . As a result, the sub-optimality and the randomness for the steps before  $h$  ( $i < h$ ) will all contribute to this distribution mismatch. Therefore, our result contains an additional summation over  $h$  to account for this effect.

Finally, given Lemma 6.4, we can provide a constant threshold  $\tau$  such that if the episode number  $k$  goes beyond  $\tau$ , then the sub-optimality gap is bounded by  $\mathcal{O}(\sqrt{1/k})$ .

**Lemma 6.5.** Under Assumptions 3.1 and 3.3, assuming the conditions in Lemmas 6.3 and 6.4 hold and  $\mathcal{E}_\phi^K$  holds for all  $\phi \in \Phi$ , then there exists a threshold

$$\tau = \text{poly}(d_\phi, \sigma_\phi^{-1}, H, \log(|\Phi|/\delta), \text{gap}_{\min}^{-1}, C_\phi, C_\psi, C_{\mathbf{M}}, C'_\psi)$$

such that for all  $\tau \leq k \leq K$ , for all  $h \in [H], s \in \mathcal{S}$  we have

$$\text{gap}_h(s, \pi_h^k(s)) \leq 2C_\psi H^2 \max_{\phi \in \Phi} \left\{ d_\phi \sqrt{2C_\phi \beta_{k,\phi} / (\sigma_\phi k)} \right\}.$$

Lemma 6.5 suggests that when the episode number  $k$  goes beyond  $\tau$ , then policy  $\pi^k$  will contribute a sub-optimality up to  $\mathcal{O}(\sqrt{1/k})$ . Thus there would exist a threshold  $k^*$  such that when  $k \geq k^*$ , the policy  $\pi^k$  will not contribute any sub-optimality at any step  $h$  given the minimal sub-optimality gap  $\text{gap}_{\min}$ . With that, it suffices to provide the proof for Theorem 5.1.

*Proof of Theorem 5.1.* We pick  $\beta_{k,\phi} = c(C_{\mathbf{M}} + C'_\psi)^2 d_\phi \log(kHC_\phi |\Phi|/\delta)$  to make sure with probability at least  $1 - \delta$ , event  $\mathcal{E}_\phi^K$  holds for all  $\phi \in \Phi$ . By the definition of the sub-optimality gap, we have  $\text{gap}_h(s, a) \geq \text{gap}_{\min}(s, a)$  as long as  $\text{gap}_h(s, a) \neq 0$ . If

$$k > \max \left\{ \frac{8C_\psi^2 H^4}{\text{gap}_{\min}^2} \max_{\phi \in \Phi} \left\{ \frac{C_\phi d_\phi^2 \beta_{k,\phi}}{\sigma_\phi} \right\}, \tau \right\}. \quad (6.3)$$

then we have for all  $\phi \in \Phi$ ,

$$2C_\psi H^2 d_\phi \sqrt{2C_\phi \beta_{k,\phi} / (\sigma_\phi k)} < \text{gap}_{\min}.$$

Thus, by Lemma 6.5, we have

$$\text{gap}_h(s, \pi_h^k(s)) \leq 2C_\psi H^2 \max_{\phi \in \Phi} \left\{ d_\phi \sqrt{2C_\phi \beta_{k,\phi} / (\sigma_\phi k)} \right\} < \text{gap}_{\min},$$

and it implies  $\text{gap}_h(s, \pi_h^k(s)) = 0$ . Since from the parameter setting,  $\beta_{k,\phi} = \mathcal{O}(\log(k))$ , it is easy to verify that there exists a threshold  $k^* = \text{poly}(C_\psi, C'_\psi, C_M, C_\phi, d_\phi, H, \sigma_\phi^{-1}, \text{gap}_{\min}^{-1}, \tau)$  such that all  $k \geq k^*$  satisfy (6.3). Thus we conclude that  $\text{gap}_h(s, \pi_h^k(s)) = 0$  for all  $k \geq k^*$ . Since the optimal policy  $\pi^*$  is unique, it follows that  $\pi^k = \pi^*$ .

Thus when  $k \geq k^*$ , the regret could be decomposed by

$$\begin{aligned} \text{Regret}(k) &= \sum_{j=1}^k V_1^*(s_1^j) - V_1^{\pi^j}(s_1^j) \\ &= \sum_{j=1}^{k^*} V_1^*(s_1^j) - V_1^{\pi^j}(s_1^j) + \sum_{j=1+k^*}^k V_1^*(s_1^j) - V_1^{\pi^j}(s_1^j) \\ &= \text{Regret}(k^*) + 0, \end{aligned}$$

where the last equality comes from the fact that  $\pi^j = \pi^*$  thus  $V_1^*(s) = V_1^{\pi^j}(s)$  for all  $s \in \mathcal{S}$  when  $j \geq k^*$ . Combining this case with the case  $k \leq k^*$ , we can conclude that  $\text{Regret}(k) \leq \text{Regret}(\min\{k, k^*\})$ . By Lemma 6.3, we have the regret is bounded by

$$\begin{aligned} &\text{Regret}(k) \\ &\leq \min_{\phi \in \Phi} \left\{ \frac{128C_\psi^2 H^5 d_\phi^2 c(C_M + C'_\psi)^2 \log(\min\{k, k^*\}) H C_\phi |\Phi| / \delta \log(1 + C_\phi \min\{k, k^*\} d_\phi)}{\text{gap}_{\min}} \right\} \\ &\quad + \frac{96H^4 \log(2 \min\{k, k^*\})(1 + \log(H/\text{gap}_{\min})) |\Phi| / \delta}{\text{gap}_{\min}} \\ &\quad + \frac{16}{3} H^2 \log(((1 + \log(H \min\{k, k^*\})) \min\{k, k^*\})^2 |\Phi| / \delta) + 2 \end{aligned}$$

with probability at least  $1 - 5\delta$  by taking the union bound of Lemma 6.3, Lemma 6.4 and  $\mathcal{E}_\phi^K$  holds.  $\square$

## 7 Conclusion and Future Work

We study the effect of representation learning for reinforcement learning. By considering a special class (Yang and Wang, 2020) of low-rank MDP (Yang and Wang, 2019; Jin et al., 2020), we are able to show the proposed algorithm, ReLEX, enjoys a constant regret bound, given some mild ‘coverage’ assumption. To the best of our knowledge, this is the first paper to study how to implicitly learn a good representation given a class of correct representation functions in reinforcement learning.

This promising result suggests a few interesting directions for future research. First, currently we are studying a special class (Yang and Wang, 2020) of low-rank MDP instead of the general low-rank MDP (Yang and Wang, 2019; Jin et al., 2020). The theoretical analysis for the representation learning task shows that getting a  $\log(|\Phi|)$  instead of  $|\Phi|$  dependency is challenging. We will address this challenge in Appendix A.

A second possible follow up work can be combining this work with FLAMBE (Agarwal et al., 2020) or MOFFLE (Modi et al., 2021). Modi et al. (2021); Agarwal et al. (2020) can select the ‘correct’ representations and our work can select the ‘good’ representation from those ‘correct’ representations. Having such an integrated approach will help design more practical, theory-backed representation learning algorithms in reinforcement learning.

## A More Discussions on Linear MDPs

In this section, we provide a brief comparison between different assumptions in [Yang et al. \(2020\)](#) and [Jin et al. \(2020\)](#). We will first introduce the formal definition of Linear MDPs.

**Definition A.1** ([Jin et al. 2020](#)). MDP  $\mathcal{M}(\mathcal{S}, \mathcal{A}, H, \{r_h\}_{h=1}^H, \{\mathbb{P}_h\}_{h=1}^H)$  is a Linear MDP such that for any step  $h \in [H]$ , there exists an unknown vector  $\boldsymbol{\mu}_h$ , unknown measures  $\boldsymbol{\theta}_h = (\boldsymbol{\theta}_h^{(1)}, \dots, \boldsymbol{\theta}_h^{(d)})^\top$  and a known feature mapping  $\phi : \mathcal{S} \times \mathcal{A} \mapsto \mathbb{R}^d$ , where for each  $(s, a, s') \in \mathcal{S} \times \mathcal{A} \times \mathcal{S}$ ,

$$\mathbb{P}_h(s'|s, a) = \langle \phi(s, a), \boldsymbol{\theta}_h(s') \rangle, \quad r_h = \langle \phi(s, a), \boldsymbol{\mu}_h \rangle. \quad (\text{A.1})$$

We further assume that  $\|\phi(s, a)\|_2 \leq 1$  for all  $(s, a) \in \mathcal{S} \times \mathcal{A}$  and  $\|\boldsymbol{\mu}_h\|_2 \leq \sqrt{d}$ ,  $\|\boldsymbol{\theta}_h(\mathcal{S})\|_2 \leq \sqrt{d}$  for all  $h \in [H]$ .

### A.1 Comparison between Bilinear MDPs and Linear MDPs

We can show that the Bilinear MDP described in [Definition 3.2](#) strictly belongs to the Linear MDP class in [Jin et al. \(2020\)](#).

In [Jin et al. \(2020\)](#),  $\|\boldsymbol{\theta}(\mathcal{S})\|_2 \leq \sqrt{d}$  gives

$$\left\| \sum_{s' \in \mathcal{S}} \boldsymbol{\theta}(s') v(s') \right\|_2 \leq \sqrt{d} \|\mathbf{v}\|_\infty, \quad (\text{A.2})$$

substituting  $\boldsymbol{\theta}(s')$  with  $\mathbf{M}^* \boldsymbol{\psi}(s')$ , [Definition 3.2](#) yields

$$\left\| \sum_{s' \in \mathcal{S}} \mathbf{M}^* \boldsymbol{\psi}(s') v(s') \right\|_2 \leq \|\mathbf{M}^*\|_2 \left\| \sum_{s' \in \mathcal{S}} \boldsymbol{\psi}(s') v(s') \right\|_2 \leq \|\mathbf{M}^*\|_F \|\boldsymbol{\Psi}^\top \mathbf{v}\|_2 \leq \sqrt{C_{\mathbf{M}} d} C_\psi \|\mathbf{v}\|_\infty,$$

which is compatible with [\(A.2\)](#) up to a constant factor  $C_\psi \sqrt{C_{\mathbf{M}}}$ . By setting  $C_\psi = C_{\mathbf{M}} = 1$ , [Definition 3.2](#) can imply  $\|\boldsymbol{\theta}(\mathcal{S})\|_2 \leq \sqrt{d}$ .

### A.2 Challenges in Linear MDPs

In this subsection, we provide a brief explanation about the challenges when migrating our analysis to the general Linear MDP ([Jin et al., 2020](#)) setting ([Definition A.1](#)). For Linear MDPs, the Q-function is a linear function over the representation  $\phi$ . Then following the LSVI-UCB algorithm ([Jin et al., 2020](#)), we consider the following ridge regression:

$$\mathbf{w}_{h,\phi}^k = \operatorname{argmin}_{\mathbf{w} \in \mathbb{R}^d} \lambda \|\mathbf{w}\|_2^2 + \sum_{j=1}^{k-1} \left( \langle \phi(s, a), \mathbf{w} \rangle - r_h(s_h^j, a_h^j) - \max_a Q_{h+1}^k(s_{h+1}^j, a) \right)^2.$$

Then the optimistic Q-function for each representation is defined by

$$Q_{h,\phi}^k(s, a) = \langle \mathbf{w}_{h,\phi}^k, \phi(s, a) \rangle + \beta_{k,\phi} \sqrt{\phi^\top(s, a) (\mathbf{U}_{h,\phi}^k)^{-1} \phi(s, a)}.$$

As [Algorithm 1](#) indicates, the tightest optimistic Q-function among all  $\phi \in \Phi$  is selected by  $Q_h^k(s, a) = \min_{\phi \in \Phi} Q_{h,\phi}^k(s, a)$ .

It is worth noting that we do not estimate the target parameter  $\theta_{h,\phi}$  or  $\mu_{h,\phi}$ . Instead, we estimate the parameter  $\mathbf{w}_h$ , which is the parameter of the Q-function. Such an estimation needs to deal with the function class the Q-function belongs to, in particular, the covering number of that function class. By Lemma D.6 in [Jin et al. \(2020\)](#), we have

$$V(s) = \min \left\{ \max_a \left\{ \min_{\phi \in \Phi} \left\{ \mathbf{w}_\phi^\top \phi(s, a) + \beta \sqrt{\phi^\top(s, a) \mathbf{U}_\phi^{-1} \phi(s, a)} \right\} \right\}, H \right\}$$

with parameter  $\{\mathbf{w}_\phi, \mathbf{U}_\phi\}_{\phi \in \Phi}$ .

Since the number of the tuple  $\{\mathbf{w}_\phi, \mathbf{U}_\phi\}$  is  $|\Phi|$ , it is obvious that the logarithm covering number  $\log \mathcal{N}_\epsilon$  contains a factor  $|\Phi|$ . Then following the proof of Lemma D.6 in [Jin et al. \(2020\)](#), we know  $\beta$  contains an additional factor  $\sqrt{|\Phi|}$ . Finally, the problem-dependent regret bound is  $\mathcal{O}(|\Phi| \log(k))$  following the proof of [He et al. \(2021\)](#).

However, such an  $\mathcal{O}(|\Phi| \log(k))$  regret has a polynomial dependence on the size of the representation function class  $|\Phi|$ , which is worse than our proved regret for bilinear MDPs in [Theorem 5.1](#). The polynomial dependence is unacceptable when  $|\Phi|$  is large. We leave extending ReLEX to the general Linear MDP and achieving a regret bound in  $\mathcal{O}(\log(|\Phi|))$  as an open problem.

## B Proof of Lemmas in Section 6

In this section, we provide the proof of the technical lemmas in [Section 6](#).

### B.1 Filtration

To facilitate our proof, we define the filtration list as follows

$$\mathcal{F}_h^k = \left\{ \left\{ \left\{ s_i^j, a_i^j \right\}_{i=1, j=1}^{H, k-1}, \left\{ s_i^k, a_i^k \right\}_{i=1}^h \right\} \right\}.$$

It is easy to verify that  $s_h^k, a_h^k$  are both  $\mathcal{F}_h^k$ -measurable. Also, for any function  $f$  built on  $\mathcal{F}_h^k$ ,  $f(s_{h+1}^k) - [\mathbb{P}_h f](s_h^k, a_h^k)$  is  $\mathcal{F}_{h+1}^k$ -measurable and it is also a zero-mean random variable conditioned on  $\mathcal{F}_h^k$ .

Arranging the filtrations as

$$\mathcal{F} = \{\mathcal{F}_1^1, \dots, \mathcal{F}_H^1, \dots, \mathcal{F}_1^k, \dots, \mathcal{F}_h^k, \dots, \mathcal{F}_H^k, \dots, \mathcal{F}_1^K, \dots, \mathcal{F}_H^K\},$$

we will use  $\mathcal{F}$  as the filtration set for the following proof.

### B.2 Proof of Lemma 6.3

To prove this lemma, we first need the following lemma showing the estimator  $Q_{h,\phi}^k$  is always optimistic.

**Lemma B.1.** Suppose the event  $\mathcal{E}_\phi^K$  holds for all  $\phi \in \Phi$ , then for any  $(s, a) \in \mathcal{S} \times \mathcal{A}$ ,  $Q_h^*(s, a) \leq Q_{h,\phi}^k(s, a)$ .

Then the following lemma suggests the error between the estimated Q function and the target Q function at time-step  $h$  can be controlled by the error at  $(h+1)$ -th step and the UCB bonus term.

**Lemma B.2.** Suppose the event  $\mathcal{E}_\phi^K$  holds, then for any  $(s, a) \in \mathcal{S} \times \mathcal{A}, k \in [K]$  and any policy  $\pi$ ,

$$Q_h^k(s, a) - Q_h^\pi(s, a) \leq 2C_\psi H \sqrt{\beta_{k, \phi} \phi^\top(s, a) (\mathbf{U}_{h, \phi}^k)^{-1} \phi(s, a)} + [\mathbb{P}_h(V_{h+1}^k - V_{h+1}^\pi)](s, a).$$

We also need the following lemma, which is similar to Lemma 6.2 in He et al. (2021).

**Lemma B.3.** For any  $0 < \Delta \leq H$ , if the event  $\mathcal{E}_\phi^K$  holds for all  $\phi \in \Phi$ , then with probability at least  $1 - \delta$ , for any  $k \in [K]$ ,

$$\sum_{j=1}^k \mathbb{1}[V_h^*(s_h^j) - Q_h^{\pi^j}(s_h^j, a_h^j) \geq \Delta] \leq \frac{16C_\psi H^4 d_\phi \beta_{k, \phi} \log(1 + C_\phi k d_\phi) + 12H^3 \log(2k/\delta)}{\Delta^2}.$$

Then we need the following lemma from He et al. (2021) to upper-bound the regret by the summation of the suboptimality.

**Lemma B.4** (Lemma 6.1, revised, He et al. (2021)). For each MDP  $\mathcal{M}$ , with probability at least  $1 - 2\delta$ , for all  $k \in [K]$ , we have

$$\text{Regret}(k) \leq 2 \sum_{j=1}^k \sum_{h=1}^H \text{gap}_h(s_h^j, a_h^j) + \frac{16H^2}{3} \log(((1 + \log(Hk))k^2/\delta) + 2).$$

**Remark B.5.** Lemma B.4 can be easily obtained from Lemma 6.1 in He et al. (2021). In the original lemma, with probability at least  $1 - \lceil \log HK \rceil \exp(-\tau)$ ,

$$\text{Regret}(k) \leq 2 \sum_{j=1}^k \sum_{h=1}^H \text{gap}_h(s_h^j, a_h^j) + \frac{16H^2 \tau}{3} + 2,$$

which implies that with probability at least  $1 - \delta$ ,

$$\text{Regret}(k) \leq 2 \sum_{j=1}^k \sum_{h=1}^H \text{gap}_h(s_h^j, a_h^j) + \frac{16H^2 \log(\lceil \log(Hk) \rceil / \delta)}{3} + 2.$$

By relaxing  $\lceil \log(Hk) \rceil$  to  $\log(HK) + 1$  and replacing  $\delta$  with  $\delta/k^2$  for different episode number  $k$ , the inequality holds with probability at least  $1 - \sum_{k=1}^K \delta/k^2 \geq 1 - \pi^2 \delta / 6 \geq 1 - 2\delta$  for all  $k \in [K]$  by union bound.

Equipped with these lemmas, we can begin our proof.

*Proof of Lemma 6.3.* By the definition of  $\text{gap}_{\min}$ , for each  $h \in [H], k \in [K]$ , we have  $V_h^*(s_h^k) - Q_h^*(s_h^k, a_h^k) = 0$  or  $\text{gap}_{\min} \leq V_h^*(s_h^k) - Q_h^*(s_h^k, a_h^k) \leq H$ . Dividing the interval  $[\text{gap}_{\min}, H]$  into  $N$  intervals  $[2^{n-1} \text{gap}_{\min}, 2^n \text{gap}_{\min})$  where  $n \in [N], N = \lceil \log(H/\text{gap}_{\min}) \rceil$ , then with probability at

least  $1 - \lceil \log(H/\text{gap}_{\min}) \rceil \delta$ , it holds that

$$\begin{aligned}
\sum_{j=1}^k (V_h^*(s_h^j) - Q_h^*(s_h^j, a_h^j)) &\leq \sum_{n=1}^N \sum_{j=1}^k 2^n \text{gap}_{\min} \mathbf{1}[2^{n-1} \text{gap}_{\min} \leq V_h^*(s_h^j) - Q_h^*(s_h^j, a_h^j) \leq 2^n \text{gap}_{\min}] \\
&\leq \sum_{n=1}^N \sum_{j=1}^k 2^n \text{gap}_{\min} \mathbf{1}[2^{n-1} \text{gap}_{\min} \leq V_h^*(s_h^j) - Q_h^{\pi^j}(s_h^j, a_h^j)] \\
&\leq \sum_{n=1}^N \frac{64C_{\psi}^2 H^4 d_{\phi} \beta_{k,\phi} \log(1 + C_{\phi} k d_{\phi}) + 48H^3 \log(2k/\delta)}{2^n \text{gap}_{\min}} \\
&\leq \frac{64C_{\psi}^2 H^4 d_{\phi} \beta_{k,\phi} \log(1 + C_{\phi} k d_{\phi}) + 48H^3 \log(2k/\delta)}{\text{gap}_{\min}},
\end{aligned}$$

where the first inequality holds by using the ‘‘peeling technique’’, which was used in local Rademacher complexity analysis (Bartlett et al., 2005). The second inequality in (B.1) comes from the fact that  $Q_h^*(s, a) \geq Q_h^{\pi^j}(s, a)$  and the third inequality holds due to Lemma B.3. Finally, the fourth inequality holds due to  $\sum_{n=1}^N 2^{-n} \leq 1$ . Substituting  $\delta$  with  $\delta/(1 + \log(H/\text{gap}_{\min}))$ , with probability at least  $1 - \delta$ , we have

$$\sum_{j=1}^k (V_h^*(s_h^j) - Q_h^*(s_h^j, a_h^j)) \leq \frac{64C_{\psi}^2 H^4 d_{\phi} \beta_{k,\phi} \log(1 + C_{\phi} k d_{\phi}) + 48H^3 \log(2k(1 + \log(H/\text{gap}_{\min}))/\delta)}{\text{gap}_{\min}}, \tag{B.1}$$

Combining (B.1) with Lemma B.4, by taking a union bound, with probability at least  $1 - 3\delta$ ,

$$\begin{aligned}
\text{Regret}(k) &\leq 2 \sum_{j=1}^k \sum_{h=1}^H \text{gap}_h(s_h^k, a_h^k) + \frac{16H^2 \log(\lceil HK \rceil / \delta)}{3} + 2 \\
&\leq \frac{128C_{\psi}^2 H^5 d_{\phi} \beta_{k,\phi} \log(1 + C_{\phi} k d_{\phi}) + 96H^4 \log(2k(1 + \log(H/\text{gap}_{\min}))/\delta)}{\text{gap}_{\min}} \\
&\quad + \frac{16}{3} H^2 \log(((1 + \log(Hk))k^2/\delta) + 2).
\end{aligned}$$

where the first inequality holds due to Lemma B.4, which utilizes the definition of the sub-optimality gap. The second inequality holds due to (B.1). Substituting  $\delta$  with  $\delta/|\Phi|$ , the claimed result (6.1) holds for all  $\phi \in \Phi$  by taking a union bound.  $\square$

### B.3 Proof of Lemma 6.4

For brevity, we denote matrix  $\mathbf{\Lambda}_{h,\phi}(s) = \phi(s, \pi_h^*(s))\phi^\top(s, \pi_h^*(s)) \in \mathbb{R}^{d \times d}$  and fix  $h, m$  in the proof. The expectation  $\mathbb{E}_{s_h}[\mathbf{\Lambda}_{h,\phi}(s_h)|s_i], i < h$  is taken with respect to the randomness of the states sequence  $s_{i+1}, \dots, s_h$ , where  $s_{i'+1} \sim \mathbb{P}_{i'}(\cdot | s_{i'}, \pi_{i'}^*(s_{i'})), i \leq i' < h$ . If the action  $a_i$  is given, the expectation  $\mathbb{E}_{s_h}[\mathbf{\Lambda}_{h,\phi}(s_h)|s_i, a_i], i < h$  is taken in which  $s_{i+1} \sim \mathbb{P}_i(\cdot | s_i, a_i)$  specially. It is worthless to show that  $\mathbb{E}_{s_h}[\mathbf{\Lambda}_{h,\phi}(s_h)|s_h^k] = \mathbf{\Lambda}_{h,\phi}(s_h^k)$ . Without specification, we ignore the subscript  $s_h$  in the expectation in the proof of this lemma.

To develop the convergence property of the summation  $\phi(s, a)\phi^\top(s, a)$ , we introduce the following matrix Azuma inequality.

**Lemma B.6.** [Matrices Azuma, Tropp (2012)] Let  $\{\mathcal{F}_k\}_{k=1}^t$  be a filtration sequence,  $\{\mathbf{X}_k\}_{k=1}^t$  be a finite adapted sequence of symmetric matrices where  $\mathbf{X}_k \in \mathbb{R}^{d \times d}$  is  $\mathcal{F}_{k+1}$ -measurable,  $\mathbb{E}[\mathbf{X}_k | \mathcal{F}_k] = \mathbf{0}$  and  $\mathbf{X}^2 \preceq \mathbf{C}^2$  a.s.. Then with probability at least  $1 - \delta$ ,

$$\lambda_{\max} \left( \sum_{k=1}^t \mathbf{X}_k \right) \leq \sqrt{8C^2 t \log(d/\delta)},$$

where  $C = \|\mathbf{C}\|_2$ .

Equipped with this lemma, we can start our proof.

*Proof of Lemma 6.4.* First it is easy to verify that for any  $k \in [K]$

$$\begin{aligned} \phi(s_h^k, a_h^k) \phi^\top(s_h^k, a_h^k) &= \mathbf{\Lambda}_{h,\phi}(s_h^k) - \mathbb{1} \left[ a_h^k \neq \pi_h^*(s_h^k) \right] \left( \mathbf{\Lambda}_{h,\phi}(s_h^k) - \phi(s_h^k, a_h^k) \phi^\top(s_h^k, a_h^k) \right) \\ &\succeq \mathbf{\Lambda}_{h,\phi}(s_h^k) - C_\phi d_\phi \mathbb{1} \left[ a_h^k \neq \pi_h^*(s_h^k) \right] \mathbf{I}_{d_\phi}, \end{aligned} \quad (\text{B.2})$$

where the inequality holds due to  $\mathbf{0} \preceq \phi(s, a) \phi^\top(s, a) \preceq (C_\phi d_\phi) \mathbf{I}_{d_\phi}$ . By the definition of  $\mathbf{\Lambda}_{h,\phi}(s_h^k)$ , we have  $\mathbf{\Lambda}_{h,\phi}(s_h^k) = \mathbb{E}[\mathbf{\Lambda}_{h,\phi}(s_h) | s_h^k]$  and it suffices to control  $\mathbb{E}[\mathbf{\Lambda}_{h,\phi}(s_h) | s_i^k]$  for any  $1 < i \leq h$ . Therefore it follows that

$$\mathbb{E}[\mathbf{\Lambda}_{h,\phi}(s_h) | s_i^k] = \underbrace{\mathbb{E}[\mathbf{\Lambda}_{h,\phi}(s_h) | s_{i-1}^k, a_{i-1}^k]}_{\mathbf{A}_i(s_{i-1}^k, a_{i-1}^k)} - \underbrace{\mathbb{E}[\mathbf{\Lambda}_{h,\phi}(s_h) | s_{i-1}^k, a_{i-1}^k] - \mathbb{E}[\mathbf{\Lambda}_{h,\phi}(s_h) | s_i^k]}_{\boldsymbol{\epsilon}_i^k}$$

where we denote the first term as  $\mathbf{A}_i(s_{i-1}^k, a_{i-1}^k)$  while the second term as  $\boldsymbol{\epsilon}_i^k$  for simplicity. We first consider the term  $\boldsymbol{\epsilon}_i^k$ , it is easy to verify that  $\boldsymbol{\epsilon}_i^k$  is  $\mathcal{F}_i^k$ -measurable,  $d \times d$  symmetric matrix with  $\mathbb{E}[\boldsymbol{\epsilon}_i^k | \mathcal{F}_{i-1}^k] = \mathbf{0}$  and

$$\|\boldsymbol{\epsilon}_i^k\|_2 \leq \left\| \mathbb{E}[\mathbf{\Lambda}_{h,\phi}(s_h) | s_{i-1}^k, a_{i-1}^k] \right\|_2 + \left\| \mathbb{E}[\mathbf{\Lambda}_{h,\phi}(s_h) | s_i^k] \right\|_2 \leq 2C_\phi d_\phi, \quad (\text{B.3})$$

where the inequality holds due to the fact that  $\|\mathbf{\Lambda}_{h,\phi}(s)\|_2 \leq C_\phi d_\phi$ . Next, for the term  $\mathbf{A}_i$ , by introducing the indicator showing whether the action  $a_{i-1}^k$  is the optimal action  $\pi_{i-1}^*(s_{i-1}^k)$ , we proceed as follows:

$$\begin{aligned} \mathbf{A}_i(s_{i-1}^k, a_{i-1}^k) &= \mathbf{A}_i(s_{i-1}^k, \pi_{i-1}^*(s_{i-1}^k)) \\ &\quad - \mathbb{1} \left[ a_{i-1}^k \neq \pi_{i-1}^*(s_{i-1}^k) \right] \left( \mathbf{A}_i(s_{i-1}^k, \pi_{i-1}^*(s_{i-1}^k)) - \mathbf{A}_i(s_{i-1}^k, a_{i-1}^k) \right) \\ &\succeq \mathbf{A}_i(s_{i-1}^k, \pi_{i-1}^*(s_{i-1}^k)) - C_\phi d_\phi \mathbb{1} \left[ a_{i-1}^k \neq \pi_{i-1}^*(s_{i-1}^k) \right] \mathbf{I}_{d_\phi} \\ &= \mathbb{E}[\mathbf{\Lambda}_{h,\phi}(s_h) | s_{i-1}^k] - C_\phi d_\phi \mathbb{1} \left[ a_{i-1}^k \neq \pi_{i-1}^*(s_{i-1}^k) \right] \mathbf{I}_{d_\phi}, \end{aligned} \quad (\text{B.4})$$

where the inequality holds due to a similar proof of (B.2). The last equality holds due to the definition that

$$\mathbb{E}[\mathbf{\Lambda}_{h,\phi}(s_h) | s_{i-1}^k, \pi_{i-1}^*(s_{i-1}^k)] = \mathbb{E}[\mathbf{\Lambda}_{h,\phi}(s_h) | s_{i-1}^k].$$

Combining (B.4) and (B.3) together yields

$$\mathbb{E}[\mathbf{\Lambda}_{h,\phi}(s_h)|s_i^k] \succeq \mathbb{E}[\mathbf{\Lambda}_{h,\phi}(s_h)|s_{i-1}^k] - C_\phi d_\phi \mathbf{1} \left[ a_{i-1}^k \neq \pi_{i-1}^*(s_{i-1}^k) \right] \mathbf{I}_{d_\phi} - \epsilon_i^k,$$

and by telescoping over  $i$  we have

$$\begin{aligned} \mathbb{E}[\mathbf{\Lambda}_{h,\phi}(s_h)|s_h^k] &\succeq \mathbb{E}[\mathbf{\Lambda}_{h,\phi}(s_h)|s_1^k] - \sum_{i=2}^h \epsilon_i^k - C_\phi d_\phi \sum_{i=1}^{h-1} \mathbf{1} \left[ a_i^k \neq \pi_i^*(s_i^k) \right] \mathbf{I}_{d_\phi} \\ &= \mathbb{E}[\mathbf{\Lambda}_{h,\phi}(s_h)] - \underbrace{\mathbb{E}[\mathbf{\Lambda}_{h,\phi}(s_h)] - \mathbb{E}[\mathbf{\Lambda}_{h,\phi}(s_h)|s_1^k]}_{\epsilon_1^k} \\ &\quad - \sum_{i=2}^h \epsilon_i^k - C_\phi d_\phi \sum_{i=1}^{h-1} \mathbf{1} \left[ a_i^k \neq \pi_i^*(s_i^k) \right] \mathbf{I}_{d_\phi}, \end{aligned} \quad (\text{B.5})$$

where  $\epsilon_1^k$  is  $\mathcal{F}_1^k$ -measurable and  $\mathbb{E}[\epsilon_1^k | \mathcal{F}_H^{k-1}] = \mathbf{0}$ ,  $\|\epsilon_1^k\|_2 \leq 2C_\phi d_\phi$ , which is similar to  $\epsilon_i^k$  above. Plugging (B.5) into (B.2) yields

$$\begin{aligned} \phi(s_h^k, a_h^k) \phi^\top(s_h^k, a_h^k) &\succeq \mathbb{E}[\mathbf{\Lambda}_{h,\phi}(s_h)] - \sum_{i=1}^h \epsilon_i^k - C_\phi d_\phi \sum_{i=1}^h \mathbf{1} \left[ a_i^k \neq \pi_i^*(s_i^k) \right] \mathbf{I}_{d_\phi}, \\ &= \mathbb{E}[\mathbf{\Lambda}_{h,\phi}(s_h)] - \sum_{i=1}^h \epsilon_i^k - C_\phi d_\phi \sum_{i=1}^h \mathbf{1} \left[ Q_i^*(s_i^k, a_i^k) \neq V_i^*(s_i) \right] \mathbf{I}_{d_\phi}, \\ &\succeq \mathbb{E}[\mathbf{\Lambda}_{h,\phi}(s_h)] - \sum_{i=1}^h \epsilon_i^k - \frac{C_\phi d_\phi}{\text{gap}_{\min}} \sum_{i=1}^h (V_i^*(s_i^j) - Q_i^*(s_i^j, a_i^j)) \mathbf{I}_{d_\phi} \end{aligned} \quad (\text{B.6})$$

where the equality follows that  $a_h^k \neq \pi_i^*(s_h^k)$  is equivalent with  $Q_i^*(s_i^k, a_h^k) \neq V_i^*(s_i)$  and the second inequality is from  $V_i^*(s_i^k) - Q_i^*(s_i^k, a_h^k) \geq \text{gap}_{\min} \mathbf{1}[Q_i^*(s_i^k, a_h^k) \neq V_i^*(s_i)]$ , which is according to the minimal sub-optimality gap condition defined in (3.2).

By the construction of the ‘‘covariance matrix’’  $\mathbf{U}_{h,\phi}^k$ , (B.6) yields

$$\begin{aligned} \mathbf{U}_{h,\phi}^k &= \mathbf{I}_{d_\phi} + \sum_{j=1}^{k-1} \phi(s_h^j, a_h^j) \phi^\top(s_h^j, a_h^j) \\ &\succeq \mathbf{I}_{d_\phi} + (k-1) \mathbf{\Lambda}_{h,\phi} - \sum_{j=1}^{k-1} \sum_{i=1}^h \epsilon_i^j - \frac{C_\phi d_\phi}{\text{gap}_{\min}} \sum_{i=1}^h \sum_{j=1}^{k-1} (V_i^*(s_i^j) - Q_i^*(s_i^j, a_i^j)) \mathbf{I}_{d_\phi}. \end{aligned} \quad (\text{B.7})$$

Recall  $\epsilon_i^j$  is a  $d_\phi \times d_\phi$  symmetric matrix, by Lemma B.6 with  $C = 2C_\phi d_\phi I_{d_\phi}$ ,  $t = (k-1)h$ , with probability at least  $1 - \delta$ , we have

$$\lambda_{\max} \left( \sum_{j=1}^{k-1} \sum_{i=1}^h \epsilon_i^j \right) \leq \sqrt{32C_\phi^2 d_\phi^2 h(k-1) \log(d_\phi/\delta)}. \quad (\text{B.8})$$

Combining (B.8) with (B.7) and substituting  $\delta$  with  $\delta/Hk(k+1)|\Phi|$ , the claim in Lemma 6.4 holds for all  $h \in [H]$ ,  $k \in [K]$ ,  $\phi \in \Phi$  by taking a union bound.  $\square$

## B.4 Proof of Lemma 6.5

In order to prove Lemma 6.5, we first need the following lemma.

**Lemma B.7.** Given the condition in Lemma 6.3 and Lemma 6.4 holds and  $\mathcal{E}_\phi^K$  holds for all  $\phi \in \Phi$ . For each  $\phi \in \Phi$ , there exists a constant threshold

$$\tau_\phi = \text{poly}(d_\phi, \sigma_\phi^{-1}, H, \log(|\Phi|/\delta), \text{gap}_{\min}^{-1}, C_\phi, C_\psi, C_M, C'_\psi)$$

such that for any  $(s, a) \in \mathcal{S} \times \mathcal{A}$ ,  $h \in [H]$ , there exists a representation candidate  $\phi \in \Phi$  where when  $k \geq \tau_\phi$ ,  $\phi^\top(s, a)(\mathbf{U}_{h,\phi}^k)^{-1}\phi(s, a) \leq 2C_\phi d_\phi / (\sigma_\phi k)$ . We denote  $\tau = \max_{\phi \in \Phi} \tau_\phi$  to be the maximum possible threshold over all representations.

Lemma B.7 suggests that the UCB bonus term is decaying in the rate of  $\mathcal{O}(1/\sqrt{k})$ . Equipped with this lemma, we can start the proof.

*Proof of Lemma 6.5.* We will prove this lemma by induction. By the assumption in Lemma 6.5,  $\mathcal{E}_\phi^K$  holds for all  $\phi \in \Phi$ . Considering  $h = H$ , for any state-action pair  $(s, a) \in \mathcal{S} \times \mathcal{A}$ , by Lemma B.7, when  $k \geq \tau$ , there exists a representation  $\phi$  where Lemma B.2 yields

$$\begin{aligned} Q_H^k(s, a) - Q_H^{\pi^k}(s, a) &\leq 2C_\psi H \sqrt{\beta_{k,\phi} \phi^\top(s, a)(\mathbf{U}_{H,\phi}^k)^{-1}\phi(s, a)} + [\mathbb{P}_H(V_{H+1}^k - V_{H+1}^\pi)](s, a) \\ &\leq 2C_\psi H \sqrt{2C_\phi d_\phi \beta_{k,\phi} / (\sigma_\phi k)} + 0, \end{aligned}$$

where the second inequality is due to Lemma B.7 and the fact that  $V_{H+1}^k, V_{H+1}^\pi$  are both equal to zero. Thus we have

$$\max_{(s,a) \in \mathcal{S} \times \mathcal{A}} \{Q_H^k(s, a) - Q_H^{\pi^k}(s, a)\} \leq \max_{\phi \in \Phi} \left\{ 2C_\psi H \sqrt{2C_\phi d_\phi \beta_{k,\phi} / (\sigma_\phi k)} \right\}.$$

Suppose for step  $h$ , we have

$$\max_{(s,a) \in \mathcal{S} \times \mathcal{A}} \{Q_h^k(s, a) - Q_h^{\pi^k}(s, a)\} \leq (H - h + 1) \max_{\phi \in \Phi} \left\{ 2C_\psi H \sqrt{2C_\phi d_\phi \beta_{k,\phi} / (\sigma_\phi k)} \right\}, \quad (\text{B.9})$$

then considering time-step  $h - 1$ , by Lemma B.2 and Lemma B.7, for each  $s, a$ , there exists a  $\phi \in \Phi$  such that

$$\begin{aligned} Q_{h-1}^k(s, a) - Q_{h-1}^{\pi^k}(s, a) &\leq 2C_\psi H \sqrt{\beta_{k,\phi} \phi^\top(s, a)(\mathbf{U}_{h-1,\phi}^k)^{-1}\phi(s, a)} + [\mathbb{P}_{h-1}(V_h^k - V_h^{\pi^k})](s, a) \\ &\leq 2C_\phi H \sqrt{2C_\phi d_\phi \beta_{k,\phi} / (\sigma_\phi k)} + [\mathbb{P}_{h-1}(Q_h^k(\cdot, \pi_h^k(\cdot)) - Q_h^{\pi^k}(\cdot, \pi_h^k(\cdot)))](s, a) \\ &\leq 2C_\phi H \sqrt{2C_\phi d_\phi \beta_{k,\phi} / (\sigma_\phi k)} + (H - h + 1) \max_{\phi \in \Phi} \left\{ 2C_\psi H \sqrt{2C_\phi d_\phi \beta_{k,\phi} / (\sigma_\phi k)} \right\} \\ &\leq (H - h + 2) \max_{\phi \in \Phi} \left\{ 2C_\psi H \sqrt{2C_\phi d_\phi \beta_{k,\phi} / (\sigma_\phi k)} \right\}. \end{aligned}$$

where the second inequality comes from the definition that  $V_h^k(s) = Q_h^k(s, \pi_h^k(s))$  and  $V_h^{\pi^k}(s) = Q_h^{\pi^k}(s, \pi_h^k(s))$ , the third inequality comes from the induction assumption (B.9) and this result conclude our induction.

Then, following Lemma B.1, we have  $Q_{h,\phi}^k(s, a) \geq Q_h^*(s, a)$ . Thus,  $Q_h^k(s, a) = \min_{\phi \in \Phi} \{Q_{h,\phi}^k\} \geq Q_h^*(s, a)$ . Then the sub-optimality gap could be bounded by

$$\begin{aligned}
\text{gap}_h(s, \pi_h^k(s)) &= Q_h^*(s, \pi_h^k(s)) - Q_h^k(s, \pi_h^k(s)) \\
&\leq Q_h^k(s, \pi_h^*(s)) - Q_h^k(s, \pi_h^k(s)) \\
&\leq Q_h^k(s, \pi_h^k(s)) - Q_h^{\pi^k}(s, \pi_h^k(s)) \\
&\leq (H - h + 1) \max_{\phi \in \Phi} \left\{ 2C_\psi H \sqrt{2C_\phi d_\phi \beta_{k,\phi} / (\sigma_\phi k)} \right\} \\
&\leq 2C_\psi H^2 \max_{\phi \in \Phi} \left\{ \sqrt{2C_\phi d_\phi \beta_{k,\phi} / (\sigma_\phi k)} \right\},
\end{aligned}$$

where the inequality on the second line holds due to Lemma B.1, and the inequality on the third line holds due to the greedy policy  $\pi_h^k(s) = \operatorname{argmax}_a Q_h^k(s, a)$ . Finally, the inequality on the fourth line comes from the result of induction (B.9) and we finish the proof.  $\square$

## C Proof of Lemmas in Appendix B

### C.1 Proof of Lemma B.1

**Lemma C.1** (Lemma 5 on  $B_n^{(2)}$ , pp. 23, Yang and Wang (2020)). Suppose  $\mathcal{E}_\phi^K$  holds, then for any  $(s, a) \in \mathcal{S} \times \mathcal{A}$ , we have

$$\|\phi(s, a)^\top (\mathbf{M}_{h,\phi}^k - \mathbf{M}_{h,\phi}^*)\|_2 \leq \sqrt{\beta_{k,\phi} \phi^\top(s, a) (\mathbf{U}_{h,\phi}^k)^{-1} \phi(s, a)}.$$

*Proof of Lemma B.1.* We prove this lemma by induction. First, it is obvious that  $Q_{H+1}^k(s, a) = Q_{H+1}^*(s, a) = 0$  for all  $(s, a) \in \mathcal{S} \times \mathcal{A}$ . Then assuming for  $1 < h \leq H$ , we have  $Q_{h+1}^k(s, a) \geq Q_{h+1}^*(s, a)$  holds for all  $(s, a)$ , considering time-step  $h$  and representation  $\phi$ , we have

$$\begin{aligned}
Q_{h,\phi}^k(s, a) &= r(s, a) + \phi^\top(s, a) \mathbf{M}_{h,\phi}^k \Psi^\top \mathbf{v}_{h+1}^k + C_\psi H \sqrt{\beta_{k,\phi} \phi^\top(s, a) (\mathbf{U}_{h,\phi}^k)^{-1} \phi(s, a)} \\
&= r(s, a) + \phi^\top(s, a) (\mathbf{M}_{h,\phi}^k - \mathbf{M}_{h,\phi}^*) \Psi^\top \mathbf{v}_{h+1}^k \\
&\quad + C_\psi H \sqrt{\beta_{k,\phi} \phi^\top(s, a) (\mathbf{U}_{h,\phi}^k)^{-1} \phi(s, a)} + [\mathbb{P}_h V_{h+1}^k](s, a) \\
&\geq r(s, a) - \|\phi^\top(s, a) (\mathbf{M}_{h,\phi}^k - \mathbf{M}_{h,\phi}^*)\|_2 \|\Psi^\top \mathbf{v}_{h+1}^k\|_2 \\
&\quad + C_\psi H \sqrt{\beta_{k,\phi} \phi^\top(s, a) (\mathbf{U}_{h,\phi}^k)^{-1} \phi(s, a)} + [\mathbb{P}_h V_{h+1}^k](s, a) \\
&\geq r(s, a) + [\mathbb{P}_h V_{h+1}^k](s, a), \tag{C.1}
\end{aligned}$$

where the first inequality comes from the fact that  $\langle \mathbf{x}, \mathbf{y} \rangle \geq -\|\mathbf{x}\|_2 \|\mathbf{y}\|_2$ , the second inequality holds due to Lemma C.1 and  $\|\Psi^\top \mathbf{v}_{h+1}^k\|_\infty \leq C_\psi H$  since  $\|\mathbf{v}_{h+1}^k\|_\infty \leq H$ . Since  $Q_{h+1}^k(s, a) \geq Q_{h+1}^*(s, a)$ , then

$$\begin{aligned}
V_{h+1}^k(s) &= \min\{H, Q_{h+1}^k(s, \pi_h^k(s))\} \\
&\geq \min\{H, Q_{h+1}^k(s, \pi_{h+1}^*(s))\} \\
&\geq \min\{H, Q_{h+1}^*(s, \pi_{h+1}^*(s))\} \\
&= V_{h+1}^*(s),
\end{aligned}$$

where the last inequality comes from the fact that  $V_{h+1}^*(s) \leq H$ . Therefore, (C.1) yields  $Q_{h,\phi}^k(s, a) \geq r(s, a) + [\mathbb{P}_h V_{h+1}^*](s, a) = Q_h^*(s, a)$  for all  $\phi \in \Phi$ . Thus

$$Q_h^k(s, a) = \min_{\phi \in \Phi} \{Q_{h,\phi}^k(s, a)\} \geq Q_h^*(s, a).$$

Then we finish our proof by induction.  $\square$

## C.2 Proof of Lemma B.2

*Proof of Lemma B.2.* First, the update rule of  $Q_{h,\phi}^k$  and Bellman equation yield

$$\begin{aligned} Q_{h,\phi}^k(s, a) - Q_h^\pi(s, a) &= \underbrace{\phi^\top(s, a) \mathbf{M}_{h,\phi}^k \Psi^\top \mathbf{v}_{h+1}^k}_{I_1} - [\mathbb{P}_h V_{h+1}^\pi](s, a) \\ &\quad + C_\psi H \sqrt{\beta_{k,\phi} \phi^\top(s, a) (\mathbf{U}_{h,\phi}^k)^{-1} \phi(s, a)}. \end{aligned} \quad (\text{C.2})$$

Since  $[\mathbb{P}_h V_{h+1}^k] = \phi^\top(s, a) \mathbf{M}_{h,\phi}^* \Psi^\top \mathbf{v}_{h+1}^k$ ,  $I_1$  can be decomposed as

$$\begin{aligned} \phi^\top(s, a) \mathbf{M}_{h,\phi}^k \Psi^\top \mathbf{v}_{h+1}^k &= \phi^\top(s, a) (\mathbf{M}_{h,\phi}^k - \mathbf{M}_{h,\phi}^*) \Psi^\top \mathbf{v}_{h+1}^k + [\mathbb{P}_h V_{h+1}^k](s, a) \\ &\leq \|\Psi^\top \mathbf{v}_{h+1}^k\|_2 \|\phi^\top(s, a) (\mathbf{M}_{h,\phi}^k - \mathbf{M}_{h,\phi}^*)\|_2 + [\mathbb{P}_h V_{h+1}^k](s, a) \\ &\leq C_\psi H \sqrt{\beta_{k,\phi} \phi^\top(s, a) (\mathbf{U}_{h,\phi}^k)^{-1} \phi(s, a)} + [\mathbb{P}_h V_{h+1}^k](s, a), \end{aligned} \quad (\text{C.3})$$

where the inequality on the second line holds due to  $\langle \mathbf{x}, \mathbf{y} \rangle \leq \|\mathbf{x}\|_2 \|\mathbf{y}\|_2$  and the inequality on the third line comes from Lemma C.1 with  $\|\mathbf{v}_{h+1}^k\|_\infty \leq H$  and Definition 3.2. Plugging (C.3) into (C.2) yields

$$Q_{h,\phi}^k(s, a) - Q_h^\pi(s, a) \leq 2C_\psi H \sqrt{\beta_{k,\phi} \phi^\top(s, a) (\mathbf{U}_{h,\phi}^k)^{-1} \phi(s, a)} + [\mathbb{P}_h (V_{h+1}^k - V_{h+1}^\pi)](s, a).$$

Since  $Q_h^k(s, a) = \min_{\phi \in \Phi} Q_{h,\phi}^k(s, a)$ , we can get the claimed result in Lemma B.2.  $\square$

## C.3 Proof of Lemmas B.3

**Lemma C.2** (Lemma 6.6, He et al. (2021)). For any subset  $C = \{c_1, \dots, c_k\} \subseteq [K]$  and any  $h \in [H]$ ,

$$\sum_{i=1}^k \phi_h^\top(s_h^{c_i}, a_h^{c_i}) (\mathbf{U}_{h,\phi}^{c_i})^{-1} \phi_h(s_h^{c_i}, a_h^{c_i}) \leq 2d_\phi \log(1 + C_\phi k d_\phi)$$

**Remark C.3.** Proof of Lemma C.2 remains the same with He et al. (2021) by changing the norm of  $\phi$  from  $\|\phi\|_2^2 \leq 1$  to  $\|\phi\|_2^2 \leq C_\phi d_\phi$  as of Definition 3.2.

**Lemma C.4** (Azuma-Hoeffding's inequality, Azuma 1967). Let  $\{x_i\}_{i=1}^n$  be a martingale difference sequence with respect to a filtration  $\{\mathcal{F}_i\}_{i=1}^n$  (i.e.  $\mathbb{E}[x_i | \mathcal{F}_i] = 0$  a.s. and  $x_i$  is  $\mathcal{F}_{i+1}$  measurable) such that  $|x_i| \leq M$  a.s.. Then for any  $0 < \delta < 1$ , with probability at least  $1 - \delta$ ,  $\sum_{i=1}^n x_i \leq M \sqrt{2n \log(1/\delta)}$ .

*Proof of Lemma B.3.* We fix  $h$  and consider the first  $k$  episodes in this proof. Let  $k_0 = 0$ , for any  $j \in [k]$ , we denote  $k_j$  as the minimum index of the episode where the sub-optimality at time-step  $h$  is no less than  $\Delta$ :

$$k_j = \min \left\{ \bar{k} : \bar{k} > k_{j-1}, V_h^*(s_h^{\bar{k}}) - Q_h^{\pi^{\bar{k}}}(s_h^{\bar{k}}, a_h^{\bar{k}}) \geq \Delta \right\}.$$

For simplicity, we denote  $k'$  to be the number of episodes such that the sub-optimality of this episode at step  $h$  is no less than  $\Delta$ , i.e.

$$k' = \sum_{j=1}^k \mathbb{1}[V_h^*(s_h^j) - Q_h^{\pi^j}(s_h^j, a_h^j) \geq \Delta].$$

Then by the definition of  $k'$ , it is obvious that

$$\begin{aligned} \sum_{j=1}^{k'} Q_h^{k_j}(s_h^{k_j}, a_h^{k_j}) - Q_h^{\pi^{k_j}}(s_h^{k_j}, a_h^{k_j}) &\geq \sum_{j=1}^{k'} Q_h^{k_j}(s_h^{k_j}, \pi_h^*(s_h^{k_j})) - Q_h^{\pi^{k_j}}(s_h^{k_j}, a_h^{k_j}) \\ &\geq \sum_{j=1}^{k'} Q_h^*(s_h^{k_j}, \pi_h^*(s_h^{k_j})) - Q_h^{\pi^{k_j}}(s_h^{k_j}, a_h^{k_j}) \\ &= \sum_{j=1}^{k'} V_h^*(s_h^{k_j}) - Q_h^{\pi^{k_j}}(s_h^{k_j}, a_h^{k_j}) \geq \Delta k', \end{aligned} \quad (\text{C.4})$$

where the first inequality holds due to  $a_h^k = \operatorname{argmax}_a Q_h^k(s_h^k, a)$  and the second inequality comes from Lemma B.1. On the other hand, following Lemma B.2, when  $\mathcal{E}_\phi^k$  holds, for all  $i \in [H], j \leq k$

$$\begin{aligned} Q_i^j(s_i^j, a_i^j) &\leq 2C_\psi H \sqrt{\beta_{j,\phi} \phi^\top(s_i^j, a_i^j) (\mathbf{U}_{i,\phi}^j)^{-1} \phi(s_i^j, a_i^j)} + [\mathbb{P}_i(V_{i+1}^j - V_{i+1}^{\pi^j})](s_i^j, a_i^j) \\ &= 2C_\psi H \sqrt{\beta_{j,\phi} \phi^\top(s_i^j, a_i^j) (\mathbf{U}_{i,\phi}^j)^{-1} \phi(s_i^j, a_i^j)} + V_{i+1}^j(s_{i+1}^j) - V_{i+1}^{\pi^j}(s_{i+1}^j) + \epsilon_i^j, \end{aligned} \quad (\text{C.5})$$

where  $\epsilon_i^j = [\mathbb{P}_i(V_{i+1}^j - V_{i+1}^{\pi^j})](s_i^j, a_i^j) - (V_{i+1}^j(s_{i+1}^j) - V_{i+1}^{\pi^j}(s_{i+1}^j))$ . It is easy to verify that  $|\epsilon_i^j| \leq H$ ,  $\epsilon_i^j$  is  $\mathcal{F}_{i+1}^j$  measurable with  $\mathbb{E}[\epsilon_i^j | \mathcal{F}_i^j] = 0$ . Taking the telescoping summation on (C.5) over  $h \leq i \leq H, j \in \{k_1, \dots, k_{k'}\}$  using the fact that  $V_i^j(s_i^j) = Q_i^j(s_i^j, a_i^j)$  and  $V_i^{\pi^j}(s_i^j) = Q_i^{\pi^j}(s_i^j, a_i^j)$  we have

$$\sum_{j=1}^{k'} Q_h^{k_j}(s_h^{k_j}, a_h^{k_j}) - Q_h^{\pi^{k_j}}(s_h^{k_j}, a_h^{k_j}) \leq I_1 + I_2, \quad (\text{C.6})$$

where

$$\begin{aligned} I_1 &= \sum_{j=1}^{k'} \sum_{i=h}^H 2C_\psi H \sqrt{\beta_{k_j,\phi} \phi^\top(s_h^{k_j}, a_h^{k_j}) (\mathbf{U}_{i,\phi}^{k_j})^{-1} \phi(s_h^{k_j}, a_h^{k_j})} \\ I_2 &= \sum_{j=1}^{k'} \sum_{i=h}^H \epsilon_i^{k_j}. \end{aligned}$$

To bound  $I_1$ , by Cauchy-Schwarz inequality,

$$\begin{aligned}
I_1 &= \sum_{j=1}^{k'} \sum_{i=h}^H 2C_\psi H \sqrt{\beta_{k_j, \phi} \phi^\top(s_h^{k_j}, a_h^{k_j}) (\mathbf{U}_{i, \phi}^{k_j})^{-1} \phi(s_h^{k_j}, a_h^{k_j})} \\
&\leq 2C_\psi H \sqrt{\beta_{k, \phi} k'} \sum_{i=h}^H \sqrt{\sum_{j=1}^{k'} \phi^\top(s_h^{k_j}, a_h^{k_j}) (\mathbf{U}_{i, \phi}^{k_j})^{-1} \phi(s_h^{k_j}, a_h^{k_j})} \\
&\leq 2C_\psi H^2 \sqrt{\beta_{k, \phi} k'} \sqrt{2d_\phi \log(1 + C_\phi k' d_\phi)} \\
&\leq 2C_\psi H^2 \sqrt{2\beta_{k, \phi} d_\phi k' \log(1 + C_\phi k d_\phi)},
\end{aligned}$$

where the second inequity on Line 3 is from Lemma C.2. To bound  $I_2$ , by Lemma C.4, with probability at least  $1 - \delta/k$ , we have

$$\sum_{j=1}^{k'} \sum_{i=h}^H \epsilon_i^{k_j} \leq \sqrt{2k' H^3 \log(k/\delta)},$$

then taking union bound over all  $k$  we can conclude that with probability at least  $1 - \delta$ ,

$$I_2 = \sum_{j=1}^{k'} \sum_{i=h}^H \epsilon_i^{k_j} \leq \sqrt{2k' H^3 \log(k/\delta)}$$

Combining (C.4) with (C.6), we can obtain

$$\Delta k' \leq 2C_\psi H^2 \sqrt{2\beta_{k, \phi} d_\phi k' \log(1 + C_\phi k d_\phi)} + \sqrt{2k' H^3 \log(k/\delta)}. \quad (\text{C.7})$$

By  $(a + b)^2 \leq 2a^2 + 2b^2$ , (C.7) immediately implies

$$k' \leq \frac{16C_\psi^2 H^4 d_\phi \beta_{k, \phi} \log(1 + C_\phi k d_\phi) + 4H^3 \log(k/\delta)}{\Delta^2} \quad (\text{C.8})$$

Since event  $\mathcal{E}_\phi^K$  directly implies  $\mathcal{E}_\phi^k$  for all  $k \leq K$ , we can get the claimed result (C.8) holds for all  $k \leq K$  with probability  $1 - \delta$ . Replace  $\delta$  with  $\delta/k(k+1)$  for different  $k$ , taking union bound for all possible  $k$ , we have with probability at least  $1 - \delta$ , for all possible  $k$ ,

$$\begin{aligned}
\sum_{j=1}^k \mathbb{1}[V_h^*(s_h^j) - Q_h^{\pi^j}(s_h^j, a_h^j)] &\leq \frac{16C_\psi^2 H^4 d_\phi \beta_{k, \phi} \log(1 + C_\phi k d_\phi) + 4H^3 \log(k^2(k+1)/\delta)}{\Delta^2} \\
&\leq \frac{16C_\psi^2 H^4 d_\phi \beta_{k, \phi} \log(1 + C_\phi k d_\phi) + 12H^3 \log(2k/\delta)}{\Delta^2}.
\end{aligned}$$

□

## C.4 Proof of Lemma B.7

*Proof of Lemma B.7.* For any state-action pair  $(s, a)$  at step  $h$ , according to Assumption 3.3, we consider the set  $\mathcal{Z}_{h,\phi}$  where  $(s, a) \in \mathcal{Z}_{h,\phi}$  and the corresponding representation  $\phi$ . By Lemma 6.4, we denote  $\mathbf{B}$  as

$$\begin{aligned} \mathbf{B} &:= (k-1)\mathbf{\Lambda}_{h,\phi} - \iota\mathbf{I}_{d_\phi} \preceq \mathbf{U}_{h,\phi}^k, \\ \iota &= \frac{C_\phi d_\phi}{\text{gap}_{\min}} \sum_{i=1}^h \sum_{j=1}^{k-1} \text{gap}_i(s_i^j, a_i^j) + C_\phi d_\phi \sqrt{32H(k-1) \log(d_\phi |\Phi| Hk(k+1)/\delta)} - 1. \end{aligned}$$

Decomposing  $\mathbf{\Lambda}_{h,\phi} = \mathbf{Q}^\top \mathbf{D} \mathbf{Q}$  where  $\mathbf{Q} \in \mathbb{R}^{d_\phi \times d_\phi}$  is the orthogonal matrix and  $\mathbf{D}$  is the diagonal matrix, we have  $\mathbf{B} = \mathbf{Q}^\top ((k-1)\mathbf{D} - \iota\mathbf{I}_{d_\phi}) \mathbf{Q}$ .

We first prove the non-singular property of  $\mathbf{B}$ . Considering the zero diagonal element  $\mathbf{D}_{[ii]}$ , we have

$$((k-1)\mathbf{D} - \iota\mathbf{I}_{d_\phi})_{[ii]} \leq -\iota \leq -C_\phi d_\phi \sqrt{32H(k-1) \log(d_\phi |\Phi| Hk(k+1)/\delta)} + 1,$$

where the second inequality comes from  $\text{gap}_h(s, a) \geq 0$ . As a result, it is obvious to verify that there exists a constant  $K_1$  such that once  $k \geq K_1$ ,  $((k-1)\mathbf{D} - \iota\mathbf{I}_{d_\phi})_{[ii]} < 0$  for all zero diagonal element  $\mathbf{D}_{[ii]}$  in  $\mathbf{D}$ . Next we consider the non-zero diagonal value  $\mathbf{D}_{[jj]}$ . By Assumption 3.3,  $\mathbf{D}_{[jj]} \geq \sigma_\phi$ . Therefore, the corresponding diagonal value  $((k-1)\mathbf{D} - \iota\mathbf{I}_{d_\phi})_{[jj]}$  could be bounded by

$$((k-1)\mathbf{D} - \iota\mathbf{I}_{d_\phi})_{[jj]} \geq \sigma_\phi(k-1) - \iota.$$

Removing the minimum operator in (6.2) in Lemma 6.3, we have

$$\begin{aligned} ((k-1)\mathbf{D} - \iota\mathbf{I}_{d_\phi})_{[jj]} &\geq 1 + \sigma_\phi(k-1) - C_\phi d_\phi \sqrt{32H(k-1) \log(d_\phi |\Phi| Hk(k+1)/\delta)} \\ &\quad - \frac{64C_\psi^2 H^4 d_\phi^2 \beta_{k,\phi} \log(1 + C_\phi k d_\phi) + 48H^3 \log(2k(1 + \log(H/\text{gap}_{\min}))/\delta)}{\text{gap}_{\min}} \end{aligned}$$

It's easy to verify that the increasing term  $\sigma_\phi k$  is  $\mathcal{O}(k)$  while the decreasing term is in the order of  $\mathcal{O}(\sqrt{k})$  and  $\mathcal{O}(\log(k))$  where  $\beta_{k,\phi} = \mathcal{O}(\log(k))$  as shown in Lemma 6.1, thus there exists a constant threshold

$$\tau_\phi = \text{poly}(d_\phi, \sigma_\phi^{-1}, H, \log(|\Phi|/\delta), \text{gap}_{\min}^{-1}, C_\phi, C_\psi, C_M, C'_\psi)$$

such that for any  $k \geq \tau_\phi$ ,  $((k-1)\mathbf{D} - \iota\mathbf{I}_{d_\phi})_{[jj]} \geq \sigma_\phi/2$ . Since we have shown that all of the diagonal value for  $(k-1)\mathbf{D} - \iota$  is either strictly smaller than zero or strictly greater than zero,  $\mathbf{B}$  is invertible.

By the definition of  $\mathcal{Z}_{h,\phi}$  in Assumption 3.3, there exists a vector  $\mathbf{x} \in \mathbb{R}^{d_\phi}$  such that  $\mathbf{\Lambda} \mathbf{x} = \phi(s, a) / \|\phi(s, a)\|_2$ . Since  $\mathbf{U}_{h,\phi}^k \succeq \mathbf{B}$  and  $\mathbf{U}_{h,\phi}^k, \mathbf{B}$  are both invertible, it follows

$$\phi^\top(s, a) (\mathbf{U}_{h,\phi}^k)^{-1} \phi(s, a) \leq \underbrace{\|\phi(s, a)\|_2^2}_{I_1} \mathbf{B}^{-1} \frac{\phi(s, a)}{\|\phi(s, a)\|_2}, \quad (\text{C.9})$$

where  $I_1$  could be rewrote by

$$\begin{aligned}
I_1 &= \mathbf{x}^\top \mathbf{\Lambda} \mathbf{B}^{-1} \mathbf{\Lambda} \mathbf{x} \\
&= \mathbf{x}^\top \mathbf{Q}^\top \mathbf{D} \mathbf{Q} \mathbf{Q}^\top ((k-1)\mathbf{D} - \iota \mathbf{I}_{d_\phi})^{-1} \mathbf{Q} \mathbf{Q}^\top \mathbf{D} \mathbf{Q} \mathbf{x} \\
&= \mathbf{x}^\top \mathbf{Q}^\top \mathbf{D} ((k-1)\mathbf{D} - \iota \mathbf{I}_{d_\phi})^{-1} \mathbf{D} \mathbf{Q} \mathbf{x}.
\end{aligned} \tag{C.10}$$

Since  $\|\mathbf{\Lambda} \mathbf{x}\|_2 = 1$ , it is easy to verify that  $\mathbf{x}^\top \mathbf{Q}^\top \mathbf{D} \mathbf{D} \mathbf{Q} \mathbf{x} = \mathbf{x}^\top \mathbf{\Lambda} \mathbf{\Lambda} \mathbf{x} = \|\mathbf{\Lambda} \mathbf{x}\|_2^2 = 1$ . We hereby denote  $\mathbf{y}$  as  $\mathbf{D} \mathbf{Q} \mathbf{x}$  and we have  $\|\mathbf{y}\|_2^2 = 1$ . Furthermore, it is obvious that  $\mathbf{y}_{[i]} = 0$  as long as  $\mathbf{D}_{[ii]} = 0$ . Therefore,  $\sum_{i=1, \mathbf{D}_{[ii]} \neq 0}^{d_\phi} \mathbf{y}_{[i]}^2 = 1$ . Then plugging the notation of  $\mathbf{y}$  into (C.10) yields

$$I_1 = \mathbf{y}^\top ((k-1)\mathbf{D} - \iota \mathbf{I}_{d_\phi})^{-1} \mathbf{y} = \sum_{i=1, \mathbf{D}_{[ii]} \neq 0}^{d_\phi} \frac{\mathbf{y}_{[i]}^2}{((k-1)\mathbf{D} - \iota \mathbf{I}_{d_\phi})_{[ii]}},$$

since we have shown that the  $((k-1)\mathbf{D} - \iota \mathbf{I}_{d_\phi})_{[ii]} \geq \sigma_\phi k/2$  when  $\mathbf{D}_{[ii]} \neq 0$  and  $k \geq \tau_\phi$ . Thus we can easily conclude that  $I_1 \leq 2/(\sigma_\phi k)$ , plugging this into (C.9) we can get the claimed result.  $\square$

## References

- ABBASI-YADKORI, Y., PACCHIANO, A. and PHAN, M. (2020). Regret balancing for bandit and rl model selection. *arXiv preprint arXiv:2006.05491* .
- ABEL, D., HERSHKOWITZ, D. and LITTMAN, M. (2016). Near optimal behavior via approximate state abstraction. In *International Conference on Machine Learning*. PMLR.
- AGARWAL, A., KAKADE, S. M., KRISHNAMURTHY, A. and SUN, W. (2020). Flambe: Structural complexity and representation learning of low rank mdps. *Advances in neural information processing systems* .
- AGARWAL, A., LUO, H., NEYSHABUR, B. and SCHAPIRE, R. E. (2017). Corraling a band of bandit algorithms. In *Conference on Learning Theory*. PMLR.
- AUER, P., CESA-BIANCHI, N., FREUND, Y. and SCHAPIRE, R. E. (2002). The nonstochastic multiarmed bandit problem. *SIAM journal on computing* **32** 48–77.
- AYOUB, A., JIA, Z., SZEPESVARI, C., WANG, M. and YANG, L. (2020). Model-based reinforcement learning with value-targeted regression. In *International Conference on Machine Learning*. PMLR.
- AZUMA, K. (1967). Weighted sums of certain dependent random variables. *Tohoku Mathematical Journal, Second Series* **19** 357–367.
- BARTLETT, P. L., BOUSQUET, O., MENDELSON, S. ET AL. (2005). Local rademacher complexities. *The Annals of Statistics* **33** 1497–1537.
- CHATTERJI, N., MUTHUKUMAR, V. and BARTLETT, P. (2020). Osom: A simultaneously optimal algorithm for multi-armed and linear contextual bandits. In *International Conference on Artificial Intelligence and Statistics*. PMLR.

- CHU, W., LI, L., REYZIN, L. and SCHAPIRE, R. (2011). Contextual bandits with linear payoff functions. In *Proceedings of the Fourteenth International Conference on Artificial Intelligence and Statistics*. JMLR Workshop and Conference Proceedings.
- DE BRUIN, T., KOBER, J., TUYLS, K. and BABUŠKA, R. (2018). Integrating state representation learning into deep reinforcement learning. *IEEE Robotics and Automation Letters* **3** 1394–1401.
- DEAN, T. and GIVAN, R. (1997). Model minimization in markov decision processes. In *AAAI/IAAI*.
- DIUK, C., COHEN, A. and LITTMAN, M. L. (2008). An object-oriented representation for efficient reinforcement learning. In *Proceedings of the 25th international conference on Machine learning*.
- DU, S., KRISHNAMURTHY, A., JIANG, N., AGARWAL, A., DUDIK, M. and LANGFORD, J. (2019). Provably efficient rl with rich observations via latent state decoding. In *International Conference on Machine Learning*. PMLR.
- DU, S. S., KAKADE, S. M., WANG, R. and YANG, L. F. (2020). Is a good representation sufficient for sample efficient reinforcement learning? In *International Conference on Learning Representations*.
- FOSTER, D., KRISHNAMURTHY, A. and LUO, H. (2019). Model selection for contextual bandits. *Advances in neural information processing systems* .
- FOSTER, D. J., KRISHNAMURTHY, A. and LUO, H. (2020a). Open problem: Model selection for contextual bandits. In *Conference on Learning Theory*. PMLR.
- FOSTER, D. J., RAKHLIN, A., SIMCHI-LEVI, D. and XU, Y. (2020b). Instance-dependent complexity of contextual bandits and reinforcement learning: A disagreement-based perspective. *arXiv preprint arXiv:2010.03104* .
- GHOSH, A., SANKARARAMAN, A. and KANNAN, R. (2021). Problem-complexity adaptive model selection for stochastic linear bandits. In *International Conference on Artificial Intelligence and Statistics*. PMLR.
- HE, J., ZHOU, D. and GU, Q. (2021). Logarithmic regret for reinforcement learning with linear function approximation. In *International Conference on Machine Learning*. PMLR.
- JIA, Z., YANG, L., SZEPESVARI, C. and WANG, M. (2020). Model-based reinforcement learning with value-targeted regression. In *Learning for Dynamics and Control*. PMLR.
- JIANG, N., KRISHNAMURTHY, A., AGARWAL, A., LANGFORD, J. and SCHAPIRE, R. E. (2017). Contextual decision processes with low bellman rank are pac-learnable. In *International Conference on Machine Learning*. PMLR.
- JIN, C., YANG, Z., WANG, Z. and JORDAN, M. I. (2020). Provably efficient reinforcement learning with linear function approximation. In *Conference on Learning Theory*. PMLR.
- KOBER, J., BAGNELL, J. A. and PETERS, J. (2013). Reinforcement learning in robotics: A survey. *The International Journal of Robotics Research* **32** 1238–1274.

- MICHAEL, S. P. S. T. J. and JORDAN, I. (1995). Reinforcement learning with soft state aggregation. *Advances in neural information processing systems* **7** 361.
- MISRA, D., HENAFF, M., KRISHNAMURTHY, A. and LANGFORD, J. (2020). Kinematic state abstraction and provably efficient rich-observation reinforcement learning. In *International conference on machine learning*. PMLR.
- MNIH, V., KAVUKCUOGLU, K., SILVER, D., GRAVES, A., ANTONOGLU, I., WIERSTRA, D. and RIEDMILLER, M. (2013). Playing atari with deep reinforcement learning. *arXiv preprint arXiv:1312.5602* .
- MODI, A., CHEN, J., KRISHNAMURTHY, A., JIANG, N. and AGARWAL, A. (2021). Model-free representation learning and exploration in low-rank mdps. *arXiv preprint arXiv:2102.07035* .
- MODI, A., JIANG, N., TEWARI, A. and SINGH, S. (2020). Sample complexity of reinforcement learning using linearly combined model ensembles. In *International Conference on Artificial Intelligence and Statistics*. PMLR.
- ODALRIC, M. and MUNOS, R. (2011). Adaptive bandits: Towards the best history-dependent strategy. In *Proceedings of the Fourteenth International Conference on Artificial Intelligence and Statistics*. JMLR Workshop and Conference Proceedings.
- PACCHIANO, A., DANN, C., GENTILE, C. and BARTLETT, P. (2020a). Regret bound balancing and elimination for model selection in bandits and rl. *arXiv preprint arXiv:2012.13045* .
- PACCHIANO, A., PHAN, M., ABBASI YADKORI, Y., RAO, A., ZIMMERT, J., LATTIMORE, T. and SZEPESVARI, C. (2020b). Model selection in contextual stochastic bandit problems. *Advances in Neural Information Processing Systems* **33**.
- PAPINI, M., TIRINZONI, A., RESTELLI, M., LAZARIC, A. and PIROTTA, M. (2021). Leveraging good representations in linear contextual bandits. In *International Conference on Machine Learning*. PMLR.
- RAVINDRAN, B. and BARTO, A. G. (2002). Model minimization in hierarchical reinforcement learning. In *International Symposium on Abstraction, Reformulation, and Approximation*. Springer.
- SIMCHOWITZ, M. and JAMIESON, K. (2019). Non-asymptotic gap-dependent regret bounds for tabular mdps. *Advances in neural information processing systems* .
- STOOKE, A., LEE, K., ABBEEL, P. and LASKIN, M. (2020). Decoupling representation learning from reinforcement learning. *arXiv preprint arXiv:2009.08319* .
- TROPP, J. A. (2012). User-friendly tail bounds for sums of random matrices. *Foundations of computational mathematics* **12** 389–434.
- WEI, C.-Y., JAHROMI, M. J., LUO, H. and JAIN, R. (2021). Learning infinite-horizon average-reward mdps with linear function approximation. In *International Conference on Artificial Intelligence and Statistics*. PMLR.
- YANG, K., YANG, L. and DU, S. (2021). Q-learning with logarithmic regret. In *International Conference on Artificial Intelligence and Statistics*. PMLR.

- YANG, L. and WANG, M. (2019). Sample-optimal parametric q-learning using linearly additive features. In *International Conference on Machine Learning*. PMLR.
- YANG, L. and WANG, M. (2020). Reinforcement learning in feature space: Matrix bandit, kernels, and regret bound. In *International Conference on Machine Learning*. PMLR.
- YANG, M., DAI, B., NACHUM, O., TUCKER, G. and SCHUURMANS, D. (2020). Offline policy selection under uncertainty. *arXiv preprint arXiv:2012.06919* .
- ZANETTE, A., LAZARIC, A., KOCHENDERFER, M. and BRUNSKILL, E. (2020). Learning near optimal policies with low inherent bellman error. In *International Conference on Machine Learning*. PMLR.
- ZHOU, D., GU, Q. and SZEPESVARI, C. (2021a). Nearly minimax optimal reinforcement learning for linear mixture markov decision processes. In *Conference on Learning Theory*. PMLR.
- ZHOU, D., HE, J. and GU, Q. (2021b). Provably efficient reinforcement learning for discounted mdps with feature mapping. In *International Conference on Machine Learning*. PMLR.