

Robust Distributed Optimization With Randomly Corrupted Gradients

Berkay Turan César A. Uribe Hoi-To Wai Mahnoosh Alizadeh

Abstract—In this paper, we propose a first-order distributed optimization algorithm that is provably robust to Byzantine failures—arbitrary and potentially adversarial behavior, where all the participating agents are prone to failure. We model each agent’s state over time as a two state Markov chain that indicates Byzantine or trustworthy behaviours at different time instants. We set no restrictions on the maximum number of Byzantine agents at any given time. We design our method based on three layers of defense: 1) Temporal gradient averaging, 2) robust aggregation, and 3) gradient normalization. We study two settings for stochastic optimization, namely Sample Average Approximation and Stochastic Approximation, and prove that for strongly convex and smooth non-convex cost functions, our algorithm achieves order-optimal statistical error and convergence rates.

I. INTRODUCTION

Convenience for large-scale data processing, privacy preservation, and parallel algorithm execution rendered the design of distributed optimization algorithms an attractive field for scholars [1]–[7]. However, the distributed nature of such methods, for example, physically separated servers connected over a network, exposes the system to vulnerabilities not faced by their traditional centralized counterparts [8]. The robustness and security of distributed methods need to be taken into account when assessing algorithm performance [2].

In a centralized system, data can be cleaned, faultless computation can be established by reliable hardware, and communication requirements are minimal. On the other hand, typical distributed algorithms assume trustworthy data, faultless computation, and reliable communication. Also, privacy constraints might not allow for data corruption checks, while distributed computing infrastructure increases the likelihood of faulty hardware, e.g., personal devices [9]. Lastly, unreliable communication might occur due to noisy wireless communication, or more importantly, due to man-in-the-middle adversarial attacks. In man-in-the-middle attacks, an adversary can take over network sub-systems and arbitrarily alter the information stored in and communicated between the machines to prevent convergence to the optimal solution, i.e., Byzantine attacks [10].

Robust distributed optimization under adversarial manipulation has been studied for various corruption models, see [11],

[12] for comprehensive reviews. For example, gradients communicated over a network are usually modeled as corrupted by: non-malicious noise [13], adversarial noise [14], quantization [15], or because the gradients are inexact oracles [16]. Although robust optimization methods with strong theoretical guarantees are well established [14], [17], a drawback of these approaches is that the corrupt gradients are assumed to be within a bounded neighborhood of the trustworthy ones, i.e., corruption can be modeled as a bounded additive noise to the trustworthy gradients.

On the other hand, an adversarial corruption model, which can be unbounded and arbitrary, has been extensively studied in the distributed learning literature under categories of data poisoning [18] and model update poisoning attacks [19], [20]. This line of work models corruption as an arbitrary manipulation on the information sent by the agents or on the data samples stored at the agents. However, the adversary is often assumed to have limited capability, i.e., the adversary is only able to manipulate a certain fraction of agents or data samples. Although successful defense mechanisms based on robust aggregation methods [21]–[27] and data sanitation using robust statistics [18] are shown to be robust to these types of manipulation, robust estimation techniques rely on a bounded α fraction of agents/data points being corrupt at all times. Therefore, they are not applicable if there exists iterations with more than α fraction of corrupted agents. For instance, if at any iteration more than half of the agents behave unpredictably and send arbitrarily corrupt information, then the aggregate will be arbitrarily corrupted. In fact, it was recently shown that even more benign-looking manipulations are able to get through these defense mechanisms with corruption rates as low as .5 – 1% [28].

In this paper, we study another corruption model where existing defense mechanisms are prone to failure. In particular, we adopt a distributed optimization framework where a group of agents communicates local gradient information to a central machine that aggregates and distributes information back to the agents. By modeling the temporal dynamics of the agents’ states (either trustworthy or corrupted/Byzantine) via a two-state Markov chain, we allow *all the agents* to be susceptible to *arbitrary corruption*. This means that, even with low corruption rates, there could exist iterations at which the majority of the agents send corrupt gradients to the central machine. For example, the setting where an adversary is able to hack into the communication channels for a finite duration of time, but also is able to take over any communication channel with some success rate fits into the scope of this model. Besides adversarial manipulation, applications that rely on user

B. Turan and M. Alizadeh are with Dept. of ECE, UCSB, Santa Barbara, CA, USA. C. A. Uribe is with Dept. of ECE, Rice University, TX, USA. H. T. Wai is with Dept. of SEEM, CUHK, Shatin, Hong Kong. This work is supported by UCOP Grant LFR-18-548175, NSF grant #1847096, and CUHK Direct Grant #4055113. E-mails: bturan@ucsb.edu, cauribe@rice.edu, htwai@se.cuhk.edu.hk, alizadeh@ucsb.edu

data and choices (e.g., text data) can encounter this type of corruption since users can make (un)intentional mistakes (e.g., typing in multiple languages) at random times. For this setting, we develop a robust distributed optimization algorithm with provable convergence guarantees for a number of function classes.

Contributions: Our main contribution is a distributed stochastic optimization algorithm, named Robust Averaging Normalized Gradient Method (RANGE), that achieves order-optimal statistical error rates and convergence rates while being robust to a new proposed Markovian gradient corruption model.

- We propose a novel Markovian Byzantine agent model that models dynamically changing sets of Byzantine agents with no assumptions on the maximum fraction of Byzantine agents at a particular iteration.
- We study two settings for stochastic optimization for RANGE, namely Sample Average Approximation (SAA) and Stochastic Approximation (SA). We prove that for both SAA and SA, when the parameters are tuned appropriately according to the spectral gap of the Markov chain, RANGE converges to a neighborhood of the optimal solution at a linear rate for strongly convex cost functions.
- We prove that for smooth (possibly non-convex) cost functions, RANGE converges to a neighborhood of a stationary point at a rate of $\mathcal{O}(1/\sqrt{T})$, where T is the number of iterations.
- For the SAA setting, we show that RANGE achieves lower error rates in the Markovian Byzantine agent setup with expected α fraction of Byzantine agents than state-of-the-art algorithms in the setup with a bounded α fraction of Byzantine agents for all iterations.
- We show that RANGE achieves lower statistical error rates in the SA setting than the SAA setting for sufficiently low corruption rates, i.e., the expected fraction of Byzantine agents. We provide explicit characterization of such bound.
- We provide numerical evidence demonstrating efficacy and robustness of RANGE in the proposed setting.

RANGE is designed with three ingredients: (1) temporal gradient averaging, (2) robust aggregation, and (3) gradient normalization. The temporal gradient averaging step estimates the robust mean of each agent’s historical gradient data over a finite window to compute a robustified gradient for each agent. Informally, the received gradients over a period of time contain a fraction of trustworthy information that can be extracted by the algorithm to perform faithful computations rather than applying potentially corrupt gradients directly. In case the robustified gradient produced by temporal averaging becomes contaminated by corruption, another layer of defense mechanism is implemented via robust aggregation of all the agents’ robustified gradients. Lastly, normalization preserves only the directional information and thus prevents large updates that corrupt gradients might cause in case the temporal averaging and robust aggregation steps do not sufficiently eliminate corruptions.

Related work: Our work has connections to the literature on (i) normalized gradient method, (ii) gradient clipping, and (iii) delayed gradient descent.

• *Normalized Gradient Method:* Normalized gradient method is a well-studied algorithm for optimization and is supported by theoretical convergence guarantees for convex [29] and quasi-convex optimization [30]. Using normalized updates is gaining popularity, especially for non-convex optimization [31], since for non-convex objectives, unlike the convex ones, the magnitude of the gradient provides less information about the value of the function, while the direction still indicates the direction of steepest descent. An important benefit of this is the fast evasion of saddle points [32]. Seeing the need for large batch sizes for variance reduction of stochastic gradients as a drawback of normalized updates, a recent work [33] proves that adding momentum removes the need for large batch sizes on non-convex objectives while matching the best-known convergence rates. In a preliminary conference report [34], we investigated the robustness properties of the normalized subgradient method for solving deterministic optimization problems in a centralized fashion. In the current work, we expand [34] into a distributed setup with a stochastic objective function, additionally study non-convex objectives both theoretically and numerically, and employ two additional layers of defense by means of robust mean estimation before applying normalization to improve our algorithm.

• *Gradient Clipping:* As a similar method to normalization, gradient clipping is a common technique in optimization used for privacy [35]. Recent studies demonstrate that gradient clipping can be applied for robustness to model update poisoning attacks [36] and label noise [37]. However, similar to robust distributed optimization literature, due to the limitations on the amount of corruption and adversarial agents, their methods are inapplicable in our setting and can be outperformed, as we will show numerically in Section VII.

• *Delayed Gradient Descent:* Gradient averaging step of our method is in principle similar to a delayed gradient descent method [38], since averaging is a linear combination of the past gradients. Motivated by applications to distributed optimization over networks, researchers have established convergence guarantees for deterministic [39] and stochastic delayed gradient methods [40]. Given strong theoretical results, we integrate the delayed gradient method to our algorithm via averaging and show that it improves robustness.

Paper Organization: The remainder of the paper is organized as follows. In Section II, we define the problem setting. In Section III, we describe our algorithm called RANGE and discuss how it can solve the proposed problem. In Sections IV and V, we present the convergence properties of RANGE for the SAA and SA settings, respectively. In Section VI, we discuss two special cases of RANGE, one without temporal averaging and one with independent random corruption. In Section VII, we provide numerical results for RANGE.

Notations and conventions: Unless otherwise specified, $\|\cdot\|$ denotes the standard Euclidean norm. For any $N \in \mathbb{N}$, $[N]$ denotes the finite set $\{1, \dots, N\}$. Given a vector v , if $\|v\| = 0$, then $v/\|v\| = 0$. The $\mathcal{O}(\cdot)$ notation hides constants, logarithmic terms, and only includes the dominant terms. Given a function $f(x, z)$, $\partial_k f(x, z)$ denotes the partial derivative of $f(x, z)$ with respect to k ’th coordinate of x .

II. PROBLEM SETUP

In this section, we formally set up our problem and introduce key concepts and definitions that will be used in the paper. We are interested in the stochastic optimization problem

$$x^* = \arg \min_{x \in \mathcal{X}} F(x) = \arg \min_{x \in \mathcal{X}} \mathbb{E}_{z \sim \mathcal{D}} [f(x, z)], \quad (1)$$

where $f(x, z)$ is a cost function of a parameter vector $x \in \mathcal{X} \subseteq \mathbb{R}^d$ associated with a data point $z \in \mathcal{Z}$ and the data points are sampled from some unknown distribution \mathcal{D} . To solve (1), we study two settings for stochastic optimization, namely Sample Average Approximation (SAA) [41] and Stochastic Approximation (SA) [42], in a distributed setup with one central machine and N agents that compute stochastic gradients at a point x via $\nabla f(x, z)$ based on independent samples $z \sim \mathcal{D}$.

In iterative distributed first-order methods, given the parameter vector x_t at iteration t , the central machine receives the feedback $\nabla F_{i,t}(x_t)$ from all the agents, aggregates by computing the average, and applies a descent step to get the updated parameter x_{t+1} . Here,

$$F_{i,t}(x_t) = \frac{1}{b} \sum_{j=1}^b f(x_t, z_{i,t}^j) \quad (2)$$

is the empirical risk function and $\{z_{i,t}^j\}_{j \in [b]}$ are the b data points used for gradient computation at agent i and iteration t . In SAA, each agent uses a fixed set of data samples to estimate the gradient at all iterations, i.e., $\{z_{i,\tau}^j\}_{j \in [b]} = \{z_{i,\tau'}^j\}_{j \in [b]}$ and $F_{i,\tau}(x) = F_{i,\tau'}(x) \forall i \in [N], x \in \mathcal{X}, \tau, \tau' \in \mathbb{N}_0$ [43]. In SA, the agents sample b new data points from \mathcal{D} at each iteration and therefore $F_{i,\tau}(x)$ and $F_{i,\tau'}(x)$ are independent random variables $\forall i \in [N], x \in \mathcal{X}, \tau, \tau' \in \mathbb{N}_0$ such that $\tau \neq \tau'$ [43].

Such methods, however, rely on the feedback received from each agent being trustworthy gradient information and might fail to converge when the feedback becomes corrupt, as one single corrupt feedback can have an arbitrarily large effect. Denote the set of agents communicating a corrupt gradient information, i.e., Byzantine agents, at iteration t by \mathcal{B}^t , and the set of agents communicating a trustworthy gradient information, i.e., trustworthy agents, at iteration t by \mathcal{T}^t . At each iteration t , the feedback is determined as:

$$g_{i,t} = \begin{cases} \nabla F_{i,t}(x_t) & \text{if } i \in \mathcal{T}^t, \\ \star & \text{if } i \in \mathcal{B}^t, \end{cases} \quad (3)$$

where the corrupt feedback \star is arbitrary and is possibly chosen by an adversary, who may have full knowledge of the problem. We note that this model encompasses a large class of scenarios where the feedback can become corrupt (e.g., errors in communication or computation, corrupt data, adversarial manipulation) since we set no restrictions on \star .

Contrary to existing literature, we study dynamically changing sets of Byzantine agents \mathcal{B}^t and trustworthy agents \mathcal{T}^t , where the transition of each agent from Byzantine/trustworthy state to trustworthy/Byzantine state happens probabilistically at each iteration. In particular, we define

$$p_b = \mathbb{P}(i \in \mathcal{B}^{t+1} | i \in \mathcal{T}^t), \quad \forall i \in [N], \forall t, \quad (4)$$

$$p_t = \mathbb{P}(i \in \mathcal{T}^{t+1} | i \in \mathcal{B}^t), \quad \forall i \in [N], \forall t, \quad (5)$$

Algorithm 1: Robust Averaging Normalized Gradient Method (RANGE)

- 1: **Input:** Initialize $x_1 \in \mathcal{X}$, step size γ , window size m , $m_0 \in \mathbb{N}_0$, T , and $\alpha_1, \alpha_2 < 0.5$ s.t. $\alpha_1 m, \alpha_2 N \in \mathbb{N}_0$.
 - 2: **for** $t = 1$ **to** $T + m - 1 + m_0$ **do**
 - 3: Broadcast x_t to the agents.
 - 4: Receive $g_{i,t}$, defined in (3), for $i \in [N]$.
 - 5: **if** $t \leq m - 1$ **then**
 - 6: Set $\hat{g}_{i,t} = g_{i,t}$.
 - 7: **else**
 - 8: Compute the robust mean $\hat{g}_{i,t}$ of $\{g_{i,t-\tau}\}_{\tau=0}^{m-1}$ using (10) with parameters α_1 and m , for $i \in [N]$.
 - 9: **end if**
 - 10: Compute the robust mean \hat{g}_t of $\{\hat{g}_{i,t}\}_{i \in [N]}$ using (10) with parameters α_2 and N .
 - 11: Compute $x_{t+1} = \Pi_{\mathcal{X}}(x_t - \gamma \hat{g}_t / \|\hat{g}_t\|)$.
 - 12: **end for**
-

where $0 < p_b < p_t < 1$. Accordingly, each agent's state transition over time is governed by a two-state Markov chain with transition matrix

$$M = \begin{bmatrix} 1 - p_b & p_b \\ p_t & 1 - p_t \end{bmatrix}, \quad (6)$$

and stationary distribution

$$\pi^* = \begin{bmatrix} \frac{p_t}{p_t + p_b} & \frac{p_b}{p_t + p_b} \end{bmatrix}, \quad (7)$$

where state 0 corresponds to the trustworthy state and state 1 corresponds to the Byzantine state. We note that the exact knowledge of the transition probabilities is not necessary. We can take p_b as an upper bound on the trustworthy to Byzantine transition probability, and p_t as a lower bound on the Byzantine to trustworthy transition probability.

In the next section, we explain the first-order method we propose to obtain a near-optimal solution to (1) in setting defined by (3)-(5). In addition to achieving order-optimal convergence rates, our goal is to converge to a neighborhood with order-optimal statistical error rates.

For completeness, we end this section with a couple of standard definitions from convex analysis regarding a differentiable function $f : \mathbb{R}^d \rightarrow \mathbb{R}$.

Definition 1. A differentiable function f is said to be *L-smooth* if there exists $L > 0$ such that

$$\|\nabla f(x_1) - \nabla f(x_2)\| \leq L \|x_1 - x_2\|, \quad (8)$$

for all $x_1, x_2 \in \mathcal{X}$.

Definition 2. A differentiable function f is said to be *μ -strongly convex* if there exists $\mu > 0$ such that

$$\langle \nabla f(x_1) - \nabla f(x_2), x_1 - x_2 \rangle \geq \mu \|x_1 - x_2\|^2, \quad (9)$$

for all $x_1, x_2 \in \mathcal{X}$.

III. ROBUST AVERAGING NORMALIZED GRADIENT METHOD (RANGE)

To solve Problem (1) in the Byzantine setting defined by (3)-(5), we propose an algorithm called Robust Averaging

Normalized Gradient MEthod (RANGE), which is summarized in Algorithm 1. There are three main interacting ideas behind Algorithm 1 to guarantee convergence and robustness: 1) temporal gradient averaging, 2) robust aggregation, and 3) gradient normalization. Temporal gradient averaging in Step 8 of Algorithm 1 aims to compute a robustified gradient for all agents by estimating a robust mean of a window of past gradients. The intuition behind this is that despite corruptions, the feedback received over a long period from every single agent contains a fraction of trustworthy information that the algorithm can extract to perform accurate computations. To defend against the scenarios where the robustified gradient produced by the temporal averaging step is corrupted for some of the agents (e.g., if the window only contains corrupted gradients), in Step 10 of Algorithm 1 we implement a second layer of robust mean estimation when aggregating all the agents' robustified gradients in order to eliminate those corrupted gradients. Lastly, by gradient normalization in Step 11 of Algorithm 1, we restrict the aggregate gradient to only contain a directional information. This prevents arbitrarily large updates in case the temporal averaging and robust aggregation steps do not sufficiently eliminate the corruptions.

Let us provide a summary of Algorithm 1. At each iteration t , the central node receives the feedback $g_{i,t}$ according to (3) from all the agents. If $t \geq m$, it estimates a robustified gradient $\hat{g}_{i,t}$ for each agent $i \in [N]$ by performing a robust temporal averaging over a window of gradients $\{g_{i,t-\tau}\}_{\tau=0}^{m-1}$ using the median-based mean estimator that will be described later. If $t < m$, it simply sets $\hat{g}_{i,t} = g_{i,t}$. Then, it aggregates the robustified gradients $\{\hat{g}_{i,t}\}_{i \in [N]}$ using the same median-based mean estimator to get the robust aggregate \hat{g}_t and moves the iterate along $\hat{g}_t / \|\hat{g}_t\|$ with step size γ . Finally the algorithm projects the point back to the decision set \mathcal{X} .

To get a good grasp of why RANGE works, let us discuss how the mechanics of each step assist the convergence of the algorithm, starting with the robust mean estimator.

Robust mean estimator: Suppose that we have a set of k vectors $\{v_i \in \mathbb{R}^d\}_{i=0}^{k-1}$ that may contain corrupted values, whose identities are not known. We wish to estimate the mean of the trustworthy vectors robustly by minimizing the impact of the corrupt gradients on the mean estimate, potentially by filtering the corrupt gradients out. We consider a simple median-based estimator applied to each coordinate $j = 1, \dots, d$. First, define the coordinate-wise median as $[v_{\text{med}}]_j = \text{med}(\{[v_i]_j\}_{i=0}^{k-1})$, where $\text{med}(\cdot)$ computes the coordinate-wise medians. Then, our estimator is computed as the mean of the nearest $(1 - \alpha)k$ neighbors of $[v_{\text{med}}]_j$, where α is a chosen threshold parameter such that $\alpha k \in \mathbb{N}_0$. We propose the estimator

$$[\hat{v}]_j = \frac{1}{(1 - \alpha)k} \sum_{i \in \mathcal{N}_j} [v_i]_j, \quad (10)$$

where $\mathcal{N}_j = \{i \in \{0, 1, \dots, k - 1\} : |[v_i - v_{\text{med}}]_j| \leq r_j\}$, such that r_j is chosen to satisfy $|\mathcal{N}_j| = (1 - \alpha)k$.

The outcome of this estimator depends on the threshold parameter α . If α is chosen such that the number of trustworthy vectors is less than $(1 - \alpha)k$, then \mathcal{N}_j will contain arbitrarily corrupted gradients and the estimate will be arbitrarily corrupted. However, if α is chosen such that the number of

trustworthy vectors is at least $(1 - \alpha)k$, we have the following theoretical guarantees for the performance of this estimator:

Proposition 1. [44, Proposition 2] *Let \mathcal{H} be the set of trustworthy vectors and $|\mathcal{H}| \geq (1 - \alpha)k$. Let $\bar{v}_{\mathcal{H}}$ be the mean of the trustworthy vectors. Suppose that $\max_{i \in \mathcal{H}} \|v_i - \bar{v}_{\mathcal{H}}\|_{\infty} \leq r$, then for any $\alpha \in [0, 1/2)$, it holds that:*

$$\|\hat{v} - \bar{v}_{\mathcal{H}}\| \leq \frac{2\alpha}{1 - \alpha} \left(1 + \sqrt{\frac{(1 - \alpha)^2}{1 - 2\alpha}}\right) r\sqrt{d}. \quad (11)$$

We note that the right hand side of (11) can be approximated as $\mathcal{O}(\alpha r\sqrt{d})$ for small α .

Temporal averaging: Following the mechanics of the robust mean estimator, two scenarios can happen every time robust temporal averaging is applied in Step 8 of Algorithm 1 to a window of m latest gradients from each agent: (i) there are less than $(1 - \alpha_1)m$ trustworthy gradients in the window of size m ; (ii) there are at least $(1 - \alpha_1)m$ trustworthy gradients in the window of size m . Under scenario (i), \mathcal{N}_j contains arbitrarily corrupted gradients, and therefore we have to assume that the estimated mean is arbitrarily corrupted. We say that the temporal averaging *fails* in this scenario. Under scenario (ii), the estimated mean is close to the true mean of the trustworthy gradients, and the error is bounded by (11). Therefore if scenario (ii) happens at any iteration, instead of using a probably corrupt gradient that can be adversarial, the robust temporal averaging step computes a robustified gradient close to the mean of past trustworthy gradients. We say that the temporal averaging *succeeds* in this scenario. Accordingly, we can view scenario (ii) as a perturbed version of the delayed gradient method, whose convergence properties have been well-studied [39]. Note that both scenarios (i) and (ii) happen with some probability determined by p_t , p_b , α_1 and m .

Robust aggregation: Similar to the temporal averaging step, two scenarios can happen every time robust aggregation is applied in Step 10 of Algorithm 1 to N robustified gradients: (I) there are less than $(1 - \alpha_2)N$ agents for which the temporal averaging step succeeds, (II) there are at least $(1 - \alpha_2)N$ agents for which the temporal averaging step succeeds. By similar arguments as above, scenario (I) results in an arbitrarily corrupted estimate, whereas scenario (II) results in an estimate that is close to the true mean of the successfully robustified gradients, and the error is bounded by (11). We note that both scenarios (I) and (II) happen with some probability determined by α_2 , N , and probabilities of scenarios (i) and (ii).

Gradient normalization: The main idea behind the normalization step is to prevent large updates that corrupt gradients might cause. Since in case of scenario (I), the temporal averaging and the robust aggregation steps fail to produce an aggregate gradient estimate for which the theoretical error bounds hold, we have to assume that the aggregate gradient estimate becomes arbitrarily corrupted. When this happens and corruptions get past through the two layers of defense, we limit the amount of damage caused by the corrupted aggregate gradient estimate by normalization.

In the next section, we state the convergence guarantees of RANGE for strongly convex and smooth (possibly non-convex) cost functions for the SAA setting.

IV. CONVERGENCE PROPERTIES OF RANGE FOR THE SAA SETTING

Before presenting the convergence results, we need to state some technical assumptions.

Assumption 1. For all $k \in [d]$ and $x \in \mathcal{X}$, define the random variable $f_k(x, z) := \partial_k f(x, z) - \partial_k F(x)$. We assume that for all $k \in [d]$ and $x \in \mathcal{X}$, $f_k(x, z)$ is a sub-gamma random variable with variance factor σ and scale parameter a for some $a \geq 0$, i.e.:

$$\log \mathbb{E}_{z \sim \mathcal{D}} [e^{\lambda f_k(x, z)}] \leq \frac{\lambda^2 \sigma^2}{2(1 - a|\lambda|)}, \quad \forall x, k, |\lambda| < \frac{1}{a}. \quad (12)$$

Assumption 1 shows bounded moments of the loss function with respect to the data distribution. Note that sub-Gaussian/sub-exponential random variables satisfy Assumption 1 with $a = 0/a = \sigma$, respectively. Therefore, Assumption 1 is less restrictive than sub-Gaussian/sub-exponential assumptions in the literature [25], [26].

Assumption 2. The function $f(\cdot, z)$ is L -smooth, $\forall z \in \mathcal{Z}$.

In addition, when $F(\cdot)$ is strongly convex, we have the following assumption on \mathcal{X} and the minimizer of $F(\cdot)$:

Assumption 3. The parameter set \mathcal{X} is assumed to be convex and compact with diameter R . Furthermore, $F(x)$ has a unique minimizer $x^* \in \mathcal{X}$ satisfying $\nabla F(x^*) = 0$.

Together with convexity of F , the above assumption implies that the minimizer of $F(\cdot)$ in \mathcal{X} is also the minimizer of $F(\cdot)$ in \mathbb{R}^d . We note that by selecting \mathcal{X} as the euclidean norm ball of a large radius R , the assumption can be satisfied.

Recall from Proposition 1 that in order for the error bound (11) to hold in Algorithm 1 Step 8, the robust mean estimator (10) requires that at least $(1 - \alpha_1)m$ vectors in $\{g_{i, t-\tau}\}_{\tau=0}^{m-1}$ are trustworthy gradients (scenario (ii) in Sec. III). Similarly, in order for the error bound (11) to hold in Algorithm 1 Step 10, the robust mean estimator (10) requires that at least $(1 - \alpha_2)N$ vectors in $\{\hat{g}_{i, t}\}_{i \in [N]}$ are successfully robustified (scenario (II) in Sec. III). In order to mathematically formalize these scenarios, we define the following random variables:

- $W_{i, t} = 1$ if $i \in \mathcal{B}^t$, 0 otherwise,
- $Y_{i, t} = 1$ if for agent i , $\sum_{\tau \in [t-m+1, t]} W_{i, \tau} > \alpha_1 m$ (scenario (i)), $Y_{i, t} = 0$ otherwise (scenario (ii)),
- $Z_t = 1$ if $\sum_{i \in [N]} Y_{i, t} > \alpha_2 N$ (scenario (I)), $Z_t = 0$ otherwise (scenario (II)).

Using the above definitions of random variables, when $Y_{i, t} = 1$, the temporal averaging step fails to produce a robustified gradient for agent i . Therefore when $Z_t = 1$, the algorithm fails to produce a robustified update direction as the robust aggregation step becomes contaminated. The challenge of the convergence analysis of Algorithm 1 arises from studying both scenarios $Z_t = 0$ and $Z_t = 1$ along with their probabilities of happening. However, given the Markovian property of $\{W_{i, t}\}_{\forall t}$, Z_t is not independent of the past, which presents an obstacle in the convergence analysis. To overcome this, we state the next lemma, which establishes a uniform bound on probability that $Z_t = 1$ given the network state at an earlier time instant:

Lemma 1. Let $\mathcal{S}_t = \{x_t, \{\pi_t^i\}_{i \in [N]}\}$ denote the system state at iteration t , where π_t^i is the distribution of the state of agent i at iteration t . Given the algorithm parameters $(m, N, \alpha_1, \alpha_2, M)$ with $\alpha_1 > p_b/(p_b + p_t)$, for all $m_0 \in \mathbb{N}_0$ and $t \geq m + m_0$, there exists a uniform bound on $\mathbb{P}(Z_t = 1 | \mathcal{S}_{t-m+1-m_0}) = \mathbb{E}[Z_t | \mathcal{S}_{t-m+1-m_0}]$ independent of $\mathcal{S}_{t-m+1-m_0}$ such that:

$$\mathbb{E}[Z_t | \mathcal{S}_{t-m+1-m_0}] \leq P_Z(m_0, m, N, \alpha_1, \alpha_2, M). \quad (13)$$

Furthermore, let $P_Z^m(m_0) := P_Z(m_0, m, N, \alpha_1, \alpha_2, M)$. Then, the following holds for all $m_0 \in \mathbb{N}_0$:

$$P_Z^m(m_0) \leq \sum_{k=\alpha_2 N+1}^N \binom{N}{k} (P_Y^m(m_0))^k (1 - P_Y^m(m_0))^{(N-k)}, \quad (14)$$

where

$$P_Y^m(m_0) = K(m_0) \exp\left(\frac{-(p_b + p_t)m(\alpha_1 - \frac{p_b}{p_b + p_t})^2}{12} + \frac{p_b + p_t}{5}\right), \quad (15)$$

and

$$K(m_0) = \sqrt{1 + (1 - p_b - p_t)^{2m_0} p_t / p_b}. \quad (16)$$

Proof of Lemma 1 can be found in Appendix A. Given a non-negative integer $m_0 \in \mathbb{N}_0$, Lemma 1 sets an upper bound on $\mathbb{E}[Z_t | \mathcal{S}_{t-m+1-m_0}]$ independent of the system state at time $t - m + 1 - m_0$, but only as functions of the algorithm parameters $(m, N, \alpha_1, \alpha_2, M)$ and m_0 . Although Lemma 1 provides a practical closed form bound, it is derived by using a Chernoff-type bound for Markov chains [45]. It facilitates exposition of the method but it is not tight. In Appendix G, we provide a tighter bound on $P_Z^m(m_0)$. Note that by Hoeffding's inequality, we have $P_Z^m(m_0) \leq e^{-2(\alpha_2 - P_Y^m(m_0))^2 N}$.

A. Strongly Convex and Smooth Functions

We are now ready to present the main technical result on convergence guarantees of RANGE for a strongly convex cost function $F(\cdot)$. For the following result, we do not require strong convexity of individual cost functions $f(\cdot, z)$.

Theorem 1. Let $F(\cdot)$ be μ -strongly convex and Assumptions 1, 2, and 3 hold. Define the condition number as $\kappa := L/\mu$. Let $m_0 \in \mathbb{N}_0$ be a non-negative integer. If the algorithm parameters $(m, N, \alpha_1, \alpha_2, M)$ satisfy

$$P_Z^m(m_0) < \frac{1}{1 + \kappa}, \quad (17)$$

then for any $T \geq 1$, the iterates produced by Algorithm 1 in the SAA setting, with

$$\gamma \leq \frac{4\sigma}{\bar{C}(m_0)\mu\sqrt{(1 - \alpha_2)Nb}}, \quad (18)$$

have the following property:

$$\begin{aligned} \mathbb{E}[\|x_{T+m+m_0} - x^*\|^2] &\leq \\ &(\|x_1 - x^*\| + \gamma(m + m_0 - 1))^2 (1 - c_0(m_0)\gamma)^T \\ &+ \mathcal{O}\left(\frac{1}{\sqrt{Nb}} + \frac{C_{\alpha_2}}{\sqrt{b}}\right), \end{aligned} \quad (19)$$

where

$$c_0(m_0) = \frac{2}{\kappa R} (1 - P_Z^m(m_0)(1 + \kappa)), \quad (20)$$

$$\bar{C}(m_0) = 1 + 4P_Z^m(m_0)(1 + 1/\kappa)(m - 1 + m_0) + 4\kappa(m - 1)(1 + C_{\alpha_1} + 2C_{\alpha_2}(C_{\alpha_1} + 1)), \quad (21)$$

$$C_{\alpha_i} = \frac{2\alpha_i}{1 - \alpha_i} \left(1 + \sqrt{\frac{(1 - \alpha_i)^2}{1 - 2\alpha_i}} \right) \sqrt{d}, \quad i = 1, 2. \quad (22)$$

The proof of Theorem 1 and the explicit constants of (19) can be found in Appendix B. According to Theorem 1, RANGE provides convergence to a neighborhood of the optimal solution at a linear rate as long as (17) is satisfied, where the neighborhood of convergence is

$$\mathcal{O} \left(\frac{1}{\sqrt{Nb}} + \frac{C_{\alpha_2}}{\sqrt{b}} \right). \quad (23)$$

Remark 1. In Appendix B, we show that the only dependence of the neighborhood of convergence in (23) on m_0 is through $P_Z^m(m_0)$ given by (14). By taking $m_0 \gg 1$, we minimize (16) to get $K(m_0) \approx 1$, which then minimizes $P_Y^m(m_0)$ and $P_Z^m(m_0)$. Hence we get a tight asymptotic bound with respect to m_0 for $m_0 \rightarrow \infty$.

Impact of temporal averaging: The temporal averaging step helps reducing the neighborhood of convergence by reducing the effective fraction of Byzantine agents at each iteration. The convergence neighborhood given by (23) consists of two terms: first term due to variance of the stochastic gradients and the second term due to Byzantine agents. In [26], it is shown that in the setting with a bounded α fraction of Byzantine agents, no algorithm can achieve an error lower than

$$\tilde{\Omega} \left(\frac{1}{\sqrt{Nb}} + \frac{\alpha}{\sqrt{b}} \right). \quad (24)$$

In the stationary distribution of the Markov chain, the probability that an agent is Byzantine is equal to $p_b/(p_b + p_t)$, and the expected fraction of Byzantine agents in an iteration is $p_b/(p_b + p_t)$. Therefore, it is reasonable to argue that α in (24) is similar to $p_b/(p_b + p_t)$. For Lemma 1 to hold, we need $\alpha_1 > p_b/(p_b + p_t)$ and thus α_1 is of the order of α in (24). On the other hand, our error bound in (23) is a function of C_{α_2} , where $C_{\alpha_2} = \mathcal{O}(\alpha_2)$ for small α_2 . Because RANGE aims to eliminate α_2 fraction of agents' robustified gradients via robust aggregation, it can be viewed as the effective fraction of Byzantine agents, and hence our bound is consistent with (24). Interestingly, we can set α_2 as arbitrarily small as possible. Note that we need to satisfy (17) for convergence. However, in (14), we can select α_2 sufficiently small for small $P_Y^m(m_0)$. But $P_Y^m(m_0)$ is given by (15), which is a function of α_1 , m , and m_0 . As such, we can always set m arbitrarily large such that $P_Y^m(m_0)$ is arbitrarily small for all $m_0 \in \mathbb{N}_0$, and hence we can select α_2 arbitrarily small to satisfy (17). As a result, by employing the robust temporal averaging step before robust aggregation, which is beneficial only when agents' states change over time, we reduce the effective fraction of Byzantine agents from $p_b/(p_b + p_t)$ to α_2 . This setup shows that the lower bound (24) does not hold for the proposed Markovian setting as a result of temporal averaging.

Observe that choice of m , α_1 , and α_2 plays an important role, as they determine whether (17) holds or not. Next, we discuss how to pick m , α_1 , and α_2 in practice.

Choices of m , α_1 , and α_2 : For a given transition matrix M , there always exists a set of parameters m , α_1 , and α_2 such that (17) is satisfied. Finding a principled way to select the set of optimal parameters is currently an open question. Instead, next we describe an implementable closed form expression for the minimum window size as a function of α_1 , α_2 , p_t , and p_b . Using Hoeffding's inequality on (14), we rewrite (17) as:

$$P_Z^m(m_0) \leq \exp(-2(\alpha_2 - P_Y^m(m_0))^2 N) < \frac{1}{1 + \kappa}. \quad (25)$$

This gives us the condition on α_2 ¹:

$$\alpha_2 > P_Y^m(m_0) + \sqrt{\frac{\log(1 + \kappa)}{2N}}. \quad (26)$$

Next, observe from (15) that $P_Y^m(m_0) \leq P_Y^m(0)$, and therefore the above condition is met if

$$\alpha_2 > P_Y^m(0) + \sqrt{\frac{\log(1 + \kappa)}{2N}}. \quad (27)$$

We plug (15) with $m_0 = 0$ into the above inequality and rearrange to get the minimum window size that is sufficient for convergence as a function of α_1 , α_2 , p_t , and p_b :

Corollary 1. Let $\alpha_2 > \sqrt{\log(1 + \kappa)/(2N)}$, $\alpha_1 > p_b/(p_b + p_t)$, and

$$m > \frac{12 \log \left(\frac{(p_b + p_t) e^{\frac{p_t + p_b}{5}}}{p_b (\alpha_2 - \sqrt{\log(1 + \kappa)/(2N)})} \right)}{(p_t + p_b) (\alpha_1 - \frac{p_b}{p_t + p_b})^2}, \quad (28)$$

then (17) holds for all $m_0 \in \mathbb{N}_0$.

Corollary 1 is convenient in practice for selecting α_1 , α_2 , and m . Given p_b , p_t , and κ , one picks α_1 such that $p_b/(p_b + p_t) < \alpha_1 < 0.5$ and α_2 such that $\sqrt{\log(1 + \kappa)/(2N)} < \alpha_2 < 0.5$ ¹ and $\alpha_2 N \in \mathbb{N}_0$. Then, the window size m is picked such that $\alpha_1 m \in \mathbb{N}_0$ and (28) holds. With these parameter choices, (17) is satisfied for all $m_0 \in \mathbb{N}_0$. Note that the $(p_t + p_b)$ term in the denominator of (28) corresponds to the spectral gap of the Markov chain. Therefore, smaller spectral gap, which also implies larger relaxation and mixing time [46], results in a larger minimum window size. Intuitively, we select the window size at the order of the mixing time so that the Markov chain gets close to its stationary distribution and the Byzantine agents transition into trustworthy state. This allows the temporal averaging step to successfully produce a robustified gradient by extracting the trustworthy information.

B. Smooth (Possibly Non-Convex) Functions

Next, we study the convergence of RANGE for smooth (possibly non-convex) cost functions. For this problem class, we need the following assumption on \mathcal{X} :

¹This is the condition on α_2 for the Hoeffding bound (25) to hold, rather than the exact inequality in (14). Consequently, it results in an additive $\sqrt{\log(1 + \kappa)/(2N)}$ term that is independent of $P_Y^m(m_0)$. However, this does not contradict our statement that we can set α_2 arbitrarily small by reducing $P_Y^m(m_0)$ with a large window m , since that statement is based on the exact form in (14) rather than the Hoeffding bound (25).

Assumption 4. Problem (1) is unconstrained, i.e., $\mathcal{X} = \mathbb{R}^d$.

The next theorem states the convergence guarantees of RANGE for smooth $F(\cdot)$:

Theorem 2. Let Assumptions 1, 2, and 4 hold. Choose step-size $\gamma = \gamma_0/\sqrt{T}$ with $\gamma_0 > 0$. Let $m_0 \in \mathbb{N}_0$ be a non-negative integer. If the algorithm parameters $(m, N, \alpha_1, \alpha_2, M)$ satisfy

$$P_Z^m(m_0) < 1/2, \quad (29)$$

then for any $T \geq 1$, the iterates $\{x_t\}_{t=m+m_0}^{T+m-1+m_0}$ produced by Algorithm 1 in the SAA setting satisfy

$$\begin{aligned} & \frac{1}{T} \sum_{t=m+m_0}^{T+m-1+m_0} \mathbb{E}[\|\nabla F(x_t)\|] \\ & \leq \frac{F(x_1) - F(x^*)}{\sqrt{T}\gamma_0(1 - 2P_Z^m(m_0))} + \frac{\bar{C}(m_0)\gamma_0}{\sqrt{T}} + \mathcal{O}\left(\frac{1}{T}\right) \\ & + \mathcal{O}\left(\frac{1}{\sqrt{Nb}} + \frac{C_{\alpha_2}}{\sqrt{b}}\right), \end{aligned} \quad (30)$$

where

$$\begin{aligned} \bar{C}(m_0) &= L\left(1/2 + 4(m-1+m_0)P_Z^m(m_0)\right. \\ & \left. + 2(m-1)(1+C_{\alpha_1}+2C_{\alpha_2}(C_{\alpha_1}+1))\right), \end{aligned} \quad (31)$$

and C_{α_i} for $i = 1, 2$, are given by (22).

Proof of Theorem 2 and the full expression of (30) can be found in Appendix C. According to Theorem 2, there exists a point $\tilde{x} \in \{x_{m+m_0}, \dots, x_{T+m-1+m_0}\}$ produced by RANGE such that

$$\mathbb{E}\|\nabla F(\tilde{x})\| \leq \mathcal{O}\left(\frac{1}{\sqrt{Nb}} + \frac{C_{\alpha_2}}{\sqrt{b}} + \frac{1}{\sqrt{T}}\right). \quad (32)$$

Note that when $T \rightarrow \infty$, the right hand side of the above inequality is the same as (23).

In the next section, we state the convergence guarantees of RANGE for strongly convex and smooth (possibly non-convex) cost functions for the SA setting.

V. CONVERGENCE PROPERTIES OF RANGE FOR THE SA SETTING

Theorems 1 and 2 state convergence guarantees of RANGE for the SAA setting. The next theorem states a similar convergence result for the SA setting for strongly convex cost functions.

Theorem 3. Let $F(\cdot)$ be μ -strongly convex and Assumptions 1, 2, and 3 hold. Define the condition number as $\kappa := L/\mu$. Let $m_0 \in \mathbb{N}_0$ be a non-negative integer. If the algorithm parameters $(m, N, \alpha_1, \alpha_2, M)$ satisfy

$$P_Z^m(m_0) < \frac{1}{1+\kappa}, \quad (33)$$

then for any $T \geq 1$, the iterates produced by Algorithm 1 in the SA setting, with

$$\gamma \leq \frac{4\sigma}{\bar{C}(m_0)\mu\sqrt{(1-\alpha_2)N(1-\alpha_1)mb}}, \quad (34)$$

have the following property:

$$\begin{aligned} & \mathbb{E}[\|x_{T+m+m_0} - x^*\|^2] \leq \\ & (\|x_1 - x^*\| + \gamma(m+m_0-1))^2 (1 - c_0(m_0)\gamma)^T \\ & + \mathcal{O}\left(\frac{1}{\sqrt{(1-\alpha_1)mNb}} + \frac{C_{\alpha_2} + C_{\alpha_1}(1+C_{\alpha_2})}{\sqrt{b}}\right), \end{aligned} \quad (35)$$

where $c_0(m_0)$, $\bar{C}(m_0)$ and C_{α_i} for $i = 1, 2$, are given by (20), (21), and (22).

Proof of Theorem 3 and the full expression of (35) can be found in Appendix D. According to Theorem 3, RANGE provides convergence to a neighborhood of the optimal solution at a linear rate as long as (33) is satisfied, where the neighborhood of convergence is

$$\mathcal{O}\left(\frac{1}{\sqrt{(1-\alpha_1)mNb}} + \frac{C_{\alpha_2} + C_{\alpha_1}(1+C_{\alpha_2})}{\sqrt{b}}\right). \quad (36)$$

Comparing the above result to (23), there are two impacts of using the SA setting instead of the SAA setting:

- 1) The error due to variance of the stochastic gradients reduces by a factor of $\mathcal{O}(\sqrt{(1-\alpha_1)m})$,
- 2) The error due to Byzantine agents increases by a factor of $\mathcal{O}(1 + C_{\alpha_1} + C_{\alpha_1}/C_{\alpha_2})$.

When agents use new samples at each iteration in the SA setting, temporal gradient averaging results in a variance reduction, since it estimates the mean of $(1-\alpha_1)m$ independent minibatch gradients. However, this comes at the cost of higher error caused by the Byzantine agents. Given these two counteracting impacts of the SA setting on the error, the order of error in (36) is less than (23) if

$$C_{\alpha_1} < \frac{1}{\sqrt{N}(1+C_{\alpha_2})}. \quad (37)$$

Therefore, RANGE performs better in the SA setting compared to the SAA setting if $\alpha_1 \ll 1$, which is possible if $p_b \ll p_t$. Otherwise, the benefit of variance reduction provided by temporal gradient averaging is dominated by the damage caused by the Byzantine agents.

The next theorem states the convergence result of RANGE for the SA setting for non-convex cost functions.

Theorem 4. Let Assumptions 1, 2, and 4 hold. Choose step-size $\gamma = \gamma_0/\sqrt{T}$ with $\gamma_0 > 0$. Let $m_0 \in \mathbb{N}_0$ be a non-negative integer. If the network and algorithm parameters $(m, N, \alpha_1, \alpha_2, M)$ satisfy

$$P_Z^m(m_0) < 1/2, \quad (38)$$

then for any $T \geq 1$, the iterates $\{x_t\}_{t=m+m_0}^{T+m-1+m_0}$ produced by Algorithm 1 in the SA setting satisfy

$$\begin{aligned} & \frac{1}{T} \sum_{t=m+m_0}^{T+m-1+m_0} \mathbb{E}[\|\nabla F(x_t)\|] \\ & \leq \frac{F(x_1) - F(x^*)}{\sqrt{T}\gamma_0(1 - 2P_Z^m(m_0))} + \frac{\bar{C}(m_0)\gamma_0}{\sqrt{T}} + \mathcal{O}\left(\frac{1}{T}\right) \\ & + \mathcal{O}\left(\frac{1}{\sqrt{(1-\alpha_1)mNb}} + \frac{C_{\alpha_2} + C_{\alpha_1}(1+C_{\alpha_2})}{\sqrt{b}}\right), \end{aligned} \quad (39)$$

where $\bar{C}(m_0)$ and C_{α_i} for $i = 1, 2$, are given by (31) and (22).

Proof of Theorem 4 and the full expression of (39) can be found in Appendix E. Note that when $T \rightarrow \infty$, the right hand side of (39) is the same as (36).




Fig. 1: Convergence performance of RANGE in linear regression with four configurations of (m, α_1, α_2) for $p_t = 0.1$, $p_b = 0.025$.

VI. SPECIAL CASES

A. Window Size $m = 1$

When we select the window size m to be 1, we have to set $\alpha_1 = 0$ since $\alpha_1 m \in \mathbb{N}_0$ and $\alpha_1 < 0.5$. This means that we skip the robust temporal averaging step and set the robustified gradient $\hat{g}_{i,t} = g_{i,t}$. In this case, the counterpart of Lemma 1 with $m = 1$ gives:

$$P_Z^1(m_0) \leq \sum_{k=\alpha_2 N+1}^N \binom{N}{k} (P_Y^1(m_0))^k (1 - P_Y^1(m_0))^{(N-k)}, \quad (40)$$

where

$$\begin{aligned} P_Y^1(m_0) &= \max_{i \in [N], t} \mathbb{P}(Y_{i,t} = 1 | \mathcal{S}_{t-m_0}) = \max_{i \in [N], t} \mathbb{P}(W_{i,t} = 1 | \mathcal{S}_{t-m_0}) \\ &= \frac{p_b + p_t(1 - p_b - p_t)^{m_0}}{p_b + p_t}. \end{aligned} \quad (41)$$

Accordingly, Theorems 1, 2, 3, and 4 hold with $m = 1$ and $P_Z^1(m_0)$ given by (40) and (41). Note that $P_Y^1(m_0) \rightarrow p_b / (p_b + p_t)$ as $m_0 \rightarrow \infty$.

B. Independent Random Corruption

A special case of the agents' state transition occurs when $p_b + p_t = 1$. We get $M = [\pi^{*T} \ \pi^{*T}]^T$, and hence the state of an agent at $t + 1$ is independent of the state at t . In this case, an agent becomes Byzantine and sends corrupted gradient information randomly with probability p_b at all iterations. Hence, we can state the counterpart of Lemma 1 without the need to condition on a previous time instant, i.e.,

$$P_Z^m := \mathbb{E}[Z_t] = \sum_{k=\alpha_2 N+1}^N \binom{N}{k} (P_Y^m)^k (1 - P_Y^m)^{(N-k)}, \quad (42)$$

where

$$P_Y^m = \sum_{j=\alpha_1 m+1}^m \binom{m}{j} p_b^j p_t^{m-j}. \quad (43)$$

Accordingly, Theorems 1, 2, 3, and 4 hold with $m_0 = 0$ and $P_Z^m(m_0)$ replaced by P_Z^m given by (42) and (43).

VII. NUMERICAL EXPERIMENTS

In this section, we present numerical evidence supporting our theoretical results and demonstrating the efficacy of RANGE. The first experiment is a simple linear regression with synthetic data to illustrate the benefits of the temporal averaging step of RANGE and to compare the SAA and the SA settings. The second experiment is an image classification




Fig. 2: Comparison of the SA and the SAA settings in linear regression.

task on the EMNIST dataset [47] using a neural network to compare the performance of RANGE to existing distributed optimization algorithms in practical non-convex tasks for the SAA setting. Both experiments were performed on a laptop computer with Intel® Core™ i7-8750H CPU (6×2.20 GHz) and 16 GB DDR4 2666MHz RAM.

A. Linear Regression with Synthetic Data

We consider the following stochastic optimization problem:

$$x^* = \arg \min_{x \in \mathcal{X}} \mathbb{E}_{V, Y} [\|Y - V^T x\|], \quad (44)$$

where $V \in \mathbb{R}^d$ is the random vector corresponding to the data points and $Y \in \mathbb{R}$ is the random variable corresponding to the associated label values or outputs. We let $d = 100$ and constructed the solution vector x^* by sampling a random point from the interior of the d -ball with radius $R = 10$. In the SAA setting, the goal is to solve the following deterministic optimization problem

$$\min_{x \in \mathcal{X}} \|y - vx\|^2, \quad (45)$$

where $v \in \mathbb{R}^{B \times d}$ is a matrix containing the B data vectors in its rows and $y \in \mathbb{R}^B$ is the vector containing the B associated label values or outputs. We let $B = 1000$ and randomly generated the entries of v from $\mathcal{N}(0, 1)$. We distributed the data points equally among $N = 10$ agents. For all $i \in [B]$, we generated the outputs y according to $y_i = v_i x^* + \xi_i$, where $\xi_i \sim \mathcal{N}(0, R^2)$ is the noise and v_i is the i 'th row of v .

We ran RANGE for 20k iterations $p_t = 0.1$ and $p_b = 0.025$ using four configurations of (m, α_1, α_2) . At each iteration, we picked the corrupt gradient as $2\|\nabla F(x_t)\|(x^* - x_t)/\|x^* - x_t\|$. In Figure 1, we plot the convergence behaviour of RANGE for all four configurations. When $m = 1$ and $\alpha_2 = 0.1$, we observe that the iterates diverge. Since $0.1 < p_b / (p_b + p_t) = 0.2$, the expected value of the fraction of Byzantine agents at each iteration is larger than α_2 , and hence the aggregate gradient estimate becomes corrupted most of the time. On the contrary, setting $\alpha_2 = 0.3$ or $\alpha_2 = 0.4$ provides robustness and RANGE converges. However, we observe that the configuration with $\alpha_2 = 0.3$ performs slightly better than the one with $\alpha_2 = 0.4$. This is because smaller α_2 aggregates more agents' gradients, which results in a larger variance reduction. All in all, while selecting a smaller α_2 provides variance reduction, it reduces the robustness of RANGE by including more agents at the robust aggregation step.

On the other hand, the configuration with $m = 100$, $\alpha_1 = 0.3$ and $\alpha_2 = 0.1$ outperforms the rest. When we utilize




Fig. 3: Training neural networks for image classification on the EMNIST dataset. Four distributed optimization algorithms are compared under $p_t = 0.2$ and $p_b = 0$ (left), $p_b = 0.015$ (middle), and $p_b = 0.15$ (right) using test accuracy of the trained network as metric. The legend is shared among all plots.

the robust temporal averaging step, it effectively reduces the expected value of the fraction of Byzantine agents at each iteration. Consequently, we can select a smaller α_2 in order to benefit from larger variance reduction while still being robust thanks to robust temporal averaging.

Next, we study the SA setting by re-sampling B new data points at each iteration. Keeping $p_t = 0.1$ constant, we simulate a high corruption rate with $p_b = 0.025$ and a low corruption rate with $p_b = 0.01$. We set $\alpha_1 = 0.3$ when $p_b = 0.025$ and $\alpha_1 = 0.1$ when $p_b = 0.01$. We fixed the window size $m = 100$ and $\alpha_2 = 0.1$ for both cases. In Figure 2 we plot the convergence behaviour of RANGE in the SA and the SAA settings for both corruption rates. We observe that when the corruption rate is low, RANGE performs better in the SA setting due to variance reduction provided by temporal averaging. However, when the corruption rate is high, RANGE performs worse in the SA setting as the damage caused by the Byzantine agents dominates.

B. Image Classification with EMNIST Dataset

In this study, we experiment with the image classification task on the EMNIST dataset [47] in the SAA setting. We train a feed-forward neural network with two hidden layers and 64 neurons at each hidden layer. We partition the data into $N = 200$ equal sizes, representing the data at N agents. The batch size for gradient computation is set to $b = 300$.

We train the neural network using (a) RANGE, (b) vanilla SGD, (c) median aggregation [26], and (d) norm clipping [36]. We note that although the median aggregation method in [26] and the norm clipping method in [36] are developed for the setting with a bounded fraction of Byzantine agents, we implement them in the Markovian Byzantine agent setting because no existing work studies the same setup as ours. For transition probabilities $p_t = 0.2$ and $p_b \in \{0, 0.05, 0.15\}$, we train three networks with learning rates 0.1, 0.01, and 0.001, and pick the best-performing one. We let $m = 50$, $\alpha_1 = 0.25$, $\alpha_2 = 0.2$ for RANGE when $p_b = 0$ and $p_b = 0.05$; $m = 50$, $\alpha_1 = 0.45$, $\alpha_2 = 0.3$ when $p_b = 0.15$. We set the threshold for norm clipping to be 10 as it is shown to perform well in [36]. We simulate corruption by simply inverting and boosting the magnitude of the gradient, i.e., by setting $\star = -c\nabla F_{i,t}(x_t)$ in (3), where c is sampled uniformly from [5, 15] at each iteration.

In Figure 3 we plot the test accuracy of the models during training. For $p_b = 0$, all algorithms successfully train the

neural network as expected. For $p_b = 0.05$, vanilla SGD has negligible performance as it is not robust to corruption. On the other hand, norm clipping and median aggregation methods have satisfactory performance. Nonetheless, RANGE outperforms norm clipping and median aggregation algorithms by margins of 3.7% and 6.3%, respectively. For $p_b = 0.15$, we observe that the median aggregation method also fails. The median is no longer robust since it is corrupted if more than half of the agents become Byzantine at any iteration, which frequently happens when $p_b/(p_b + p_t)$ is high. Norm clipping is still robust, however, RANGE beats it by a margin of 8.3%.

VIII. CONCLUSIONS AND FUTURE WORK

We introduced a distributed optimization algorithm, named RANGE, that is provably robust to Byzantine failures. By modeling each agent’s state transition trajectory over time, namely from trustworthy to Byzantine and vice versa, as a two-state Markov chain, we allow all the agents to be prone to failure. RANGE is based on three ideas: 1) temporal gradient averaging, which computes a robustified gradient for each agent by estimating a robust mean of a window of past gradients, 2) robust aggregation, which computes a robust mean of all the agents’ robustified gradients to estimate the aggregate gradient, and 3) gradient normalization, which restricts the aggregate gradient to only contain directional information and therefore prevents arbitrarily large updates that corrupt gradients might cause. We prove that for strongly convex and smooth non-convex cost functions RANGE achieves order-optimal statistical error rates with order-optimal convergence rates. Numerical experiments on linear regression and image classification on EMNIST dataset demonstrate the robustness and efficacy of RANGE.

Future work should study accelerated formulations of RANGE. As shown in [33] momentum-based approaches accelerate normalized SGD. Whether RANGE benefits from momentum terms while maintaining its robustness properties is an open question. Additionally, future work should study the robustness properties of statistically preconditioning approaches for large-scale distributed optimization methods [48]–[50].

REFERENCES

- [1] C.-K. Yu, M. Van Der Schaar, and A. H. Sayed, “Distributed learning for stochastic generalized nash equilibrium problems,” *IEEE Transactions on Signal Processing*, vol. 65, no. 15, pp. 3893–3908, 2017.

- [2] T. Yang, X. Yi, J. Wu, Y. Yuan, D. Wu, Z. Meng, Y. Hong, H. Wang, Z. Lin, and K. H. Johansson, "A survey of distributed optimization," *Annual Reviews in Control*, vol. 47, pp. 278–305, 2019.
- [3] P. Mertikopoulos, E. V. Belmega, R. Negrel, and L. Sanguinetti, "Distributed stochastic optimization via matrix exponential learning," *IEEE Transactions on Signal Processing*, vol. 65, no. 9, pp. 2277–2290, 2017.
- [4] C. Tekin and M. Van Der Schaar, "Distributed online learning via cooperative contextual bandits," *IEEE transactions on signal processing*, vol. 63, no. 14, pp. 3700–3714, 2015.
- [5] S. Chouvardas, G. Mileounis, N. Kalouptsidis, and S. Theodoridis, "Greedy sparsity-promoting algorithms for distributed learning," *IEEE Transactions on Signal Processing*, vol. 63, no. 6, pp. 1419–1432, 2015.
- [6] S. Marano, V. Matta, and P. Willett, "Nearest-neighbor distributed learning by ordered transmissions," *IEEE Transactions on signal processing*, vol. 61, no. 21, pp. 5217–5230, 2013.
- [7] B. Swenson, S. Kar, and J. Xavier, "Empirical centroid fictitious play: An approach for distributed learning in multi-agent games," *IEEE Transactions on Signal Processing*, vol. 63, no. 15, pp. 3888–3901, 2015.
- [8] Y. Chen, S. Kar, and J. M. Moura, "The internet of things: Secure distributed inference," *IEEE Signal Processing Magazine*, vol. 35, no. 5, pp. 64–75, 2018.
- [9] J. Konečný, H. B. McMahan, F. X. Yu, P. Richtárik, A. T. Suresh, and D. Bacon, "Federated learning: Strategies for improving communication efficiency," *arXiv preprint arXiv:1610.05492*, 2016.
- [10] A. Vempaty, L. Tong, and P. K. Varshney, "Distributed inference with byzantine data: State-of-the-art review on data falsification attacks," *IEEE Signal Processing Magazine*, vol. 30, no. 5, pp. 65–75, 2013.
- [11] P. Kairouz, H. B. McMahan, B. Avent, A. Bellet, M. Bennis, A. N. Bhagoji, K. Bonawitz, Z. Charles, G. Cormode, R. Cummings *et al.*, "Advances and open problems in federated learning," *arXiv preprint arXiv:1912.04977*, 2019.
- [12] Z. Yang, A. Gang, and W. U. Bajwa, "Adversary-resilient distributed and decentralized statistical inference and machine learning: An overview of recent advances under the byzantine threat model," *IEEE Signal Processing Magazine*, vol. 37, no. 3, pp. 146–159, 2020.
- [13] V. Mnih and G. E. Hinton, "Learning to label aerial images from noisy data," in *Proceedings of the 29th International conference on machine learning (ICML-12)*, 2012, pp. 567–574.
- [14] F. Tramer and D. Boneh, "Adversarial training and robustness for multiple perturbations," *arXiv preprint arXiv:1904.13000*, 2019.
- [15] D. Alistarh, D. Grubic, J. Li, R. Tomioka, and M. Vojnovic, "Qsgd: Communication-efficient sgd via gradient quantization and encoding," *arXiv preprint arXiv:1610.02132*, 2016.
- [16] F. S. Stonyakin, D. Dvinskikh, P. Dvurechensky, A. Kroshnin, O. Kuznetsova, A. Agafonov, A. Gasnikov, A. Tyurin, C. A. Uribe, D. Pasechnyuk, and S. Artamonov, "Gradient methods for problems with inexact model of the objective," in *Mathematical Optimization Theory and Operations Research*, M. Khachay, Y. Kochetov, and P. Pardalos, Eds. Cham: Springer International Publishing, 2019, pp. 97–114.
- [17] N. Natarajan, I. S. Dhillon, P. Ravikumar, and A. Tewari, "Learning with noisy labels," in *NIPS*, vol. 26, 2013, pp. 1196–1204.
- [18] J. Steinhardt, P. W. Koh, and P. Liang, "Certified defenses for data poisoning attacks," in *Proceedings of the 31st International Conference on Neural Information Processing Systems*, ser. NIPS'17. Red Hook, NY, USA: Curran Associates Inc., 2017, p. 3520–3532.
- [19] Z. Wu, Q. Ling, T. Chen, and G. B. Giannakis, "Federated variance-reduced stochastic gradient descent with robustness to byzantine attacks," *IEEE Transactions on Signal Processing*, vol. 68, pp. 4583–4596, 2020.
- [20] E. Bagdasaryan, A. Veit, Y. Hua, D. Estrin, and V. Shmatikov, "How to backdoor federated learning," in *International Conference on Artificial Intelligence and Statistics*. PMLR, 2020, pp. 2938–2948.
- [21] Y. Chen, L. Su, and J. Xu, "Distributed statistical machine learning in adversarial settings: Byzantine gradient descent," *Proceedings of the ACM on Measurement and Analysis of Computing Systems*, vol. 1, no. 2, pp. 1–25, 2017.
- [22] L. Chen, H. Wang, Z. Charles, and D. Papailiopoulos, "Draco: Byzantine-resilient distributed training via redundant gradients," in *International Conference on Machine Learning*. PMLR, 2018, pp. 903–912.
- [23] X. Cao and L. Lai, "Distributed approximate newton's method robust to byzantine attackers," *IEEE Transactions on Signal Processing*, vol. 68, pp. 6011–6025, 2020.
- [24] P. Blanchard, E. M. El Mhamdi, R. Guerraoui, and J. Stainer, "Machine learning with adversaries: Byzantine tolerant gradient descent," in *Proceedings of the 31st International Conference on Neural Information Processing Systems*, 2017, pp. 118–128.
- [25] D. Yin, Y. Chen, R. Kannan, and P. Bartlett, "Defending against saddle point attack in byzantine-robust distributed learning," in *International Conference on Machine Learning*. PMLR, 2019, pp. 7074–7084.
- [26] D. Yin, Y. Chen, R. Kannan, and P. Bartlett, "Byzantine-robust distributed learning: Towards optimal statistical rates," in *International Conference on Machine Learning*. PMLR, 2018, pp. 5650–5659.
- [27] Z. Yang and W. U. Bajwa, "Byrdie: Byzantine-resilient distributed coordinate descent for decentralized learning," *IEEE Transactions on Signal and Information Processing over Networks*, vol. 5, no. 4, pp. 611–627, 2019.
- [28] H. Wang, K. Sreenivasan, S. Rajput, H. Vishwakarma, S. Agarwal, J.-y. Sohn, K. Lee, and D. Papailiopoulos, "Attack of the tails: Yes, you really can backdoor federated learning," *arXiv preprint arXiv:2007.05084*, 2020.
- [29] Y. Nesterov, *Introductory Lectures on Convex Optimization*. Springer Science & Business Media, 2004, vol. 87.
- [30] E. Hazan, K. Levy, and S. Shalev-Shwartz, "Beyond convexity: Stochastic quasi-convex optimization," in *Advances in Neural Information Processing Systems*, 2015, pp. 1594–1602.
- [31] Y. You, I. Gitman, and B. Ginsburg, "Large batch training of convolutional networks," *arXiv preprint arXiv:1708.03888*, 2017.
- [32] K. Y. Levy, "The power of normalization: Faster evasion of saddle points," *arXiv preprint arXiv:1611.04831*, 2016.
- [33] A. Cutkosky and H. Mehta, "Momentum improves normalized sgd," in *International Conference on Machine Learning*. PMLR, 2020, pp. 2260–2268.
- [34] B. Turan, C. A. Uribe, H.-T. Wai, and M. Alizadeh, "On robustness of the normalized subgradient method with randomly corrupted subgradients," *arXiv preprint arXiv:2009.13725*, 2020.
- [35] M. Abadi, A. Chu, I. Goodfellow, H. B. McMahan, I. Mironov, K. Talwar, and L. Zhang, "Deep learning with differential privacy," in *Proceedings of the 2016 ACM SIGSAC conference on computer and communications security*, 2016, pp. 308–318.
- [36] Z. Sun, P. Kairouz, A. T. Suresh, and H. B. McMahan, "Can you really backdoor federated learning?" *arXiv preprint arXiv:1911.07963*, 2019.
- [37] A. K. Menon, A. S. Rawat, S. J. Reddi, and S. Kumar, "Can gradient clipping mitigate label noise?" 2020.
- [38] A. Nedić, D. P. Bertsekas, and V. S. Borkar, "Distributed asynchronous incremental subgradient methods," *Studies in Computational Mathematics*, vol. 8, no. C, pp. 381–407, 2001.
- [39] M. Gurbuzbalaban, A. Ozdaglar, and P. A. Parrilo, "On the convergence rate of incremental aggregated gradient algorithms," *SIAM Journal on Optimization*, vol. 27, no. 2, pp. 1035–1048, 2017.
- [40] A. Agarwal and J. C. Duchi, "Distributed delayed stochastic optimization," in *2012 IEEE 51st IEEE Conference on Decision and Control (CDC)*. IEEE, 2012, pp. 5451–5452.
- [41] A. J. Kleywegt, A. Shapiro, and T. Homem-de Mello, "The sample average approximation method for stochastic discrete optimization," *SIAM Journal on Optimization*, vol. 12, no. 2, pp. 479–502, 2002.
- [42] M. T. Wasan, *Stochastic approximation*. Cambridge University Press, 2004, no. 58.
- [43] S. Kim, R. Pasupathy, and S. G. Henderson, "A guide to sample average approximation," *Handbook of simulation optimization*, pp. 207–243, 2015.
- [44] B. Turan, C. A. Uribe, H.-T. Wai, and M. Alizadeh, "Resilient primal-dual optimization algorithms for distributed resource allocation," *IEEE Transactions on Control of Network Systems*, vol. 8, no. 1, pp. 282–294, 2021.
- [45] P. Lezaud, "Chernoff-type bound for finite markov chains," *Annals of Applied Probability*, pp. 849–867, 1998.
- [46] D. A. Levin and Y. Peres, *Markov chains and mixing times*. American Mathematical Soc., 2017, vol. 107.
- [47] G. Cohen, S. Afshar, J. Tapson, and A. Van Schaik, "Emnist: Extending mnist to handwritten letters," in *2017 International Joint Conference on Neural Networks (IJCNN)*. IEEE, 2017, pp. 2921–2926.
- [48] H. Hendrikx, L. Xiao, S. Bubeck, F. Bach, and L. Massoulié, "Statistically preconditioned accelerated gradient method for distributed optimization," in *International Conference on Machine Learning*. PMLR, 2020, pp. 4203–4227.
- [49] X.-T. Yuan and P. Li, "On convergence of distributed approximate newton methods: Globalization, sharper bounds and beyond," *Journal of Machine Learning Research*, vol. 21, no. 206, pp. 1–51, 2020.
- [50] P. Dvurechensky, D. Kamzolov, A. Lukashevich, S. Lee, E. Orndtlich, C. A. Uribe, and A. Gasnikov, "Hyperfast second-order local solvers for efficient statistically preconditioned distributed optimization," *arXiv preprint arXiv:2102.08246*, 2021.

- [51] S. Boucheron, G. Lugosi, and P. Massart, *Concentration inequalities: A nonasymptotic theory of independence*. Oxford university press, 2013.
- [52] H. J. Helgert, "On sums of random variables defined on a two-state markov chain," *Journal of Applied Probability*, vol. 7, no. 3, pp. 761–765, 1970.

APPENDIX

A. Proof of Lemma 1

The goal is to find a uniform bound on $\mathbb{E}[Z_t | \mathcal{S}_{t-m+1-m_0}]$ independent of the system state at $t-m+1-m_0$. Note that

$$\mathbb{E}[Z_t | \mathcal{S}_{t-m+1-m_0}] = \mathbb{P}(Z_t = 1 | \mathcal{S}_{t-m+1-m_0}) \quad (46)$$

$$= \mathbb{P}\left(\frac{1}{N} \sum_{i \in [N]} Y_{i,t} > \alpha_2 | \mathcal{S}_{t-m+1-m_0}\right) \quad (47)$$

$$\leq \sum_{k=\alpha_2 N+1}^N \binom{N}{k} (P_Y^m(m_0))^k (1 - P_Y^m(m_0))^{(N-k)}, \quad (48)$$

where

$$P_Y^m(m_0) = P_Y^m(m_0, m, \alpha_1, M) = \max_{i \in [N], t} \mathbb{E}[Y_{i,t} | \mathcal{S}_{t-m+1-m_0}] \quad (49)$$

$$= \max_{i \in [N], t} \mathbb{P}[Y_{i,t} = 1 | \mathcal{S}_{t-m+1-m_0}] \quad (50)$$

$$= \max_{i \in [N], t} \mathbb{P}\left(\frac{1}{m} \sum_{\tau=t-m+1}^t W_{i,\tau} > \alpha_1 | \mathcal{S}_{t-m+1-m_0}\right) \quad (51)$$

We now upper bound $P_Y^m(m_0)$ using the following Theorem in [45], which establishes a Chernoff's bound for ergodic Markov processes:

Theorem 5. [45, Theorem 1.1] *Let (P, π) be an irreducible and reversible markov chain on a finite set G . Let $f : G \rightarrow \mathbb{R}$ be such that $\pi f = 0$, $\|f\|_\infty \leq 1$ and $0 < \|f\|^2 \leq 1$. Then, for any initial distribution q , any positive intereger n and all $0 < \gamma \leq 1$,*

$$\mathbb{P}_q\left(\sum_{i=1}^n f(X_i) \geq \gamma n\right) \leq e^{\epsilon(P)/5} N_q \exp\left(-\frac{n\gamma^2 \epsilon(P)}{12}\right), \quad (52)$$

where $N_q = \|q/\pi\|_2$ and $\epsilon(P) = 1 - \lambda_1(P)$, where $\lambda_1(P)$ is the second largest eigenvalue of P .

We let q to be the distribution at time $t-m+1$ given $\mathcal{S}_{t-m+1-m_0}$, denoted as $\pi_{t-m+1|t-m+1-m_0}^i$, let $f(W_{i,\tau}) = W_{i,\tau} - \frac{p_b}{p_b+p_t}$, and have $\lambda_1(M) = 1 - p_b - p_t$. All in all, we have the following bound:

$$P_Y^m(m_0) \leq \max_{i \in [N], t} K_{i,t} e^{\frac{p_b+p_t}{5}} \exp\left(\frac{-(p_b+p_t)m(\alpha_1 - \frac{p_b}{p_b+p_t})^2}{12}\right), \quad (53)$$

where $K_{i,t} = \|\pi_{t-m+1|t-m+1-m_0}^i / \pi^*\|_2$, i.e., the $L^2(\pi)$ -density of $\pi_{t-m+1|t-m+1-m_0}^i$ relative to the stationary distribution π^* . It can be computed as:

$$K_{i,t}^2 = \frac{(\pi_{t-m+1|t-m+1-m_0}^i(0))^2}{\pi^*(0)} + \frac{(\pi_{t-m+1|t-m+1-m_0}^i(1))^2}{\pi^*(1)} \quad (54)$$

$$= 1 + \frac{(1-p_b-p_t)^{2m_0} (\pi_{t-m+1-m_0}^i(0) p_b - \pi_{t-m+1-m_0}^i(1) p_t)^2}{p_b p_t} \quad (55)$$

$$\leq 1 + (1-p_b-p_t)^{2m_0} \frac{p_t}{p_b}, \quad \forall i \in [N], \quad (56)$$

where the last inequality holds with equality if $\pi_{t-m+1-m_0}^i(1) = 1$, i.e., at time $t-m+1-m_0$ the agent was corrupted, which is the worst-case intuition. Plugging (56) into (53) gives the desired result.

B. Proof of Theorem 1

The proof will use the following theorem in [51] as an auxiliary result, which offers a convenient bound for the expected value of the maximum of finitely many exponentially integrable random variables.

Theorem 6. [51, Theorem 2.5] *Let Z_1, \dots, Z_N be real-valued random variables such that for every $\lambda \in (0, a)$ and $i = 1, \dots, N$, the logarithm of the moment generating function of Z_i satisfies $\mathbb{E}[e^{\lambda Z_i}] \leq \phi(\lambda)$ where ϕ is a convex and continuously differentiable function on $[0, a)$ with $0 < a \leq \infty$ such that $\phi(0) = \phi'(0) = 0$. Then*

$$\mathbb{E}[\max_{i=1, \dots, N} Z_i] \leq \inf_{\lambda \in (0, a)} \left[\frac{\log N + \phi(\lambda)}{\lambda} \right]. \quad (57)$$

Using the update rule, we write

$$\|x_{t+1} - x^*\|^2 = \|\Pi_{\mathcal{X}}\{x_t - \gamma \hat{g}_t / \|\hat{g}_t\|\} - x^*\|^2 \quad (58)$$

$$\leq \|x_t - x^* - \gamma \hat{g}_t / \|\hat{g}_t\|\|^2 \quad (59)$$

$$= \|x_t - x^*\|^2 - 2\gamma \langle \hat{g}_t / \|\hat{g}_t\|, x_t - x^* \rangle + \gamma^2 \quad (60)$$

$$= \|x_t - x^*\|^2 - 2\gamma(1 - Z_t) \left\langle \frac{\hat{g}_t^{Z_t=0}}{\|\hat{g}_t^{Z_t=0}\|}, x_t - x^* \right\rangle \quad (61)$$

$$- 2\gamma Z_t \left\langle \frac{\hat{g}_t^{Z_t=1}}{\|\hat{g}_t^{Z_t=1}\|}, x_t - x^* \right\rangle + \gamma^2$$

$$\leq \|x_t - x^*\|^2 - 2\gamma(1 - Z_t) \left\langle \frac{\nabla F(x_t)}{\|\nabla F(x_t)\|}, x_t - x^* \right\rangle$$

$$- 2\gamma(1 - Z_t) \left\langle \frac{\hat{g}_t^{Z_t=0}}{\|\hat{g}_t^{Z_t=0}\|} - \frac{\nabla F(x_t)}{\|\nabla F(x_t)\|}, x_t - x^* \right\rangle \quad (62)$$

$$+ 2\gamma Z_t \|x_t - x^*\| + \gamma^2$$

$$\leq \|x_t - x^*\|^2 - 2\gamma(1 - Z_t) \frac{\mu}{L} \|x_t - x^*\|$$

$$- 2\gamma(1 - Z_t) \left\langle \frac{\hat{g}_t^{Z_t=0}}{\|\hat{g}_t^{Z_t=0}\|} - \frac{\nabla F(x_t)}{\|\nabla F(x_t)\|}, x_t - x^* \right\rangle \quad (63)$$

$$+ 2\gamma Z_t \|x_t - x^*\| + \gamma^2$$

$$\leq \|x_t - x^*\|^2 - \frac{2\gamma}{\kappa} (1 - Z_t (1 + \kappa)) \|x_t - x^*\| \quad (64)$$

$$+ 2\gamma \|e_t\| \|x_t - x^*\| + \gamma^2,$$

where

$$e_t = \frac{\nabla F(x_t)}{\|\nabla F(x_t)\|} - \frac{\hat{g}_t^{Z_t=0}}{\|\hat{g}_t^{Z_t=0}\|} \quad (65)$$

In case of the event $Z_t = 0$, we know that there are at least $(1 - \alpha_2)N$ agents for which $Y_{i,t} = 0$. Therefore, we define the following sets:

• Define \mathcal{T}^t as the set of $(1 - \alpha_2)N$ agents with smallest indices $i \in [N]$ for which $Y_{i,t} = 0$, i.e.,

$$\mathcal{T}^t = \{i | i \in [N], Y_{i,t} = 0, \sum_i 1 = (1 - \alpha_2)N\} \quad (66)$$

such that $\sum_{i \in \mathcal{T}^t} i$ is minimized.

- For all agents $i \in \mathcal{T}^t$, define \mathcal{T}_i^t as the set of $(1 - \alpha_1)m$ smallest time indices $\tau \in [t - m + 1, t]$ for which $W_{i,\tau} = 0$, i.e.,

$$\mathcal{T}_i^t = \{\tau | \tau \in [t - m + 1, t], W_{i,\tau} = 0, \sum_{\tau \in \mathcal{T}_i^t} 1 = (1 - \alpha_1)m\} \quad (67)$$

such that $\sum_{\tau \in \mathcal{T}_i^t} \tau$ is minimized.

Using the above sets, the following Lemma, whose proof can be found in Appendix F, bounds the norm of e_t :

Lemma 2. *Suppose that $F(\cdot)$ and $F_{i,\tau}(\cdot)$, $\forall i, \tau$, are L -smooth. Define $\hat{g}_t^{Z_t=0}$ as the robustified gradient at iteration t when $Z_t = 0$. Define the error e_t as*

$$e_t = \frac{\nabla F(x_t)}{\|\nabla F(x_t)\|} - \frac{\hat{g}_t^{Z_t=0}}{\|\hat{g}_t^{Z_t=0}\|}$$

Then for all $t \geq m$, the following bounds the norm of the error:

$$\begin{aligned} \|e_t\| &\leq \frac{2}{\|\nabla F(x_t)\|} \left(L\gamma(m-1)(1+C_{\alpha_1}+2C_{\alpha_2}(C_{\alpha_1}+1)) \right. \\ &+ \left\| \nabla F(x_t) - \frac{1}{(1-\alpha_1)m(1-\alpha_2)N} \sum_{i \in \mathcal{T}^t} \sum_{\tau \in \mathcal{T}_i^t} \nabla F_{i,\tau}(x_t) \right\| \\ &+ 2C_{\alpha_2} \max_{i \in \mathcal{T}^t} \left\| \frac{1}{(1-\alpha_1)m} \sum_{\tau \in \mathcal{T}_i^t} \nabla F_{i,\tau}(x_t) - \nabla F(x_t) \right\|_{\infty} \\ &+ \frac{1}{(1-\alpha_2)N} \sum_{i \in \mathcal{T}^t} \max_{\tau, \tau' \in \mathcal{T}_i^t} C_{\alpha_1} \|\nabla F_{i,\tau}(x_{\tau'}) - \nabla F_{i,\tau'}(x_{\tau'})\|_{\infty} \\ &+ 2C_{\alpha_2} C_{\alpha_1} \max_{i \in \mathcal{T}^t, \tau, \tau' \in \mathcal{T}_i^t} \|\nabla F_{i,\tau}(x_{\tau'}) - \nabla F_{i,\tau'}(x_{\tau'})\|_{\infty} \left. \right) \end{aligned} \quad (68)$$

We plug (68) into (64) and take expectation of both sides with respect to $z \sim \mathcal{D}$ noting that $\nabla F_{i,\tau}(x_t) = \nabla F_{i,\tau'}(x_t)$, $\forall t, \tau, \tau'$ for the SAA, and use μ -strong convexity of $F(\cdot)$:

$$\begin{aligned} \mathbb{E}_{z \sim \mathcal{D}} [\|x_{t+1} - x^*\|^2] &\leq \mathbb{E}_{z \sim \mathcal{D}} [\|x_t - x^*\|^2] + \gamma^2 \\ &- \frac{2\gamma}{\kappa} (1 - Z_t(1 + \kappa)) \mathbb{E}_{z \sim \mathcal{D}} [\|x_t - x^*\|] \\ &+ \frac{4\gamma^2 L(m-1)(1+C_{\alpha_1}+2C_{\alpha_2}(C_{\alpha_1}+1))}{\mu} \\ &+ \frac{4\gamma\sigma}{\mu\sqrt{(1-\alpha_2)Nb}} \\ &+ \frac{8\gamma C_{\alpha_2}}{\mu} \mathbb{E}_{z \sim \mathcal{D}} [\max_{i \in \mathcal{T}^t} \|\nabla F_{i,t}(x_t) - \nabla F(x_t)\|_{\infty}] \\ &\leq \mathbb{E}_{z \sim \mathcal{D}} [\|x_t - x^*\|^2] + \gamma^2 \\ &- \frac{2\gamma}{\kappa} (1 - Z_t(1 + \kappa)) \mathbb{E}_{z \sim \mathcal{D}} [\|x_t - x^*\|] \\ &+ \frac{4\gamma^2 L(m-1)(1+C_{\alpha_1}+2C_{\alpha_2}(C_{\alpha_1}+1))}{\mu} \\ &+ \frac{4\gamma\sigma}{\mu\sqrt{(1-\alpha_2)Nb}} \\ &+ \frac{8\gamma C_{\alpha_2}}{\mu} \inf_{\lambda \in (0, b/a)} \left[\frac{\log(2(1-\alpha_2)Nd) + b\phi(\lambda/b)}{\lambda} \right], \end{aligned} \quad (70)$$

where the second inequality uses Assumption 1 and Theorem 6 with

$$\begin{aligned} &\mathbb{E}_{z \sim \mathcal{D}} [\max_{i \in \mathcal{T}^t} \|\nabla F_{i,t}(x_t) - \nabla F(x_t)\|_{\infty}] \\ &= \mathbb{E}_{z \sim \mathcal{D}} [\max_{i \in \mathcal{T}^t, k \in [d]} |\nabla F_{i,t}(x_t) - \nabla F(x_t)|_k] \end{aligned} \quad (71)$$

$$= \mathbb{E}_{z \sim \mathcal{D}} [\max_{i \in \mathcal{T}^t, k \in [d]} \{|\nabla F_{i,t}(x_t) - \nabla F(x_t)|_k, |\nabla F(x_t) - \nabla F_{i,t}(x_t)|_k\}] \quad (72)$$

and

$$\mathbb{E}_{z \sim \mathcal{D}} [e^{\lambda|\nabla F_{i,t}(x_t) - \nabla F(x_t)|_k}] \leq b\phi(\lambda/b), \quad (73)$$

$\forall x_t \in \mathcal{X}, k \in [d], |\lambda| \leq b/a$, with $\phi(\lambda) = \frac{\lambda^2 \sigma^2}{2(1-a|\lambda|)}$. Note that the maximization is taken over $2|\mathcal{T}^t|d = 2(1-\alpha_2)Nd$ sub-gamma random variables. The $\inf_{\lambda \in (0, b/a)} [\cdot]$ term attains its minimum at

$$\lambda^* = \frac{2\sqrt{\log(2(1-\alpha_2)Nd)}}{2a\sqrt{\log(2(1-\alpha_2)Nd)/b} + \sqrt{2\sigma^2/b}} \quad (74)$$

and the expression evaluated at λ^* becomes

$$\begin{aligned} &\left[\frac{\log(2(1-\alpha_2)Nd) + b\phi(\lambda/b)}{\lambda} \right]_{\lambda=\lambda^*} \\ &= \frac{a}{b} \log(2(1-\alpha_2)Nd) + \frac{\sigma\sqrt{2\log(2(1-\alpha_2)Nd)}}{\sqrt{b}} \end{aligned} \quad (75)$$

Next step is to take expectation of (70) with respect to all randomness, where the challenge is to compute $\mathbb{E}[Z_t \|x_t - x^*\|]$. However, Z_t is a random variable that depends on $\{Y_{i,t}\}_{i \in [N]}$, and $Y_{i,t}$ is a random variable which depends on $\{W_{i,\tau}\}_{\tau \in [t-m+1, t]}$. All in all, Z_t is a random variable which depends on the agents' state at time $t - m + 1$ (which also not independent of history). Since x_t is also dependent on the agents' state at time $t - m + 1$, Z_t and x_t are dependent random variables. Therefore, we can not directly compute $\mathbb{E}[Z_t \|x_t - x^*\|]$. But considering the fact that the two-state Markov chain governing the agents' states converges exponentially fast to its stationary distribution, the idea is to use total law of expectation by conditioning on the state at time $t - m + 1 - m_0$ for some $m_0 \geq 0$, i.e.,

$$\mathbb{E}[Z_t \|x_t - x^*\|] = \mathbb{E}[\mathbb{E}[Z_t \|x_t - x^*\| | \mathcal{S}_{t-m+1-m_0}], \quad (76)$$

where $\mathcal{S}_{t-m+1-m_0} = \{x_{t-m+1-m_0}, \{\pi_{i-m+1-m_0}^i\}_{i \in [N]}\}$ and $\pi_{i-m+1-m_0}^i$ is the distribution of the state of agent i at time $t - m + 1 - m_0$. Note that due to normalized updates:

$$\|x_t - x^*\| \leq \|x_{t-m+1-m_0} - x^*\| + \gamma(m-1+m_0), \quad (77)$$

and therefore (76) can be rewritten as

$$\begin{aligned} &\mathbb{E}[\mathbb{E}[Z_t \|x_t - x^*\| | \mathcal{S}_{t-m+1-m_0}]] \\ &\leq \mathbb{E}[\|x_{t-m+1-m_0} - x^*\| \mathbb{E}[Z_t | \mathcal{S}_{t-m+1-m_0}]] \\ &\quad + \mathbb{E}[\gamma(m-1+m_0) \mathbb{E}[Z_t | \mathcal{S}_{t-m+1-m_0}]]. \end{aligned} \quad (78)$$

We now use Lemma 1 (or Lemma 3 in Appendix G) to establish uniform bounds on $\mathbb{E}[Z_t | \mathcal{S}_{t-m+1-m_0}]$:

$$\mathbb{E}[\|x_t - x^*\| | Z_t] \leq \mathbb{E}[\|x_{t-m+1-m_0} - x^*\|] P_Z^m(m_0) + \gamma(m-1+m_0) P_Z^m(m_0) \quad (79)$$

$$\leq P_Z^m(m_0) (\mathbb{E}[\|x_t - x^*\|] + 2\gamma(m-1+m_0)), \quad (80)$$

where the last inequality follows from the normalized updates. Now we take expectation of (70) with respect to all randomness and use (80):

$$\begin{aligned} \mathbb{E}[\|x_{t+1} - x^*\|^2] &\leq \mathbb{E}[\|x_t - x^*\|^2] + \gamma^2 \\ &\quad - \frac{2\gamma}{\kappa}(1 - P_Z^m(m_0)(1 + \kappa))\mathbb{E}[\|x_t - x^*\|] \\ &\quad + 4\gamma^2 P_Z^m(m_0)(1 + 1/\kappa)(m - 1 + m_0) \\ &\quad + 4\gamma^2 \kappa(m - 1)(1 + C_{\alpha_1} + 2C_{\alpha_2}(C_{\alpha_1} + 1)) \\ &\quad + \frac{4\gamma\sigma}{\mu\sqrt{(1 - \alpha_2)Nb}} + \frac{8\gamma C_{\alpha_2} a}{\mu} \frac{1}{b} \log(2(1 - \alpha_2)Nd) \\ &\quad + \frac{8\gamma C_{\alpha_2} \sigma \sqrt{2 \log(2(1 - \alpha_2)Nd)}}{\mu \sqrt{b}}. \end{aligned} \quad (81)$$

Since $P_Z^m(m_0) < 1/(1 + \kappa)$, the coefficient of $\mathbb{E}[\|x_t - x^*\|]$ term is negative. Therefore, to upper bound the inequality, we lower bound $\mathbb{E}[\|x_t - x^*\|]$ as:

$$\mathbb{E}[\|x_t - x^*\|] = \mathbb{E}\left[\frac{\|x_t - x^*\|^2}{\|x_t - x^*\|}\right] \geq \frac{\mathbb{E}[\|x_t - x^*\|^2]}{R}. \quad (82)$$

Using above, we rewrite (81) for all $m_0 \in \mathbb{N}_0$ such that $P_Z^m(m_0) < 1/(1 + \kappa)$:

$$\begin{aligned} \mathbb{E}[\|x_{t+1} - x^*\|^2] &\leq \mathbb{E}[\|x_t - x^*\|^2] \left(1 - \frac{2\gamma}{\kappa R}(1 - P_Z^m(m_0)(1 + \kappa))\right) \\ &\quad + \gamma^2 \bar{C}(m_0) + \frac{4\gamma\sigma}{\mu\sqrt{(1 - \alpha_2)Nb}} \\ &\quad + \frac{8\gamma C_{\alpha_2} a}{\mu} \frac{1}{b} \log(2(1 - \alpha_2)Nd) \\ &\quad + \frac{8\gamma C_{\alpha_2} \sigma \sqrt{2 \log(2(1 - \alpha_2)Nd)}}{\mu \sqrt{b}}, \end{aligned} \quad (83)$$

where

$$\begin{aligned} \bar{C}(m_0) &= 1 + 4P_Z^m(m_0)(1 + 1/\kappa)(m - 1 + m_0) \\ &\quad + 4\kappa(m - 1)(1 + C_{\alpha_1} + 2C_{\alpha_2}(C_{\alpha_1} + 1)), \end{aligned} \quad (84)$$

$$c_0(m_0) = \frac{2}{\kappa R} (1 - P_Z^m(m_0)(1 + \kappa)). \quad (85)$$

Note that (83) holds for all $t \geq m + m_0$. Hence, we can write:

$$\begin{aligned} \mathbb{E}[\|x_{T+m+m_0} - x^*\|^2] &\leq \mathbb{E}[\|x_{m+m_0} - x^*\|^2] (1 - c_0(m_0)\gamma)^T \\ &\quad + \frac{4\gamma\sigma}{\mu\sqrt{(1 - \alpha_2)Nb}} \sum_{t=m+m_0}^{T+m+m_0-1} \prod_{i=t+1}^{T+m+m_0-1} (1 - c_0(m_0)\gamma) \\ &\quad + \frac{8\gamma C_{\alpha_2}}{\mu} \sum_{t=m+m_0}^{T+m+m_0-1} \prod_{i=t+1}^{T+m+m_0-1} (1 - c_0(m_0)\gamma) \times \\ &\quad \left(\frac{a}{b} \log(2(1 - \alpha_2)Nd) + \frac{\sigma \sqrt{2 \log(2(1 - \alpha_2)Nd)}}{\sqrt{b}}\right) \\ &\quad + \bar{C}(m_0)\gamma^2 \sum_{t=m+m_0}^{T+m+m_0-1} \prod_{i=t+1}^{T+m+m_0-1} (1 - c_0(m_0)\gamma) \end{aligned} \quad (86)$$

$$\begin{aligned} &= \mathbb{E}[\|x_{m+m_0} - x^*\|^2] (1 - c_0(m_0)\gamma)^T \\ &\quad + \frac{4\sigma}{\mu\sqrt{(1 - \alpha_2)Nb}} \frac{(1 - (1 - c_0(m_0)\gamma)^T)}{c_0(m_0)} \\ &\quad + \frac{8C_{\alpha_2} a}{\mu} \frac{1}{b} \log(2(1 - \alpha_2)Nd) \frac{(1 - (1 - c_0(m_0)\gamma)^T)}{c_0(m_0)} \\ &\quad + \frac{8C_{\alpha_2} \sigma \sqrt{2 \log(2(1 - \alpha_2)Nd)}}{\mu \sqrt{b}} \frac{(1 - (1 - c_0(m_0)\gamma)^T)}{c_0(m_0)} \\ &\quad + \bar{C}(m_0)\gamma \frac{(1 - (1 - c_0(m_0)\gamma)^T)}{c_0(m_0)}. \end{aligned} \quad (87)$$

Next, we observe that $(1 - (1 - c_0(m_0)\gamma)^T) \leq 1$ and $\|x_{m+m_0} - x^*\| \leq (\|x_1 - x^*\| + (m + m_0 - 1)\gamma)^2$ to get the desired result:

$$\begin{aligned} \mathbb{E}[\|x_{T+m+m_0} - x^*\|^2] &\leq \\ &\quad (\|x_1 - x^*\| + \gamma(m + m_0 - 1))^2 (1 - c_0(m_0)\gamma)^T \\ &\quad + \frac{4\sigma}{\mu\sqrt{(1 - \alpha_2)Nb}c_0(m_0)} + \frac{\bar{C}(m_0)\gamma}{c_0(m_0)} \\ &\quad + \frac{8aC_{\alpha_2} \log(2(1 - \alpha_2)Nd)}{\mu c_0(m_0)b} + \frac{8C_{\alpha_2} \sigma \sqrt{2 \log(2(1 - \alpha_2)Nd)}}{\mu c_0(m_0)\sqrt{b}}. \end{aligned} \quad (88)$$

C. Proof of Theorem 2

Due to Assumption 4, the iterates generated by the algorithm stay in \mathcal{X} without projection. Hence, we proceed to analyze the convergence of the algorithm without projection.

Since $f(\cdot, z)$ is L -smooth, $F(\cdot)$ is L -smooth:

$$F(x_{t+1}) - F(x_t) \leq \langle \nabla F(x_t), x_{t+1} - x_t \rangle + \frac{L}{2} \|x_{t+1} - x_t\|^2 \quad (89)$$

$$\leq -\gamma \langle \nabla F(x_t), \frac{\hat{g}_t}{\|\hat{g}_t\|} \rangle + \frac{L\gamma^2}{2} \quad (90)$$

$$= -\gamma(1 - Z_t) \langle \nabla F(x_t), \frac{\hat{g}_t^{Z_t=0}}{\|\hat{g}_t^{Z_t=0}\|} \rangle \quad (91)$$

$$- \gamma Z_t \langle \nabla F(x_t), \frac{\hat{g}_t^{Z_t=1}}{\|\hat{g}_t^{Z_t=1}\|} \rangle + \frac{L\gamma^2}{2}$$

$$= -\gamma(1 - Z_t) \langle \nabla F(x_t), \frac{\nabla F(x_t)}{\|\nabla F(x_t)\|} \rangle \quad (92)$$

$$+ \gamma(1 - Z_t) \langle \nabla F(x_t), \frac{\nabla F(x_t)}{\|\nabla F(x_t)\|} - \frac{\hat{g}_t^{Z_t=0}}{\|\hat{g}_t^{Z_t=0}\|} \rangle$$

$$- \gamma Z_t \langle \nabla F(x_t), \frac{\hat{g}_t^{Z_t=1}}{\|\hat{g}_t^{Z_t=1}\|} \rangle + \frac{L\gamma^2}{2}$$

$$\leq -\gamma(1 - 2Z_t) \|\nabla F(x_t)\| + \gamma(1 - Z_t) \|\nabla F(x_t)\| \|e_t\| + \frac{L\gamma^2}{2}, \quad (93)$$

where

$$e_t = \frac{\nabla F(x_t)}{\|\nabla F(x_t)\|} - \frac{\hat{g}_t^{Z_t=0}}{\|\hat{g}_t^{Z_t=0}\|}. \quad (94)$$

Similar to Proof of Theorem 1 we define the following sets:

- Define \mathcal{T}^t as the set of $(1 - \alpha_2)N$ agents with smallest indices $i \in [N]$ for which $Y_{i,t} = 0$, i.e.,

$$\mathcal{T}^t = \{i \mid i \in [N], Y_{i,t} = 0, \sum_i 1 = (1 - \alpha_2)N\} \quad (95)$$

such that $\sum_{i \in \mathcal{T}^t} i$ is minimized.

- For all agents $i \in \mathcal{T}^t$, define \mathcal{T}_i^t as the set of $(1 - \alpha_1)m$ smallest time indices $\tau \in [t - m + 1, t]$ for which $W_{i,\tau} = 0$, i.e.,

$$\mathcal{T}_i^t = \{\tau \in [t - m + 1, t], W_{i,\tau} = 0, \sum_{\tau} 1 = (1 - \alpha_1)m\} \quad (96)$$

such that $\sum_{\tau \in \mathcal{T}_i^t} \tau$ is minimized.

We now use Lemma 2 to bound $\|e_t\|$ and take expectation of both sides with respect to $z \sim \mathcal{D}$ noting that $\nabla F_{i,\tau}(x_t) = \nabla F_{i,\tau'}(x_t)$, $\forall t, \tau, \tau'$:

$$\begin{aligned} \mathbb{E}_{z \sim \mathcal{D}} [F(x_{t+1}) - F(x_t)] &\leq -\gamma(1 - 2Z_t) \mathbb{E}_{z \sim \mathcal{D}} [\|\nabla F(x_t)\|] + \frac{L\gamma^2}{2} \\ &+ 2L\gamma^2(1 - Z_t)(m - 1)(1 + C_{\alpha_1} + 2C_{\alpha_2}(C_{\alpha_1} + 1)) \\ &+ 2\gamma(1 - Z_t) \mathbb{E}_{z \sim \mathcal{D}} \left\| \nabla F(x_t) - \frac{1}{(1 - \alpha_2)N} \sum_{i \in \mathcal{T}^t} \nabla F_{i,t}(x_t) \right\| \\ &+ 4\gamma(1 - Z_t)C_{\alpha_2} \mathbb{E}_{z \sim \mathcal{D}} [\max_{i \in \mathcal{T}^t} \|\nabla F_{i,t}(x_t) - \nabla F(x_t)\|_{\infty}] \quad (97) \end{aligned}$$

$$\begin{aligned} &\leq -\gamma(1 - 2Z_t) \mathbb{E}_{z \sim \mathcal{D}} [\|\nabla F(x_t)\|] + \frac{L\gamma^2}{2} \\ &+ 2L\gamma^2(m - 1)(1 + C_{\alpha_1} + 2C_{\alpha_2}(C_{\alpha_1} + 1)) \\ &+ 2\gamma \frac{\sigma}{\sqrt{(1 - \alpha_2)Nb}} \quad (98) \end{aligned}$$

$$\begin{aligned} &+ 4\gamma C_{\alpha_2} \inf_{\lambda \in (0, b/a)} \left[\frac{\log(2(1 - \alpha_2)Nd) + b\phi(\lambda/b)}{\lambda} \right] \\ &\leq -\gamma(1 - 2Z_t) \mathbb{E}_{z \sim \mathcal{D}} [\|\nabla F(x_t)\|] + \frac{L\gamma^2}{2} \\ &+ 2L\gamma^2(m - 1)(1 + C_{\alpha_1} + 2C_{\alpha_2}(C_{\alpha_1} + 1)) \\ &+ 2\gamma \frac{\sigma}{\sqrt{(1 - \alpha_2)Nb}} + 4\gamma C_{\alpha_2} \frac{a}{b} \log(2(1 - \alpha_2)Nd) \quad (99) \\ &+ 4\gamma C_{\alpha_2} \frac{\sigma \sqrt{2 \log((2(1 - \alpha_2)Nd)}}{\sqrt{b}}, \end{aligned}$$

where the last two inequalities follow from (71)-(75) in proof of Theorem 1.

Next step is to take expectation with respect to all randomness, where the challenge is to compute $\mathbb{E}[Z_t \|\nabla F(x_t)\|]$. Due to the same reasoning in proof of Theorem 1, x_t and Z_t are dependent random variables. Therefore, we use a similar trick and use total law of expectation by conditioning on the state at time $t - m + 1 - m_0$ for some $m_0 \geq 0$, i.e.,

$$\mathbb{E}[Z_t \|\nabla F(x_t)\|] = \mathbb{E}[\mathbb{E}[Z_t \|\nabla F(x_t)\| | \mathcal{S}_{t-m+1-m_0}], \quad (100)$$

where $\mathcal{S}_{t-m+1-m_0} = \{x_{t-m+1-m_0}, \{\pi_{t-m+1-m_0}^i\}_{i \in [N]}\}$ and $\pi_{t-m+1-m_0}^i$ is the distribution of the state of agent i at time $t - m + 1 - m_0$. Note that due to smoothness of $F(\cdot)$ and normalized updates:

$$\|\nabla F(x_t)\| \leq \|\nabla F(x_{t-m+1-m_0})\| + L\gamma(m - 1 + m_0), \quad (101)$$

and therefore (100) can be rewritten as

$$\begin{aligned} &\mathbb{E}[\mathbb{E}[Z_t \|\nabla F(x_t)\| | \mathcal{S}_{t-m+1-m_0}]] \\ &\leq \mathbb{E}[\|\nabla F(x_{t-m+1-m_0})\| \mathbb{E}[Z_t | \mathcal{S}_{t-m+1-m_0}]] \\ &\quad + \mathbb{E}[L\gamma(m - 1 + m_0) \mathbb{E}[Z_t | \mathcal{S}_{t-m+1-m_0}]] \quad (102) \end{aligned}$$

We now use Lemma 1 (or Lemma 3 in Appendix G) to establish uniform bounds on $\mathbb{E}[Z_t | \mathcal{S}_{t-m+1-m_0}]$:

$$\mathbb{E}[\|\nabla F(x_t)\| | Z_t] \leq \mathbb{E}[\|\nabla F(x_{t-m+1-m_0})\|] P_Z^m(m_0) + L\gamma(m - 1 + m_0) P_Z^m(m_0) \quad (103)$$

$$\leq P_Z^m(m_0) (\mathbb{E}[\|\nabla F(x_t)\|] + 2L\gamma(m - 1 + m_0)), \quad (104)$$

where the last inequality follows from smoothness of $F(\cdot)$ and normalized updates. Now we take expectation of (98) with respect to all randomness and use (104):

$$\begin{aligned} \mathbb{E}[F(x_{t+1}) - F(x_t)] &\leq -\gamma(1 - 2P_Z^m(m_0)) \mathbb{E}[\|\nabla F(x_t)\|] + \frac{L\gamma^2}{2} \\ &+ 4L\gamma^2 P_Z^m(m_0)(m - 1 + m_0) \\ &+ 2L\gamma^2(m - 1)(1 + C_{\alpha_1} + 2C_{\alpha_2}(C_{\alpha_1} + 1)) \\ &+ 2\gamma \frac{\sigma}{\sqrt{(1 - \alpha_2)Nb}} + 4\gamma C_{\alpha_2} \frac{a}{b} \log(2(1 - \alpha_2)Nd) \\ &+ 4\gamma C_{\alpha_2} \frac{\sigma \sqrt{2 \log((2(1 - \alpha_2)Nd)}}{\sqrt{b}} \quad (105) \end{aligned}$$

Noting that $F(x_t) \geq F(x^*)$ for all t , we rearrange the terms, sum from $t = m + m_0$ to $t = T + m + m_0 - 1$ to get the following result for all $m_0 \in \mathbb{N}_0$ for which $P_Z^m(m_0) < 1/2$:

$$\begin{aligned} \frac{1}{T} \sum_{t=m+m_0}^{T+m+m_0-1} \mathbb{E}[\|\nabla F(x_t)\|] &\leq \\ &\frac{\mathbb{E}[F(x_{m+m_0})] - F(x^*)}{\gamma T(1 - 2P_Z^m(m_0))} + \bar{C}(m_0)\gamma \\ &+ \frac{2\sigma}{(1 - 2P_Z^m(m_0))\sqrt{(1 - \alpha_2)Nb}} \\ &+ \frac{4C_{\alpha_2} a \log(2(1 - \alpha_2)Nd)}{(1 - 2P_Z^m(m_0))b} \\ &+ \frac{4C_{\alpha_2} \sigma \sqrt{2 \log((2(1 - \alpha_2)Nd)}}{(1 - 2P_Z^m(m_0))\sqrt{b}}, \quad (106) \end{aligned}$$

where

$$\begin{aligned} \bar{C}(m_0) &= L(0.5 + 4P_Z^m(m_0)(m - 1 + m_0) \\ &\quad + 2(m - 1)(1 + C_{\alpha_1} + 2C_{\alpha_2}(C_{\alpha_1} + 1))). \quad (107) \end{aligned}$$

Next, we upper bound $\mathbb{E}[F(x_{m+m_0})]$ using smoothness of F :

$$\begin{aligned} F(x_{m+m_0}) &\leq F(x_1) + \langle \nabla F(x_1), x_{m+m_0} - x_1 \rangle \\ &\quad + \frac{L}{2} \|x_{m+m_0} - x_1\|^2 \quad (108) \end{aligned}$$

$$\leq F(x_1) + \|\nabla F(x_1)\| \gamma(m + m_0 - 1) + \frac{L}{2} \gamma^2(m + m_0 - 1)^2. \quad (109)$$

Finally, we set $\gamma = \gamma_0/\sqrt{T}$ and plug the above inequality into (106) to get the final result:

$$\begin{aligned} \frac{1}{T} \sum_{t=m+m_0}^{T+m-1+m_0} \mathbb{E}[\|\nabla F(x_t)\|] &\leq \\ &\frac{F(x_1) - F(x^*)}{\sqrt{T}\gamma_0(1 - 2P_Z^m(m_0))} + \frac{\bar{C}(m_0)\gamma_0}{\sqrt{T}} \\ &+ \frac{\|\nabla F(x_1)\|(m - 1 + m_0)}{T(1 - 2P_Z^m(m_0))} + \frac{L\gamma_0(m - 1 + m_0)^2}{2T^{3/2}(1 - 2P_Z^m(m_0))} \\ &+ \frac{2\sigma}{(1 - 2P_Z^m(m_0))\sqrt{(1 - \alpha_2)Nb}} \\ &+ \frac{4C_{\alpha_2} a \log(2(1 - \alpha_2)Nd)}{(1 - 2P_Z^m(m_0))b} \\ &+ \frac{4C_{\alpha_2} \sigma \sqrt{2 \log((2(1 - \alpha_2)Nd)}}{(1 - 2P_Z^m(m_0))\sqrt{b}}, \quad (110) \end{aligned}$$

D. Proof of Theorem 3

The proof is identical to that of Theorem 1 until (64). Next, we plug (68) into (64) and take expectation of both sides with respect to $z \sim \mathcal{D}$, this time noting that $\nabla F_{i,\tau}(x_t)$ and $\nabla F_{i,\tau'}(x_t)$ are iid random variables $\forall t, \tau, \tau'$ such that $\tau \neq \tau'$ in the SA setting. This results in:

$$\begin{aligned}
& \mathbb{E}_{z \sim \mathcal{D}} [\|x_{t+1} - x^*\|^2] \leq \mathbb{E}_{z \sim \mathcal{D}} [\|x_t - x^*\|^2] + \gamma^2 \\
& - \frac{2\gamma}{\kappa} (1 - Z_t(1 + \kappa)) \mathbb{E}_{z \sim \mathcal{D}} [\|x_t - x^*\|] \\
& + \frac{4\gamma^2 L(m-1)(1 + C_{\alpha_1} + 2C_{\alpha_2}(C_{\alpha_1} + 1))}{\mu} \\
& + \frac{4\gamma\sigma}{\mu\sqrt{(1-\alpha_2)N(1-\alpha_1)mb}} \\
& + \frac{8\gamma C_{\alpha_2}}{\mu} \mathbb{E}_{z \sim \mathcal{D}} [\max_{i \in \mathcal{T}^t} \|\nabla F_{i,t}(x_t) - \nabla F(x_t)\|_{\infty}] \\
& + \frac{4\gamma C_{\alpha_1}}{\mu(1-\alpha_2)N} \sum_{i \in \mathcal{T}^t} 2 \mathbb{E}_{z \sim \mathcal{D}} [\max_{\tau, \tau' \in \mathcal{T}_i^t} \|\nabla F_{i,\tau}(x_{\tau'}) - \nabla F(x_{\tau'})\|_{\infty}] \\
& + \frac{8\gamma C_{\alpha_1} C_{\alpha_2}}{\mu} 2 \mathbb{E}_{z \sim \mathcal{D}} [\max_{i \in \mathcal{T}^t, \tau, \tau' \in \mathcal{T}_i^t} \|\nabla F_{i,\tau}(x_{\tau'}) - \nabla F(x_{\tau'})\|_{\infty}].
\end{aligned} \tag{111}$$

Next, we use Theorem 6 on the last three terms above, noting that the first maximization is over $2(1 - \alpha_2)Nd$ sub-gamma random variables, the second maximization is over $4(1 - \alpha_1)md$ sub-gamma random variables, and the last maximization is over $4(1 - \alpha_1)m(1 - \alpha_2)Nd$ sub-gamma random variables. The rest of the proof is identical to that of Theorem 1, resulting in:

$$\begin{aligned}
& \mathbb{E}[\|x_{T+m+m_0} - x^*\|^2] \leq \\
& (\|x_1 - x^*\| + \gamma(m + m_0 - 1))^2 (1 - c_0(m_0)\gamma)^T \\
& + \frac{4\sigma}{\mu\sqrt{(1-\alpha_2)N(1-\alpha_1)mb}c_0(m_0)} + \frac{\bar{C}(m_0)\gamma}{c_0(m_0)} \\
& + \frac{8aC_{\alpha_2} \log(2(1-\alpha_2)Nd)}{\mu c_0(m_0)b} \\
& + \frac{8C_{\alpha_2}\sigma\sqrt{2\log(2(1-\alpha_2)Nd)}}{\mu c_0(m_0)\sqrt{b}} \\
& + \frac{8aC_{\alpha_1} \log(4(1-\alpha_1)md)}{\mu c_0(m_0)b} \\
& + \frac{8C_{\alpha_1}\sigma\sqrt{2\log(4(1-\alpha_1)md)}}{\mu c_0(m_0)\sqrt{b}} \\
& + \frac{16aC_{\alpha_1}C_{\alpha_2} \log(4(1-\alpha_2)N(1-\alpha_1)md)}{\mu c_0(m_0)b} \\
& + \frac{16C_{\alpha_1}C_{\alpha_2}\sigma\sqrt{2\log(4(1-\alpha_2)N(1-\alpha_1)md)}}{\mu c_0(m_0)\sqrt{b}},
\end{aligned} \tag{112}$$

E. Proof of Theorem 4

The proof is identical to that of Theorem 2 until (93). Next, we plug (68) into (93) and take expectation of both sides with respect to $z \sim \mathcal{D}$, this time noting that $\nabla F_{i,\tau}(x_t)$ and $\nabla F_{i,\tau'}(x_t)$ are iid random variables $\forall t, \tau, \tau'$ such that $\tau \neq \tau'$ in the SA setting:

$$\begin{aligned}
& \mathbb{E}_{z \sim \mathcal{D}} [F(x_{t+1}) - F(x_t)] \\
& \leq -\gamma(1 - 2Z_t) \mathbb{E}_{z \sim \mathcal{D}} [\|\nabla F(x_t)\|] + \frac{L\gamma^2}{2} \\
& + 2L\gamma^2(m-1)(1 + C_{\alpha_1} + 2C_{\alpha_2}(C_{\alpha_1} + 1)) \\
& + 2\gamma \frac{\sigma}{\sqrt{(1-\alpha_2)N(1-\alpha_1)mb}} \\
& + 4\gamma C_{\alpha_2} \mathbb{E}_{z \sim \mathcal{D}} [\max_{i \in \mathcal{T}^t} \|\nabla F_{i,t}(x_t) - \nabla F(x_t)\|_{\infty}] \\
& + \frac{2\gamma C_{\alpha_1}}{(1-\alpha_2)N} \sum_{i \in \mathcal{T}^t} 2 \mathbb{E}_{z \sim \mathcal{D}} [\max_{\tau, \tau' \in \mathcal{T}_i^t} \|\nabla F_{i,\tau}(x_{\tau'}) - \nabla F(x_{\tau'})\|_{\infty}] \\
& + 4\gamma C_{\alpha_1} C_{\alpha_2} 2 \mathbb{E}_{z \sim \mathcal{D}} [\max_{i \in \mathcal{T}^t, \tau, \tau' \in \mathcal{T}_i^t} \|\nabla F_{i,\tau}(x_{\tau'}) - \nabla F(x_{\tau'})\|_{\infty}].
\end{aligned} \tag{113}$$

Next, we use Theorem 6 on the last three terms above, noting that the first maximization is over $2(1 - \alpha_2)Nd$ sub-gamma random variables, the second maximization is over $4(1 - \alpha_1)md$ sub-gamma random variables, and the last maximization is over $4(1 - \alpha_1)m(1 - \alpha_2)Nd$ sub-gamma random variables. The rest of the proof is identical to that of Theorem 2, resulting in:

$$\begin{aligned}
& \frac{1}{T} \sum_{t=m+m_0}^{T+m-1+m_0} \mathbb{E}[\|\nabla F(x_t)\|] \\
& \leq \frac{F(x_1) - F(x^*)}{\sqrt{T}\gamma_0(1 - 2P_Z^m(m_0))} + \frac{\bar{C}(m_0)\gamma_0}{\sqrt{T}} \\
& + \frac{\|\nabla F(x_1)\|(m-1+m_0)}{T(1 - 2P_Z^m(m_0))} + \frac{L\gamma_0(m-1+m_0)^2}{2T^{3/2}(1 - 2P_Z^m(m_0))} \\
& + \frac{2\sigma}{(1 - 2P_Z^m(m_0))\sqrt{(1-\alpha_2)N(1-\alpha_1)mb}} \\
& + \frac{4C_{\alpha_2}a \log(2(1-\alpha_2)Nd)}{(1 - 2P_Z^m(m_0))b} \\
& + \frac{4C_{\alpha_2}\sigma\sqrt{2\log((2(1-\alpha_2)Nd))}}{(1 - 2P_Z^m(m_0))\sqrt{b}} \\
& + \frac{4C_{\alpha_1}a \log(4(1-\alpha_1)md)}{(1 - 2P_Z^m(m_0))b} \\
& + \frac{4C_{\alpha_1}\sigma\sqrt{2\log(4(1-\alpha_1)md)}}{(1 - 2P_Z^m(m_0))\sqrt{b}} \\
& + \frac{8C_{\alpha_1}C_{\alpha_2}a \log(4(1-\alpha_2)N(1-\alpha_1)md)}{(1 - 2P_Z^m(m_0))b} \\
& + \frac{8C_{\alpha_1}C_{\alpha_2}\sigma\sqrt{2\log(4(1-\alpha_2)N(1-\alpha_1)md)}}{(1 - 2P_Z^m(m_0))\sqrt{b}}
\end{aligned} \tag{114}$$

F. Proof of Lemma 2

$$\|e_t\| = \left\| \frac{\nabla F(x_t)}{\|\nabla F(x_t)\|} - \frac{\hat{g}_t^{Z_t=0}}{\|\hat{g}_t^{Z_t=0}\|} \right\| \tag{115}$$

$$= \left\| \frac{\nabla F(x_t)\|\hat{g}_t^{Z_t=0}\| - \hat{g}_t^{Z_t=0}\|\nabla F(x_t)\|}{\|\nabla F(x_t)\|\|\hat{g}_t^{Z_t=0}\|} \right\| \tag{116}$$

$$= \left\| \frac{\|\hat{g}_t^{Z_t=0}\| \|\nabla F(x_t) - \hat{g}_t^{Z_t=0}\|}{\|\nabla F(x_t)\| \|\hat{g}_t^{Z_t=0}\|} + \frac{\hat{g}_t^{Z_t=0} (\|\hat{g}_t^{Z_t=0}\| - \|\nabla F(x_t)\|)}{\|\nabla F(x_t)\| \|\hat{g}_t^{Z_t=0}\|} \right\| \quad (117)$$

$$\leq 2 \frac{\|\nabla F(x_t) - \hat{g}_t^{Z_t=0}\|}{\|\nabla F(x_t)\|} \quad (118)$$

Using the sets \mathcal{T}^t and $\{\mathcal{T}_i^t\}_{i \in \mathcal{T}^t}$, we define:

$$\bar{g}_t = \frac{1}{(1-\alpha_1)m(1-\alpha_2)N} \sum_{i \in \mathcal{T}^t} \sum_{\tau \in \mathcal{T}_i^t} \nabla F_{i,\tau}(x_\tau), \quad (119)$$

$$\hat{g}_t = \frac{1}{(1-\alpha_2)N} \sum_{i \in \mathcal{T}^t} \hat{g}_{i,t}. \quad (120)$$

Here, \bar{g} is the true mean of $(1-\alpha_1)m(1-\alpha_2)N$ trustworthy gradients with time indices $\tau \in \mathcal{T}_i^t$ from agents $i \in \mathcal{T}^t$, and \hat{g}_t is the mean of the robustified gradients of agents $i \in \mathcal{T}^t$.

We split the numerator of (118) as follows:

$$\|\nabla F(x_t) - \hat{g}_t^{Z_t=0}\| \leq \|\nabla F(x_t) - \bar{g}_t\| + \|\bar{g}_t - \hat{g}_t\| + \|\bar{g}_t - \hat{g}_t^{Z_t=0}\|. \quad (121)$$

Next, we upper bound each term above using smoothness of F , normalized updates, and triangular inequality:

$$1) \|\nabla F(x_t) - \bar{g}_t\| = \left\| \nabla F(x_t) - \frac{1}{(1-\alpha_1)m(1-\alpha_2)N} \sum_{i \in \mathcal{T}^t} \sum_{\tau \in \mathcal{T}_i^t} \nabla F_{i,\tau}(x_\tau) \right\| \quad (122)$$

$$\leq \left\| \nabla F(x_t) - \frac{1}{(1-\alpha_1)m(1-\alpha_2)N} \sum_{i \in \mathcal{T}^t} \sum_{\tau \in \mathcal{T}_i^t} \nabla F_{i,\tau}(x_t) \right\| \quad (123)$$

$$+ \left\| \frac{1}{(1-\alpha_1)m(1-\alpha_2)N} \sum_{i \in \mathcal{T}^t} \sum_{\tau \in \mathcal{T}_i^t} \nabla F_{i,\tau}(x_t) - \nabla F_{i,\tau}(x_\tau) \right\|$$

$$\leq \left\| \nabla F(x_t) - \frac{1}{(1-\alpha_1)m(1-\alpha_2)N} \sum_{i \in \mathcal{T}^t} \sum_{\tau \in \mathcal{T}_i^t} \nabla F_{i,\tau}(x_t) \right\|$$

$$+ \frac{L}{(1-\alpha_1)m(1-\alpha_2)N} \sum_{i \in \mathcal{T}^t} \sum_{\tau \in \mathcal{T}_i^t} \|x_t - x_\tau\| \quad (124)$$

$$\leq \left\| \nabla F(x_t) - \frac{1}{(1-\alpha_1)m(1-\alpha_2)N} \sum_{i \in \mathcal{T}^t} \sum_{\tau \in \mathcal{T}_i^t} \nabla F_{i,\tau}(x_t) \right\|$$

$$+ L\gamma(m-1). \quad (125)$$

$$2) \|\bar{g}_t - \hat{g}_t\| = \left\| \frac{1}{(1-\alpha_1)N} \sum_{i \in \mathcal{T}^t} \bar{g}_{i,t} - \hat{g}_{i,t} \right\|$$

$$\leq \frac{1}{(1-\alpha_2)N} \sum_{i \in \mathcal{T}^t} \|\bar{g}_{i,t} - \hat{g}_{i,t}\| \quad (126)$$

$$\leq \frac{1}{(1-\alpha_2)N} \sum_{i \in \mathcal{T}^t} \max_{\tau \in \mathcal{T}_i^t} C_{\alpha_1} \|\nabla F_{i,\tau}(x_\tau) - \frac{1}{(1-\alpha_1)m} \sum_{\tau' \in \mathcal{T}_i^t} \nabla F_{i,\tau'}(x_{\tau'})\|_\infty \quad (127)$$

$$\leq \frac{1}{(1-\alpha_2)N} \sum_{i \in \mathcal{T}^t} \max_{\tau, \tau' \in \mathcal{T}_i^t} C_{\alpha_1} \|\nabla F_{i,\tau}(x_\tau) - \nabla F_{i,\tau'}(x_{\tau'})\|_\infty \quad (128)$$

$$\leq \frac{1}{(1-\alpha_2)N} \sum_{i \in \mathcal{T}^t} \max_{\tau, \tau' \in \mathcal{T}_i^t} C_{\alpha_1} \|\nabla F_{i,\tau}(x_\tau) - \nabla F_{i,\tau'}(x_{\tau'})\|_\infty \quad (129)$$

$$+ \frac{1}{(1-\alpha_2)N} \sum_{i \in \mathcal{T}^t} \max_{\tau, \tau' \in \mathcal{T}_i^t} C_{\alpha_1} \|\nabla F_{i,\tau}(x_{\tau'}) - \nabla F_{i,\tau'}(x_{\tau'})\|_\infty$$

$$\leq C_{\alpha_1} L\gamma(m-1) + \frac{1}{(1-\alpha_2)N} \sum_{i \in \mathcal{T}^t} \max_{\tau, \tau' \in \mathcal{T}_i^t} C_{\alpha_1} \|\nabla F_{i,\tau}(x_{\tau'}) - \nabla F_{i,\tau'}(x_{\tau'})\|_\infty. \quad (130)$$

$$3) \|\bar{g}_t - \hat{g}_t^{Z_t=0}\| \leq C_{\alpha_2} \max_{i \in \mathcal{T}^t} \|\hat{g}_{i,t} - \frac{1}{(1-\alpha_2)N} \sum_{j \in \mathcal{T}^t} \hat{g}_{j,t}\|_\infty$$

$$\leq C_{\alpha_2} \max_{i,j \in \mathcal{T}^t} \|\hat{g}_{i,t} - \hat{g}_{j,t}\|_\infty \quad (131)$$

$$\leq C_{\alpha_2} \max_{i,j \in \mathcal{T}^t} (\|\hat{g}_{i,t} - \bar{g}_{i,t}\|_\infty + \|\hat{g}_{j,t} - \bar{g}_{j,t}\|_\infty + \|\bar{g}_{i,t} - \bar{g}_{j,t}\|_\infty) \quad (132)$$

$$\leq 2C_{\alpha_2} \max_{i \in \mathcal{T}^t} \|\hat{g}_{i,t} - \bar{g}_{i,t}\|_\infty + 2C_{\alpha_2} \max_{i \in \mathcal{T}^t} \|\bar{g}_{i,t} - \nabla F(x_t)\|_\infty \quad (133)$$

$$\leq 2C_{\alpha_2} \max_{i \in \mathcal{T}^t} \|\hat{g}_{i,t} - \bar{g}_{i,t}\|_\infty + 2C_{\alpha_2} \max_{i \in \mathcal{T}^t} \left\| \frac{1}{(1-\alpha_1)m} \sum_{\tau \in \mathcal{T}_i^t} \nabla F_{i,\tau}(x_\tau) - \nabla F_{i,\tau}(x_t) \right\|_\infty$$

$$+ 2C_{\alpha_2} \max_{i \in \mathcal{T}^t} \left\| \frac{1}{(1-\alpha_1)m} \sum_{\tau \in \mathcal{T}_i^t} \nabla F_{i,\tau}(x_t) - \nabla F(x_t) \right\|_\infty \quad (134)$$

$$\leq 2C_{\alpha_2} \max_{i \in \mathcal{T}^t} \|\hat{g}_{i,t} - \bar{g}_{i,t}\|_\infty + 2C_{\alpha_2} L\gamma(m-1) + 2C_{\alpha_2} \max_{i \in \mathcal{T}^t} \left\| \frac{1}{(1-\alpha_1)m} \sum_{\tau \in \mathcal{T}_i^t} \nabla F_{i,\tau}(x_t) - \nabla F(x_t) \right\|_\infty \quad (135)$$

$$\leq 2(C_{\alpha_1} + 1)C_{\alpha_2} L\gamma(m-1) + 2C_{\alpha_2} C_{\alpha_1} \max_{i \in \mathcal{T}^t, \tau, \tau' \in \mathcal{T}_i^t} \|\nabla F_{i,\tau}(x_{\tau'}) - \nabla F_{i,\tau'}(x_{\tau'})\|_\infty$$

$$+ 2C_{\alpha_2} \max_{i \in \mathcal{T}^t} \left\| \frac{1}{(1-\alpha_1)m} \sum_{\tau \in \mathcal{T}_i^t} \nabla F_{i,\tau}(x_t) - \nabla F(x_t) \right\|_\infty, \quad (136)$$

where the last inequality follows from (127)-(130). Gathering all three terms, we get the desired result.

G. Tighter Bound on $P_Z(m_0)$

Lemma 3. *Given the network and algorithm parameters $(m, N, \alpha_1, \alpha_2, M)$, the following holds for all $m_0 \in \mathbb{Z}^+$:*

$$P_Z(m_0) \leq \sum_{k=\alpha_2 N+1}^N \binom{N}{k} (P_Y^m(m_0))^k (1 - P_Y^m(m_0))^{(1-k)}, \quad (137)$$

where

$$P_Y^m(m_0) = \sum_{s=0}^1 \sum_{k=\alpha_1 m+1}^m r_s(k; m, 1-p_t, p_b) \Pi_{m_0}(s) \quad (138)$$

with

$$r_s(k; m, 1-p_t, p_b) = \sum_{i=0}^{\min(k, n-k)} \binom{n-i}{k} \binom{k}{i} (1-p_t)^{k-i} (1-p_b)^{n-k-i} (1-p_t-p_b)^i$$

$$+ \sum_{i=0}^{\min(k-1+s, n-k-s)} \binom{n-i-1}{k-1+s} \binom{k-1+s}{i} (1-p_t)^{n-k-i-1+s} \times (1-p_b)^{n-k-i-s} (1-p_t-p_b)^{i+1} \quad (139)$$

and

$$\Pi_{m_0}(0) = \frac{p_t - p_t(1-p_b-p_t)^{m_0}}{p_b + p_t} \quad (140)$$

$$\Pi_{m_0}(1) = \frac{p_b + p_t(1-p_b-p_t)^{m_0}}{p_b + p_t} \quad (141)$$

Proof. The goal here is to find a tighter upper bound on $P_Z(m_0)$ than the bound provided in Lemma 1. The proof is identical to that of Lemma 1 until (51). A tighter bound is established by deriving the exact expression on $P_Y^m(m_0)$ rather than using a Chernoff's bound.

Using the Markovian property of the agents' behaviour, we can rewrite (51) using total law of probability:

$$P_Y^m(m_0) = \max_{i \in [N]} \sum_{s=0}^1 \mathbb{P} \left(\frac{1}{m} \sum_{\tau=t-m+1}^t W_{i,\tau} > \alpha_1 | W_{i,t-m+1} = s \right) \times \mathbb{P}_{\pi_{t-m+1-m_0}^i} (W_{i,t-m+1} = s), \quad (142)$$

where $\mathbb{P}_{\pi_{t-m+1-m_0}^i} (W_{i,t-m+1} = s)$ is the probability that $W_{i,t-m+1} = s$ given the distribution at time $t-m+1-m_0$. The first multiplicand in the above equation has a closed form as follows [52]:

$$\mathbb{P} \left(\frac{1}{m} \sum_{\tau=t-m+1}^t W_{i,\tau} > \alpha_1 | W_{i,t-m+1} = s \right) = \sum_{k=\alpha_1 m+1}^m \mathbb{P} \left(\sum_{\tau=t-m+1}^t W_{i,\tau} = k | W_{i,t-m+1} = s \right) \quad (143)$$

$$= \sum_{k=\alpha_1 m+1}^m r_s(k; m, 1-p_t, p_b), \quad (144)$$

where

$$\begin{aligned} r_s(k; m, 1-p_t, p_b) &= \sum_{i=0}^{\min(k, m-k)} \binom{m-i}{k} \binom{k}{i} (1-p_t)^{k-i} (1-p_b)^{m-k-i} (1-p_t-p_b)^i \\ &+ \sum_{i=0}^{\min(k-1+s, m-k-s)} \binom{m-i-1}{k-1+s} \binom{k-1+s}{i} (1-p_t)^{m-k-i-1+s} \\ &\quad \times (1-p_b)^{m-k-i-s} (1-p_t-p_b)^{i+1}. \end{aligned} \quad (145)$$

Next, we determine $\mathbb{P}_{\pi_{t-m+1-m_0}^i} (W_{i,t-m+1} = s)$ for $s = \{0, 1\}$ as follows:

$$\begin{aligned} \mathbb{P}_{\pi_{t-m+1-m_0}^i} (W_{i,t-m+1} = 0) &= \frac{p_t}{p_b + p_t} \\ &+ \frac{(1-p_b-p_t)^{m_0}}{p_b + p_t} (\pi_{t-m+1-m_0}^i(0)p_b - \pi_{t-m+1-m_0}^i(1)p_t) \end{aligned} \quad (146)$$

$$\mathbb{P}_{\pi_{t-m+1-m_0}^i} (W_{i,t-m+1} = 1) = 1 - \mathbb{P}_{\pi_{t-m+1-m_0}^i} (W_{i,t-m+1} = 0) \quad (147)$$

The above probabilities depend on the distribution at time $t-m+1-m_0$. Noting that $r_1(\cdot) > r_0(\cdot)$, we upper bound (142) by upper bounding $\mathbb{P}_{\pi_{t-m+1-m_0}^i} (W_{i,t-m+1} = 1)$. To do so, we lower bound (146) by setting $\pi_{t-m+1-m_0}^i(1) = 1$, i.e., by assuming that at time $t-m+1-m_0$ the agent was Byzantine, which is the worst-case intuition. All in all we have:

$$P_Y^m(m_0) = \sum_{s=0}^1 \sum_{k=\alpha_1 m+1}^m r_s(k; m, 1-p_t, p_b) \Pi_{m_0}(s), \quad (148)$$

$$\Pi_{m_0}(0) = \frac{p_t - p_t(1-p_b-p_t)^{m_0}}{p_b + p_t} \quad (149)$$

$$\Pi_{m_0}(1) = \frac{p_b + p_t(1-p_b-p_t)^{m_0}}{p_b + p_t} \quad (150)$$

□