

---

# SPANISH LANGUAGE MODELS

---

**Asier Gutiérrez-Fandiño\***  
Text Mining Unit  
Barcelona Supercomputing Center  
asier.gutierrez@bsc.es

**Jordi Armengol-Estapé\***  
Text Mining Unit  
Barcelona Supercomputing Center  
jordi.armengol@bsc.es

**Marc Pàmies**  
Text Mining Unit  
Barcelona Supercomputing Center  
marc.pamies@bsc.es

**Joan Llop-Palao**  
Text Mining Unit  
Barcelona Supercomputing Center  
joan.lloppalao@bsc.es

**Joaquín Silveira-Ocampo**  
Text Mining Unit  
Barcelona Supercomputing Center  
joaquin.silveira@bsc.es

**Casimiro Pio Carrino**  
Text Mining Unit  
Barcelona Supercomputing Center  
casimiro.pio@bsc.es

**Aitor Gonzalez-Agirre**  
Text Mining Unit  
Barcelona Supercomputing Center  
aitor.gonzalez@bsc.es

**Carme Armentano-Oller**  
Text Mining Unit  
Barcelona Supercomputing Center  
carme.armentano@bsc.es

**Carlos Rodriguez-Penagos**  
Text Mining Unit  
Barcelona Supercomputing Center  
carlos.rodriguez1@bsc.es

**Marta Villegas**  
Text Mining Unit  
Barcelona Supercomputing Center  
marta.villegas@bsc.es

October 25, 2021

## ABSTRACT

This paper presents the Spanish RoBERTa-base and RoBERTa-large models, as well as the corresponding performance evaluations. Both models were pre-trained using the largest Spanish corpus known to date, with a total of 570GB of clean and deduplicated text processed for this work, compiled from the web crawlings performed by the National Library of Spain from 2009 to 2019. We extended the current evaluation datasets with an extractive Question Answering dataset and our models outperform the existing Spanish models across tasks and settings.

## 1 Introduction and Previous Work

In recent years, the language-specific modeling literature has been quite prolific [1]. In the case of Spanish, BETO [2], a Spanish BERT [3], outperformed a strong multilingual baseline, mBERT. BETO was trained with a collection of existing corpora, such as the Spanish Wikipedia. Nevertheless, there aren't many high-quality Spanish-specific models available.

In this work, we:

1. Process the largest *clean* Spanish corpus based on the web crawlings performed by the National Library of Spain from 2009 to 2019.
2. Train RoBERTa-base [4] and RoBERTa-large (the largest Spanish-specific model to date) models with these data.<sup>1</sup>

---

\*Equal contribution.

<sup>1</sup>Publicly available at <https://huggingface.co/BSC-TeMU/roberta-base-bne> and <https://huggingface.co/BSC-TeMU/roberta-large-bne>.

3. Conduct a complete evaluation on a diverse set of tasks.

In Section 2, we describe the new dataset and how we generated it. In Section 3, we compute word embeddings as a simple baseline for future experiments. Then in Section 4, we describe the new RoBERTa models. In Section 5, we evaluate the new models and compare their results with strong monolingual (BETO) and multilingual (mBERT) models. In addition, we compare it to the BERTIN model<sup>2</sup> produced in the Flax/Jax Community Week.<sup>3</sup> Finally, we present our conclusions and suggestions for future work, in Section 6.

## 2 Data

The National Library of Spain (Biblioteca Nacional de España<sup>4</sup>) crawls all *.es* domains once a year. Besides this massive crawl, the library performs selective crawls that can be classified into three categories: themed based (this includes 15 different thematic collections, from fine arts to universities, feminism and politics), relevant events (that is, events of special relevance for the Spanish society, and of special significance for future research on Spanish history, society and culture) and domains at risk of disappearing.<sup>5</sup> The data used for training the language models derive from these selective crawls, carried out from 2009 to 2019.

Due to the size of the data, the Library ran the first data extraction from WARC formatted files using the Selectolax Python library<sup>6</sup> in its own premises. This process generated 59TB of JSON files containing some metadata along with the text extracted from the WARC files, namely: paragraphs, headers, keywords and links’ texts.

To ensure the quality of the data, we developed a cleaning pipeline [5] which splits data into sentences, detects the language, removes noisy and ill-formed sentences (based on some heuristics), deduplicates and eventually outputs the data with their original document boundaries. The pipeline is inspired by the heuristics proposed in Virtanen et al. [6]. For this cleaning process, we used 100 nodes, each with 48 CPU cores, of MareNostrum 4 during 96 hours. At the end of the process we were left with 2TB of clean data at document level. Finally, to remove repetitive content, we concatenated the entire corpus and deduplicated again, obtaining a total of 570GB of high quality data.

### 2.1 SQAC

The Spanish Question Answering Corpus (SQAC) is an extractive QA dataset with no adversarial or unanswerable questions created from articles extracted from the Spanish Wikipedia, Wikinews and from the AnCora corpus [7]. It was created by commissioning 18,817 questions with their answer spans from 6,247 textual contexts. The guidelines were adapted from SQuAD v1.1 (Rajpurkar et al. [8]), and the annotators were all native Spanish speakers with university studies in various fields related to linguistics. Following XQuAD structure, no additional answers were collected.

For human performance evaluation, we commissioned to an independent company the annotation of the answer spans in nearly 600 randomly chosen questions. We obtained a human score equal to 85% F1 and 71% EM (after answer normalization).

We felt the need to create SQAC because the lack of quality datasets for fine-tuning or evaluating in this task. The Spanish portion of XQuAD is only an evaluation set and, although it purportedly is a professional translation of the English contexts and questions, it is not a good sample, culturally or idiomatically, for Spanish. The SQAC (Spanish Question Answering Corpus) dataset contributes greatly to the benchmarking datasets in this language, that too often consists either of bad manual or automatic translations from other languages, or are too small or not documented enough.

## 3 Embeddings

We computed both CBOW and Skip-gram word embeddings with 300 dimensions using FastText [9] and are available on Zenodo:

- CBOW.<sup>7</sup>

<sup>2</sup><https://huggingface.co/flax-community/bertin-roberta-large-spanish>

<sup>3</sup><https://discuss.huggingface.co/t/open-to-the-community-community-week-using-jax-flax-for-nlp-cv/7104>

<sup>4</sup><http://www.bne.es/en/Inicio/index.html>

<sup>5</sup><http://www.bne.es/en/Colecciones/ArchivoWeb/Subcolecciones/selectivas.html>

<sup>6</sup><https://pypi.org/project/selectolax>

<sup>7</sup><https://zenodo.org/record/5044988>

- Skip-gram.<sup>8</sup>

With the clean data at document level mentioned on the Corpora section, the processing took around 20 days on a HPC node equipped with an AMD EPYC 7742 (@ 2.250GHz) processor using the 128 threads.

## 4 Models

The architecture and training procedure (masked language modeling without next sentence prediction) selected for our models was RoBERTa [4], in base and large sizes (following the standard BERT nomenclature). Both models were pre-trained for a single epoch as proposed in Komatsuzaki [10], following recent trends [11]. Following the mentioned literature, we do not use dropout to increase convergence speed taking into account that the model will not overfit to a large dataset in a single pass, but keep weight decay to 0.01 because it has been proven to still be beneficial in single-epoch regimes [12]. As vocabulary, we use Byte-Level BPE [13], as in the original RoBERTa, trained with our train corpus. For training, we use the Fairseq [14] library, and for fine-tuning, Huggingface Transformers [15].

## 5 Evaluation

We compare our RoBERTa-base and RoBERTa-large models with the mBERT, BETO and BERTIN models.

The BERT multilingual base model cased (mBERT) is a BERT language model with 12 self-attention layers, 12 attention heads each, a hidden size of 768, and a total of 110M parameters. It was pretrained on 104 languages with the Wikipedia dataset.

According to the authors, the BETO model has 12 self-attention layers, 16 attention heads each, a hidden layer of size 1024, and a total of 110M parameters.<sup>9</sup> It was pretrained with text from different sources: all the Spanish data from Wikipedia and the Spanish portion of the OPUS Project.<sup>10</sup> However, the actual version uploaded to Huggingface<sup>11</sup> is a BERT-base with 12 self-attention layers, 12 attention heads each, a hidden size of 768, and a total of 110M parameters.

Although BERTIN was announced as a RoBERTa-large model, it is actually a RoBERTa-base model with 12 layers, 12 attention heads each, hidden size of 768, and a total 125M parameters<sup>12</sup>. It was trained from scratch on the Spanish portion of mC4. The BERTIN version we are evaluating is the one pointed out by the authors.

We fine-tuned each model in the following tasks:

- The Cross-lingual Adversarial Dataset for Paraphrase Identification (PAWS-X) [16].
- The Multilingual Document Classification Corpus (MLDoc) [17, 18].
- Named Entity Recognition from the Capitel Corpus (Capitel-NER) [19].<sup>13</sup>
- Part of Speech from the Capitel Corpus (Capitel-POS) [19].<sup>14</sup>
- Semantic Textual Similarity (STS) from 2014 [20] and 2015 [21].
- Part of Speech from Universal Dependencies<sup>15</sup> (UD-POS).
- The Cross-Lingual NLI Corpus (XNLI) [22].
- Named Entity Recognition from Conll2002 (Conll-NER) [23].
- Extractive Question Answering with the Spanish Question Answering Corpus (SQAC) presented in this paper.<sup>16</sup>

For all models and tasks, we conduct a small grid search and pick the best value for each model:

<sup>8</sup><https://zenodo.org/record/5046525>

<sup>9</sup>Note that the claimed parameter count of BETO does not add up, since BERT-base has the same number of parameters with 12 attention heads and an embedding size of 786.

<sup>10</sup><https://opus.nlpl.eu/>

<sup>11</sup><https://huggingface.co/dccuchile/bert-base-spanish-wwm-cased>

<sup>12</sup>A previous version of this preprint described BERTIN as a RoBERTa-large model. We correct this information now.

<sup>13</sup>[https://sites.google.com/view/capitel2020#h.p\\_CbqX2kG3XEIp](https://sites.google.com/view/capitel2020#h.p_CbqX2kG3XEIp)

<sup>14</sup>[https://sites.google.com/view/capitel2020#h.p\\_eFTF8UCJXFmQ](https://sites.google.com/view/capitel2020#h.p_eFTF8UCJXFmQ)

<sup>15</sup><https://universaldependencies.org/>

<sup>16</sup>Available on <https://huggingface.co/datasets/BSC-TeMU/SQAC>

- Batch size: 16, 32.
- Weight decay: 0.01, 0.1.
- Learning rate: 1e-5, 3e-5, 5e-5.
- Epochs: The best (as per the validation set) out of 5 epochs.

Table 1 summarizes the results with the best configurations for all models and tasks. Then, tables, 2, 3, 4, 5, 6, 7, 8, 9, and 10 report the best hyperparameters for each model for UD-POS, Conll-NER, Capitel-POS, Capitel-NER, STS, MLDoc, PAWS, XNLI, and SQAC, respectively.

We note that these are preliminary results and that the final evaluation is subject to change, especially in terms of the RoBERTa-large fine-tuning, for which we have encountered some numerical instability due to the difficulty of training large models.

Dataset	Metric	RoBERTa-b	RoBERTa-l	BETO	mBERT	BERTIN	ELECTRA
UD-POS	F1	<b>0.9907</b>	0.9898	0.9900	0.9886	0.9898	0.9818
Conll-NER	F1	<b>0.8851</b>	0.8772	0.8759	0.8691	0.8835	0.7954
Capitel-POS	F1	0.9846	<b>0.9851</b>	0.9836	0.9839	0.9847	0.9816
Capitel-NER	F1	0.8960	<b>0.8998</b>	0.8772	0.8810	0.8856	0.8035
STS	Combined	<b>0.8533</b>	0.8353	0.8159	0.8164	0.7945	0.8063
MLDoc	Accuracy	0.9623	<b>0.9675</b>	0.9663	0.9550	0.9673	0.9493
PAWS-X	F1	0.9000	<b>0.9060</b>	0.9000	0.8955	0.8990	0.9025
XNLI	Accuracy	0.8016	0.7958	<b>0.8130</b>	0.7876	0.7890	0.7878
SQAC	F1	0.7923	<b>0.7993</b>	0.7923	0.7562	0.7678	0.7383

Table 1: Evaluation table of models.

Model	Batch Size	Weight decay	Learning rate	Eval F1	Test F1
RoBERTa-b	16	0.1	0.00005	0.9907	<b>0.9907</b>
RoBERTa-l	32	0.1	0.00005	0.9911	0.9898
BETO	16	0.01	0.00003	0.9907	0.9900
mBERT	32	0.1	0.00005	0.9892	0.9886
BERTIN	32	0.01	0.00005	0.9910	0.9898
ELECTRA	16	0.1	0.00005	0.9826	0.9818

Table 2: Best configurations for the eval UD-POS dataset with F1 for eval and test.

Model	Batch Size	Weight decay	Learning rate	Eval F1	Test F1
RoBERTa-b	32	0.01	0.00005	0.8870	<b>0.8851</b>
RoBERTa-l	32	0.01	0.00001	0.8882	0.8772
BETO	16	0.1	0.00003	0.8710	0.8759
mBERT	16	0.1	0.00003	0.8727	0.8691
BERTIN	16	0.1	0.00005	0.8835	0.8835
ELECTRA	16	0.1	0.00005	0.7986	0.7954

Table 3: Best configurations for the eval Conll-NER dataset with F1 for eval and test.

## 6 Conclusions & Future Work

In this work, we have processed the largest clean Spanish corpus to date. Furthermore, the textual richness provided by our dataset should be *additive* to the ones in the previously used Spanish datasets, because we have not used them (e.g., our models have not seen Wikipedia).

Model	Batch Size	Weight decay	Learning rate	Eval F1	Test F1
RoBERTa-b	32	0.1	0.00005	0.9848	0.9846
RoBERTa-l	16	0.01	0.00001	0.9854	<b>0.9851</b>
BETO	32	0.1	0.00005	0.9839	0.9836
mBERT	16	0.1	0.00005	0.9835	0.9839
BERTIN	16	0.1	0.00005	0.9847	0.9847
ELECTRA	16	0.01	0.00005	0.9822	0.9816

Table 4: Best configurations for the eval Capitel-POS dataset with F1 for eval and test.

Model	Batch Size	Weight decay	Learning rate	Eval F1	Test F1
RoBERTa-b	16	0.01	0.00005	0.9013	0.8960
RoBERTa-l	16	0.1	0.00001	0.9043	<b>0.8998</b>
BETO	32	0.1	0.00005	0.8909	0.8772
mBERT	16	0.1	0.00003	0.8877	0.8810
BERTIN	16	0.1	0.00005	0.8969	0.8856
ELECTRA	16	0.01	0.00005	0.8017	0.8035

Table 5: Best configurations for the eval Capitel-NER dataset with F1 for eval and test.

Model	Batch Size	Weight decay	Learning rate	Eval Combined Score	Test Combined Score
RoBERTa-b	16	0.01	0.00003	0.9095	<b>0.8533</b>
RoBERTa-l	32	0.01	0.00003	0.9179	0.8353
BETO	16	0.1	0.00003	0.8919	0.8159
mBERT	16	0.1	0.00005	0.9193	0.8164
BERTIN	16	0.1	0.00003	0.8976	0.7945
ELECTRA	16	0.1	0.00005	0.9181	0.8063

Table 6: Best configurations for the eval STS dataset with Combined Score for eval and test.

Model	Batch Size	Weight decay	Learning rate	Eval Accuracy	Test Accuracy
RoBERTa-b	32	0.1	0.00001	0.9700	0.9623
RoBERTa-l	16	0.01	0.00001	0.9780	<b>0.9675</b>
BETO	32	0.01	0.00005	0.9740	0.9663
mBERT	16	0.01	0.00003	0.9670	0.9550
BERTIN	32	0.1	0.00005	0.9770	0.9673
ELECTRA	32	0.1	0.00003	0.9530	0.9493

Table 7: Best configurations for the eval MLDoc dataset with Accuracy for eval and test.

Model	Batch Size	Weight decay	Learning rate	Eval F1	Test F1
RoBERTa-b	16	0.01	0.00003	0.9020	0.9000
RoBERTa-l	32	0.1	0.00001	0.9085	<b>0.9060</b>
BETO	16	0.1	0.00003	0.9025	0.9000
mBERT	16	0.01	0.00003	0.8990	0.8955
BERTIN	32	0.1	0.00005	0.8975	0.8990
ELECTRA	32	0.01	0.00003	0.9040	0.9025

Table 8: Best configurations for the eval PAWS-X dataset with F1 for eval and test.

Our contributions in this paper also include the creation *ex novo* of a much needed high-quality dataset for extractive QA in Spanish (SQAC), that will allow more meaningful comparisons with other models regarding language acceptability, in addition to subtask evaluation.

Model	Batch Size	Weight decay	Learning rate	Eval Accuracy	Test Accuracy
RoBERTa-b	16	0.01	0.00003	0.8124	0.8016
RoBERTa-l	16	0.1	0.00001	0.8116	0.7958
BETO	16	0.01	0.00001	0.8269	<b>0.8130</b>
mBERT	32	0.1	0.00001	0.8032	0.7876
BERTIN	16	0.1	0.00005	0.8044	0.7890
ELECTRA	16	0.01	0.00005	0.8028	0.7878

Table 9: Best configurations for the eval XNLI dataset with Accuracy for eval and test.

Model	Batch Size	Weight decay	Learning rate	Eval F1	Test F1
RoBERTa-b	16	0.01	0.00005	0.8086	0.7923
RoBERTa-l	16	0.1	0.00001	0.8153	<b>0.7993</b>
BETO	32	0.01	0.00005	0.8044	0.7923
mBERT	32	0.01	0.00005	0.7805	0.7562
BERTIN	16	0.1	0.00005	0.7827	0.7678
ELECTRA	16	0.01	0.00005	0.7572	0.7383

Table 10: Best configurations for the eval SQAC dataset with F1 for eval and test.

The RoBERTa-base model outperforms the strong BETO, mBERT and BERTIN baselines in most tasks (UD-POS, Conll-NER, Capitel-POS, Capitel-NER, STS and PAWS-X). The RoBERTa-large, despite obtaining better results than BETO and mBERT, struggles to outperform its base counterpart in all but two tasks, which we attribute to the difficulty of the process of optimization of larger models.

As future work, we are planning to:

1. Combine the new dataset with other sources (such as the Spanish Wikipedia),
2. Further investigate the training procedure of RoBERTa-large to get its results to its full potential.

## Acknowledgements

We want to thank the National Library of Spain for such a large effort on the data gathering.

This work was partially funded by the Spanish State Secretariat for Digitalization and Artificial Intelligence (SEDIA) within the framework of the Plan-TL, and the Future of Computing Center, a Barcelona Supercomputing Center and IBM initiative (2020).

## Appendix I

This Appendix contains a sample of Masked Language Modelling prediction assessments for understanding the models' predictions.

### Agreement

Sentence: "Juana se dejó el libro en el coche porque es muy {mask} con sus cosas."

RoBERTa-base-BNE: [*'lista', 'buena', 'cuidadosa', 'estricta', 'generosa'*]

RoBERTa-large-BNE: [*'cuidadosa', 'pesada', 'tranquila', 'lista', 'ocupada'*]

BETO: [*'cuidadoso', 'sensible', 'bueno', 'buena', 'rpido'*]

mBERT: [*'buena', 'feliz', 'bien', 'triste', 'fuerte'*]

Sentence: "La chica que encontraron en el parque estaba leyendo un libro {mask} en el banco."

RoBERTa-base-BNE: [*'sentada', 'sentado', 'tumbado', 'viejo', 'esperando'*]

RoBERTa-large-BNE: [*'sentado', 'sentada', 'tumbado', 'y'*]

BETO: [*'robado', 'tirado', 'nuevo', 'colgado'*]

mBERT: [*'escrito', 'estaba', 'suyo', 'y'*]

Sentence: "De entre todas, eligieron en el concurso de baile a quién estaba mejor {mask}."

RoBERTa-base-BNE: [*'vestida', 'preparada', 'dotado', 'vestido', 'preparado'*]

RoBERTa-large-BNE: [*'vestida', 'preparada', 'formada'*]

BETO: [*'vestida', 'vestido', 'bailando', 'preparada', 'vestidos'*]

mBERT: [*'##a', '##ado', 'puesto', 'colocado', 'ubicado'*]

Sentence: "A la chica los pantalones le quedaban cortos porque eran muy {mask} para su edad."

RoBERTa-base-BNE: [*'cortos', 'altos', 'largos', 'ajustados', 'pequeos'*]

RoBERTa-large-BNE: [*'cmodos', 'largos', 'cortos', 'pequeos', 'grandes'*]

BETO: [*'cortos', 'pequeos', 'largos', 'grandes', 'altos'*]

mBERT: [*'grandes', 'populares', 'importantes', 'jvenes', 'buenas'*]

Sentence: "Le gustaban mucho, pero no {mask} podía comprarlas porque eran demasiado caras."

RoBERTa-base-BNE: [*'las', 'se', 'le', 'la', 'lo'*]

RoBERTa-large-BNE: [*'siempre', 'se', 'todas', 'me', 'todos'*]

BETO: [*'se', 'siempre', 'le', 'les', 'las'*]

mBERT: [*'se', 'le', 'slo', 'solo', 'lo'*]

### Polarity agreement

Sentence: "Llegamos muy pronto y no pude hablar con {mask}."

RoBERTa-base-BNE: [*'ellos', 'nadie', 'vosotros', 'l', 'ella'*]

RoBERTa-large-BNE: [*'el', 'ella', 'ellos', 'l', 'nadie'*]

BETO: [*'l', 'ella', 'nadie', 'ellos', '[UNK]'*]

mBERT: [*'ellos', 'l', 'ella', 'nada', 'ellas'*]

Sentence: "No lo había visto {mask}."

RoBERTa-base-BNE: [*'nunca', 'antes', 'yo', 'jams', 'nadie'*]

RoBERTa-large-BNE: [*'nunca', 'antes', 'yo', 'jams', 'yo'*]

BETO: [*'antes', 'nunca', 'jams', 'yo', 'anteriormente'*]

mBERT: [*l', que', ', (' por'*]

### Lexical selection

Sentence: "Quita las manzanas verdes del cesto y deja solo las {mask}."

RoBERTa-base-BNE: [*rojas', naranjas', verdes', amarillas', nueces'*]

RoBERTa-large-BNE: [*manzanas', de', naranjas', hojas', .'*]

BETO: [*semillas', verdes', manzanas', rojas', malas'*]

mBERT: [*verdes', flores', manos', otras', mismas'*]

Sentence: "Este es un problema para el cual la solución es {mask}."

RoBERTa-base-BNE: [*sencilla', simple', inmediata', fcil', clara'*]

RoBERTa-large-BNE: [*sencilla', :', fcil', la', simple'*]

BETO: [*simple', sencilla', fcil', desconocida', complicada'*]

mBERT: [*simple', solucin', problema', til', necesaria'*]

Sentence: "Tenemos un problema para el cual hay que tomar una decisión y hay que {mask}."

RoBERTa-base-BNE: [*solucionarlo', hacerlo', actuar', hablar', esperar'*]

RoBERTa-large-BNE: [*actuar', solucionarlo', hacerlo', resolver', ...'*]

BETO: [*actuar', hacerla', hacerlo', votar', tomar'*]

mBERT: [*decidir', hacerlo', hacer', tomar', pensar'*]

Sentence: "Felipe {mask} que Juan conoce a Marta."

RoBERTa-base-BNE: [*dice', cree', asegura', descubre', confiesa'*]

RoBERTa-large-BNE: [*dice', cree', confiesa', afirma', asegura'*]

BETO: [*descubre', dice', sabe', explica', revela'*]

mBERT: [*dice', ordena', indica', de', afirma'*]

Sentence: "Mi amigo es bastante {mask}."

RoBERTa-base-BNE: [*bueno', mayor', guapo', listo', grande'*]

RoBERTa-large-BNE: [*bueno', guapo', grande', interesante', divertido'*]

BETO: [*bueno', guapo', fuerte', listo', inteligente'*]

mBERT: [*bien', fuerte', popular', importante', buen'*]

Sentence: "Mi amiga es bastante {mask}."

RoBERTa-base-BNE: [*buena', mayor', mala', guapa', lista'*]

RoBERTa-large-BNE: [*buena', linda', guapa', interesante', grande'*]

BETO: [*buena', guapa', bonita', agradable', hermosa'*]

mBERT: [*fuerte', buena', bien', regular', cercana'*]

Sentence: "Salió a cazar y mató un {mask}."

RoBERTa-base-BNE: [*len', perro', toro', conejo', gato'*]

RoBERTa-large-BNE: [*len', perro', lobo', hombre', oso'*]

BETO: [*oso', conejo', zorro', len', perro'*]

mBERT: [*hombre', soldado', piloto', caza', home'*]

Sentence: "Una {mask} situada en la región de Alta Normandía."

RoBERTa-base-BNE: [*villa', ciudad', localidad', isla', aldea'*]



RoBERTa-large-BNE: [*'ciudad', 'localidad', 'poblacin', 'regin', 'villa'*]  
 BETO: [*'francesa', 'ciudad', 'localidad', 'poblacin', 'comuna'*]  
 mBERT: [*'comuna', 'localidad', 'poblacin', 'parroquia', 'commune'*]  
 Sentence: "Te voy a contar una {mask} sobre mi prima."  
 RoBERTa-base-BNE: [*'historia', 'anecdota', 'cosa', 'leyenda', 'verdad'*]  
 RoBERTa-large-BNE: [*'historia', 'cosa', 'anecdota', 'curiosidad', 'verdad'*]  
 BETO: [*'historia', 'cosa', 'pista', 'verdad', 'teora'*]  
 mBERT: [*'novela', 'historia', 'pelcula', 'pista', 'cinta'*]  
 Sentence: "Martin se {mask} para ir a pescar al río."  
 RoBERTa-base-BNE: [*'prepara', 'ofrece', 'desnuda', 'casa', 'arregla'*]  
 RoBERTa-large-BNE: [*'prepara', 'preparaba', 'levanta', 'ofrece', 'prepar'*]  
 BETO: [*'prepara', 'despierta', 'fue', 'prepar', 'preparan'*]  
 mBERT: [*'va', 'ofrece', 'encuentra', 'preparar', 'queda'*]  
 Sentence: "Mi vida no ha sido fácil, pero yo {mask} la vida."  
 RoBERTa-base-BNE: [*'amo', 'es', 'soy', 'quiero'*]  
 RoBERTa-large-BNE: [*'amo', 'tengo', 'prefiero', 'vivo', 'adoro'*]  
 BETO: [*'amo', 'soy', 'vivo', 'tengo', 'gano'*]  
 mBERT: [*'es', 'tiene', 'ama', 'recuerda'*]  
 Sentence: "Llamó a su {mask} para que le ayudara con los niños."  
 RoBERTa-base-BNE: [*'madre', 'padre', 'hermana', 'hermano', 'mujer'*]  
 RoBERTa-large-BNE: [*'madre', 'padre', 'hijo', 'hija', 'hermana'*]  
 BETO: [*'madre', 'padre', 'hermana', 'hermano', 'abuela'*]  
 mBERT: [*'padre', 'madre', 'hijo', 'familia', 'esposa'*]  
 Sentence: "Llamó a su {mask} para que le ayudara con la limpieza."  
 RoBERTa-base-BNE: [*'madre', 'padre', 'hermana', 'mujer', 'hermano'*]  
 RoBERTa-large-BNE: [*'madre', 'hijo', 'padre', 'mujer', 'hermana'*]  
 BETO: [*'madre', 'padre', 'hermana', 'hermano', 'ta'*]  
 mBERT: [*'padre', 'madre', 'hijo', 'amigo', 'hermano'*]  
 Sentence: "Llamó a su {mask} porque se encontraba mal."  
 RoBERTa-base-BNE: [*'madre', 'padre', 'casa', 'mdico', 'familia'*]  
 RoBERTa-large-BNE: [*'madre', 'hijo', 'puerta', 'padre', 'familia'*]  
 BETO: [*'madre', 'padre', 'familia', 'casa', 'mdico'*]  
 mBERT: [*'padre', 'hijo', 'hermano', 'madre', 'amigo'*]  
 Sentence: "Llamó a su {mask} porque el coche hacía un ruido raro."  
 RoBERTa-base-BNE: [*'padre', 'madre', 'mujer', 'hermano', 'hermana'*]  
 RoBERTa-large-BNE: [*'madre', 'padre', 'hijo', 'coche', 'familia'*]  
 BETO: [*'mvil', 'madre', 'casa', 'padre', 'coche'*]  
 mBERT: [*'coche', 'familia', 'padre', 'casa', 'madre'*]

**Bias**

Sentence: "Los {mask} también pueden llevar falda."

RoBERTa-base-BNE: [*'hombres', 'nios', 'chicos', 'futbolistas', 'bebs'*]

RoBERTa-large-BNE: [*'hombres', 'nios', 'chicos', 'bebs', 'perros'*]

BETO: [*'hombres', 'nios', 'varones', '[UNK]', 'perros'*]

mBERT: [*'caballos', 'animales', 'hombres', 'romanos', 'colores'*]

Sentence: "El papel de la mujer en la ciencia es {mask}."

RoBERTa-base-BNE: [*'fundamental', 'imprescindible', 'incuestionable', 'clave', 'crucial'*]

RoBERTa-large-BNE: [*'fundamental', 'el', 'esencial', 'clave', 'crucial'*]

BETO: [*'importante', 'relevante', 'fundamental', 'crucial', 'significativo'*]

mBERT: [*'social', 'fundamental', 'diferente', 'importante', 'universal'*]

Sentence: "El papel de la {mask} en la ciencia es relevante."

RoBERTa-base-BNE: [*'mujer', 'msica', 'religin', 'publicidad', 'tecnologa'*]

RoBERTa-large-BNE: [*'mujer', 'familia', 'publicidad', 'msica', 'educacin'*]

BETO: [*'mujer', 'ciencia', 'tecnologa', 'educacin', 'investigacin'*]

mBERT: [*'mujer', 'educacin', 'ciencia', 'fuerza', 'tecnologa'*]

Sentence: "El papel de la mujer en la {mask} es relevante."

RoBERTa-base-BNE: [*'ciencia', 'empresa', 'sociedad', 'educacin', 'Universidad'*]

RoBERTa-large-BNE: [*'ciencia', 'empresa', 'msica', 'sociedad', 'historia'*]

BETO: [*'sociedad', 'educacin', 'poltica', 'economia', 'cultura'*]

mBERT: [*'sociedad', 'mujer', 'educacin', 'vida', 'cultura'*]

Sentence: "Lo más importante para ella es su {mask}."

RoBERTa-base-BNE: [*'salud', 'familia', 'vida', 'futuro', 'trabajo'*]

RoBERTa-large-BNE: [*'corazn', 'sonrisa', 'familia', 'marido', 'hijo'*]

BETO: [*'seguridad', 'familia', 'vida', 'felicidad', 'trabajo'*]

mBERT: [*'vida', 'trabajo', 'amor', 'clase', 'voz'*]

Sentence: "Lo más importante para él es su {mask}."

RoBERTa-base-BNE: [*'salud', 'vida', 'familia', 'trabajo', 'felicidad'*]

RoBERTa-large-BNE: [*'familia', 'sonrisa', 'persona', 'trabajo', 'equipo'*]

BETO: [*'familia', 'seguridad', 'trabajo', 'vida', 'dinero'*]

mBERT: [*'vida', 'amor', 'voz', 'trabajo', 'educacin'*]

Sentence: "Los {mask} son groseros y violentos."

RoBERTa-base-BNE: [*'comentarios', 'insultos', 'animales', 'hombres', 'dos'*]

RoBERTa-large-BNE: [*'comentarios', 'insultos', 'nios', 'mensajes', 'dos'*]

BETO: [*'hombres', 'animales', 'nios', 'humanos', 'adultos'*]

mBERT: [*'pies', 'frutos', 'ojos', 'postes', 'otros'*]

Sentence: "No vayas por esa calle, que hay muchos {mask} y te podría pasar algo."

RoBERTa-base-BNE: [*'coches', 'sitios', 'perros', 'problemas', 'nios'*]

RoBERTa-large-BNE: [*'coches', 'sitios', 'semforos', 'peligros', 'robos'*]

BETO: [*'coches', 'policas', 'rboles', 'edificios', 'nios'*]

mBERT: [',', 'nios', 'barrios', 'lugares', 'personas']

## References

- [1] Debora Nozza, Federico Bianchi, and Dirk Hovy. What the [mask]? making sense of language-specific BERT models. *CoRR*, abs/2003.02912, 2020. URL <https://arxiv.org/abs/2003.02912>.
- [2] José Cañete, Gabriel Chaperon, Rodrigo Fuentes, Jou-Hui Ho, Hojin Kang, and Jorge Pérez. Spanish pre-trained bert model and evaluation data. In *PMLADC at ICLR 2020*, 2020.
- [3] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: pre-training of deep bidirectional transformers for language understanding. *CoRR*, abs/1810.04805, 2018. URL <http://arxiv.org/abs/1810.04805>.
- [4] Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. Roberta: A robustly optimized bert pretraining approach, 2019.
- [5] Jordi Armengol-Estapé, Casimiro Pio Carrino, Carlos Rodriguez-Penagos, Ona de Gibert Bonet, Carme Armentano-Oller, Aitor Gonzalez-Agirre, Maite Melero, and Marta Villegas. Are multilingual models the best choice for moderately under-resourced languages? a comprehensive assessment for catalan, 2021.
- [6] Antti Virtanen, Jenna Kanerva, Rami Ilo, Jouni Luoma, Juhani Luotolahti, Tapio Salakoski, Filip Ginter, and Sampo Pyysalo. Multilingual is not enough: BERT for finnish. *CoRR*, abs/1912.07076, 2019. URL <http://arxiv.org/abs/1912.07076>.
- [7] Mariona Taulé, M. Antònia Martí, and Marta Recasens. AnCora: Multilevel annotated corpora for Catalan and Spanish. In *Proceedings of the Sixth International Conference on Language Resources and Evaluation (LREC'08)*, Marrakech, Morocco, May 2008. European Language Resources Association (ELRA). URL [http://www.lrec-conf.org/proceedings/lrec2008/pdf/35\\_paper.pdf](http://www.lrec-conf.org/proceedings/lrec2008/pdf/35_paper.pdf).
- [8] Pranav Rajpurkar, Jian Zhang, Konstantin Lopyrev, and Percy Liang. Squad: 100,000+ questions for machine comprehension of text, 2016.
- [9] Piotr Bojanowski, Edouard Grave, Armand Joulin, and Tomas Mikolov. Enriching word vectors with subword information. *arXiv preprint arXiv:1607.04606*, 2016.
- [10] Aran Komatsuzaki. One epoch is all you need, 2019.
- [11] Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. *CoRR*, abs/2005.14165, 2020. URL <https://arxiv.org/abs/2005.14165>.
- [12] Tom Henighan, Jared Kaplan, Mor Katz, Mark Chen, Christopher Hesse, Jacob Jackson, Heewoo Jun, Tom B. Brown, Prafulla Dhariwal, Scott Gray, Chris Hallacy, Benjamin Mann, Alec Radford, Aditya Ramesh, Nick Ryder, Daniel M. Ziegler, John Schulman, Dario Amodei, and Sam McCandlish. Scaling laws for autoregressive generative modeling. *CoRR*, abs/2010.14701, 2020. URL <https://arxiv.org/abs/2010.14701>.
- [13] Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. Language Models are Unsupervised Multitask Learners. 2019. URL <https://openai.com/blog/better-language-models/>.
- [14] Myle Ott, Sergey Edunov, Alexei Baevski, Angela Fan, Sam Gross, Nathan Ng, David Grangier, and Michael Auli. fairseq: A fast, extensible toolkit for sequence modeling. In *Proceedings of NAACL-HLT 2019: Demonstrations*, 2019.
- [15] Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, Joe Davison, Sam Shleifer, Patrick von Platen, Clara Ma, Yacine Jernite, Julien Plu, Canwen Xu, Teven Le Scao, Sylvain Gugger, Mariama Drame, Quentin Lhoest, and Alexander M. Rush. Transformers: State-of-the-art natural language processing. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pages 38–45, Online, October 2020. Association for Computational Linguistics. URL <https://www.aclweb.org/anthology/2020.emnlp-demos.6>.
- [16] Yinfei Yang, Yuan Zhang, Chris Tar, and Jason Baldridge. PAWS-X: A Cross-lingual Adversarial Dataset for Paraphrase Identification. In *Proc. of EMNLP*, 2019.
- [17] Holger Schwenk and Xian Li. A corpus for multilingual document classification in eight languages. In Nicoletta Calzolari (Conference chair), Khalid Choukri, Christopher Cieri, Thierry Declerck, Sara Goggi, Koiti Hasida, Hitoshi Isahara, Bente Maegaard, Joseph Mariani, H el ene Mazo, Asuncion Moreno, Jan Odijk, Stelios Piperidis, and Takenobu Tokunaga, editors, *Proceedings of the Eleventh International Conference on Language Resources*

- and Evaluation (LREC 2018)*, Paris, France, may 2018. European Language Resources Association (ELRA). ISBN 979-10-95546-00-9.
- [18] David D Lewis, Yiming Yang, Tony Russell-Rose, and Fan Li. Rcv1: A new benchmark collection for text categorization research. *Journal of machine learning research*, 5(Apr):361–397, 2004.
  - [19] Jordi Porta-Zamorano and Luis Espinosa-Anke. Overview of capitel shared tasks at iberlef 2020: Named entity recognition and universal dependencies parsing, 2020.
  - [20] Eneko Agirre, Carmen Banea, Claire Cardie, Daniel Cer, Mona Diab, Aitor Gonzalez-Agirre, Weiwei Guo, Rada Mihalcea, German Rigau, and Janyce Wiebe. Semeval-2014 task 10: Multilingual semantic textual similarity. In *Proceedings of the 8th international workshop on semantic evaluation (SemEval 2014)*, pages 81–91, 2014.
  - [21] Eneko Agirre, Carmen Banea, Claire Cardie, Daniel Cer, Mona Diab, Aitor Gonzalez-Agirre, Weiwei Guo, Inigo Lopez-Gazpio, Montse Maritxalar, Rada Mihalcea, et al. Semeval-2015 task 2: Semantic textual similarity, english, spanish and pilot on interpretability. In *Proceedings of the 9th international workshop on semantic evaluation (SemEval 2015)*, pages 252–263, 2015.
  - [22] Alexis Conneau, Ruty Rinott, Guillaume Lample, Adina Williams, Samuel R. Bowman, Holger Schwenk, and Veselin Stoyanov. Xnli: Evaluating cross-lingual sentence representations. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics, 2018.
  - [23] Erik F. Tjong Kim Sang. Introduction to the CoNLL-2002 shared task: Language-independent named entity recognition. In *COLING-02: The 6th Conference on Natural Language Learning 2002 (CoNLL-2002)*, 2002. URL <https://aclanthology.org/W02-2024>.