

MRCpy: A Library for Minimax Risk Classifiers

Karthek Bondugula

*BCAM-Basque Center for Applied Mathematics
Bilbao, Spain*

KBONDUGULA@BCAMATH.ORG

Santiago Mazuelas

*BCAM-Basque Center for Applied Mathematics, IKERBASQUE-Basque Foundation for Science
Bilbao, Spain*

SMAZUELAS@BCAMATH.ORG

Aritz Pérez

*BCAM-Basque Center for Applied Mathematics
Bilbao, Spain*

APEREZ@BCAMATH.ORG

Editor: XXX

Abstract

Existing libraries for supervised classification implement techniques that are based on empirical risk minimization and utilize surrogate losses. We present **MRCpy** library that implements minimax risk classifiers (MRCs) that are based on robust risk minimization and can utilize 0–1-loss. Such techniques give rise to a manifold of classification methods that can provide tight bounds on the expected loss. **MRCpy** provides a unified interface for different variants of MRCs and follows the standards of popular Python libraries. The presented library also provides implementation for popular techniques that can be seen as MRCs such as L1-regularized logistic regression, zero-one adversarial, and maximum entropy machines. In addition, **MRCpy** implements recent feature mappings such as Fourier, ReLU, and threshold features. The library is designed with an object-oriented approach that facilitates collaborators and users. The source code is available under the MIT license at <https://github.com/MachineLearningBCAM/MRCpy>.

Keywords: Supervised classification, robust risk minimization, minimax risk classifiers, feature mappings

1. Introduction

Existing libraries for supervised classification, such as **scikit-learn**, implement techniques that are based on empirical risk minimization and utilize surrogate losses, such as support vector machines and logistic regression (see e.g., Mohri et al., 2018). These techniques minimize the expected loss with respect to the empirical distribution. The recently proposed minimax risk classifiers (MRCs) are based on robust risk minimization and can utilize 0–1-loss (Mazuelas et al., 2020, 2021). These techniques minimize the maximum expected loss with respect to an uncertainty set of distributions and can provide upper and lower bounds on expected loss. In addition, existing techniques can be seen as MRCs under certain additional constraints related to the empirical marginal distributions.

We present **MRCpy**, an open-source Python library that provides a unified interface for different variants of MRCs and follows the standards of popular libraries such as **scikit-learn**. The presented library also provides implementation for popular existing techniques that can be seen as MRCs such as L1-regularized logistic regression (see e.g., Mohri et al., 2018),

MRCpy	Corresponding Techniques	Existing Libraries
MRC (0–1-loss)	✗	✗
MRC (log-loss)	✗	✗
CMRC (0–1-loss)	Zero-one adversarial, Maximum entropy machine	✗
CMRC (log-loss)	L1-regularized logistic regression	scikit-learn, shark

Table 1: Techniques corresponding to MRCs and their existing libraries

zero-one adversarial (Asif et al., 2015), and maximum entropy machines (Fathony et al., 2016). Table 1 summarizes the 4 variants of MRCs currently implemented by MRCpy along with the corresponding techniques and their implementation in existing libraries. In addition, MRCpy implements recent feature mappings such as Fourier, ReLU, and threshold features (Rahimi and Recht, 2008a,b; Lebanon and Lafferty, 2001; Sun et al., 2018). The library is designed with an object-oriented approach that facilitates collaborators and users. For instance, the library provides users with a convenient way to implement their own feature mapping object and combine it with the MRCs.

The rest of the paper is organized as follows. Section 2 provides a description of the variants of MRCs implemented. Section 3 describes the code design and presents an overview of MRCpy. Finally, Section 4 illustrates the usage of the library through elementary examples.

2. Minimax Risk Classification

MRCs obtain a classification rule h^u that minimizes the maximum expected ℓ -loss with respect to distributions in an uncertainty set \mathcal{U} defined by expectation constraints, that is,

$$h^u \in \arg \min_h \max_{p \in \mathcal{U}} \ell(h, p)$$

This minimax risk optimization problem composes the learning stage of MRCs and is equivalent to a convex optimization problem with L1-regularization as detailed by Mazuelas et al. (2021).

MRCpy currently implements 4 variants of MRCs that use two types of uncertainty sets and loss functions. The first type of uncertainty set (\mathcal{U}_1) is defined by constraints that bound the expectations of a feature mapping. MRCs (MRC) using this type of uncertainty sets provide upper and lower bounds on the expected loss. The second type of uncertainty set (\mathcal{U}_2) is defined by an additional constraint that fixes the instances’ marginal distribution such that they coincide with the empirical marginal distribution. MRCs (CMRC) using this type of uncertainty sets correspond to popular techniques that do not provide bounds on the expected loss. The first type of loss function (0–1-loss) quantifies the probability of classification error. The second type of loss function (log-loss) quantifies the negative log-likelihood for a classification rule. While MRCs can utilize 0–1-loss that directly provides the classification error, common techniques rely on surrogate losses, such as log-loss and hinge-loss.

MRCs use feature mappings to represent instance-label pairs as real vectors similarly to other existing techniques (see e.g., Mohri et al., 2018). Currently, MRCpy implements 3

kinds of recently proposed feature mappings: random Fourier features (Rahimi and Recht, 2008a), random ReLU features (Sun et al., 2018), and threshold features (Rahimi and Recht, 2008a; Lebanon and Lafferty, 2001; Mazuelas et al., 2020) that can be easily combined with the variants of MRCs in the library. In addition to these feature mappings, the library also implements the usual identity feature map referred to as linear feature map.

3. Overview and Design

MRCpy provides implementation for different MRCs with an object-oriented approach. The different MRCs in the library inherit from a `BaseMRC` class, and implement the functions `minimax_risk` and `predict_proba`. The function `minimax_risk` solves the minimax risk optimization problem and the function `predict_proba` returns the classification probabilities for given instances. The parent class `BaseMRC` implements the usual functions `fit` and `predict` that utilize the sub-class functions `minimax_risk` and `predict_proba` respectively. Currently, MRCpy implements the 4 variants of MRCs, as described in Section 2, using the classes `MRC` and `CMRC` that inherit from the `BaseMRC` class. These classes correspond to MRCs that use the uncertainty sets \mathcal{U}_1 and \mathcal{U}_2 , respectively, with each class having implementation for different loss functions. In addition to the functions defined above, the `MRC` class implements the functions `get_upper_bound` and `get_lower_bound` that provide the upper and lower bounds for expected loss. The upper bound is directly obtained by the minimax risk optimization while the lower bound is obtained by solving an additional optimization problem. To solve the convex optimization problems, the library provides the option to use either a fast optimization algorithm based on Nesterov acceleration (Tao et al., 2020) or a more accurate subroutine that uses `cvxpy` library but can be slower.

MRCpy enables to use multiple types of recent feature mappings using the module `phi`. This module provides implementation for different kinds of feature mappings with an object-oriented approach. A feature mapping in the module inherits from a `BasePhi` class, and implements the functions `fit` and `transform`. The function `fit` learns the required parameters used to compute the features and the function `transform` returns the features computed using the parameters. The parent class `BasePhi` implements the other utility functions, in addition to `fit` and `transform`, that are used by the MRCs in the library. Currently, the module implements 3 kinds of feature mappings based on random features and thresholds using the classes `RandomFourierPhi`, `RandomReLUPhi`, and `ThresholdPhi`, in addition to the linear feature map implemented by the `BasePhi` class itself.

MRCpy depends on standard scientific Python libraries `numpy`, `scipy`, `scikit-learn` and `cvxpy`. It also comes with a `datasets` module that provides multiple public benchmark data sets on supervised classification along with functions that simplify their usage. The library is hosted on GitHub at <https://github.com/MachineLearningBCAM/MRCpy> which offers a convenient way to request support and to raise issues. The code follows standards that facilitate readability and collaboration, and undergoes unit-testing with continuous integration using the service Travis CI that ensures code quality and clarity with the Python tool `flake8`. The detailed documentation is available at <https://MachineLearningBCAM.github.io/MRCpy> and includes the installation guidelines, examples and the description of the API.

4. Usage

The current version (v0.1.1) of MRCpy is available for Python 3.6 and provided under the MIT license. The library can be easily installed by following the instructions given in the GitHub repository. In the following, we present some examples to illustrate the usage of the MRCpy’s intuitive API.

The code snippet shown below trains a MRC classifier using 0–1-loss on a classification data set available in the library.

```

from MRCpy import MRC
from MRCpy.datasets import load_mammographic
from sklearn.model_selection import train_test_split

# Load the mammographic data set
X, Y = load_mammographic(return_X_y=True)
# Split the data into training and testing
X_train, X_test, y_train, y_test = train_test_split(X, Y, test_size
    =0.2, random_state=42)
# Create the MRC classifier using default loss (0-1)
clf = MRC()
# Fit the classifier on the training data
clf.fit(X_train, y_train)
# Bounds on the classification error (only for MRC)
lower_error = clf.get_lower_bound()
upper_error = clf.get_upper_bound()
# Compute the accuracy on the test set
accuracy = clf.score(X_test, y_test)

```

The default loss function used in the library is the 0–1-loss and the log-loss can be used by setting the parameter `loss='log'` in the object declaration. In addition, the default feature mapping is linear and the other feature mappings can be used by setting the parameter `phi` in the object declaration. The following code snippet illustrates the use of the 3 different feature mappings that are currently available in MRCpy using the log-MRC variant.

```

# Create the MRC using log-loss and different feature mappings
clf1 = MRC(loss='log', phi='fourier')
clf2 = MRC(loss='log', phi='relu')
clf3 = MRC(loss='log', phi='threshold')

```

In addition, all the examples shown here can also be reproduced for the CMRC class except for the bounds on expected loss.

The library also provides users with a convenient way to implement their own feature mapping object. A basic approach to implement a new feature mapping can be to extend `BasePhi` and implement the functions `fit` and `transform`. This object can be easily combined with the MRCs in the library by setting it to the parameter `phi`. Additional examples together with the detailed API can be found in the library’s documentation.

5. Conclusion

We presented the Python library MRCpy that implements for recently proposed supervised classification techniques called minimax risk classifiers (MRCs). In addition, the presented library implements recent feature mappings. MRCpy is designed with an objected-oriented approach that facilitates adaptability. The library is available on GitHub at

<https://github.com/MachineLearningBCAM/MRCpy> and provided under the MIT license. The code is consistent with the standards of popular libraries and undergoes continuous testing with upcoming updates. The library is actively maintained and will keep incorporating components such as additional loss functions and feature mappings.

Acknowledgments

Funding in direct support of this work has been provided by the Spanish Ministry of Economy and Competitiveness MINECO through Ramon y Cajal Grant RYC-2016-19383, BCAM's Severo Ochoa Excellence Accreditation SEV-2017-0718, Project PID2019-105058GA-I00, and by the Basque Government through the ELKARTEK and BERC 2018-2021 programmes.

References

- Kaiser Asif, Wei Xing, Sima Behpour, and Brian D. Ziebart. Adversarial cost-sensitive classification. In *Conference on Uncertainty in Artificial Intelligence*, pages 92–101, 2015.
- Rizal Fathony, Anqi Liu, Kaiser Asif, and Brian D. Ziebart. Adversarial multiclass classification: a risk minimization perspective. In *Advances in Neural Information Processing Systems*, volume 29, pages 559–567, 2016.
- Guy Lebanon and John Lafferty. Boosting and maximum likelihood for exponential models. In *Advances in Neural Information Processing Systems*, volume 20, pages 447–454, 2001.
- Santiago Mazuelas, Andrea Zanoni, and Aritz Pérez. Minimax classification with 0-1 loss and performance guarantees. In *Advances in Neural Information Processing Systems*, volume 33, pages 302–312, 2020.
- Santiago Mazuelas, Yuan Shen, and Aritz Pérez. Generalized maximum entropy for supervised classification. *To be published in IEEE Transactions on Information Theory, currently available as arXiv preprint*, arXiv:2007.05447, 2021.
- Mehryar Mohri, Afshin Rostamizadeh, and Ameet Talwalkar. *Foundations of machine learning*. MIT press, Cambridge, MA, second edition, 2018.
- Ali Rahimi and Benjamin Recht. Random features for large-scale kernel machines. In *Advances in Neural Information Processing Systems*, volume 20, pages 1177–1184, 2008a.
- Ali Rahimi and Benjamin Recht. Uniform approximation of functions with random bases. In *46th Annual Allerton Conference on Communication, Control, and Computing*, pages 555–561, 2008b.
- Yitong Sun, Anna Gilbert, and Ambuj Tewari. On the approximation properties of random ReLU features. *arXiv preprint*, arXiv:1810.04374, 2018.
- Wei Tao, Zhisong Pan, Gao wei Wu, and Qing Tao. The strength of Nesterov's extrapolation in the individual convergence of nonsmooth optimization. *IEEE Transactions on Neural Networks and Learning Systems*, 31:2557–2568, 2020.