

Nonparametric Extrema Analysis in Time Series for Envelope Extraction, Peak Detection and Clustering

Kaan Gokcesu, Hakan Gokcesu

Abstract—In this paper, we propose a nonparametric approach that can be used in envelope extraction, peak-burst detection and clustering in time series. Our problem formalization results in a naturally defined splitting/forking of the time series. With a possibly hierarchical implementation, it can be used for various applications in machine learning, signal processing and mathematical finance. From an incoming input signal, our iterative procedure sequentially creates two signals (one upper bounding and one lower bounding signal) by minimizing the cumulative L_1 drift. We show that a solution can be efficiently calculated by use of a Viterbi-like path tracking algorithm together with an optimal elimination rule. We consider many interesting settings, where our algorithm has near-linear time complexities.

I. INTRODUCTION

A. Extrema Analysis

The problem of extrema analysis of time series [1]–[3], whether in the form of envelope extraction [4], peak-burst detection [5], clustering [6] or signal bands/channels [7] have become prominent in machine learning, data mining and mathematical finance. The identification and analysis of the extrema in a given time series is essential in many applications because of its useful topological implications and features [5] in a myriad of fields, including but not limited to mass spectrometry [8], signal processing [9], [10], image processing [11], bioinformatics [12]–[14] and astrophysics [15].

The extrema can implicate certain increases (or decreases) in a time series, which can be used in the problem of classification [16]. For example, the workload (utilization) of a server CPU (processors) can be analyzed to extract idle or busy states, which can be used to forecast future states [17]. The extrema analysis can efficiently track the nominal behavior of a time series, which can be used in the problem of anomaly detection [18]–[20]. For example, the volumes of traffic in network data can be analyzed for anomalous or malicious behavior (such as attacks), where the analysis of periodicities or similarities can be meaningful [21]. The extrema analysis can model the dependencies in a time series, which can be used in the problem of online learning [22]–[24]. For example, the trading volume and prices in financial data can be analyzed for the prediction of oversold or overbought markets, where their correlating burst events can be meaningful [25]. The extrema can track the most informative values in the time series, such as the envelope of the electromyography (EMG) signal for use in robotic systems and prosthesis control [26] to achieve a perfect collaboration between man and robot. In general, the extrema can provide useful robust features [3], especially for robust learning [27]. The extrema are very important in these applications whether in the form of maxima or minima [5].

B. Envelope Extraction

The first of many applications of the extrema analysis is the envelope extraction, which is of utmost importance in the informative data analysis of a modulated signal, where the envelope is extracted by use of a demodulator [28].

Moreover, its usefulness is most apparent in the analysis of random signals, which is commonly encountered in the study of seakeeping and oceanography (or ocean engineering), where waves often occur in groups, which can result in severe damage to the offshore structures. The theory of the envelope of a random signal have been historically used to investigate the statistical properties of such wave groups and correspondingly the wave amplitude distribution [29]–[31]. Their use is of high importance in the prediction of the deck motion (which is necessary for safe landing and take-off for helicopters), where the extraction of the deck motion envelope is used in the platform movement predictions [32]. The works of [33], [34] has established the basis for the envelope statistics and the expression for its spectra was obtained by [4]. The efficient calculation of the envelope is addressed in [35].

Furthermore, the envelope extraction problem has become prominent with the rise of the field of bioinformatics, especially the electrical activity of the human body and specifically the skeletal muscle tissue, i.e., the electromyography (EMG) signal. The most widely used techniques to extract the EMG envelope are the Hilbert transform [36], mean square error (MSE) criterion [37] and the rectified signal waveform [38]. Many algorithms have been developed in literature to extract the EMG envelope, which primarily exploit the signal's moving average activity together with a noise reduction [39]. However, such methods may suffer large bias errors and be unable to avoid measurement spikes [40]. The Savitsky-Golay smoother combined with a low-pass filter was used to address such problems [41], where the smoothing improves envelope shaping but introduces time delays, which may be intolerable in certain applications (such as robotics). In [26], the signal envelope has been extracted with time-frequency analysis on finite time windows (using Short-time Fourier Transform). In [42], the authors suggest rectifying the EMG signal a priori, which can enhance the muscle activation information but still struggles with high envelope variability [43]. In addition, Kalman and Wiener filter based algorithms have been developed for EMG by many works [44]–[48]. While the traditional Kalman setting has effective tracking when noise is white Gaussian; it provides no meaningful advantage against other methods, since EMG noise is strictly non-white [40]. Another approach by [49] completely forgoes the unbiased noise assumption and is considered more robust [50].

C. Peak-Burst Detection

Another application of interest for the extrema analysis is the well-studied peak (and burst) detection, which is the study of sudden increases or decreases in the data set for informative purposes. Note that while it is easy to visually identify peaks in small datasets or time-series, the notion of peak need to be formalized for objectivity and for the development of automated peak detection algorithms. The automation becomes important in applications involving large datasets and variables, such as the data center monitoring where there are many large time-series about the utilization of CPU and memory in many servers, which need to be analyzed in real-time. In [5], several different notions of peak was introduced together with their corresponding algorithms.

Peak detection is a common task in many applications involving time series analysis. Standard approaches include either fitting a known function to the (possibly smoothed) time series; or matching a known peak shape in the time-series. Another widely used approach to detect the peaks is the detection of the zero-crossings of the gradient in the time series (i.e., local extrema), which is found by analyzing the differences between a point and its neighbors for the change in the gradient sign. However, such methods are susceptible to errors in noisy observations, which needs to be solved by the use of a signal to noise ratio (SNR) threshold [9], [51]. The work in [11] parametrically learns such threshold by adapting it to the noise levels in the time-series.

It is also possible to analyze the time series according to different properties of a possible peak and detecting the ones which satisfy all these requirements. One such work is [13], where the analysis of peaks in gene expression microarray time series data (specifically, for malaria parasite *Plasmodium falciparum*) is studied using multiple methods, each of which assigns a score to every point of the time series. In one of the methods, the score is set as the rate of change (gradient) at each point. In another one, it is the fraction of the area under a certain candidate peak point. For each method, the top 10 performing candidates are selected and the peaks detected by multiple methods are estimated as the true peaks, i.e., it is assumed that the true peaks need to satisfy more than one condition. In that application, the peaks detected are used to identify genes, and support vector machine (SVM) is used to assign each estimated gene to a group. The main problems encountered in peak detection are the existing noise in the time series and the fact that peaks can have varying amplitudes and scales, which may result in a high false positive rate [5].

There are some algorithms, which utilize the shape characteristics of the peaks in certain applications. One such approach is [52], which proposes a continuous wavelet transform (CWT) based algorithm to match preset pattern shapes to the possible peaks in mass spectroscopy data. The two dimensional CWT coefficients of the dataset is calculated using a Mexican-Hat mother wavelet (which has a basic peak shape) for the incoming time-series at multiple distinct scales. The changes in the wavelet transform are examined to identify possible peaks. Other wavelet based approaches to analyze spectroscopy data also exists [8], [53].

Another approach is to analyze the rate of change in the time series. One example is [10], which proposes a 'momentum' based algorithm to detect possible peaks. The main idea is to compute the 'velocity', i.e., gradient, and 'momentum', i.e., the product of the functional value and the 'velocity' at various points. If a ball were to be dropped from a previous peak, it should gain momentum as it rolls down and similarly lose momentum as it climbs up the next peak. The point where it comes to rest and stop, i.e., when the momentum is zero, should be the next peak. Physical world analogs of the Newton's laws are proposed to calculate the changes in momentum as the ball follows along the time-series.

The burst detection is also a prominent problem in machine learning, where the bursts are, in a sense, wider versions of the peaks. While a burst is made up of a wide region of extreme values with fast changes on both sides, a peak is made up of a narrow region of extreme values with fast changes on both sides. In [15], the authors propose a wavelet based burst detection algorithm. The wavelet coefficients for Haar wavelets together with some time-domain statistics such as the windowed average are used in a data structure called the shifted wavelet tree (SWT). Each level of the tree represents a resolution (time scale) and each node of a level corresponds to a certain window. By iterating over different window sizes and time scales, the bursts are detected. The work in [15] apply this method to detect burst in Gamma ray time series in real-time for the Milagro astronomical telescope, where the burst durations vary greatly from minutes to days.

The work in [21] propose a moving average based algorithm for burst detection. The time-series is smoothed with a moving average filter and the values which are larger than some preset parameter θ times the standard deviation of the smoothed time-series are detected. They choose θ typically between 1.5 and 2. The smoothing window is selected by using domain knowledge (e.g., 30 for daily data). In [25], the authors detect burst in real-time streaming stock market data and analyze correlations between the detected bursts.

D. Clustering

The extrema analysis and specifically peak detection based approaches are also widely used in applications considering clustering (or unsupervised classification). One such popular application is the detection of the QRS complex in electrocardiogram (ECG) signals. Many different methods have been developed for detection of such events, which can be summarized as those based on wavelet transform [6], [8], [52], [54]–[57], traditional window-threshold techniques [58]–[60], Hilbert transform [61], combining Hilbert and wavelet transform [62], artificial neural networks [63], [64], techniques using templates [65], [66], morphology filtering [67], [68], nonlinear filtering [69]–[72], Kalman filtering [73], Gabor filtering [74], Gaussian second derivative filtering [75], linear prediction analysis [76], higher-order statistics [77], K-Means clustering [78], fuzzy C-Means clustering [79], Empirical Mode Decomposition [80], hidden Markov models [81], and techniques using histogram/cumulative distribution function [82], intensity weighted variance [83], stochastic resonance [84], or a smoothed nonlinear energy operator [85].

E. Signal Bands

The time-series bands or channels is another (maybe most widely used) application (especially in the stock market). Within economics and mathematical finance, the trading bands are used for a variety of different trading approaches because of the various studies in support of them [86]–[88].

A trading band is, in its most simple form, an envelope (or channel) around a certain evolving metric (property) of the time series. Traditionally, these kinds of bands are constructed by creating two signals that are individually a certain distance away from a centralizing signal, which consequently define an upper and a lower band. The distance between the upper and lower bands is typically dependent on the trading band type, which is usually either a measure of volatility or a function of some other related parameter [89]. The upper and lower bands could be considered as some forms of support and resistance lines; where support and resistance are the values from which a quantity struggles to descend and ascend respectively [90].

One of the most popular signal bands/channels is the Donchian Price Channels [7], which defines a simple band with a set of three bands in total: one upper, one lower and a middle band, which is the direct average of them. For a preset window size n , the upper and the lower bands are the maximum and the minimum respectively of the last n samples. Bollinger bands are another popular technical analysis tool in mathematical finance. Aside from the field of economics, Bollinger bands have also been used to measure the accident rate (as a safety indicator) in the air travel industry and as a method of inspection in patterned fabrics [88]. Bollinger bands consist of two main values, which are a measure of the central tendency together with a measure of the volatility [89]. The traditionally used central tendency measure is the moving average μ_t and volatility measure is the moving standard deviation σ_t . These two values create three bands in total, where the middle band is the moving average μ_t and the upper and lower bands are $\mu_t \pm 2\sigma_t$. Another popular signal band is Keltner channels, which again uses the moving average for the measure of the central tendency. However, for the measure of the volatility, they adopt the Average True Range (ATR) [91].

F. Contributions and Organization

The problem with most of the algorithms in literature is in their parametric nature, where the more generally applicable and nonrestrictive they are, the more free parameters they have [5], [92]. However, the selection of parameters not only depend on the application and the dataset, it is also non trivial. To this end, we propose a nonparametric approach for the extrema analysis problem, which can be used in many types of applications including envelope extraction, peak-burst detection and clustering. In Section II, we mathematically formalize the problem setting in a natural way. In Section III, we provide the methodology to find the solution for that formulation, which sequentially outputs two non-crossing time series for a given input time series. In Section IV, we provide the computational complexity analysis for many interesting settings and show its efficiency. In Section V, we provide some concluding remarks.

II. PROBLEM FORMULATION

In this section, we formalize the extrema analysis problem for a given signal, mathematically. We start with an incoming time series, i.e., $\{x_1, x_2, \dots, x_T\}$, which is written for brevity as $\{x_t\}_{t=1}^T$. For this incoming time series, we want to create two signals, which are $\{a_t\}_{t=1}^T$ and $\{b_t\}_{t=1}^T$. These two signals will be our upper and lower bounding time series respectively. Thus, we want $a_t \geq x_t$ and $b_t \leq x_t$ for all t .

We postulate that there is a natural nonparametric way of defining the upper and lower bounding time series. For a definition that is parameter-free, we create the sequences $\{a_t\}_{t=1}^T$ and $\{b_t\}_{t=1}^T$ directly from the time series x_t , such that at any time t , x_t is either a_t or b_t . Hence, the problem is to split the time series $\{x_t\}_{t=1}^T$ into two sequences $\{a_t\}_{t=1}^T$ and $\{b_t\}_{t=1}^T$ by finding a binary sequence $\{s_t\}_{t=1}^T$, for which

$$a_t = s_t x_t + (1 - s_t) a_{t-1}, \quad (1)$$

$$b_t = (1 - s_t) x_t + s_t b_{t-1}. \quad (2)$$

The sequence $\{s_t\}_{t=1}^T$ is selected by minimizing the following objective:

$$\min_{\{s_t\}_{t=1}^T} \left(\sum_{t=2}^T |a_t - a_{t-1}| + \sum_{t=2}^T |b_t - b_{t-1}| \right). \quad (3)$$

Hence, the problem is to split x_t into two sequences such that the sum of their L_1 (Manhattan) drifts (sum of the successive samples distances) are minimized.

We have constructed the envelopes $\{a_t\}_{t=1}^T$ and $\{b_t\}_{t=1}^T$ with piecewise constant interpolation for the formulation, where a_t (and similarly b_t) is either x_t or x_τ for some $\tau < t$. However, we can just as easily use linear interpolation (which is more common and intuitive) for the missing the indices, which does not change the L_1 drift (and the objective function). With linear interpolation, we have the following beautiful property.

Lemma 1. *The signals $\{a_t\}_{t=1}^T$ and $\{b_t\}_{t=1}^T$ never cross.*

Proof. Suppose they cross at some t_c , which is a real number and both a and b are interpolated there. For that, let us have $t_{a,1} < t_c < t_{a,2}$ and $t_{b,1} < t_c < t_{b,2}$, where $a_{t_{a,1}} = x_{t_{a,1}}$, $a_{t_{a,2}} = x_{t_{a,2}}$, $b_{t_{b,1}} = x_{t_{b,1}}$, $b_{t_{b,2}} = x_{t_{b,2}}$ and a_t and b_t are interpolated between the samples $\{t_{a,1}, t_{a,2}\}$ and $\{t_{b,1}, t_{b,2}\}$ respectively. This will have the following loss

$$\begin{aligned} L_T = & \sum_{t=2}^{t_{a,1}} |a_t - a_{t-1}| + \sum_{t=t_{a,2}}^T |a_t - a_{t-1}| + |a_{t_{a,1}} - a_{t_{a,2}}|, \\ & + \sum_{t=2}^{t_{b,1}} |b_t - b_{t-1}| + \sum_{t=t_{b,2}}^T |b_t - b_{t-1}| + |b_{t_{b,1}} - b_{t_{b,2}}|. \end{aligned} \quad (4)$$

Now, if we switch the classes of the samples after t_c , i.e., $a_{t \geq t_{b,2}} \leftarrow b_{t \geq t_{b,2}}$ and vice-versa, we will have a loss which has a Δ difference resulting from the cross at t_c , which is $\Delta = |a_{t_{a,1}} - b_{t_{b,2}}| + |b_{t_{b,1}} - a_{t_{a,2}}| - |a_{t_{a,1}} - a_{t_{a,2}}| - |b_{t_{b,1}} - b_{t_{b,2}}|$. Since the original a_t and b_t were crossing each other, we want to compare the sum of the diagonals of a butterfly with the sum of its sides. From the triangle inequality, we have $\Delta < 0$, i.e., a smaller loss, which concludes the proof. \square

III. METHODOLOGY

A. Path Tracking Algorithm

The brute force approach is to try for all possible $\{s_t\}_{t=1}^T$ sequence, which are 2^T in total (i.e., exponential), and thus intractable.

A tractable approach is to use a path tracking method similar in spirit to the Viterbi algorithm [93]. In this approach, we sequentially calculate the losses of the sequences (or paths) $\{s_t\}_{t=1}^T$ and only keep the paths with the minimal losses (the survival rule).

Definition 1. At any time t' , let $\{s_{1,t}\}_{t=1}^{t'}$ and $\{s_{2,t}\}_{t=1}^{t'}$ be two distinct sequences, which are identical after some time t_s , such that

- $s_{1,t} = s_{2,t} = b$ for $t_s < t \leq t'$ (where $b \in \{0, 1\}$),
- $s_{1,t_s} = s_{2,t_s} = 1 - b$,
- $\{s_{1,t}\}_{t=1}^{t_s-1}$ is distinct to $\{s_{2,t}\}_{t=1}^{t_s-1}$.

Proposition 1. For two sequences $\{s_{1,t}\}_{t=1}^{t'}$ and $\{s_{2,t}\}_{t=1}^{t'}$ as in Definition 1, let their losses be $L_{1,t'}$ and $L_{2,t'}$. We need only to keep track of the sequence with the smaller loss.

Proof. We observe that the last time $\{s_{1,t}\}_{t=1}^{t'}$ and $\{s_{2,t}\}_{t=1}^{t'}$ is 0 and 1 coincide, thus, the additive loss resulting from the new sample $x_{t'+1}$ is identical. Without loss of generality, assume that the loss of $\{s_{1,t}\}_{t=1}^{t'}$ up to t' , $L_{1,t'}$ is smaller. Then, there is no reason to keep track of the loss of $\{s_{2,t}\}_{t=1}^{t'}$, since for any sequence $\{s_t\}_{t=t'+1}^T$, the loss of $\{s_{1,t}\}_{t=1}^{t'} \cup \{s_t\}_{t=t'+1}^T$ will be smaller than the loss of $\{s_{2,t}\}_{t=1}^{t'} \cup \{s_t\}_{t=t'+1}^T$, which concludes the proof. \square

Using this property, we keep track of the sequences with equivalence classes. At any time t' , $A_{t'}; b_{\tau}$ for $\tau < t'$ denote the class of the sequences $\{s_t\}_{t=1}^{t'}$, where the last index of 1 is t' and the last index of 0 is τ . Similarly, we have $B_{t'}; a_{\tau}$. At any time t , we will have $2(t-1)$ classes with the corresponding losses, which are given as

$$A_t; b_{\tau < t} : L_{\tau < t}^a, \quad (5)$$

$$B_t; a_{\tau < t} : L_{\tau < t}^b. \quad (6)$$

Note that each class keeps track of a single surviving sequence with the best loss. With a new incoming sample x_{t+1} , we update the classes and their losses as follows:

$$A_{t+1}; b_{\tau < t} : L_{\tau < t}^a + |x_{t+1} - x_t|, \quad (7)$$

$$A_{t+1}; b_t : \min_{\tau < t} (L_{\tau}^b + |x_{t+1} - x_{\tau}|), \quad (8)$$

$$B_{t+1}; a_{\tau < t} : L_{\tau < t}^b + |x_{t+1} - x_t|, \quad (9)$$

$$B_{t+1}; a_t : \min_{\tau < t} (L_{\tau}^a + |x_{t+1} - x_{\tau}|), \quad (10)$$

The minimum operations at (8) and (10) are where the Viterbi behavior comes from. At the end of T rounds, we will have

$$A_T; b_{\tau < T} : L_{\tau < T}^a, \quad (11)$$

$$B_T; a_{\tau < T} : L_{\tau < T}^b, \quad (12)$$

We can select the class with the minimum cumulative loss, which will minimize (3). This approach has quadratic $O(T^2)$ computational and memory complexity.

B. Efficient Algorithm

First of all, we observe that keeping both the equivalence classes $A_t; b_{\tau}$ and $B_t; a_{\tau}$ at time t is unnecessary (since there is no distinction between them). To this end, we revamp the design and only keep the following losses at each time t :

$$L_{t,\tau}, \quad t \in 0, 1, \dots, t-1, \quad (13)$$

where $L_{t,\tau}$ represents the loss of the best sequence where $\{s_{t'}\}_{t'=\tau+1}^t$ is $b \in \{0, 1\}$ and $s_{\tau} = 1 - b$, i.e., if $\{x_{t'}\}_{t'=\tau+1}^t$ belongs to the time series a then x_{τ} belongs to the time series b and vice-versa (thus, at τ , the assignment changes). The sequential update of $L_{t,\tau}$ is given as the following:

$$L_{t+1,\tau} = L_{t,\tau} + |x_{t+1} - x_t|, \tau \in \{0, 1, \dots, t-1\}, \quad (14)$$

$$L_{t+1,t} = \min(L_{t,0}, \min_{1 \leq \tau < t} (L_{t,\tau} + |x_{t+1} - x_{\tau}|)). \quad (15)$$

We observe that the individual updates to $L_{t+1,\tau}$ for $\tau \in \{0, 1, \dots, t-1\}$ is unnecessary since we only need to compare the losses at the end. Thus, we modify it as the following:

$$M_{t+1,\tau} = \begin{cases} M_{t,\tau}, & \tau \in \{0, 1, \dots, t-1\}, \\ \min_{0 \leq \tau' < t} (M_{t,\tau'} + d_{t,\tau'}), & \tau = t \end{cases} \quad (16)$$

where $d_{t,0} = -|x_{t+1} - x_t|$, $d_{t,\tau} = -|x_{t+1} - x_t| + |x_{t+1} - x_{\tau}|$.

Note that we have $M_{1,0} = 0$, $M_{t,0} = 0$. For further efficiency, we also keep the minimizer τ at each time t

$$\tau_t = \arg \min_{0 \leq \tau < t} (M_{t,\tau} + d_{t,\tau}). \quad (17)$$

At the end, we recreate the sequence as follows: We calculate

$$\tau^* = \arg \min_{0 \leq \tau \leq T-1} M_{T,\tau}, \quad (18)$$

which means the samples between $t \in \{\tau^* + 1, \dots, T\}$ belong to the first time series. Then, we get the next index, which is τ_{τ^*} , which means the samples between $t \in \{\tau_{\tau^*} + 1, \dots, \tau^*\}$ belong to the second time series. Then, setting $\tau^* \leftarrow \tau_{\tau^*}$, we recursively recalculate the time indices and setting the samples in the corresponding time series alternatively.

We can see that the double indexing is unnecessary since

$$M_{t,t'} = M_{t'+1,t'} = \min_{0 \leq \tau < t'} (M_{t',\tau} + d_{t',\tau}), \quad (19)$$

Thus, we can remove one of the indexing and just write that

$$M_t = \min_{0 \leq \tau \leq t-1} (M_{\tau} + d_{t,\tau}), \quad \tau_t = \arg \min_{0 \leq \tau \leq t-1} (M_{\tau} + d_{t,\tau}) \quad (20)$$

where

$$d_{t,\tau} = \begin{cases} -|x_{t+1} - x_t| + |x_{t+1} - x_{\tau}|, & 1 \leq \tau \leq t-1 \\ -|x_{t+1} - x_t|, & \tau = 0 \end{cases}. \quad (21)$$

This approach has $O(T)$ memory complexity and $O(T)$ backtrack. However, it will still have $O(T^2)$ complexity in total because of the calculation in M_t .

C. Optimal Elimination

We observe that the reason for the quadratic time complexity is because the complexity at each time t is proportional with the number of equivalence classes at time t . To make it efficient, we can eliminate certain equivalence classes. Sub-optimal ways include the elimination of M_τ where $\tau \leq t - w$ for some window w , or similarly, keeping the best w classes (with the minimum M_τ).

We observe that there is a trimming approach to the equivalence classes without loss of optimality.

Lemma 2. *We observe that we can directly eliminate all M_{τ_1} for $\tau_1 \neq 0$, such that*

$$M_{\tau_1} \geq M_{\tau_2} + |x_{\tau_2} - x_{\tau_1}|,$$

for some $\tau_2 \notin \{0, \tau_1\}$.

Proof. From the algorithm, we know that for any time t , if

$$t^* = \arg \min_{0 \leq \tau \leq t-1} (M_\tau + d_{t,\tau}), \quad (22)$$

we have

$$M_t = M_{t^*} + d_{t,t^*}. \quad (23)$$

Let $\tau_1, \tau_2 < t$. Then, we have

$$M_{\tau_1} \geq M_{\tau_2} + |x_{\tau_2} - x_{\tau_1}|, \quad (24)$$

$$\geq M_{\tau_2} + |x_t - x_{\tau_2}| - |x_t - x_{\tau_1}|, \quad (25)$$

from the triangle inequality. Thus,

$$M_{\tau_1} + d_{t,\tau_1} \geq M_{\tau_2} + d_{t,\tau_2}. \quad (26)$$

Thus there exists a t^* , which is distinct from τ_1 . Hence, we can eliminate M_{τ_1} , which concludes the proof. \square

Theorem 1. *If, for some $t_1 < t_2$,*

$$x_{t_1} \in [\min(x_{t_2}, x_{t_2+1}), \max(x_{t_2}, x_{t_2+1})],$$

M_{t_1} does not survive.

Proof. From Lemma 2, for survivability, we require

$$M_{t_1} < M_{t_2} + |x_{t_1} - x_{t_2}|, \quad (27)$$

for all nonzero $t_1 \neq t_2$ pairs in the running. If $t_1 < t_2$, we have

$$M_{t_2} \leq M_{t_1} - |x_{t_2+1} - x_{t_2}| + |x_{t_2+1} - x_{t_1}|, \quad (28)$$

from (20); and

$$M_{t_1} - |x_{t_1} - x_{t_2}| \leq M_{t_1} - |x_{t_2+1} - x_{t_2}| + |x_{t_2+1} - x_{t_1}| \quad (29)$$

from triangle inequality. However, (29) holds with equality, i.e.,

$$M_{t_1} - |x_{t_1} - x_{t_2}| = M_{t_1} - |x_{t_2+1} - x_{t_2}| + |x_{t_2+1} - x_{t_1}| \quad (30)$$

when x_{t_1} is between x_{t_2} and x_{t_2+1} , which, together with (28) results in

$$M_{t_1} - |x_{t_1} - x_{t_2}| \geq M_{t_2}. \quad (31)$$

Thus, M_{t_1} breaks the condition in (27), which concludes the proof. \square

IV. COMPLEXITY ANALYSIS

In this section, we analyze the computational complexity of our optimal trimming. We analyze the number of surviving equivalence classes since the computational complexity per time is linearly dependent on that. While the complexity is straightforward to see for periodic signals, random processes need more analysis.

A. Uniform i.i.d. Process

Let x_t be a uniform i.i.d. process such that $x_t \sim U([0, 1])$, i.e., $f(x) = 1$ for $x \in [0, 1]$ and 0 otherwise.

Corollary 1. *For a uniform i.i.d. process, the expected computational complexity of our algorithm is $O(\log T)$ per time.*

Proof. At any arbitrary time T , let $\tau = T - t$ be the number of samples that come after x_t . From Theorem 1, the only way M_t will survive at time T is if all the samples $x_{t'+t}$ are in $[0, x_t]$ or in $(x_t, 1]$. Thus, the probability that M_t survives is

$$P_t = x_t^\tau + (1 - x_t)^\tau, \quad (32)$$

where $\tau = T - t$. Since the survival is a Bernoulli trial with P_t , the expected survivability z_t of M_t is

$$z_t \triangleq \mathbb{E}_{x_t}[P_t], \quad (33)$$

$$= \int_0^1 (x_t^\tau + (1 - x_t)^\tau) dx_t, \quad (34)$$

$$= \left(\frac{x_t^{\tau+1}}{\tau+1} - \frac{(1-x_t)^{\tau+1}}{\tau+1} \right) \Big|_0^1, \quad (35)$$

$$= \frac{2}{\tau+1}. \quad (36)$$

Hence, the expected number of survivors S_T at time T is

$$S_T = O(\log T), \quad (37)$$

which concludes the proof. \square

B. Arbitrary i.i.d. Process

Let $x_t \in \mathfrak{R}$ be i.i.d. with $x_t \sim \mathcal{D}$ for some distribution \mathcal{D} . Let its probability density function (PDF) be $f(x)$ and its cumulative distribution function (CDF) be $F(x)$.

Corollary 2. *For an arbitrary i.i.d. process, the expected complexity of our algorithm is $O(\log T)$ per time.*

Proof. For M_t to survive, we again need all of the upcoming samples $x_{t'+t}$ be strictly less or more than x_t . Thus, the probability of survival is

$$P_t = (F(x_t))^\tau + (1 - F(x_t))^\tau, \quad (38)$$

and its expectation is

$$z_t = \int_{\mathfrak{R}} f(x_t) P_t dx_t, \quad (39)$$

$$= \int_{\mathfrak{R}} f(x_t) [(F(x_t))^\tau + (1 - F(x_t))^\tau] dx_t, \quad (40)$$

$$= \int_0^1 [(F)^\tau + (1 - F)^\tau] dF, \quad (41)$$

$$= \frac{2}{t+1}. \quad (42)$$

Hence, the expected number of survivals at T is $O(\log T)$. \square

C. Simple Symmetric Random Walk

Let x_t be a simple symmetric random walk, where the successive difference

$$\delta_t \triangleq x_t - x_{t-1}, \quad (43)$$

is an unbiased random variable in $\{-1, 1\}$, i.e.,

$$\delta_t = \begin{cases} +1, & \text{with probability } 0.5 \\ -1, & \text{with probability } 0.5 \end{cases}. \quad (44)$$

Corollary 3. *For a simple symmetric lattice random walk with step size 1, we have $O(\sqrt{T})$ complexity.*

Proof. At time T , the survivability given x_T , z_t , of M_t is again the sum of the probabilities of x_t being greater or less than all of the following samples, which is given by

$$z_t = \begin{cases} \mathbb{P}(x_\tau > x_t; t < \tau \leq T), & x_T > x_t \\ \mathbb{P}(x_\tau < x_t; t < \tau \leq T), & x_T < x_t \end{cases}, \quad (45)$$

where $\mathbb{P}(\cdot)$ is the probability operator. From the Ballot theorem [94], we have

$$z_t = \frac{|x_T - x_t|}{T - t}. \quad (46)$$

Since the sum $\sum_{t'=t+1}^T \delta_{t'}$ converges in distribution to a Gaussian with variance $T - t$, the expectation of its absolute is $O(\sqrt{T - t})$. Thus, the total number of expected survivors S_T at T is

$$S_T = O(\sqrt{T}), \quad (47)$$

which concludes the proof. \square

Remark 1. *The complexity bound will be the same for any arbitrary step size δ since we only compare whether the values x_t are greater (or less) than the following samples $x_{\tau > t}$.*

D. General Symmetric Random Walk

Let x_t be a random walk, where the successive difference

$$\delta_t \triangleq x_t - x_{t-1}, \quad (48)$$

is an unbiased, finite variance random variable with a distribution \mathcal{D} , i.e.,

$$\delta_t \sim \mathcal{D}, \quad \mathbb{E}[\delta_t] = 0, \quad \mathbb{E}[\delta_t^2] < \infty. \quad (49)$$

Corollary 4. *For a symmetric random walk with an unbiased, finite variance random step size δ , we have $O(\sqrt{T})$ complexity.*

Proof. Similarly to the simple random walk, the survivability z_t of M_t is

$$\mathbb{E}[s_t] = O\left(\frac{1}{\sqrt{T - t}}\right), \quad (50)$$

from the extended Ballot theorem [95]. Thus, the expected number of survivors at time T is

$$S_T = O(\sqrt{T}), \quad (51)$$

which concludes the proof. \square

E. All-time Maximum and Minimum

Another interesting setting is, let x_t be the all time maximum with probability p_t and all time minimum with probability q_t , i.e.,

$$\mathbb{P}(x_t \geq x_\tau; \tau < t) = p_t, \quad (52)$$

$$\mathbb{P}(x_t \leq x_\tau; \tau < t) = q_t, \quad (53)$$

where $\mathbb{P}(\cdot)$ is again the probability operator.

Corollary 5. *If at any time t , x_t is the all time maximum with probability p_t and all time minimum with probability q_t , where p_t and q_t are nonincreasing, i.e., $p_t \leq p_{t-1}$, $q_t \leq q_{t-1}$; the expected number of survivors is*

$$S_T = O(p_T^{-1} + q_T^{-1}). \quad (54)$$

Proof. At time T , let t_1 be the last time we get an all time maximum and t_2 be the last time we get an all time minimum. Then, the number of surviving sequences are bounded by

$$\sum_{t=1}^T z_t \leq \max(t'_{1,T}, t'_{2,T}) \leq t'_{1,T} + t'_{2,T}, \quad (55)$$

where $t'_{1,T} \triangleq T - t_1$ and $t'_{2,T} \triangleq T - t_2$. Since the all time maximum and minimum probabilities are p_t and q_t . Then, at time T , the expectation of $t'_{1,T}$ is

$$\mathbb{E}[t'_{1,T}] = p_T + 2(1 - p_T)p_{T-1} \quad (56)$$

$$+ 3(1 - p_T)(1 - p_{T-1})p_{T-2} \dots, \\ \leq 1 + (1 - p_T) + (1 - p_T)(1 - p_{T-1}) + \dots, \quad (57)$$

where we have the following recursion

$$\mathbb{E}[t'_{1,T}] \leq 1 + (1 - p_T)\mathbb{E}[t'_{1,T-1}], \quad (58)$$

and a similar recursion for $t'_{2,T}$ as well. Thus,

$$\mathbb{E}[t'_{1,T}] \leq \sum_{i=0}^T (1 - p_T)^i \leq \frac{1}{p_T}, \quad (59)$$

for nonincreasing p_t (similarly for $\mathbb{E}[t'_{2,T}]$ and q_T), which concludes the proof. \square

V. CONCLUSION

In this paper, we proposed a nonparametric approach that can be used in envelope extraction, peak-burst detection and clustering in time series. Our proposed problem formulation naturally defines a splitting/forking of the time series, which can be used for various applications in machine learning, signal processing and mathematically finance (with a possibly hierarchical implementation via successive application of our method to the generated forks). We proposed an algorithm that sequentially creates two signals (one upper bounding and one lower bounding signal) from an incoming input signal by minimizing the cumulative L_1 drift. We showed that a solution can be efficiently calculated by use of a Viterbi-like path tracking algorithm and in many interesting settings, our algorithm has low time complexities.

REFERENCES

- [1] P. Hall, L. Peng, and Q. Yao, "Moving-maximum models for extrema of time series," *Journal of statistical planning and inference*, vol. 103, no. 1-2, pp. 51–63, 2002.
- [2] E. Fink and H. S. Gandhi, "Compression of time series by extracting major extrema," *Journal of Experimental & Theoretical Artificial Intelligence*, vol. 23, no. 2, pp. 255–270, 2011.
- [3] P. K. Vemulapalli, V. Monga, and S. N. Brennan, "Robust extrema features for time-series data analysis," *IEEE transactions on pattern analysis and machine intelligence*, vol. 35, no. 6, pp. 1464–1479, 2012.
- [4] M. A. Tayfun and J.-M. Lo, "Wave envelope and related spectra," *Journal of waterway, port, coastal, and ocean engineering*, vol. 115, no. 4, pp. 515–533, 1989.
- [5] G. Palshikar *et al.*, "Simple algorithms for peak detection in time-series," in *Proc. 1st Int. Conf. Advanced Data Analysis, Business Analytics and Intelligence*, vol. 122, 2009.
- [6] S. Kadambe, R. Murray, and G. F. Boudreaux-Bartels, "Wavelet transform-based qrs complex detector," *IEEE Transactions on Biomedical Engineering*, vol. 46, no. 7, pp. 838–848, 1999.
- [7] R. D. Donchian, "Commodities: High finance in copper," *Financial Analysts Journal*, vol. 16, no. 6, pp. 133–142, 1960.
- [8] K. R. Coombes, S. Tsavachidis, J. S. Morris, K. A. Baggerly, M.-C. Hung, and H. M. Kuerer, "Improved peak detection and quantification of mass spectrometry data acquired from surface-enhanced laser desorption and ionization by denoising spectra with the undecimated discrete wavelet transform," *Proteomics*, vol. 5, no. 16, pp. 4107–4117, 2005.
- [9] V. T. Jordanov and D. L. Hall, "Digital peak detector with noise threshold," in *2002 IEEE Nuclear Science Symposium Conference Record*, vol. 1. IEEE, 2002, pp. 140–142.
- [10] K. Harmer, G. Howells, W. Sheng, M. Fairhurst, and F. Deravi, "A peak-threshold detection algorithm based on momentum," in *2008 Congress on Image and Signal Processing*, vol. 4. IEEE, 2008, pp. 454–458.
- [11] M. Ma, A. Van Genderen, and P. Beukelman, "Developing and implementing peak detection for real-time image registration," in *Proceedings of the 16th Annual Workshop on Circuits, Systems & Signal Processing (ProRISC2005)*. Citeseer, 2005, pp. 641–652.
- [12] K. Gokcesu, M. Ergeneçi, E. Ertan, and H. Gokcesu, "An adaptive algorithm for online interference cancellation in emg sensors," *IEEE Sensors Journal*, vol. 19, no. 1, pp. 214–223, 2018.
- [13] I. Azzini, R. Dell'Anna, F. Ciocchetta, F. Demichelis, A. Sboner, E. Blanzieri, and A. Malossini, "Simple methods for peak detection in time series microarray data," *Proc. CAMDA'04 (Critical Assessment of Microarray Data)*, 2004.
- [14] K. Gokcesu, M. Ergeneçi, E. Ertan, A. Z. Alkilani, and P. Kosmas, "An semg-based method to adaptively reject the effect of contraction on spectral analysis for fatigue tracking," in *Proceedings of the 2018 ACM International Symposium on Wearable Computers*, 2018, pp. 80–87.
- [15] Y. Zhu and D. Shasha, "Efficient elastic burst detection in data streams," in *Proceedings of the ninth ACM SIGKDD international conference on Knowledge discovery and data mining*, 2003, pp. 336–345.
- [16] K. Gokcesu and H. Gokcesu, "Optimally efficient sequential calibration of binary classifiers to minimize classification error," *arXiv preprint arXiv:2108.08780*, 2021.
- [17] J.-G. Choi, J.-K. Park, K.-H. Kim, and J.-C. Kim, "A daily peak load forecasting system using a chaotic time series," in *Proceedings of International Conference on Intelligent System Application to Power Systems*. IEEE, 1996, pp. 283–287.
- [18] K. Gokcesu, M. M. Neyshabouri, H. Gokcesu, and S. S. Kozat, "Sequential outlier detection based on incremental decision trees," *IEEE Transactions on Signal Processing*, vol. 67, no. 4, pp. 993–1005, 2018.
- [19] I. Delibalta, K. Gokcesu, M. Simsek, L. Baruh, and S. S. Kozat, "Online anomaly detection with nested trees," *IEEE Signal Processing Letters*, vol. 23, no. 12, pp. 1867–1871, 2016.
- [20] K. Gokcesu and S. S. Kozat, "Online anomaly detection with minimax optimal density estimation in nonstationary environments," *IEEE Transactions on Signal Processing*, vol. 66, no. 5, pp. 1213–1227, 2017.
- [21] M. Vlachos, C. Meek, Z. Vagena, and D. Gunopulos, "Identifying similarities, periodicities and bursts for online search queries," in *Proceedings of the 2004 ACM SIGMOD international conference on Management of data*, 2004, pp. 131–142.
- [22] K. Gokcesu and H. Gokcesu, "A generalized online algorithm for translation and scale invariant prediction with expert advice," *arXiv preprint arXiv:2009.04372*, 2020.
- [23] M. M. Neyshabouri, K. Gokcesu, H. Gokcesu, H. Ozkan, and S. S. Kozat, "Asymptotically optimal contextual bandit algorithm using hierarchical structures," *IEEE transactions on neural networks and learning systems*, vol. 30, no. 3, pp. 923–937, 2018.
- [24] K. Gokcesu and H. Gokcesu, "Recursive experts: An efficient optimal mixture of learning systems in dynamic environments," *arXiv preprint arXiv:2009.09249*, 2020.
- [25] M. Vlachos, K.-L. Wu, S.-K. Chen, and S. Y. Philip, "Correlating burst events on streaming stock market data," *Data Mining and Knowledge Discovery*, vol. 16, no. 1, pp. 109–133, 2008.
- [26] G. Jang, J. Kim, S. Lee, and Y. Choi, "Emg-based continuous control scheme with simple classifier for electric-powered wheelchair," *IEEE Transactions on Industrial Electronics*, vol. 63, no. 6, pp. 3695–3705, 2016.
- [27] K. Gokcesu and H. Gokcesu, "Generalized huber loss for robust learning and its efficient minimization for a robust statistics," *arXiv preprint arXiv:2108.12627*, 2021.
- [28] R. N. Bracewell and R. N. Bracewell, *The Fourier transform and its applications*. McGraw-Hill New York, 1986, vol. 31999.
- [29] M. S. Longuet-Higgins, "Statistical properties of wave groups in a random sea state," *Philosophical Transactions of the Royal Society of London. Series A, Mathematical and Physical Sciences*, vol. 312, no. 1521, pp. 219–250, 1984.
- [30] M. K. Ochi and I. I. Sahinoglu, "Stochastic characteristics of wave groups in random seas: Part 1-time duration of and number of waves in a wave group," *Applied Ocean Research*, vol. 11, no. 1, pp. 39–50, 1989.
- [31] M. A. Tayfun, "Nonlinear effects of the distribution of amplitudes of sea waves," *Ocean engineering*, vol. 11, no. 3, pp. 245–264, 1984.
- [32] F. Tiecheng, W. Shanqin, and L. Zhenhua, "Real time prediction of motions of ocean platforms in waves [j]," *The Ocean Engineering*, vol. 3, 1991.
- [33] S. O. Rice, "Mathematical analysis of random noise," *The Bell System Technical Journal*, vol. 23, no. 3, pp. 282–332, 1944.
- [34] —, "Mathematical analysis of random noise," *The Bell System Technical Journal*, vol. 24, no. 1, pp. 46–156, 1945.
- [35] Z.-s. Fang and N. Xie, "An analysis of various methods for computing the envelope of a random signal," *Applied ocean research*, vol. 17, no. 1, pp. 9–19, 1995.
- [36] L. Chen and Y. Hao, "Feature extraction and classification of ehg between pregnancy and labour group using hilbert-huang transform and extreme learning machine," *Computational and mathematical methods in medicine*, vol. 2017, 2017.
- [37] T. D'Alessio and S. Conforto, "Extraction of the envelope from surface emg signals," *IEEE Engineering in Medicine and Biology Magazine*, vol. 20, no. 6, pp. 55–61, 2001.
- [38] H. Xie and Z. Wang, "Mean frequency derived via hilbert-huang transform with application to fatigue emg signal analysis," *Computer methods and programs in biomedicine*, vol. 82, no. 2, pp. 114–120, 2006.
- [39] R. Kleissen and G. Zilvold, "Estimation uncertainty in ensemble averaged surface emg profiles during gait," *Journal of Electromyography and Kinesiology*, vol. 4, no. 2, pp. 83–94, 1994.
- [40] S. Márquez-Figueroa, Y. S. Shmaliy, and O. Ibarra-Manzano, "Analysis and smoothing of emg signal envelope using kalman and ufir filtering under colored measurement noise," in *MATEC Web of Conferences*, vol. 292. EDP Sciences, 2019, p. 04002.
- [41] C. H. Yeh, H. W. V. Young, C. Y. Wang, Y. H. Wang, P. L. Lee, J. H. Kang, and M. T. Lo, "Quantifying spasticity with limited swinging cycles using pendulum test based on phase amplitude coupling," *IEEE Transactions on Neural Systems and Rehabilitation Engineering*, vol. 24, no. 10, pp. 1081–1088, 2016.
- [42] L. Myers, M. Lowery, M. O'malley, C. Vaughan, C. Heneghan, A. S. C. Gibson, Y. Harley, and R. Sreenivasan, "Rectification and non-linear pre-processing of emg signals for cortico-muscular analysis," *Journal of neuroscience methods*, vol. 124, no. 2, pp. 157–165, 2003.
- [43] T. J. Roberts and A. M. Gabaldón, "Interpreting muscle function from emg: lessons learned from direct measurements of muscle force," *Integrative and comparative biology*, vol. 48, no. 2, pp. 312–320, 2008.
- [44] Y. Zhan, S. Guo, K. M. Kendrick, and J. Feng, "Filtering noise for synchronised activity in multi-trial electrophysiology data using wiener and kalman filters," *BioSystems*, vol. 96, no. 1, pp. 1–13, 2009.
- [45] N. M. López, F. di Sciascio, C. M. Soria, and M. E. Valentinuzzi, "Robust emg sensing system based on data fusion for myoelectric control of a robotic arm," *Biomedical engineering online*, vol. 8, no. 1, pp. 1–13, 2009.
- [46] C. S. L. Tsui, J. Q. Gan, and S. J. Roberts, "A self-paced brain-computer interface for controlling a robot simulator: an online event labelling paradigm and an extended kalman filter based algorithm for online

- training," *Medical & biological engineering & computing*, vol. 47, no. 3, pp. 257–265, 2009.
- [47] L. L. Menegaldo, "Real-time muscle state estimation from emg signals during isometric contractions using kalman filters," *Biological cybernetics*, vol. 111, no. 5, pp. 335–346, 2017.
- [48] T. Triwiyanto, O. Wahyunggoro, H. A. Nugroho, and H. Herianto, "Muscle fatigue compensation of the electromyography signal for elbow joint angle estimation using adaptive feature," *Computers & Electrical Engineering*, vol. 71, pp. 284–293, 2018.
- [49] Y. S. Shmaliy, S. Zhao, and C. K. Ahn, "Unbiased finite impulse response filtering: An iterative alternative to kalman filtering ignoring noise and initial conditions," *IEEE Control Systems Magazine*, vol. 37, no. 5, pp. 70–89, 2017.
- [50] Y. S. Shmaliy, F. Lehmann, S. Zhao, and C. K. Ahn, "Comparing robustness of the kalman, H_∞ , and ufr filters," *IEEE Transactions on Signal Processing*, vol. 66, no. 13, pp. 3447–3458, 2018.
- [51] G. Nijm, A. V. Sahakian, S. Swiryn, and A. C. Larson, "Comparison of signal peak detection algorithms for self-gated cardiac cine mri," in *2007 Computers in Cardiology*. IEEE, 2007, pp. 407–410.
- [52] P. Du, W. A. Kibbe, and S. M. Lin, "Improved peak detection in mass spectrum by incorporating continuous wavelet transform-based pattern matching," *bioinformatics*, vol. 22, no. 17, pp. 2059–2065, 2006.
- [53] E. Lange, C. Gröpl, K. Reinert, O. Kohlbacher, and A. Hildebrandt, "High-accuracy peak picking of proteomics data using wavelet techniques," in *Biocomputing 2006*. World Scientific, 2006, pp. 243–254.
- [54] P. J. M. Fard, M. Moradi, and M. Tajvidi, "A novel approach in r peak detection using hybrid complex wavelet (hcw)," *International Journal of Cardiology*, vol. 124, no. 2, pp. 250–253, 2008.
- [55] J. M. Gregoire, D. Dale, and R. B. Van Dover, "A wavelet transform algorithm for peak detection and application to powder x-ray diffraction data," *Review of Scientific Instruments*, vol. 82, no. 1, p. 015105, 2011.
- [56] Z. Nenadic and J. W. Burdick, "Spike detection using the continuous wavelet transform," *IEEE transactions on Biomedical Engineering*, vol. 52, no. 1, pp. 74–87, 2004.
- [57] O. Singh and R. K. Sunkaria, "A robust r-peak detection algorithm using wavelet packets," *Int. J. Comput. Appl.*, vol. 36, pp. 37–43, 2011.
- [58] J. Pan and W. J. Tompkins, "A real-time qrs detection algorithm," *IEEE transactions on biomedical engineering*, no. 3, pp. 230–236, 1985.
- [59] A. Jacobson, "Auto-threshold peak detection in physiological signals," in *2001 Conference Proceedings of the 23rd Annual International Conference of the IEEE Engineering in Medicine and Biology Society*, vol. 3. IEEE, 2001, pp. 2194–2195.
- [60] J. Excoffier and G. Guiochon, "Automatic peak detection in chromatography," *Chromatographia*, vol. 15, no. 9, pp. 543–545, 1982.
- [61] D. Benitez, P. Gaydecki, A. Zaidi, and A. Fitzpatrick, "The use of the hilbert transform in ecg signal analysis," *Computers in biology and medicine*, vol. 31, no. 5, pp. 399–406, 2001.
- [62] H. Rabbani, M. P. Mahjoob, E. Farahabadi, and A. Farahabadi, "R peak detection in electrocardiogram signal based on an optimal combination of wavelet transform, hilbert transform, and adaptive thresholding," *Journal of medical signals and sensors*, vol. 1, no. 2, p. 91, 2011.
- [63] Q. Xue, Y. H. Hu, and W. J. Tompkins, "Neural-network-based adaptive matched filtering for qrs detection," *IEEE Transactions on biomedical Engineering*, vol. 39, no. 4, pp. 317–329, 1992.
- [64] G. Vijaya, V. Kumar, and H. Verma, "Ann-based qrs-complex analysis of ecg," *Journal of medical engineering & technology*, vol. 22, no. 4, pp. 160–167, 1998.
- [65] N. Mtetwa and L. S. Smith, "Smoothing and thresholding in neuronal spike detection," *Neurocomputing*, vol. 69, no. 10–12, pp. 1366–1370, 2006.
- [66] V. P. Andreev, T. Rejtar, H.-S. Chen, E. V. Moskovets, A. R. Ivanov, and B. L. Karger, "A universal denoising and peak picking algorithm for lc-ms based on matched filtration in the chromatographic time domain," *Analytical chemistry*, vol. 75, no. 22, pp. 6314–6326, 2003.
- [67] F. Zhang and Y. Lian, "Qrs detection based on multiscale mathematical morphology for wearable ecg devices in body area networks," *IEEE Transactions on Biomedical Circuits and Systems*, vol. 3, no. 4, pp. 220–228, 2009.
- [68] —, "Qrs detection based on morphological filter and energy envelope for applications in body sensor networks," *Journal of Signal Processing Systems*, vol. 64, no. 2, pp. 187–194, 2011.
- [69] Y. Sun, S. Suppappola, and T. A. Wrublewski, "Microcontroller-based real-time qrs detection," *Biomedical instrumentation & technology*, vol. 26, no. 6, pp. 477–484, 1992.
- [70] Y. Ferdi, J. Herbeuval, A. Charef, and B. Boucheham, "R wave detection using fractional digital differentiation," *Ithm-Rbm*, vol. 24, no. 5–6, pp. 273–280, 2003.
- [71] M. Aboy, J. McNames, T. Thong, D. Tsunami, M. S. Ellenby, and B. Goldstein, "An automatic beat detection algorithm for pressure signals," *IEEE Transactions on Biomedical Engineering*, vol. 52, no. 10, pp. 1662–1670, 2005.
- [72] B. Shim, H. Min, and S. Yoon, "Nonlinear preprocessing method for detecting peaks from gas chromatograms," *BMC bioinformatics*, vol. 10, no. 1, pp. 1–10, 2009.
- [73] A. T. Tzallas, V. P. Oikonomou, and D. I. Fotiadis, "Epileptic spike detection using a kalman filter based approach," in *2006 international conference of the IEEE engineering in medicine and biology society*. IEEE, 2006, pp. 501–504.
- [74] N. Nguyen, H. Huang, S. Oraintara, and A. Vo, "Peak detection in mass spectrometry by gabor filters and envelope analysis," *Journal of bioinformatics and computational biology*, vol. 7, no. 03, pp. 547–569, 2009.
- [75] M. J. Fredriksson, P. Petersson, B.-O. Axelsson, and D. Bylund, "An automatic peak finding method for lc-ms data using gaussian second derivative filtering," *Journal of separation science*, vol. 32, no. 22, pp. 3906–3918, 2009.
- [76] K.-P. Lin and W. H. Chang, "Qrs feature extraction using linear prediction," *IEEE Transactions on Biomedical Engineering*, vol. 36, no. 10, pp. 1050–1055, 1989.
- [77] K. I. Panoulas, L. J. Hadjileontiadis, and S. M. Panas, "Enhancement of r-wave detection in ecg data analysis using higher-order statistics," in *2001 Conference Proceedings of the 23rd Annual International Conference of the IEEE Engineering in Medicine and Biology Society*, vol. 1. IEEE, 2001, pp. 344–347.
- [78] S. Mehta, D. Shete, N. Lingayat, and V. Chouhan, "K-means algorithm for the detection and delineation of qrs-complexes in electrocardiogram," *Irbm*, vol. 31, no. 1, pp. 48–54, 2010.
- [79] S. Sharma, S. Mehta, and H. Mehta, "Development of derivative based algorithm for the detection of qrs-complexes in single lead electrocardiogram using fcm," *IJCA Special Issue on Electronics, Information and Communication Engineering ICEICE*, no. 4, 2011.
- [80] Z.-E. H. Slimane and A. Naït-Ali, "Qrs complex detection using empirical mode decomposition," *Digital Signal Processing*, vol. 20, no. 4, pp. 1221–1228, 2010.
- [81] D. A. Coast, R. M. Stern, G. G. Cano, and S. A. Briller, "An approach to cardiac arrhythmia analysis using hidden markov models," *IEEE Transactions on biomedical Engineering*, vol. 37, no. 9, pp. 826–836, 1990.
- [82] M. I. Sezan, "A peak detection algorithm and its application to histogram-based image data reduction," *Computer vision, graphics, and image processing*, vol. 49, no. 1, pp. 36–51, 1990.
- [83] K. H. Jarman, D. S. Daly, K. K. Anderson, and K. L. Wahl, "A new approach to automated peak detection," *Chemometrics and intelligent laboratory systems*, vol. 69, no. 1–2, pp. 61–76, 2003.
- [84] H. Deng, B. Xiang, X. Liao, and S. Xie, "A linear modulation-based stochastic resonance algorithm applied to the detection of weak chromatographic peaks," *Analytical and bioanalytical chemistry*, vol. 386, no. 7, pp. 2199–2205, 2006.
- [85] S. Mukhopadhyay and G. Ray, "A new interpretation of nonlinear energy operator and its efficacy in spike detection," *IEEE Transactions on biomedical engineering*, vol. 45, no. 2, pp. 180–187, 1998.
- [86] J. L. Treynor and R. Ferguson, "In defense of technical analysis," *The Journal of Finance*, vol. 40, no. 3, pp. 757–773, 1985.
- [87] W. Brock, J. Lakonishok, and B. LeBaron, "Simple technical trading rules and the stochastic properties of stock returns," *The Journal of finance*, vol. 47, no. 5, pp. 1731–1764, 1992.
- [88] B. Cowie and B. Irwin, "An evaluation of trading bands as indicators for network telescope datasets," *Proceedings of the SATNAC*, 2011.
- [89] B. John, "Bollinger on bollinger bands," 2002.
- [90] J. J. Murphy, *Study Guide to Technical Analysis of the Financial Markets: A Comprehensive Guide to Trading Methods and Applications*. Penguin, 1999.
- [91] J. Wilder, *New Concepts in Technical Trading Systems*. Trend Research, 1978.
- [92] F. Scholkmann, J. Boss, and M. Wolf, "An efficient algorithm for automatic peak detection in noisy periodic and quasi-periodic signals," *Algorithms*, vol. 5, no. 4, pp. 588–603, 2012.
- [93] A. Viterbi, "Error bounds for convolutional codes and an asymptotically optimum decoding algorithm," *IEEE transactions on Information Theory*, vol. 13, no. 2, pp. 260–269, 1967.
- [94] M. Renault, "Four proofs of the ballot theorem," *Mathematics magazine*, vol. 80, no. 5, pp. 345–352, 2007.
- [95] L. Addario-Berry and B. Reed, "Ballot theorems for random walks with finite variance," *arXiv preprint arXiv:0802.2491*, 2008.