

Near-Linear Time Algorithm with Near-Logarithmic Regret Per Switch for Mixable/Exp-Concave Losses

Kaan Gokcesu, Hakan Gokcesu

Abstract—We investigate the problem of online learning, which has gained significant attention in recent years due to its applicability in a wide range of fields from machine learning to game theory. Specifically, we study the online optimization of mixable loss functions with logarithmic static regret in a dynamic environment. The best dynamic estimation sequence that we compete against is selected in hindsight with full observation of the loss functions and is allowed to select different optimal estimations in different time intervals (segments). We propose an online mixture framework that uses these static solvers as the base algorithm. We show that with the suitable selection of hyper-expert creations and weighting strategies, we can achieve logarithmic and squared logarithmic regret per switch in quadratic and linearithmic computational complexity, respectively. For the first time in literature, we show that it is also possible to achieve near-logarithmic regret per switch with sub-polynomial complexity per time. Our results are guaranteed to hold in a strong deterministic sense in an individual sequence manner.

I. INTRODUCTION

In machine learning literature [1], [2], the problems of online learning, prediction and estimation [3]–[5] are heavily investigated because of their applications in a wide variety of fields including decision theory [6], game theory [7], [8], control theory [9], optimization [10], [11], density estimation or source coding [12]–[15], anomaly detection [16], adversarial bandits [17]–[21], prediction [22], [23] and signal processing [24]–[26].

A. Online Learning

In online learning, at each time t of the decision process, we make a prediction θ_t and incur a corresponding loss [4]. Since the loss functions at each round of the decision process may differ, they are generally denoted as a time varying process, i.e., the loss incurred is $l_t(\theta_t)$. As opposed to the batch learning setting, we need to produce these decision θ_t sequentially, where each prediction θ_t can only depend on our past predictions $\{\theta_\tau\}_{\tau=1}^{t-1}$ and their corresponding observations (i.e., the predictions are made before observing the resulting loss). Depending on the problem setting, we may either have access to the whole description of the losses $l_t(\cdot)$, only their evaluations $l_t(\theta_t)$ or some other auxiliary information such as the gradient ∇l_t or the Hessian $\nabla^2 l_t$. The goal is to create the predictions θ_t in such a way that we minimize the cumulative loss incurred, i.e., $\sum_{t=1}^T l_t(\theta_t)$. This phenomena can be better understood by the online portfolio management problem [27]. In the online portfolio management, the equity at hand is distributed among several stocks at time t . However, we cannot see the reward (or the loss) of this action until we see the price changes in the stock market. Hence, the decisions need to be made sequentially in an online manner.

B. Mixable Losses

There is a myriad of different losses utilized in the literature and they are generally classified according to some nice properties they possess, which helps the learning process. For example, because of its general applicability to different problem scenarios and relatively straightforward solutions, convex losses has been extremely popular in the online learning literature [28]. However, this applicability, which stems from its comparatively milder conditions, may result in slow learning. Some stricter conditions have been studied starting with the notion of strong-convexity for faster convergence in online learning literature [29]. However, while these losses result in a much faster learning, their conditions can become too strict and limit their applicability [4], [5]. To this end, the conditions of the strong-convexity have been loosened by the notion of mixability [30]. When a loss $l(\cdot)$ is α -mixable, they conform to the following definition.

Definition 1. $l(\theta)$ is α -mixable in θ if we have

$$e^{-\alpha l(\hat{\theta})} \geq \sum_i P_i e^{-\alpha l(\theta_i)}$$

where $\{P_i\}_{i=1}^n$ is some probability distribution and

$$\hat{\theta} = F(\{\theta_i, P_i\}_{i=1}^n),$$

for a surrogate function $F(\cdot)$.

The surrogate function or mixture rule $F(\cdot)$ in Definition 1 is specific for different losses. Few examples are as follows.

Example 1. The square loss function, where $\theta \in [-1, 1]$, and $l(\theta) = (\theta - x)^2$ (for some x) is mixable with $\alpha = \frac{1}{2}$ [30], [31], where

$$\hat{\theta} = \frac{1}{2} \sum_{q=-1}^1 q \log \left(\sum_{i=1}^n P_i e^{-\frac{1}{2}(\theta_i - q)^2} \right)$$

is the aggregate estimation.

Example 2. Density estimation (or source coding) under log-loss [13] is 1-mixable with the estimator

$$\hat{\theta} = \sum_i P_i \theta_i,$$

where the mixability inequality holds with equality.

Example 3. Exp-concave loss functions [32] are mixable, where λ -exp-concave loss is λ -mixable with the mean estimator as in Example 2 since

$$e^{-\lambda l(\hat{\theta}, x)} \geq \sum_i P_i e^{-\lambda l(\theta_i, x)},$$

from the exp-concavity.

C. Notion of Regret and Oracle

In the problem of online learning, the loss functions can be arbitrarily high and achieving small losses may be quite challenging if not impossible. To this end, it has been the norm to aim for a loss as much as a viable competition [4]. Although infeasible, we can achieve the best performance when we make the decisions with full knowledge of the losses in advance. To this end, the challenge is to get as close as possible to that best performance, which is called the oracle loss. Hence, the notion of regret has been used in a competitive framework. The notion of regret is defined as the difference between the losses incurred by an algorithm and the losses incurred by a competition oracle. Against the oracle selections $\{\theta_t^*\}_{t=1}^T$, the cumulative regret up to time T is given by

$$R_T \triangleq \sum_{t=1}^T r_t = \sum_{t=1}^T l_t(\theta_t) - \sum_{t=1}^T l_t(\theta_t^*). \quad (1)$$

Note that, we can not achieve small regret against arbitrary oracle selections and some form of regularity needs to be applied. One example is the fixed oracle (static), where we compete against a fixed estimation θ^* , i.e., $\theta_t^* = \theta^*$ for all t . The literature on these static learners is abundant and its applications are numerous [4]. In our work, we are specifically interested in the static learners with logarithmic regret bounds, i.e., $R_T = O(\log(T))$ such as [11], [30]. A harder competition would be against dynamically switching oracle estimations, where θ_t^* can change arbitrarily during a time horizon T . In this setting, the static learners are prone to stagnation and different strategies are utilized [33]–[37].

D. Competing Against Dynamically Switching Estimations

Although static learners are able to perform satisfactorily when competing against fixed oracles, they can under-perform when competing against dynamically changing oracle predictions. In some problem settings, making a static learner adaptive is pretty straightforward in lieu of parameter tuning such as online convex optimization [10]. However, it is not the case for other problem scenarios [4], [5]. For this purpose, there are various approaches in literature.

The sleeping experts in [38] starts by creating a pool of hyper-experts, each of which mimics the learner's behavior (final output) during the first $t - 1$ rounds (i.e., they are specialist experts [39] that abstains from prediction up to time t). Each expert provides predictions from time t onward and combined for adaptivity to create the final output estimations. These sleeping experts can be generalized to use different time selection functions as well [36]. The restarting experts in [37] utilizes a main base algorithm and start a copy of it each time t . Then, by aggregating the predictions of these copies, the final output predictions are produced and adaptivity is achieved. It has been shown that, both of these approaches reduce to the Fixed Share algorithm [40] with variable switching rates. The recursive experts in [41] creates the prediction outputs recursively by mixing a static expert, i.e., a single run of the base algorithm, with a dynamic expert, i.e., subsequent reruns of the base algorithm, recursively.

Therefore, the final predictions are constructed by selecting a set of time intervals which run a base algorithm and aggregating their individual predictions. The design of the time intervals requires care. While the set of intervals should be large enough to cover the whole time horizon sufficiently, they should not number too many, which may substantially increase the computational complexity. In the works of [42], [43], the authors developed ways to construct intervals by trading effectiveness with efficiency. The geometric interval selections (generally powers of 2) has become popular for efficient coverage of the time horizon [44]–[46]. Moreover, aggregation itself is a heavily investigated topic and there are techniques like Exponential Weights Algorithm (EWA) and Multiplicative Weights Algorithm (MWA) [44], [47]–[49].

E. Contributions and Organization

For the mixable losses, the optimal achievable regret stems from knowing the time instances the competition changes and individually learning them. With universal prediction and mixture techniques, it is possible to achieve this optimal regret bounds up to a finite multiplicative redundancy. Even so, these approaches have linear per time (or quadratic) computational complexities, which is inefficient. To this end, efficient time interval selections and their merger have been studied such as geometric coverage techniques. In spite of their efficient logarithmic per time (linearithmic) computational complexities, their regret bounds may become sub-optimal when the static problem has logarithmic regret. Thus, our goal is to combine the best of both worlds and design algorithms that are as efficient as possible whilst having near optimal regret. While the work in [50] specifically studies this problem of dynamic regret under mixable losses, their results are most meaningful when the base algorithm regret is sub-logarithmic or super-logarithmic. In this work, we bridge this gap.

1) *Problem Description*: In Section II, we provide some useful preliminaries; which include the mathematical formulations of the static and dynamic problems together with a general static solver, which will be utilized as a base algorithm.

2) *Algorithmic Framework*: In Section III, we provide the algorithmic framework, which incorporates a hyper-expert scheme (that runs the base algorithm) and a weighting scheme (their aggregation method). We also provide some important definitions for the regret analysis.

3) *Algorithm Design*: In Section IV, we provide generalized designs for the hyper expert scheme and the weighting scheme to compete against dynamically changing estimations. We also analyze their computational complexity and regret.

4) *Inefficient Optimal*: In Section V, we provide a quadratic time algorithm that can achieve optimal regret bounds much like [13], [14], [50].

5) *Efficient Sub-optimal*: In Section VI, we provide a linearithmic time algorithm that can achieve sub-optimal regret bounds as in [37], [41], [50]

6) *Efficient Near-Optimal*: In Section VII, for the first time in literature, we provide a near linear time algorithm that can achieve near-optimal regret bounds.

7) *Conclusion*: In Section VIII, we finish with some concluding remarks.

II. PROBLEM DESCRIPTION

In this section, we mathematically describe the problems when we compete against a static (fixed) and a dynamic (changing) oracle estimations similar to [41], [50]. We also introduce a generic base algorithm as a building block.

A. Logarithmic Regret Base Algorithm for the Static Problem

We start by first tackling the static problem setting. Let θ_t be some estimation we produce at the time t , and let

$$\theta_1^T \triangleq \{\theta_1, \dots, \theta_T\} \quad (2)$$

be our estimations for the whole time horizon, i.e., from $t = 1$ to T . Let $l_t(\theta_t)$ be a finite loss we incur from our estimation θ_t and the cumulative loss for the time horizon be given by

$$L_T(\theta_1^T) \triangleq \sum_{t=1}^T l_t(\theta_t). \quad (3)$$

Let θ^* be the best fixed estimation chosen in hindsight, i.e.,

$$\theta^* = \arg \min_{\theta} \sum_{t=1}^T l_t(\theta), \quad (4)$$

and its cumulative loss in the time horizon be given by

$$L_T(\theta^*) \triangleq \sum_{t=1}^T l_t(\theta^*). \quad (5)$$

The regret of the static problem is given by the difference of these cumulative losses in (3) and (5), i.e.,

$$R(T, \theta^*) \triangleq L_T(\theta_1^T) - L_T(\theta^*). \quad (6)$$

Let us have an algorithm (building block) that can solve the static problem. The base algorithm creates its estimation θ_t and incurs the corresponding loss $l_t(\theta_t)$ at time t . After that, it sequentially updates its estimation such that θ_{t+1} is a function of the past estimations $\{\theta_t, \theta_{t-1}, \dots, \theta_1\}$, losses $\{l_t(\theta_t), l_{t-1}(\theta_{t-1}), \dots, l_1(\theta_1)\}$ and possibly some auxiliary parameters $\{\lambda_t, \dots, \lambda_1\}$. The update is formally given by

$$\theta_{t+1} = f(\theta_t, \dots, \theta_1; l_t(\theta_t), \dots, l_1(\theta_1); \lambda_t, \dots, \lambda_1). \quad (7)$$

Note that, the update function $f(\cdot)$ depends on the structure of the base algorithm and the underlying problem setting (i.e., can vary in distinct applications). In sequential updates, the next estimation θ_{t+1} depends only on the current estimation and the algorithm's current state, i.e., it is given by

$$\theta_{t+1} = f_t(\theta_t), \quad (8)$$

for some $f_t(\cdot)$, which models the evolving algorithmic state (including the observations such as the loss). A summary is given in Algorithm 1. We make the following assumption about the algorithm in Algorithm 1.

Assumption 1. For the problem in (6), Algorithm 1 has logarithmic regret bounds, i.e.,

$$R_{Base}(T) = O(\log(T)),$$

for any T , where $O(\cdot)$ denotes the big- O notation, i.e., asymptotically, $R_{Base}(T) \leq K \log(T)$ for some finite K .

As opposed to the polynomial [41] or generic [50] regret, we specifically study logarithmic regret base algorithms.

Algorithm 1 The Base Algorithm

- 1: Initialize internal parameters, θ_1
 - 2: **for** $t = 1, 2, \dots$ **do**
 - 3: Observe $\lambda_t, l_t(\theta_t)$
 - 4: Determine $f_t(\cdot)$
 - 5: Update $\theta_{t+1} = f_t(\theta_t)$
 - 6: **end for**
-

B. The Dynamic Problem and Its Achievable Regret Bound

Here, we explain the dynamic version of the static problem in (6). While our estimations θ_1^T in (2) and their cumulative loss $L_T(\theta_1^T)$ in (3) are as before, the competition differs. Instead of a fixed estimation, let us compete against a dynamically changing estimation. Let S denote the number of times the competing estimations θ^* change throughout the time horizon T . Let us define θ_s^* for $s \in \{1, \dots, S\}$ as the competing estimations for individual distinct S time segments that cover the time horizon T . Let t_s denote the length of the s^{th} segment and T_s be the sum of $t_{s'}$ from $s' = 1$ to s (i.e., s^{th} segment ends on T_s). The expression in (5) changes as

$$L_T(\{\theta_s^*, t_s\}_{s=1}^S) = \sum_{s=1}^S \sum_{T_{s-1}+1}^{T_s} l_t(\theta_s^*), \quad (9)$$

where T_s is 0 for $s = 0$. Thus, our regret definition in (6) changes to

$$R(T, \{\theta_s^*, t_s\}_{s=1}^S) \triangleq L_T(\theta_1^T) - L_T(\{\theta_s^*, t_s\}_{s=1}^S). \quad (10)$$

Although, Algorithm 1 is able to compete against an optimal fixed parameter (the static problem), it may fail to compete against a dynamically changing estimation throughout the time horizon (the dynamic problem). For this problem, if we know of the time instances the competing parameter sequence changes (i.e., the exact times where we compete against distinct estimations θ_s^* for $s \in \{1, \dots, S\}$), we can use Algorithm 1 as it is and restart it at the beginning of these time segments. When the regret of the base algorithm for the static problem is as in Assumption 1. We have the following for the dynamic problem.

Remark 1. If we know the time instances T_s when the competition changes, we can restart Algorithm 1 in these times to get the regret bound

$$R_{Base}(T, S) = O\left(S \log\left(\frac{T}{S}\right)\right),$$

which, in general, is the best regret bound achievable with Algorithm 1 for the dynamic problem in (10).

Note that, irrespective of whether the base algorithm itself is optimal or not, the result in Remark 1 is the optimal regret achievable by using Algorithm 1. Furthermore, the number of changes S should be at least sub-linear (i.e., $o(T)$) for possibly viable learning, i.e., sub-linear regret bounds.

In some specific problem settings, it is straightforward to make a base algorithm adaptive to changes (such as the convex optimization [10]). However, for general learning systems, it is not trivial [4], [5], [41], [50]. In the next section, we will explain in detail how to incorporate this adaptivity.

III. ALGORITHMIC FRAMEWORK

A. Mixture of Hyper-Experts

The framework starts similarly to [50], where we use a hyper-expert scheme to create a set of experts that use the base algorithm in Algorithm 1.

Definition 2. The experts i are created from the base algorithm according to an hyper-expert scheme \mathcal{H} such that

$$\mathcal{H} : H(i) = \{\lambda_i\}, \quad \forall i, t, \quad (11)$$

where λ_i collectively defines the necessary information about how to utilize the base algorithm for the i^{th} expert (e.g., start and finish times of the individual runs of the base algorithm).

At any time t , let us have a set \mathcal{N}_t of parallel running hyper-experts, where each hyper-expert $i \in \mathcal{N}_t$ provides us with its parameter estimate $\theta_{i,t}$. To create our final estimate θ_t at time t , we combine their estimates $\theta_{i,t}$ with some mixture probability distribution $P_{i,t}$ (i.e., $\sum_{i \in \mathcal{N}_t} P_{i,t} = 1$) using the surrogate function $F(\cdot)$. Hence, θ_t is given by

$$\theta_t = F(\{\theta_{i,t}, P_{i,t}\}_{i \in \mathcal{N}_t}). \quad (12)$$

$P_{i,t}$ are given by the normalization of the weights $\tilde{P}_{i,t}$, i.e.,

$$P_{i,t} = \frac{\tilde{P}_{i,t}}{\sum_{j \in \mathcal{N}_t} \tilde{P}_{j,t}}, \quad \text{for } i \in \mathcal{N}_t. \quad (13)$$

Each hyper-expert weight $\tilde{P}_{i,t}$ is designed to be dependent on the past performance of that expert. Furthermore, we also mix these weights with each other to compete against a dynamically changing estimation sequence. The performance weights are recursively calculated with a telescoping rule as

$$\tilde{P}_{j,t} = \sum_{i \in \mathcal{N}_{t-1}} \tilde{P}_{i,t-1} e^{-\alpha l_{t-1}(\theta_{i,t-1})} \tau_t(i, j) \quad (14)$$

where $\tau_t(i, j)$ is the transition from the i^{th} to j^{th} hyper-expert.

Definition 3. The transition weights $\tau_t(i, j)$ for all (i, j, t) are collectively defined as a weighting scheme \mathcal{T} such that

$$\mathcal{T} : \tau_t(i, j), \quad \forall i, j, t, \quad (15)$$

where $\tau_t(i, j)$ is nonnegative for all (i, j, t) and upper-bounded by a probability distribution, i.e.,

$$\sum_j \tau_t(i, j) \leq 1, \quad \forall j, t. \quad (16)$$

Lemma 1. When the mixture uses the weighting scheme \mathcal{T} , which defines the transition weights $\tau_t(\cdot, \cdot)$, $\forall t$; we have the following upper bound on our losses in terms of the losses of a sequence of hyper-expert selections $\{I_1, I_2, \dots, I_T\}$ from the expert sets $\{\mathcal{N}_1, \mathcal{N}_2, \dots, \mathcal{N}_T\}$ (from the scheme \mathcal{H})

$$\sum_{t=1}^T l_t(\theta_t) \leq \sum_{t=1}^T l_t(\theta_{I_t,t}) + \frac{1}{\alpha} \mathcal{W}_{\mathcal{T}}(\{I_t\}_{t=1}^T).$$

where $\mathcal{W}_{\mathcal{T}}(\{I_t\}_{t=1}^T) \triangleq -\log\left(\prod_{t=1}^T \tau_t(I_{t-1}, I_t)\right)$, $I_t \in \mathcal{N}_t$, $\tau_1(I_0, I_1) \leq P_{I_1,1}$ and each $l_t(\cdot)$ is α -mixable.

Proof. The proof is in [50]. \square

B. Important Definitions

In an S segment competition during a time horizon T , we compete against a dynamically changing oracle predictions $\{\theta_s^*\}_{s=1}^S$ for the duration of the time lengths $\{t_s\}_{s=1}^S$. The result of Lemma 1 results in a regret bound in terms of the regret of an arbitrary expert selection sequence $I_1^T \triangleq \{I_t\}_{t=1}^T$.

Definition 4. The expert regret of the hyper-expert construction scheme \mathcal{H} is given by

$$E_{S,T}(I_1^T) \triangleq \sum_{s=1}^S \sum_{t=T_{s-1}+1}^{T_s} l_t(\theta_{I_t,t}) - l_t(\theta_s^*)$$

which is the regret of the selections $\{\theta_{I_t}\}_{t=1}^T$ against the competitions $\{\theta_s^*\}_{s=1}^T$.

Definition 5. The mixture regret of the transition weighting scheme \mathcal{T} for the hyper-expert scheme \mathcal{H} is given by

$$W_{S,T}(I_1^T) \triangleq \mathcal{W}_{\mathcal{T}}(\{I_t\}_{t=1}^T),$$

which is the mixture redundancy of the selections $\{\theta_{I_t}\}_{t=1}^T$ in our algorithm.

Corollary 1. Similarly to [50], the regret resulting from Lemma 1 can be divided in two parts as

$$\begin{aligned} R_{S,T}(\{I_t\}_{t=1}^T) &\triangleq \sum_{s=1}^S \sum_{t=T_{s-1}+1}^{T_s} l_t(\theta_t) - l_t(\theta_s^*) \\ &\leq E_{S,T}(I_1^T) + \frac{1}{\alpha} W_{S,T}(I_1^T), \end{aligned}$$

where $E_{S,T}(I_1^T)$ is the expert regret of the hyper-expert construction scheme \mathcal{H} ; and $W_{S,T}(I_1^T)$ is the mixture regret of the transition weighting scheme \mathcal{T} in a time horizon T when competing against S time segments.

Definition 6. Let I_1^T be a sequence of experts from \mathcal{H} that is able to 'compete', i.e., whenever $I_t \neq I_{t-1}$, I_t^{th} expert starts a new run of the base algorithm. Hence, this sequence of experts $\{I_t\}_{t=1}^T$ collectively imply a sequence of runs of the base algorithm (the structure of which depends on \mathcal{H}), where during each individual run, the competition θ_s^* stays the same. Let S_T be the number of segments in $\{I_t\}_{t=1}^T$ such that

$$\mathcal{S}(\{t_s\}_{s=1}^S) \triangleq S_T = 1 + \sum_{t=2}^T \mathbb{1}_{I_t \neq I_{t-1}},$$

where $\mathbb{1}_x$ is the identity operator. We point out that $S_T \leq o(T)$ for viable learning, where $o(\cdot)$ is the Little-O notation, because, otherwise, the base algorithm cannot sufficiently learn the optimal parameter in its segment.

Definition 7. We use the following expression

$$F(T) = \hat{O}(G(T)),$$

to denote an asymptotically near upper bound if $F(T) \leq K(G(T))^{1+\epsilon}$, as $T \rightarrow \infty$ for every finite $\epsilon > 0$, i.e., the fraction of $F(T)$ over $G(T)$ is asymptotically sub-polynomial in $G(T)$. Although a function $F(\cdot)$ may not necessarily be upper bounded by an order of $G(T)$, i.e., not $O(G(T))$, it may be $\hat{O}(G(T))$, since it is a looser bound.

IV. ALGORITHM DESIGN

There are two components that needs to designed in the algorithmic framework, which are the hyper-expert scheme and the weighting scheme. The weighting scheme determines the switches between the specific hyper-experts, which in turn, determines how the base algorithm is utilized. Unlike [50], we start with a generic design of the hyper-experts.

A. Hyper Expert Scheme Design

We start the design by creating a number of hyper-experts which run the base algorithm in given time intervals such that

$$\mathcal{H}_D : H(i) = \{p_i, s_i, t_i, r_i\}, \quad \forall i, \quad (17)$$

where the hyper-expert parameters

$$p_i \in \{1, 2, 3, \dots\},$$

is the period (i.e., how long does the base algorithm run before restarting) of the i^{th} expert, and

$$s_i \in \{1, 2, 3, \dots\},$$

is the initial start time (i.e., when we start the run of the base algorithm for the first time) of the i^{th} expert,

$$t_i \triangleq \text{rem}((t - s_i), p_i) + 1 \quad (18)$$

is the current runtime of the base algorithm at time t (i.e., the time since the last start of the base algorithm) for the expert i , and

$$r_i \triangleq t - t_i + p_i + 1 \quad (19)$$

is the next reset at time t (i.e., the next time instance the base algorithm resets) for the expert i .

B. Wighting Scheme Design

To mix these hyper-experts, we need a weighting scheme as in Definition 3. The problem setting is not as generic as [50] and the base algorithm does not need to know its total runtime at its start. We use the following weighting scheme

$$\mathcal{T}_D : \tau_t(i, j) = \begin{cases} \frac{1}{t_i}, & \text{if } t_j = 1 \text{ and } j = J_t \\ \frac{t_i - 1}{t_i}, & \text{if } i = j, t_i \neq 1 \\ 0, & \text{otherwise} \end{cases}, \quad (20)$$

where J_t is the index of the expert with the greatest period that resets at time t (tie breaker does not matter), i.e.,

$$J_t \triangleq \arg \max_{i: t=r_i} p_i. \quad (21)$$

Note that the weighting scheme \mathcal{T}_D satisfies Definition 3 and is a valid weighting scheme, since it either stays on the same expert or switches to a single expert at any time t .

C. Complexity

The complexity is directly related to the number of parallel running hyper-experts in accordance with the hyper-expert scheme \mathcal{H}_D . Thus, the computational complexity at time t is given by the cardinality of the set $C_t \triangleq \{H(i) \in \mathcal{H}_D : s_i \leq t\}$. Since this is a growing set, the per time complexity for a time horizon T is bounded by $C_T \triangleq \{H(i) \in \mathcal{H}_D : s_i \leq T\}$.

D. Regret Analysis

For a given S segment competition, where we compete against parameters $\{\theta_s^*\}_{s=1}^S$ with time lengths $\{t_s\}_{s=1}^S$, let there be a hyper-expert selection sequence $\{I_1^T\}$ that implies S_T restarts of the base algorithm.

Lemma 2. *We have the following expert regret for the scheme \mathcal{H}_D*

$$E_{S,T}(I_1^T) = O\left(S_T \log\left(\frac{T}{S_T}\right)\right).$$

Proof. The base algorithm can restart either when we are at the same hyper-expert or when we switch to a different hyper-expert (from the weighting scheme \mathcal{T}_D , we switch to an expert only when it restarts the base algorithm). Let τ_s be the total runtime of the base algorithm whenever we go to a new start of the base algorithm. Then, the regret is

$$E_{S,T}(\mathcal{H}_D) = \sum_{s=1}^{S_T} O(\log(\tau_s)), \quad (22)$$

from the base algorithm regret in Assumption 1. Since

$$\sum_{s=1}^{S_T} t_s = T, \quad (23)$$

we have from concavity of the logarithm

$$E_{S,T}(\mathcal{H}_D) = O\left(S_T \log\left(\frac{T}{S_T}\right)\right), \quad (24)$$

which concludes the proof. \square

Lemma 3. *We have the following mixture regret for the scheme \mathcal{T}_D*

$$W_{S,T}(\mathcal{T}_D) = O\left(S_T \log\left(\frac{T}{S_T}\right)\right).$$

Proof. From \mathcal{T}_D , we stay at the same expert for a runtime t_i of the base algorithm and incur $\log(t_i)$ redundancy during our stay. This is the total redundancy if we stay at the same expert. However, if we switch, we incur an additional $\log(t_i + 1)$ redundancy. Thus, we have

$$W_{S,T}(\mathcal{T}_D) \leq \sum_{s=1}^{S_T} 2 \log(t_s + 1), \quad (25)$$

which, from the concavity of the logarithm, gives

$$W_{S,T}(\mathcal{T}_D) = O\left(S_T \log\left(\frac{T}{S_T}\right)\right), \quad (26)$$

which concludes the proof. \square

Theorem 1. *The regret bound for using \mathcal{H}_D and \mathcal{T}_D with Algorithm 1 is given by*

$$R_{S,T}(\{\hat{\theta}_t\}_{t=1}^T) = O\left(S_T \log\left(\frac{T}{S_T}\right)\right),$$

for finite mixability α , where S_T is the total number of times the base algorithm resets.

Proof. The proof is straightforward from the combination of Lemma 2 and Lemma 3 in accordance with Corollary 1. \square

V. QUADRATIC COMPLEXITY ALGORITHM WITH OPTIMAL LOGARITHMIC PER SWITCH REGRET

For the optimal achievable regret, we need to have a base algorithm starting at each time t , since we do not know the time indices the competition changes. To do this, we create an expert at each time t that never resets and continues to sequentially run the base algorithm similarly with [37], [38].

We start the design by creating a number of hyper-experts which run the base algorithm in given time intervals such that

$$\mathcal{H}_{\text{lin}} : H(i) = \{s_i, p_i, t_i, r_i\}, \quad \forall i, \quad (27)$$

where the hyper-expert parameters

$$p_i = \infty, \quad (28)$$

is the period (i.e., the algorithm never restarts) of the i^{th} expert, and

$$s_i \in \{1, 2, 3, \dots\}, \quad (29)$$

is the initial start time (i.e., when we start the run of the base algorithm for the first time) of the i^{th} expert,

$$t_i = t - s_i + 1 \quad (30)$$

is the current runtime of the base algorithm at time t (i.e., the time since the last start of the base algorithm) for the expert i , and

$$r_i = \begin{cases} s_i, & t \leq s_i, \\ \infty, & \text{otherwise} \end{cases} \quad (31)$$

is the next reset at time t (i.e., the next time instance the base algorithm resets) for the expert i .

For this design of the hyper-expert scheme, we have the following complexity and regret.

Corollary 2. *For a time horizon T , the cardinality bound of the parallel running experts is*

$$C_T = T,$$

which results in a linear per time complexity, i.e., $O(T)$ per time.

Proof. The proof comes from the fact that the set of hyper-experts grows linearly (at each time instance, we create a new hyper-expert). \square

Corollary 3. *For a time horizon T , the number of base algorithm restarts S_T is bounded as*

$$S_T = S,$$

which results in the regret bound

$$R_{T,S} = O\left(S \log\left(\frac{T}{S}\right)\right)$$

Proof. The proof comes from the fact that at each time t , there is only one hyper-expert that starts the base algorithm, which we switch to. Thus, for every change in the competition, we switch to a different hyper-expert. \square

Remark 2. \mathcal{H}_{lin} implies an inefficient linear per time (i.e., $O(T)$) algorithm with the optimal regret per switch $O(\log(T/S))$.

VI. LINEARITHMIC COMPLEXITY ALGORITHM WITH SUB-OPTIMAL LOG-SQUARED PER SWITCH REGRET

For efficiency, the traditional approach is to use the doubling trick [51] where we run the algorithm with time lengths that is the double of the previous run (e.g., $2^0, 2^1, 2^2, \dots$). Hence, the hyper-experts end up running the base algorithm for lengths that are powers of 2. We efficiently implement our algorithm by creating hyper experts that rerun the base algorithm in specific time intervals. These hyper-experts will be designed such that the i^{th} expert, $i \in \{1, \dots, N\}$, will run the base algorithm individually in subsequent time segments of length 2^k for some k similarly with [41], [50].

We design the hyper-experts with the parameter k_i , which is a parameter such that

$$k_i \in \{2^0, 2^1, 2^2, 2^3, \dots\}, \quad (32)$$

where the hyper-expert i with k_i start its run at $t = k_i$; and runs the base algorithm for an interval of k_i . Thus,

$$\mathcal{H}_{\text{log}} : H(i) = \{s_i, p_i, t_i, r_i\}, \quad \forall i, \quad (33)$$

where the hyper-expert parameters

$$p_i \in \{2^0, 2^1, 2^2, 2^3, \dots\}, \quad (34)$$

is the period of the i^{th} expert, and

$$s_i = p_i, \quad (35)$$

is the initial start time of the i^{th} expert,

$$t_i = \text{rem}((t - p_i), p_i) + 1 \quad (36)$$

is the runtime of the base algorithm at t for the expert i , and

$$r_i = t - t_i + p_i + 1 \quad (37)$$

is the next reset at time t (i.e., the next time instance the base algorithm resets) for the expert i .

Corollary 4. *For a time horizon T , the cardinality bound of the parallel running experts is*

$$C_T = O(\log(T)),$$

which results in a logarithmic per time complexity.

Proof. The proof comes from the fact that there is only one hyper-expert with the same period and this set grows logarithmically with time. \square

Corollary 5. *For a time horizon T , the number of base algorithm starts S_T is bounded as*

$$S_T = S \log(T/S),$$

which results in the regret bound

$$R_{T,S} = O\left(S \log^2(T/S)\right)$$

Proof. From the construction of \mathcal{H}_{log} , we see that if we switch to a period p_i at time t for some competition θ_s^* , we can only switch to a bigger period at $t + p_i$. This results in the worst case scenario of $\log(t_s)$ restarts for the competition segment length t_s , which concludes the proof. \square

Remark 3. \mathcal{H}_{log} implies an efficient logarithmic per time (i.e., $O(\log(T))$) algorithm with sub-optimal regret per switch $O(\log^2(T/S))$.

VII. NEAR-LINEAR COMPLEXITY ALGORITHM WITH
NEAR-OPTIMAL NEAR-
LOGARITHMIC PER SWITCH REGRET

In this section, we combine the better properties of the designs in Section V and Section VI. We leave the period structure generic, which is not necessarily an exponentially growing one as in Section VI

$$p_i \in \{f_1, f_2, \dots\}, \quad (38)$$

where $f_1 = 1$. For $n \geq 2$, let $f_n = \alpha_n f_{n-1} + \beta_n$, where α_n is a natural number and $0 \leq \beta_n \leq f_{n-1}$. We design the hyper experts such that for every period f_n , the start times will range from $\{\beta_n + f_{n-1}, \beta_n + 2f_{n-1}, \dots, \beta_n + \alpha_n f_{n-1}\}$. Thus,

$$\mathcal{H}_{\text{sub}} : H(i) = \{s_i, p_i, t_i, r_i\}, \quad \forall i, \quad (39)$$

where the hyper-expert parameters

$$p_i = f_n \in \{f_1, f_2, \dots\}, \quad (40)$$

for some n , is the period of the i^{th} expert, and

$$s_i \in \{\beta_n + f_{n-1}, \beta_n + 2f_{n-1}, \dots, \beta_n + \alpha_n f_{n-1}\}, \quad (41)$$

is the initial start time of the i^{th} expert,

$$t_i = \text{rem}((t - s_i), p_i) + 1 \quad (42)$$

is the runtime of the base algorithm at t for the expert i , and

$$r_i = t - t_i + p_i + 1 \quad (43)$$

is the next reset at time t for the expert i .

Remark 4. When $\alpha_n = 1$ for all n and $\beta_n = f_{n-1}$, we have the structure of Section VI as in [41], [50].

Definition 8. We define the following metric which will be useful in both the complexity and the regret analysis. Let

$$n_t = \max_{n: f_n < t} n,$$

which is the index of the maximum period that is less than the time length t .

Theorem 2. For a time horizon T , the cardinality bound of the parallel running experts is

$$C_T \leq 1 + n_T \max_{n \in \{2, \dots, n_T + 1\}} \alpha_n,$$

where n_T is as in Definition 8.

Proof. We observe that for an expert with f_n period to start for the first time, we need to have passed the time mark f_{n-1} . For a time horizon T , we have from Definition 8

$$n_T = \max_{n: f_n < T} n \quad (44)$$

Then, complexity is

$$C_T \leq 1 + \sum_{n=1}^{n_T} \alpha_{n+1}, \quad (45)$$

$$\leq 1 + n_T \max_{n \in \{2, \dots, n_T + 1\}} \alpha_n, \quad (46)$$

where the additive 1 comes from the single hyper-expert with the period $f_1 = 1$, which completes the proof. \square

Theorem 3. For a time horizon T , \mathcal{H}_{sub} results in the regret

$$R_{T,S} = O\left(\left(S + \sum_{s=1}^S n_{t_s}\right) \log\left(\frac{T}{S + \sum_{s=1}^S n_{t_s}}\right)\right),$$

where n_{t_s} is as in Definition 8.

Proof. For any competition segment t_s , let

$$n_{t_s} = \max_{n: f_n < t_s} n. \quad (47)$$

Whenever we switch to an expert with $f_{n_{t_s}+1}$, we can cover until the end of the competition. Moreover, we do not need to switch to the same period twice. Thus, total number of switches is bounded by $n_{t_s} + 1$ and $S_T \leq S + \sum_{s=1}^S n_{t_s}$. \square

We design the periods f_n for $n \geq 2$ as the following

$$f_n = \lfloor \exp(a \exp(b \log^c(n))) \rfloor, \quad (48)$$

where $a > 0$, $b > 0$, $c > 1$. From Definition 8, we have

$$n_{t_s} \leq \exp((\log(\log(t_s + 1)/a)/b)^{1/c}), \quad (49)$$

which is sub-logarithmic for finite $c > 1$.

Corollary 6. For a time horizon T , the cardinality bound of the parallel running experts is asymptotically

$$C_T = o(T^\epsilon),$$

for any finite $\epsilon > 0$, i.e., sub-polynomial.

Proof. For $c > 1$, we have

$$\alpha_{n_T} = O\left(T^{\frac{bc \log^{c-1}(n_T)}{n_T}}\right), \quad (50)$$

from asymptotic convexity of $\exp(b \log^c(n))$. The result comes from Theorem 2 and the fact that n_T is sub-logarithmic and divergent. \square

Corollary 7. Using the periods in (48) results in the regret

$$R_{T,S} = \hat{O}(S \log(T/S)),$$

since S_T is sub-logarithmic per S .

Proof. Using (49) and Theorem 3, we have

$$S_T = O(S \exp((\log(\log(T/S + 1)/a)/b)^{1/c})), \quad (51)$$

which results in a near-logarithmic regret per switch. \square

Remark 5. \mathcal{H}_{sub} implies an efficient near-linear time algorithm with near-optimal near-logarithmic regret per switch.

VIII. CONCLUSION

We studied the online optimization of mixable loss functions in a dynamic environment, where there exists an algorithm that achieves $O(\log(T))$ regret against a fixed estimator. We proposed an online mixture framework that uses these static solvers as its base algorithm. Against a competition with S segments, we showed that, with the suitable selection of hyper-expert creations and weighting strategies, we can achieve $O(S \log(T/S))$ and $O(S \log^2(T/S))$ regret in $O(T)$ and $O(\log(T))$ computational complexity per round, respectively. Furthermore, we showed that it is also possible to achieve asymptotically $O(S \log^{1+\epsilon}(T/S))$ regret for any finite $\epsilon > 0$ (near-logarithmic, thus near-optimal) with $O(T^{1+\delta})$ computational complexity for any finite $\delta > 0$ (near-linear).

REFERENCES

- [1] M. I. Jordan and T. M. Mitchell, "Machine learning: Trends, perspectives, and prospects," *Science*, vol. 349, no. 6245, pp. 255–260, 2015.
- [2] M. Mohri, A. Rostamizadeh, and A. Talwalkar, *Foundations of machine learning*. MIT press, 2018.
- [3] S. Shalev-Shwartz *et al.*, "Online learning and online convex optimization," *Foundations and trends in Machine Learning*, vol. 4, no. 2, pp. 107–194, 2011.
- [4] N. Cesa-Bianchi and G. Lugosi, *Prediction, learning, and games*. Cambridge university press, 2006.
- [5] H. V. Poor, *An Introduction to Signal Detection and Estimation*. NJ: Springer, 1994.
- [6] J. Moody and M. Saffell, "Learning to trade via direct reinforcement," *IEEE Transactions on Neural Networks*, vol. 12, no. 4, pp. 875–889, Jul 2001.
- [7] R. Song, F. L. Lewis, and Q. Wei, "Off-policy integral reinforcement learning method to solve nonlinear continuous-time multiplayer nonzero-sum games," *IEEE Transactions on Neural Networks and Learning Systems*, vol. PP, no. 99, pp. 1–10, 2016.
- [8] H. S. Chang, J. Hu, M. C. Fu, and S. I. Marcus, "Adaptive adversarial multi-armed bandit approach to two-person zero-sum markov games," *IEEE Transactions on Automatic Control*, vol. 55, no. 2, pp. 463–468, Feb 2010.
- [9] H. R. Berenji and P. Khedkar, "Learning and tuning fuzzy logic controllers through reinforcements," *IEEE Transactions on Neural Networks*, vol. 3, no. 5, pp. 724–740, Sep 1992.
- [10] M. Zinkevich, "Online convex programming and generalized infinitesimal gradient ascent," in *Proceedings of the 20th International Conference on Machine Learning (ICML-03)*, 2003, pp. 928–936.
- [11] E. Hazan, A. Kalai, S. Kale, and A. Agarwal, "Logarithmic regret algorithms for online convex optimization," in *Learning Theory*, G. Lugosi and H. U. Simon, Eds. Berlin, Heidelberg: Springer Berlin Heidelberg, 2006, pp. 499–513.
- [12] K. Gokcesu and S. S. Kozat, "Online density estimation of nonstationary sources using exponential family of distributions," *IEEE transactions on neural networks and learning systems*, vol. 29, no. 9, pp. 4473–4478, 2017.
- [13] F. M. J. Willems, "Coding for a binary independent piecewise-identically-distributed source," *IEEE Transactions on Information Theory*, vol. 42, no. 6, pp. 2210–2217, 1996.
- [14] N. Merhav, "On the minimum description length principle for sources with piecewise constant parameters," *IEEE Transactions on Information Theory*, vol. 39, no. 6, pp. 1962–1967, Nov 1993.
- [15] G. I. Shamir and N. Merhav, "Low-complexity sequential lossless coding for piecewise-stationary memoryless sources," *IEEE Transactions on Information Theory*, vol. 45, no. 5, pp. 1498–1519, Jul 1999.
- [16] K. Gokcesu and S. S. Kozat, "Online anomaly detection with minimax optimal density estimation in nonstationary environments," *IEEE Transactions on Signal Processing*, vol. 66, no. 5, pp. 1213–1227, March 2018.
- [17] S. Bubeck and N. Cesa-Bianchi, "Regret analysis of stochastic and nonstochastic multi-armed bandit problems," *Foundations and Trends in Machine Learning*, vol. 5, no. 1, pp. 1–122, 2012.
- [18] M. M. Neyshabouri, K. Gokcesu, H. Gokcesu, H. Ozkan, and S. S. Kozat, "Asymptotically optimal contextual bandit algorithm using hierarchical structures," *IEEE transactions on neural networks and learning systems*, vol. 30, no. 3, pp. 923–937, 2018.
- [19] N. M. Vural, H. Gokcesu, K. Gokcesu, and S. S. Kozat, "Minimax optimal algorithms for adversarial bandit problem with multiple plays," *IEEE Transactions on Signal Processing*, vol. 67, no. 16, pp. 4383–4398, 2019.
- [20] N. Cesa-Bianchi, Y. Mansour, and G. Stoltz, "Improved second-order bounds for prediction with expert advice," *Machine Learning*, vol. 66, no. 2-3, pp. 321–352, 2007.
- [21] K. Gokcesu and S. S. Kozat, "An online minimax optimal algorithm for adversarial multiarmed bandit problem," *IEEE Transactions on Neural Networks and Learning Systems*, pp. 1–16, 2018.
- [22] A. C. Singer and M. Feder, "Universal linear prediction by model order weighting," *IEEE Transactions on Signal Processing*, vol. 47, no. 10, pp. 2685–2699, Oct 1999.
- [23] —, "Universal linear least-squares prediction," in *Information Theory, 2000. Proceedings. IEEE International Symposium on*, 2000, pp. 81–81.
- [24] K. Gokcesu, M. Ergeneci, E. Ertan, and H. Gokcesu, "An adaptive algorithm for online interference cancellation in emg sensors," *IEEE Sensors Journal*, vol. 19, no. 1, pp. 214–223, 2018.
- [25] H. Ozkan, M. A. Donmez, S. Tunc, and S. S. Kozat, "A deterministic analysis of an online convex mixture of experts algorithm," *IEEE Transactions on Neural Networks and Learning Systems*, vol. 26, no. 7, pp. 1575–1580, July 2015.
- [26] T. Moon, "Universal switching fir filtering," *IEEE Transactions on Signal Processing*, vol. 60, no. 3, pp. 1460–1464, March 2012.
- [27] B. Li and S. C. Hoi, "Online portfolio selection: A survey," *ACM Computing Surveys (CSUR)*, vol. 46, no. 3, pp. 1–36, 2014.
- [28] S. Boyd, S. P. Boyd, and L. Vandenberghe, *Convex optimization*. Cambridge university press, 2004.
- [29] J.-P. Vial, "Strong convexity of sets and functions," *Journal of Mathematical Economics*, vol. 9, no. 1-2, pp. 187–205, 1982.
- [30] V. G. Vovk, "Aggregating strategies," in *Proceedings of the Third Annual Workshop on Computational Learning Theory*, ser. COLT '90. San Francisco, CA, USA: Morgan Kaufmann Publishers Inc., 1990, pp. 371–386.
- [31] D. Haussler, J. Kivinen, and M. K. Warmuth, "Sequential prediction of individual sequences under general loss functions," *IEEE Transactions on Information Theory*, vol. 44, no. 5, pp. 1906–1925, 1998.
- [32] T. Koren, "Open problem: Fast stochastic exp-concave optimization," in *Conference on Learning Theory*. PMLR, 2013, pp. 1073–1075.
- [33] M. Herbster and M. K. Warmuth, "Tracking the best expert," *Machine Learning*, vol. 32, no. 2, pp. 151–178, 1998.
- [34] Y. Freund and R. E. Schapire, "A decision-theoretic generalization of on-line learning and an application to boosting," *Journal of Computer and System Sciences*, vol. 55, no. 1, pp. 119 – 139, 1997.
- [35] E. Lehrer, "A wide range no-regret theorem," *Games and Economic Behavior*, vol. 42, no. 1, pp. 101–115, 2003.
- [36] A. Blum and Y. Mansour, "From external to internal regret," *Journal of Machine Learning Research*, vol. 8, no. Jun, pp. 1307–1324, 2007.
- [37] E. Hazan and C. Seshadhri, "Efficient learning algorithms for changing environments," in *Proceedings of the 26th annual international conference on machine learning*, 2009, pp. 393–400.
- [38] A. Chernov and V. Vovk, "Prediction with expert evaluators' advice," in *International Conference on Algorithmic Learning Theory*. Springer, 2009, pp. 8–22.
- [39] Y. Freund, R. E. Schapire, Y. Singer, and M. K. Warmuth, "Using and combining predictors that specialize," in *Proceedings of the twenty-ninth annual ACM symposium on Theory of computing*, 1997, pp. 334–343.
- [40] D. Adamskiy, W. M. Koolen, A. Chernov, and V. Vovk, "A closer look at adaptive regret," *The Journal of Machine Learning Research*, vol. 17, no. 1, pp. 706–726, 2016.
- [41] K. Gokcesu and H. Gokcesu, "Recursive experts: An efficient optimal mixture of learning systems in dynamic environments," *CoRR*, vol. abs/2009.09249, 2020.
- [42] A. Gyorgy, T. Linder, and G. Lugosi, "Efficient tracking of large classes of experts," *IEEE Transactions on Information Theory*, vol. 58, no. 11, pp. 6709–6725, 2012.
- [43] L. Zhang, T. Yang, Z.-H. Zhou *et al.*, "Dynamic regret of strongly adaptive methods," in *International Conference on Machine Learning*, 2018, pp. 5882–5891.
- [44] A. Daniely, A. Gonen, and S. Shalev-Shwartz, "Strongly adaptive online learning," in *International Conference on Machine Learning*, 2015, pp. 1405–1411.
- [45] L. Zhang, T.-Y. Liu, and Z.-H. Zhou, "Adaptive regret of convex and smooth functions," in *International Conference on Machine Learning*. PMLR, 2019, pp. 7414–7423.
- [46] L. Zhang, S. Lu, and T. Yang, "Minimizing dynamic regret and adaptive regret simultaneously," in *International Conference on Artificial Intelligence and Statistics*. PMLR, 2020, pp. 309–319.
- [47] K. Gokcesu and H. Gokcesu, "A generalized online algorithm for translation and scale invariant prediction with expert advice," *CoRR*, vol. abs/2009.04372, 2020.
- [48] N. Littlestone and M. Warmuth, "The weighted majority algorithm," *Information and Computation*, vol. 108, no. 2, pp. 212 – 261, 1994.
- [49] P. Auer, N. Cesa-Bianchi, Y. Freund, and R. E. Schapire, "The non-stochastic multiarmed bandit problem," *SIAM J. Comput.*, vol. 32, no. 1, pp. 48–77, Jan. 2003.
- [50] K. Gokcesu and H. Gokcesu, "Optimal and efficient algorithms for general mixable losses against switching oracles," *arXiv preprint arXiv:2108.06411*, 2021.
- [51] N. Cesa-Bianchi, Y. Freund, D. Haussler, D. P. Helmbold, R. E. Schapire, and M. K. Warmuth, "How to use expert advice," *J. ACM*, vol. 44, no. 3, pp. 427–485, May 1997.