

Free Commutative Monoids in Homotopy Type Theory

Vikraman Choudhury

Department of Computer Science and Technology,
University of Cambridge
Cambridge, UK
vc378@cl.cam.ac.uk

Marcelo Fiore

Department of Computer Science and Technology,
University of Cambridge
Cambridge, UK
Marcelo.Fiore@cl.cam.ac.uk

Abstract

We develop a constructive theory of finite multisets, defining them as free commutative monoids in Homotopy Type Theory. We formalise two algebraic presentations of this construction using 1-HITs, establishing the categorical universal property for each and thereby their equivalence. These presentations correspond to equational theories including a commutation axiom. In this setting, we prove important structural combinatorial properties of singleton multisets arising from concatenations and projections of multisets. This is done in generality, without assuming decidable equality on the carrier set. Further, as applications, we present a constructive formalisation of the relational model of differential linear logic and use it to characterise the equality type of multisets. This leads us to a novel conditional equational presentation of the finite-multiset construction and thereby to a sound and complete deduction system for multiset equality.

Keywords: finite-multiset construction, free commutative-monoid construction, constructive mathematics, homotopy type theory, higher inductive types, category theory, linear logic, differential linear logic

1 Introduction

Martin-Löf Type Theory (MLTT) introduces the identity type to express equality in type theory. Homotopy Type Theory and Univalent Foundations (HoTT/UF) [38] embraces this proof-relevant notion of equality, and extends it with Voevodsky’s univalence principle [29], homotopy types, and Higher Inductive Types (HITs), proposing a foundational system for constructive mathematics.

Algebraic structures, that is, sets with operations satisfying equations, are ubiquitous in computer science and mathematics. In HoTT, given a type A , and terms $x, y : A$, the identity type $x =_A y$ carries interesting structure. Using this equality type for equations, it is a challenging problem to define (higher) algebraic structures. For example, the problem of defining (free higher) groups has been considered

by Kraus and Altenkirch [32], Buchholtz, van Doorn, and Rijke [10], Altenkirch and Scoccola [2]. In this paper, we consider the problem of defining and, crucially, studying *free commutative monoids* in HoTT, using various HITs.

Since commutative monoids are sets, we only consider types which are 0-truncated in this paper but, importantly, we *do not* assume decidable equality on the carrier sets. We also comment on further generalising our results to free symmetric monoidal groupoids.

1.1 Type Theory

We choose to work in the type-theoretic language of the HoTT book [38]; all our claims will hold in a Cubical type theory [13, 3, 39] as well. Most of our results are formalised in Cubical Agda [39], and we refer the reader to the formalisation for detailed proofs. We briefly remark on the notation we use in the paper.

We write dependent function types as $\prod_{x:A} B(x)$, or simply $(x : A) \rightarrow B(x)$, and sigma types as $\sum_{x:A} B(x)$, or simply $(x : A) \times B(x)$, following Agda inspired notation. Sometimes, we leave function arguments implicit, marked with braces $\{x : A\}$. We also take a few liberties with notation, when using infix, or (un)curried forms of operations, with appropriately assigned associativity.

The identity type between $x, y : A$ is written as $x =_A y$, and we write $p \circ q$ for path composition and p^{-1} for the path inverse operations. The constant path is given by $\text{refl}_x : x =_A x$ and $\text{ap}_f : \prod_{x,y:A} x =_A y \rightarrow f(x) =_B f(y)$ gives the functorial action on paths.

The (univalent) universe of types is denoted \mathcal{U} . For a type family (fibration) $B : A \rightarrow \mathcal{U}$, the transport operation lifts paths in the base type A to functions between the fibers, that is, $\text{transport}_B : \prod_{x,y:A} x =_A y \rightarrow B(x) \rightarrow B(y)$. For $u : B(x)$ and $v : B(y)$, we write $p_\star(u)$ for $\text{transport}_B^p(u)$, and $u =_p^B v$ for the lifted path over p given by $p_\star(u) =_{B(y)} v$. The functorial action on sections $f : \prod_{x:A} B(x)$ of the fibration is given by $\text{apd}_f : \prod_{x,y:A} (p : x =_A y) \rightarrow f(x) =_p^B f(y)$.

Equivalences between types A and B are denoted by $A \simeq B$, and homotopies between functions f and g are denoted by $f \sim g$. By univalence/funext, these are equivalent to the corresponding identity types. We use \equiv for definitions and \equiv for denoting judgemental equalities.

For homotopy n -types, we use the standard definitions for contractible types (-2), propositions (-1) and sets (0), which are given by $\text{isContr}(A) := \sum_{x:A} \prod_{y:A} y = x$, $\text{isProp}(A) := \prod_{x,y:A} \text{isContr}(x = y)$, and $\text{isSet}(A) := \prod_{x,y:A} \text{isProp}(x = y)$. We write hProp and hSet for the universe of propositions and sets respectively. We write Set for the (univalent) category of hSets and functions [38, Chapter 10.1]. When writing commuting diagrams, we mean that they commute upto homotopy (or equivalently, upto the identity type).

The n -truncation of a type A is written as $\|A\|_n$, with the point constructor $|-| : A \rightarrow \|A\|_n$. When working with propositions ((-1)-truncated types), we use standard logical notation, that is truth values, $\perp := \mathbf{0}$, $\top := \mathbf{1}$, binary connectives $\phi \wedge \psi := \phi \times \psi$, and $\phi \vee \psi := \|\phi + \psi\|_{-1}$, and quantifiers given by $\forall_{(x:A)}.P(x) := \prod_{x:A} P(x)$ and $\exists_{(x:A)}.P(x) := \|\sum_{x:A} P(x)\|_{-1}$ (see [38, Definition 3.7.1]).

1.2 Outline and Contributions

The main goal of the paper is to develop a constructive theory of free commutative monoids and their finite-multiset representation, with applications to models of differential linear logic and combinatorial Fock space.

- In section 2, we start by briefly defining commutative monoids and their homomorphisms in HoTT.
- In section 3, we give two algebraic presentations of free commutative monoids, proving that they satisfy the same universal property and are hence equivalent. We further prove that the induced free commutative monoid monad is commutative.
- In section 4, we investigate structural combinatorial aspects of free commutative monoids by characterising the equality between singleton multisets and both concatenations and projections of multisets.
- In section 5, we describe the power relative monad. We then develop the category of relations in the spirit of Lawvere's Generalized Logic for sets regarded as groupoids enriched over propositions. We further lift the free commutative monoid monad from sets to relations in the light of Day's promonoidal convolution.
- In section 6, we develop a constructive formalisation of the relational model of differential linear logic.
- In section 7, we characterise the equality type between non-empty multisets using the commutation relation of creation/annihilation operators associated with the free commutative monoid construction seen as a combinatorial Fock space.
- In section 8, we introduce a new conditional equational presentation for free commutative monoids.
- In section 9, we present a novel deduction system for multiset equality that we prove to be sound and complete.
- In section 10, we briefly discuss related work and future directions.

We include a formalisation of most of our results using the proof assistant Cubical Agda. Informal paper proofs and proof sketches are also provided in the included appendices.

2 Commutative Monoids

We start by giving the definition of commutative monoids in type theory; they are monoids with an additional commutation axiom.

Definition 2.1 (Commutative monoid). *A commutative monoid is a set M with the following data:*

- a multiplication function $\cdot : M \times M \rightarrow M$; and
- a unit element $e : M$

such that

- for $x : M$, we have $x \cdot e = x$ and $e \cdot x = x$;
- for $x, y, z : M$, we have $x \cdot (y \cdot z) = (x \cdot y) \cdot z$; and
- for $x, y : M$, we have $x \cdot y = y \cdot x$.

Example 2.1. *The natural numbers \mathbb{N} are a commutative monoid under addition, with unit 0, and also under multiplication, with unit 1. Lists $\mathcal{L}(A)$ with the empty list nil for unit, and the append operation $\#$ for multiplication are a monoid, but not generally a commutative monoid.*

Definition 2.2 (Homomorphism). *For commutative monoids $(M; \cdot_M, e_M)$ and $(N; \cdot_N, e_N)$, a function $f : M \rightarrow N$ is a homomorphism if it preserves the unit and multiplication.*

$$\text{isCMonHom}(f) :=$$

$$f(e_M) = e_N \wedge \forall(x, y : M). f(x \cdot_M y) = f(x) \cdot_N f(y)$$

The set of homomorphisms is

$$\text{CMon}(M, N) := \sum_{f:M \rightarrow N} \text{isCMonHom}(f)$$

3 The Free Commutative Monoid Monad

We are mainly interested in free commutative monoids whose universal definition we state next.

Definition 3.1 (Universal property of free commutative monoids).

For a set A , a commutative monoid $\mathcal{M}(A)$ together with a function $\eta : A \rightarrow \mathcal{M}(A)$ is the free commutative monoid on A whenever, for every commutative monoid M , composition with η determines an equivalence as follows

$$(-) \circ \eta : \text{CMon}(\mathcal{M}(A), M) \xrightarrow{\sim} (A \rightarrow M)$$

Alternatively, for every function $f : A \rightarrow M$, there is a unique canonical lifting to a homomorphism $f^\# : \text{CMon}(\mathcal{M}(A), M)$; that is, the type $\sum_{h:\text{CMon}(\mathcal{M}(A), M)} h \circ \eta \sim f$ is contractible.

Proposition 3.2. *Let $\mathcal{L}(A)$ be the free monoid (equivalently, the list construction) on A . The free commutative monoid and the free monoid on the unit type 1 are canonically equivalent:*

$$\mathcal{M}(1) \simeq \mathcal{L}(1) .$$

Hence, $\mathcal{M}(1) \simeq \mathbb{N}$.

We have described the universal property of \mathcal{M} , but not a construction. We now discuss two constructions of free commutative monoids in HoTT: the naive one from universal algebra (section 3.1) and a swapped-list construction from computer science (section 3.2). The situation here is similar to that of free monoids, which can either be described by generators and relations, or by using the inductive list datatype [38, Chapter 6.11].

A third construction, which is important for reasoning about equality in free commutative monoids, will be introduced in section 8.

3.1 Universal-Algebraic Construction

Using the standard construction of free algebras for equational theories, from universal algebra, the free commutative monoid on a set may be defined using the following HIT.

Definition 3.3 (FCM). *Let A be a type, we define the HIT $\text{FCM}(A)$ with the following point and path constructors:*

$$\begin{aligned} \eta &: A \rightarrow \text{FCM}(A) \\ e &: \text{FCM}(A) \\ - \cdot - &: \text{FCM}(A) \times \text{FCM}(A) \rightarrow \text{FCM}(A) \\ \text{assoc} &: (x \ y \ z : \text{FCM}(A)) \rightarrow x \cdot (y \cdot z) = (x \cdot y) \cdot z \\ \text{unitl} &: (x : \text{FCM}(A)) \rightarrow e \cdot x = x \\ \text{unitr} &: (x : \text{FCM}(A)) \rightarrow x \cdot e = x \\ \text{comm} &: (x \ y : \text{FCM}(A)) \rightarrow x \cdot y = y \cdot x \\ \text{trunc} &: \text{isSet}(\text{FCM}(A)) \end{aligned}$$

The first constructor η postulates that A maps to $\text{FCM}(A)$. The next two give the operations on a monoid: the identity element and multiplication (written in an infix style). The four path constructors after that assert the axioms of a commutative monoid – associativity, unitality, and commutativity. Finally, we add a path constructor to truncate $\text{FCM}(A)$ to a set, since we wish to ignore any higher paths introduced by the path constructors.

For completeness, we state the induction principle for FCM. Note that we use judgemental equality for the computation rules for the point constructors, and the computation rules for the path constructors hold upto the identity type.

Definition 3.4 (Induction principle for FCM).

Given a type family $P : \text{FCM}(A) \rightarrow \mathcal{U}$ with the following data:

$$\begin{aligned} \eta^* &: (x : A) \rightarrow P(\eta(x)) \\ e^* &: P(e) \\ - \cdot - &: \{x \ y : \text{FCM}(A)\} \rightarrow P(x) \rightarrow P(y) \rightarrow P(x \cdot y) \\ \text{assoc}^* &: \{x \ y \ z : \text{FCM}(A)\}(p : P(x))(q : P(y))(r : P(z)) \\ &\rightarrow p \cdot^* (q \cdot^* r) \stackrel{P}{=}_{\text{assoc}(x,y,z)} (p \cdot^* q) \cdot^* r \\ \text{unitl}^* &: \{x : \text{FCM}(A)\}(p : P(x)) \rightarrow e^* \cdot^* p \stackrel{P}{=}_{\text{unitl}(x)} p \\ \text{unitr}^* &: \{x : \text{FCM}(A)\}(p : P(x)) \rightarrow p \cdot^* e^* \stackrel{P}{=}_{\text{unitr}(x)} p \\ \text{comm}^* &: \{x \ y : \text{FCM}(A)\}(p : P(x))(q : P(y)) \\ &\rightarrow p \cdot^* q \stackrel{P}{=}_{\text{comm}(x,y)} q \cdot^* p \\ \text{trunc}^* &: (x : \text{FCM}(A)) \rightarrow \text{isSet}(P(x)) \end{aligned}$$

there is a unique function $f : (x : \text{FCM}(A)) \rightarrow P(x)$ with the following computation rules:

$$\begin{aligned} f(\eta(x)) &\equiv \eta^*(x) \\ f(e) &\equiv e^* \\ f(x \cdot y) &\equiv f(x) \cdot^* f(y) \\ \text{apd}_f(\text{assoc}(x, y, z)) &= \text{assoc}^*(f(x), f(y), f(z)) \\ \text{apd}_f(\text{unitl}(x)) &= \text{unitl}^*(f(x)) \\ \text{apd}_f(\text{unitr}(x)) &= \text{unitr}^*(f(x)) \\ \text{apd}_f(\text{comm}(x, y)) &= \text{comm}^*(f(x), f(y)) \end{aligned}$$

$\text{FCM}(A)$ is straightforwardly a commutative monoid. Using the induction principle and computation rules, one can prove that it satisfies the categorical universal property of the free commutative monoid (definition 3.1).

Theorem 3.5. *For every set A , $\eta : A \rightarrow \text{FCM}(A)$ is the free commutative monoid on A .*

3.2 Swapped-List Construction

Alternatively, one can define free commutative monoids by means of a folklore *swapped-list* construction. Just like free monoids are given by finite lists (defined as an inductive type), free commutative monoids can be defined as lists, but identified upto swappings.

Definition 3.6 (sList). *The swapped-lists over a type A is given by the type $\text{sList}(A)$, which is a HIT with the following point and path constructors:*

$$\begin{aligned} \text{nil} &: \text{sList}(A) \\ - :: - &: A \times \text{sList}(A) \rightarrow \text{sList}(A) \\ \text{swap} &: (x \ y : A)(xs : \text{sList}(A)) \\ &\rightarrow x :: y :: xs = y :: x :: xs \\ \text{trunc} &: \text{isSet}(\text{sList}(A)) \end{aligned}$$

The first two constructors are the standard ones for lists (free monoids), that is, nil and cons or (infix) $::$, but we have

an additional swap path constructor asserting that the first two elements of the list can be swapped around. Note that, unlike FCM, this is a recursively defined HIT, that is, the points and paths are recursively generated. In particular, by the congruence of cons, these adjacent swaps may also be performed elsewhere inside the list. Finally, we truncate $\text{sList}(A)$ to a set, since we wish to ignore the higher paths introduced by swap.

Classically, finite multisets are usually defined as lists quotiented by permutations of its elements. In our setting, we are generating this equivalence relation recursively, that is, we are generating the path space of finite multisets simply using the swap path constructor. To establish this fact formally, we will prove that $\text{sList}(A)$ is indeed the free commutative monoid on A , by establishing its universal property.

The main means of reasoning about swapped-lists is the following induction principle. It is akin to the induction principle for lists, but one additionally needs to enforce invariance under swapping. Also, note that since we truncate to sets, one is only allowed to eliminate to sets. This is restrictive. However, for the purposes of this paper, we are only interested in establishing the universal property of free commutative monoids and we only ever need to eliminate to sets (or propositions).

Definition 3.7 (Induction principle for sList).

Given a type family $P : \text{sList}(A) \rightarrow \mathcal{U}$ with the following data:

$$\begin{aligned} \text{nil}^* &: P(\text{nil}) \\ - ::^* - &: (x : A) \{xs : \text{sList}(A)\} \rightarrow P(xs) \rightarrow P(x :: xs) \\ \text{swap}^* &: (x \ y : A) \{xs : \text{sList}(A)\} (p : P(xs)) \\ &\rightarrow x ::^* y ::^* p =_{\text{swap}(x,y,xs)}^P y ::^* x ::^* p \\ \text{trunc}^* &: (xs : \text{sList}(A)) \rightarrow \text{isSet}(P(xs)) \end{aligned}$$

there is a unique function $f : (xs : \text{sList}(A)) \rightarrow P(xs)$ satisfying the following computation rules:

$$\begin{aligned} f(\text{nil}) &\equiv \text{nil}^* \\ f(x :: xs) &\equiv x ::^* f(xs) \\ \text{apd}_f(\text{swap}(x, y, xs)) &= \text{swap}^*(x, y, f(xs)) \end{aligned}$$

When eliminating to propositions, the induction principle can be simplified. One only needs to provide an image for the nil and $::$ constructors, similar to lists.

Lemma 3.8 (Propositional induction principle for sList). Let $P : \text{sList}(A) \rightarrow \mathcal{U}$ be a type family with the following data.

$$\begin{aligned} \text{nil}^* &: P(\text{nil}) \\ - ::^* - &: (x : A) \{xs : \text{sList}(A)\} \rightarrow P(xs) \rightarrow P(x :: xs) \\ \text{trunc}^* &: (xs : \text{sList}(A)) \rightarrow \text{isProp}(P(xs)) \end{aligned}$$

Then, there is a unique function $f : (xs : \text{sList}(A)) \rightarrow P(xs)$ satisfying the appropriate computation rules.

We now exhibit the swapped-list construction as the free commutative monoid construction.

Definition 3.9 (η). We define the generators map.

$$\begin{aligned} \eta : A &\rightarrow \text{sList}(A) \\ a &\mapsto [a] \equiv a :: \text{nil} \end{aligned}$$

We show that $\text{sList}(A)$ is a commutative monoid with the empty multiset nil as unit and the binary multiplication given by the concatenation operation $\#$ defined below.

Definition 3.10 ($\#$). The concatenation operation $- \# - : \text{sList}(A) \rightarrow \text{sList}(A) \rightarrow \text{sList}(A)$ is defined by recursion on the first argument. On the point constructors, we have

$$\begin{aligned} \text{nil} \# ys &\equiv ys \\ (x :: xs) \# ys &\equiv x :: (xs \# ys) \end{aligned}$$

On the path constructors, we have

$$\begin{aligned} (x :: y :: xs) \# ys & \\ \equiv x :: y :: (xs \# ys) & \quad \text{definition} \\ \equiv y :: x :: (xs \# ys) & \quad \text{by swap}(x, y, xs \# ys) \\ \equiv (y :: x :: xs) \# ys & \quad \text{definition} \end{aligned}$$

Finally, $\text{sList}(A)$ is a set and so is $\text{sList}(A) \rightarrow \text{sList}(A)$, hence it respects trunc .

To show that $\text{sList}(A)$ is a commutative monoid, we need to prove a few identities about elements of $\text{sList}(A)$. Since $\text{sList}(A)$ is a set, its equality type is a proposition, so we can use the propositional induction principle from lemma 3.8. Hence, the proofs of monoid laws are just the same as the ones for lists.

Lemma 3.11. The concatenation operation $\#$ is associative and nil is a left and right unit.

1. For all $xs, ys, zs : \text{sList}(A)$, we have $xs \# (ys \# zs) = (xs \# ys) \# zs$.
2. For all $xs : \text{sList}(A)$, we have $\text{nil} \# xs = xs$.
3. For all $xs : \text{sList}(A)$, we have $xs \# \text{nil} = xs$.

We further need to establish that the concatenation operation is commutative. Similar to proving commutativity of addition for natural numbers, this is shown in two steps as follows.

Lemma 3.12. For $x : A$ and $xs, ys : \text{sList}(A)$, we have

1. $x :: xs = xs \# [x]$, and
2. $xs \# ys = ys \# xs$.

Proposition 3.13. For every type A , $\text{sList}(A)$ is a commutative monoid.

Proposition 3.14. Given a set A , a commutative monoid M , and a map $f : A \rightarrow M$ of sets, f extends to a homomorphism $f^\# : \text{CMon}(\text{sList}(A), M)$.

Theorem 3.15. For every set A , $\eta : A \rightarrow \text{sList}(A)$ is the free commutative monoid on A .

3.3 Equivalence of Presentations

As both FCM and sList satisfy the same (categorical) universal property, it follows that they are equivalent.

Theorem 3.16. *For every set A , $\text{FCM}(A) \simeq \text{sList}(A)$.*

Convention 3.1. *We will henceforth use $\mathcal{M}(A)$ to indicate the free commutative monoid on a set A that will be also referred to as the finite-multiset construction.*

Our results for \mathcal{M} will therefore apply to either FCM or sList using univalence and transport.

3.4 Commutativity

We have so far given a construction of the free commutative monoid as an endofunctor $\mathcal{M} : \text{hSet} \rightarrow \text{hSet}$. As it is standard, the free commutative monoid construction extends to a strong monad on Set.

Definition 3.17.

1. For a function between sets $f : A \rightarrow B$, there is a functorial action

$$\mathcal{M}(f) := (\lambda(a:A). \eta_B(fa))^{\sharp} : \mathcal{M}(A) \rightarrow \mathcal{M}(B)$$

2. unit

$$\eta_A : A \rightarrow \mathcal{M}(A)$$

3. multiplication

$$\mu_A := (\lambda(x:A). x)^{\sharp} : \mathcal{M}(\mathcal{M}(A)) \rightarrow \mathcal{M}(A)$$

4. left tensorial strength

$$\begin{aligned} \sigma_{A,B} : \mathcal{M}(A) \times B &\rightarrow \mathcal{M}(A \times B) \\ (as, b) &\mapsto \mathcal{M}(\lambda(a:A). (a, b))(as) \end{aligned}$$

5. right tensorial strength

$$\begin{aligned} \tau_{A,B} : A \times \mathcal{M}(B) &\rightarrow \mathcal{M}(A \times B) \\ (a, bs) &\mapsto \mathcal{M}(\lambda(b:B). (a, b))(bs) \end{aligned}$$

As shown below, the free commutative monoid monad is commutative in the categorical sense of Kock [31].

Proposition 3.18. *For all sets A and B , the following diagram commutes (upto homotopy).*

$$\begin{array}{ccc} \mathcal{M}(A) \times \mathcal{M}(B) & \xrightarrow{\sigma_{A, \mathcal{M}(B)}} & \mathcal{M}(A \times \mathcal{M}(B)) \\ \tau_{\mathcal{M}(A), B} \downarrow & & \downarrow \tau_{A, \mathcal{M}(B)}^{\sharp} \\ \mathcal{M}(\mathcal{M}(A) \times B) & \xrightarrow{\sigma_{A, B}^{\sharp}} & \mathcal{M}(A \times B) \end{array}$$

Example 3.1. *The free commutative monoid on $\mathbf{1}$, $\mathcal{M}(\mathbf{1})$, has the additive structure of natural numbers (proposition 3.2). Thereby, any free commutative monoid comes equipped with a length function.*

$$\ell_A := \mathcal{M}(\lambda(a:A). \star) : \mathcal{M}(A) \rightarrow \mathcal{M}(\mathbf{1}) .$$

The multiplicative structure of $\mathcal{M}(\mathbf{1})$ is given by

$$\begin{aligned} \eta(\star) &: \mathcal{M}(\mathbf{1}) \\ \pi_2^{\sharp} \circ \sigma_{\mathbf{1}, \mathcal{M}(\mathbf{1})} &: \mathcal{M}(\mathbf{1}) \times \mathcal{M}(\mathbf{1}) \rightarrow \mathcal{M}(\mathbf{1}) . \end{aligned}$$

This is commutative by proposition 3.18.

4 Singletons

As we will see in section 7, to characterise the equality type of finite multisets, we will require fundamental structural properties of them. In this section, we present combinatorial properties of singleton multisets.

We start by describing empty and singleton multisets. A multiset is empty if it is equal to nil, and it is a singleton if it is equal to the one-element multiset.

Definition 4.1. *For $as : \mathcal{M}(A)$,*

$$\begin{aligned} \text{isEmpty}(as) &:= (as = \text{nil}) \\ \text{isSing}(as) &:= \sum_{a:A} (as = [a]) \end{aligned}$$

Since the equality type of $\mathcal{M}(A)$ is a proposition, it follows that $\text{isEmpty}(as)$ is a proposition. Further, it is also the case that $\text{isSing}(as)$ is a proposition (since there is a unique choice for elements of a singleton).

Remark 4.1. *For any $as : \mathcal{M}(A)$, $\text{isEmpty}(as)$ and $\text{isSing}(as)$ are propositions.*

The empty multiset is characterised by being of length zero and singleton multisets are characterised by being of length one.

Proposition 4.2. *For $as : \mathcal{M}(A)$,*

1. $\text{isEmpty}(as) \Leftrightarrow (\ell(as) = 0)$, and
2. $\text{isSing}(as) \Leftrightarrow (\ell(as) = 1)$.

Definition 4.3. *The type (set) of multiset singletons over a set A is*

$$\text{Sing}(A) := \sum_{as:\mathcal{M}(A)} \text{isSing}(as)$$

One thus obtains a choice function $\text{Sing}(A) \rightarrow A$ extracting the (only) element of a singleton multiset. Further, we can identify elements with singletons.

Proposition 4.4. *The universal map $\eta_A : A \rightarrow \mathcal{M}(A)$ is an embedding; that is, for any $x, y : A$, $\text{ap}_{\eta} : x = y \rightarrow [x] = [y]$ is an equivalence.*

Corollary 4.5. *For any set A , $\pi_1 \circ \pi_2 : \text{Sing}(A) \rightarrow A$ is an equivalence.*

Finally, we establish properties of singleton multisets arising from concatenations and projections of multisets. These structural combinatorial properties will play a pivotal role in section 6.2.

Proposition 4.6. *Let A be a set.*

1. For $s : \mathcal{M}(\mathcal{M}(A))$, $a : A$,

$$\mu(s) = [a] \Leftrightarrow \exists (t : \mathcal{M}(\mathcal{M}(A))). \mu(t) = \text{nil} \wedge [a] :: t = s$$

2. For a set B and $t : \mathcal{M}(A \times B)$, $a : A$,

$$\mathcal{M}(\pi_1)(t) = [a] \Leftrightarrow \exists (b : B). t = [(a, b)]$$

3. For $as, bs : \mathcal{M}(A)$ and $a : A$,

$$as \# bs = [a] \Leftrightarrow (as = [a] \wedge bs = \text{nil}) \vee (as = \text{nil} \wedge bs = [a])$$

5 Generalized Logic

In this section, we provide first steps towards applications of the free commutative monoid construction. Specifically, we consider \mathbf{hSets} in \mathbf{HoTT} from the viewpoint of Lawvere's Generalized Logic [34]. The latter takes place in enriched category theory and the analogy that we pursue here is that of regarding \mathbf{hSets} as groupoids *intrinsically* enriched over propositions (or, in informal technical jargon, \mathbf{hProp} -groupoids with the groupoid structure provided by the identity type, where \mathbf{hProp} is considered with its complete Heyting algebra structure). Central to us, is that this turns out to provide the appropriate framework for developing the calculus of relations in \mathbf{HoTT} .

We begin by introducing powers, recalling that we work in predicative type theory and use subscripts to indicate universe levels.

Definition 5.1 (Power construction).

$$\begin{aligned} \mathfrak{P} &: \mathbf{hSet}_i \rightarrow \mathbf{hSet}_{i+1} \\ \mathfrak{P}(A) &:= A \rightarrow \mathbf{hProp}_i \end{aligned}$$

We note that the above is not a powerset construction; for instance, it is not even an endofunction on \mathbf{hSet}_i . If so inclined, one may turn it into the powerset monad using Voevodsky's *propositional resizing axiom* [40] to lower the universe level. Instead, we choose here to work with the power construction as a *relative monad* [1, 20] and follow the framework of Kleisli bicategories [27, 20] to consider relations in \mathbf{HoTT} . Henceforth, we drop the universe levels.

From the viewpoint of generalized logic, the power relative monad structure is given by the Yoneda embedding and left Kan extension along it. Internally, in \mathbf{HoTT} , these operations are easily constructed using the identity type and (suitably truncated) sigma types, respectively.

Definition 5.2 (Power relative monad). *We define the relative monad operations for \mathfrak{P} as follows.*

1. The unit is

$$\begin{aligned} y_A &: A \rightarrow \mathfrak{P}(A) \\ y_A(a) &:= \lambda(x : A). a =_A x \end{aligned}$$

2. The extension operation, for $f : A \rightarrow \mathfrak{P}(B)$, is

$$\begin{aligned} f^* &: \mathfrak{P}(A) \rightarrow \mathfrak{P}(B) \\ f^*(\alpha, b) &:= \exists (a : A). f(a, b) \wedge \alpha(a) \end{aligned}$$

We establish the properties of the Kleisli structure.

Proposition 5.3. *The following identities hold.*

1. $y_A^* = \text{id}_{\mathfrak{P}(A)}$.
2. For $f : A \rightarrow \mathfrak{P}(B)$, we have $f = f^* \circ y_A$.
3. For $f : A \rightarrow \mathfrak{P}(B)$ and $g : B \rightarrow \mathfrak{P}(C)$, we have that $(g^* \circ f)^* = g^* \circ f^*$.

Finally, one can define the category of relations (also see [38, Example 9.1.19]).

Definition 5.4 (Rel). *Rel has objects \mathbf{hSets} , and homs*

$$A \mapsto B := A \rightarrow \mathfrak{P}(B)$$

Proposition 5.5. *Rel is a (univalent) category.*

The category \mathbf{Rel} has a symmetric monoidal structure given by the cartesian product of sets $A \otimes B := A \times B$ with unit 1. It is also closed, with $A \multimap B := A \times B$:

$$\begin{aligned} C \otimes A \mapsto B &\equiv (C \times A) \rightarrow B \rightarrow \mathbf{hProp} \\ &\simeq C \rightarrow A \rightarrow B \rightarrow \mathbf{hProp} \\ &\simeq C \rightarrow (A \times B) \rightarrow \mathbf{hProp} \equiv C \mapsto (A \multimap B) \end{aligned}$$

In fact, \mathbf{Rel} is compact closed [17, 30], as the canonical map

$$\kappa : C \otimes (A \multimap B) \longrightarrow A \multimap (C \otimes B)$$

is an equivalence. Furthermore, as $A \multimap 1 \simeq A$, \mathbf{Rel} is self dual, with involution

$$(-)^\dagger : A \mapsto B \simeq B \mapsto A$$

given by

$$A \rightarrow (B \rightarrow \mathbf{hProp}) \simeq B \rightarrow (A \rightarrow \mathbf{hProp})$$

Definition 5.6. *We define the inclusion $(-)_* : \mathbf{Set} \rightarrow \mathbf{Rel}$ as mapping functions $f : A \rightarrow B$ to relations $y_B \circ f : A \mapsto B$.*

Note that $(-)_*$ preserves coproducts, which in \mathbf{Rel} become biproducts. This is important for sections 6.2 and 7.

6 Differential Linear Logic

In this section, we give a constructive formalisation of the relational model of differential linear logic [25, 18], developing it in \mathbf{HoTT} from the perspective of generalized logic considered in the previous section. We introduce the linear exponential and differential structures in sections 6.1 and 6.2 respectively.

6.1 Linear Exponential Structure

We will establish that the symmetric monoidal closed category with finite biproducts \mathbf{Rel} admits cofree commutative comonoids, and is therefore a model of linear logic with linear exponential structure [7, 28], as first considered by Lafont [33].

The key to the development is the lifting of (commutative) monoid structure to powers. This is achieved by means of Day's *promonoidal convolution* [16].

Theorem 6.1 (Promonoidal convolution). *If*

$$m : M \otimes M \rightarrow M \leftarrow 1 : e$$

is a (commutative) monoid in Rel, then $\mathfrak{P}(M)$ is a (commutative) monoid in Set, with multiplication $\hat{m} : \mathfrak{P}(M) \times \mathfrak{P}(M) \rightarrow \mathfrak{P}(M)$ and unit $\hat{e} : \mathfrak{P}(M)$ given by

$$\hat{m}(p, q)(x) := \exists (y:M). \exists (z:M). p(y) \wedge q(z) \wedge m(y, z)(x)$$

$$\hat{e}(x) := e(\star)(x)$$

Example 6.1. *Since $(-)_*$ maps products to tensors, every (commutative) monoid (M, \cdot, e) in Set yields a (commutative) monoid in Rel that, by promonoidal convolution (theorem 6.1), produces a (commutative) monoid $(\mathfrak{P}(M), \hat{\cdot}, \hat{e})$ in Set. In concrete terms,*

$$(p \hat{\cdot} q)(x) := \exists (y:M). \exists (z:M). p(y) \wedge q(z) \wedge (y \cdot z = x)$$

$$\hat{e}(x) := (e = x)$$

The universal property of \mathcal{M} lifts from Set to Rel.

Theorem 6.2. *For every set A , $y_A \circ \eta_A : A \rightarrow \mathcal{M}(A)$ is the free commutative monoid on A in Rel.*

We now turn our attention to the dual algebraic structure of commutative comonoids.

Definition 6.3 (Commutative comonoid). *A commutative comonoid in Rel is a set K with the following data:*

- a comultiplication $w : K \rightarrow K \otimes K$, and
- a counit $k : K \rightarrow 1$

satisfying the following commutative diagrams (upto homotopy):

$$\begin{array}{ccc} K & \xrightarrow{w} & K \otimes K \\ & \searrow \cong & \downarrow K \otimes k \\ & & K \otimes 1 \end{array}$$

$$\begin{array}{ccc} K & \xrightarrow{w} & K \otimes K \\ & \searrow \cong & \downarrow k \otimes K \\ & & 1 \otimes K \end{array}$$

$$\begin{array}{ccc} K & \xrightarrow{w} & K \otimes K \\ w \downarrow & & \downarrow K \otimes w \\ K \otimes K & \xrightarrow{w \otimes K} & K \otimes K \otimes K \end{array}$$

$$\begin{array}{ccc} & & K \otimes K \\ w \nearrow & & \downarrow \cong \\ K & & c \\ w \searrow & & \downarrow \\ & & K \otimes K \end{array}$$

where c is the symmetry isomorphism.

Example 6.2. *Each set has a unique commutative comonoid structure in Set which is preserved by $(-)_*$ to give a commutative comonoid structure on the set in Rel. This is the unique commutative comonoid structure on 0 and 1.*

Example 6.3. *In Rel, by self duality, every (commutative) monoid induces a (commutative) comonoid, and vice versa.*

Definition 6.4 (Homomorphism). *For commutative comonoids (K, w, k) and (K', w', k') , a relation $r : K \rightarrow K'$ is a homomorphism whenever*

- $w' \circ r = (r \otimes r) \circ w$, and
- $k' \circ r = k$.

Corollary 6.5. *For any set A , $\epsilon_A := ((\eta_A)_*)^\dagger : \mathcal{M}(A) \rightarrow A$ is the cofree commutative comonoid on A in Rel.*

Theorem 6.6. *Rel is a constructive model of linear logic, with linear exponential comonad structure as follows:*

$$\delta_A := ((\mu_A)_*)^\dagger : \mathcal{M}(A) \rightarrow \mathcal{M}(\mathcal{M}(A))$$

$$\epsilon_A := ((\eta_A)_*)^\dagger : \mathcal{M}(A) \rightarrow A$$

$$\varphi_{A,B} := (\epsilon_A \otimes \epsilon_B)_\# : \mathcal{M}(A) \times \mathcal{M}(B) \rightarrow \mathcal{M}(A \times B)$$

$$\phi := (\text{id}_1)_\# : 1 \rightarrow \mathcal{M}(1)$$

$$w_A := ((\#_A)_*)^\dagger : \mathcal{M}(A) \rightarrow \mathcal{M}(A) \times \mathcal{M}(A)$$

$$k_A := ((\lambda(x:1). \text{nil})_*)^\dagger : \mathcal{M}(A) \rightarrow 1$$

Proposition 6.7.

$$\varphi = (((\langle \mathcal{M}(\pi_1), \mathcal{M}(\pi_2) \rangle)_*)^\dagger), \quad \phi = (((\langle \rangle)_*)^\dagger)$$

We also have the Seely (or storage) isomorphisms [37].

Proposition 6.8.

$$\mathcal{M}(A) \times \mathcal{M}(B) \xrightarrow{\cong} \mathcal{M}(A + B), \quad 1 \xrightarrow{\cong} \mathcal{M}(0)$$

These give a strong monoidal functor from the biproduct structure to the symmetric monoidal structure.

We therefore have the following (see for instance [21, 19]), which plays an important role in sections 6.2 and 7.

Proposition 6.9. *In Rel, we define*

$$\begin{array}{ccc} \mathcal{M}(A) \times \mathcal{M}(A) & \xrightarrow{\cong} & \mathcal{M}(A + A) \\ m \searrow & & \swarrow \mathcal{M}(\nabla) \\ & \mathcal{M}(A) & \\ w \swarrow & & \searrow \mathcal{M}(\Delta) \\ \mathcal{M}(A) \times \mathcal{M}(A) & \xrightarrow{\cong} & \mathcal{M}(A + A) \end{array}$$

$$\begin{array}{ccc} 1 & \xrightarrow{\cong} & \mathcal{M}(0) \\ e \searrow & & \swarrow \mathcal{M}(u) \\ & \mathcal{M}(A) & \\ k \swarrow & & \searrow \mathcal{M}(n) \\ 1 & \xrightarrow{\cong} & \mathcal{M}(0) \end{array}$$

and have that the canonical commutative bialgebra structure for $(A, \nabla, \Delta, u, n)$ transfers to one for $(\mathcal{M}(A), m, w, e, k)$.

6.2 Differential Structure

Differential structure in categorical models of linear logic may be described in a variety of forms, see for instance [8, 21, 18]. Here, we follow the presentation of Fiore [21] in the context of models with biadditive structure (that is, biproducts). In Rel, this differential structure consists of a *creation map* [21, Definition 3.4]

$$\eta : A \rightarrow \mathcal{M}(A)$$

subject to three laws as follows (which as explained in [8] induce a *differential category* [9] structure):

$$\begin{array}{c}
 \begin{array}{ccc}
 & \mathcal{M}(A) & \\
 \eta \nearrow & & \searrow \epsilon \\
 A & \xrightarrow{\text{id}} & A
 \end{array} \\
 \\
 \begin{array}{ccccc}
 A & \xrightarrow{\eta} & !A & \xrightarrow{\delta} & !!A \\
 \cong \downarrow & & & & \uparrow m \\
 A \otimes I & \xrightarrow{\eta \otimes e} & !A \otimes !A & \xrightarrow{\eta \otimes \delta} & !!A \otimes !!A
 \end{array} \\
 \\
 \begin{array}{ccc}
 A \otimes \mathcal{M}(B) & \xrightarrow{\eta \otimes \text{id}} & \mathcal{M}(A) \otimes \mathcal{M}(B) \\
 \text{id} \otimes \epsilon \downarrow & & \downarrow \varphi \\
 A \otimes B & \xrightarrow{\eta} & \mathcal{M}(A \otimes B)
 \end{array}
 \end{array}$$

In elementary terms, the above amount to the properties below, that follow from the results of section 4.

- For $a, a' : A$,

$$a = a' \Leftrightarrow [a] = [a']$$

- For $a : A$ and $s : \mathcal{M}(\mathcal{M}(A))$,

$$[a] = \mu(s)$$

\Leftrightarrow

$$\exists (t : \mathcal{M}(\mathcal{M}(A))). \mu(t) = \text{nil} \wedge [a] :: t = s$$

- For $a : A$, $bs : \mathcal{M}(B)$ and $ps : \mathcal{M}(A \times B)$,

$$[a] = \mathcal{M}(\pi_1)(ps) \wedge bs = \mathcal{M}(\pi_2)(ps)$$

\Leftrightarrow

$$\exists (b : B). bs = [b] \wedge [(a, b)] = ps$$

We therefore have the following result.

Theorem 6.10. *Rel is a constructive model of differential linear logic.*

7 Multiset Equality

A central application of our development is an understanding of multiset equality. Indeed, we give a characterisation of multiset equality that, besides congruence relations, corresponds to the commutation relation of creation/annihilation operators associated with the multiset construction seen as a combinatorial Fock space. We refer the reader to Fiore [21, 19] for this theory.

From proposition 6.9, we have the following bialgebra law:

$$\begin{array}{ccc}
 \mathcal{M}(A)^2 & \xrightarrow{m} & \mathcal{M}(A) & \xrightarrow{w} & \mathcal{M}(A)^2 \\
 w \times w \downarrow & & & & \uparrow m \times m \\
 \mathcal{M}(A)^4 & \xrightarrow{\text{id}} & \mathcal{M}(A) \times c \times \mathcal{M}(A) & \xrightarrow{\text{id}} & \mathcal{M}(A)^4
 \end{array}$$

Spelling this out in elementary terms, we have that, for $as, bs, cs, ds : \mathcal{M}(A)$,

$$as \# bs = cs \# ds$$

\Leftrightarrow

$$\exists (xs_1, xs_2, ys_1, ys_2 : \mathcal{M}(A)).$$

$$as = xs_1 \# xs_2 \wedge bs = ys_1 \# ys_2$$

$$\wedge xs_1 \# ys_1 = cs \wedge xs_2 \# ys_2 = ds$$

Thus, it follows that, for $a : A$ and $as, bs, cs : \mathcal{M}(A)$,

$$a :: as = bs \# cs$$

\Leftrightarrow

$$(\exists (xs : \mathcal{M}(A)). a :: xs = bs \wedge as = xs \# cs)$$

$$\vee (\exists (ys : \mathcal{M}(A)). a :: ys = cs \wedge as = bs \# ys)$$

and we obtain the characterisation below as a corollary.

Theorem 7.1 (Commutation relation). *For a set A , $a, b : A$, and $as, bs : \mathcal{M}(A)$,*

$$a :: as = b :: bs$$

\Leftrightarrow

$$(a = b \wedge as = bs)$$

$$\vee (\exists (cs : \mathcal{M}(A)). as = b :: cs \wedge a :: cs = bs)$$

In addition, cons and nil are disjoint.

Proposition 7.2 (Disjointness). *For a set A , $a : A$, and $as : \mathcal{M}(A)$,*

$$(a :: as = \text{nil}) \Rightarrow \perp$$

8 Commuted-List Construction

The commutation relation (theorem 7.1) embodies the following deduction rule for multiset equality:

$$\frac{as = b :: cs \quad a :: cs = bs}{a :: as = b :: bs} \text{ comm}$$

As can be seen from the examples below, this is to be regarded as a generalised-swap operation.

Example 8.1. *For $a, b, c : A$ and $cs, ds : \mathcal{M}(A)$,*

1.

$$\frac{b :: cs = b :: cs \quad a :: cs = a :: cs}{a :: b :: cs = b :: a :: cs} \text{ comm}$$

2.

$$\frac{b :: c :: ds = c :: b :: ds \quad a :: b :: ds = b :: a :: ds}{a :: b :: c :: ds = c :: b :: a :: ds} \text{ comm}$$

We now introduce a presentation for finite multisets that uses the deduction rule comm as a path constructor. This is novel in being *conditional* equational and is the only natural example of such a HIT that we are aware of.

Definition 8.1 (cList). For a type A , the HIT $\text{cList}(A)$ is given by the following point and path constructors:

$$\begin{aligned} \text{nil} &: \text{cList}(A) \\ - :: - &: A \times \text{cList}(A) \rightarrow \text{cList}(A) \\ \text{comm} &: \{a \ b : A\} \{as \ bs \ cs : \text{cList}(A)\} \\ &\rightarrow (as = b :: cs) \rightarrow (a :: cs = bs) \\ &\rightarrow a :: as = b :: bs \\ \text{trunc} &: \text{isSet}(\text{cList}(A)) \end{aligned}$$

The above uses the standard constructors for lists but, instead of a swap constructor, it adds the generalised comm path constructor. Since comm takes as argument paths in cList, it is a conditional path constructor.

Definition 8.2 (Induction principle for cList). For every type family $P : \text{cList}(A) \rightarrow \mathcal{U}$ with the following data:

$$\begin{aligned} \text{nil}^* &: P(\text{nil}) \\ - ::^* - &: (a : A) \{as : \text{cList}(A)\} \rightarrow P(as) \rightarrow P(a :: as) \\ \text{comm}^* &: \{a \ b : A\} \{as \ bs \ cs : \text{cList}(A)\} \\ &\rightarrow \{pas : P(as)\} \{pbs : P(bs)\} \{pcs : P(cs)\} \\ &\rightarrow (p : as = b :: cs) \rightarrow (pas =_p^P b ::^* pcs) \\ &\rightarrow (q : a :: cs = bs) \rightarrow (a ::^* pcs =_q^P pbs) \\ &\rightarrow a ::^* pas =_{\text{comm}(p,q)}^P b ::^* pbs \\ \text{trunc}^* &: (as : \text{cList}(A)) \rightarrow \text{isSet}(P(as)) \end{aligned}$$

there is a unique function $f : (as : \text{cList}(A)) \rightarrow P(as)$ with the following computation rules.

$$\begin{aligned} f(\text{nil}) &\equiv \text{nil}^* \\ f(a :: as) &\equiv a ::^* f(as) \\ \text{apd}_f(\text{comm}(p, q)) &= \text{comm}^*(p, \text{apd}_f(p), q, \text{apd}_f(q)) \end{aligned}$$

Note that from example 8.1, the swap operation can be recovered as

$$\begin{aligned} \text{swap}(x, y, xs) \\ \equiv \text{comm}(\text{refl}, \text{refl}) : (x :: y :: xs) = (y :: x :: xs) \end{aligned}$$

Proposition 8.3. For every set A , $\text{cList}(A)$ is a commutative monoid.

Theorem 8.4 (Universal property of cList). For every set A , $\eta : A \rightarrow \text{sList}(A)$ is the free commutative monoid on A .

Theorem 8.5 (Equivalence of sList and cList). For every set A , $\text{sList}(A) \simeq \text{cList}(A)$.

9 Multiset-Equality Deduction System

From the commuted-list construction (definition 8.1), one may extract a sound and complete deduction system for multiset equality. This is formalised below and, besides congruence rules, consists of a commutation rule.

Definition 9.1. For a type A , let $\sim : \mathcal{M}(A) \times \mathcal{M}(A) \rightarrow \mathcal{U}$ be the inductive family with the following constructors:

$$\begin{aligned} \text{nil-cong} &: \text{nil} \sim \text{nil} \\ \text{cons-cong} &: \{a \ b : A\} \{as \ bs : \mathcal{M}(A)\} \\ &\rightarrow (a = b) \rightarrow (as \sim bs) \\ &\rightarrow (a :: as \sim b :: bs) \\ \text{comm-rule} &: \{a \ b : A\} \{as \ bs \ cs : \mathcal{M}(A)\} \\ &\rightarrow (as \sim b :: cs) \rightarrow (a :: cs \sim bs) \\ &\rightarrow (a :: as \sim b :: bs) \end{aligned}$$

Example 9.1. For $a : A$, the type

$$(a :: a :: \text{nil} \sim a :: a :: \text{nil})$$

is inhabited by both

$$\text{cons-cong}(\text{refl}, \text{cons-cong}(\text{refl}, \text{nil-cong}))$$

and

$$\begin{aligned} \text{comm-rule} \\ (\text{cons-cong}(\text{refl}, \text{nil-cong}), \text{cons-cong}(\text{refl}, \text{nil-cong})) \end{aligned}$$

Proposition 9.2. For a set A and $as, bs : \mathcal{M}(A)$, we have a soundness map

$$(as \sim bs) \rightarrow (as = bs)$$

Definition 9.3. For $as, bs : \mathcal{M}(A)$, let

$$(as \approx bs) := \|\text{as} \sim \text{bs}\|_{-1}$$

Proposition 9.4. For a set A , we have a reflexivity map

$$(as : \mathcal{M}(A)) \rightarrow (as \approx as)$$

As a corollary, our deduction system is sound and complete for multiset equality.

Theorem 9.5 (Soundness and Completeness). For a set A and $as, bs : \mathcal{M}(A)$,

$$(as \approx bs) \Leftrightarrow (as = bs)$$

10 Discussion and Related Work

We have described various constructions of free commutative monoids using set-truncated HITs.

The type FCM is a non-recursive HIT, the type sList is a recursive HIT, and the type cList is a recursive HIT with conditional path constructors. While Cubical Agda [39] accepts all three HIT definitions, the status of defining HITs in HoTT and Cubical type theories in general is an open research question. Various schemas for defining HITs have been proposed [35, 14, 11, 22, 23]. HITs have also been used in other computer science applications [5, 24, 6, 4].

A drawback of our HITs is that they are 0-truncated, which only allows elimination into sets. An interesting problem is to figure out whether finite-multisets can be defined without the truncation constructor. In type theory, permutations can be encoded as bijections $\text{Fin}(n) \simeq \text{Fin}(n)$. Altenkirch proposes an encoding of finite-multisets on A as functions $\text{Fin}(n) \rightarrow A$,

that is, functions with finite support, with equality of multisets given by a permutation $\phi : \text{Fin}(n) \simeq \text{Fin}(n)$. This can be encoded using a setoid. However, this definition does not lead to the categorical universal property, which is the one we are exploiting in this paper.

Other definitions of finite multisets in type theory have been considered before, for instance using setoids [15, 26, 4]. None of these encodings prove the universal property of free commutative monoids and most results use the assumption of decidable equality. Hence, our characterisation of multiset equality is novel.

There are other ways of representing permutations in type theory, for instance one could also quotient lists by a different encoding of the permutation relation. There are well-established codes for representing permutations, such as Lehmer codes, or subexcedant sequences, corresponding to words in the symmetric group. Using these techniques and appealing to proofs of monoidal coherence theorems in type theory, it is possible to prove the categorical universal property [12].

A previous version of this work, with extensions to free symmetric monoidal groupoids and the construction of the bicategory of generalised species, has been considered by Choudhury and Fiore [12]. Generalising to groupoids requires a higher path constructor to establish coherence of swap. The construction of the free symmetric monoidal groupoid has also been considered by Piccighello [36].

References

- [1] Thorsten Altenkirch, James Chapman, and Tarmo Uustalu. 2010. Monads Need Not Be Endofunctors. In *Foundations of Software Science and Computational Structures (Lecture Notes in Computer Science)*, Luke Ong (Ed.). Springer, Berlin, Heidelberg, 297–311. https://doi.org/10.1007/978-3-642-12032-9_21
- [2] Thorsten Altenkirch and Luis Scoccola. 2020. The Integers as a Higher Inductive Type. In *Proceedings of the 35th Annual ACM/IEEE Symposium on Logic in Computer Science (LICS '20)*. Association for Computing Machinery, New York, NY, USA, 67–73. <https://doi.org/10.1145/3373718.3394760>
- [3] Carlo Angiuli. 2019. *Computational Semantics of Cartesian Cubical Type Theory*. Ph.D. Dissertation. Carnegie Mellon University, Pittsburgh, PA. <https://www.cs.cmu.edu/~cangiuli/thesis/thesis.pdf>
- [4] Carlo Angiuli, Evan Cavallo, Anders Mörtberg, and Max Zeuner. 2021. Internalizing Representation Independence with Univalence. *Proceedings of the ACM on Programming Languages* 5, POPL (Jan. 2021), 12:1–12:30. <https://doi.org/10.1145/3434293>
- [5] Carlo Angiuli, Edward Morehouse, Daniel R. Licata, and Robert Harper. 2016/ed. Homotopical Patch Theory*. *Journal of Functional Programming* 26 (2016/ed). <https://doi.org/10.1017/S0956796816000198>
- [6] Henning Basold, Herman Geuvers, and Niels van der Weide. 2017. Higher Inductive Types in Programming. (2017). <https://doi.org/10.3217/JUCS-023-01-0063>
- [7] Nick Benton, Gavin Bierman, Valeria de Paiva, and Martin Hyland. 1993. Linear λ -Calculus and Categorical Models Revisited. In *Computer Science Logic (Lecture Notes in Computer Science)*, E. Börger, G. Jäger, H. Kleine Büning, S. Martini, and M. M. Richter (Eds.). Springer, Berlin, Heidelberg, 61–84. https://doi.org/10.1007/3-540-56992-8_6
- [8] R. F. Blute, J. R. B. Cockett, J.-S. P. Lemay, and R. A. G. Seely. 2020. Differential Categories Revisited. *Applied Categorical Structures* 28, 2 (April 2020), 171–235. <https://doi.org/10.1007/s10485-019-09572-y>
- [9] R. F. Blute, J. R. B. Cockett, and R. a. G. Seely. 2006. Differential Categories. *Mathematical Structures in Computer Science* 16, 6 (Dec. 2006), 1049–1083. <https://doi.org/10.1017/S0960129506005676>
- [10] Ulrik Buchholtz, Floris van Doorn, and Egbert Rijke. 2018. Higher Groups in Homotopy Type Theory. In *Proceedings of the 33rd Annual ACM/IEEE Symposium on Logic in Computer Science (LICS '18)*. Association for Computing Machinery, New York, NY, USA, 205–214. <https://doi.org/10.1145/3209108.3209150>
- [11] Evan Cavallo and Robert Harper. 2019. Higher Inductive Types in Cubical Computational Type Theory. *Proceedings of the ACM on Programming Languages* 3, POPL (Jan. 2019), 1:1–1:27. <https://doi.org/10.1145/3290314>
- [12] Vikraman Choudhury and Marcelo Fiore. 2019. The Finite-Multiset Construction in HoTT. (Aug. 2019), 40. <https://hott.github.io/HoTT-2019/conf-slides/Choudhury.pdf>
- [13] Cyril Cohen, Thierry Coquand, Simon Huber, and Anders Mörtberg. 2018. Cubical Type Theory: A Constructive Interpretation of the Univalence Axiom. (2018), 34 pages. <https://doi.org/10.4230/LIPICS.TYPES.2015.5>
- [14] Thierry Coquand, Simon Huber, and Anders Mörtberg. 2018. On Higher Inductive Types in Cubical Type Theory. In *Proceedings of the 33rd Annual ACM/IEEE Symposium on Logic in Computer Science (LICS '18)*. Association for Computing Machinery, New York, NY, USA, 255–264. <https://doi.org/10.1145/3209108.3209197>
- [15] Nils Anders Danielsson. 2012. Bag Equivalence via a Proof-Relevant Membership Relation. In *Interactive Theorem Proving (Lecture Notes in Computer Science)*, Lennart Beringer and Amy Felty (Eds.). Springer, Berlin, Heidelberg, 149–165. https://doi.org/10.1007/978-3-642-32347-8_11
- [16] Brian Day. 1970. On Closed Categories of Functors. In *Reports of the Midwest Category Seminar IV (Lecture Notes in Mathematics)*, S. MacLane, H. Applegate, M. Barr, B. Day, E. Dubuc, Phreilambud, A. Pultr, R. Street, M. Tierney, and S. Swierczkowski (Eds.). Springer, Berlin, Heidelberg, 1–38. <https://doi.org/10.1007/BFb0060438>
- [17] B. J. Day. 1977. Note on Compact Closed Categories. *Journal of the Australian Mathematical Society* 24, 3 (Nov. 1977), 309–311. <https://doi.org/10.1017/S1446788700020334>
- [18] Thomas Ehrhard. 2018. An Introduction to Differential Linear Logic: Proof-Nets, Models and Antiderivatives. *Mathematical Structures in Computer Science* 28, 7 (Aug. 2018), 995–1060. <https://doi.org/10.1017/S0960129516000372>
- [19] Marcelo Fiore. 2015. An Axiomatics and a Combinatorial Model of Creation/Annihilation Operators. *arXiv:1506.06402 [math]* (June 2015). [arXiv:1506.06402 \[math\]](https://arxiv.org/abs/1506.06402) <http://arxiv.org/abs/1506.06402>
- [20] Marcelo Fiore, Nicola Gambino, Martin Hyland, and Glynn Winskel. 2018. Relative Pseudomonads, Kleisli Bicategories, and Substitution Monoidal Structures. *Selecta Mathematica* 24, 3 (July 2018), 2791–2830. <https://doi.org/10.1007/s00029-017-0361-3> [arXiv:1612.03678](https://arxiv.org/abs/1612.03678)
- [21] Marcelo P. Fiore. 2007. Differential Structure in Models of Multiplicative Biadditive Intuitionistic Linear Logic. In *Typed Lambda Calculi and Applications (Lecture Notes in Computer Science)*, Simona Ronchi Della Rocca (Ed.). Springer, Berlin, Heidelberg, 163–177. https://doi.org/10.1007/978-3-540-73228-0_13
- [22] Marcelo P. Fiore, Andrew M. Pitts, and S. C. Steenkamp. 2020. Constructing Infinitary Quotient-Inductive Types. In *Foundations of Software Science and Computation Structures (Lecture Notes in Computer Science)*, Jean Goubault-Larrecq and Barbara König (Eds.). Springer International Publishing, Cham, 257–276. https://doi.org/10.1007/978-3-030-45231-5_14
- [23] Marcelo P. Fiore, Andrew M. Pitts, and S. C. Steenkamp. 2021. Quotients, Inductive Types, and Quotient Inductive

- Types. *arXiv:2101.02994 [cs]* (Jan. 2021). [arXiv:2101.02994 \[cs\]](https://arxiv.org/abs/2101.02994)
[http://arxiv.org/abs/2101.02994](https://arxiv.org/abs/2101.02994)
- [24] Dan Frumin, Herman Geuvers, Léon Gondelman, and Niels van der Weide. 2018. Finite Sets in Homotopy Type Theory. In *Proceedings of the 7th ACM SIGPLAN International Conference on Certified Programs and Proofs (CPP 2018)*. Association for Computing Machinery, New York, NY, USA, 201–214. <https://doi.org/10.1145/3167085>
- [25] Jean-Yves Girard. 1987. Linear Logic. *Theoretical Computer Science* 50, 1 (Jan. 1987), 1–101. [https://doi.org/10.1016/0304-3975\(87\)90045-4](https://doi.org/10.1016/0304-3975(87)90045-4)
- [26] Håkon Robbestad Gylterud. 2020. Multisets in Type Theory. *Mathematical Proceedings of the Cambridge Philosophical Society* 169, 1 (July 2020), 1–18. <https://doi.org/10.1017/S0305004119000045>
- [27] J. M. E. Hyland. 2014. Elements of a Theory of Algebraic Theories. *Theoretical Computer Science* 546 (Aug. 2014), 132–144. <https://doi.org/10.1016/j.tcs.2014.03.005>
- [28] Martin Hyland and Andrea Schalk. 2003. Glueing and Orthogonality for Models of Linear Logic. *Theoretical Computer Science* 294, 1 (Feb. 2003), 183–231. [https://doi.org/10.1016/S0304-3975\(01\)00241-9](https://doi.org/10.1016/S0304-3975(01)00241-9)
- [29] Chris Kapulkin, Peter LeFanu Lumsdaine, and Vladimir Voevodsky. 2018. Univalence in Simplicial Sets. *arXiv:1203.2553 [math]* (Oct. 2018). [arXiv:1203.2553 \[math\]](https://arxiv.org/abs/1203.2553) <http://arxiv.org/abs/1203.2553>
- [30] G. M. Kelly and M. L. Laplaza. 1980. Coherence for Compact Closed Categories. *Journal of Pure and Applied Algebra* 19 (Dec. 1980), 193–213. [https://doi.org/10.1016/0022-4049\(80\)90101-2](https://doi.org/10.1016/0022-4049(80)90101-2)
- [31] Anders Kock. 1970. Monads on Symmetric Monoidal Closed Categories. *Archiv der Mathematik* 21, 1 (Dec. 1970), 1–10. <https://doi.org/10.1007/BF01220868>
- [32] Nicolai Kraus and Thorsten Altenkirch. 2018. Free Higher Groups in Homotopy Type Theory. In *Proceedings of the 33rd Annual ACM/IEEE Symposium on Logic in Computer Science (LICS '18)*. Association for Computing Machinery, New York, NY, USA, 599–608. <https://doi.org/10.1145/3209108.3209183>
- [33] Y. Lafont. 1988. The Linear Abstract Machine. *Theoretical Computer Science* 59, 1 (July 1988), 157–180. [https://doi.org/10.1016/0304-3975\(88\)90100-4](https://doi.org/10.1016/0304-3975(88)90100-4)
- [34] F. William Lawvere. 1973. Metric Spaces, Generalized Logic, and Closed Categories. *Rendiconti del Seminario Matematico e Fisico di Milano* 43, 1 (Dec. 1973), 135–166. <https://doi.org/10.1007/BF02924844>
- [35] Peter Lefanu Lumsdaine and Michael Shulman. 2020. Semantics of Higher Inductive Types. *Mathematical Proceedings of the Cambridge Philosophical Society* 169, 1 (July 2020), 159–208. <https://doi.org/10.1017/S030500411900015X>
- [36] Stefano Piceghello. 2019. Coherence for Symmetric Monoidal Groupoids in HoTT/UF. (2019), 2. http://www.ii.uib.no/~bezem/abstracts/TYPES_2019_paper_10
- [37] R. A. G. Seely. 1989. Linear Logic, *-Autonomous Categories and Cofree Coalgebras. In *In Categories in Computer Science and Logic*. American Mathematical Society, 371–382.
- [38] The Univalent Foundations Program. 2013. *Homotopy Type Theory: Univalent Foundations of Mathematics*. Univalent Foundations Program, Institute for Advanced Study. <https://homotopytypetheory.org/book>
- [39] Andrea Vezzosi, Anders Mörtberg, and Andreas Abel. 2019. Cubical Agda: A Dependently Typed Programming Language with Univalence and Higher Inductive Types. *Proceedings of the ACM on Programming Languages* 3, ICFP (July 2019), 87:1–87:29. <https://doi.org/10.1145/3341691>
- [40] Vladimir Voevodsky. 2011. Resizing Rules - Their Use and Semantic Justification. https://www.math.ias.edu/vladimir/sites/math.ias.edu.vladimir/files/2011_Bergen.pdf

A Proofs for Section 3 (The Free Commutative Monoid Monad)

Theorem 3.5. For every set A , $\eta : A \rightarrow \text{FCM}(A)$ is the free commutative monoid on A .

Proof. Assuming $f : A \rightarrow M$, we define $f^\# : \text{FCM}(A) \rightarrow M$ by induction. It is straightforward to check that $f^\#$ is a homomorphism. Finally, we need show that $(-)^{\#}$ is inverse to $(-) \circ \eta$. We establish the homotopies $(h \circ \eta)^\# \sim h$ and $f^\# \circ \eta \sim f$ by calculation. \square

Lemma 3.8 (Propositional induction principle for sList). Let $P : \text{sList}(A) \rightarrow \mathcal{U}$ be a type family with the following data.

$$\begin{aligned} \text{nil}^* &: P(\text{nil}) \\ - ::^* - &: (x : A)\{xs : \text{sList}(A)\} \rightarrow P(xs) \rightarrow P(x :: xs) \\ \text{trunc}^* &: (xs : \text{sList}(A)) \rightarrow \text{isProp}(P(xs)) \end{aligned}$$

Then, there is a unique function $f : (xs : \text{sList}(A)) \rightarrow P(xs)$ satisfying the appropriate computation rules.

Proof. Using the standard induction principle for sList, we need to give an image swap^* for swap . Consider $\phi_1 : P(x :: y :: xs)$ and $\phi_2 : P(y :: x :: xs)$. Transporting ϕ_1 along swap , and using the fact that they are propositions, one gets the path $\phi_1 =_{\text{swap}(x,y,xs)}^P \phi_2$. \square

Lemma 3.11. The concatenation operation $\#$ is associative and nil is a left and right unit.

1. For all $xs, ys, zs : \text{sList}(A)$, we have $xs \# (ys \# zs) = (xs \# ys) \# zs$.
2. For all $xs : \text{sList}(A)$, we have $\text{nil} \# xs = xs$.
3. For all $xs : \text{sList}(A)$, we have $xs \# \text{nil} = xs$.

Proof. By the propositional induction principle, the only required cases are for nil and $::$, and this is the same proof as for lists. \square

Lemma 3.12. For $x : A$ and $xs, ys : \text{sList}(A)$, we have

1. $x :: xs = xs \# [x]$, and
2. $xs \# ys = ys \# xs$.

Proof. The idea is to recursively apply the swap constructor to shift the first element to the end. To prove commutativity by induction, the multiset is first split into appends of singleton multisets.

1. By induction on xs , we have

$$x :: \text{nil} = \text{nil} \# [x] \quad \text{left unit}$$

and

$$\begin{aligned} &x :: (y :: xs) \\ &= y :: (x :: xs) && \text{by } \text{swap}(x, y, xs) \\ &= y :: (xs \# [x]) && \text{induction hypothesis} \\ &\equiv y :: (xs \# [x]) && \text{definition} \end{aligned}$$

2. By induction on xs , we have

$$\begin{aligned} &\text{nil} \# ys \\ &\equiv ys && \text{definition} \\ &= ys \# \text{nil} && \text{right unit} \end{aligned}$$

and

$$\begin{aligned}
& (x :: xs) \# ys \\
\equiv & x :: (xs \# ys) && \text{definition} \\
= & x :: (ys \# xs) && \text{induction hypothesis} \\
\equiv & (x :: ys) \# xs && \text{definition} \\
= & (ys \# [x]) \# xs && \text{item 1} \\
= & ys \# ([x] \# xs) && \text{associativity} \\
\equiv & ys \# (x :: xs) && \text{definition}
\end{aligned}$$

□

Proposition 3.14. *Given a set A , a commutative monoid M , and a map $f : A \rightarrow M$ of sets, f extends to a homomorphism $f^\# : \text{CMon}(\text{sList}(A), M)$.*

Proof. We define $f^\# : \text{sList}(A) \rightarrow M$ by induction. On the point constructors, we define

$$\begin{aligned}
f^\#(\text{nil}) &::= e \\
f^\#(x :: xs) &::= f(x) \cdot f^\#(xs)
\end{aligned}$$

On the path constructor, we have

$$\begin{aligned}
& f(x) \cdot f(y) \cdot f^\#(xs) \\
= & (f(x) \cdot f(y)) \cdot f^\#(xs) && \text{associativity} \\
= & (f(y) \cdot f(x)) \cdot f^\#(xs) && \text{commutativity} \\
= & f(y) \cdot f(x) \cdot f^\#(xs) && \text{associativity}
\end{aligned}$$

To check that this is a homomorphism, we establish that $f^\#(xs \# ys) = f^\#(xs) \cdot f^\#(ys)$ for all $xs, ys : \text{sList}(A)$. Since this is a proposition, by induction on xs , we have

$$\begin{aligned}
& f^\#(\text{nil} \# ys) \\
\equiv & f^\#(ys) && \text{definition} \\
= & e \cdot f^\#(ys) && \text{unit law} \\
\equiv & f^\#(\text{nil}) \cdot f^\#(ys) && \text{definition} \\
\\
& f^\#((x :: xs) \# ys) \\
\equiv & f^\#(x :: (xs \# ys)) && \text{definition} \\
\equiv & f(x) \cdot f^\#(xs \# ys) && \text{definition} \\
= & f(x) \cdot (f^\#(xs) \cdot f^\#(ys)) && \text{induction hypothesis} \\
= & (f(x) \cdot f^\#(xs)) \cdot f^\#(ys) && \text{associativity} \\
\equiv & f^\#(x :: xs) \cdot f^\#(ys) && \text{definition}
\end{aligned}$$

□

Theorem 3.15. *For every set A , $\eta : A \rightarrow \text{sList}(A)$ is the free commutative monoid on A .*

Proof. We need to show that $(-)^{\#}$ is inverse to $(-) \circ \eta$. We establish the homotopies $(h \circ \eta)^{\#} \sim h$ and $f^{\#} \circ \eta \sim f$ by calculation. □

Theorem 3.16. *For every set A , $\text{FCM}(A) \simeq \text{sList}(A)$.*

Proof. The two maps are constructed by extending η , that is, $\eta^{\#}$. Using the universal property, their composition is homotopic to id . □

Proposition 3.18. *For all sets A and B , the following diagram commutes (upto homotopy).*

$$\begin{array}{ccc}
 \mathcal{M}(A) \times \mathcal{M}(B) & \xrightarrow{\sigma_{A,\mathcal{M}(B)}} & \mathcal{M}(A \times \mathcal{M}(B)) \\
 \tau_{\mathcal{M}(A),B} \downarrow & & \downarrow \tau_{A,B^\#} \\
 \mathcal{M}(\mathcal{M}(A) \times B) & \xrightarrow{\sigma_{A,B^\#}} & \mathcal{M}(A \times B)
 \end{array}$$

Proof. We need to establish the equality $\tau^\# \circ \sigma = \sigma^\# \circ \tau$. By function extensionality, we need to show that for all $as : \text{sList}(A)$ and $bs : \text{sList}(B)$, $\tau^\#(\sigma(as, bs)) = \sigma^\#(\tau(as, bs))$. This follows by induction on as and bs , using the propositional induction principle. \square

B Proofs for Section 4 (Singletons)

Proposition 4.2. *For $as : \mathcal{M}(A)$,*

1. $\text{isEmpty}(as) \Leftrightarrow (\ell(as) = 0)$, and
2. $\text{isSing}(as) \Leftrightarrow (\ell(as) = 1)$.

Proof. We characterise the path space of the singleton and empty multisets by using the induction principle for sList . Note that, swap only acts on multisets of length at least 2, hence the case for swap can be eliminated. \square

Proposition 4.4. *The universal map $\eta_A : A \rightarrow \mathcal{M}(A)$ is an embedding; that is, for any $x, y : A$, $\text{ap}_\eta : x = y \rightarrow [x] = [y]$ is an equivalence.*

Proof. To construct the inverse to ap_η , we apply the unique choice function to the singleton multisets $[x]$ and $[y]$. \square

Proposition 4.6. *Let A be a set.*

1. For $s : \mathcal{M}(\mathcal{M}(A))$, $a : A$,

$$\mu(s) = [a] \Leftrightarrow \exists (t : \mathcal{M}(\mathcal{M}(A))). \mu(t) = \text{nil} \wedge [a] :: t = s$$

2. For a set B and $t : \mathcal{M}(A \times B)$, $a : A$,

$$\mathcal{M}(\pi_1)(t) = [a] \Leftrightarrow \exists (b : B). t = [(a, b)]$$

3. For $as, bs : \mathcal{M}(A)$ and $a : A$,

$$as \# bs = [a] \Leftrightarrow (as = [a] \wedge bs = \text{nil}) \vee (as = \text{nil} \wedge bs = [a])$$

Proof. Since these are equivalences of propositions, one simply needs to write down both the maps. Going from right to left is easy and just follows by calculation. To go from left to right, we use the characterisation of the path space of singleton multisets and the unique choice function. \square

C Proofs for Section 5 (Generalized Logic)

Proposition 5.3. *The following identities hold.*

1. $\mathbf{y}_A^* = \text{id}_{\mathfrak{P}(A)}$.
2. For $f : A \rightarrow \mathfrak{P}(B)$, we have $f = f^* \circ \mathbf{y}_A$.
3. For $f : A \rightarrow \mathfrak{P}(B)$ and $g : B \rightarrow \mathfrak{P}(C)$, we have that $(g^* \circ f)^* = g^* \circ f^*$.

Proof.

1. For any $f : A \rightarrow \mathfrak{P}(A)$ and $a : A$, we have

$$\begin{aligned}
 \mathbf{y}_A^*(f, a) &\equiv \exists (b : A). \mathbf{y}_A(a, b) \times f(a) \\
 &\equiv \exists (b : A). (a = b) \times f(a) \\
 &\simeq f(a)
 \end{aligned}$$

2. For any $a : A$ and $b : B$, we have

$$\begin{aligned}
 f^*(\mathbf{y}_A(a), b) &\equiv \exists (c : A). f(c, b) \times \mathbf{y}_A(a, c) \\
 &\equiv \exists (c : A). f(c, b) \times (a = c) \\
 &= f(a, b)
 \end{aligned}$$

3. For any $\alpha : \mathfrak{P}(A)$ and $c : C$, we have

$$\begin{aligned}
& (g^* \circ f)^*(\alpha, c) \\
& \equiv \exists_{(x:A)}. (g^* \circ f)(x, c) \times \alpha(x) \\
& \equiv \exists_{(x:A)}. g^*(f(x))(c) \times \alpha(x) \\
& \equiv \exists_{(x:A)}. \exists_{(y:B)}. (g(y, c) \times f(x, y)) \times \alpha(x) \\
& \simeq \exists_{(y:B)}. g(y, c) \times (\exists_{(x:A)}. f(x, y) \times \alpha(x)) \\
& \equiv \exists_{(y:B)}. (g(y, c) \times f^*(\alpha)(y)) \\
& \equiv g^*(f^*(\alpha))(c) \\
& \equiv (g^* \circ f^*)(\alpha, c)
\end{aligned}$$

□

Proposition 5.5. *Rel is a (univalent) category.*

Proof. We note that $\text{Hom}_{\text{Rel}}(A, B) \equiv A \rightarrow B$ is an hSet since hProp is. The identity arrow $1_A : \text{Hom}(A, A)$ is given by y_A . The composition of $g : B \rightarrow C$ and $f : A \rightarrow B$ is given by $g^* \circ f$. The unit and associativity laws follow from proposition 5.3. To show that Rel is univalent, see [38, Example 9.1.19]. □

D Proofs for Section 6 (Differential Linear Logic)

Theorem 6.2. *For every set A , $y_A \circ \eta_A : A \rightarrow \mathcal{M}(A)$ is the free commutative monoid on A in Rel .*

Proof. For a commutative monoid M in Rel and $f : A \rightarrow M$, one needs to define a unique homomorphic extension $\mathcal{M}(A) \rightarrow M$. Using that $\mathfrak{P}(M)$ is a commutative monoid in Set , this is given by $f^\# : \mathcal{M}(A) \rightarrow \mathfrak{P}(M)$. The rest of the argument is established by calculation. □

Corollary 6.5. *For any set A , $\epsilon_A \equiv ((\eta_A)_*)^\dagger : \mathcal{M}(A) \rightarrow A$ is the cofree commutative comonoid on A in Rel .*

Proof. This follows from theorem 6.2 by self duality of Rel . For a commutative comonoid (K, w, k) in Rel and $r : K \rightarrow A$, the homomorphic coextension $r_\# : K \rightarrow \mathcal{M}(A)$ is $((r^\dagger)^\#)^\dagger$ where the homomorphic extension is taken with respect to the promonoidal convolution on the commutative monoid $(K, w^\dagger, e^\dagger)$. □