Evaluating the Faithfulness of Importance Measures in NLP by Recursively Masking Allegedly Important Tokens and Retraining

Andreas Madsen^{1,2} Nicholas Meade^{1,3,*} Vaibhav Adlakha^{1,3,*} Siva Reddy^{1,3,4}

¹ Mila – Quebec AI Institute ² Polytechnique Montréal

³ McGill ⁴ Facebook CIFAR AI Chair

firstname.lastname@mila.quebec

Abstract

To explain NLP models, many methods inform which inputs tokens are important for a prediction. However, an open question is if these methods accurately reflect the model's logic, a property often called *faithfulness*. In this work, we adapt and improve a recently proposed faithfulness benchmark from computer vision called ROAR (RemOve And Retrain), by Hooker et al. (2019).

We improve ROAR by recursively removing dataset redundancies, which otherwise interfere with ROAR. We adapt and apply ROAR, to popular NLP importance measures, namely attention, gradient, and integrated gradients. Additionally, we use mutual information as an additional baseline. Evaluation is done on a suite of classification tasks often used in the *faithfulness of attention* literature. Finally, we propose a scalar faithfulness metric, which makes it easy to compare results across papers.

We find that, importance measures considered to be unfaithful for computer vision tasks perform favorably for NLP tasks, the faithfulness of an importance measure is task-dependent, and the computational overhead of integrated gradient is rarely justified.

1 Introduction

The ability to explain neural networks benefits both accountability and ethics when deploying models (Doshi-Velez et al., 2017) and developing a scientific understanding of what models do (Doshi-Velez and Kim, 2017). Particularly, in NLP, attention (Bahdanau et al., 2015) is often used as an explanation to provide insight into the logical process of a model (Belinkov and Glass, 2019).

Attention, among other methods such as gradient (Baehrens et al., 2010; Li et al., 2016) and integrated gradient (Sundararajan et al., 2017; Mudrakarta et al., 2018), explain which input tokens are relevant for a given prediction. This type of explanation is called an *importance measure*. However, there is no mathematical guarantee that these importance measures accurately reflects the models logic, a property called faithfulness.

In the NLP literature, the faithfulness of *attention* is regularly debated (Jain and Wallace, 2019; Wiegreffe and Pinter, 2019; Vashishth et al., 2019; Serrano and Smith, 2019; Pruthi et al., 2020), often with contradicting conclusions. In related work (Section 2), we summarize the issues with these previous methods used to analyze *attention*. In computer vision, the faithfulness of the *gradient* and *integrated gradient* methods have been debated too (Adebayo et al., 2018; Kindermans et al., 2017).

Measuring faithfulness is inherently difficult, as it is usually impossible to provide gold labels for a "correct explanation", making proxy measures the only alternative. The analysis in this paper is based on ROAR (Hooker et al., 2019), this too is a proxy measure but is argued to be more principled.

ROAR's foundational principle is: *if information is truly important, then removing it from the dataset and retraining the model should result in a worse model*. Importantly, this can be compared with removing random information.

However, ROAR assumes that there are no data redundancies. Because, after important information is removed, those redundancies can keep the model's performance high, giving the illusion of a unfaithful importance measure. To solve this, we propose a modified version of ROAR, called *Recursive ROAR*.

Our primary contributions are: 1) developing *Recursive ROAR*, 2) adopting ROAR to NLP tasks, and 3) measuring faithfulness of *attention*, *gradient*, and *integrated gradient*. In addition, we also:

- Propose a metric for the faithfulness of importance measures, as a standard benchmark.
- Propose mutual information as an additional baseline to the random baseline.

^{*}Equal contribution.

We find that no importance measure is generally better than others, rather the faithfulness is task-dependent. This is valuable knowledge, as although each importance measure might be equal in faithfulness, they are not equal in computationally requirements or understandably to humans.

In particular, we find that *attention* generally provides more sparse explanations than *gradient* or *integrated gradient*. Although the faithfulness may be the same, a sparser explanation is often easier for humans to understand (Miller, 2019).

Computationally speaking, *integrated gradient* is 50 times more expensive than the *gradient* method. This additional complexity is usually justified by being considered more faithful than *gradient*. However, our results indicate that this is not a worthwhile trade-off.

2 Related Work

Much recent work in NLP has been devoted to investigating the faithfulness of *attention* as an interpretability method (Jain and Wallace, 2019; Wiegreffe and Pinter, 2019; Vashishth et al., 2019; Serrano and Smith, 2019; Pruthi et al., 2020; Meister et al., 2021). In this section, we categorize the most relevant methods into three general ideas and discuss their drawbacks.

Importantly all publications, including ours, use the same model, dataset, and training procedure of Jain and Wallace (2019), all works are therefore easily comparable.

2.1 Comparing with alternative importance measure

The idea is to compare *attention* with an alternative importance measure, such as *gradient*, if there is a correlation, then this would validate *attention's* faithfulness. Jain and Wallace (2019) specifically compare with the *gradient* method and the *leave-one-out* method. Meister et al. (2021) repeat this experiment in a broader context.

Both Jain and Wallace (2019) and Meister et al. (2021) find that there is little correlation between the importance measures and interpret this as attention being not-faithful.

Jain and Wallace (2019) does acknowledge the limitations of this approach, as the alternative importance measures are not themselves guaranteed to be faithful. A correlation, or lack of correlation, does therefore not inform about faithfulness. A criticism which we agree with and highlight here.

2.2 Mutate attention to deceive

Jain and Wallace (2019) propose that if there exist alternative attention weights that produce the same prediction, *attention* is unfaithful.

Jain and Wallace (2019) implement this idea, by optimizing for no prediction change but a large change in *attention*, and find that deceiving attention distributions do exists. Vashishth et al. (2019) and Meister et al. (2021) apply a similar method and achieve similar results.

Wiegreffe and Pinter (2019) find this analysis problematic because the attention distribution is changed directly, thereby creating an out-ofdistribution issue. This means that the new attention distribution may be impossible to obtain naturally from just changing the input, and it therefore says little about the faithfulness of attention.

2.3 Optimize model to deceive

Because the *mutate attention to deceive* approach has been criticized for using direct mutation, an alternative idea is to learn an adversarial *attention*.

Wiegreffe and Pinter (2019) approach is to maximize the KL-divergence between normal attention and adversarial attention while minimizing the prediction difference of the two models. By varying the allowed prediction difference, they show that it is not possible to significantly change the attention weights without changing the predictions. Thereby invalidating the *mutate attention to deceive* experiments. Pruthi et al. (2020) perform a similar analysis but finds the opposite; that it is possible to significantly change the attention weights without affecting performance. Furthermore, they use this as evidence for attention being not faithful.

We find this approach to be problematic because by changing the optimization criteria the analysis is no longer about attention in a standard model, which is the subject of interest. We therefore find that this analysis only works as a criticism of the *mutate attention to deceive* approach, not as an evaluation of faithfulness.

2.4 Why evaluating faithfulness is difficult

It is worth recognizing, that evaluating faithfulness is difficult because we are not able to explain the models ourselves just from the weights and internal states. Therefore, it is often impossible for humans to annotate what is a correct explanation, which leaves us with only proxy-measures.

3 ROAR: RemOve And Retrain

To avoid the problems with the current approaches to measure faithfulness described in Section 2, we apply ROAR.

ROAR has been used in Computer Vision to evaluate the faithfulness of importance measure (Hooker et al., 2019). The central idea is that if information is truly important, then removing it from the dataset and re-training the model on this reduced dataset should result in a worse performance. This can then be compared with an uninformative baseline, where information is removed randomly. The hypothesis is, if the importance measure is faithful it should drop more in performance compared to the baseline.

This section covers how ROAR is adapted to an NLP context. Furthermore, we resolve an issue where ROAR can't tell the difference between dataset redundancies and a non-faithful importance measure, by applying ROAR recursively.

3.1 Adaptation to NLP

ROAR was originally proposed for importance measures in computer vision. In this context, pixels measured to be important are "removed" by replacing them with an uninformative value, for example, a gray pixel (Hooker et al., 2019).

In this work, ROAR is applied to attention and other importance measures used on both singlesequence and paired-sequence classification models. Because these models use tokens, the uninformative value is a special [MASK] token (for an example, see Figure 1). We choose a [MASK] token rather than removing the token to keep the sequence length, which is an information source unrelated to importance measures. Additionally, removing tokens could result in ungrammatical inputs, using a [MASK] allows the model to infer the missing information.

0%	The	movie	is	great	•	I	really	liked	it			
10%	The	movie	is	[MAS	SK.]	. I rea	ally lil	ked	it		
20%	The	[MASI	K]	is [M	AS	SK].I	really	lik	ced	it	

Figure 1: Demonstrates replacing a relative number of important tokens with [MASK]. The highlight indicates at 0% masked, indicates importance.

3.2 Recursive ROAR

When the model performance is worse on the dataset with allegedly important tokens removed

compared to when random tokens are removed, the conclusion is that the importance measure is faithful. However, when the performance is similar the conclusion is unclear. Hooker et al. (2019) explain that it can either be there is a dataset redundancy or the importance measure is not faithful.

The reason why a dataset redundancy can affect the results is that, after truly important tokens are removed, the redundant information, which the model would normally not use, still exists and provides the necessary information to keep the model's performance high. An example of this issue is demonstrated in Figure 1.

We solve this issue by recursively recomputing the importance measure at each iteration of information removal. This way, if the importance measure is faithful it would mark the redundant information as important, and the redundancy would then be removed afterward. Note that already masked tokens are kept masked, regardless of if the importance measure considered the [MASK] token important. We call this Recursive ROAR and provide an example in Figure 2.

0%	The	movie	is	great		I	rea	lly	lik	ed	it			
10%	The	movie	is	[MAS	SK]		Ι	rea	ally	lil	ked	it		
20%	The	movie	is	[MAS	SK]		Ι	rea	ally	[]	/AS	SK]	it	

Figure 2: Example of how a dataset redundancy can be removed by reevaluating the importance measure. Compare this to Figure 1, where redundancies are not removed and the performance can remain the same, even when the importance measure is faithful. Note, the redundant information may be expressed in more complex ways than demonstrated here.

Note, Recursive ROAR might not remove all redundancies unless the step size is one token. However, because ROAR requires retraining the model, for every evaluation step, this is infeasible. Instead, we approximate it by removing a relative number of tokens. We discuss this more in Appendix A.

4 Models and Tasks

The tasks, models, hyperparameters, and pretrained word embeddings are the same as in Jain and Wallace (2019). There are two types of tasks and models: single-sequence and paired-sequence.

In general we refer $\mathbf{x} \in \mathbb{R}^{T \times V}$ as the one-hot encoding of the primary input sequence, of length T and vocabulary size V. The logits are then $f(\mathbf{x})$, and the target class is denoted as c.

4.1 Single-sequence

A *d*-dimentional word embedding followed by a bidirectional LSTM (BiLSTM) encoder is used transform the one-hot encoding into the hidden states $\mathbf{h}_x \in \mathbb{R}^{T \times 2d}$. These hidden states are then aggregate using an additive attention layer $\mathbf{h}_{\alpha} = \sum_{i=1}^{T} \alpha_i \mathbf{h}_{x,i}$.

To compute the attention weights α_i for each token:

$$\alpha_i = \frac{\exp(\mathbf{u}_i^{\top} \mathbf{v})}{\sum_j \exp(\mathbf{u}_j^{\top} \mathbf{v})}, \ u_i = \tanh(\mathbf{W} \mathbf{h}_{x,i} + \mathbf{b})$$
(1)

where $\mathbf{W}, \mathbf{b}, \mathbf{v}$ are model parameters. Finally, the \mathbf{h}_{α} is passed through a fully-connected layer to obtain the logits $f(\mathbf{x})$.

Single-sequence tasks

- 1. *Stanford Sentiment Treebank (SST)* (Socher et al., 2013) Sentences are classified as positive or negative.¹
- IMDB Movie Reviews (Maas et al., 2011) Movie reviews are classified as positive or negative.
- MIMIC (Diabetes) (Johnson et al., 2016) Uses health records to detect if a patient has Diabetes.
- 4. *MIMIC (Chronic vs Acute Anemia)* (Johnson et al., 2016) Uses health records to detect whether a patient has chronic or acute anemia.

4.2 Paired-sequence

For paired-sequence problems the two sequences are denoted as $\mathbf{x} \in \mathbb{R}^{T_x \times V}$ and $\mathbf{y} \in \mathbb{R}^{T_y \times V}$. The inputs are then transformed to embeddings using the same embedding matrix, and then transformed using two separate BiLSTM encoders to get the hidden states, \mathbf{h}_x and \mathbf{h}_y . Likewise they are aggregated using additive attention $\mathbf{h}_\alpha = \sum_{i=1}^{T_x} \alpha_i \mathbf{h}_{x,i}$.

The attention weights α_i are computed as:

$$\alpha_{i} = \frac{\exp(\mathbf{u}_{i}^{\top}\mathbf{v})}{\sum_{j}\exp(\mathbf{u}_{j}^{\top}\mathbf{v})}$$
(2)
$$\mathbf{u}_{i} = \tanh(\mathbf{W}_{x}\mathbf{h}_{x,i} + \mathbf{W}_{y}\mathbf{h}_{y,T_{2}}),$$

where $\mathbf{W}_x, \mathbf{W}_y, \mathbf{v}$ are model parameters. Finally, \mathbf{h}_{α} is transformed with a dense layer.

Paired-sequence tasks

- Stanford Natural Language Inference (SNLI) (Bowman et al., 2015) – Inputs are premise and hypothesis. The hypothesis either entails, contradicts, or is neutral w.r.t. the premise.
- bAbI (Weston et al., 2016) A set of artificial text for understanding and reasoning. We use the first three tasks, which consist of questions answerable using one, two, and three sentences from a passage, respectively.

5 Importance Measures

In this section, we describe the importance measures that will be evaluated with ROAR. Notably, it is important to distinguish between those that could reflect the model, and the baselines that by design are independent of the model.

5.1 Model dependent

Attention These are the α 's defined in Section 4. Note that by design, α for the [CLS] and [EOS] tokens is zero. Hence, those tokens can not be masked by ROAR. To keep the comparison with other importance measures fair, they are constrained to have the same property.

Gradient Let the logits from Section 4 be denoted as $f(\mathbf{x})$. Then the gradient explanation is $\nabla_{\mathbf{x}} f(\mathbf{x})$, where \mathbf{x} is the one-hot-encoding of the input tokens (Baehrens et al., 2010; Li et al., 2016). To reduce the vocabulary dimension, we use an L_2 -norm.

Integrated Gradient A successor to the gradient explanation is Integrated Gradient (IG), which they argue to be more faithful via axiomatic proofs. However, it requires computing k gradients and a baseline b. We use k = 50 like the original paper (Sundararajan et al., 2017), and uses $\mathbf{b} = \mathbf{0}$ as is done in NLP literature (Mudrakarta et al., 2018).

$$IG(\mathbf{x}) = (\mathbf{x} - \mathbf{b}) \odot \frac{1}{k} \sum_{i=1}^{k} \nabla_{\tilde{\mathbf{x}}_{i}} f(\tilde{\mathbf{x}}_{i})_{c}$$

$$\tilde{\mathbf{x}}_{i} = \mathbf{b} + \frac{i}{k} (\mathbf{x} - \mathbf{b})$$
(3)

5.2 Baselines

Random Similarly to the ROAR paper (Hooker et al., 2019) we use an uninformative baseline, by sampling from a uniform distribution.

¹The original dataset has 5 classes. Following Jain and Wallace (2019), we label (1,2) as negative, (4,5) as positive, and ignore the neural sentences.

Mutual Information As an alternative modelagnostic baseline, we use mutual information (MI) (Manning et al., 2008) aggregated with a weighted average over each class. For a word w and class c, let $P_{w,c}$ be the empirical Bernoulli distribution for observing the word-class pair. Additionally, let P_w and P_c be the marginalized distributions. The averaged mutual information MI(w) is then

$$\mathrm{MI}(w) = \sum_{c} P_c(1) \,\mathrm{I}(w, c) \tag{4}$$

$$I(w,c) = D_{KL}(P_{w,c} \parallel P_w \odot P_c)$$
 (5)

Intuitively, as the Mutual Information I(w, c) increases, the for a word-class pair becomes more important for identifying the class. To avoid leaking the target label, by removing all occurrences of a token only for sentences of a given class, we average over all classes.

6 Experiments

Our datasets, models, and performance metrics are identical to those used in Jain and Wallace (2019) and most other literature evaluating the faithfulness of *attention*.

Specifically, we use the micro-F1 score for SNLI, accuracy for bAbI, and the macro-F1 score for SST, IMDB, Diabetes, and Anemia. Reproduced results, comparison with Jain and Wallace (2019), and dataset statistics are presented in Table 1.

In general, all results are aggregates over 5 seeds using a mean and a 95% confidence interval using a t-distribution in logistic-space.

6.1 Sparsity

Before performing the main ROAR experiments to evaluate the faithfulness, we evaluate the sparsity of each importance measure. The motivation is that *attention* can become sparse, meaning the majority of the attention is applied to just a few tokens (Bahdanau et al., 2015). If this is the case, it would not make sense to mask out 50% of a sequence of 200 tokens, if the top-5 tokens contribute 99% of the attention mass. Instead, it would be more appropriate to mask an absolute number of tokens, for example, to mask from 0 to 10 tokens.

To evaluate the sparsity of each importance measure, we simply measure how much of the total importance is assigned to a specific number of tokens. The results in Figure 3 reveal that *attention* is not sparse enough to justify masking an absolute number of tokens. Interestingly, *attention* is still more sparse than *gradient* and *integrated gradient*. An important property that can make it easier for humans to understand (Miller, 2019). In the discussion section, we elaborate on this.



Figure 3: The relative amount of the importance measures covered by selecting a given number of tokens. Results are mean over 5 seeds with a 95% confidence interval. The figure shows that no importance measure is particularly sparse.

6.2 ROAR

To evaluate the faithfulness we apply both *ROAR* (Not Recursive) and our *Recursive ROAR* experiment to each dataset. The results are presented in Figure 4 and aggregate over 5 different seeds.

Dataset	Avg. Length	Train size	Test size	Performance [%]			
				Jain and Wallace (2019)	Reproduced		
SST	20	3130/3449	889/887	81.0	$82^{+1.2}_{-1.2}$		
IMDB	181	8685/8527	2234/2128	88.0	$90^{+0.8}_{-0.8}$		
SNLI	16	183416/183187/182764	3368/3237/3219	78.0	$78_{-0.4}^{+0.4}$		
Anemia	2267	1522/2740	449/793	92.0	$89^{+1.0}_{-1.1}$		
Diabetes	2207	6650/1416	1389/340	79.0	$81_{-4.0}^{+3.4}$		
bAbI-1/2/3	38/96/308	8500	1000	100.0/48.0/62.0	$100/70^{+15.7}_{-22.1}/61^{+9.0}_{-9.8}$		

Table 1: Datasets statistics for single-sequence and paired-sequence tasks. Following Jain and Wallace (2019), we use the same BiLSTM model and report performance as macro-F1 for SST, IMDB, Anemia and Diabetes, micro-F1 for SNLI, and accuracy for bAbI.



Figure 4: ROAR results, showing model performance at x% of tokens masked. A model performance below *random* indicates faithfulness, while above or similar to *random* indicates a non-faithful importance measure for the recursive column. Performance is averaged over 5 seeds with a 95% confidence interval.

How to interpret Because *Recursive ROAR* mitigates the dataset redundancy issue discussed in Section 3.2, the *Recursive ROAR* results in Figure 4 are the most relevant. The *ROAR* (Not Recursive) results primarily exist as an ablation study.

If the model performance of a given importance measure is below the random baseline, then this indicates that the importance measure is faithful. For the *Recursive ROAR* case, if the model performance is above or equal to the random baseline, then this indicates that the importance measure is not faithful. For the *ROAR* (Not Recursive) case, it is not possible to make a conclusion when model performance is above or equal to the random baseline, since this can also be due to a dataset redundancy.

As a secondary baseline, we include *mutual in-formation*. Note, *mutual information* can by definition not explain the model, as it does not depend on the model. However, it provides value as a qualitative comparison, as it is often effective at selecting relevant information. Hence, when the model performance of an importance measure is below that of *mutual information*, it indicates that while the importance measure might be faithful, a more faithful importance measure should exist.

Figure 4 also presents the model performance at 100% masking. This provides a lower bound for the model performance, which is useful for comparison as datasets are often biased. These biases come from unbalanced class representation, a correlation between sequence length and the gold label, or the secondary sequence for the paired-sequence tasks (Gururangan et al., 2018).

Important observations Based on the tresults in Figure 4 we highlight the following:

- No importance measure is consistently faithful, instead the faithfulness is task dependent.
- Although attention provides no mathematical guarantee to be a faithful explanation, models often converge such that attention is faithful.
- Importance measures often work best for the top-20% most important tokens. Above 20%, *mutual information* often masks relevant tokens similarly to the importance measures.
- *Integrated gradient* is not necessarily more faithful than *gradient* or *attention*. This is evident from the bAbI and Diabetes datasets. This is surprising as *integrated gradient* is argued to be more faithful than the *gradient* method (Sundararajan et al., 2017).

- Comparing *ROAR* (Not Recursive) and *Recursive ROAR*, most datasets have redundancies that interfere with ROAR. For example, with the Diabetes dataset, only with *Recursive ROAR* can *gradient* be seen to be faithful.
- When the performance increases as more tokens are masked, this is due to class leakage. For example, if the and token is masked given positive sentiment, the and token becomes a good predictor of negative sentiment. This new redundancy will then be removed in the next iteration. However, because *Recursive ROAR* is approximated with a step-size of 10%, this is imperfect. For more details, see Appendix A.
- Compared to ROAR results for computer vision (Hooker et al., 2019), the *gradient* and *integrated gradient* are sometimes faithful in NLP, while in CV they are consistently not faithful. Although, because Hooker et al. (2019) did not remove redundancies, it could also be due to differences in redundancies. But given that other importance measures were faithful, this is an unlikely conclusion.

6.3 Faithfulness metric

While a ROAR plot can provide valuable insights, such as "this importance measure is only faithful for the top-30% most important tokens", it doesn't summarize the faithfulness to a single value, given an importance measure and dataset pair. Which is useful for comparison across multiple papers.

To provide a scalar benchmark, we propose using an area-between-curves metric. Specifically, the goal is to maximize the area between the random baseline curve and the importance measure curve. Additionally, when the importance measure is above the baseline a negative area is contributed. Finally, the metric should be normalized by an upper bound based on 100% masking.

Using an area-between-curves is useful because unlike many other summarizing statistics it is invariant to the ROAR resolution. In our case, we have a step size of 10%, which was chosen for computational reasons. Future work may choose a smaller or larger step size depending on their computational resources.

Let r_i be masking ratio at step i out of I total step, in our case $r = \{0\%, 10\%, \dots, 100\%\}$. Let p_i be the model performance for a given importance measure and b_i be the random baseline performance. With this, the metric is defined in (6), and we present the results in Table 2.

$\text{faithfulness} = \frac{\sum_{i=1}^{I-1} \frac{1}{2} \Delta x_i (\Delta p_i + \Delta p_{i+1})}{\sum_{i=1}^{I-1} \frac{1}{2} \Delta x_i (\Delta b_i + \Delta b_{i+1})}$	
where $\Delta x_i = x_{i+1} - x_i$ step size	(6)
$\Delta p_i = b_i - p_i$ performance delta	
$\Delta b_i = b_i - b_I$ baseline delta	

Dataset	Importance Measure	Faithfulness
	Attention	$7.6\%^{+11.5\%}_{-11.7\%}$
Anemia	Gradient	$1.0\%^{+5.5\%}_{-5.5\%}$
	Integrated Gradient	$4.9\%^{+3.4\%}_{-3.4\%}$
	Attention	$67.7\%^{+11.4\%}_{-15.9\%}$
Diabetes	Gradient	$58.1\%^{+11.4\%}_{-14.3\%}$
	Integrated Gradient	$11.5\%^{+18.6\%}_{-19.4\%}$
	Attention	$29.9\%^{+6.8\%}_{-7.1\%}$
IMDB	Gradient	$3.1\%^{+4.3\%}_{-4.3\%}$
	Integrated Gradient	$32.5\%^{+1.5\%}_{-1.5\%}$
	Attention	$36.5\%^{+5.2\%}_{-5.4\%}$
SNLI	Gradient	$18.7\%^{+6.6\%}_{-6.7\%}$
	Integrated Gradient	$-14.0\%^{+8.3\%}_{-8.1\%}$
	Attention	$15.8\%^{+3.7\%}_{-3.8\%}$
SST	Gradient	$7.6\%^{+3.4\%}_{-3.4\%}$
	Integrated Gradient	$37.9\%^{+7.4\%}_{-8.0\%}$
	Attention	$68.0\%^{+12.7\%}_{-18.7\%}$
bAbI-1	Gradient	$66.8\%^{+9.2\%}_{-11.9\%}$
	Integrated Gradient	$59.8\%^{+10.4\%}_{-12.9\%}$
	Attention	$76.3\%^{+8.2\%}_{-11.7\%}$
bAbI-2	Gradient	$66.6\%^{+6.9\%}_{-8.3\%}$
	Integrated Gradient	$35.7\%^{+20.4\%}_{-24.6\%}$
	Attention	$80.3\%^{+11.2\%}_{-22.7\%}$
bAbI-3	Gradient	$74.7\%^{+11.2\%}_{-18.0\%}$
	Integrated Gradient	$26.2\%^{+13.7\%}_{-14.9\%}$

Table 2: Faithfulness metric defined as a area-betweencurves, see (6). Higher values means more faithful, zero or negative values means distinctly not-faithful.

These in Table 2 makes it more clear that *attention* is a surprisingly faithful importance measure, only for IMDB and SST does it not provide the highest faithfulness. However, it is worth mentioning that for most other datasets it is not statistically significantly better than either *gradient* or *integrated gradient*.

7 Discussion

In general, the ROAR results indicate that the faithfulness of the tested importance measure is taskdependent. For *attention* this is not surprising, as its faithfulness depends on the BiLSTM layer, specifically how much it mix or shifts the input embeddings. Since the behavior of BiLSTM should be task-dependent, this also makes the faithfulness of *attention* task-dependent.

However, this does not answer why *gradient* and *integrated gradient* are also task-dependent, as these importance measures should consider the BiLSTM behavior. Understanding this remains an open question.

Although we found no importance measure to be significantly more faithful than others, *attention* is often more sparse than other importance measures depending on the task. This is valuable as sparse explanations are often easier to understand to humans (Miller, 2019).

Because interpretability is the "ability to explain or to present in understandable terms to a human" (Doshi-Velez and Kim, 2017), how effective an explanation is in communicating to a human and the faithfulness of the explanation, are two separate but equally important concerns (Doshi-Velez and Kim, 2017; Jacovi and Goldberg, 2020).

Each importance measure also have different computational requirements, with the *attention* explanation being free and *integrated gradient* being 50 times more expensive than *gradient*.

This computational difference makes *attention* an attractive choice. However, for more complex models like BERT (Devlin et al., 2019) the many layers mix embeddings to such an extent, that *attention* may be no longer faithful. Future work will need to determine which, if any, importance measures can be used for such models.

8 Conclusion

This paper evaluates the faithfulness of *attention*, *gradient*, and *integrated gradient* using an improved version of ROAR, called Recursive ROAR.

Our analysis provides valuable insights, which we describe in Section 6. In general, all three importance measures are faithful, although none is significantly more faithful than others.

We hope this paper can help to establish ROAR as a standardized benchmark for the faithfulness of importance measures in NLP.

Acknowledgements

SR is supported by the Canada CIFAR AI Chairs program and the NSERC Discovery Grant program.

References

- Julius Adebayo, Justin Gilmer, Michael Muelly, Ian Goodfellow, Moritz Hardt, Been Kim, and Google Brain. 2018. Sanity checks for saliency maps. In Advances in Neural Information Processing Systems, volume 2018-Dec, pages 9505–9515.
- David Baehrens, Timon Schroeter, Stefan Harmeling, Motoaki Kawanabe, Katja Hansen, and Klaus Robert Müller. 2010. How to explain individual classification decisions. *Journal of Machine Learning Research*, 11:1803–1831.
- Dzmitry Bahdanau, Kyung Hyun Cho, and Yoshua Bengio. 2015. Neural machine translation by jointly learning to align and translate. In 3rd International Conference on Learning Representations, ICLR 2015 - Conference Track Proceedings, pages 1–15. International Conference on Learning Representations, ICLR.
- Yonatan Belinkov and James Glass. 2019. Analysis Methods in Neural Language Processing: A Survey. *Transactions of the Association for Computational Linguistics*, 7:49–72.
- Samuel R. Bowman, Gabor Angeli, Christopher Potts, and Christopher D. Manning. 2015. A large annotated corpus for learning natural language inference. In *Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing*, pages 632–642, Stroudsburg, PA, USA. Association for Computational Linguistics.
- Jacob Devlin, Ming Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: Pre-training of deep bidirectional transformers for language understanding. In NAACL HLT 2019 - 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies - Proceedings of the Conference, volume 1, pages 4171–4186. Association for Computational Linguistics (ACL).
- Finale Doshi-Velez and Been Kim. 2017. Towards A Rigorous Science of Interpretable Machine Learning. *arXiv*.
- Finale Doshi-Velez, Mason Kortz, Ryan Budish, Christopher Bavitz, Sam Gershman, David O'Brien, Kate Scott, Stuart Schieber, James Waldo, David Weinberger, Adrian Weller, and Alexandra Wood. 2017. Accountability of AI Under the Law: The Role of Explanation. *SSRN Electronic Journal*, Online.

- Suchin Gururangan, Swabha Swayamdipta, Omer Levy, Roy Schwartz, Samuel Bowman, and Noah A. Smith. 2018. Annotation Artifacts in Natural Language Inference Data. In Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 2 (Short Papers), volume 2, pages 107–112, Stroudsburg, PA, USA. Association for Computational Linguistics.
- Sara Hooker, Dumitru Erhan, Pieter-Jan Jan Kindermans, and Been Kim. 2019. A benchmark for interpretability methods in deep neural networks. In *Advances in Neural Information Processing Systems*, volume 32.
- Alon Jacovi and Yoav Goldberg. 2020. Towards Faithfully Interpretable NLP Systems: How Should We Define and Evaluate Faithfulness? In Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics, pages 4198–4205, Stroudsburg, PA, USA. Association for Computational Linguistics.
- Sarthak Jain and Byron C. Wallace. 2019. Attention is not Explanation. In Proceedings of the 2019 Conference of the North, volume 1, pages 3543–3556, Stroudsburg, PA, USA. Association for Computational Linguistics.
- Alistair E.W. Johnson, Tom J. Pollard, Lu Shen, Liwei H. Wei H. Lehman, Mengling Feng, Mohammad Ghassemi, Benjamin Moody, Peter Szolovits, Leo Anthony Celi, and Roger G. Mark. 2016. MIMIC-III, a freely accessible critical care database. *Scientific Data*, 3(1):160035.
- Pieter-Jan Kindermans, Sara Hooker, Julius Adebayo, Maximilian Alber, Kristof T Schütt, Sven Dähne, Dumitru Erhan, and Been Kim. 2017. The (Un)reliability of saliency methods. *Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics)*, 11700 LNCS:267–280.
- Jiwei Li, Xinlei Chen, Eduard Hovy, and Dan Jurafsky. 2016. Visualizing and Understanding Neural Models in NLP. In Proceedings of the 2016 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, pages 681–691, Stroudsburg, PA, USA. Association for Computational Linguistics.
- Andrew L. Maas, Raymond E. Daly, Peter T. Pham, Dan Huang, Andrew Y. Ng, and Christopher Potts. 2011. Learning word vectors for sentiment analysis. In ACL-HLT 2011 - Proceedings of the 49th Annual Meeting of the Association for Computational Linguistics: Human Language Technologies, volume 1, pages 142–150, Portland, Oregon, USA. Association for Computational Linguistics.
- Christopher D Manning, Prabhakar Raghavan, and Hinrich Schütze. 2008. *Introduction to Information Retrieval*. Cambridge University Press, USA.

- Clara Meister, Stefan Lazov, Isabelle Augenstein, and Ryan Cotterell. 2021. Is Sparse Attention more Interpretable? In Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 2: Short Papers), pages 122–129, Stroudsburg, PA, USA. Association for Computational Linguistics.
- Tim Miller. 2019. Explanation in artificial intelligence: Insights from the social sciences. *Artificial Intelligence*, 267:1–38.
- Pramod K. Mudrakarta, Ankur Taly, Mukund Sundararajan, and Kedar Dhamdhere. 2018. Did the model understand the question? In ACL 2018 -56th Annual Meeting of the Association for Computational Linguistics, Proceedings of the Conference (Long Papers), volume 1, pages 1896–1906.
- Danish Pruthi, Mansi Gupta, Bhuwan Dhingra, Graham Neubig, and Zachary C. Lipton. 2020. Learning to Deceive with Attention-Based Explanations. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 4782–4793, Stroudsburg, PA, USA. Association for Computational Linguistics.
- Sofia Serrano and Noah A Smith. 2019. Is Attention Interpretable? In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 2931–2951, Stroudsburg, PA, USA. Association for Computational Linguistics.
- Richard Socher, John Bauer, Christopher D. Manning, and Andrew Y. Ng. 2013. Parsing with compositional vector grammars. In ACL 2013 - 51st Annual Meeting of the Association for Computational Linguistics, Proceedings of the Conference, volume 1, pages 455–465. Association for Computational Linguistics.
- Mukund Sundararajan, Ankur Taly, and Qiqi Yan. 2017. Axiomatic attribution for deep networks. In 34th International Conference on Machine Learning, ICML 2017, volume 7, pages 5109–5118.
- Shikhar Vashishth, Shyam Upadhyay, Gaurav Singh Tomar, and Manaal Faruqui. 2019. Attention Interpretability Across NLP Tasks. *arXiv*.
- Jason Weston, Antoine Bordes, Sumit Chopra, Alexander M. Rush, Bart Van Merriënboer, Armand Joulin, and Tomas Mikolov. 2016. Towards AI-complete question answering: A set of prerequisite toy tasks.
- Sarah Wiegreffe and Yuval Pinter. 2019. Attention is not not Explanation. Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP), pages 11–20.

A ROAR Results with step size of one

Because using a relative step-size, such as 10% of tokens, can create dataset redundancies by leaking the class, the performance can increase. This is particularly clear in the Recursive ROAR bAbI-3 results from Figure 4. To prevent this, one should use a step-size of exactly 1 token. Unfortunately, using a step-size of 1 token is too computationally expensive; for example, the Diabetes dataset has an average length of 2207 tokens. Instead, we approximate Recursive ROAR by using a 10% step size.

However, in this appendix section, we provide the Recursive ROAR results for a step-size of 1 token, in Figure 5. But do not exceed 10 masked tokens, to keep the number of retrained models low.

Figure 5 shows that the performance does not increase when a step-size of exactly 1 token is used because it is not an approximation. In particular, when comparing the Recursive ROAR bAbI-3 results from Figure 4 and Figure 5 is the difference very noticeable.



Figure 5: ROAR results, showing model performance at an absolute number of tokens masked. A model performance below *random* indicates faithfulness, while above or similar to *random* indicates a non-faithful importance measure for the recursive column. Performance is averaged over 5 seeds with a 95% confidence interval.