

# Modular population protocols

Mikhail Raskin 

Technical University of Munich, Germany  
raskin@mccme.ru, raskin@in.tum.de

---

## Abstract

---

Population protocols are a model of distributed computation intended for the study of networks of independent computing agents with dynamic communication structure. Each agent has a finite number of states, and communication opportunities occur nondeterministically, allowing the agents involved to change their states based on each other's states. Population protocols are often studied in terms of reaching a consensus on whether the input configuration satisfied some predicate.

A desirable property of a computation model is modularity, the ability to combine existing simpler computations in a straightforward way. In the present paper we present a more general notion of functionality implemented by a population protocol. This notion allows to design multiphase protocols as combinations of independently defined phases. The additional generality also increases the range of behaviours that can be captured in applications.

**2012 ACM Subject Classification** Networks → Protocol testing and verification; Computing methodologies → Agent / discrete models; Software and its engineering → Software verification

**Keywords and phrases** population protocols, protocol verification, modularity

**Funding** The project has received funding from the European Research Council (ERC) under the European Union's Horizon 2020 research and innovation programme under grant agreement No 787367 (PaVeS)

**Acknowledgements** I would like to thank Javier Esparza, Jérôme Leroux and Chana Weil-Kennedy for useful discussions.

## 1 Introduction

Population protocols have been introduced in [1, 2] as a restricted yet useful subclass of general distributed protocols. Each agent in a population protocol has a fixed amount of local storage, and an execution consists of selecting pairs of agents and letting them update their states based on an interaction. The choice of pairs is assumed to be performed by an adversary subject to a fairness condition. The fairness condition ensures that the adversary must allow the protocol to progress.

Typically, population protocols are studied from the point of view of recognising some properties of an input configuration. In this context population protocols and their subclasses have been studied from the point of view of expressive power [4], verification complexity [6, 11, 10], time to convergence [3, 8], necessary state count [5], etc.

The original target application of population protocols and related models is modelling networks of restricted sensors, starting from the original paper [1] on population protocols. Of course, in the modern applications the cheapest microcontrollers typically have thousands of bits of volatile memory permitting the use of simpler and faster algorithms for recognising properties of an input configuration. So on the one hand, the original motivation for the restrictions in the population protocol model seems to have less relevance. On the other hand, verifying distributed systems benefits from access to a variety of restricted models with a wide range of trade-offs between the expressive power and verification complexity, as most problems are undecidable in the unrestricted case. Complex, unrestricted, and impossible to verify distributed deployments lead to undesirable and hard to predict and sometimes even diagnose situations such as so called gray failures [12] and similar.

From the theoretical point of view, population protocols provide a model of distributed computing with some of verification problems still decidable[9] although non-elementary[7]. This property puts them near the edge of decidability of verification, which is interesting on its own.

Unfortunately, as the standard approach considers protocols that compute predicates, composing protocols directly is limited to boolean combinations. Whenever a multiphase protocol needs to be constructed, the interaction between phases needs to be described and proven in an ad hoc way. We find it desirable to have better modularity in protocol design.

Additionally, desirable behaviours of distributed systems go beyond consensus about a single property of initial configuration. For example, one might want to maintain task allocation across a fleet of servers. Task allocation usually depends on the server models, and servers are sometimes taken out of service for maintenance. From this point of view, we also find it interesting to study a more general notion of expressive power.

In the present paper we introduce an alternative notion of a protocol implementing a specification. A specification is relation on the input configuration and the agent outputs in the final configuration. A protocol implements the specification, if in each fair execution from an input configuration there is a step after which the specification is always satisfied. The standard notion of computing predicates by stable consensus corresponds to a natural class of specifications where output is a single bit, only consensus output configurations are acceptable, and for each input configuration only one of the two consensus options is acceptable.

Additionally, we define computations with shutdown requests. We allow the scheduler to add new agents, or to tell existing agents to leave the computation. Each leaving agent can take some time to hand over the information, but must eventually terminate (in a fair execution). Whenever there is no turnover, specification must be eventually stably satisfied.

We show a natural completely mechanical way of combining two population protocols with shutdown requests implementing two relations to obtain a protocol with shutdown requests implementing the composition of these relations.

The rest of the present paper is organised as follows. First we provide the basic definitions and the previously known results about expressive power from the point of view of computing predicates. We continue by defining implementation of specifications and shutdown requests. Afterwards we prove the main result about composition of protocols. The paper ends with conclusion and future directions.

## 2 Basic definitions

In this section we recall the standard definitions and facts related to population protocols. We use the definition where agents have identities for the purposes of analysis but cannot distinguish each other. This will also be relevant in the generalisations. First we define the population protocols. We start by describing what information we need to specify a protocol.

► **Definition 1.** *A population protocol is defined by a finite set of states  $Q$  and a step relation  $Step \subset Q^2 \times Q^2$ . When there is no ambiguity about the protocol, we abbreviate  $((q_1, q_2), (q'_1, q'_2)) \in Step$  as  $(q_1, q_2) \mapsto (q'_1, q'_2)$  and call the quadruple  $(q_1, q_2) \mapsto (q'_1, q'_2)$  a transition.*

We use the following notation to work with function on agents.

► **Definition 2.** *For a function  $f$  let  $Dom(f)$  denote the domain of the function.*

For a function  $f$  and  $x \notin \text{Dom}(f)$  let  $f \cup \{x \mapsto y\}$  denote the function  $g$  defined on  $\text{Dom}(f) \cup \{x\}$  such that  $g|_{\text{Dom}(f)} = f$  and  $g(x) = y$ . For  $u \in \text{Dom}(f)$  let  $f[u \mapsto v]$  denote the function  $h$  defined on  $\text{Dom}(f)$  such that  $h|_{\text{Dom}(f) \setminus \{u\}} = f|_{\text{Dom}(f) \setminus \{u\}}$  and  $h(u) = v$ . For symmetry, if  $w = f(u)$  let  $f \setminus \{u \mapsto w\}$  denote restriction  $f|_{\text{Dom}(f) \setminus \{u\}}$ .

Use of this notation implies an assertion of correctness, i.e.  $x \notin \text{Dom}(f)$ ,  $u \in \text{Dom}(f)$ , and  $w = f(u)$ .

► **Definition 3.** A configuration of a population protocol is a set  $A$  of agent identities, and a state function  $C : A \rightarrow Q$ , assigning states to agents. We identify the configuration with the state function as  $A = \text{Dom}(C)$ . The size of a configuration  $C$  is the number of agents. An execution of a population protocol is a finite or infinite sequence  $(C_0, C_1, \dots)$  of configurations such that the set of agents is the same for each  $C_j$ , and for each  $j$  between 1 and the execution length we have some two agents  $a_1, a_2$  that interact according to the rules, i.e.  $C_j(a_1) = q_1$ ,  $C_j(a_2) = q_2$ ,  $C_{j+1} = C_j[a_1 \mapsto q'_1][a_2 \mapsto q'_2]$  where  $((q_1, q_2), (q'_1, q'_2)) \in \text{Step}$ . In other words, we let two agents with states  $q_1$  and  $q_2$  interact in some way permitted by the Step relation.

► **Example 4.** Consider the set of states  $\{q_0, q_1, q_2, q_3\}$ . The step relation is described by

$$\begin{aligned} (q_1, q_1) &\mapsto (q_0, q_2), \\ (q_2, q_1) &\mapsto (q_0, q_3), \\ (q_2, q_2) &\mapsto (q_1, q_3), \\ (q_0, q_3) &\mapsto (q_3, q_3), \\ (q_1, q_3) &\mapsto (q_3, q_3), \\ (q_2, q_3) &\mapsto (q_3, q_3). \end{aligned}$$

Using agent identities 1, 2, and 3, and denoting a function from 1, 2, 3 as a tuple, we can consider the following execution:  $(q_1, q_1, q_1), (q_2, q_1, q_0), (q_3, q_0, q_0), (q_3, q_3, q_0), (q_3, q_3, q_3)$ . Here we use the first two steps, then twice the fourth step.

► **Remark 5.** Note that all the configurations in an execution have the same size.

We often consider executions with the steps chosen by an adversary. However, we need to restrict adversary to ensure that some useful computation remains possible. To prevent the adversary from e.g. only letting one pair of agents to interact, we require the executions to be fair. The fairness condition can also be described by comparison with random choice of steps to perform: fairness is a combinatorial way to exclude a zero-probability set of bad executions.

► **Definition 6.** Consider a population protocol  $(Q, \text{Step})$ .

A configuration  $C'$  is reachable from configuration  $C$  iff there is a finite execution with the initial configuration  $C$  and the final configuration  $C'$ .

A finite execution is fair if it is not a beginning of any longer execution.

An infinite execution  $C_0, C_1, \dots$  is fair if for every configuration  $C'$  either  $C'$  is not reachable from some  $C_j$  (and all the following configurations), or  $C'$  occurs among  $C_j$  infinitely many times.

► **Example 7.** The finite executions in the example 4 are fair.

The most popular notion of expressive power for population protocols is computing predicates, defined in the following way.

► **Definition 8.** Consider a population protocol  $(Q, \text{Step})$  with additionally defined nonempty set of input states  $I \subset Q$ , output alphabet  $O$  and output function  $o : Q \rightarrow O$ .

Support of a configuration  $C$  is the set of all states with nonzero images, The states belonging to the support of a configuration are also called inhabited in the configuration.  $\text{supp } C = Q \setminus C^{-1}(0)$ .

A configuration  $C$  is an input configuration if its support is a subset of the set of the input states,  $\text{supp } C \subset I$ .

A configuration  $C$  is a  $b$ -consensus for some  $b \in O$  if the output function yields  $b$  for all the inhabited states, A configuration is a stable  $b$ -consensus if it is a  $b$ -consensus together with all the configurations reachable from it. A configuration is called just a consensus or a stable consensus if it is a  $b$ -consensus (respectively stable  $b$ -consensus) for some  $b$ .

A protocol computes a function  $\varphi : \mathbb{N}^I \rightarrow O$  iff for each input configuration  $C$  every fair execution with initial configuration  $C$  contains a stable  $\varphi(C)$ -consensus. We usually use the protocols computing predicates, which corresponds to  $O = \{\text{true}, \text{false}\}$ .

► **Example 9.** If we define the set of input states  $I = \{q_1\}$ , output set  $O = \{\text{true}, \text{false}\}$  and the output function  $o(q) = (q = q_3)$ , the protocol in the example 4 computes the predicate  $\varphi(C) = (C(q_1) \geq 3)$ .

### 3 Specifications and turnover

In this section we introduce our definitions permitting composition of protocols. The intuition behind the extended model is as follows. We want the agents to maintain (eventually) a distribution of roles satisfying some constraints dependent on the initial inputs (e.g. servers might assume roles suitable for specific server models). We also want to be able to remove some agents from the group. However, in order to avoid data loss, we inform each agent of their planned removal and let the agent shutdown when it becomes safe. This corresponds to the common practice of scheduling server maintenance and waiting for the migration of tasks. Of course we expect that every agent marked for removal will eventually turn off.

Note that the agent addition does not need to be modelled, because the scheduler can avoid scheduling some agents for interaction. While this will not be a fair execution, it will have the same properties as a fair execution with the isolated agents not existing; allowing more agents to participate would be essentially equivalent to adding new agents.

We now define the notion of implementing a specification, which generalises computing a predicate. Note that in the case of computing a predicate there is only one correct output; here we may have a specification with substantially different ways to satisfy it, and we separately require output stabilisation.

► **Definition 10.** A specification is a predicate on multisets of pairs, each pair containing the initial input state and the final output value. A pair of configurations  $(C_i, C_f)$  with the same domain  $\text{Dom}(C_i) = \text{Dom}(C_f)$  satisfies the specification  $\phi$  if the multiset of pairs  $(C_i(a), o(C_f(q)))$ , taking states occurring in  $C_i$  and the images under the output function  $o$  of the states occurring in  $C_f$ , satisfies  $\phi$ . A protocol implements a specification  $\phi$ , if for every input configuration  $C_0$  and every fair execution of the protocol  $C_0, C_1, \dots$ , there is a number  $n_0$  such that the output value  $o(C_n(a))$  of the agent  $a$  is equal to the output value  $o(C_{n_0}(a))$  at the step  $n_0$ , and moreover taking  $C_0$  as the initial configuration and  $C_{n_0}$  as the final configuration satisfies  $\phi$ . In particular, for finite fair executions  $C_{n_0}$  should exist.

► **Remark 11.** Note that fairness guarantees that configurations with different output values become unreachable at some point in time.

We now define the notion of protocols with shutdown requests, corresponding to the agent removal. This notion alters the execution model, fairness, and specification implementation.

► **Definition 12.** *A protocol with shutdown requests is specified by a population protocol together with a shutdown request function  $s : Q \rightarrow Q$  and a special shutdown state  $\perp$ . The shutdown state may not participate in any non-silent transitions, i.e. interacting with it never changes the other agent's state. We assume for technical convenience that the output value  $o(\perp)$  of the shutdown state is  $\perp$ , its image  $s(\perp)$  under the shutdown request function is  $\perp$ , and the shutdown state is an input state.*

*An execution of a protocol with shutdown requests contains normal execution steps of the protocol part, and two special types of steps. Shutdown request step replaces the state  $q$  of some agent  $a$  with its image  $s(q)$  under the action of shutdown request function, i.e.  $C_{j+1} = C_j[a \mapsto s(C_j(a))]$ . Shutdown step removes some agent  $a$  in the shutdown state, i.e.  $C_{j+1} = C_j \setminus [a \mapsto \perp]$ .*

*An execution is an extinction execution if each agent receives at least one shutdown request.*

*A fair execution of a protocol with shutdown requests should run a shutdown step for every agent reaching the shutdown state. Additionally, as before, all configurations that stay reachable via normal protocol transitions must be reached infinitely many times.*

*A pair  $C_i$  and  $C_f$  of configurations with different domains satisfies a specification  $\phi$ , if the latter has a strictly smaller domain  $\text{Dom}(C_f) \subseteq \text{Dom}(C_i)$ , and the restriction of the former configuration to the latter domain together with the latter configuration satisfies  $\phi$ . Informally, some agents have terminated, and the rest should distribute work according to their capabilities (encoded in the input states).*

*A protocol with shutdown requests implements a specification, if in each fair non-extinction execution from an input configuration all the agents involved in the shutdown request steps and only these agents reach the shutdown state, and like before the configuration of the remaining agents satisfies the specification from some moment on (using the updated notion of satisfaction).*

► **Remark 13.** If all agents receive shutdown requests the last one might never shutdown because there is no other agent left to hand over the responsibilities.

► **Remark 14.** An agent can receive multiple shutdown requests during a fair execution.

► **Example 15.** Consider a protocol with states  $ODD$ ,  $odd$ ,  $ODD'$ ,  $even$ ,  $even'$ ,  $\perp$ . Let the

protocol have the following transitions:

$$\begin{aligned}
(ODD, ODD) &\mapsto (even, even), \\
(ODD, even) &\mapsto (ODD, odd), \\
(odd, even) &\mapsto (even, even), \\
(ODD', ODD) &\mapsto (\perp, even), \\
(ODD', odd) &\mapsto (\perp, even), \\
(ODD', even) &\mapsto (\perp, ODD), \\
(ODD', ODD') &\mapsto (\perp, even'), \\
(ODD', even') &\mapsto (\perp, ODD'), \\
(even', ODD) &\mapsto (\perp, ODD), \\
(even', odd) &\mapsto (\perp, even), \\
(even', even) &\mapsto (\perp, even), \\
(even', ODD') &\mapsto (\perp, ODD'), \\
(even', even') &\mapsto (\perp, even').
\end{aligned}$$

Let  $ODD$  be the only input state. Let the output function be the identity function. Let shutdown request function be defined by the conditions  $s(ODD) = s(even') = even'$ ,  $s(odd) = s(even) = s(ODD') = ODD'$ , and  $s(\perp) = \perp$ .

This protocol with shutdown requests implements the following specification. If there is an odd number of agents, there is one agent with output value  $ODD$  and all others have output value  $odd$ . Otherwise all agents have output value  $even$ .

Indeed, the parity of the number of agents with the  $ODD$  and  $ODD'$  states is the same as the parity of the number of agents who have not received a shutdown request. Moreover, there is also an agent in one of the states  $ODD$ ,  $ODD'$ ,  $even$ , and  $even'$ . The number of agents in the  $ODD$  and  $ODD'$  states reduces when two such agents interact; once new shutdown requests cease arriving, this number will reach either zero or one. A unique  $ODD$  agent in absence of  $ODD'$  agents can (and in a fair execution eventually will) convert all other agents to  $odd$  state;  $even$  agents in absence of  $ODD$  and  $ODD'$  ones can convert all  $odd$  agents to  $even$ . Note also that after receiving a shutdown request agents stay in primed states, and shut down at latest after the next interaction with an agent in an unprimed state, which will be available in a non-extinction execution.

## 4 Composing protocols

In this section we show that population protocols with shutdown requests that implement some relations can be composed. The main result can be stated as follows.

► **Theorem 16.** *For two population protocols with shutdown requests implementing specifications  $\phi_1$  and  $\phi_2$ , with codomain of  $\phi_1$  included in the domain of  $\phi_2$ , there is a protocol with polynomial number of states implementing  $\phi_2 \circ \phi_1$  where composition means composition of relations.*

*Here we assume that input states allowed by  $\phi_2$  do not include  $\perp$ .*

Informally speaking, the composition protocol has each agents store states according to both protocols. On interaction, the agents typically interact according to the first protocol. If the output values stay the same, they also interact according to the second protocol. Otherwise, each agent with the changed output value for the first protocol applies shutdown

request function to the second component of the state. Once the second component reaches the shutdown state, it is replaced with the output value from the first protocol. If the first component reaches the shutdown state, the second component receives a shutdown request. Once both components shut down, so does the agent.

► **Definition 17.** Consider two population protocols with shutdown requests. Let them be defined as  $(Q_1, T_1, I_1, o_1, s_1)$  and  $(Q_2, T_2, I_2, o_2, s_2)$ .

The protocols are disjoint if the only common state is the shutdown state, e.g.  $Q_1 \cap Q_2 = \{\perp\}$ . The protocols are compatible if the output values of the first protocol are input states of the second one, e.g.  $\text{Im}o_1 \subseteq I_2$ .

The direct composition protocol of two disjoint compatible protocols is the following protocol. The set of states is  $Q = Q_1 \times Q_2 \times I_2 \times \{\top, \perp\} \cup \{\perp\}$ . We have two components corresponding to the two protocols being run in parallel, and additionally we keep track the initial state for the second component together with whether the second component has received a shutdown request.

The transitions are as follows (we assume for simplicity that  $T_1$  and  $T_2$  include do-nothing transitions for all pairs of states).

- $(q_1^1, q_2^1, i^1, b^1), (q_1^2, q_2^2, i^2, b^2) \mapsto (q_1^3, q_2^3, i^1, b^1), (q_1^4, q_2^4, i^2, b^2)$   
where  $((q_1^1, q_1^2) \mapsto (q_1^3, q_1^4)) \in T_1$ , and  $((q_2^1, q_2^2) \mapsto (q_2^3, q_2^4)) \in T_2$ .
- $(q_1^1, q_2^1, i^1, \top), (q_1^2, q_2^2, i^2, \top) \mapsto (q_1^1, s_2(q_2^2), i^1, \perp), (q_1^2, q_2^2, i^2, \top)$   
where  $o_1(q_1^1) \neq i^1$ .
- $(q_1^1, \perp, i^1, \perp), (q_1^2, q_2^2, i^2, b^2) \mapsto (q_1^1, o_1(q_1^1), o_1(q_1^1), \top), (q_1^2, q_2^2, i^2, b^2)$ .
- $(\perp, \perp, i^1, b^1), (q_1^2, q_2^2, i^2, b^2) \mapsto \perp, (q_1^2, q_2^2, i^2, b^2)$ .

The input states are all pairs  $(q_1, o(q_1), o(q_1), \top)$  for  $q_1 \in Q_1$ . The output function is defined by looking at the second component in the normal case and the first component otherwise,  $o(q_1, q_2, o_1(q_1), \top) = o_2(q_2)$  and  $o(q_1, q_2, i, b) = o_2(o_1(q_1))$  when the former is unapplicable. The shutdown request function applies the corresponding shutdown request functions to the first component,  $s((q_1, q_2, i, b)) = (s_1(q_1), q_2, i, b)$ .

First we prove that the substantial behaviour is the expected one.

► **Theorem 18.** Consider two population protocols with shutdown requests implementing specifications  $\phi_1$  and  $\phi_2$ . Let them be defined as  $(Q_1, T_1, I_1, o_1, s_1)$  and  $(Q_2, T_2, I_2, o_2, s_2)$ . Assume that  $o_1(q_1) = \perp$  implies  $q_1 = \perp$ , and  $o_2(q_2) = \perp$  implies  $q_2 = \perp$ . Then the composition of the protocols implements the specification  $\phi_2 \circ \phi_1 \circ ((q_1, o_1(q_1), o_1(q_1), \top) \mapsto q_1)$ .

**Proof.** Note that from the point of view of the first components of each agent's state we have a normal execution of the first protocol (up to eventual shutting down). Moreover, the first component receives shutdown requests exactly when a shutdown request occurs in the composition protocol. Thus in a fair non-extinction execution of the composition protocol the first components of the agent states represent a fair non-extinction execution of the first protocol. In particular, in a fair non-extinction execution agents receiving shutdown requests will eventually have  $\perp$  as the first component of the state, and no other agent will. This also implies that no agent will shutdown without receiving a shutdown request. Moreover, in a fair non-extinction execution the agents with states not equal to  $\perp$  and not having  $\perp$  as the first component will eventually have images of the first components of the state under  $o_1$  constant. These states when considered together with the first components of the initial states of the corresponding agents will also satisfy  $\phi_1$ .

Consider now the situation with the second components. There we have an execution of the second protocol interrupted by shutdown requests coming from updates in the initial

state advised by the output value coming from the first protocol, including the case of the first component reaching the shutdown state. Additionally, when the second component reaches the shutdown state without the first component having reached the shutdown state, the second component gets replaced with the initial state equal to the output value for the first component.

Observe that replacing the shutdown state with an input state is equivalent to running a shutdown step to remove the agent and adding another agent with the necessary input state, as agent identities do not affect interactions. Addition of an agent is indistinguishable from finally letting the agent to interact after having it from the beginning but isolated. Note also that the second component of an agent can receive a shutdown request only when this second component has not received a shutdown request and there is another agent with the second component not having received a shutdown request. Thus the configuration of the second components in a reachable configuration  $C$  is always reachable via some finite non-extinction execution from a larger input configuration. Moreover, the restriction of the initial configuration to available agents is equal to the third components of  $C$ .

As we have seen above, in a fair non-extinction execution the output values corresponding to the first components stabilise after some point, and not all of them are  $\perp$ . Afterwards the second component of each agent can receive at most one shutdown request, as in case shutting down occurs afterwards the new initial state will match the output value from the first component. Furthermore, if the second component receives a shutdown request and reaches the shutdown state, either the agent shuts down, the second component gets replaced and will never reach the shutdown state afterwards (as it will not receive shutdown requests). Thus there will be the last time some second component reaches the shutdown state. By the fairness of the execution of the direct composition protocol, each agent will either reach the overall shutdown state and be removed by a later shutdown state, or get the second component reset with the fourth component getting set to  $\top$ . As the overall execution is fair, the second component also models a fair execution of the second protocol. In a fair non-extinction execution of the second protocol, all agents having received a shutdown request have to reach the shutdown state. Overall, from some point on the fourth component of the states of all the remaining agents will be always  $\top$ .

Due to the fairness of the overall execution of the direct composition protocol we know that in the rest of the execution the second components cannot receive shutdown requests, as if they could, they would. There can be two (non-exclusive) reasons for that: either there is only one agent left, or the third components are all equal to the output values for the first components.

In the former case, the first component  $q_1$  of the only agent satisfies  $\phi_1$  with respect to the initial state of the first component of the agent, there is a fair do-nothing execution of the second protocol where the state  $o_1(q_1)$  is assigned to an agent having nothing to interact with, so lone  $o_2(o_1(q_1))$  with  $o_1(q_1)$  as the input has to satisfy  $\phi_2$ . Thus the necessary composition of relations is satisfied.

In the latter case, the output values of the first component satisfy  $\phi_1$  with respect to the corresponding initial input states of the first component, the output values of second components eventually stabilise and satisfy  $\phi_2$  with respect to the third components equal to the output values of the first components, and the overall output values are exactly the output values for the second components. Again we see that the necessary composition of relations is satisfied.

This concludes the proof. ◀

We can now complete the proof of the more streamlined Theorem 16.

**Proof.** We alter the direct composition only slightly.

If there is an output value of the first protocol that is not an input state in the second protocol, we can formally add it as a state of the second protocol with non-silent interactions and itself as the output value. The shutdown request function can map it directly to  $\perp$ . We formally extend  $\phi_2$  to accept any configurations with this input state or output value. As the first protocol is guaranteed by implementing  $\phi_1$  to eventually stop producing this output value, such a change does not affect the composition.

If  $\perp$  is allowed as the output value, we can rename it to something else; note that we still forbid it to appear as an input value in anything accepted by  $\phi_2$ , so the composition doesn't change if we rename it to some new object.

We also need to rename states of the composition protocol so that it takes the same input states as the first protocol. This is a formality that doesn't substantially affect execution or the output values.



## 5 Conclusion and future work

We have presented an extension of the population protocols model with a better support for modular design and synthesis of the protocols.

As the next step we plan to show that the expressive power of this extension is similar to the expressive power of classical population protocols, namely that all semilinear relations with nonempty image of each input configuration can be implemented. This is a work in progress.

A natural future direction would be a study of convergence speed for population protocols with shutdown requests implementing specifications, and of the effect of composition on convergence speed. This might make construction of succinct and fast population protocols for complicated semilinear relations more practical.

---

### References

- 1 Dana Angluin, James Aspnes, Zoë Diamadi, Michael J. Fischer, and René Peralta. Computation in networks of passively mobile finite-state sensors. In Soma Chaudhuri and Shay Kutten, editors, *PODC*, pages 290–299. ACM, 2004. doi:10.1145/1011767.1011810.
- 2 Dana Angluin, James Aspnes, Zoë Diamadi, Michael J. Fischer, and René Peralta. Computation in networks of passively mobile finite-state sensors. *Distributed Computing*, 18(4):235–253, 2006.
- 3 Dana Angluin, James Aspnes, and David Eisenstat. Fast computation by population protocols with a leader. In Shlomi Dolev, editor, *IN DISTRIBUTED COMPUTING: 20TH INTERNATIONAL SYMPOSIUM, DISC 2006*, volume 4167 of *Lecture Notes in Computer Science*, pages 61–75. Springer, 2006.
- 4 Dana Angluin, James Aspnes, David Eisenstat, and Eric Ruppert. The computational power of population protocols. *Distributed Computing*, 20(4):279–304, 2007. URL: <https://arxiv.org/abs/cs/0608084>.
- 5 Michael Blondin, Javier Esparza, Blaise Genest, Martin Helfrich, and Stefan Jaax. Succinct population protocols for presburger arithmetic. *in submission*, 2019. URL: <http://arxiv.org/abs/1910.04600>.
- 6 Michael Blondin, Javier Esparza, Stefan Jaax, and Philipp J. Meyer. Towards efficient verification of population protocols. In Elad Michael Schiller and Alexander A. Schwarzmann, editors, *PODC*, pages 423–430. ACM, 2017.

- 7    Wojciech Czerwiński, Sławomir Lasota, Ranko Lazić, Jérôme Leroux, and Filip Mazowiecki. The reachability problem for Petri nets is not elementary. In *Proc. 51<sup>st</sup> Annual ACM SIGACT Symposium on Theory of Computing (STOC)*, pages 24–33, 2019. doi:10.1145/3313276.3316369.
- 8    David Doty and David Soloveichik. Stable leader election in population protocols requires linear time. In Yoram Moses, editor, *DISC*, volume 9363 of *Lecture Notes in Computer Science*, pages 602–616. Springer, 2015. URL: <https://arxiv.org/abs/1502.04246>.
- 9    Javier Esparza, Pierre Ganty, Jérôme Leroux, and Rupak Majumdar. Model Checking Population Protocols. In Akash Lal, S. Akshay, Saket Saurabh, and Sandeep Sen, editors, *36th IARCS Annual Conference on Foundations of Software Technology and Theoretical Computer Science (FSTTCS 2016)*, volume 65 of *Leibniz International Proceedings in Informatics (LIPIcs)*, pages 27:1–27:14, Dagstuhl, Germany, 2016. Schloss Dagstuhl–Leibniz-Zentrum fuer Informatik. URL: <http://drops.dagstuhl.de/opus/volltexte/2016/6862>, doi:10.4230/LIPIcs.FSTTCS.2016.27.
- 10   Javier Esparza, Stefan Jaax, Mikhail A. Raskin, and Chana Weil-Kennedy. The complexity of verifying population protocols. *Distributed Comput.*, 34(2):133–177, 2021. doi:10.1007/s00446-021-00390-x.
- 11   Javier Esparza, Mikhail Raskin, and Chana Weil-Kennedy. Parameterized analysis of immediate observation petri nets, 2019. URL: <http://arxiv.org/abs/1902.03025>.
- 12   Peng Huang, Chuanxiong Guo, Lidong Zhou, Jacob R. Lorch, Yingnong Dang, Murali Chintalapati, and Randolph Yao. Gray failure. In *Proceedings of the 16th Workshop on Hot Topics in Operating Systems - HotOS '17*. ACM Press, 2017. doi:10.1145/3102980.3103005.