

# THE FIRST-ORDER LOGIC OF CZF IS INTUITIONISTIC

ROBERT PASSMANN

ABSTRACT. We prove that the first-order logic of CZF is intuitionistic first-order logic. To do so, we introduce a new model of transfinite computation (Set Register Machines) and combine the resulting notion of realisability with Beth semantics. On the way, we also show that the propositional admissible rules of CZF are exactly those of intuitionistic propositional logic.

## 1. INTRODUCTION

The *first-order logic of a theory  $T$*  consists of those first-order formulas for which all substitution instances are provable in  $T$ . A classical result of Friedman and Ščedrov [9] is that very few axioms suffice for a set theory to exceed the logical strength of intuitionistic first-order logic:

**Theorem** (Friedman & Ščedrov, 1986). *Let  $T$  be a set theory based on intuitionistic first-order logic that contains the axioms of extensionality, pairing and (finite) union, as well as the separation schema. Then the first-order logic of  $T$  exceeds the strength of intuitionistic first-order logic.*

This result applies to intuitionistic Zermelo-Fraenkel Set Theory (IZF) but not to constructive Zermelo-Fraenkel set theory (CZF) because the separation schema of CZF is restricted to  $\Delta_0$ -formulas. It has, thus, been a long-standing open question whether the first-order logic of CZF exceeds the strength of intuitionistic logic as well. We give an answer to this question:

**Theorem** (see Corollary 52). *The first-order logic of CZF is intuitionistic first-order logic.*

We prove this result by developing a realisability semantics for CZF based on a new model of transfinite computation, the so-called *Set Register Machines* (SRMs). The main result is obtained by adapting a technique that van Oosten [22] had developed for Heyting arithmetic: we combine the resulting notion of SRM-realisation with Beth semantics to obtain a model of CZF that matches logical truth in a universal Beth model.

Carl et al. [3] gave a first proof-theoretic application of transfinite computability and provided a realisability interpretation for (infinitary) IKP set theory using OTMs. In particular, they proved that the propositional admissible rules of IKP are exactly the admissible rules of intuitionistic propositional logic. On the way to proving our main result, we will prove the same result for CZF. Our motivation for introducing SRMs instead of working with OTMs is that the former are easier adapted for realising stronger set theories than IKP. This work is thus another fruitful application of techniques of transfinite computability to proof-theoretic questions.

**Overview.** After recalling some preliminaries in section 2, we will begin, in section 3, with introducing our new notion of transfinite machines, the so-called *set register machines* (SRMs). The main result of this section will be a generalisation of a classical result by Kleene and Post about the existence of mutually irreducible degrees of computability. In section 4, we introduce a realisability semantics based on SRMs and show that (a certain extension of) these machines allows to realise CZF set theory. It also serves as a preparation for section 5, in which we will combine our realisability semantics with Beth models to prove our main result.

---

*Date:* December 2, 2021.

## 2. PRELIMINARIES

**2.1. Constructive Set Theory.** We will be concerned with constructive Zermelo–Fraenkel set theory, CZF, and now recall its definition and some basic facts. First, recall the axiom schemes of *strong collection*,

$$\forall a[\forall x \in a \exists y \varphi(x, y) \rightarrow \exists b(\forall x \in a \exists y \in b \varphi(x, y) \wedge \forall y \in b \exists x \in a \varphi(x, y))],$$

for all formulas  $\varphi$ , in which  $b$  is not free, and *subset collection*,

$$\forall a \forall b \exists c \forall u[\forall x \in a \exists y \in b \varphi(x, y, u) \rightarrow \exists d \in c(\forall x \in a \exists y \in d \varphi(x, y, u) \wedge \forall y \in d \exists x \in a \varphi(x, y, u))],$$

for all formulas  $\varphi$ , in which  $c$  is not free. By  $\Delta_0$ -separation we denote the restriction of the separation schema to  $\Delta_0$ -formulas.

**Definition 1.** Constructive Zermelo–Fraenkel Set Theory, CZF, is based on intuitionistic first-order logic in the language of set theory and consists of the following axioms and axiom schemes: extensionality, pairing, union, empty set, infinity,  $\Delta_0$ -separation, strong collection, subset collection, and  $\in$ -induction.

We denote CZF without the subset collection schema by  $\text{CZF}^-$ . The exponentiation axiom states that function sets exists:

$$\forall a \forall b \exists c \forall f (f \in c \leftrightarrow \text{“}f \text{ is a function from } a \text{ to } b\text{”}).$$

The following is well known (consult, e.g., Aczel and Rathjen [1]).

**Fact 2.** In  $\text{CZF}^-$ , the power set axiom implies the subset collection axiom. Moreover, in  $\text{CZF}^-$ , the subset collection scheme implies the exponentiation axiom.

**2.2. Logics & De Jongh’s Theorem.** Given a theory  $T$ , based on intuitionistic logic, the logically valid principles of  $T$  may exceed those valid in intuitionistic logic. The most well-known example of this phenomenon is probably the following consequence of what is known as *Diaconescu’s theorem* (see Diaconescu [7], Goodman and Myhill [10]): IZF extended with the axiom of choice implies the law of excluded middle, i.e.  $\text{IZF} + \text{AC} \vdash \varphi \vee \neg\varphi$  for all set-theoretic formulas  $\varphi$ . This suggests that it is incorrect to say that the logic of  $\text{IZF} + \text{AC}$  is intuitionistic: after all, the law of excluded middle is valid! For this reason, we define the propositional and first-order logics of a theory  $T$  as follows, in terms of translations. Note that we denote intuitionistic propositional logic by **IPC** and intuitionistic first-order logic by **IQC**.

**Definition 3.** Let  $T$  be a theory in a language  $\mathcal{L}_T$ . A *propositional translation* is a function  $\tau$  assigning  $\mathcal{L}_T$ -sentences to propositional formulas such that:

- (i)  $\tau(p)$  is an  $\mathcal{L}_T$ -sentence for every propositional letter  $p$ ,
- (ii)  $\tau(\perp) = \perp$ , and,
- (iii)  $\tau(A \circ B) = \tau(A) \circ \tau(B)$  for  $\circ \in \{\wedge, \vee, \rightarrow\}$ .

As customary with translations, we will often write  $A^\tau$  instead of  $\tau(A)$ .

**Definition 4.** The *propositional logic of  $T$* ,  $\text{PL}(T)$ , consists of all propositional formulas  $A$  such that  $T \vdash A^\tau$  for all propositional translations  $\tau$ .

A result concerning the first-order logic of Heyting arithmetic was proved by de Jongh in his doctoral dissertation [4].

**Theorem 5** (de Jongh, 1970). *The propositional logic of Heyting arithmetic is intuitionistic propositional logic,  $\text{PL}(\text{HA}) = \text{IPC}$ .*

This result is now known as *de Jongh’s theorem*, and, in general, we say that a theory  $T$  *satisfies de Jongh’s theorem* whenever  $\text{PL}(T) = \text{IPC}$ .

**Definition 6.** Let  $T$  be a theory in a language  $\mathcal{L}_T$ . A *first-order translation* is a function  $\tau$  assigning  $\mathcal{L}_T$ -formulas to propositional formulas such that:

- (i)  $\tau(R(x_1, \dots, x_n))$  is an  $\mathcal{L}_T$ -formula  $\varphi$  with free variables among  $x_1, \dots, x_n$ ,
- (ii)  $\tau(\perp) = \perp$ ,
- (iii)  $\tau(A \circ B) = \tau(A) \circ \tau(B)$  for  $\circ \in \{\wedge, \vee, \rightarrow\}$ , and,
- (iv)  $\tau(\mathcal{Q}xA(x)) = \mathcal{Q}x\tau(A(x))$  for  $\mathcal{Q} \in \{\forall, \exists\}$ .

**Definition 7.** The *first-order logic of  $T$* ,  $\mathbf{QL}(T)$ , consists of all first-order formulas  $A$  such that  $T \vdash A^\tau$  for all first-order translations  $\tau$ .

Since de Jongh's initial work, many notable results have been obtained in this area. Leivant [17] showed that  $\mathbf{QL}(\text{HA}) = \mathbf{IQC}$ ; van Oosten [22] gave a semantic proof of this fact (the idea of his construction will reappear in our construction in Section 5). De Jongh, Verbrugge and Visser [6] consider a generalised version of de Jongh's theorem: given a (propositional or first-order) logic  $J$  and a theory  $T$ , we can consider the theory  $T(J)$  obtained by closing  $T$  under  $J$ . We then say that  $T$  satisfy the *de Jongh property for  $J$*  if  $\mathbf{PL}(T(J)) = J$  ( $\mathbf{QL}(T(J)) = J$  in case  $J$  is a first-order logic).

The main negative result concerning logics of set theory is due to Friedman and Ščedrov [9], and was also mentioned in the introduction. Here is a reformulation based on the terminology just introduced.

**Theorem 8.** *Let  $T$  be a set theory based on intuitionistic first-order logic that contains the axioms of extensionality, pairing and (finite)union, as well as the separation scheme. Then,  $\mathbf{IQC} \subsetneq \mathbf{QL}(T)$ .*

Passmann [18] showed that the  $\mathbf{PL}(\text{IZF}) = \mathbf{IPC}$ , and consequently,  $\mathbf{PL}(\text{CZF}) = \mathbf{IPC}$ . Iemhoff and Passmann [14] analysed the logical structure of IKP and proved, among other things, that  $\mathbf{QL}(\text{IKP}) = \mathbf{IQC}$ .

**2.3. Admissible Rules.** We can further generalise an analysis of the logical structure of a given theory by not only considering its logical validities but also by determining its rules.

**Definition 9.** Let  $T$  be a theory in a language  $\mathcal{L}_T$ , and let  $A$  and  $B$  be propositional formulas. We say that a propositional rule  $A/B$  is *admissible in  $T$* , written  $A \sim_T B$ , if and only if  $T \vdash A^\tau$  implies  $T \vdash B^\tau$  for all propositional translations  $\tau$ .

We say that a theory  $T$  has the disjunction property if  $T \vdash \varphi \vee \psi$  implies  $T \vdash \varphi$  or  $T \vdash \psi$ . The *restricted Visser's rules*  $\{V_n\}_{n < \omega}$  are defined as follows and play a special role for admissibility (Iemhoff [11] proved that they form a so-called basis of the admissible rules of intuitionistic propositional logic):

$$\frac{\left( \bigwedge_{i=1}^n (p_i \rightarrow q_i) \right) \rightarrow (p_{n+1} \vee p_{n+2})}{\bigvee_{j=1}^{n+2} \left( \bigwedge_{i=1}^n (p_i \rightarrow q_i) \rightarrow p_j \right)}$$

Denote by  $V_n^a$  the antecedent and by  $V_n^c$  the consequent of the rule. We will make use of the following result of Iemhoff [12] to determine admissible rules.

**Theorem 10** (Iemhoff, [12, Theorem 3.9, Corollary 3.10]). *If the restricted Visser's rules are propositional admissible for a theory  $T$  with the disjunction property, then the propositional admissible rules of  $T$  are exactly the propositional admissible rules of intuitionistic propositional logic,  $\sim_T = \sim_{\mathbf{IPC}}$ .*

Visser [23] proved that the propositional admissible rules of Heyting Arithmetic HA are exactly the admissible rules of intuitionistic propositional logic  $\mathbf{IPC}$ . Using realisability techniques, Carl et al. [3] determined the propositional admissible rules of IKP to be exactly the admissible rules of propositional intuitionistic logic. Iemhoff and Passmann [13] proved that the propositional admissible rules of  $\text{CZF}_{\text{ER}}$

and  $\text{IZF}_R$  are the admissible rules of intuitionistic propositional logic by using a modification of the so-called blended models (earlier introduced by Passmann [18]).<sup>1</sup> It is possible to consider first-order admissible rules; van den Berg and Moerdijk [21] show that certain constructive principles are first-order admissible rules of CZF (calling them *derived* rules).

### 3. SET REGISTER MACHINES

**3.1. Definitions & Basic Properties.** Let us begin with some intuitive understanding of set register machines (SRMs). A set register machine has a finite set of registers  $R_0, \dots, R_n$  on which it conducts computations. However, the registers do not contain natural numbers (as in the case of register machines) or ordinal numbers (as in the case of ordinal register or Turing machines) but rather arbitrary sets. Accordingly, SRMs use a different set of operations: for example, adding a set contained in a register to another register, or removing a member of a set contained in a certain register.

We assume that  $<_\tau$  is a global well-ordering such that  $\text{rank}(x) < \text{rank}(y)$  implies  $x <_\tau y$ .<sup>2</sup> This means that we are working under the assumption of the global axiom of choice and extend our set-theoretical language with the symbol  $<_\tau$ . Note that this extended theory is conservative over ZFC (see Fraenkel et al. [8, 72-73]). The reason for using this theory as our meta-theory is that we want SRM-computations to be deterministic, and assuming a global well-ordering is a convenient way to achieve this. For a discussion of alternatives see Remark 13.

We will now first define programs by giving the permissible operations, and then computations for set register machines. While defining the permissible operations, we will directly give an intuitive description of what the operation does.

**Definition 11.** A *set register program*  $p$  is a finite sequence  $p = (p_0, \dots, p_{n-1})$ , where each  $p_i$  is one of the following commands:

- (i) “ $R_i := \emptyset$ ”: replace the content of the  $i$ th register with the empty set.
- (ii) “ $\text{ADD}(i, j)$ ”: replace the content of the  $j$ th register with  $R_j \cup \{R_i\}$ .
- (iii) “ $\text{COPY}(i, j)$ ”: replace the content of the  $j$ th register with  $R_i$ .
- (iv) “ $\text{TAKE}(i, j)$ ”: replace the content of the  $j$ th register with the  $<_\tau$ -least set contained in  $R_i$ , if  $R_i$  is non-empty.
- (v) “ $\text{REMOVE}(i, j)$ ”: replace the content of the  $j$ th register with the set  $R_i \setminus \{R_j\}$ .
- (vi) “ $\text{IF } R_i = \emptyset \text{ THEN GO TO } k$ ”: check whether the  $i$ th register is empty; if so, move to program line  $k$ , and, if not, move to the next line.
- (vii) “ $\text{IF } R_i \in R_j \text{ THEN GO TO } k$ ”: check whether  $R_i \in R_j$ ; if so, move to program line  $k$ , and, if not, move to the next line.
- (viii) “ $\text{POW}(i, j)$ ”: replace the content of the  $j$ th register with the power set of  $R_i$ .

**Definition 12.** Let  $p$  be a set register program and  $k < \omega$  be the highest register index appearing in  $p$ . A *configuration* of  $p$  is a sequence  $(l, r_0, \dots, r_k)$  consisting of the active program line  $l \in \mathbb{N}$  and the current content  $r_i$  of register  $R_i$ . If  $c = (l, r_0, \dots, r_k)$  is a configuration of  $p$ , then its successor configuration  $c^+ = (l^+, r_0^+, \dots, r_k^+)$  is obtained as follows:

- (i) If  $p_l$  is “ $R_i := \emptyset$ ”, then let  $r_i^+ = \emptyset$ ,  $r_j^+ = r_j$  for  $j \neq i$ , and  $l^+ = l + 1$ .
- (ii) If  $p_l$  is “ $\text{ADD}(i, j)$ ”, then let  $r_j^+ = r_j \cup \{r_i\}$ ,  $r_n^+ = r_n$  for  $n \neq j$ , and  $l^+ = l + 1$ .
- (iii) If  $p_l$  is “ $\text{COPY}(i, j)$ ”, then let  $r_j^+ = r_i$ ,  $r_n^+ = r_n$  for  $n \neq j$ , and  $l^+ = l + 1$ .

<sup>1</sup>To obtain  $\text{CZF}_{\text{ER}}$  and  $\text{IZF}_R$ , replace subset collection and (strong) collection by exponentiation and replacement, respectively.

<sup>2</sup>Whenever  $<_\tau$  is a global well-ordering, we can assume that this is the case by defining  $x <'_\tau y$  if and only if  $\text{rank}(x) < \text{rank}(y)$  or  $\text{rank}(x) = \text{rank}(y)$  and  $x <_\tau y$ . Note that  $<'_\tau$  is again a well-order.

- (iv) If  $p_i$  is “TAKE( $i, j$ )”, then let  $r_j^+$  be the  $<_\tau$ -minimal element of  $r_i$  (if that exists; if  $r_i = \emptyset$ , then  $r_j^+ = r_j$ ),  $r_n^+ = r_n$  for  $n \neq j$ , and  $l^+ = l + 1$ .
- (v) If  $p_i$  is “REMOVE( $i, j$ )”, then let  $r_j^+ = r_j \setminus \{r_i\}$ ,  $r_n^+ = r_n$  for  $n \neq j$ , and  $l^+ = l + 1$ .
- (vi) If  $p_i$  is “IF  $R_i = \emptyset$  THEN GO TO  $m$ ”, then  $r_i^+ = r_i$  for all  $i \leq k$ ; and, if  $r_i = \emptyset$ , then  $l^+ = m$ ; if  $r_i \neq \emptyset$ , then  $l^+ = l + 1$ .
- (vii) If  $p_i$  is “IF  $R_i \in R_j$  THEN GO TO  $m$ ”, then  $r_i^+ = r_i$  for all  $i \leq k$ ; and, if  $r_i \in r_j$ , then  $l^+ = m$ ; if  $r_i \notin r_j$ , then  $l^+ = l + 1$ .
- (viii) If  $p_i$  is “POW( $i, j$ )”, then  $r_j^+ = \mathcal{P}(r_i)$ ,  $r_n^+ = r_n$  for all  $n \neq i$ , and  $l^+ = l + 1$ .

A computation of  $p$  with input  $x_0, \dots, x_j$  is a sequence  $d$  of ordinal length  $\alpha + 1$  consisting of configurations of  $p$  such that:

- (i)  $d_0 = (1, x_0, \dots, x_j, \emptyset, \dots, \emptyset)$ ,
- (ii) if  $\beta < \alpha$ , then  $d_{\beta+1} = d_\beta^+$ ,
- (iii) if  $\beta < \alpha$  is a limit, then  $l_\beta = \liminf_{\gamma < \beta} l_\gamma$ , and  $r_\beta = \liminf_{\gamma < \beta} r_\gamma$ , where the limes inferior of a sequence of sets is the set obtained from the limes inferior of the characteristic functions, and,
- (iv)  $d_\alpha^+$  is undefined (i.e.,  $l_\alpha > m$ ).

The notion of computability obtained by restricting Definitions 11 and 12 to clauses (i) – (vii) will be referred to as SRM; the full notion will be referred to as SRM<sup>+</sup>. In other words, SRM<sup>+</sup> is obtained from SRM by adding the power set operation. We allow SRMs and SRM<sup>+</sup>s to make use of finitely many set parameters which will be treated as additional input in a fixed register as specified in the program code.

**Remark 13.** There are several alternatives for working with a global well-ordering function  $<_\tau$ : first, it is possible to develop a theory of non-deterministic SRMs, where the TAKE-command takes an arbitrary set. Second, SRMs could work on well-ordered sets (i.e. sets equipped with a well-order). This approach is not useful for SRM<sup>+</sup> as there is no canonical way in extending the well-ordering of a set to its power set (i.e. a certain degree of non-determinateness is introduced again). A third approach is to make computations dependent on a large enough well-ordering of some initial  $V_\alpha$ . Finally, one could work in the constructible universe  $L$  where we have a  $\Sigma_1$ -definable well-ordering  $<_L$ . We will, in fact, consider this approach in Section 3.3 but for different reasons: for our main application, we need computations to be definable in the language of set theory without an additional symbol for the global well-ordering.

**Definition 14.** A function  $f$  is SRM<sup>(+)</sup>-computable if there is an SRM<sup>(+)</sup>-program  $p$ , possibly with parameters, which computes  $f(x)$  on input  $x$ . A predicate is called SRM<sup>(+)</sup>-computable if its characteristic function is SRM<sup>(+)</sup>-computable.

Note that every function with set-sized domain is SRM-computable. Clearly, if a function or predicate is SRM-computable, then it is also SRM<sup>+</sup>-computable. The converse does not hold: consider, for example, the power set operation.

**Proposition 15.** *Equality of sets is SRM-computable.*

*Proof.* The following SRM-program computes whether the sets contained in registers  $R_0$  and  $R_1$  are equal: the program successively takes elements of the first set, checks whether they are contained in the second set, and removes the element from both sets. If both registers  $R_0$  and  $R_1$  are empty at the same time, then the original sets must have been equal. Otherwise, the original sets were not equal.

- 1: IF  $R_0 = \emptyset$  THEN GO TO 3
- 2: GO TO 5
- 3: IF  $R_1 = \emptyset$  THEN GO TO 11
- 4: GO TO 14

```

5: TAKE(0, 2)
6: REMOVE(2, 0)
7: IF  $R_2 \in R_1$  THEN GO TO 9
8: GO TO 14
9: REMOVE(2, 1)
10: GO TO 1
11:  $R_0 := \emptyset$ 
12: ADD(0, 0)
13: GO TO 15
14:  $R_0 := \emptyset$ 

```

Note that the operation “GO TO  $i$ ” is a shortcut for “IF  $R_j = \emptyset$  THEN GO TO  $i$ ” where  $j$  is chosen in such a way that the register  $R_j$  is not mentioned in any other instruction of the program.  $\square$

In view of this proposition, we can use an operation “IF  $R_i = R_j$  THEN GO TO  $k$ ” by implementing the program of the proof of the proposition as a subroutine. The following lemma shows that many basic operations and predicates are  $\text{SRM}^+$ -computable.

**Lemma 16.** *The following functions and predicates are  $\text{SRM}^+$ -computable:*

- (i) the binary union function  $(x, y) \mapsto x \cup y$ ,
- (ii) the intersection function  $(x, y) \mapsto x \cap y$ ,
- (iii) the singleton and pairing functions,  $x \mapsto \{x\}$  and  $(x, y) \mapsto \{x, y\}$ ,
- (iv) the ordered pairing function  $(x, y) \mapsto \langle x, y \rangle$ ,
- (v) the first and second projections  $\langle x, y \rangle \mapsto x$ ,  $\langle x, y \rangle \mapsto y$ ,
- (vi) the predicate “ $x$  is an ordered pair”,
- (vii) the predicate “ $x$  is a function”,
- (viii) the union of a set,  $x \mapsto \bigcup x$ ,
- (ix) the intersection of a set,  $x \mapsto \bigcap x$ ,
- (x) the function mapping a function to its domain  $f \mapsto \text{dom}(f)$ ,
- (xi) function application  $(f, x) \mapsto f(x)$ ,
- (xii) the predicate “ $x$  is an ordinal”,
- (xiii) the predicate “ $x$  is a sequence of ordinal length”,
- (xiv) the function computing the  $<_\tau$ -least element  $x \in y$  satisfying an  $\text{SRM}^+$ -computable predicate  $P(x)$ ,
- (xv) the  $\alpha$ th projection on a sequence,  $\langle x_i \mid i < \beta \rangle \mapsto x_\alpha$ ,
- (xvi) the power set function,  $x \mapsto \mathcal{P}(x)$ ,
- (xvii) the predicate “ $x$  is the power set of  $y$ ”,
- (xviii) the limes inferior of a sequence of sets.

*Proof.* We will give explicit programs for the first few cases and then move to increasingly abstract descriptions of the desired programs:

- (i) Observe that the following program computes the union of the sets in registers  $R_0$  and  $R_1$  by adding all elements of  $R_1$  to  $R_0$ :

```

1: IF  $R_1 = \emptyset$  THEN GO TO 6
2: TAKE(1, 2)
3: REMOVE(2, 1)
4: ADD(2, 0)

```

- 5: GO TO 1
- (ii) Observe that the intersection of the sets contained in registers  $R_0$  and  $R_1$  can be computed as follows. Check for each element of  $R_1$  whether it is contained in  $R_0$  and, if so, save it into a register for the intersection:
- 1: IF  $R_1 = \emptyset$  THEN GO TO 8
  - 2: TAKE(1, 2)
  - 3: REMOVE(2, 1)
  - 4: IF  $R_2 \in R_0$  THEN GO TO 6
  - 5: GO TO 1
  - 6: ADD(2, 3)
  - 7: GO TO 1
  - 8: COPY(3, 0)
- (iii) The functions of (iii) can be easily implemented.
- (iv) Recall that  $\langle x, y \rangle = \{\{x\}, \{x, y\}\}$ , and this can easily be computed.
- (v) Note that  $\bigcap \langle x, y \rangle = x$  and  $\bigcup \langle x, y \rangle = \{x, y\}$ . So we can construct the desired programs by combining the procedures from (i) and (ii) in a straightforward way.
- (vi) We have to implement a procedure that checks whether  $x$  is an ordered pair: use (v) to compute the first and second projection of  $x$ , say,  $y$  and  $z$ . Then compute  $\langle y, z \rangle$  with (iv) and check whether this equals  $x$ .
- (vii) Check whether  $x$  consists of ordered pairs (using (vi)), and then check that  $x$  is functional with (v).
- (viii) Use four registers:  $R_0$  contains  $x$ ,  $R_1$  for the union of  $x$ , and  $R_2$  and  $R_3$  as auxiliary registers. Then proceed as follows: as long as  $R_0$  is non-empty, take a set from  $R_0$  and save it in  $R_2$ , then remove it from  $R_0$ . Then, as long as  $R_2$  is non-empty, take an element of  $R_2$  and save it in  $R_3$ , then remove it from  $R_2$  and add it to  $R_1$ . Once  $R_0$  is empty, we are done: copy our result from  $R_1$  to  $R_0$ , and stop.
- (ix) A similar procedure as in the previous item does the job.
- (x) Take and remove elements from  $R_0$  as long as it is non-empty. To each element, apply the first-projection from (v), and add it to  $R_1$ . Once  $R_0$  is empty,  $R_1$  contains the domain of  $x$ .
- (xi) Search through  $f$  until a pair with first coordinate  $x$  is found. Then return the second projection of that pair.
- (xii) Observe that it is straightforward to compute whether “ $x$  is a transitive set of transitive sets”.
- (xiii) Check whether  $x$  is a function whose domain is an ordinal.
- (xiv) Given a procedure for checking  $P$ , take and remove elements from  $y$  until some  $x$  is found satisfying  $P(x)$ . By the definition of the TAKE-operation, this will be the  $<_\tau$ -minimal element of  $y$  satisfying  $P$ .
- (xv) This is just function application.
- (xvi) This is straightforward using the POW-operation.
- (xvii) Again, straightforward using the POW-operation.
- (xviii) Note that the limes inferior of a sequence of sets can be presented as follows:

$$\liminf_{\gamma < \alpha} x_\gamma = \bigcup_{\beta < \alpha} \bigcap_{\gamma \in [\beta+1, \alpha)} x_\gamma.$$

This can be straightforwardly implemented by combining the previous items of this lemma.

□

**Lemma 17.** *Let  $\varphi(\bar{x})$  be a  $\Delta_0$ -formula. There is an SRM  $p$  such that  $p(\ulcorner \varphi \urcorner, \bar{x}) = 1$  if  $V \models \varphi(\bar{x})$  and  $p(\ulcorner \varphi \urcorner, \bar{x}) = 0$  if  $V \models \neg \varphi(\bar{x})$ .*

*Proof.* We construct a machine that recursively calls itself. For the base cases, let  $p(\ulcorner x_i = x_j \urcorner, \bar{x})$  be the program that returns 1 if  $x_i = x_j$  and 0 if  $x_i \neq x_j$ . Similarly, let  $p(\ulcorner x_i \in x_j \urcorner, \bar{x})$  be the program that returns 1 if  $x_i \in x_j$  and 0 if  $x_i \notin x_j$ . The cases for conjunction, disjunction and implication are easily constructed by recursion. For the bounded existential quantifier,  $\exists x \in a \varphi(x)$ , the machine  $p$  conducts a search through  $a$  by consecutively taking and removing elements. If  $p$  finds some  $b \in a$  such that  $p(\ulcorner \varphi \urcorner, \langle a, x \rangle) = 1$ , then  $p$  returns 1. If no such  $b$  is found, then  $a$  does not contain a witness for  $\varphi$  and  $p$  returns 0. The bounded universal quantifier can be implemented similarly with a bounded search.  $\square$

The next theorem shows that moving from Ordinal Turing Machines to Set Register Machines does not increase the computational strength. We do not give a detailed proof since the result is not used in the remainder of this article.

**Theorem 18.** *Ordinal Turing machines with parameters (OTMs) and set register machines with parameters (SRMs) can simulate each other.*

*Proof.* For the first direction, recall that OTMs and ordinal register machines (ORMs) can simulate each other (e.g. Carl [2]). It will, therefore, be enough to show that SRMs simulate ORM programs but, in fact, more is true: it is straightforward to see that every ORM-program can be executed by an SRM.

The other direction can be shown by a straightforward but tedious coding argument by using a large enough fragment of the well-order  $<_\tau$  as a parameter (Carl et al. [3] spell out a very similar argument in an appendix; Carl [2, Section 2.3.2 and Chapter 3] discusses codings as well).  $\square$

**3.2. Oracles and relative computability.** As with other notions of computability, we can enrich  $\text{SRM}^+$ s with oracles. Let  $O : V \rightarrow V$  be a partial class function. We obtain oracle  $\text{SRM}^{+,O}$  by extending Definition 11 with the following operation:

“ORACLE( $i, j$ )”: replace the contents of the  $j$ th register with the result of querying the oracle  $O$  with  $R_i$ .

We also extend Definition 12:

If  $p_i$  is “ORACLE( $i, j$ )”, proceed as follows: if  $O(r_i)$  is defined, let  $r_j^+ = O(r_i)$ ,  $r_n^+ = r_n$  for all  $n \neq i$ , and  $l^+ = l + 1$ . If  $O(r_i)$  is undefined, let  $r_j^+ = r_j$  for all  $j \leq k$  and  $l^+ = l$ .

The evaluation function is chosen like this to ensure that any  $\text{SRM}^{+,O}$  loops whenever the oracle is queried on undefined input. This entails that the oracle is only queried on its domain within a successful computation. Given oracles, we can define a relative notion of computability.

**Definition 19.** We say that a function  $f$  is  $\text{SRM}^+$ -computable in  $g$  if and only if there is an  $\text{SRM}^{+,g}$  program  $p$  that computes  $f$ .

Note that a function is  $\text{SRM}^+$ -computable if and only if it is  $\text{SRM}^+$ -computable in the empty function. In fact, a function is  $\text{SRM}^+$ -computable if and only if it is  $\text{SRM}^+$ -computable in every set-sized function.

We will now work towards generalising a result of Kleene and Post [16], which will be useful later but is also interesting in its own regard.

**Proposition 20.** *The class function  $V_{(\cdot)} : \text{Ord} \rightarrow V, \alpha \mapsto V_\alpha$  is  $\text{SRM}^+$ -computable.*

*Proof.* An  $\text{SRM}^+$ -program does this by starting with the empty set and consecutively computing power sets while keeping the current rank in an auxiliary register. The program keeps computing until it reaches the desired  $\alpha$ .

This procedure is implemented in the following program, where the input  $\alpha$  is written into  $R_0$ ; note that the initial configuration of all other registers is  $\emptyset$ . We use  $R_1$  to count our current stage  $\beta$  and  $R_2$  to save the current  $V_\beta$ .

- 1: IF  $R_0 = R_1$  THEN GO TO 5
- 2: POW(2, 2)
- 3: ADD(1, 1)
- 4: GO TO 1

Note that the register  $R_0$  remains unchanged, and the registers  $R_1$  and  $R_2$  are monotonically increasing. Therefore, the program does the job also at limit stages.  $\square$

The following proposition can be anticipated from how the evaluation of the TAKE-operation was defined.

**Proposition 21.** *The global well-ordering  $<_\tau$  is  $\text{SRM}^+$ -decidable.*

*Proof.* This is implemented by an  $\text{SRM}^+$  that does the following: check whether  $x = y$ . If so, we are done. If not, compute the least  $\alpha$  such that  $x, y \in V_\alpha$ . This can be done by slightly adapting the procedure from the proof of the previous proposition. Then keep taking and removing elements  $z$  from  $V_\alpha$  until either  $z = x$  or  $z = y$ . In the first case,  $x \leq_\tau y$  and otherwise, we have  $y \leq_\tau x$ .  $\square$

By the  $\alpha$ th element of  $V$  according to  $<_\tau$ , we denote the unique  $x$  such that the order type of  $(\{y \mid y <_\tau x\}, <_\tau)$  is  $\alpha$ .

**Proposition 22.** *The bijective class function  $F_\tau : \text{Ord} \rightarrow V$  mapping  $\alpha$  to the  $\alpha$ th element of  $V$  according to  $<_\tau$  is  $\text{SRM}^+$ -computable and so is its inverse.*

*Proof.* A slight adaptation of the procedure from the previous proposition does the job: essentially, we need to keep book of which elements we have already enumerated and at what stage  $\gamma$  of the enumeration we currently are. Once we have reached  $\alpha$  (i.e., until  $\gamma = \alpha$ ), we are done. For the inverse function, observe that we can replace the break condition ' $\gamma = \alpha$ ' with the condition that the current set is equal to the one we are looking for, and then return  $\gamma$ . Note that these procedures work because of our assumption that  $\text{rank}(x) < \text{rank}(y)$  implies  $x <_\tau y$ . This ensures that computing  $<_\tau$  on some  $V_\alpha$  means to compute an initial segment of  $<_\tau$ .  $\square$

**Proposition 23.** *Let  $O$  be a (partial) class function. The  $\text{SRM}^{+,O}$  halting problem is  $\text{SRM}^{+,O}$  undecidable.*

*Proof.* This is proved by contradiction. Assume that there is a machine  $p$  such that  $p(x) = 1$  if and only if  $x$  is an  $\text{SRM}^+$  that halts, and  $p(x) = 0$  otherwise. Then define a machine  $q$  such that  $q(x)$  does not halt if and only if  $p(x) = 1$ . Then,  $p(q) = 1$  if and only if  $q(q)$  does not halt if and only if  $p(q) = 0$ . A contradiction.  $\square$

**Proposition 24.** *Let  $O$  be a (partial) class function. Then there is an oracle  $\tilde{O}$  such that there is an  $\text{SRM}^{+,\tilde{O}}$ -program  $u$  which is universal for  $\text{SRM}^{+,O}$ , i.e.  $u(p, x)$  and  $p(x)$  are both defined and equal whenever at least one of them is defined. Moreover, there is an  $\text{SRM}^{+,\tilde{O}}$ -program  $c$  such that  $c(p, x) = 1$  if  $x$  is a successful computation of  $p$  and  $c(p, x) = 0$  otherwise. In particular, if  $O$  is the empty function, then  $\tilde{O}$  can be taken empty as well.*

*Proof.* Let  $\tilde{O}$  be the function such that  $\tilde{O}(x) = \langle 1, O(x) \rangle$  whenever  $O(x)$  is defined and  $\tilde{O}(x) = \langle 0, 0 \rangle$  whenever  $O(x)$  is undefined. Using Lemma 16 and  $\tilde{O}$ , it is straightforward (but tedious) to construct a program  $c$  such that  $c(p, x) = 1$  if  $x$  is a successful computation of  $p$  and  $c(p, x) = 0$  otherwise. Then note that  $p(x)$  is defined if and only if there is a successful computation of  $p$  on input  $x$ . For this reason, the universal machine can be implemented as an unbounded search through  $V$  that stops if a successful computation for  $p$  on input  $x$  is found, and returns  $p(x)$ . In the case where  $O$  is the empty function, we can take  $\tilde{O}$  to be the empty function as well because all  $\text{SRM}^+$ -operations are  $\text{SRM}^+$ -decidable.  $\square$

It is possible to construct a  $\text{SRM}^{+,O}$ -universal machine for  $\text{SRM}^{+,O}$ , if one changes the definition of oracle evaluation in such a way that the universal machine can call the oracle without the risk of not halting.

Let  $D(x, y)$  be a binary predicate in the language of set theory. Adapting from Kleene and Post [16], we write  $D_z(x) := D(x, z)$  and

$$D^z(x, y) := \begin{cases} D(x, y) & \text{if } y \neq z, \\ D(x, \emptyset) & \text{if } y = z \text{ and } x \neq \emptyset, \\ D(x, 1) & \text{if } y = z \text{ and } x = \emptyset. \end{cases}$$

The proof of the following theorem is a generalisation of a result by Kleene and Post [16, Theorem 2]; our proof will be a generalisation of their diagonal argument to the case of  $\text{SRM}^+$ .

**Theorem 25.** *There is a non- $\text{SRM}^+$ -computable set-theoretic predicate  $D(x, y)$  such that  $D_z$  is not  $\text{SRM}^+$ -computable in  $D^z$ .*

*Proof.* We define the predicate by informally describing a total  $\text{SRM}^{+,H}$ -program that makes use of an oracle  $H$  for the  $\text{SRM}^+$ -halting problem.

Let  $R_{init}$  be an auxiliary register which is used to save an initial segment of the predicate we are defining. Let  $R_{stage}$  be an auxiliary register that contains an ordinal representing the current stage of the construction.

To ensure the non-computability desired in the theorem, we have to satisfy class-many conditions, for each  $\text{SRM}^+$ -program  $e$  (possibly with parameters) and set  $z$ :

( $P_{e,z}$ ) The program  $e$  does not witness that  $D_z$  is  $\text{SRM}^+$ -computable in  $D^z$ .

( $Q_e$ ) The program  $e$  does not witness that  $D$  is  $\text{SRM}^+$ -computable.

Apply the inverse Gödel pairing function to  $R_{stage}$  obtain ordinals  $\alpha$  and  $\beta$ . By Proposition 22, calculate  $e := F_\tau^{-1}(\alpha)$  and  $z := F_\tau^{-1}(\beta)$ . We want to extend  $R_{init}$  in such a way that  $P_{e,z}$  will hold.

**Case 1:** There is an extension  $D_{init}$  of  $R_{init}$  such that there is a successful computation of  $e$  on input  $(x, z)$  using  $D_{init}$  as an oracle, where  $x$  is the  $<_\tau$ -least set for which  $D_{init}(x, z)$  is undefined. Note that our machine can decide this by using the oracle for the  $\text{SRM}^+$ -halting problem. Let  $y \in \{0, 1\}$  be the result of this computation. Set  $R_{init} := D_{init} \cup \{((x, z), 1 - y)\}$ . This ensure that  $e$  does not witness that  $D_z$  is computable in  $D^z$ .

**Case 2:** There is no such extension of  $R_{init}$ . This means that no matter how  $R_{init}$  is extended,  $e$  will not witness that  $D_z$  is computable in  $D^z$ . So we can set the value for the  $<_\tau$ -least  $x$  such that  $D(x, z)$  is undefined in an arbitrary way, so set  $R_{init} := R_{init} \cup \{((x, y), 0)\}$ .

Now note that  $Q_e$  holds automatically: if  $D$  was computable as witnessed by  $e$ , then, trivially,  $e$  witnesses that  $D_z$  is computable in  $D^z$  but we just ensured that this is not the case.

The program defined this way will eventually give rise to a completely defined predicate  $D$  on  $V \times V$ . The value of  $D(x, y)$  can be computed by running the procedure above until the value for  $(x, y)$  is known.  $\square$

Note that the program described in the proof above does not use any parameters and can thus be coded as a natural number.

**Remark 26.** In fact, Kleene and Post prove a stronger result which allows to locate  $D$  between any two Turing degrees. A similar result is possible here but we leave the proof to the interested reader as we do not need it.

**3.3. Constructible SRMs.** For our applications to the first-order logic of CZF, it will be important that we can express the predicate “ $D(x, y)$  holds” in a way that only uses the language of set theory without introducing an extra relation symbol into our language to refer to the global well-order. This

means that we have to circumvent referring to  $<_\tau$  as this is an extra symbol that cannot be defined in terms of a set-theoretic formula. Due to the following well-known fact, we will restrict our attention to constructible sets (for reference see, e.g., Jech [15, Theorem 13.18 & Lemma 13.19]):

**Fact 27.** *There is a  $\Sigma_1$ -definable well-ordering  $<_L$  of the constructible universe  $L$ .*

So if we restrict our attention to  $\text{SRM}^+$ s that work only on constructible sets, we can replace  $<_\tau$  with  $<_L$  in Definition 12. The resulting notion of SRM will be called *constructible*  $\text{SRM}^+$  and denoted, in short, by  $\text{SRM}_L^+$ . Note that all of the results obtained so far about  $\text{SRM}^+$ s can be relativised to  $L$  and thus transferred to  $\text{SRM}_L^+$ . In particular, we get the following versions of Lemma 17 and Theorem 25:

**Lemma 28.** *Let  $\varphi(\bar{x})$  be a  $\Delta_0$ -formula. There is an  $\text{SRM}_L$ -program  $p$  such that  $p(\ulcorner \varphi \urcorner, \bar{x}) = 1$  if  $L \models \varphi$  and  $p(\ulcorner \varphi \urcorner, \bar{x}) = 0$  if  $L \models \neg \varphi$ .*

**Corollary 29.** *There is a non- $\text{SRM}_L^+$ -computable set-theoretic predicate  $D(x, y)$ , expressible in the language of set theory, such that  $D_z$  is not  $\text{SRM}_L^+$ -computable in  $D^z$ .*

#### 4. REALISABILITY

We will now define a notion of realisability based on  $\text{SRM}^+$ s, and observe a few proof-theoretic consequences for CZF.

**Definition 30.** We define the realisability relation  $\Vdash$  recursively for an  $\text{SRM}_{(L)}^{(+),(O)}$   $r$  as follows:

- (i)  $r \Vdash a \in b$  if and only if  $a \in b$ ;
- (ii)  $r \Vdash a = b$  if and only if  $a = b$ ;
- (iii)  $r \Vdash \varphi_0 \wedge \varphi_1$  if and only if  $r(0) \Vdash \varphi_0$  and  $r(1) \Vdash \varphi_1$ ;
- (iv)  $r \Vdash \varphi_0 \vee \varphi_1$  if and only if  $r(1) \Vdash \varphi_{r(0)}$ ;
- (v)  $r \Vdash \varphi_0 \rightarrow \varphi_1$  if and only if whenever  $s \Vdash \varphi_0$ , then  $r(s) \Vdash \varphi_1$ ;
- (vi)  $r \Vdash \exists x \varphi(x)$  if and only if  $r(1) \Vdash \varphi(r(0))$ ;
- (vii)  $r \Vdash \forall x \varphi(x)$  if and only if  $r(a) \Vdash \varphi(a)$  for every set  $a$ .

We say that  $\varphi$  is SRM-realizable if and only if there is an SRM realising  $\varphi$ . Similarly, we say that  $\varphi$  is  $\text{SRM}^+$ -realizable if and only if there is an  $\text{SRM}^+$  realising  $\varphi$ ; and so for  $\text{SRM}^{+,O}$ ,  $\text{SRM}_L^+$ , and  $\text{SRM}_L^{+,O}$ .

This could be extended to infinitary languages as done by Carl et al. [3]. Analogously to (i) and (ii), one could give realisability semantics to the global well-order  $<_\tau$ .

**Theorem 31.**  $\text{SRM}_{(L)}^{(+),(O)}$ -realisability is sound for intuitionistic logic.

*Proof.* This is a standard argument and can be established, for example, by providing a realiser for every axiom in a Hilbert-style formalisation of **IQC** and showing that *modus ponens* is valid. The latter follows immediately from the definition of the realisability relation.  $\square$

**Lemma 32.** *Let  $\varphi(\bar{x})$  be a  $\Sigma_1$ -formula. Then there is some realiser  $r \Vdash \varphi(\bar{x})$  if and only if  $\mathbb{V} \models \varphi(\bar{x})$ .*

*Proof.* This is a straightforward induction on  $\Sigma_1$ -formulas. We will prove a more intricate version of this lemma below, see Lemma 45.  $\square$

**Theorem 33.** *The axioms (and schemes) of extensionality, pairing, union, infinity, collection,  $\in$ -induction, and  $\Delta_0$ -separation are SRM-realizable. The axiom of choice, AC, is SRM-realizable. The axioms of power set and strong collection are  $\text{SRM}^+$ -realizable. In conclusion, IKP + AC is SRM-realizable, and CZF + PowerSet + AC is  $\text{SRM}^+$ -realizable. Moreover, IKP + AC is  $\text{SRM}_L$ -realizable, and CZF + PowerSet + AC is  $\text{SRM}_L^+$ -realizable.*

*Proof.* It is straightforward to construct a realiser for the extensionality axiom. For the empty set axiom, let  $r$  be an SRM that returns the empty set on input 0 and the identity function on input 1. Then  $r(1) \Vdash \forall y (y \in r(0) \rightarrow \perp)$  because  $\not\vdash_w y \in \emptyset$  for all  $w \in P$  and  $y \in V$ . Hence,  $r \Vdash \exists x \forall y (y \notin x)$ . A realiser for the union axiom is an SRM  $r$  such that, for every  $a \in V$ ,  $r(a)(0) = \bigcup a$ , using Lemma 16,  $r(a)(1)(x)(0) = \text{id}$ , and  $r(a)(1)(x)(1) = \text{id}$  for every  $x$ . The infinity axiom is realised by an SRM  $r$  with  $r(0) = \omega$ ,  $r(1)(x)(0) = \text{id}$ , and  $r(1)(x)(1) = \text{id}$  for every  $x \in V$ . Using the power set operation provided by  $\text{SRM}^+$ -programs, it is straightforward to construct a realiser of the power set axiom. Note that the subset collection schema is a consequence of the power set axiom.

Let us consider  $\Delta_0$ -separation next, i.e. the schema consisting of

$$\forall x \exists y \forall z (z \in y \leftrightarrow z \in x \wedge \varphi(x)),$$

where  $\varphi(x)$  is a  $\Delta_0$ -formula. By combining Lemmas 28 and 32, we know that  $\Vdash \varphi(x)$  if and only if  $p(\ulcorner \varphi \urcorner, x) = 1$ , and  $p(\ulcorner \varphi \urcorner, x) = 0$  in case  $\not\vdash \varphi(x)$ . Hence, we can compute the witnessing set  $y$  by conducting a bounded search through  $x$  and collecting all  $z \in x$  such that  $p(\ulcorner \varphi \urcorner, z) = 1$ . It is then trivial to realise  $\forall z (z \in y \leftrightarrow z \in x \wedge \varphi(x))$  because  $\varphi$  is a  $\Delta_0$ -formula.

Consider the schema of  $\in$ -induction next:

$$\forall x (\forall y \in x \varphi(y) \rightarrow \varphi(x)) \rightarrow \forall x \varphi(x).$$

An SRM  $r$  is a realiser for this if and only if, if  $s \Vdash \forall x (\forall y \in x \varphi(y) \rightarrow \varphi(x))$ , then  $r(s) \Vdash \forall x \varphi(x)$ . Now, in this situation,  $s$  allows us to iteratively construct realisers for every  $x \in V$  by successively building realisers for every  $V_\alpha$ . Hence, given  $x \in V$ , we just compute realisers until we reach  $x$  and then output the realiser for  $\varphi(x)$ .

Next, we consider the strong collection schema:

$$\forall x [(\forall y \in x \exists z \varphi(y, z)) \rightarrow \exists w (\forall y \in x \exists z \in w \varphi(y, z) \wedge \forall z \in w \exists y \in x \varphi(y, z))],$$

for all formulas  $\varphi(x, y)$  for which  $w$  is not free. Given  $x \in V$ , let  $r(x)(s)$ , for  $s \Vdash \forall y \in x \exists z \varphi(y, z)$ , be an SRM that computes a set consisting of all  $s(y)(0)$  for every  $y \in x$ , and returns this set on input 0. Using  $s$ , it is straightforward to construct a realiser  $r(x)(s)(1) \Vdash \forall y \in x \exists z \in r(x)(s)(0) \varphi(y, z) \wedge \forall z \in r(x)(s)(0) \exists y \in x \varphi(y, z)$ .

Finally, consider the axiom of choice,

$$\forall x ((\forall y \in x \exists z z \in y) \rightarrow \exists f \forall y \in x f(y) \in y).$$

This axiom states that whenever  $x$  consists of non-empty sets, then there is a choice function  $f$  on  $x$ . Using Lemma 16, it is straightforward to construct an SRM that computes such a choice function: for every element of  $y \in x$ , use the TAKE-operation to obtain some  $z \in y$ . Then add  $(x, y)$  to the register in which we build the choice function.

The corresponding results for  $\text{SRM}_L$  and  $\text{SRM}_L^+$  are obtained through relativisation and absoluteness properties (or by observing that the exact same realisers still do the job).  $\square$

It turns out that IZF is not  $\text{SRM}^+$ -realisable.

**Theorem 34.** *There is an instance of the separation axiom that is not  $\text{SRM}^+$ -realisable. In conclusion, IZF is not  $\text{SRM}^+$ -realisable.*

*Proof.* Consider the predicate  $H(x, y)$  expressing that “ $x$  is an  $\text{SRM}^+$  that halts on input  $y$ ”. One can easily construct a formula  $\varphi(x, y)$  such that  $\varphi(x, y)$  is realised if and only if  $H(x, y)$  is true (see also the proof of Lemma 48 for a similar argument). Then let  $s$  be a realiser of the following instance of the separation axiom:

$$\forall x \forall y \forall z \exists w \forall u (u \in w \leftrightarrow (u \in z \wedge \varphi(x, y))).$$

We can then construct an SRM  $r$  that does the following. Given  $x$  and  $y$ , compute  $w := s(x)(y)(1)(0)$  and return the result. By construction,  $r(x, y) = 1$  just in case  $H(x, y)$  holds, and  $r(x, y) = 0$  otherwise.

So  $r$  is an  $\text{SRM}^+$  solving the  $\text{SRM}^+$  halting problem but the usual diagonal argument shows that this is impossible.  $\square$

In fact, we have just seen that  $\text{CZF} + \text{PowerSet}$  is  $\text{SRM}^+$ -realisable. The following proposition shows that we cannot be more fine-grained: if there is an SRM realising the exponentiation axiom (possibly using an oracle), then we can already compute power sets. Recall that the axiom of exponentiation is a consequence of subset collection (Fact 2).

**Proposition 35.** *Let  $r$  be an SRM, possibly using an oracle, such that  $r$  realises the axiom of exponentiation, then there is an SRM, using  $r$  as an oracle, that computes power sets.*

*Proof.* Let  $r$  be a realiser of the axiom of exponentiation:

$$\forall x \forall y \exists z \forall f (f \in z \leftrightarrow \text{“}f \text{ is a function from } x \text{ to } y\text{”}),$$

where “ $f$  is a function from  $x$  to  $y$ ” is expressed as a  $\Delta_0$ -formula. Then, given a set  $a$ , the set  $b := r(a)(\{0, 1\})(0)$  contains all  $f$  for which there is a realiser of “ $f$  is a function from  $x$  to  $y$ ”. As this is a  $\Delta_0$ -formula, Lemma 32 implies that  $b$  consists of all functions from  $a$  to 2. It is now easy to compute the power set of  $a$  as follows: for each element  $f$  of  $b$ , compute the set consisting of exactly those  $x \in a$  for which  $f(x) = 1$ . This results in the power set of  $a$  because each subset of  $a$  gives rise to its characteristic function contained in  $b$ .  $\square$

Our realisability semantics also allow to give an upper bound for  $\Pi_2$ -formulas provable in CZF in terms of the computable strength of  $\text{SRM}^+$ .

**Theorem 36.** *Let  $\varphi$  be a  $\Sigma_1$ -formula. If  $\text{CZF} \vdash \forall x \exists y \varphi(x, y)$ , then there is an  $\text{SRM}^+$   $p$  such that  $\mathbb{V} \vDash \varphi(x, p(x))$ .*

*Proof.* If  $\text{CZF} \vdash \forall x \exists y \varphi(x, y)$ , then, by Theorem 33, there exists an  $\text{SRM}^+$   $r \Vdash \forall x \exists y \varphi(x, y)$ . Take  $p(x) := r(x)(0)$ . Then, for all  $x$ ,  $\varphi(x, p(x))$  is realisable. As  $\varphi$  is a  $\Sigma_1$ -formula, it follows with Lemma 32 that  $\mathbb{V} \vDash \varphi(x, p(x))$ .  $\square$

Finally, we can use  $\text{SRM}^+$ -realisability to easily generalise a theorem of Carl, Galeotti and Passmann [3, Theorem 56].

**Theorem 37.** *The propositional admissible rules of CZF are exactly the propositional admissible rules of intuitionistic logic.*

*Proof.* Using the fact that CZF is  $\text{SRM}^+$ -realisable, we can prove this with glued realisability using Theorem 10; almost exactly as we did in earlier joint work with Carl et al. [3].  $\square$

## 5. BETH REALISABILITY MODELS

**5.1. Fallible Beth models.** In this section, we will make use of so-called *fallible* Beth models because these satisfy a particular handy universal model theorem.

**Definition 38.** A *fallible Beth frame*  $(P, U)$  consists of a tree  $P$  and an upwards closed set  $U \subseteq P$  such that if every path through  $p \in P$  meets  $U$ , then  $p \in U$ .

**Definition 39** (Fallible Beth model). A *fallible Beth model*  $(P, U, D, I)$  for first-order logic consists of a fallible Beth tree  $(P, U)$ , domains  $D_p$  for  $p \in P$ , and an interpretation  $I_p$  of the language of first-order logic for each  $p \in P$  such that:

- (i)  $I_v(R) \subseteq I_w(R)$  for all  $w \geq v$ ,
- (ii)  $I_v(R) = D_v$  for all  $v \in U$ , and,
- (iii) if  $R$  is an  $n$ -ary relation symbol,  $\bar{x} \in D_v^n$  and on every path through  $v$  there is some  $w$  such that  $\bar{x} \in I_w(R)$ , then  $\bar{x} \in I_v(R)$ .

A *Beth model* is a fallible Beth model where  $U = \emptyset$ . If  $p \in P$ , then a *bar for  $p$*  is a set  $B \subseteq P$  such that every path through  $p$  meets  $B$ . A  *$U$ -bar for  $p$*  is a set  $B \subseteq P$  such that  $B \cup U$  is a bar for  $p$ .

**Definition 40.** Let  $(P, U, D, I)$  be a fallible Beth model and  $v \in P$ . We define by recursion on sentences in the language of propositional logic:

- (i)  $v \Vdash \perp$  if and only if  $v \in U$ ;
- (ii)  $v \Vdash R(d_1, \dots, d_n)$  if and only if  $(d_1, \dots, d_n) \in I_v(R)$ ;
- (iii)  $v \Vdash \varphi \wedge \psi$  if and only if  $v \Vdash \varphi$  and  $v \Vdash \psi$ ;
- (iv)  $v \Vdash \varphi \vee \psi$  if and only if there is a bar  $B$  for  $v$  such that for every  $w \in B$ ,  $w \Vdash \varphi$  or  $w \Vdash \psi$ ;
- (v)  $v \Vdash \varphi \rightarrow \psi$  if and only if for every  $w \geq v$ , if  $w \Vdash \varphi$ , then  $w \Vdash \psi$ ;
- (vi)  $v \Vdash \exists x \varphi(x)$  if and only if there is a bar  $B$  for  $v$  such that for all  $w \in B$ , there is some  $a \in D_w$  with  $w \Vdash \varphi(a)$ ;
- (vii)  $v \Vdash \forall x \varphi(x)$  if and only if for every  $w \geq v$  and  $a \in D_w$ ,  $w \Vdash \varphi(a)$ .

Note that, by this definition, if  $v \in U$ , then  $v$  forces every formula trivially, i.e. the relation  $\Vdash$  trivialises in  $U$ . By definition of  $U$ , it follows that if  $v \notin U$  and  $B$  is a  $U$ -bar for  $v$ , then  $B \setminus U$  is non-empty. The following result of Troelstra and van Dalen [20, Chapter 13, Remark 2.6 and Theorem 2.8] will be a crucial ingredient of our proof.

**Theorem 41.** *Let  $J$  be a recursively enumerable theory in intuitionistic first-order logic. Then there is a fallible Beth model  $\mathcal{B}_J$  with constant domain  $\omega$ , based on the full binary tree of height  $\omega$ , such that  $\mathcal{B} \Vdash \varphi$  if and only if  $J \vdash \varphi$  for every sentence  $\varphi$  of first-order logic.*

In what follows, we will refer to  $\mathcal{B}_J$  as the *universal Beth model for  $J$* .

**5.2. Beth realisability models.** Inspired by van Oosten [22], we now combine our notion of  $\text{SRM}_L^{+,O}$ -realisability with Beth semantics. To make coherent use of oracles, we need the following definition.

**Definition 42.** Let  $P$  be a partial order. A *system of oracles*  $(O_v)_{v \in P}$  consists of partial class functions  $O_v : V \rightarrow V$  such that, for all  $w \geq v$ , we have that  $\text{dom}(O_v) \subseteq \text{dom}(O_w)$  and  $O_v(x) = O_w(x)$  for all  $x \in \text{dom}(O_v)$ .

From now on, we write  $r^v(x)$  to denote the output of computing  $r$  on input  $x$  when using the oracles at  $v$ . If we write  $r(x)$ , then we mean the output (if it exists) of  $r$  run with empty oracles.

**Definition 43.** Let  $(P, U)$  be a fallible Beth frame,  $(O_v)_{v \in P}$  be a system of oracles. We define recursively for sentences  $\varphi$  and  $\psi$  in the language of set theory, for  $a, b \in L$ ,  $v \in P$  and  $r \in S_v$ :

- (i)  $r \Vdash_v \perp$  if and only if  $v \in U$ ;
- (ii)  $r \Vdash_v a = b$  if and only if  $a = b$  or  $v \in U$ ;
- (iii)  $r \Vdash_v a \in b$  if and only if  $a \in b$  or  $v \in U$ ;
- (iv)  $r \Vdash_v \varphi \wedge \psi$  if and only if  $r^v(0) \Vdash_v \varphi$  and  $r^v(1) \Vdash_v \psi$ ;
- (v)  $r \Vdash_v \varphi \vee \psi$  if and only if there is a  $U$ -bar  $B$  for  $v$  such that, for every  $w \in B$ , either  $r^w(0) = 0$  and  $r^w(1) \Vdash_w \varphi$ , or  $r^w(0) = 1$  and  $r^w(1) \Vdash_w \psi$ ;
- (vi)  $r \Vdash_v \varphi \rightarrow \psi$  if and only if for every  $w \geq v$ , if  $s \Vdash_w \varphi$ , then  $r^w(s) \Vdash_w \psi$ ;
- (vii)  $r \Vdash_v \exists x \varphi(x)$  if and only if there is a  $U$ -bar  $B$  for  $v$  such that for all  $w \in B$ ,  $p^w(1) \Vdash_w \varphi(p^w(0))$ ;
- (viii)  $r \Vdash_v \forall x \varphi(x)$  if and only if for every  $a$ ,  $r^v(a) \Vdash_v \varphi(a)$ .

If  $v \in U$ , then  $r \Vdash_v \varphi$  for every realiser  $r$  and set-theoretic sentence  $\varphi$ . The following is established by a standard argument.

**Theorem 44.** *Beth-realisability is sound for the axioms and rules of intuitionistic first-order logic.*

**Lemma 45.** *Let  $\varphi(\bar{x})$  be a  $\Sigma_1$ -formula and  $v \notin U$ . Then there is some realiser  $r \Vdash_v \varphi(\bar{x})$  if and only if  $L \vDash \varphi(\bar{x})$ .*

*Proof.* As  $v \notin U$ , we know that any  $U$ -bar  $B$  for  $v$  satisfies  $B \setminus B \neq \emptyset$ . We prove this by induction. The cases for equality and set-membership are trivial.

Suppose that  $\Vdash_v \varphi(\bar{a}) \wedge \psi(\bar{a})$ . By definition, this is equivalent to  $\Vdash_v \varphi(\bar{a})$  and  $\Vdash_v \psi(\bar{a})$ . Applying the induction hypothesis, this holds if and only if  $L \vDash \varphi(\bar{a})$  and  $L \vDash \psi(\bar{a})$ . This is, of course, equivalent to  $L \vDash \varphi(\bar{a}) \wedge \psi(\bar{a})$ .

For disjunction, first suppose that  $r \Vdash_v \varphi(\bar{a}) \vee \psi(\bar{a})$ . By definition, this means that there is a  $U$ -bar  $B$  for  $v$  such that for all  $w \in B$  we have either  $r^w(0) = 0$  and  $r^w(1) \Vdash_w \varphi(\bar{a})$ , or  $r^w(0) = 1$  and  $r^w(1) \Vdash_w \psi(\bar{a})$ . Recall that  $B \setminus U$  is non-empty. So take any  $w \in B \setminus U$ , then  $\Vdash_w \varphi(\bar{a})$  or  $\Vdash_w \psi(\bar{a})$ . By induction hypothesis,  $L \vDash \varphi(\bar{a})$  or  $L \vDash \psi(\bar{a})$ . Hence  $L \vDash \varphi(\bar{a}) \vee \psi(\bar{a})$ . Conversely, assume that  $L \vDash \varphi(\bar{a}) \vee \psi(\bar{a})$ . Then  $L \vDash \varphi(\bar{a})$  or  $L \vDash \psi(\bar{a})$ . It follows, by induction hypothesis, that  $\Vdash_v \varphi(\bar{a})$  or  $\Vdash_v \psi(\bar{a})$ , but then  $\Vdash_v \varphi(\bar{a}) \vee \psi(\bar{a})$ .

For implication, assume that  $r \Vdash_v \varphi \rightarrow \psi$ . If  $L \not\vDash \varphi$ , then trivially  $L \vDash \varphi \rightarrow \psi$ . So assume that  $L \vDash \varphi$ . By induction hypothesis, we know that there is a realiser  $s \Vdash_v \varphi$ . Hence,  $r(s) \Vdash_v \psi$ . Applying the induction hypothesis once more, we get  $L \vDash \psi$ . Conversely, assume that  $L \vDash \varphi \rightarrow \psi$ . If  $L \not\vDash \varphi$ , then, by induction hypothesis,  $\not\vDash_w \varphi$  for all  $w \geq v$ . So  $\Vdash_v \varphi \rightarrow \psi$  holds trivially. If  $L \vDash \varphi$ , then  $L \vDash \psi$ . So, by induction hypothesis, there is a realiser  $s \Vdash_v \psi$ . Hence, a realiser for  $\varphi \rightarrow \psi$  is the SRM  $p$  that returns  $s$  on any input.

For bounded universal quantification, assume that  $L \vDash \forall x \in y \varphi(x)$ . Then, by induction hypothesis, we can find a function  $f : y \rightarrow L$  such that  $f(z) \Vdash_v \varphi(z)$ . Let  $p$  be the SRM with parameter  $f$  that returns  $f(z)$  on input  $z$ . Then  $p \Vdash_v \forall x \in y \varphi(x)$ . Conversely, note that  $\Vdash_v \forall x \in y \varphi(x)$  entails that  $\Vdash_v \varphi(x)$  for every  $x \in y$ . An application of the induction hypothesis yields  $L \vDash \forall x \in y \varphi(x)$ .

For unbounded existential quantification, assume that  $L \vDash \exists x \varphi(x)$ . Then there is some  $a \in L$  such that  $L \vDash \varphi(a)$ . By induction hypothesis, there is a realiser  $s \Vdash_v \varphi(a)$ . Let  $p$  be an SRM such that  $p(1) = s$  and  $p(0) = a$  (by using, if necessary, parameter  $a$ ). Then  $p \Vdash_v \exists x \varphi(x)$ . Conversely, if  $p \Vdash_v \exists x \varphi(x)$ , then there is a  $U$ -bar  $B$  for  $v$  such that for all  $w \in B$ ,  $p^w(1) \Vdash_w \varphi(p^w(0))$ . Take any  $w \in B$  and the induction hypothesis implies that  $L \vDash \varphi(p^w(0))$ , and, hence,  $L \vDash \exists x \varphi(x)$ .  $\square$

**Theorem 46.** *The Beth realisability model satisfies CZF + PowerSet + AC.*

*Proof.* Realisers for the axioms and schemas can be constructed (almost exactly) as in the proof of Theorem 33. For the case of  $\Delta_0$ -separation, observe that the use of Lemma 32 has to be replaced with Lemma 45. (Note that we only need to consider the cases for  $v \notin U$ , as the other case is trivial.)  $\square$

**5.3. Constructing a model for a given logic.** The goal of this section is to construct a Beth-realisation model that matches the truth in the universal Beth model  $\mathcal{B}_J = (P, U, D, I)$  for a given logic  $J$ . To begin with, we define the two systems of oracles  $(F_v)_{v \in P}$  and  $(G_v)_{v \in P}$ . If  $a$  is a set, let  $\text{rank}_\omega(a)$  be the unique natural number such that  $\text{rank}(a) = \alpha + \text{rank}_\omega(a)$  for a maximal (possibly 0) limit ordinal  $\alpha$ .

(i) We define  $F_v : V \rightarrow V$  by recursion on  $v \in P$  ( $P$  being the binary tree of height  $\omega$ ) such that:

$$F_v(n, y) = \begin{cases} x, & \text{if } F_w(n, y) = x \text{ for some } w \leq v, \\ a, & \text{if } n = \ulcorner \exists a \varphi(a, \bar{y}) \urcorner \text{ and } a \in \omega \text{ least with } \mathcal{B}_J, v \Vdash \varphi(a, \bar{y}), \\ i, & \text{if } n = \ulcorner \varphi_0 \vee \varphi_1 \urcorner \text{ and } i \text{ least such that } \mathcal{B}_J, v \Vdash \varphi_i, \\ \text{undefined,} & \text{otherwise.} \end{cases}$$

(ii) We define  $G_v : V \rightarrow V$  such that:

$$G_v(y, x) = \begin{cases} 1, & \text{if } y = \langle i, y_0, \dots, y_n \rangle; \mathcal{B}_J, v \Vdash A_i(\text{rank}_\omega(y_0), \dots, \text{rank}_\omega(y_n)); \text{ and } D(x, y) = 1, \\ 0, & \text{if } y = \langle i, y_0, \dots, y_n \rangle; \mathcal{B}_J, v \Vdash A_i(\text{rank}_\omega(y_0), \dots, \text{rank}_\omega(y_n)); \text{ and } D(x, y) = 0, \\ \text{undefined,} & \text{otherwise.} \end{cases}$$

**Lemma 47.** *The sequences  $(F_v)_{v \in P}$  and  $(G_v)_{v \in P}$  form systems of oracles.*  $\square$

From now on, we consider the Beth-realisation based on these systems of oracles. Note that, without loss of generality, we can combine two systems of oracles into one by, e.g. taking  $O(\langle 0, x \rangle) = F(x)$  and  $O(\langle 1, x \rangle) = G(x)$ .

**Lemma 48.** *Let  $v \notin U$ . There is a negative formula  $\psi(x, y)$  such that there is a realiser  $r \Vdash_v \psi(x, y)$  is realised if and only if  $D(x, y) = 1$ .*

*Proof.* Except for the power set case, every clause of the definition of successful computation (Definition 12), adapted for  $\text{SRM}_L^+$ , can be written as a  $\Sigma_1$ -formula. For the TAKE-operation, recall that  $<_L$  is  $\Sigma_1$ -definable. Now consider the predicate “ $x = \mathcal{P}(y)$ ” which is needed for the POW-operation and can be formalised as “ $\forall z(z \in x \leftrightarrow \forall w \in z w \in y)$ ”. As the part in brackets is a  $\Delta_0$ -formula, it follows with Lemma 45 that this predicate is realised if and only if it is true. Note, in particular, that also the successor case for the halting problem oracle is realised if and only if it is true in L. This is because the existence of a successful computation is absolute, as we have just seen.

Applying Lemma 45 once more, these observations show that we can construct a formula  $\chi$  expressing “ $c$  is a successful computation of  $D(x, y)$  with result 0” such that  $\chi(c, x, y)$  is realised if and only if it is true in L. Take  $\psi(x, y)$  to be  $\neg \exists c \chi(c, x, y)$ . It follows that  $\psi(x, y)$  is realised if and only if  $D(x, y) = 1$  because  $D$  halts on every input with either 0 or 1 as output.  $\square$

**Lemma 49.** *Let  $P_i(z_0, \dots, z_n)$  be a predicate in the language of first-order logic. There is a set-theoretic formula  $\varphi_i(z_0, \dots, z_n)$  such that, for all  $a_0, \dots, a_n \in L$ , there is some  $r \Vdash_v \varphi_i(a_0, \dots, a_n)$  if and only if  $\mathcal{B}_J, v \Vdash P_i(\text{rank}_\omega(a_0), \dots, \text{rank}_\omega(a_n))$ .*

*Proof.* Let  $\psi$  be the negative formula from Lemma 48 expressing that  $D(x, y) = 1$ . As  $\psi$  is negative, we know that, for every  $v$ , either  $\Vdash_v \psi$  or  $\Vdash_v \neg \psi$ . Then take:

$$\varphi_i(y_0, \dots, y_n) := \forall x (\psi(x, \langle i, y_0, \dots, y_n \rangle) \vee \neg \psi(x, \langle i, y_0, \dots, y_n \rangle)).$$

Suppose there was a realiser  $r \Vdash_v \varphi_i(a_0, \dots, a_n)$  but  $\mathcal{B}_J, v \not\Vdash P_i(\text{rank}_\omega(a_0), \dots, \text{rank}_\omega(a_n))$ . In this situation, we can decide  $D_x(\bar{y})$  from  $r$ : if  $r(\bar{y})$  returns a realiser for  $\psi_i(\bar{y})$ , then  $D_x(\bar{y}) = 1$ ; if  $r(\bar{y})$  returns a realiser for  $\neg \psi_i(\bar{y})$ , then  $D_x(\bar{y}) = 0$ . However, by our assumption,  $G_v(\bar{y}, x)$  is undefined for all  $x$ . This means that  $r$  cannot use the oracle on  $\bar{y}$  (as otherwise, the computation would not be successful). Hence  $r$  witnesses that  $D_x$  is computable in  $D^x$ . A contradiction to Corollary 29. (Note that  $F$  does not matter here because the information contained in  $F$  could be saved in a set-sized parameter.)

Conversely, assume that  $\mathcal{B}_J, v \Vdash P_i(\text{rank}_\omega(y_0), \dots, \text{rank}_\omega(y_n))$ . By definition of  $G$ , it follows that  $G_v(\bar{y}, x)$  is defined for all  $x \in L$ . Hence, a realiser for  $\psi_i$  can be easily obtained by querying the oracle  $G(\bar{y}, x)$ . If the result is 1, then return a realiser of  $\psi_i(y_0, \dots, y_n)$ . If the result is 0, then return a realiser of  $\neg \psi_i(y_0, \dots, y_n)$ . In both cases, the computation of a realiser is trivial because the formulas are negative.  $\square$

Let  $\tau(P_i) = \varphi_i$  and extend  $\tau$  to a translation of all formulas in the language of first-order logic in the obvious way. Note that the formulas  $\varphi_i$  are  $\Pi_3$ -formulas.

**Lemma 50.** *Let  $A(\bar{y})$  be a formula in the language of first-order logic. There is a realiser  $r \Vdash_v A^\tau(\bar{a})$  if and only if  $\mathcal{B}_J, v \Vdash A(\text{rank}_\omega(a_0), \dots, \text{rank}_\omega(a_n))$ .*

*Proof.* We begin with the forward direction. The base case is done in Lemma 49.

For conjunction,  $A \wedge B$ , note that  $r \Vdash_v A^\tau \wedge B^\tau$  entails  $r \Vdash_v A^\tau$  and  $r \Vdash_v B^\tau$ . Hence, by induction hypothesis,  $\mathcal{B}_J, v \Vdash A$  and  $\mathcal{B}_J, v \Vdash B$ . So,  $\mathcal{B}_J, v \Vdash A \wedge B$ .

For disjunction,  $A \vee B$ , we have that  $r \Vdash_v A^\tau \vee B^\tau$  entails that there is a  $U$ -bar  $B$  for  $v$  such that for every  $w \in B$ , either  $r^w(0) = 0$  and  $r^w(1) \Vdash_w A^\tau$  or  $r^w(0) = 1$  and  $r^w(1) \Vdash_w B^\tau$ . By induction hypothesis, this means that there is a  $U$ -bar  $B$  for  $v$  such that for every  $w \in B$ ,  $w \Vdash A$  or  $w \Vdash B$ . Hence  $v \Vdash A \vee B$ .

The case for implication is similar, and the cases for universal and existential quantification follow with the induction hypothesis.

We will prove the backwards direction by induction and simultaneously constructing a realiser  $r_A$  for each formula  $A$ . The base case was established in Lemma 49.

For conjunction  $A \wedge B$ , take  $r_{A \wedge B}(0) = r_A$  and  $r_{A \wedge B}(1) = r_B$ . An application of the induction hypothesis shows that  $r_{A \wedge B}$  does the job.

For implication  $A \rightarrow B$ , we know by our induction hypothesis that  $r_B \Vdash_w B$  if and only if  $w \Vdash B$  for all  $w \geq v$ . Hence, let  $r_{A \rightarrow B}(s) = r_B$ . It is straightforward to check that this does the job.

For disjunction, define  $r_{A \vee B}$  to be the SRM that proceeds as follows: on input 0, it calls the oracle  $F$  on  $(\ulcorner A \vee B^\urcorner, \emptyset)$  and returns this value. On input 1, it returns  $r_A$  if  $F(\ulcorner A \vee B^\urcorner, \emptyset) = 0$  and it returns  $r_B$  otherwise. To see that this machine does the job, assume that  $U$ -bar  $B$  such that for every  $w \in B$ ,  $w \Vdash A$  or  $w \Vdash B$ . Equivalently, by induction hypothesis, for every  $w \in B$ ,  $r_A \Vdash_w A$  or  $r_B \Vdash_w B$ . By definition of  $r_{A \vee B}$ , it follows that  $r_{A \vee B}^w(0) = r_A$  or  $r_{A \vee B}^w(0) = r_B$ . Hence,  $r_{A \vee B} \Vdash_w A \vee B$ .

For existential quantification, define  $r_{\exists x A(x,y)}$  to be the function that returns calls the oracle  $F$  on input  $(\ulcorner \exists x A(x,y)^\urcorner, y)$ . Let the result of this query be  $n \in \omega$ . Then  $r_{\exists x A(x,y)}(0) = n$  and  $r_{\exists x A(x,y)}(1) = r_{A(n,y)}$ . Note that there are, at most,  $\omega$ -many different realisers  $r_{A(n,y)}$  that need to be returned. So, if necessary, these can be stored in a set-sized parameter. It is straightforward to check that  $r_{\exists x A(x,y)}$  does the job, similar to the case of disjunction.

For universal quantification, define  $r_{\forall x A(x,y)}$  to be the function that returns  $r_{A(x,y)}(x,y)$ .  $\square$

If  $J$  is a set of formulas in first-order logic, we write  $J^\tau$  for the image of  $J$  under  $\tau$  (i.e.  $J^\tau = \tau[J]$ ).

**Theorem 51.** *Let  $J$  be a recursively enumerable theory in intuitionistic first-order logic, and  $T \subseteq \text{CZF} + \text{PowerSet} + \text{AC}$ . Then  $T + J^\tau \vdash A^\tau$  if and only if  $J \vdash_{\text{IQC}} A$ .*

*Proof.* The backwards direction is straightforward with the soundness of the Beth realisability model. For the forward direction, assume that  $J \not\vdash A$ . Then, by Theorem 41, we know that  $\mathcal{B}_J \not\vdash A$ . In this situation, Lemma 50 implies that there is no realiser of  $A^\tau$ . But the same lemma implies that  $B^\tau$  is realised for every  $B \in J$ . Hence,  $T + J^\tau \not\vdash A^\tau$ .  $\square$

The following corollary follows immediately by taking  $J = \emptyset$ .

**Corollary 52.** *Let  $T \subseteq \text{CZF} + \text{PowerSet} + \text{AC}$  be a set theory. Then the first-order logic of  $T$  is intuitionistic first-order logic,  $\text{QL}(T) = \text{IQC}$ . In particular,  $\text{QL}(\text{CZF}) = \text{IQC}$ .*

**Remark 53.** Rathjen [19] points out that “the combination of CZF and the general axiom of choice has no constructive justification in Martin-Löf type theory”. In contrast, our results show that the combination of CZF and the axiom of choice is innocent *on a logical level* in that adding the axiom of choice does not result in an increase of logical strength:  $\text{QL}(\text{CZF} + \text{AC}) = \text{QL}(\text{CZF}) = \text{IQC}$ . Note, of course, that the axiom of choice entails excluded middle for  $\Delta_0$ -formulas in the context of CZF.

**Acknowledgements.** I would like to thank Merlin Carl, Lorenzo Galeotti, Benedikt Löwe, Benno van den Berg and Ned Wontner for helpful discussions.

**Funding.** This research was supported by a doctoral scholarship of the *Studienstiftung des deutschen Volkes* (German Academic Scholarship Foundation).

## REFERENCES

- [1] Peter Aczel and Michael Rathjen. Notes on constructive set theory, 2001.
- [2] Merlin Carl. *Ordinal computability*, volume 9 of *De Gruyter Series in Logic and its Applications*. De Gruyter, Berlin, 2020. ISBN 978-3-11-049562-1; 978-3-11-049615-4; 978-3-11-049291-0. doi: 10.1515/9783110496154. URL <https://doi.org/10.1515/9783110496154>. An introduction to infinitary machines.
- [3] Merlin Carl, Lorenzo Galeotti, and Robert Passmann. Realisability for infinitary intuitionistic set theory, 2020.
- [4] Dick de Jongh. The maximality of the intuitionistic predicate calculus with respect to heyting’s arithmetic. Unpublished article with abstract appearing in [5], 1968.
- [5] Dick de Jongh. The maximality of the intuitionistic predicate calculus with respect to Heyting’s arithmetic. *The Journal of Symbolic Logic*, 35(4):606, 1970.
- [6] Dick de Jongh, Rineke Verbrugge, and Albert Visser. Intermediate logics and the de Jongh property. *Archive for Mathematical Logic*, 50(1):197–213, Feb 2011.
- [7] Radu Diaconescu. Axiom of choice and complementation. *Proceedings of the American Mathematical Society*, 51:176–178, 1975. ISSN 0002-9939. doi: 10.2307/2039868. URL <https://doi-org.proxy.uba.uva.nl:2443/10.2307/2039868>.
- [8] Abraham Adolf Fraenkel, Yehoshua Bar-Hillel, and Azriel Levy. *Foundations of set theory*. Elsevier, 1973.
- [9] Harvey M. Friedman and Andrej Ščedrov. On the quantificational logic of intuitionistic set theory. *Mathematical Proceedings of the Cambridge Philosophical Society*, 99(1):5–10, 1986. ISSN 0305-0041. doi: 10.1017/S0305004100063854. URL <https://doi.org/10.1017/S0305004100063854>.
- [10] N Goodman and J Myhill. Choice implies excluded middle. *Mathematical Logic Quarterly*, 24 (25-30):461–461, 1978.
- [11] Rosalie Iemhoff. On the admissible rules of intuitionistic propositional logic. *The Journal of Symbolic Logic*, 66(1):281–294, 2001. ISSN 00224812. URL <http://www.jstor.org/stable/2694922>.
- [12] Rosalie Iemhoff. Intermediate logics and Visser’s rules. *Notre Dame J. Formal Logic*, 46(1):65–81, 01 2005. doi: 10.1305/ndjfl/1107220674. URL <https://doi.org/10.1305/ndjfl/1107220674>.
- [13] Rosalie Iemhoff and Robert Passmann. Notes on admissible rules for constructive set theories. Draft, 2019.
- [14] Rosalie Iemhoff and Robert Passmann. Logics of intuitionistic Kripke-Platek set theory. *Ann. Pure Appl. Logic*, 172(10):Paper No. 103014, 22, 2021. ISSN 0168-0072. doi: 10.1016/j.apal.2021.103014. URL <https://doi.org/10.1016/j.apal.2021.103014>.
- [15] Thomas Jech. *Set theory*. Springer Monographs in Mathematics. Springer-Verlag, Berlin, 2003. ISBN 3-540-44085-2. The third millennium edition, revised and expanded.
- [16] S. C. Kleene and Emil L. Post. The upper semi-lattice of degrees of recursive unsolvability. *Ann. of Math. (2)*, 59:379–407, 1954. ISSN 0003-486X. doi: 10.2307/1969708. URL <https://doi.org/10.2307/1969708>.
- [17] Daniel Leivant. *Absoluteness of Intuitionistic Logic*, volume 13 of *ILLC Historical Dissertations Series (HDS)*. Institute for Logic, Language and Computation, University of Amsterdam, 1979.
- [18] Robert Passmann. De Jongh’s theorem for intuitionistic Zermelo-Fraenkel set theory. In Maribel Fernández and Anca Muscholl, editors, *28th EACSL Annual Conference on Computer Science Logic, CSL 2020, January 13-16, 2020, Barcelona, Spain*, volume 152 of *LIPICs*, pages 33:1–33:16. Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 2020. doi: 10.4230/LIPICs.CSL.2020.33. URL <https://doi.org/10.4230/LIPICs.CSL.2020.33>.

- [19] Michael Rathjen. Choice principles in constructive and classical set theories. In *Logic Colloquium*, volume 2, pages 299–326. Cambridge University Press, 2002.
- [20] A. S. Troelstra and D. van Dalen. *Constructivism in mathematics. Vol. II*, volume 123 of *Studies in Logic and the Foundations of Mathematics*. North-Holland Publishing Co., Amsterdam, 1988. ISBN 0-444-70358-6. An introduction.
- [21] Benno van den Berg and Ieke Moerdijk. Derived rules for predicative set theory: an application of sheaves. *Annals of pure and applied logic*, 163(10):1367–1383, 2012.
- [22] Jaap van Oosten. A semantical proof of de Jongh’s theorem. *Arch. Math. Logic*, 31(2):105–114, 1991. ISSN 0933-5846. doi: 10.1007/BF01387763. URL <https://doi.org/10.1007/BF01387763>.
- [23] Albert Visser. Rules and arithmetics. *Notre Dame J. Formal Logic*, 40(1):116–140, 1999. ISSN 0029-4527. doi: 10.1305/ndjfl/1039096308. URL <https://doi.org/10.1305/ndjfl/1039096308>. Special issue in honor and memory of George S. Boolos (Notre Dame, IN, 1998).

INSTITUTE FOR LOGIC, LANGUAGE AND COMPUTATION, FACULTY OF SCIENCE, UNIVERSITY OF AMSTERDAM, P.O. BOX 94242, 1090 GE AMSTERDAM, THE NETHERLANDS

*Email address:* `r.passmann@uva.nl`