

A Survey of Robot Manipulation in Contact

Markku Suomalainen^{1*}, Yiannis Karayiannidis² and Ville Kyrki³ ^{*†‡§}

December 6, 2021

Abstract

In this survey we present the the current status on robots performing manipulation tasks that require varying contact with the environment, such that the robot must either implicitly or explicitly control the contact force with the environment to complete the task. Robots can perform more and more manipulation tasks that are still done by humans, and there is a growing number of publications on the topics of 1) performing tasks that always require contact and 2) mitigating uncertainty by leveraging the environment in tasks that, under perfect information, could be performed without contact. The recent trends have seen robots perform tasks earlier left for humans, such as massage, and in the classical tasks, such as peg-in-hole, there is more efficient generalization to other similar tasks, better error tolerance and faster planning or learning of the tasks. Thus, in this survey we cover the current stage of robots performing such tasks, starting from surveying all the different in-contact tasks robots can perform, observing how these tasks are controlled and represented and finally presenting the learning and planning of the skills required to complete these tasks.

^{*1}Corresponding author; Center of Ubiquitous Computing, Faculty of Information Technology and Electrical Engineering, University of Oulu, Finland (e-mail: markku.suomalainen@oulu.fi).

^{†2}Systems and Control, Department of Electrical Engineering, Chalmers University of Technology, Gothenburg, Sweden (e-mail: yiannis@chalmers.se).

^{‡3}Intelligent Robotics research group, Department of Electrical Engineering and Automation, School of Electrical Engineering, Aalto University, Helsinki, Finland (e-mail: ville.kyrki@aalto.fi).

[§]This work was in part supported by Academy of Finland project PERCEPT 322637 and in part by European Research Council project ILLUSIVE 101020977,

1 Introduction

For a long time contact with the environment in robotic manipulation was considered problematic and tedious to manage. However, this paradigm is under rapid change at the moment. Tasks that have been considered too difficult for robots due to the need for delicate modulation of forces by humans are being performed by robots. Additionally, in many tasks contact is not only managed but exploited such that robots can localize themselves and their tools with the help of contact to perform tasks when faced with uncertainties. The methods for managing and exploiting contacts have also evolved such that the computational burden is not infeasible. Several workshops in the main robotic conferences during the recent years have been organized under the theme of managing contact, and terms such as "manipulation with the environment" have been coined. This is expected evolution, as humans take extensive advantage of the environment during various manipulation tasks with limited clearances [1].

In this survey we present an overview of how robots perform contact-rich tasks, which we call *manipulation in contact*; the contact can be between the robot's hand and the environment, or between a tool held by the robot and the environment. Such tasks require *explicit or implicit control of the interaction forces*; either the robot or a tool held by the robot is in contact with the environment for considerable periods of time. The tasks range from traditional assembly tasks, such as screwing and peg-in-hole, to material-removing tasks such as excavation and wood planing, and even to tasks mainly performed by humans currently, such as melon scooping and massaging; in other words, tasks where the robot is in contact with the environment for extended duration while needing to manage varying contacts with the environment. Especially in Small and Medium-sized Enterprises (SMEs) there is an increasing interest in the use of cobots, *i.e.* robots that can exhibit compliant behavior in such tasks [2]. A more comprehensive list of such tasks is presented in Section 2. Dynamic tasks, such as throwing or batting that are more dependent on kinematics due to the short contact time, are not considered in this survey; see [3] for a recent survey on robots performing this kind of tasks.

The first requirement for a robot to perform tasks while in continuous contact with the environment is a suitable low-level *controller*. The first choice is between *explicit or implicit control of the forces*. For explicit control where a desired force level is set, the classical force controller, or often a hybrid force/position controller [4], is a common choice; in the classical version, a PI-controller with high frequency updates attempts to keep the force applied by the robot at a desired level.

Implicit control of contact forces is often referred to as *compliance*. For

creating compliance through software, impedance control [5] is a popular choice, where deviation from a desired trajectory is allowed, allowing both free space and in-contact motions without switching the controller. Compliance can also be created with a mechanical device, such as a Variable Stiffness Actuator (VSA) or the relatively novel field of soft robotics [6]; in this survey we will not go deeper into mechanical compliance, but present certain works where mechanical compliance is used. More advanced versions of impedance controllers have been designed, from which we will present several novel ones in Section 3; a survey focusing only on the controllers was published six years ago [7].

Whereas sometimes the whole skill is represented at the control level, often a higher level representation is used which then passes commands to the controller. There are many ways to form these representations, and they may be hierarchical even beyond the control layer: we will survey the representations used with in-contact tasks in Section 4. Then, in Section 5 we make a coarse division into three different categories the skill to perform a task can be conveyed to the robot; *planning*, *Learning from Demonstration (LfD)* and *Reinforcement Learning (RL)*. Planning, or motion planning, is the classic method for planning the motion of a robot from known information while avoiding obstacles. Whereas exact planning for in-contact tasks is difficult, there are various modern methods that can achieve this that will be presented in this survey. In LfD the underlying assumption is that a human user can perform the skill efficiently, and that transferring the skill to a robot results in a successful and efficient execution. Finally, RL is currently a highly popular machine learning method, where the algorithm actively searches for a good solution. An overview of the structure of the paper is presented in Fig. 1

There are a few other related surveys which may interest the readers of this paper. For a more general survey on LfD for other sort of skills besides in-contact skills, we recommend [8, 9, 10]; similarly, there are general surveys on RL for robotics (*e.g.* [11]) and a very general survey on all kinds of robot learning [12]. There are also more detailed surveys on LfD and RL focusing on assembly tasks [13, 14, 15]. Finally, when considering vision in the loop, there is a survey of the interplay between vision and touch [16]; for this reason this survey will not consider vision-based manipulation either, and we will focus on works where the sole feedback, if any, is force. Even though many frameworks could be extended, or used on, in-contact manipulation, in this survey we focus on publications that explicitly show performance on an in-contact task.




Figure 1: The structure of the paper.

2 Tasks requiring manipulation in contact

We define manipulation in contact as tasks where explicit or implicit control of the interaction forces is required. There are actually very few tasks where explicit control of the forces is strictly required; an example of such a task is tightening a screw with a specific torque value. However, even though many tasks such as polishing could be done with implicit control of the forces as well, using explicit force values may improve the success of a learned or planned task. Finally, there are tasks which could be performed without any control of the forces under perfect knowledge, such as the classical peg-in-hole and similar workpiece alignment tasks and articulated motions, such as opening a door. However, any uncertainty in such tasks raises the need for controlling the contact forces to prevent excessive collisions; moreover, by leveraging compliance a robot can perform, for example, a peg-in-hole task with clearance smaller than the robot’s accuracy [17]. In this section more details of the manipulation skills requiring controlling of force interactions will be given under three categories; environment shaping, workpiece alignment and articulated motions. Table 1 provides a list of tasks used in the included papers where the task was a focal point of the publication. More details on the control-related terminology used in this section can be found in Section 3.

Many tasks where manipulation in contact is required also involve tools. They can either be rigidly attached to the robot arm or can be grasped by the robot for use; in this survey we do not differentiate between these cases, except by noting that grasping a tool always creates uncertainty regarding

Table 1: The most popular tasks accomplished by the surveyed papers.

Wiping or polishing	[18, 19, 20, 21, 22, 23, 24, 25, 26, 27]
Grinding or similar	[28, 29, 30, 31, 32, 33, 34, 35, 36, 37]
Scooping	[38, 39]
Peg-in-hole variants	[40, 41, 42, 43, 44, 45, 17, 46, 47, 48, 49, 50] [51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64] [65, 66, 67, 68, 69, 45, 70, 71, 72, 73, 74]
Articulated motions	[75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87]
Hydraulic	[88, 89, 90, 91, 92, 93, 94]
Rare tasks	Massage [95], velcro peeling [96] engraving [97]

the location of the tooltip, which increases the need for compliance when in contact. There are of course methods to alleviate this uncertainty if enough information of the tool has been properly measured (for example, [98]).

We also note that there are other uses for compliance in robotics, which are however not covered in this survey; often a key point of these methods is to use a variance of trajectories as a signal when compliance is needed, by assuming that a low variance across multiple demonstrations at a stage of the demonstrations means that that location is important and thus compliance should not be allowed. Vice versa, when the variance is high, the exact location is not important and compliance can be increased to (see, for example, [99, 100, 101, 102, 103]). However, this idea is often not applicable to in-contact tasks, since during contact variance is low but compliance is required. These methods work well in learning collaborative tasks [99, 100], physical Human-Robot Interaction (HRI) [104, 105, 106] and in free space tasks such as delivering and pouring a drink [103, 101].

2.1 Environment shaping

Shaping the environment means often removing a small layer of material either uniformly or from a fixed location. This sort of tasks can be differentiated by the accuracy required; whereas surface wiping (removing the dust) is essentially only a surface following task, engraving and wood planing require such high precision that they are likely not possible to complete with only implicit control of the interaction force. Another way to differentiate between this sort of skills is whether they are periodic or not: wiping can be considered a periodic task, a property exploited by some of the presented methods, whereas engraving is performed on a very detailed and fixed path.

The simplest tasks in this region is perhaps wiping [18], which has been revisited upon multiple papers with different methods [19, 20, 21, 22, 23]; in this task the original material is not affected, since wiping mostly refers

to cleaning the material. Another term used for, practically, the same task, is polishing [24, 25, 26, 27]. These tasks have been completed with either implicit or explicit control of the forces; implicit is often enough since an important part is keeping contact with the surface. Interestingly, from the aforementioned publications, only [24, 26] use implicit control, whereas the other works explicitly control the contact force (possibly with admittance control to allow room for error). A possible reason is that with implicit control, if there is no force feedback loop, it is possible to lose contact without noticing, but with force feedback in place the use of explicit control emerges naturally. Finally, loosely connected to this type of tasks is massage [95], which however requires more accurate force control and surface adaptation.

The task gets more complicated when removing the environmental material is considered; there are multiple variations of removing the outer layer of material using a tool to make the surface smoother. These tasks are often found in industry and carpentry: scraping [28], wood planing [29, 30, 31], deburring [32] and sanding [33]. All of these tasks employ explicit force control, as expected and can be considered periodic; a non-periodic similar task is engraving [97]. Additionally, interesting related tasks are grating [107], grinding [34, 35, 36, 37] and drawing [31, 108], where material is removed from the tool being held instead of the environment; as expected, grinding and grating are more periodic and require more accurate force management, whereas with drawing keeping the contact is more important but there is no periodicity. In scooping often a larger amount of a softer material is removed [38], but also parts for an assembly task can be scooped [39]. Also the use of a drill by a robot requires careful control of the environment forces [109, 110]. Finally, a fundamentally different material removing task is velcro peeling [96], which has potential to spawn other similar works for robots.

Whereas the above examples were tasks typically performed on a human scale, similar motions performed by much larger machines can be found from earthmoving, mostly performed by excavators or wheel loaders [88]. The main difference is the use of hydraulics in most of the heavy machines, which, due to the nontrivial closed-loop kinematics and interactions of the hydraulic valves, makes controlling of the forces more challenging; additionally, the material being excavated often has high variance in resistance (for example, rocks in sand). For the previously mentioned reasons, excavation is often done even without force feedback; as such, autonomous excavation has been accomplished with real machinery [89, 90, 91, 92, 93]. However, there is also work towards estimating the forces [111] and using an impedance controller with hydraulic manipulators [112, 94].

2.2 Workpiece alignment

With the term workpiece alignment we mean mainly tasks found in industrial assembly, often variations of the classic peg-in-hole; however, similar tasks are often found inside homes, such as plugging in a socket [40] or assembling furniture [41]. There are almost infinite variations of peg-in-hole, starting with the difference in clearance (industrial assembly often requires very low clearances) and ranging to multi-peg-in-hole where a plug which has two or three pegs that have to slide in simultaneously (for example, [42]). Another flavor is dual-arm peg-in-hole; however, in this case often one arm performs most of the motions, both with humans and robots [43]. The mechanics, forces and errors in peg-in-hole assembly, to enable finding the best way to perform it, have been researched from the 1980s [113] and are still under active research [114].

Compliance has been found to be a useful property in performing peg-in-hole type assembly motions already in the 1980s [115] and similar research on peg-in-hole compliance is still ongoing [64]. In the 90's research on compliant assembly was centered around *fixtures*, devices for holding workpieces during assembly. Schimmels and Peschkin [116] showed how to insert a workpiece into a fixture guided by contact forces alone, and the topic has later been revisited in (at least) [63]. Yu *et al.* [117, 118] then formalized the contact force guidance into a planar sensor-based compliant motion planning problem, *i.e.* a preimage planning problem [119]; these methods have thrived also due to increasing accuracy of contact state estimation [120], which is still seeing vast improvements [121]. In recent works, both explicit and implicit force controls have been used; even though explicit force control may not be strictly necessary, it is often beneficial especially in certain variants of the task.

Regardless of the long history, a human can still outperform a robot in peg-in-hole tasks in certain metrics, such as generalization, managing surprising situations and uncertainties and really tight clearances [44]; however, there is work to overcome these, such as meta-reinforcement learning for generalization [45] and clearances smaller than the robot's accuracy ($6\mu M$) [17]. There are also more difficult variants, such as multi-peg-in-hole [42], assembly construction [122], hole-in-peg with threaded parts [123] or peg-in-hole combined with articulated motions, which include as folding [75] or snapping [76, 77] where either more elaborate motions or force over a certain threshold is required to complete the task. Also, most works in the field assume rigid pieces, but there is also work towards the more challenging field of elastic pieces [73]. Since the peg-in-hole is such a standard problem in industry and homes, active research in the topic continues as methods and hardware evolve. For example, preimage planning [119] was long considered

infeasible for planning compliant motions in contact [124], but nowadays it is possible to plan near-optimal plans nonetheless [125]; similarly, there are better simulation tools under development which can greatly ease transfer learning [126].

2.3 Articulated motions

In articulated motions the objects can only move along a pre-defined path, which may not be obvious from a visual inspection of the object; typically the robot needs to interact with the articulated objects in order to perceive the underlying kinematic structure. The majority of everyday articulated objects that afford single arm manipulations can be modeled as one degree of freedom mechanisms (doors, drawers, handles) even though doors with handles can be seen as a combined two degrees of freedom mechanism. Also many opening tasks, such as jars [78] and valve turnings [79, 80], are articulated motions.

A level of force control is often used, although a direct force control scheme would not be strictly necessary. A big portion of the modern approaches in force-driven door opening follow the seminal work of Nimeyer and Slotine [81] that is based on: i) the implementation of a damped desired behaviour along the allowed direction of motion, and ii) the estimation of the direction of motion. The realization of the desired behaviour have been achieved through indirect compliant control [82]. A richer desired impedance has been used instead of simple damping term in [83] realised in an admittance control framework. Alternatively, hybrid force/motion control with an implicit realization allow the use of velocity-controlled robots [84, 85, 86]. While traditionally only the linear motion is considered, the last decade the orientation control is also studied both in the context of adaptive [86] and learning control [87].

The estimation of the direction of motion while opening a door/drawer is a specific case of estimation of constrained motion [127, 128]. Velocity-based (twist-based) estimation has been employed aiming at reducing chattering due to measurement noise and dealing with the ill-definedness of the normalization for slow end-effector motion such as spatial filtering [81], moving average filters [83] employing simple drop-out heuristics [82]. From a control perspective, decoupled estimation and control is considered to be indirect adaptive control as opposed to direct adaptive control approaches [86] that are more robust particularly for cases where the estimation dynamics suffer from lags. The reader is referred also to [86] for a richer summary of the door opening literature until 2015. While the estimation of motion directions for simple one-degree mechanisms is possible using proprioception and force measurements, the tracking of multi-body articulated objects requires richer perception input including vision and probabilistic methods to deal with noise and uncertainty

in the models, e.g. when the contact is lost [129].

2.4 Dual-arm manipulation in contact

A survey focusing on dual-arm manipulation can be found in [130], where the focus is mainly on centralized settings with two arms that can get feedback from each other. We will not focus on the specifics of dual-arm systems in this paper, but certain methods presented are also applicable in dual-arm methods. Thus, we will shortly consider performing tasks with two arms instead of one, and in the remainder of this survey dual-arm tasks are treated together along with single-arm tasks.

Considering industrial assembly tasks, [131] did a thorough analysis of industrial assembly tasks occurring within Toyota car manufacturing, but did not report cases where simultaneous motions of two arms were required; thus, the second arm in many tasks acts as a fixture. However, in a classic articulated rotation tasks such as opening a jar, rotating a pepper mill or just manually tightening nuts and bolts [78, 132, 133] the task may be performed faster if both arms move in harmony, reducing the number of required grip changes. Also in tasks such as melon scooping while one arm holds and the other one scoops [38], drawing on a board held by another robot [108] or peg-in-hole where also the "hole" is held [43, 46], it can be advantageous if also the holder arm can explicit compliance, even if no active motions are performed; this is also how a human performs such tasks [43]. Dual-arm manipulation has been employed for manipulating 2-DOF articulated objects with co-located prismatic and revolute joints where F/T sensing and proprioception of both were utilized to localize the joints and track their states [134]; such an approach can be used for modeling and performing bimanual folding assembly.

3 Control of manipulation in contact

Robots perform complex tasks often with a hierarchical policy where control is the lowest level; essentially, it translates the motion or force commands to actual motor currents on a high frequency. In this survey we will focus more on the higher level policies, but nonetheless introduce the different control methods used together with the higher-level policies; for a survey focusing more on compliant control methods, see, *e.g.*, [7]. The majority of force control approaches can be divided into the following groups: *i) direct* [4] and *ii) indirect control* [135] based on the force control objective and *i) explicit* and *ii) implicit* based on the nature of input control signal. Specifically, we

introduce the main control methods for explicitly controlling the forces (direct force control, admittance control) and for implicitly controlling the forces by allowing deviations from a defined path (impedance control) and their use in in-contact skills.

3.1 Force Control

A straightforward method for managing manipulation in contact without damaging the robot or the environment is *direct force control* [136, 137]. Direct control approaches offer the possibility of driving the contact force to a desired set-point or trajectory (regulation/tracking problem respectively). The direct force control can be either explicit or implicit depending on whether the robot is torque-controlled or not [138]. Another dichotomy that can be noticed mainly when direct force control is combined with motion control (namely force/motion control) is based on how the force and motion control spaces are accommodated in the control action. *Hybrid force/motion controllers* are formulated based on an explicit decomposition of control subspaces based on the motion constraints. *Parallel force/motion control* does not use constraints in order to define different control subspaces but a force control loop based on integral action dominating over a compliance-based position control loop. As force measurements are often noisy and thus their differentiation does not produce meaningful results, usually a Proportional-Integral (PI) controller is used in the force control loop. For usable force control, the update frequency must be high enough to avoid instabilities [139] and also often a damping term is added to prevent uncontrolled acceleration in the case of losing contact.

There are several methods for measuring the force data required for force control. In Cartesian control a straightforward method is to place a Force-Torque sensor (F/T sensor), which can be added afterwards to most robots, at the wrist of the manipulator. For electrically actuated robots, other methods include motor currents, motor output torques [140, 25] or torque sensors at the joints, with explicit force sensing providing better accuracy than the implicit methods of joint motors. For hydraulically actuated manipulators, forces from possibly hundreds of kilograms of payload can easily damage most available F/T sensors. The method analogous to motor current estimation is using the hydraulic fluid chamber pressures for estimating the Cartesian wrench [141].

3.2 Impedance control

Impedance control is an implicit force control; the idea is to follow a trajectory in space, but allow displacements from the trajectory in proportion to set gains,

in essence placing a virtual spring to the end-effector of the robot. The gains of the spring can be edited along three axes both in rotation and in translation, where the gains correspond to the spring constant in Hooke’s law ($F_s = kx$, where F_s is the force, x the spring’s displacement from the equilibrium and k the gain, or spring constant). Whereas the original work by Hogan [5, 135] considered the impedance to remain unchanged, there are nowadays various works considering varying the impedance during execution and how that affects the stability of the system [142, 143, 144]. Similarly as a traditional spring, a virtual spring can store energy and thus the traditional impedance controller is not passive [142], which can cause instabilities, especially when combined with learning approaches [67]. There are several possible solutions to this problem, for example dissipating the energy into non-relevant directions [145], storing it into a tank [146] or filtering the impedance profile if it seems to provoke instabilities [147]. Also, it should be noted that an impedance controller can also work as a feed-forward controller, thus avoiding the need for a force sensor or other feedback loop to simplify the robot’s requirements [148, 47]. Finally, Whereas most of the work is shown true to electric manipulators, stable impedance control has also been designed for hydraulic manipulators [112].

3.3 Admittance control

The idea of admittance control is to allow deviations from the commanded force in proportion to set gains, similarly as impedance control allows displacements from the trajectory. It allows for implementing a desired impedance without necessarily relying on torque-controlled robots. With admittance control we here refer to all types of force-to-desired-motion relationships that can feed inner motion control loops, namely a) position/velocity-based impedance control where the reference motion command is the output of a desired impedance [149], and b) accommodation or inverse damping control mainly implemented on non-backdrivable robots. The latter is very common for force-guided robotic assembly applications [150]. For example, model predictive control based on learnt models have been used to determine the force fed in an inverse-damping controller to perform food-cutting [151]. In this context, recent works [152, 153] study admittance parameter selection or propose variable admittance structures [154]. Admittance control has been used in, for example, excavation [92, 91] and peg-in-hole [50, 51, 22]; other use cases not considered in-depth in this survey include, for example, physical Human-Robot Interaction [155].

4 Representing manipulation in contact

To make a robot execute a skill to complete a task, the robot must have a representation of the skill, essentially a mapping from the task requirements and sensor feedback to controller inputs. This mapping is often called a policy, which tells the robot what to do sensory inputs h from state x^1 , thus commanding the lower-level controller to apply certain forces or move to a certain location with an action u . Thus, a policy π maps state and sensor input h into actions, $u = \pi(h(x))$. In its most straightforward form, π can be a discrete set of state-action pairs, but this is only feasible in small problems. Thus, π is often a condensed representation of such state-action pairs.

Policies are often hierarchical, meaning that a policy Π first chooses to either apply policy π_1 or π_2 based on $h(x)$, and then π_1 and π_2 give the commands that the low-level controller can interpret; these *continuous*² representations will be covered in Section 4.1. Then in Section 4.2 we will cover the discrete representations Π which consider choosing a suitable subpolicy at each moment; we note, however, that certain methods such as Hidden Markov Model (HMM) and its extensions are often used as both Π and π_i , but we present them only in Section 4.1 for clarity. A list of the papers in this survey using certain representations can be found in Table 2.

Table 2: The most popular representation methods used in the surveyed papers.

DMP & extensions	[31, 30, 29, 36, 19, 21, 39] [22, 156, 52, 49, 102, 157, 50, 51, 158, 159]
GMM-based	[160, 71, 161, 38, 95, 26, 27]
HMM & extensions	[132, 162, 48, 161, 163, 164, 165, 166]
(PO)MDP	[60, 167, 125, 168, 169, 170, 171, 172, 173]
NN	[174, 175, 44, 41]

4.1 Continuous representations

Perhaps the most straightforward continuous representations are polynomials, and indeed, polynomial splines are used even in recent papers for representing

¹Even though some of the surveyed methods work without force sensor feedback, at least proprioceptive feedback from, *e.g.*, the angle sensors of a manipulator are used in practically all the applications, and thus we do not consider any of the approaches to be completely feed-forward, even if we use the term later for approaches that don't require force information.

²We mean continuous in the sense that the "continuous" policy has a wide, often continuous range of outputs (motion or force commands it can feed to the controller), whereas the "discrete" policy simply makes the choice between subpolicies.

robot motion policies [176]. However, policies in in-contact skills often employ other kind of representations, and thus in this section we will focus on representations that have been successfully used with in-contact tasks. Many of these representations are probabilistic, often taking advantage of structures such as Gaussian Mixture Models (GMMs), to model the uncertainty always present with in-contact tasks; often these are combined with dynamical systems to achieve time-invariant and stable behavior. Others are simply parametric function approximators, such as neural networks, or spring-damper systems built around function approximators, such as the Dynamic Movement Primitives (DMP). In this section we will show how these representations can be used to make an autonomous machine perform motions requiring contact with the environment.

A very popular family of motion primitives are based on DMP [177] and employed especially with LfD but also with RL, especially for further improvements after a human demonstration (for example [29]). A DMP consists of three distinctive components: a *transformation system*, a simple linear dynamical system acting as a spring-damper and driving the system forwards; the *forcing function*, a function approximator which perturbs the system from being a simple attractor and essentially creates the trajectory. Traditionally the forcing function is a Radial Basis Function (RBF) [178], but other options such as a Neural Network (NN) [74] have been proposed. As DMPs are learned distinctively for each Degree of Freedom (DoF), either in Cartesian or joint space, the DoFs need to be synchronized, which is performed with the third component, a *canonical function*.

This classic DMP was used for position only; however, there have been multiple updates on it, some of which allow DMP to be used for in-contact tasks. The simplest way is to use DMPs directly with explicit force control [31, 30, 29, 36, 19, 21] or with admittance control [39, 22]. Another logical step is to augment a trajectory in space with a force or admittance profile [156, 52, 49] or an impedance profile [102], which is synchronized with the canonical function; this is sometimes called Compliant Movement Primitives (CMP) [157], when the superposed torque signal is encoded with RBFs called *torque primitives*. Furthermore, CMP has also been task-parametrized [50, 51] and thus generalized to new situations if the parameters of the tasks are known: for example, the depth of a hole where a peg is inserted. This means there is a direct mapping from the task parameter, such as the depth of the hole in peg-in-hole, to the weights of the primitive to easily perform variations of a similar task. Additionally, one could build a library of different CMP skills with the task-parametrization [158]. Other modifications of DMP include incremental learning with impedance control [159], Probabilistic Movement Primitive (ProMP) [179] and Kernelized Movement Primitives (KMP) [180].

A different approach is to use a GMM to encode the trajectory, essentially placing a number of multidimensional Gaussian distributions along the trajectory and learning suitable mean and variance parameters for them. There is a wide variety of different methods that take advantage of GMMs, where a major difference is in the way the transitions between different Gaussians are handled. A straightforward solution is the use of Gaussian Mixture Regression (GMR), which first builds a joint distribution of the Gaussians and then derives the regression function from the joint distribution [181, 182]. As with DMP, the vanilla solution of GMM-GMR is not suitable for in-contact tasks, but augmenting it with a force profile creates the possibility of performing in-contact tasks too [160]. Similarly as with DMP-based methods, also GMM-GMR can be improved with RL after demonstration for in-contact tasks (for example, multi-peg-in-hole [71]).

Another method for exploiting GMM in a learning task is Stable Estimator of Dynamical Systems (SEDS) [183]. SEDS, unlike DMP and GMR, is time-invariant due to the nature of the dynamical systems, and has also been shown to be stable with a nonlinear Dynamical System (DS). Whereas the original version is again for position only, there have been extensions that allow the usage in in-contact tasks. Dynamical systems have been shown to manage variable impedance control [161, 38, 95] for in-contact tasks, and also recently to provide accurate force control on unknown surfaces [26, 27].

With the rapid raise of Deep Learning (DL) in the recent years, NNs have become popular as general function approximators encoding control policies, in both learning from demonstration and RL, potentially using human demonstrations as starting points. Methods that use DL can be categorized based on the modeling target: The deep networks can encode either directly the control policy (e.g. [174]) or a trajectory for a predefined low-level controller (e.g. [175]). In addition, it would be also possible to use deep networks to encode environment dynamics, but this is seldom done in in-contact manipulation, most likely due to the difficulty of collecting sufficient training data for the data hungry models. To address the need of data, other methods such as trajectory optimization can be used for generating sufficient data while the neural network will allow the use of a single policy that generalizes by interpolating the training data [174]. For situations where the policy provides an entire trajectory, the data efficiency can also be increased by using a low-dimensional latent trajectory embedding learned from unlabeled data [175].

Finally, there are several other methods; another one besides SEDS taking advantage of dynamical systems is Unified Motion and variable Impedance Control (UMIC) [184], which combines motion and variable impedance in a time-invariant system, showing stability of the system. Unlike the previous

methods, UMIC is not a trajectory following system, and requires more than a single demonstration. Linear Motion with Compliance (LMC) [47] was designed for a more narrow use case of LfD in workpiece alignment tasks, and has also been used with hydraulic manipulators [94] and in a dual-arm setting [46]. Another method for a special case of maintaining a contact between two surfaces, surface-to-surface primitives, was suggested in [20]. Also, there are a few methods where impedance profile can be added to any kind of trajectory representation, learned either through LfD [102] or Bayesian optimization [148].

4.2 Discrete representations

Discrete representations are typically one level higher in a hierarchical policy than the continuous representations presented in the previous section; a classical example fitting to the topic at hand is to have a different policy for times before and after the contact with the environment is initiated [168] or by completely interleaving these two strategies [169]. Another, often proposed idea, is to have a library of continuous policies (often referred to as skills) available, from which the robot can choose a correct one at correct time and for a correct context [119, 185, 186, 187, 188]. There are many ways to establish these transitions between skills or policies, and often different kinds of probabilistic methods are used to learn and smoothen the process. Thus, in this section we survey the literature on different ways to represent such different behavior under different conditions.

A straightforward way, especially for tasks involving contact, is to use threshold values for the detected forces (for example, [189]). The thresholds are sometimes referred to as *guarded motions* in robotics [190, 191]. Johansson *et al.* have a considerable number of works regarding sequencing of skills based on detected contact wrench. They have been using transients [189], making the programming of such force-based segments easier for humans [192] and detecting successful assembly even without a F/T sensor in a snap-fit scenario [193]. There are also probabilistic methods used for such tasks with robots, such as the Bayesian Online Changepoint method [58]. A slightly more complex approach is to use thresholds in the contact formation space with suitable motion primitives based on RRT [194].

A popular probabilistic method to approach this problem is the HMM, which assumes the modeled system to be a Markov process with unobserved variables. The earliest works of using HMM to segment a demonstration in LfD (dividing a human demonstration automatically into sections that require different policies) and then choose a suitable policy during runtime were presented already in 1996 [195]. A popular extension was to make the

HMM autoregressive with a beta process prior [196, 197, 198]. Whereas this model is not explicitly meant for in-contact tasks, further modifications were proposed that allowed the usage of autoregressive state space model together with an HMM on tasks such as rotating a pepper mill [132, 162] and also for assembly tasks with an impedance controller requiring constant contact [48]. Even further extension was shown to learn tasks requiring constant, varying contact in slicing and grating vegetables [161, 163]. Finally, sometimes it is useful to have time as a variable even in in-contact skills; Hidden Semi-Markov Models (HSMM) have been shown applicable to such cases [164] and can also be task-parametrized and used similarly as the motion primitives presented earlier [166].

The classical Markov Decision Process (MDP) and their extensions, most notably Partially Observable Markov Decision Process (POMDP), have been used extensively as representations for both planning [125, 167] and learning [60, 96] frameworks. Whereas both are very popular in robotics in general, with different techniques available to reduce the computational complexity, there is a limited number of in-contact tasks they have been used for; popular examples being [168, 169], who used POMDP to handle motions requiring both free space and in-contact motions. POMDP has also been used to leverage contact for localization both in classical tasks [170] and when teaching the robot to search for a goal from a human demonstration [171, 172, 173].

An interesting use case especially for assembly in-contact tasks, which can be handled with many different methods, is *exception strategies*; in difficult in-contact tasks the robot can often partially fail or end up with stuck workpieces, situations which can be managed through switching policies. For detecting such errors, for example HMM [165] and Support Vector Machines (SVM) [199] have been used. Abu-dakka *et al.* [52] used random walk in case an assembly task failed and searching had to be done. Jasim, Plapper and Voos [62] used an Archimedean spiral, which is guaranteed to find the goal with the correct resolution and starting position. Chapter 5 in [200] used incremental learning, where the human assists the robot during insertion if the robot gets stuck. Ehlers *et al.* [40] proposed looking into the *area coverage* literature instead of trajectory following to learn area or force-based search strategies. Hayami *et al.* [77] use the force signal on snapping assembly to figure out when and how things go wrong. Also, [65] use PCA to detect context of assembly tasks to apply the correct exception strategy.

5 Learning and planning of manipulation in contact

When a suitable representation of a task is chosen, the actual policy must be found for a skill the robot will then use to complete the task. This phase is typically called planning or learning. Even though many people associate their approach with either of the terms, there are often similarities, and nowadays combinations of these approaches; also several representations can be used with either approach. In Section 5.1 we present planning approaches for manipulation in contact, and how contact can be leveraged for better or faster plans. In Section 5.2 we present reinforcement learning approaches. Finally, we present imitation learning methods for in-contact manipulation in Section 5.3, where the idea is to use human expertise to find a suitable policy for the robot.

When considering planning or learning of in-contact tasks, there are two main approaches following the control methods presented in section 3: first, policies can consist of a sequence of force contacts, possibly together with motions, where the contacts are used for localization. Second, the policy can consist of motions with an impedance profile to provide the necessary compliance to overcome uncertainty in contact. In this section methods from both of these approaches are considered. Table 3 presents the surveyed papers divided into categories with respect to how the policy was eventually found, for those works where finding the policy was a major contribution.

Table 3: The papers divided across the methods of finding the correct policy.

Force control planning	[62, 43, 59, 201, 140, 189, 193, 117, 118, 68, 75, 202, 64].
Contact for localization	[203, 63, 204, 205, 206, 68, 207]
Compliant motion planning	[167, 168, 169, 208, 125, 209, 210, 61]
LfD	[31, 30, 29, 36, 19, 21, 39, 22, 156, 52, 49] [102, 157, 50, 51, 158, 159, 161, 38, 95, 160]
RL	[211, 212, 29, 174, 44, 42, 213, 54, 214, 70] [41, 60, 45, 215, 72, 216, 217, 69, 122].

5.1 Planning of manipulation in contact

The origins of motion planning for compliant motions can be traced to fine motion planning [218, 219]; however, this approach always suffered from a high computational load, as did another early approach for planning compliant motions, preimage planning [119]. Another early approach was the use of

threshold values to plan for assembly tasks, such as [116], and there have been attempts to use other popular methods, such as the probabilistic roadmaps, on in-contact skills [220]. Additionally, whereas most of the methods reported in this section have been proven on small-scale tasks, also excavation has been successfully done with planning [90].

The use of force values for planning is perhaps more popular than compliance. For peg-in-hole assembly, there are several planning methods taking advantage of contacts: whereas the easier approach is to attach a force sensor to the robot arm [62, 43, 59], it is also possible to plan force-based assembly tasks without a force sensor [201, 140]. Sometimes these threshold values are also called transients [189, 193]. Another popular term is fixture loading; fixtures are physical guides that help guide an assembly task, where planning motions has been shown useful [117, 118]. There is also novel development in this field, such as finding optimal placements for fixtures so that they can mitigate uncertainty [68]. Further, planning has also been used on assembly tasks where accurate combination of force and motion is required to accomplish a task, such as folding [75] or snapping [202]. Also, general force profiles can be used to plan compliant motions with the use of force control [64].

Even though planning of optimal compliant motions is infeasible, there are many approximations through which near-optimal solutions can be found. Phillips-Grafflin and Berenson [167] used MDP approach to overcome actuation uncertainties for planning assembly tasks taking advantage of compliance. Also the extension of imperfect information, POMDP has been used as the representation for planning [168], targeting pushing with a switching policy depending on the contact state, or for completely interleaving in-contact and free space motions [169]. Also, the earlier mentioned probabilistic roadmaps have also been used together with contact states to plan compliant motions [208]. A notable result in this area was achieved by Guan, Vega-Brown and Roy [125], who showed near-optimal planning of compliant motions using a feedback MDP. The often complex planning problem can also be simplified by realizing that in compliant motions, different motions of the robot can result in a same kind of motion of the object [209]. Finally, when rich information of the workpieces is known beforehand, such as the CAD model [210] or the mesh model [61], planning can be done efficiently.

An interesting approach is to use contacts as localization to mitigate uncertainty; the straightforward approach is to consider point-contacts for localization [203]. An approach beyond contact thresholds is the concept of Contact State (CS), which means finding the exact contact point, or points, of a tool. This can be done with only a force-position mapping to solve the task, in this case peg-in-hole [63], but there is also a wide literature on detecting where a contact to an assemblable piece occurs and how to make more general

plan: first, the state of contact (for example, point contact or face-to-face contact) needs to be detected [204], before they can be exploited during autonomous compliant motions by the help of Kalman filtering and Bayesian estimation [205, 206]. To improve such strategies, [68] learn how to place fixtures at the environment to optimize this kind of uncertainty mitigation offered by contact. Finally, physical exploration can also be required to perform complex and new tasks, which was explored in [207].

5.2 Reinforcement learning of manipulation in contact

Reinforcement learning (RL) methods aim to learn an optimal control policy for stochastic time-series systems by exploring the dynamics of the environment [221]. Reinforcement learning has recently seen wide interest in robotics, with multiple surveys spanning the entire spectrum of RL including [11]. In this section we focus solely on the use of reinforcement learning for in-contact manipulation tasks. Types of tasks that have been addressed using RL include pushing [211], manipulation of articulated objects such as door opening [212], tool use [29], as well as peg-in-hole and similar assembly tasks [174, 44, 42].

Learning in-contact manipulation directly in a physical robot system using reinforcement learning is challenging, because the exploration needed for the learning is often a safety hazard due to potentially high contact forces in high stiffness environment interactions. Methods exploring in physical systems alleviate the potential hazard by limiting contact forces using torque control (e.g. [174]), impedance control with limited stiffness (e.g. [29]), or explicit limiting of actions using safety based constraints [213]. The data hungry nature of reinforcement learning presents an additional challenge for learning directly in a physical system. This is often alleviated by using a human demonstration as a starting point for the RL-based policy optimization [29, 54, 214].

In contrast to learning in a physical system, policies can also be learned in a simulation environment before executing them in the physical system. This allows the exploration to be performed safely in simulation and provides access to vast amounts of training data. However, the approach results in another challenge in the form of the reality gap between the simulation and the physical system. The gap can be reduced by calibrating the simulation using system identification [70]. Alternatively, policies can be robustified by training them with simulated noise [211, 41], or over a known distribution of simulator parameters also known as domain randomization [60]. Also, a simulation-trained policy may be further refined in real-world, for example using meta-learning to learn adaptable policies [45].

RL has been used to optimize various aspects of in-contact policies, includ-

ing controller set point trajectories (assuming a known controller), controller parameters (assuming known target trajectories and controller structure), and entire feedback policies. Set point trajectories can be learned e.g. for end-effector poses of an impedance controlled manipulator [29, 215]. Another common approach is to use RL to optimize control parameters such as gains [60] or compliance parameters [215, 72, 214]. In the case of feedback policies, the choice of action space (e.g. velocity vs force) has been found to be application dependent [216]. RL can also be combined with other control and decision making approaches, including classical control methods such as impedance control [217] and operational space control [69], planning [122], or fuzzy logic [42].

5.3 Learning from demonstration of manipulation in contact

In LfD, also known as imitation learning or Programming by Demonstration (PbD), a user shows the robot how a task should be done. We note that many works of LfD for in-contact tasks focus on finding novel, better representations that can better encode the task. We covered already in Section 4 these parts, such as extending popular approaches (DMP, GMM, SEDS) to in-contact tasks, as well as less-known representations meant for in-contact tasks. Thus, in this section we will focus more on issues such as good demonstration, force data gathering and number of required demonstrations.

Whereas LfD is already a well established idea in robotics [10], there is a specific requirement to perform LfD with in-contact tasks: the contact force during the demonstration must be either measured or estimated. This is a crucial part when deciding the demonstration method: with perhaps the most popular demonstration method, grabbing the robot and leading it through the motions (also known as kinesthetic teaching), a F/T sensor is often required since the joint torque sensors cannot observe the force if the user holds the robot near the tool (there are however various ways to place the sensor, with two different ones presented in [24] and [30]). For teleoperation with electrically actuated robots, motor currents, motor output torques [140] or torque sensors at the joints that robots such as the Franka Emika Panda have, can be used to estimate the contact force during the demonstration; for hydraulically actuated robots, hydraulic fluid chamber pressures can be used to estimate the contact forces [141]. Other proven methods include handheld devices with methods to modulate impedance [222, 223, 103] or electromyography sensors on the demonstrator [109]. There are also certain things a human does, such as slipping the grip, which need special methods

for a robot to detect in a demonstration [224].

Once the force data is gathered, there are various options to encode the data, most of which were handled already in Section 4. The requirements may also vary: DMP and its variants can be used to learn from a single demonstration only, but if multiple demonstrations are used they need to be aligned in time (simplifications have been proposed, for example [74]). The GMM-based methods can naturally handle multiple demonstrations, but often require more than one to start with. These representations, and their extensions, are the most popular ones used in LfD, and are covered in more depth already in Section 4, with both continuous and discrete representations being used, often hierarchically. In addition, methods mostly used in planning have also been adapted to LfD, such as contact state estimation [57]. A common problem with many of the aforementioned strategies is that the segmentation part often produces too many segments; pruning and joining of these segments to simplify execution, regardless of the representation, has been suggested in [225, 226].

Another challenge in LfD with in-contact tasks is that often the robot should exploit the environment for more accurate positioning; however, as users often give as good demonstrations as they can, it can be challenging to gather demonstrations where uncertainty forces the demonstrator to exploit the environment. There are several works looking into how to give good demonstration, which show that explicit instructions help the demonstrator [227, 228]. More implicit methods include incremental learning [159, 229], where the robot gradually develops the correct behavior from multiple demonstrations and corrections, and active learning [230] where the robot communicates to the teacher what sort of demonstrations are required. Whereas there are recent works about active learning for manipulation [231, 232] for in-contact tasks there are currently no known active learning approaches. Finally, the task can be made more difficult for the demonstrator to observe the required behavior, for example by using blurring glasses [233] or simply blindfolding the teacher [171, 40].

Finally, it is an interesting question whether LfD is even a good way to learn such tasks, or are the human demonstrations already sub-optimal. Whereas there is no clear answer, at least for the classic peg-in-hole task people do have an efficient strategy to learn from [234]. Whereas LfD can often be used to quickly learn tasks in, for example, assembly lines, when more optimization is required a powerful strategy is pairing LfD with RL, such that the robot’s policy is further optimized offline with reinforcement learning or optimization methods [29, 148, 214], or the demonstrations can be used to enhance the effectiveness of classical motion planning methods [235].

6 Conclusions and future work

In this survey we provide readers a comprehensive look into various state-of-the-art methods for making robots perform in-contact tasks, which are a natural next step for increasing the automation level in factories and at homes. After laying out the kind of in-contact tasks that have been performed by robots, we further showed how to control robots during such tasks, followed by representations used to encode such tasks and finally methods to exploit the representations in a correct way.

In-contact tasks are very often required both in factory assembly and at service tasks. For factories, leveraging compliance can further increase the amount of tasks that can be performed by robots, also for cases where the products often vary; at home mastering in-contact tasks will endow service robots of the future with an increasing number of abilities. Whereas contact between the robot and the environment is not any more viewed as a nuisance, there is still a long way to view it as useful as people do; thus, we hope that this survey will help people delve into the area of in-contact tasks, exploit the researched ones and come up with new ideas.

Several areas for future work can be identified from this survey. In general, state-of-the-art in robotics is always trying to perform more complicated tasks faster and with less time spent on planning or learning. Regarding tasks, almost all tasks with stiff objects can already be completed with enough preparation time; however, there are only few works with objects that bend. Whereas cloth folding is a researched topic (for example [236]), assembly tasks with objects that bend is even more complex than that, since the interplay of deformation and friction creates a complex physics task to reason about. Another interesting use case would be painting; whereas similar to wiping, painting a wall such that the result is not uneven requires a very delicate manipulation of forces, which would require a lot from a physics engine to simulate, or very accurate recording of motions for LfD. Also, there are still certain assembly tasks even with stiff objects, such as board-to-board matings, where the accuracy can be improved by leveraging contact.

Besides the tasks, the other points of advance are similar as for any subfield of robotics, namely learning time and generalization. Teaching new in-contact tasks to robots has to be fast; methods such as one-shot imitation learning and transfer learning can help in this, when they are easy enough to deploy in factories and also capable of learning even complex tasks from a single demonstration. Also, the improvements in physics simulation can allow better transfer learnings, such that even difficult tasks such as exploiting contact and friction can be learned in simulation before being deployed to the real world (domain randomization, even though providing great results, is not

very fast [237]). For simulations, also demonstrations can be given in Virtual Reality (VR) with sufficiently good physics engines, something that is under active development [238, 239]. Another LfD-related future work is the HRI side; how would a non-roboticist understand what is a good demonstration for the robot to learn various tricks in difficult tasks, such as wood handling?. Finally, even though there is research on inferring contact forces with vision only [240, 241], this work is limited to grasping; with novel deep learning methodologies, it should be possible for robots to learn tasks even such as sawing from only watching a video.

References

- [1] E. Klingbeil, S. Menon, and O. Khatib, “Experimental analysis of human control strategies in contact manipulation tasks,” in *International Symposium on Experimental Robotics*, pp. 275–286, Springer, 2016.
- [2] A. Cencen, J. Verlinden, and J. Geraedts, “A design methodology to improve human-robot coproduction in small and medium sized enterprises,” *IEEE/ASME Transactions on Mechatronics*, 2018.
- [3] F. Ruggiero, V. Lippiello, and B. Siciliano, “Nonprehensile dynamic manipulation: A survey,” *IEEE Robotics and Automation Letters*, vol. 3, no. 3, pp. 1711–1718, 2018.
- [4] M. H. Raibert and J. J. Craig, “Hybrid position/force control of manipulators,” *Journal of Dynamic Systems, Measurement, and Control*, vol. 103, no. 2, pp. 126–133, 1981.
- [5] N. Hogan, “Stable execution of contact tasks using impedance control,” in *1987 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 1047–1054, IEEE, 1987.
- [6] K. Chin, T. Hellebrekers, and C. Majidi, “Machine learning for soft robotic sensing and control,” *Advanced Intelligent Systems*, vol. 2, no. 6, p. 1900171, 2020.
- [7] S. G. Khan, G. Herrmann, M. Al Grafi, T. Pipe, and C. Melhuish, “Compliance control and human–robot interaction: Part 1—survey,” *International Journal of Humanoid Robotics*, vol. 11, no. 03, p. 1430001, 2014.

- [8] B. D. Argall, S. Chernova, M. Veloso, and B. Browning, “A survey of robot learning from demonstration,” *Robotics and autonomous systems*, vol. 57, no. 5, pp. 469–483, 2009.
- [9] T. Osa, J. Pajarinen, G. Neumann, J. Bagnell, P. Abbeel, and J. Peters, “An algorithmic perspective on imitation learning,” *Foundations and Trends in Robotics*, vol. 7, no. 1-2, pp. 1–179, 2018.
- [10] H. Ravichandar, A. S. Polydoros, S. Chernova, and A. Billard, “Recent advances in robot learning from demonstration,” *Annual Review of Control, Robotics, and Autonomous Systems*, vol. 3, 2020.
- [11] J. Kober, J. A. Bagnell, and J. Peters, “Reinforcement learning in robotics: A survey,” *The International Journal of Robotics Research*, vol. 32, no. 11, pp. 1238–1274, 2013.
- [12] O. Kroemer, S. Niekum, and G. Konidaris, “A review of robot learning for manipulation: Challenges, representations, and algorithms,” *arXiv preprint arXiv:1907.03146*, 2019.
- [13] J. Xu, Z. Hou, Z. Liu, and H. Qiao, “Compare contact model-based control and contact model-free learning: A survey of robotic peg-in-hole assembly strategies,” *arXiv preprint arXiv:1904.05240*, 2019.
- [14] Z. Zhu and H. Hu, “Robot learning from demonstration in robotic assembly: A survey,” *Robotics*, vol. 7, no. 2, p. 17, 2018.
- [15] M. Braun and S. Wrede, “Incorporation of expert knowledge for learning robotic assembly tasks,” in *2020 25th IEEE International Conference on Emerging Technologies and Factory Automation (ETFA)*, vol. 1, pp. 1594–1601, IEEE, 2020.
- [16] J. Bohg, K. Hausman, B. Sankaran, O. Brock, D. Kragic, S. Schaal, and G. S. Sukhatme, “Interactive perception: Leveraging action in perception and perception in action,” *IEEE Transactions on Robotics*, vol. 33, no. 6, pp. 1273–1291, 2017.
- [17] S. Gubbi, S. Kolathaya, and B. Amrutur, “Imitation learning for high precision peg-in-hole tasks,” in *2020 6th International Conference on Control, Automation and Robotics (ICCAR)*, pp. 368–372, 2020.
- [18] H. Urbanek, A. Albu-Schaffer, and P. van der Smagt, “Learning from demonstration: repetitive movements for autonomous service robotics,” in *2004 IEEE/RSJ International Conference on Intelligent Robots and*

- Systems (IROS)*(*IEEE Cat. No. 04CH37566*), vol. 4, pp. 3495–3500, IEEE, 2004.
- [19] Z. Deng, J. Mi, Z. Chen, L. Einig, C. Zou, and J. Zhang, “Learning human compliant behavior from demonstration for force-based robot manipulation,” in *2016 IEEE International Conference on Robotics and Biomimetics (ROBIO)*, pp. 319–324, IEEE, 2016.
- [20] M. Khansari, E. Klingbeil, and O. Khatib, “Adaptive human-inspired compliant contact primitives to perform surface–surface contact under uncertainty,” *The International Journal of Robotics Research*, vol. 35, no. 13, pp. 1651–1675, 2016.
- [21] A. Gams, T. Petrič, M. Do, B. Nemeč, J. Morimoto, T. Asfour, and A. Ude, “Adaptation and coaching of periodic motion primitives through physical and visual interaction,” *Robotics and Autonomous Systems*, vol. 75, pp. 340–351, 2016.
- [22] A. Kramberger, E. Shahriari, A. Gams, B. Nemeč, A. Ude, and S. Haddadin, “Passivity based iterative learning of admittance-coupled dynamic movement primitives for interaction with changing environments,” in *2018 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 6023–6028, IEEE, 2018.
- [23] D. Leidner, G. Bartels, W. Bejjani, A. Albu-Schäffer, and M. Beetz, “Cognition-enabled robotic wiping: Representation, planning, execution, and interpretation,” *Robotics and Autonomous Systems*, vol. 114, pp. 199–216, 2019.
- [24] A. Brunete, C. Mateo, E. Gambao, M. Hernando, J. Koskinen, J. M. Ahola, T. Seppälä, and T. Heikkilä, “User-friendly task level programming based on an online walk-through teaching approach,” *Industrial Robot: An International Journal*, vol. 43, no. 2, pp. 153–163, 2016.
- [25] Y. Qian, J. Yuan, S. Bao, and L. Gao, “Sensorless hybrid normal-force controller with surface prediction,” in *2019 IEEE International Conference on Robotics and Biomimetics (ROBIO)*, pp. 83–88, IEEE, 2019.
- [26] W. Amanhoud, M. Khoramshahi, and A. Billard, “A dynamical system approach to motion and force generation in contact tasks,” *Robotics: Science and Systems (RSS)*, 2019.

- [27] W. Amanhoud, M. Khoramshahi, M. Bonnesoeur, and A. Billard, “Force adaptation in contact tasks with dynamical systems,” in *2020 IEEE International Conference on Robotics and Automation (ICRA)*, IEEE, 2020.
- [28] Y. Chebotar, O. Kroemer, and J. Peters, “Learning robot tactile sensing for object manipulation,” in *2014 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 3368–3375, IEEE, 2014.
- [29] M. Hazara and V. Kyrki, “Reinforcement learning for improving imitated in-contact skills,” in *2016 IEEE-RAS 16th International Conference on Humanoid Robotics (Humanoids)*, pp. 194–201, IEEE, 2016.
- [30] A. Montebelli, F. Steinmetz, and V. Kyrki, “On handing down our tools to robots: Single-phase kinesthetic teaching for dynamic in-contact tasks,” in *2015 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 5628–5634, IEEE, 2015.
- [31] F. Steinmetz, A. Montebelli, and V. Kyrki, “Simultaneous kinesthetic teaching of positional and force requirements for sequential in-contact tasks,” in *2015 IEEE-RAS 15th International Conference on Humanoid Robots (Humanoids)*, pp. 202–209, IEEE, 2015.
- [32] F.-Y. Hsu and L.-C. Fu, “Intelligent robot deburring using adaptive fuzzy hybrid position/force control,” *IEEE Transactions on Robotics and Automation*, vol. 16, no. 4, pp. 325–335, 2000.
- [33] B. Maric, A. Mutka, and M. Orsag, “Collaborative human-robot framework for delicate sanding of complex shape surfaces,” *IEEE Robotics and Automation Letters*, vol. 5, no. 2, pp. 2848–2855, 2020.
- [34] C. W. Ng, K. H. Chan, W. K. Teo, and I.-M. Chen, “A method for capturing the tacit knowledge in the surface finishing skill by demonstration for programming a robot,” in *2014 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 1374–1379, IEEE, 2014.
- [35] W. Ng, H. Chan, W. K. Teo, and I.-M. Chen, “Programming robotic tool-path and tool-orientations for conformance grinding based on human demonstration,” in *2016 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 1246–1253, IEEE, 2016.
- [36] B. Nemeč, K. Yasuda, N. Mullennix, N. Likar, and A. Ude, “Learning by demonstration and adaptation of finishing operations using virtual mechanism approach,” in *2018 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 7219–7225, IEEE, 2018.

- [37] H. Zhang, L. Li, J. Zhao, J. Zhao, S. Liu, and J. Wu, “Design and implementation of hybrid force/position control for robot automation grinding aviation blade based on fuzzy pid,” *The International Journal of Advanced Manufacturing Technology*, vol. 107, no. 3, pp. 1741–1754, 2020.
- [38] L. P. Ureche and A. Billard, “Constraints extraction from asymmetrical bimanual tasks and their use in coordinated behavior,” *Robotics and autonomous systems*, vol. 103, pp. 222–235, 2018.
- [39] A. Kramberger, I. Iturrate, M. Deniša, S. Mathiesen, and C. Sloth, “Adapting learning by demonstration for robot based part feeding applications,” in *2020 IEEE/SICE International Symposium on System Integration (SII)*, pp. 954–959, IEEE, 2020.
- [40] D. Ehlers, M. Suomalainen, J. Lundell, and V. Kyrki, “Imitating human search strategies for assembly,” *2019 IEEE International Conference on Robotics and Automation (ICRA)*, 2019. Accepted for Publication. arXiv:1809.04860.
- [41] A. A. Apolinarska, M. Pacher, H. Li, N. Cote, R. Pastrana, F. Gramazio, and M. Kohler, “Robotic assembly of timber joints using reinforcement learning,” *Automation in Construction*, vol. 125, p. 103569, 2021.
- [42] Z. Hou, Z. Li, C. Hsu, K. Zhang, and J. Xu, “Fuzzy logic-driven variable time-scale prediction-based reinforcement learning for robotic multiple peg-in-hole assembly,” *IEEE Transactions on Automation Science and Engineering*, pp. 1–12, 2020.
- [43] X. Zhang, Y. Zheng, J. Ota, and Y. Huang, “Peg-in-hole assembly based on two-phase scheme and f/t sensor for dual-arm robot,” *Sensors*, vol. 17, no. 9, p. 2004, 2017.
- [44] T. Inoue, G. De Magistris, A. Munawar, T. Yokoya, and R. Tachibana, “Deep reinforcement learning for high precision assembly tasks,” in *2017 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 819–825, IEEE, 2017.
- [45] G. Schoettler, A. Nair, J. A. Ojea, S. Levine, and E. Solowjow, “Meta-reinforcement learning for robotic industrial insertion tasks,” in *2020 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 9728–9735, 2020.

- [46] M. Suomalainen, S. Calinon, E. Pignat, and V. Kyrki, “Improving dual-arm assembly by master-slave compliance,” in *2019 IEEE International Conference on Robotics and Automation (ICRA)*, IEEE, 2019. Accepted for Publication. arXiv:1902.07007.
- [47] M. Suomalainen, F. J. Abu-Dakka, and V. Kyrki, “Imitation learning-based framework for learning 6-d linear compliant motions,” *Autonomous Robots*, vol. 45, no. 3, pp. 389–405, 2021.
- [48] T. Hagos, M. Suomalainen, and V. Kyrki, “Segmenting and sequencing of compliant motions,” in *2018 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 6057–6064, IEEE, 2018.
- [49] F. J. Abu-Dakka, B. Nemeč, J. A. Jørgensen, T. R. Savarimuthu, N. Krüger, and A. Ude, “Adaptation of manipulation skills in physical contact with the environment to reference force profiles,” *Autonomous Robots*, vol. 39, no. 2, pp. 199–217, 2015.
- [50] A. Kramberger, A. Gams, B. Nemeč, C. Schou, D. Chrysostomou, O. Madsen, and A. Ude, “Transfer of contact skills to new environmental conditions,” in *2016 IEEE-RAS 16th International Conference on Humanoid Robotics (Humanoids)*, pp. 668–675, IEEE, 2016.
- [51] A. Kramberger, A. Gams, B. Nemeč, D. Chrysostomou, O. Madsen, and A. Ude, “Generalization of orientation trajectories and force-torque profiles for robotic assembly,” *Robotics and Autonomous Systems*, vol. 98, pp. 333–346, 2017.
- [52] F. J. Abu-Dakka, B. Nemeč, A. Kramberger, A. G. Buch, N. Krüger, and A. Ude, “Solving peg-in-hole tasks by human demonstration and exception strategies,” *Industrial Robot: An International Journal*, vol. 41, no. 6, pp. 575–584, 2014.
- [53] Z. Su, O. Kroemer, G. E. Loeb, G. S. Sukhatme, and S. Schaal, “Learning manipulation graphs from demonstrations using multimodal sensory signals,” in *2018 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 2758–2765, IEEE, 2018.
- [54] S. Hoppe, Z. Lou, D. Hennes, and M. Toussaint, “Planning approximate exploration trajectories for model-free reinforcement learning in contact-rich manipulation,” *IEEE Robotics and Automation Letters*, vol. 4, no. 4, pp. 4042–4047, 2019.

- [55] Q. Wang, J. De Schutter, W. Witvrouw, and S. Graves, “Derivation of compliant motion programs based on human demonstration,” in *Proceedings of IEEE International Conference on Robotics and Automation*, vol. 3, pp. 2616–2621, IEEE, 1996.
- [56] S. Scherzinger, A. Roennau, and R. Dillmann, “Contact skill imitation learning for robot-independent assembly programming,” in *2019 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 4309–4316, 2019.
- [57] W. Meeussen, J. Rutgeerts, K. Gadeyne, H. Bruyninckx, and J. De Schutter, “Contact-state segmentation using particle filters for programming by human demonstration in compliant-motion tasks,” *IEEE Transactions on Robotics*, vol. 23, no. 2, pp. 218–231, 2007.
- [58] Z. Su, O. Kroemer, G. E. Loeb, G. S. Sukhatme, and S. Schaal, “Learning to switch between sensorimotor primitives using multimodal haptic signals,” in *International Conference on Simulation of Adaptive Behavior*, pp. 170–182, Springer, 2016.
- [59] K. Van Wyk, M. Culleton, J. Falco, and K. Kelly, “Comparative peg-in-hole testing of a force-based manipulation controlled robotic hand,” *IEEE Transactions on Robotics*, vol. 34, no. 2, pp. 542–549, 2018.
- [60] C. C. Beltran-Hernandez, D. Petit, I. G. Ramirez-Alpizar, T. Nishi, S. Kikuchi, T. Matsubara, and K. Harada, “Learning force control for contact-rich manipulation tasks with rigid position-controlled robots,” *IEEE Robotics and Automation Letters*, vol. 5, no. 4, pp. 5709–5716, 2020.
- [61] K. Nottensteiner, F. Stulp, and A. Albu-Schäffer, “Robust, locally guided peg-in-hole using impedance-controlled robots,” in *2020 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 5771–5777, 2020.
- [62] I. F. Jasim, P. W. Plapper, and H. Voos, “Position identification in force-guided robotic peg-in-hole assembly tasks,” *Procedia Cirp*, vol. 23, pp. 217–222, 2014.
- [63] W. S. Newman, Y. Zhao, and Y.-H. Pao, “Interpretation of force and moment signals for compliant peg-in-hole assembly,” in *2001 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 571–576, 2001.

- [64] H. Park, J. Park, D.-H. Lee, J.-H. Park, and J.-H. Bae, “Compliant peg-in-hole assembly using partial spiral force trajectory with tilted peg posture,” *IEEE Robotics and Automation Letters*, vol. 5, no. 3, pp. 4447–4454, 2020.
- [65] B. Nemeč, M. Simonič, and A. Ude, “Learning of exception strategies in assembly tasks,” in *2018 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 865–872, IEEE, 2018.
- [66] Z. Wu, W. Lian, V. Unhelkar, M. Tomizuka, and S. Schaal, “Learning dense rewards for contact-rich manipulation tasks,” 2020.
- [67] S. A. Khader, H. Yin, P. Falco, and D. Kragic, “Stability-guaranteed reinforcement learning for contact-rich manipulation,” *IEEE Robotics and Automation Letters*, vol. 6, no. 1, pp. 1–8, 2020.
- [68] L. Shao, T. Migimatsu, and J. Bohg, “Learning to scaffold the development of robotic manipulation skills,” in *2020 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 5671–5677, IEEE, 2020.
- [69] J. Luo, E. Solowjow, C. Wen, J. A. Ojea, A. M. Agogino, A. Tamar, and P. Abbeel, “Reinforcement learning on variable impedance controller for high-precision robotic assembly,” in *2019 International Conference on Robotics and Automation (ICRA)*, pp. 3080–3087, IEEE, 2019.
- [70] M. Kaspar, J. D. Muñoz Osorio, and J. Bock, “Sim2real transfer for reinforcement learning without dynamics randomization,” in *2020 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 4383–4388, 2020.
- [71] Y. Ma, D. Xu, and F. Qin, “Efficient insertion control for precision assembly based on demonstration learning and reinforcement learning,” *IEEE Transactions on Industrial Informatics*, vol. 17, no. 7, pp. 4492–4502, 2021.
- [72] M. Oikawa, T. Kusakabe, K. Kutsuzawa, S. Sakaino, and T. Tsuji, “Reinforcement learning for robotic assembly using non-diagonal stiffness matrix,” *IEEE Robotics and Automation Letters*, vol. 6, no. 2, pp. 2737–2744, 2021.
- [73] F. Wirnshofer, P. S. Schmitt, P. Meister, G. v. Wichert, and W. Burgard, “Robust, compliant assembly with elastic parts and model uncertainty,”

- in *2019 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 6044–6051, IEEE, 2019.
- [74] A. Pervez, Y. Mao, and D. Lee, “Learning deep movement primitives using convolutional neural networks,” in *2017 IEEE-RAS 17th International Conference on Humanoid Robotics (Humanoids)*, 2017.
- [75] D. Almeida and Y. Karayiannidis, “Folding assembly by means of dual-arm robotic manipulation,” in *2016 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 3987–3993, IEEE, 2016.
- [76] A. Stolt, M. Linderöth, A. Robertsson, and R. Johansson, “Force controlled assembly of emergency stop button,” in *2011 IEEE International Conference on Robotics and Automation*, pp. 3751–3756, IEEE, 2011.
- [77] Y. Hayami, W. Wan, K. Koyama, P. Shi, J. Rojas, and K. Harada, “Error identification and recovery in robotic snap assembly,” in *2021 IEEE/SICE International Symposium on System Integration (SII)*, pp. 46–53, IEEE, 2021.
- [78] R. Zollner, T. Asfour, and R. Dillmann, “Programming by demonstration: Dual-arm manipulation tasks for humanoid robots,” in *2004 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)(IEEE Cat. No. 04CH37566)*, vol. 1, pp. 479–484, IEEE, 2004.
- [79] A. Carrera, N. Palomeras, N. Hurtós, P. Kormushev, and M. Carreras, “Learning multiple strategies to perform a valve turning with underwater currents using an i-auv,” in *OCEANS 2015-Genova*, pp. 1–8, IEEE, 2015.
- [80] A. K. Tanwani and S. Calinon, “Learning robot manipulation tasks with task-parameterized semitied hidden semi-markov model,” *IEEE Robotics and Automation Letters*, vol. 1, no. 1, pp. 235–242, 2016.
- [81] G. Niemeyer and J.-J. Slotine, “A simple strategy for opening an unknown door,” in *IEEE International Conference on Robotics and Automation*, vol. 2, pp. 1448–1453, apr 1997.
- [82] E. Lutscher and G. Cheng, “A set-point-generator for indirect-force-controlled manipulators operating unknown constrained mechanisms,” in *2012 IEEE/RSJ International Conference on Intelligent Robots and Systems*, pp. 4072–4077, 2012.

- [83] E. Lutscher, M. Lawitzky, G. Cheng, and S. Hirche, “A control strategy for operating unknown constrained mechanisms,” in *IEEE International Conference on Robotics and Automation*, pp. 819–824, may 2010.
- [84] Y. Karayiannidis, C. Smith, F. E. Vina, P. Ogren, and D. Kragic, ““open sesame!” adaptive force/velocity control for opening unknown doors,” in *2012 IEEE/RSJ International Conference on Intelligent Robots and Systems*, pp. 4040–4047, IEEE, 2012.
- [85] Y. Karayiannidis, C. Smith, F. E. Vina, P. Ögren, and D. Kragic, “Model-free robot manipulation of doors and drawers by means of fixed-grasps,” in *2013 IEEE International Conference on Robotics and Automation*, pp. 4485–4492, IEEE, 2013.
- [86] Y. Karayiannidis, C. Smith, F. E. V. Barrientos, P. Ögren, and D. Kragic, “An adaptive control approach for opening doors and drawers under uncertainties,” *IEEE Transactions on Robotics*, vol. 32, no. 1, pp. 161–175, 2016.
- [87] B. Nemeč, L. Žlajpah, and A. Ude, “Door opening by joining reinforcement learning and intelligent control,” in *2017 18th International Conference on Advanced Robotics (ICAR)*, pp. 222–228, 2017.
- [88] S. Dadhich, *A survey in automation of earth-moving machines*. Luleå tekniska universitet, 2015.
- [89] G. J. Maeda, D. C. Rye, and S. P. Singh, “Iterative autonomous excavation,” in *Field and service robotics*, pp. 369–382, Springer, 2014.
- [90] D. Jud, G. Hottiger, P. Leemann, and M. Hutter, “Planning and control for autonomous excavation,” *IEEE Robotics and Automation Letters*, vol. 2, no. 4, pp. 2151–2158, 2017.
- [91] A. A. Dobson, J. A. Marshall, and J. Larsson, “Admittance control for robotic loading: Underground field trials with an lhd,” in *Field and Service Robotics*, pp. 487–500, Springer, 2016.
- [92] J. A. Marshall, P. F. Murphy, and L. K. Daneshmend, “Toward autonomous excavation of fragmented rock: full-scale experiments,” *IEEE Transactions on Automation Science and Engineering*, vol. 5, no. 3, pp. 562–566, 2008.
- [93] P. Egli and M. Hutter, “Towards rl-based hydraulic excavator automation,” in *IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS 2020)*, 2020.

- [94] M. Suomalainen, J. Koivumäki, S. Lampinen, J. Mattila, and V. Kyrki, “Learning from demonstration for hydraulic manipulators,” in *2018 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 3579–3586, IEEE, 2018.
- [95] M. Khoramshahi, G. Henriks, A. Naef, S. S. M. Salehian, J. Kim, and A. Billard, “Arm-hand motion-force coordination for physical interactions with non-flat surfaces using dynamical systems: Toward compliant robotic massage,” 2020.
- [96] J. Yuan, N. Häni, and V. Isler, “Multi-step recurrent q-learning for robotic velcro peeling,” in *2021 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 6657–6663, IEEE, 2021.
- [97] V. Koropouli, D. Lee, and S. Hirche, “Learning interaction control policies by demonstration,” in *2011 IEEE/RSJ International Conference on Intelligent Robots and Systems*, pp. 344–349, IEEE, 2011.
- [98] Y. Karayiannidis, C. Smith, F. E. Vina, and D. Kragic, “Online contact point estimation for uncalibrated tool use,” in *2014 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 2488–2494, IEEE, 2014.
- [99] S. Calinon, I. Sardellitti, and D. G. Caldwell, “Learning-based control strategy for safe human-robot interaction exploiting task and robot redundancies,” in *2010 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 249–254, IEEE, 2010.
- [100] L. Rozo Castañeda, S. Calinon, D. Caldwell, P. Jimenez Schlegl, and C. Torras, “Learning collaborative impedance-based robot behaviors,” in *Proceedings of the Twenty-Seventh AAAI Conference on Artificial Intelligence*, pp. 1422–1428, 2013.
- [101] K. Kronander and A. Billard, “Learning compliant manipulation through kinesthetic and tactile human-robot interaction,” *IEEE Transactions on Haptics*, vol. 7, no. 3, pp. 367–380, 2014.
- [102] F. J. Abu-Dakka, L. Rozo, and D. G. Caldwell, “Force-based variable impedance learning for robotic manipulation,” *Robotics and Autonomous Systems*, vol. 109, pp. 156–167, 2018.
- [103] K. Kronander and A. Billard, “Online learning of varying stiffness through physical human-robot interaction,” in *2012 IEEE International*

- Conference on Robotics and Automation (ICRA)*, pp. 1842–1849, IEEE, 2012.
- [104] G. M. Gasparri, F. Fabiani, M. Garabini, L. Pallottino, M. Catalano, G. Grioli, R. Persichin, and A. Bicchi, “Robust optimization of system compliance for physical interaction in uncertain scenarios,” in *2016 IEEE-RAS 16th International Conference on Humanoid Robotics (Humanoids)*, pp. 911–918, IEEE, 2016.
- [105] E. Gribovskaya, A. Kheddar, and A. Billard, “Motion learning and adaptive impedance for robot control during physical interaction with humans,” in *2011 IEEE International Conference on Robotics and Automation*, pp. 4326–4332, IEEE, 2011.
- [106] B. Nemeč, N. Likar, A. Gams, and A. Ude, “Human robot cooperation with compliance adaptation along the motion trajectory,” *Autonomous robots*, vol. 42, no. 5, pp. 1023–1035, 2018.
- [107] A. L. P. Ureche, K. Umezawa, Y. Nakamura, and A. Billard, “Task parameterization using continuous constraints extracted from human demonstrations,” *IEEE Transactions on Robotics*, vol. 6, no. 31, pp. 1458–1471, 2015.
- [108] J. Lee, P. H. Chang, and R. S. Jamisola, “Relative impedance control for dual-arm robots performing asymmetric bimanual tasks,” *IEEE transactions on industrial electronics*, vol. 61, no. 7, pp. 3786–3796, 2013.
- [109] L. Peternel, L. Rozo, D. Caldwell, and A. Ajoudani, “A method for derivation of robot task-frame control authority from repeated sensory observations,” *IEEE Robotics and Automation Letters*, vol. 2, no. 2, pp. 719–726, 2017.
- [110] K. K. Babarahmati, C. Tiseo, Q. Rouxel, Z. Li, and M. Mistry, “Robust and dexterous dual-arm tele-cooperation using fractal impedance control,” *arXiv preprint arXiv:2108.04567*, 2021.
- [111] J. Koivumäki and J. Mattila, “High performance nonlinear motion/force controller design for redundant hydraulic construction crane automation,” *Automation in construction*, vol. 51, pp. 59–77, 2015.
- [112] J. Koivumäki and J. Mattila, “Stability-guaranteed impedance control of hydraulic robotic manipulators,” *IEEE/ASME Transactions on Mechatronics*, vol. 22, no. 2, pp. 601–612, 2017.

- [113] D. E. Whitney, “Quasi-static assembly of compliantly supported rigid parts,” *Journal of Dynamic Systems, Measurement, and Control*, vol. 104, no. 1, pp. 65–77, 1982.
- [114] L. B. Chernyakhovskaya and D. A. Simakov, “Peg-on-hole: mathematical investigation of motion of a peg and of forces of its interaction with a vertically fixed hole during their alignment with a three-point contact,” *The International Journal of Advanced Manufacturing Technology*, vol. 107, no. 1, pp. 689–704, 2020.
- [115] M. T. Mason, “Compliance and force control for computer controlled manipulators,” *IEEE Transactions on Systems, Man, and Cybernetics*, vol. 11, no. 6, pp. 418–432, 1981.
- [116] J. M. Schimmels and M. A. Peshkin, “Force-assemblability: Insertion of a workpiece into a fixture guided by contact forces alone,” in *1991 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 1296–1301, IEEE, 1991.
- [117] K. Yu and K. Goldberg, “Fixture loading with sensor-based motion plans,” in *Proceedings of the 1995 IEEE International Symposium on Assembly and Task Planning*, pp. 362–367, IEEE, 1995.
- [118] K. Yu and K. Y. Goldberg, “A complete algorithm for fixture loading,” *The International Journal of Robotics Research*, vol. 17, no. 11, pp. 1214–1224, 1998.
- [119] T. Lozano-Perez, M. T. Mason, and R. H. Taylor, “Automatic synthesis of fine-motion strategies for robots,” *The International Journal of Robotics Research*, vol. 3, no. 1, pp. 3–24, 1984.
- [120] J. De Schutter, H. Bruyninckx, S. Dutré, J. De Geeter, J. Katupitiya, S. Demey, and T. Lefebvre, “Estimating first-order geometric parameters and monitoring contact transitions during force-controlled compliant motion,” *The International Journal of Robotics Research*, vol. 18, no. 12, pp. 1161–1184, 1999.
- [121] F. Wirnshofer, P. S. Schmitt, P. Meister, G. v. Wichert, and W. Burgard, “State estimation in contact-rich manipulation,” in *2019 International Conference on Robotics and Automation (ICRA)*, pp. 3790–3796, 2019.
- [122] B. Belousov, B. Wibranek, J. Schneider, T. Schneider, G. Chalvatzaki, J. Peters, and O. Tessmann, “Robotic architectural assembly with tactile

- skills: Simulation and optimization,” *Automation in Construction*, vol. 133, p. 104006, 2022.
- [123] A. Salem and Y. Karayiannidis, “Robotic assembly of rounded parts with and without threads,” *IEEE Robotics and Automation Letters*, vol. 5, no. 2, pp. 2467–2474, 2020.
- [124] J. Canny and J. Reif, “New lower bound techniques for robot motion planning problems,” in *Foundations of Computer Science, 1987., 28th Annual Symposium on*, pp. 49–60, IEEE, 1987.
- [125] C. Guan, W. Vega-Brown, and N. Roy, “Efficient planning for near-optimal compliant manipulation leveraging environmental contact,” in *2018 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 215–222, IEEE, 2018.
- [126] A. Ajay, J. Wu, N. Fazeli, M. Bauza, L. P. Kaelbling, J. B. Tenenbaum, and A. Rodriguez, “Augmenting physical simulators with stochastic neural networks: Case study of planar pushing and bouncing,” in *2018 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 3066–3073, IEEE, 2018.
- [127] J. D. Schutter and H. V. Brussel, “Compliant robot motion i. a formalism for specifying compliant motion tasks,” *The International Journal of Robotics Research*, vol. 7, no. 4, pp. 3–17, 1988.
- [128] T. Yoshikawa and A. Sudou, “Dynamic hybrid position/force control of robot manipulators-on-line estimation of unknown constraint,” *IEEE Transactions on Robotics and Automation*, vol. 9, no. 2, pp. 220–226, 1993.
- [129] R. Martín-Martín and O. Brock, “Coupled recursive estimation for online interactive perception of articulated objects,” *The International Journal of Robotics Research*, vol. 0, no. 0, p. 0278364919848850, 0.
- [130] C. Smith, Y. Karayiannidis, L. Nalpantidis, X. Gratal, P. Qi, D. V. Dimarogonas, and D. Kragic, “Dual arm manipulation—a survey,” *Robotics and Autonomous systems*, vol. 60, no. 10, pp. 1340–1353, 2012.
- [131] Y. Yamada, S. Nagamatsu, and Y. Sato, “Development of multi-arm robots for automobile assembly,” in *1995 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 2224–2229, IEEE, 1995.

- [132] O. Kroemer, H. Van Hoof, G. Neumann, and J. Peters, “Learning to predict phases of manipulation tasks as hidden states,” in *2014 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 4009–4014, IEEE, 2014.
- [133] R. L. A. Shauri and K. Nonami, “Assembly manipulation of small objects by dual-arm manipulator,” *Assembly Automation*, vol. 31, no. 3, pp. 263–274, 2011.
- [134] D. Almeida and Y. Karayiannidis, “Cooperative manipulation and identification of a 2-dof articulated object by a dual-arm robot,” in *2018 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 5445–5451, 2018.
- [135] N. Hogan, “Impedance control: An approach to manipulation: Part ii—implementation,” *Journal of dynamic systems, measurement, and control*, vol. 107, no. 1, pp. 8–16, 1985.
- [136] D. E. Whitney, “Force Feedback Control of Manipulator Fine Motions,” *Journal of Dynamic Systems, Measurement, and Control*, vol. 99, pp. 91–97, 06 1977.
- [137] D. E. Whitney, “Historical perspective and state of the art in robot force control,” in *1985 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 262–268, IEEE, 1985.
- [138] J. Roy and L. Whitcomb, “Adaptive force control of position/velocity controlled robots: theory and experiment,” *IEEE Transactions on Robotics and Automation*, vol. 18, no. 2, pp. 121–137, 2002.
- [139] E. Colgate and N. Hogan, “An analysis of contact instability in terms of passive physical equivalents,” in *Proceedings, 1989 international conference on robotics and automation*, pp. 404–409, IEEE, 1989.
- [140] A. Stolt, M. Linderoth, A. Robertsson, and R. Johansson, “Force controlled robotic assembly without a force sensor,” in *2012 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 1538–1543, IEEE, 2012.
- [141] J. Koivumäki and J. Mattila, “Stability-guaranteed force-sensorless contact force/motion control of heavy-duty hydraulic manipulators,” *IEEE Transactions on Robotics*, vol. 31, no. 4, pp. 918–935, 2015.

- [142] K. Kronander and A. Billard, “Stability considerations for variable impedance control,” *IEEE Transactions on Robotics*, vol. 32, no. 5, pp. 1298–1305, 2016.
- [143] E. Shahriari, A. Kramberger, A. Gams, A. Ude, and S. Haddadin, “Adapting to contacts: Energy tanks and task energy for passivity-based dynamic movement primitives,” in *2017 IEEE-RAS 17th International Conference on Humanoid Robotics (Humanoids)*, pp. 136–142, IEEE, 2017.
- [144] E. Shahriari, L. Johannsmeier, E. Jensen, and S. Haddadin, “Power flow regulation, adaptation, and learning for intrinsically robust virtual energy tanks,” *IEEE Robotics and Automation Letters*, vol. 5, no. 1, pp. 211–218, 2019.
- [145] K. Kronander and A. Billard, “Passive interaction control with dynamical systems,” *IEEE Robotics and Automation Letters*, vol. 1, no. 1, pp. 106–113, 2016.
- [146] F. Ferraguti, C. Secchi, and C. Fantuzzi, “A tank-based approach to impedance control with variable stiffness,” in *2013 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 4948–4953, IEEE, 2013.
- [147] M. Bednarczyk, H. Omran, and B. Bayle, “Passivity filter for variable impedance control,” in *2020 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 7159–7164, IEEE, 2020.
- [148] L. Roveda, M. Magni, M. Cantoni, D. Piga, and G. Bucca, “Assembly task learning and optimization through human’s demonstration and machine learning,” in *2020 IEEE International Conference on Systems, Man, and Cybernetics (SMC)*, pp. 1852–1859, IEEE, 2020.
- [149] H. Seraji, “Adaptive admittance control: an approach to explicit force control in compliant motion,” in *1994 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 2705–2712, IEEE, 1994.
- [150] J. Schimmels and M. Peshkin, “Admittance matrix design for force-guided assembly,” *IEEE Transactions on Robotics and Automation*, vol. 8, no. 2, pp. 213–227, 1992.
- [151] I. Mitsioni, Y. Karayiannidis, and D. Kragic, “Modelling and learning dynamics for robotic food-cutting,” in *2021 IEEE 17th International Conference on Automation Science and Engineering (CASE21)*, 2021.

- [152] A. Q. Keemink, H. van der Kooij, and A. H. Stienen, “Admittance control for physical human–robot interaction,” *The International Journal of Robotics Research*, vol. 37, no. 11, pp. 1421–1444, 2018.
- [153] C. T. Landi, F. Ferraguti, L. Sabattini, C. Secchi, and C. Fantuzzi, “Admittance control parameter adaptation for physical human-robot interaction,” in *2017 IEEE international conference on robotics and automation (ICRA)*, pp. 2911–2916, IEEE, 2017.
- [154] F. Ferraguti, C. Talignani Landi, L. Sabattini, M. Bonfè, C. Fantuzzi, and C. Secchi, “A variable admittance control strategy for stable physical human–robot interaction,” *The International Journal of Robotics Research*, vol. 38, no. 6, pp. 747–765, 2019.
- [155] A.-N. Sharkawy, P. N. Koustournpardis, and N. Aspragathos, “Variable admittance control for human-robot collaboration based on online neural network training,” in *2018 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 1334–1339, IEEE, 2018.
- [156] A. Gams, B. Nemec, A. J. Ijspeert, and A. Ude, “Coupling movement primitives: Interaction with the environment and bimanual tasks,” *IEEE Transactions on Robotics*, vol. 30, no. 4, pp. 816–830, 2014.
- [157] M. Deniša, A. Gams, A. Ude, and T. Petrič, “Learning compliant movement primitives through demonstration and statistical generalization,” *IEEE/ASME Transactions on Mechatronics*, vol. 21, no. 5, pp. 2581–2594, 2016.
- [158] T. Petrič, A. Gams, L. Colasanto, A. J. Ijspeert, and A. Ude, “Accelerated sensorimotor learning of compliant movement primitives,” *IEEE Transactions on Robotics*, vol. 34, pp. 1636–1642, 2018.
- [159] M. Tykal, A. Montebelli, and V. Kyrki, “Incrementally assisted kinesthetic teaching for programming by demonstration,” in *Proceedings of the 2016 ACM/IEEE International Conference on Human-Robot Interaction (HRI)*, pp. 205–212, IEEE Press, 2016.
- [160] L. Rozo, D. Bruno, S. Calinon, and D. G. Caldwell, “Learning optimal controllers in human-robot cooperative transportation tasks with position and force constraints,” in *2015 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 1024–1030, IEEE, 2015.
- [161] N. Figueroa, A. L. P. Ureche, and A. Billard, “Learning complex sequential tasks from demonstration: A pizza dough rolling case study,”

- in *Proceedings of the 2016 ACM/IEEE International Conference on Human-Robot Interaction (HRI)*, pp. 611–612, IEEE, 2016.
- [162] O. Kroemer, C. Daniel, G. Neumann, H. Van Hoof, and J. Peters, “Towards learning hierarchical skills for multi-phase manipulation tasks,” in *2015 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 1503–1510, IEEE, 2015.
- [163] N. Figueroa and A. Billard, “Transform-invariant non-parametric clustering of covariance matrices and its application to unsupervised joint segmentation and action discovery,” *arXiv preprint arXiv:1710.10060*, 2017.
- [164] M. Racca, J. Pajarinen, A. Montebelli, and V. Kyrki, “Learning in-contact control strategies from demonstration,” in *2016 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 688–695, IEEE, 2016.
- [165] E. Di Lello, T. De Laet, and H. Bruyninckx, “Hierarchical dirichlet process hidden markov models for abnormality detection in robotic assembly,” in *Neural Information Processing Systems, Date: 2012/12/03-2012/12/08, Location: Lake Tahoe, Nevada*, 2012.
- [166] A. T. Le, M. Guo, N. van Duijkeren, L. Rozo, R. Krug, A. G. Kupcsik, and M. Buerger, “Learning forceful manipulation skills from multi-modal human demonstrations,” *arXiv preprint arXiv:2109.04222*, 2021.
- [167] C. Phillips-Grafflin and D. Berenson, “Planning and resilient execution of policies for manipulation in contact with actuation uncertainty,” in *Workshop on the Algorithmic Foundations of Robotics (WAFR)*, 2016.
- [168] M. Koval, N. Pollard, and S. Srinivasa, “Pre- and post-contact policy decomposition for planar contact manipulation under uncertainty,” *The International Journal of Robotics Research*, vol. 35, no. 1–3, pp. 244–264, 2016.
- [169] A. Sieverling, C. Eppner, F. Wolff, and O. Brock, “Interleaving motion in contact and in free space for planning under uncertainty,” in *IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 4011–4017, 2017.
- [170] M. Toussaint, N. Ratliff, J. Bohg, L. Righetti, P. Englert, and S. Schaal, “Dual execution of optimized contact interaction trajectories,” in *2014*

- IEEE/RSJ International Conference on Intelligent Robots and Systems*, pp. 47–54, IEEE, 2014.
- [171] G. P. L. De Chambrier, *Learning Search Strategies from Human Demonstrations*. PhD thesis, École polytechnique fédérale de Lausanne (EPFL), 2016.
- [172] G. de Chambrier and A. Billard, “Learning search behaviour from humans,” in *2013 IEEE International Conference on Robotics and Biomimetics (ROBIO)*, pp. 573–580, IEEE, 2013.
- [173] G. De Chambrier and A. Billard, “Learning search policies from humans in a partially observable context,” *Robotics and Biomimetics*, vol. 1, no. 1, p. 8, 2014.
- [174] S. Levine, N. Wagener, and P. Abbeel, “Learning contact-rich manipulation skills with guided policy search,” in *2015 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 156–163, IEEE, 2015.
- [175] K. Arndt, A. Ghadirzadeh, M. Hazara, and V. Kyrki, “Few-shot model-based adaptation in noisy conditions,” *IEEE Robotics and Automation Letters*, vol. 6, no. 2, pp. 4193–4200, 2021.
- [176] R. Van Parys and G. Pipeleers, “Spline-based motion planning in an obstructed 3d environment,” *IFAC-PapersOnLine*, vol. 50, no. 1, pp. 8668–8673, 2017.
- [177] S. Schaal, *Dynamic movement primitives-a framework for motor control in humans and humanoid robotics*, pp. 261–280. Springer, 2006.
- [178] R. L. Hardy, “Multiquadric equations of topography and other irregular surfaces,” *Journal of geophysical research*, vol. 76, no. 8, pp. 1905–1915, 1971.
- [179] A. Paraschos, E. Rueckert, J. Peters, and G. Neumann, “Model-free probabilistic movement primitives for physical interaction,” in *2015 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 2860–2866, IEEE, 2015.
- [180] Y. Huang, L. Rozo, J. Silvério, and D. G. Caldwell, “Kernelized movement primitives,” *The International Journal of Robotics Research*, vol. 38, no. 7, pp. 833–852, 2019.

- [181] S. Calinon, F. Guenter, and A. Billard, “On learning, representing, and generalizing a task in a humanoid robot,” *IEEE Transactions on Systems, Man, and Cybernetics, Part B (Cybernetics)*, vol. 37, no. 2, pp. 286–298, 2007.
- [182] S. Calinon, “A tutorial on task-parameterized movement learning and retrieval,” *Intelligent service robotics*, vol. 9, no. 1, pp. 1–29, 2016.
- [183] S. M. Khansari-Zadeh and A. Billard, “Learning stable nonlinear dynamical systems with gaussian mixture models,” *IEEE Transactions on Robotics*, vol. 27, no. 5, pp. 943–957, 2011.
- [184] S. M. Khansari-Zadeh and O. Khatib, “Learning potential functions from human demonstrations with encapsulated dynamic and compliant behaviors,” *Autonomous Robots*, vol. 41, no. 1, pp. 45–69, 2017.
- [185] R. Tedrake, “Lqr-trees: Feedback motion planning on sparse randomized trees,” in *Proceedings of Robotics: Science and Systems*, 2009.
- [186] G. Konidaris, S. Kuindersma, R. Grupen, and A. Barto, “Robot learning from demonstration by constructing skill trees,” *The International Journal of Robotics Research*, vol. 31, no. 3, pp. 360–375, 2012.
- [187] S. Alartartsev, S. Stellmacher, and F. Ortmeier, “Robotic task sequencing problem: A survey,” *Journal of Intelligent & Robotic Systems*, vol. 80, no. 2, pp. 279–298, 2015.
- [188] T. Eiband and D. Lee, “Identification of common force-based robot skills from the human and robot perspective,” in *2020 IEEE-RAS 20th International Conference on Humanoid Robots (Humanoids)*, pp. 507–513, IEEE, 2021.
- [189] A. Stolt, M. Linderoth, A. Robertsson, and R. Johansson, “Detection of contact force transients in robotic assembly,” in *2015 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 962–968, IEEE, 2015.
- [190] P. M. Will and D. D. Grossman, “An experimental system for computer controlled mechanical assembly,” *IEEE Transactions on computers*, vol. 9, pp. 879–888, 1975.
- [191] H. Inoue, “Force feedback in precise assembly tasks,” 1974.

- [192] M. Stenmark, J. Malec, and A. Stolt, “From high-level task descriptions to executable robot code,” in *Intelligent Systems’ 2014*, pp. 189–202, Springer, 2015.
- [193] M. Karlsson, A. Robertsson, and R. Johansson, “Detection and control of contact force transients in robotic manipulation without a force sensor,” in *2018 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 21–25, 2018.
- [194] X. Cheng, E. Huang, Y. Hou, and M. T. Mason, “Contact mode guided motion planning for dexterous manipulation,” *arXiv preprint arXiv:2105.14431*, 2021.
- [195] G. E. Hovland, P. Sikka, and B. J. McCarragher, “Skill acquisition from human demonstration using a hidden markov model,” in *1996 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 2706–2711, IEEE, 1996.
- [196] S. Niekum, S. Osentoski, G. Konidaris, and A. G. Barto, “Learning and generalization of complex tasks from unstructured demonstrations,” in *2012 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 5239–5246, IEEE, 2012.
- [197] S. Niekum, S. Osentoski, G. Konidaris, S. Chitta, B. Marthi, and A. G. Barto, “Learning grounded finite-state representations from unstructured demonstrations,” *The International Journal of Robotics Research*, vol. 34, no. 2, pp. 131–157, 2015.
- [198] S. Niekum and S. Chitta, “Incremental semantically grounded learning from demonstration.” in *Proceedings of Robotics: Science and Systems*, 2013.
- [199] A. Rodriguez, D. Bourne, M. Mason, G. F. Rossano, and J. Wang, “Failure detection in assembly: Force signature analysis,” in *2010 IEEE International Conference on Automation Science and Engineering*, pp. 210–215, IEEE, 2010.
- [200] K. J. A. Kronander, *Control and Learning of Compliant Manipulation Skills*. PhD thesis, École polytechnique fédérale de Lausanne (EPFL), 2015.
- [201] M. Erdmann and M. T. Mason, “An exploration of sensorless manipulation,” *IEEE Journal of Robotics and Automation*, vol. 4, pp. 369 – 379, August 1988.

- [202] A. Stolt, *On Robotic Assembly using Contact Force Control and Estimation*. PhD thesis, Lund University, 2015.
- [203] E. Páll, A. Sieverling, and O. Brock, “Contingent contact-based motion planning,” in *2018 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 6615–6621, IEEE, 2018.
- [204] K. Gadeyne, T. Lefebvre, and H. Bruyninckx, “Bayesian hybrid model-state estimation applied to simultaneous contact formation recognition and geometrical parameter estimation,” *The International Journal of Robotics Research*, vol. 24, no. 8, pp. 615–630, 2005.
- [205] T. Lefebvre, H. Bruyninckx, and J. De Schutter, “Online statistical model recognition and state estimation for autonomous compliant motion,” *IEEE Transactions on Systems, Man, and Cybernetics, Part C (Applications and Reviews)*, vol. 35, no. 1, pp. 16–29, 2005.
- [206] T. Lefebvre, H. Bruyninckx, and J. De Schutter, “Polyhedral contact formation identification for autonomous compliant motion: Exact non-linear bayesian filtering,” *IEEE Transactions on Robotics*, vol. 21, no. 1, pp. 124–129, 2005.
- [207] M. Baum, M. Bernstein, R. Martin-Martin, S. Höfer, J. Kulick, M. Toussaint, A. Kacelnik, and O. Brock, “Opening a lockbox through physical exploration,” in *2017 IEEE-RAS 17th International Conference on Humanoid Robotics (Humanoids)*, pp. 461–467, IEEE, 2017.
- [208] Xuerong Ji and Jing Xiao, “Planning motion compliant to complex contact states,” in *IEEE International Conference on Robotics and Automation (ICRA)*, vol. 2, pp. 1512–1517 vol.2, 2001.
- [209] N. Chavan-Daffe, R. Holladay, and A. Rodriguez, “Planar in-hand manipulation via motion cones,” *The International Journal of Robotics Research (IJRR)*, vol. 39, no. 2-3, pp. 163–182, 2020.
- [210] F. Wirnshofer, P. S. Schmitt, W. Feiten, G. v. Wichert, and W. Burgard, “Robust, compliant assembly via optimal belief space planning,” in *2018 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 5436–5443, IEEE, 2018.
- [211] E. Valassakis, Z. Ding, and E. Johns, “Crossing the gap: A deep dive into zero-shot sim-to-real transfer for dynamics,” in *2020 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 5372–5379, IEEE.

- [212] M. Kalakrishnan, L. Righetti, P. Pastor, and S. Schaal, “Learning force control policies for compliant manipulation,” in *2011 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 4639–4644, IEEE, 2011.
- [213] C.-Y. Kuo, A. Schaarschmidt, Y. Cui, T. Asfour, and T. Matsubara, “Uncertainty-aware contact-safe model-based reinforcement learning,” *IEEE Robotics and Automation Letters*, vol. 6, no. 2, pp. 3918–3925, 2021.
- [214] Y. Wang, C. C. Beltran-Hernandez, W. Wan, and K. Harada, “Hybrid trajectory and force learning of complex assembly tasks: A combined learning framework,” *IEEE Access*, 2021.
- [215] M. Bogdanovic, M. Khadiv, and L. Righetti, “Learning variable impedance control for contact sensitive tasks,” *IEEE Robotics and Automation Letters*, vol. 5, no. 4, pp. 6129–6136, 2020.
- [216] R. Martín-Martín, M. A. Lee, R. Gardner, S. Savarese, J. Bohg, and A. Garg, “Variable impedance control in end-effector space: An action space for reinforcement learning in contact-rich tasks,” in *2019 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 1010–1017, IEEE, 2019.
- [217] P. Kulkarni, J. Kober, R. Babuška, and C. Della Santina, “Learning assembly tasks in a few minutes by combining impedance control and residual recurrent reinforcement learning,” *Advanced Intelligent Systems*, p. 2100095, 2021.
- [218] J. Canny, “On computability of fine motion plans,” in *ICRA*, May 1989.
- [219] M. Erdmann, “Using backprojections for fine motion planning with uncertainty,” *IJRR*, vol. 5, no. 1, pp. 19–45, 1986.
- [220] T. Siméon, J.-P. Laumond, J. Cortés, and A. Sahbani, “Manipulation planning with probabilistic roadmaps,” *The International Journal of Robotics Research (IJRR)*, vol. 23, no. 7-8, pp. 729–746, 2004.
- [221] R. S. Sutton and A. G. Barto, *Reinforcement learning: An introduction*. MIT press, 2018.
- [222] L. Peternel, T. Petrič, and J. Babič, “Human-in-the-loop approach for teaching robot assembly tasks using impedance control interface,” in *2015 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 1497–1502, IEEE, 2015.

- [223] L. Peternel, T. Petrič, and J. Babič, “Robotic assembly solution by human-in-the-loop teaching method based on real-time stiffness modulation,” *Autonomous Robots*, vol. 42, no. 1, pp. 1–17, 2018.
- [224] M. Hagenow, B. Zhang, B. Mutlu, M. Zinn, and M. Gleicher, “Recognizing orientation slip in human demonstrations,” in *2021 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 2790–2797, IEEE, 2021.
- [225] R. Lioutikov, G. Neumann, G. Maeda, and J. Peters, “Probabilistic segmentation applied to an assembly task,” in *2015 IEEE-RAS 15th International Conference on Humanoid Robotics (Humanoids)*, pp. 533–540, IEEE, 2015.
- [226] R. Lioutikov, G. Neumann, G. Maeda, and J. Peters, “Learning movement primitive libraries through probabilistic segmentation,” *The International Journal of Robotics Research*, vol. 36, no. 8, pp. 879–894, 2017.
- [227] A. Sena, Y. Zhao, and M. J. Howard, “Teaching human teachers to teach robot learners,” in *2018 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 5675–5681, IEEE, 2018.
- [228] A. Sena and M. J. Howard, “Quantifying teaching behaviour in robot learning from demonstration,” *arXiv preprint arXiv:1905.04218*, 2019.
- [229] F. Dimeas and Z. Doulgeri, “Progressive automation of periodic tasks on planar surfaces of unknown pose with hybrid force/position control,” in *2020 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 5246–5252, IEEE, 2020.
- [230] C. Chao, M. Cakmak, and A. L. Thomaz, “Transparent active learning for robots,” in *Proceedings of the 2010 ACM/IEEE International Conference on Human-Robot Interaction (HRI)*, pp. 317–324, IEEE, 2010.
- [231] A. Bestick, R. Pandya, R. Bajcsy, and A. D. Dragan, “Learning human ergonomic preferences for handovers,” in *2018 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 3257–3264, IEEE, 2018.
- [232] G. Maeda, M. Ewerton, T. Osa, B. Busch, and J. Peters, “Active incremental learning of robot movement primitives,” in *Conference on Robot Learning*, pp. 37–46, PMLR, 2017.

- [233] C. Eppner, R. Deimel, J. Alvarez-Ruiz, M. Maertens, and O. Brock, “Exploitation of environmental constraints in human and robotic grasping,” *The International Journal of Robotics Research*, vol. 34, no. 7, pp. 1021–1038, 2015.
- [234] T. R. Savarimuthu, D. Liljekrans, L.-P. Ellekilde, A. Ude, B. Nemeč, and N. Kruger, “Analysis of human peg-in-hole executions in a robotic embodiment using uncertain grasps,” in *Robot Motion and Control (RoMoCo), 2013 9th Workshop on*, pp. 233–239, IEEE, 2013.
- [235] M. Guo and M. Bürger, “Geometric task networks: Learning efficient and explainable skill coordination for object manipulation,” *IEEE Transactions on Robotics*, 2021.
- [236] Y. Tsurumine, Y. Cui, E. Uchibe, and T. Matsubara, “Deep reinforcement learning with smooth policy update: Application to robotic cloth manipulation,” *Robotics and Autonomous Systems*, vol. 112, pp. 72–83, 2019.
- [237] J. Tobin, R. Fong, A. Ray, J. Schneider, W. Zaremba, and P. Abbeel, “Domain randomization for transferring deep neural networks from simulation to the real world,” in *2017 IEEE/RSJ international conference on intelligent robots and systems (IROS)*, pp. 23–30, IEEE, 2017.
- [238] J. S. Dyrstad, E. R. Øye, A. Stahl, and J. R. Mathiassen, “Teaching a robot to grasp real fish by imitation learning from a human supervisor in virtual reality,” in *2018 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 7185–7192, IEEE, 2018.
- [239] T. Zhang, Z. McCarthy, O. Jowl, D. Lee, X. Chen, K. Goldberg, and P. Abbeel, “Deep imitation learning for complex manipulation tasks from virtual reality teleoperation,” in *2018 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 5628–5635, IEEE, 2018.
- [240] T.-H. Pham, A. Kheddar, A. Qammaz, and A. A. Argyros, “Towards force sensing from vision: Observing hand-object interactions to infer manipulation forces,” in *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 2810–2819, 2015.
- [241] T.-H. Pham, N. Kyriazis, A. A. Argyros, and A. Kheddar, “Hand-object contact force estimation from markerless visual tracking,” *IEEE transactions on pattern analysis and machine intelligence*, vol. 40, no. 12, pp. 2883–2896, 2017.