

Speech Resources in the Tamasheq Language

Marcely Zanon Boito¹, Fethi Bougares², Florentin Barbier³, Souhir Gahbiche³,
Loïc Barrault², Mickael Rouvier¹, Yannick Estève¹

¹LIA - Avignon Université, France

²LIUM - Le Mans Université, France

³Airbus - France

contact: {marcely.zanon-boito, yannick.esteve}@univ-avignon.fr

Abstract

In this paper we present two datasets for Tamasheq, a developing language mainly spoken in Mali and Niger. These two datasets were made available for the IWSLT 2022 low-resource speech translation track, and they consist of collections of radio recordings from the Studio Kalangou (Niger) and Studio Tamani (Mali) daily broadcast news. We share (i) a massive amount of unlabeled audio data (671 hours) in five languages: French from Niger, Fulfulde, Hausa, Tamasheq and Zarma, and (ii) a smaller parallel corpus of audio recordings (17 hours) in Tamasheq, with utterance-level translations in the French language. All this data is shared under the Creative Commons BY-NC-ND 3.0 license. We hope these resources will inspire the speech community to develop and benchmark models using the Tamasheq language.

Keywords: speech corpus, speech translation, tamasheq, zarma, hausa, fulfulde, french

1. Introduction

The vast majority of speech pipelines are developed for and in *high-resource* languages, a small percentage of languages for which there is a large amount of annotated data freely available (Joshi et al., 2020). This not only limits the investigation of language impact in current pipelines, as the applied languages are usually from the same subset, but it also fails to reflect the real-world performance these approaches will have in diverse and smaller datasets.

In recent years, the IWSLT Challenge¹ introduced a low-resource speech translation track focused on developing and benchmarking translation tools for under-resourced languages. While for a vast majority of these languages, there is a lack of speech translation parallel data at the scale needed to train large translation models, in these cases we might still have access to limited disparate resources, such as word-level translations, small parallel text data, monolingual text, and raw audio. The *challenge* is then to leverage this data, in order to build effective systems under these realistic settings.

In this paper we present the resources in the Tamasheq language we share in the context of the IWSLT 2022: low-resource speech translation track. Tamasheq is a variety of Tuareg, a Berber macro-language spoken by nomadic tribes across North Africa in Algeria, Mali, Niger and Burkina Faso (Heath, 2006). It accounts for approximately 500,000 native speakers, being mostly spoken in Mali and Niger (Ethnologue: Languages of the World, 2021). We share a large audio corpus, made of 224 hours of Tamasheq, together with 417 hours in other four languages of Niger (French, Fulfulde, Hausa and Zarma). We also share a smaller corpus of 17 hours

of Tamasheq utterances aligned with French translations. We hope that these resources will represent an interesting use-case for the speech community, allowing them to not only develop low-resource speech systems in Tamasheq, but also to investigate the leveraging of unannotated audio data in diverse languages that co-exist in the same geographic region.

This paper is organized as follows. Section 2 presents the source content of the data shared: thanks to the *Fondation Hirondelle Initiative* and local partners, we are able to collect broadcast news in diverse African languages. Section 3 presents the small parallel corpus between Tamasheq and French, and Section 4 presents the collection of unannotated audio data in French from Niger, Fulfulde, Hausa, Tamasheq and Zarma. Finally, Section 5 presents a speech translation baseline model, and Section 6 concludes this work.

2. The source content: The Fondation Hirondelle Initiative

The Fondation Hirondelle² is a Swiss non-profit organization founded in 1995 by journalists, with the goal of supporting local independent media in areas of social unrest. They produce and broadcast information and dialogue programs in different countries, providing local partners with editorial, managerial and structural support and training to function in a sustainable manner.

In this work we focus on their daily news radio episodes, produced by local partners and broadcast by them in different languages. These allow the local communities to get informed in their own dialects, in contrast to mainstream media that tends to cover only the countries' official languages. For the Tamasheq lan-

¹<https://iwslt.org/2022/low-resource>

²<https://www.hirondelle.org/en/>

guage, we find these episodes being produced daily in Mali (Studio Tamani³) and Niger (Studio Kalangou⁴).

Speech Style and Quality. The radio episodes are recorded in local studios: for each episode, one or two hosts present some news, and often interviews and advertisements are included. Most of the speech correspond to good quality audio speech, with rare instances of background music during advertisements. For interviews, we notice some cases of overlapping speech, mainly when simultaneous translation is performed, and background noise such as outdoor sounds.

Audio Web-crawling. With the authorization of the Fondation Hironnelle and partners, we downloaded the .mp3 radio episodes by generating URLs from the local partners' main broadcast pages.⁵ The corpora presented in Section 3 and Section 4 use these audio files as source content.

3. The Tamasheq-French Parallel Corpus

This corpus corresponds to 17 hours of *controlled* speech segments, with manual translations to the French language. We also share a 2 hours longer version of this corpus, including potentially noisy speech segments. We detail below the steps for creating this corpus, and present some general statistics.

1. Data downloading. A total of 100 radio episodes were downloaded from the Studio Kalangou website in February 2019: 23 episodes from 2016, 36 episodes from 2017 and 2018, and 5 episodes from 2019. This results in 25 hours of raw speech, with an average duration of 14.97 minutes.

2. Translation Process. We commissioned ELDA (Evaluations and Language resources Distribution Agency)⁶ for directly translating the 25 hours of Tamasheq into French text (no transcription). The translation was performed by at least two native Tamasheq speakers (the number and identity of the translators is not disclosed), with posterior text correction by professionals in the French language. The translators had access to 5 pages of guidelines for producing their translations, including guidelines for segmenting the long speech into utterances. Annotation used the *Transcriber* open-source tool.⁷ Some utterances contain gender information and speaker identification. Unfortunately, this annotation was not unified across translators, and some speakers are referred by different speaker ids in different files, with difficult disambiguation. Thus, we caution to the use of this information.

³<https://www.studiotamani.org/>

⁴<https://www.studiokalangou.org/>

⁵<http://<studio-name>.org/journaux/>

⁶<http://www.elra.info/en/about/elda/>

⁷<http://trans.sourceforge.net/>

3. Annotation Processing. From the original *Transcriber* annotation files, we filtered out segments corresponding to pauses, noise and music, and removed segments flagged by the annotators as corresponding to foreign languages, such as Arabic and French. We then applied *sacremoses*, the python port of the Moses toolkit (Koehn et al., 2007), for punctuation normalization and tokenization in French.

Finally, we noticed that some segments (roughly two hours) were flagged as being of poor source audio quality. For these, the translation was produced nevertheless, so we decided to still process these segments, including them in the larger, *less controlled* version of the shared corpus. This choice is justified by the reduced size of the final dataset.

4. Audio processing. From the resulting collection of segments, we split the episodes into utterance-level audio files. For posterior use in standard speech processing libraries, we also convert the original .mp3 files into .wav, 16bits, 16KHz, single channel. We then remove all utterances shorter than 1s and longer than 30s.

5. Statistics. Table 1 presents the statistics for the two versions of the Tamasheq-French parallel corpus we share with the community. The difference between the *17h* and the *19h* versions is the inclusion of potentially noisy segments, for which we do not know the quality of the translations and audio signal. Training and validation sets for both versions are made available through GitHub: https://github.com/mzboito/IWSLT2022_Tamasheq_data. The test set will be released in a posterior date, respecting the timeline for IWSLT2022.

4. The Studios Tamani-Kalangou Audio Collection

This unannotated audio collection corresponds to 671 hours of episodes in five languages: French from Niger, Fulfulde, Hausa, Tamasheq and Zarma. We automatically segmented this audio data, generating 641 hours of content ready for deployment in speech processing pipelines. We detail below the creation of this audio collection, and present some general statistics.

1. Data downloading. We downloaded 606 episodes in Tamasheq from Studio Tamani,⁸ and 2,160 episodes in all the available languages from Studio Kalangou: French (464), Fulfulde (459), Hausa (424), Tamasheq (408) and Zarma (405). These episodes correspond to the content we managed to retrieve with our web-crawler.⁹ It explored URLs ranging from November 2019 to September 2021 for Studio Kalangou, and from January 2020 to September 2021 for Stu-

⁸For Studio Tamani news are broadcast twice a day. These correspond to *matin* and *soir* segments in the source files, respectively morning and evening shows.

⁹Data accessing and downloading date: 07/10/2021.

	17h version				19h version			
	male	female	unknown	total	male	female	unknown	total
# utterances	2,116	10	3,557	5,683	2,724	11	3,680	6,415
# hours	6:58:54	0:00:48	10:05:12	17:04:55	8:55:43	0:00:51	10:28:24	19:24:59

Table 1: Statistics for the 17 hours (left) and 19 hours long (right) Tamasheq-French parallel corpus.

	# episodes	# hours	# utterances	# hours (male)	# hours (female)	# hours (total)
French	464	116:22:09	38,332	52:15:07	58:46:00	111:01:07
Fulfulde	459	114:23:40	39,255	73:31:36	35:54:47	109:26:23
Hausa	424	105:32:48	35,684	75:05:12	25:39:40	100:44:52
Tamasheq	1,014	234:36:29	75,995	134:11:32	90:33:44	224:45:16
Zarma	405	100:42:34	34,198	57:03:37	38:55:33	95:59:10
Total	2,766	671:37:43	223,464	392:07:04	249:49:44	641:56:50

Table 2: Statistics for the Studios Tamani-Kalangou audio collection raw content (left) and automatically segmented version (right), produced by the use of a speech segmentation system with gender labeling.

dio Tamani.¹⁰

The left portion of Table 2 presents the statistics for the downloaded .mp3 files: 671 hours of audio, being 116 hours in French, 114 hours in Fulfulde, 105 hours in Hausa, 234 hours in Tamasheq, and 100 hours in Zarma. These correspond to a total of 2,766 episodes, with an average duration of 15 minutes (Studio Kalangou) or 13 minutes (Studio Tamani).

2. Segmenting Episodes into Breath Turns. The raw episodes downloaded from the websites are used as input for the LIUM_SpkDiarization tool (Meignier and Merlin, 2010). The goal of this step is (i) to produce a format more compatible to current speech processing models, that cannot deal with very long speech turns, and (ii) to remove silence, music and other non speech events.

The LIUM_SpkDiarization performs speech diarization, separating turns of speech. This allows us to slice the source episodes into smaller audio chunks (breath turns).¹¹ It also has the advantage of producing gender annotation, which allow us to estimate the gender representation for each language.

After applying the diarization tool, we also remove the first 12 seconds of each episode, as these often corresponded to intro jingles. The right portion of Table 2 presents the obtained result: 641 hours of audio, being 111 hours of French, 109 hours of Fulfulde, 100 hours of Hausa, 224 hours of Tamasheq, and 95 hours of Zarma. There are 392 hours estimated to be from male speakers, and 249 hours from female speakers.

3. Resulting Corpus. We make both versions of this corpus (Table 2) available to the community: the 671 hours long corpus based on episodes, and the 641 hours long corpus based on breath turns. This is because, even though we believe our seg-

mentation process to be of good quality, it is still supported by an automatic diarization tool. By providing the source content, we allow the community to choose their own segmentation approach. The corpus is made available through a dedicated website: <https://demo-lia.univ-avignon.fr/studios-tamani-> In the next section, we briefly go over the languages included in this audio collection.

4.1. The Languages

The speech resources we collect and share in this paper correspond to five languages: French, Fulfulde, Hausa, Tamasheq and Zarma. These are the five languages for which the Studio Kalangou daily news radio broadcast is available in Niger. While the target of this paper is to provide resources for the Tamasheq language, we find an interesting use-case to include other languages spoken in the same region, as an unknown degree of code-switching and lexical borrowing might happen due to their constant interaction. We now provide a brief description of these languages.

- **French (FRA):** French is the official language of the Niger, and a high-resource romance language from the indo-european family. At first, we intended to include only the other four languages listed in this section in the audio collection. However, we noticed some french segments in the Tamasheq annotation from Section 3, and hypothesized that some lexical borrowing might happen due to the geographic proximity of the languages.¹²
- **Fulfulde (FUV):** Fulfulde, also known as *Fula*, *Peul* or *Fulani*, is a Senegambian branch of the Niger-Congo language family. Unlike most Niger-Congo languages, it does not have tones (Brown and Ogilvie, 2010). The number of speakers is estimated to be above 40 mil-

¹⁰Since the sites vary in their file indexing, not all episodes from the indicated periods are successfully retrieved.

¹¹By default, the maximum turn length is set to 20 milliseconds.

¹²The same might be true for the Arabic language.

lion (Hammarström, 2015). The native speakers of this language, the Fula people, are one of the largest ethnic groups in the Sahel and West Africa (Hughes, 2009).¹³

- **Hausa (HAU):** Hausa is a Chadic language, member of the Afro-Asiatic language family. It is spoken mainly within the northern half of Nigeria and the southern half of Niger, with Wolff et al. (1991) and Newman (2009) estimating the number of speakers between 20 and 50 million. Early studies in Hausa showcased a remarkable number of loanwords from Arabic, Kanuri, and Tamasheq (Schön, 1862).
- **Tamasheq (TAQ):** Tamasheq is a variety of Tuareg, a Berber macro-language spoken by nomadic tribes across North Africa in Algeria, Mali, Niger and Burkina Faso (Heath, 2006). It accounts for approximately 500,000 native speakers, being mostly spoken in Mali and Niger (Hammarström, 2015). The livelihood of the Tuareg people has been under threat in the last century, due to climate change and a series of political conflicts (Decalo, 1997). This reduced considerably the number of speakers of Tamasheq however, partially due to the Malian government’s active promotion of the language in recent years, Tamasheq is now classified as a *developing language* (Hammarström, 2015).
- **Zarma (DJE):** Zarma, also spelled *Djerma*, is a leading indigenous Songhay language of the southwest lobe of the west African nation of Niger, spoken by over 2 million speakers. This tonal language is also spoken in Nigeria, Burkina Faso, Mali, Sudan, Benin and Ghana (Britannica, The Editors of Encyclopedia, 2015).

5. Use case: Speech Translation Baseline

In this section we present a baseline for end-to-end speech translation using the Tamasheq-French Parallel Corpus.

Dataset. We run this baseline experiment using both versions of the corpus from Section 3. Training and validation sets are detailed in Table 3. We extract 80-dimensional Mel filterbank (MFB) features from the Tamasheq utterances. For the French text, we build a 1k unigram vocabulary using Sentencepiece (Kudo and Richardson, 2018) without pre-tokenization.

Architecture. We use the FAIRSEQ S2T toolkit (Wang et al., 2020), training end-to-end speech translation Transformer models (Vaswani et al., 2017),

¹³Lexical resources can be found at: <http://www.language-archives.org/language/ful>

¹⁴Lexical resources can be found at: <http://www.language-archives.org/language/dj>

	Training	Validation	Test
17h	4,257 / 12h41	567 / 1h48	-
19h	4,999 / 15h02	-	-

Table 3: Number of utterances and duration per set. The 17h and 19h versions share the same validation and test sets. *Information about the test set will be released respecting the calendar for IWSLT 2022.*

	BLEU score
17h	2.51 (20.1/3.5/1.1/0.5)
19h	2.85 (21.0/4.0/1.4/0.6)

Table 4: End-to-end speech translation BLEU4 results for the baselines, with detailed scores between parenthesis.

preceded by two convolutional layers for dimensionality reduction.¹⁵ These models are trained for 500 epochs using the Adam optimizer (Kingma and Ba, 2014) with 10k warm-up steps. For decoding, we use beam search with a beam size of 5, and we evaluate the models using the best checkpoint with respect to the validation set.

Results and Discussion. The reported results in Table 4 are detokenized case-sensitive BLEU computed using sacreBLEU (Post, 2018) over the validation set. In a future version of this paper we will include results over the test set, that is not used at this point because it is the official test dataset of the IWSLT 2022 campaign.

We notice that the 19h version of this dataset, which contains two extra hours in the training set, improves slightly over the 17h version. This could hint that more data, even when being of low-quality, can help in scenarios of data scarcity. Nevertheless, the performance of these baselines is *very* low. This highlights the challenge of low-resource end-to-end speech translation when the only data used is of parallel nature. We believe results can be further improved by using auxiliary monolingual tools and models.

For the text, and since French is a high-resource language, one could incorporate pre-trained embeddings to the translation decoder. For the decoding procedure, language models – such as CAMEMBERT (Martin et al., 2020) and FLAUBERT (Le et al., 2020) – can be used.

For the speech, the self-supervised speech representation produced by models such as HUBERT (Hsu et al., 2021) and WAV2VEC2.0 (Baevski et al., 2020) can help the speech translation encoder. One can use freely available pretrained models in high-resource languages, or train these models from scratch. In both cases, self-supervised (also called *task-agnostic*) fine-tuning

¹⁵Settings are detailed at their `s2t_transformer_xs`

in the target language can increase results, but the best option seems to be to fine-tune in the target task directly (Evain et al., 2021; Babu et al., 2021).

Lastly, an interesting research direction the leveraging of multilingual data. There are massive models that successfully leverage data from many unrelated languages during training (Conneau et al., 2020; Babu et al., 2021). However, we currently do not know if these models are in fact better than having models with a smaller set of languages that are closely related (i.e. in speech style, geography, phonology, linguistic family). Thus, it might be interesting to compare the speech representations produced by a multilingual model based on the languages from Section 4, with current multilingual baselines, such as XLSR-53 (Conneau et al., 2020) and XLS-R (Babu et al., 2021).

6. Conclusion

In this paper we presented two resources that focus on the Tamasheq language. The **Studios Tamani-Kalangou audio collection** contains 641 hours of speech in French from Niger, Fulfulde, Hausa, Tamasheq and Zarma, making it an interesting dataset for self-supervised approaches for speech representation (Baevski et al., 2020; Hsu et al., 2021; Conneau et al., 2020), focusing on languages that are geographically close. This resource is freely available to the community through our website: <https://demo-lia.univ-avignon.fr/studios-tamani-kalangou>

The second resource, the **The Tamasheq-French Parallel Corpus**, focuses on speech translation. It provides speech in Tamasheq (17 to 19 hours) aligned at the utterance-level to translations in French. It is freely available to the community through our GitHub page: <https://github.com/mzboito/IWSLT2022-Tamasheq>

Lastly, we also presented baseline end-to-end speech translation models working from only 17 or 19 hours of Tamasheq speech. The results highlight the great challenge of developing effective approaches in such low-resource settings. We believe that by leveraging monolingual tools and more data into the model, notably through the use of the audio collection presented in this paper, one might be able to develop more effective translation models in Tamasheq.

7. Acknowledgements

We are very thankful to Fondation Hironnelle, Studios Kalangou from Niger, and Studios Tamani from Mali, for allowing us to download, use and distribute their audio data under the Creative Commons BY-NC-ND 3.0 license for non-commercial use.

This work was funded by the French Research Agency (ANR) through the ON-TRAC project under contract number ANR-18-CE23-0021. This paper was also partially funded by the European Commission through the SELMA project under grant number 957017.

8. Bibliographical References

- Babu, A., Wang, C., Tjandra, A., Lakhotia, K., Xu, Q., Goyal, N., Singh, K., von Platen, P., Saraf, Y., Pino, J., et al. (2021). Xls-r: Self-supervised cross-lingual speech representation learning at scale. *arXiv preprint arXiv:2111.09296*.
- Baevski, A., Zhou, H., Mohamed, A., and Auli, M. (2020). wav2vec 2.0: A framework for self-supervised learning of speech representations. *arXiv preprint arXiv:2006.11477*.
- Britannica, The Editors of Encyclopedia. (2015). Songhai languages. [Online; accessed 3-01-2022].
- Brown, K. and Ogilvie, S. (2010). *Concise encyclopedia of languages of the world*. Elsevier.
- Conneau, A., Baevski, A., Collobert, R., Mohamed, A., and Auli, M. (2020). Unsupervised cross-lingual representation learning for speech recognition. *arXiv preprint arXiv:2006.13979*.
- Decalo, S. (1997). Historical dictionary of niger. Ethnologue: Languages of the World. (2021). Tamasheq. [Online; accessed 07-12-2021].
- Evain, S., Nguyen, H., Le, H., Boito, M. Z., Md-haffar, S., Alisamir, S., Tong, Z., Tomashenko, N., Dinarelli, M., Parcollet, T., et al. (2021). Task agnostic and task specific self-supervised learning from speech with lebenchmark. In *Thirty-fifth Conference on Neural Information Processing Systems Datasets and Benchmarks Track (Round 2)*.
- Hammastrom, H. (2015). "ethnologue" 16/17/18th editions: A comprehensive review. *Language*, pages 723–737.
- Hsu, W.-N., Bolte, B., Tsai, Y.-H. H., Lakhotia, K., Salakhutdinov, R., and Mohamed, A. (2021). Hubert: Self-supervised speech representation learning by masked prediction of hidden units. *arXiv preprint arXiv:2106.07447*.
- Hughes, M. E. (2009). Africa and the americas: Culture, politics, and history. *Reference & User Services Quarterly*, 48(4):402–403.
- Joshi, P., Santy, S., Budhiraja, A., Bali, K., and Choudhury, M. (2020). The state and fate of linguistic diversity and inclusion in the nlp world. *arXiv preprint arXiv:2004.09095*.
- Kingma, D. P. and Ba, J. (2014). Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*.
- Koehn, P., Hoang, H., Birch, A., Callison-Burch, C., Federico, M., Bertoldi, N., Cowan, B., Shen, W., Moran, C., Zens, R., et al. (2007). Moses: Open source toolkit for statistical machine translation. In *Proceedings of the 45th annual meeting of the association for computational linguistics companion volume proceedings of the demo and poster sessions*, pages 177–180.
- Kudo, T. and Richardson, J. (2018). Sentencepiece: A simple and language independent subword tokenizer

- and detokenizer for neural text processing. *arXiv preprint arXiv:1808.06226*.
- Le, H., Vial, L., Frej, J., Segonne, V., Coavoux, M., Lecouteux, B., Allauzen, A., Crabbé, B., Besacier, L., and Schwab, D. (2020). FlauBERT: Un-supervised language model pre-training for French. In *Proceedings of the 12th Language Resources and Evaluation Conference*, pages 2479–2490, Marseille, France, May. European Language Resources Association.
- Martin, L., Muller, B., Ortiz Suárez, P. J., Dupont, Y., Romary, L., de la Clergerie, É., Seddah, D., and Sagot, B. (2020). CamemBERT: a tasty French language model. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 7203–7219, Online, July. Association for Computational Linguistics.
- Meignier, S. and Merlin, T. (2010). Lium spkdiarization: an open source toolkit for diarization. In *CMU SPUD Workshop*.
- Newman, P. (2009). Hausa and the chadic languages. Routledge.
- Post, M. (2018). A call for clarity in reporting bleu scores. *arXiv preprint arXiv:1804.08771*.
- Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., Kaiser, Ł., and Polosukhin, I. (2017). Attention is all you need. In *Advances in neural information processing systems*, pages 5998–6008.
- Wang, C., Tang, Y., Ma, X., Wu, A., Okhonko, D., and Pino, J. (2020). Fairseq s2t: Fast speech-to-text modeling with fairseq. *arXiv preprint arXiv:2010.05171*.
- Wolff, E. H., von Gleich, U., and Wolff, E. (1991). Standardization and varieties of written hausa (west africa). *Gleich, Utta von and Wolff Ekkehard (eds.)*, pages 21–33.

9. Language Resource References

- Heath, J. (2006). *Dictionnaire touareg du Mali: tamachek-anglais-français*. KARTHALA Editions.
- Schön, J. F. (1862). *Grammar of the Hausa language*. Church missionary house.