

LINEAR LEXICOGRAPHIC OPTIMIZATION AND PREFERENTIAL BIDDING SYSTEM

NOUR ELHOUDA TELLACHE, FRÉDÉRIC MEUNIER, AND AXEL PARMENTIER

ABSTRACT. This paper addresses the construction of the pilots' schedules under the preferential bidding system in the airline industry. In this system, the pilots bid on the different activities and the airline constructs the schedules that maximize the scores of the pilots lexicographically: the most senior is served first, then the second one, etc. A sequential approach to solve this problem is natural, and actually quite common: the problem is first solved with the bids of the most senior pilot in the objective function; then it is solved with those of the second most senior without decreasing the score of the most senior, and so on. Each step often involves column generation, requires solving an integer program, and usually takes into account the possible schedules of the less senior crew members approximately, which might compel to time-consuming backtrackings. The known existing exact method for this problem follows the sequential approach. The literature commonly admits that the structure of the problems somehow imposes such an approach.

In this work, we show that this belief is actually not completely correct by proposing another exact method that first solves the continuous relaxation of the full problem (with its lexicographic objective) via column generation which provides an upper bound on the optimal value. It then calls an IP solver to compute a lower bound by using only the previously generated columns. Finally, it makes use of the upper and lower bounds to identify columns that might improve the value of the lower bound and calls again the IP solver to compute eventually an optimal solution. The problem of generating new columns is solved using a lexicographic resource-constrained longest path algorithm.

With this approach, we show that standard schemes of mathematical programming (such as column generation, bounds, dominance, etc.) can be extended directly to optimization problems with lexicographic objectives. Numerical experiments on industrial instances provided by Air France show that the method can solve these instances in relatively short computational time that is compatible with the operational constraints of the airline.

1. INTRODUCTION

1.1. Context. The airline crew scheduling problem is one of the most important problems in the airline planning process because the total crew cost (salaries, benefits, and expenses) is considered, next to the fuel cost, the largest single cost of an airline [12]. For large fleets, this problem is decomposed into crew pairing and crew assignment, which are solved sequentially. The first consists of generating a set of least-cost crew pairings (sequences of flights starting and ending at the same crew base) that cover all the flights. The second aims at finding monthly schedules (sequences of pairings) for crew members that cover the pairings previously built.

Key words and phrases. Linear lexicographic optimization; preferential bidding system; column generation; shortest paths.

Different scheduling processes exist to construct the schedules of the crew members. With the bidline process, anonymous schedules are first computed (various objectives can be considered). Crew members bid on these schedules and are later assigned to them according to their bids and seniority [2]. The rostering process consists of computing personalized schedules, taking into account preassigned activities such as vacations and training periods while optimizing an objective function such as the cost, the covered pairings, the global satisfaction, etc. [10, 15]. In the preferential bidding system (PBS), that is the subject of the present paper, the crew members express their preferences on the various activities (pairings, pre-assignments, rest periods, etc.) in the form of bids. Then, the system builds the schedules that maximize the scores of the crew members in a lexicographic order: the most senior is served first, then the second one, etc. The score of a schedule for a crew member is calculated from his bids.

As discussed hereafter, designing a method that outputs a solution satisfying exactly the requirements of the preferential bidding system is an extremely difficult problem, and the literature mainly focuses on its application to pilots. This also the case for the present paper.

1.2. Challenges of exact methods. The number of feasible schedules grows exponentially with the number of pairings, and this clearly makes the PBS problem difficult. Yet, classical techniques from mathematical programming are available to deal efficiently with such issues (e.g., column generation), but what makes it non-standard is its lexicographic objective function. Two exact approaches for dealing with such an objective function have been considered in the literature: a “sequential” approach and a “weighting” approach.

The principle of a sequential approach goes as follows. First, the largest possible score that is achievable by the most senior pilot is determined: this is done by solving the PBS problem with the objective function restricted to his preferences. Then, the largest possible score that is achievable by the second most senior pilot, without decreasing that of the most senior, is determined: this is done by solving the problem with the objective function restricted to the preferences of the second most senior, and by restricting the set of feasible solutions to those yielding the optimal score for the most senior. And so on.

A weighting approach consists in considering a single objective function where the score of each pilot gets a weight. This way, we replace the original integer linear lexicographic program to a classical integer linear program (e.g., with a single objective function). The challenge here is to find the weights so that the optimal solutions of the two programs are the same. Such weights exist: indexing the pilots from 1 to m from the most senior to the least senior, choose for pilot i a weight equal to M^{m-i} , where M is any upper bound on the maximal achievable score over all pilots. To be valid in full generality, these weights must actually increase exponentially with the number m of pilots. Gamache et al. [11] and Achour et al. [1] note that numerical precision issues prevent any use of this approach for realistic number of pilots and they conclude to the necessity of the sequential approach.

The two approaches reduce then to the classical resolution of integer programs with one-dimensional objective functions, which are efficiently solved via column generation for the continuous relaxation and via branch-and-bound to get optimal integer solutions.

1.3. Contributions. We propose a third alternative to the sequential and weighting approaches, and this alternative comes under the scope of a classical integer programming

paradigm. Isermann [14] has proved that several results of linear programming extend to linear lexicographic programming just by replacing the ordinary order on \mathbb{R} by the lexicographic order on \mathbb{R}^m . We show that this extension allows continuous relaxation to provide bounds for integer lexicographic programs in the same way it provides bounds for ordinary integer program, and to design a column generation method based on dual information, similarly to ordinary column generation.

The overall exact method we propose for the PBS problem goes as follows. First, a continuous relaxation is solved via column generation, providing an upper bound to the optimal value. This continuous relaxation takes the form of a linear lexicographic program and, as usual, the game consists in identifying columns with positive reduced costs (the “pricing” problem, which is a longest path problem). Second, a lower bound is computed with an IP solver that can deal with lexicographic objectives (like Gurobi). Third, columns “in the gap,” that is new columns that might improve the value of the solution, are generated (and identified as such via their reduced costs), and the solver is called again. We emphasize that all comparisons involved in expressions like “upper bound,” “lower bound,” “positive,” and “in the gap” are understood according to the lexicographic order.

In the above paragraph, the task of generating new columns takes the form of a resource-constrained longest path problem with lexicographic costs, and we show that a classical algorithm based on bounds and dominance can solve this problem. We eventually achieve excellent performances by exploiting the specific form of the pricing problem.

Experiments have been conducted on instances provided by the French airline Air France and have proved the efficiency of the method: realistic instances with up to 100 pilots are solved exactly in less than 8 hours. Such instances are already considered as quite large by Air France—and anyway are the largest considered in the literature in terms of number of pilots—and the computational times are compatible with their operational constraints. Our method is thus applicable in practice. We also believe that what makes this method appealing is not only its efficiency but also its conceptual simplicity.

So, we can summarize our main contribution not only as an efficient method for solving the PBS problem but also as the proof that standard schemes of mathematical programming (such as column generation, bounds, dominance, etc.) can be extended directly to optimization problems with lexicographic objectives.

Acknowledgments. The authors are grateful to Boris Detienne for bringing to their attention the references [7, 8] mentioned in Section 3.2. We are also thankful to Mohand Ait Alamara and Séverine Bonnechère at Air France for their explanations concerning the constraints defining feasible schedules and for providing concrete instances.

2. LITERATURE REVIEW

In accordance with our approach, the literature review is split into two parts: solving the PBS problem; solving linear lexicographic programs. We have not been able to find relevant works on shortest or longest paths in a graph with lexicographic costs.

2.1. PBS problem. The PBS problem has been less studied in the literature in comparison to the other crew assignment systems. The earliest papers dealing with this problem use heuristics that sequentially construct the schedules of the crew members following a seniority order. Moore et al. [16] and Byrne [3] have proposed greedy heuristics for Qantas that build a

feasible schedule for each crew member, from the most senior to the most junior, by selecting iteratively the pairing with the highest score among the residual pairings. Feasibility checks are performed in order to ensure that the iteration can yield a feasible schedule and that the problem remains feasible for the less senior crew members.

Gamache et al. [11] have proposed another sequential heuristic approach for Air Canada that associates to each crew member, starting from the most senior, a mixed integer linear program. This program consists in finding a maximal-score schedule for the current crew member, while taking into account the schedules assigned to the most senior crew members and ensuring that the less senior ones can cover the remaining pairings. This latter feasibility condition is taken into account in an approximate way by relaxing the decision variables corresponding to the less senior crew members. As a consequence, some programs may not be feasible which requires time-consuming backtracking to correct bad decisions. Each program is solved using a column generation algorithm embedded in a branch-and-bound framework. A second branching tree is used to maintain the links between the different programs in case of backtracking. This heuristic has been tested on 24 instances with size up to 108 pilots and the most difficult instance requires 8 hours and 1 minute to be solved. In another paper, Gamache et al. [9] added to this heuristic approach a feasibility test to avoid backtracks. This test determines at each iteration if it is possible to assign a feasible schedule to each crew member while covering all pairings. The feasibility test problem is modeled as a graph coloring problem and solved using a tabu search algorithm. The proposed method has been validated on an instance from a North American carrier with 330 crew members (not only pilots).

Since several schedules may yield the same score for a given crew member, fixing a schedule for that crew may reduce the best scores of less senior crew members. For this reason, the approach of Gamache et al. [11] is not exact. A few years later, Achour et al. [1] proposed an exact algorithm that adds to the heuristic of Gamache et al. [11] a mechanism delaying the selection of a best-score schedule for a senior crew member until there is only one schedule left for that crew that can yield his best score. To do so, after solving to optimality the program of a given crew member, the set of all residual best-score schedules for that crew is computed. The sets corresponding to the best-score schedules of the most senior crew members and the sets corresponding to the feasible schedules of the junior ones are updated accordingly. If we are left with one best-score schedule for a senior crew member, a feasibility check is performed before assigning that schedule. This is done by solving the mixed integer linear program of the current crew member in which the integrality is imposed on the decision variables of all senior crew members. This program is also solved using a branch-and-price algorithm. If the problem is not feasible, the program of the current crew member is solved again by adding a cut restricting the score of that crew. Recall that, similarly to the heuristic of Gamache et al. [11], the overall approach may result in non-feasible programs for some crew members. A backtracking is applied, in this case, using the second branching tree. This exact algorithm has been tested and compared with the heuristic of [11] on 8 instances corresponding to the PBS problem for the pilots at a North American carrier. The size of the instances varies from 17 to 91 pilots, and the most difficult instance requires more than 5 days with the exact algorithm while the heuristic spends more than 7 days on that instance.

2.2. Linear lexicographic optimization. Most of the literature on linear lexicographic optimization focuses on sequential or weighted approaches to deal with lexicographic objectives. To our knowledge, the earliest paper that considers such problems and suggests a different approach is the work of Isermann [14]. The author proposed the lexicographic simplex method which is an extension of the ordinary simplex method in a lexicographic context where all the objectives are considered simultaneously. He provides the existence and duality theory which are the theoretical basis of the solution method. No numerical experiments are presented in the paper and the algorithm has been illustrated on an example. Pourkarimi et al. [20] described another approach in which they solve a single linear program. This latter corresponds to the dual of the weighted problem associated with the linear lexicographic program. The algorithm has been tested on an example.

Recently, Cococcioni et al. [6] proposed a solution method that also considers all the objectives at the same time. This approach adds to the usual numeral system a new numeral, which they call “grossone” and which is defined as the number of elements of the set of natural numbers. (Curiously, they do not refer to the standard notion of \aleph_0 .) This allows the authors to transform the lexicographic objective into a single objective, with “infinitesimal” weights whose order decreases with the decrease of the importance of the objectives. The obtained program is solved using a simplex-like method (called GrossSimplex) working with grossone-based numbers that can include infinitesimal parts. The proposed method has been tested on 4 examples with at most 10 objective functions. The same authors addressed in [5] the case in which some variables are integers. They solved the problem using a branch-and-bound algorithm in which the relaxation at each node of the search tree is solved using the GrossSimplex. The algorithm has been tested on 5 examples; 4 of them have at most 7 objective functions and the last example has 200 objectives. This later requires 32h and 13 minutes to be solved on an Intel i7 920 with cores at 3.6 GHz.

3. PROBLEM STATEMENT AND OVERVIEW OF THE METHOD

3.1. Problem formulation and modeling. The problem we consider is the PBS problem for pilots. We are given a set \mathcal{P} of pairings and a set $\mathcal{S} \subseteq 2^{\mathcal{P}}$ of feasible schedules. There are m pilots, identified with the integers from 1 to m . We denote their set by $I := [m]$. The numbers reflect the seniority: the most senior is identified with 1 and the least senior is identified with m . Each pilot i provides a score g_{ip} to every pairing p . In practice, this score is expressed indirectly by the pilot who only formulates preferences, e.g., morning flight, specific destination, etc.

The goal is to find an injective assignment $\sigma: I \rightarrow \mathcal{S}$ of the pilots to the feasible schedules so that the selected schedules $\sigma(I)$

- form a partition of the pairing set \mathcal{P} , and
- maximize the scores of the pilots lexicographically.

The lexicographic maximization of the scores can be formalized as follows: the vector $(c_{1\sigma(1)}, c_{2\sigma(2)}, \dots, c_{m\sigma(m)})$ must be lexicographically maximal, where $c_{is} = \sum_{p \in s} g_{ip}$ is the score of schedule s according to pilot i .

This problem can be modeled as the following integer linear lexicographic program:

$$\begin{aligned}
& \text{lexmax } C\mathbf{x} \\
& \text{s.t. } \sum_{s \in \mathcal{S}} x_{is} = 1 \quad \forall i \in I \quad (1) \\
(P) \quad & \sum_{i \in I} \sum_{s \in \mathcal{S}: s \ni p} x_{is} = 1 \quad \forall p \in \mathcal{P} \quad (2) \\
& x_{is} \in \{0, 1\} \quad \forall i \in I, s \in \mathcal{S}.
\end{aligned}$$

The notation “lexmax $C\mathbf{x}$ ” means that we are looking for a feasible solution such that

$$\left(\sum_{s \in \mathcal{S}} c_{1s} x_{1s}, \sum_{s \in \mathcal{S}} c_{2s} x_{2s}, \dots, \sum_{s \in \mathcal{S}} c_{ms} x_{ms} \right), \quad (3)$$

is lexicographically maximal.

Even if it is not necessary at this stage, since we have a well-defined mathematical program, we remark that the notation $C\mathbf{x}$ does also make sense with the following definition of C . It is a matrix with rows identified with I and with columns identified with $I \times \mathcal{S}$. The entry on row i and column (j, s) is equal to c_{is} if $i = j$ and 0 otherwise. This way, $C\mathbf{x}$ is exactly the (transpose of the) vector given in equation (3).

In the specific version of the PBS problem studied in this paper, the set \mathcal{S} is only given implicitly. Pairings are considered over a given month. A pairing comes together with many characteristics. In the paper, we focus on the main ones: starting and ending times, number of flight hours, and working hours. A subset s of the pairing set \mathcal{P} belongs to \mathcal{S} if the following constraints are satisfied (a day in a schedule is *on* or *off* depending on whether there is some work on that day or not):

- No two pairings in s overlap in time.
- The total number of days on is at most 17 (in case it is a 30-day month).
- The days off must include at least 7 consecutive days. (Here, a day starts at 12am and finishes at 11:59pm.)
- The total number of flight hours does not exceed 85 hours.
- The total number of working hours should not exceed 55 for every sequence of 7 consecutive days.

3.2. Preliminaries on linear lexicographic programming. According to Isermann [14], linear lexicographic programming studies linear programs with a finite number of objective functions that “are to be optimized [...] in a *lexicographic order*, i.e., low priority objectives are optimized as far as they do not interfere with the optimization of higher priority objectives.” Such linear lexicographic programs are linear programs where the order on $\bar{\mathbb{R}} = \mathbb{R} \cup \{-\infty, +\infty\}$ in the objective function is replaced by the lexicographic order \leq_{lex} on $\bar{\mathbb{R}}^m$, defined as follows. We have $\mathbf{x} <_{\text{lex}} \mathbf{y}$ if there exists $j \in [m]$ such that $x_j < y_j$ and $x_h = y_h$ for all $h < j$. We have $\mathbf{x} \leq_{\text{lex}} \mathbf{y}$ if $\mathbf{x} <_{\text{lex}} \mathbf{y}$ or $\mathbf{x} = \mathbf{y}$.

Without loss of generality, such a linear program can be written as follows:

$$\begin{aligned}
& \text{lexmax} && C\mathbf{x} \\
\text{(LLP)} & \text{s.t.} && A\mathbf{x} = \mathbf{b} \\
& && \mathbf{x} \geq \mathbf{0},
\end{aligned}$$

where A and C are respectively $k \times n$ and $m \times n$ real matrices, and \mathbf{b} is a vector in \mathbb{R}^k . The notation “lexmax $C\mathbf{x}$ ” means that we are looking for a feasible \mathbf{x}^* such that $C\mathbf{x}^* \geq_{\text{lex}} C\mathbf{x}$ for every feasible \mathbf{x} .

Assume that A has full rank. We keep the definition of basis and feasible basis of ordinary linear programming (the objective function is not involved). We also keep the standard notation M_X meaning that we restrict a matrix M to a subset X of its columns. Given a feasible basis B , we define then the *reduced cost of x_j with respect to B* as $\bar{\mathbf{c}}_j = \mathbf{c}_j - C_B A_B^{-1} \mathbf{a}_j$, where \mathbf{a}_j and \mathbf{c}_j are the j -th column of A and C , respectively. In particular, $\mathbf{c}_j = \mathbf{0}$ when $j \in B$. Note that the reduced cost of a variable is now an m -dimensional vector, and, when $m = 1$, this definition coincides with the ordinary one.

As shown by Isermann (see the paragraph before Proposition 1 in his paper), the standard criterion ensuring the optimality of a feasible basis still holds in the lexicographic setting. A basis is *primal-dual feasible* if the corresponding reduced costs $\bar{\mathbf{c}}_j$ satisfy $\bar{\mathbf{c}}_j \leq_{\text{lex}} \mathbf{0}$ for all j .

Lemma 1. *Any solution determined by a primal-dual feasible basis is optimal.*

As in standard linear programming, the converse is not true: there might exist optimal solutions determined by bases that are not primal-dual feasible.

A sufficient condition for the existence of such a basis is given in the following result, which is a corollary of Theorem 1, stated and proved in Section 4. (The existence of a basis determining an optimal solution is proved within the proof of Lemma 2 in Isermann’s paper; yet, the part regarding the dual feasibility is not present and, since it is crucial for our method to work, we provide a proof in Section 4.)

Corollary 1. *If (LLP) is lexicographically bounded from above, then there exists a primal-dual feasible basis.*

In Section 4, we will show that there is actually an efficient way to find a basis as in Corollary 1.

We end this section with a lemma providing a way to reduce the size of an integer lexicographic program. It will play an important role in our method. The lemma is actually just an extension to the lexicographic context of a classical trick for ordinary integer programming; see Crowder et al. [7, Section 3.3] or Nemhauser and Wolsey [17] (Proposition 2.1, p. 389). Actually this trick was already used by Dantzig et al. [8] in 1954 for solving to optimality an instance of the traveling salesman problem with 49 cities.

Consider the following integer linear lexicographic program.

$$\begin{aligned}
& \text{lexmax} && C\mathbf{x} \\
\text{(ILLP)} & \text{s.t.} && A\mathbf{x} = \mathbf{b} \\
& && \mathbf{x} \in \mathbb{Z}_+^n.
\end{aligned}$$

Lemma 2. Let $\boldsymbol{\ell} \in \mathbb{R}^m$ be a lower bound of (ILLP) and $\mathbf{u} \in \mathbb{R}^m$ the optimal value of its linear relaxation. Consider a primal-dual feasible basis and a non-basic variable x_j . If $\bar{\mathbf{c}}_j <_{\text{lex}} \boldsymbol{\ell} - \mathbf{u}$, then x_j is equal to 0 in all optimal solutions of (ILLP).

Proof. Denote by B the basis considered in the statement. According to Lemma 1, the solution determined by B is optimal and thus $C_B A_B^{-1} \mathbf{b} = \mathbf{u}$. By definition of reduced costs, every feasible solution \mathbf{x} of the linear relaxation satisfies therefore $C\mathbf{x} = \mathbf{u} + \sum_{j' \in N} x_{j'} \bar{\mathbf{c}}_{j'}$, where N is the set $[n] \setminus B$ of non-basic indices. The vector $\boldsymbol{\ell}$ being a lower bound, we have $\boldsymbol{\ell} - \mathbf{u} \leq_{\text{lex}} \sum_{j' \in N} x_{j'} \bar{\mathbf{c}}_{j'}$. Since $\bar{\mathbf{c}}_{j'} \leq_{\text{lex}} \mathbf{0}$ for all $j' \in N$, every feasible solution \mathbf{x} of the linear relaxation satisfies $\boldsymbol{\ell} - \mathbf{u} \leq_{\text{lex}} x_j \bar{\mathbf{c}}_j$.

Consider now an optimal solution \mathbf{x}^* of (ILLP) and suppose that $\bar{\mathbf{c}}_j <_{\text{lex}} \boldsymbol{\ell} - \mathbf{u}$. According to what has just been proved, we have $\boldsymbol{\ell} - \mathbf{u} \leq_{\text{lex}} x_j^* \bar{\mathbf{c}}_j$, which implies $\bar{\mathbf{c}}_j <_{\text{lex}} x_j^* \bar{\mathbf{c}}_j$. Since $\bar{\mathbf{c}}_j \leq_{\text{lex}} \mathbf{0}$, we have $a\bar{\mathbf{c}}_j \leq_{\text{lex}} \bar{\mathbf{c}}_j$ for every positive integer a (because the lexicographic order is compatible with addition). Therefore, $x_j^* = 0$, which is the desired conclusion. \square

3.3. Method for solving the PBS problem. Informally, our method relies on a column generation method in which the ordinary linear programming theory is replaced by the linear lexicographic programming theory. As in any column generation method, the mathematical program to be solved is restricted to a subset of the original variables, which is updated iteratively. We do not depart from this procedure and the following mathematical program will play a central role. Here, \mathcal{S}'_i is a subset of \mathcal{S} .

$$\begin{aligned}
 & \text{lexmax} \quad C\mathbf{x} \\
 & \text{s.t.} \quad \sum_{s \in \mathcal{S}'_i} x_{is} = 1 \quad \forall i \in I \quad (4) \\
 \text{(P')} \quad & \sum_{i \in I} \sum_{s \in \mathcal{S}'_i: s \ni p} x_{is} = 1 \quad \forall p \in \mathcal{P} \quad (5) \\
 & x_{is} \in \{0, 1\} \quad \forall i \in I, s \in \mathcal{S}'_i.
 \end{aligned}$$

The overall algorithm is Algorithm 1. It makes use of the notion of “linear relaxation” and of “reduced costs” in linear lexicographic programming. Reduced costs have already been defined in Section 3.2. As expected, the linear relaxation of (P') consists simply in replacing $x_{is} \in \{0, 1\}$ by $x_{is} \in [0, 1]$.

Apart from relying on linear lexicographic programming, it follows a quite standard strategy for solving integer programs with a huge number of variables and with “partitioning” constraints; see, e.g., [4].

Step 3 is well-defined by Corollary 1 because (P') is lexicographically bounded from above. The algorithm terminates: at each iteration of the loop, the size of \mathcal{S}'_i increases for at least one pilot i (no feasible schedule in the \mathcal{S}'_i can have a lexicographically positive reduced cost because the basis is primal-dual feasible), and \mathcal{S}'_i is included in \mathcal{S} which is finite. Lemma 1 ensures that, when we leave the loop at step 5, the vector \mathbf{u} is the optimal value of the linear relaxation of (P). At step 6, the vector $\boldsymbol{\ell}$ is a lexicographic lower bound on the optimal value since any feasible solution of (P') is a feasible solution of (P). Lemma 2 shows then that the returned solution is indeed optimal.

$$\begin{aligned}
& \max \quad \mathbf{c}'_{S^{(l)}} \cdot \mathbf{y} \\
& \text{s.t.} \quad A_{S^{(l)}} \mathbf{y} = \mathbf{b} \\
& \quad \quad \mathbf{y} \geq \mathbf{0}.
\end{aligned} \tag{P_l}$$

Set $S^{(1)} = [n]$. Then, for $l = 1, \dots, m$,

- define $B^{(l)}$ as any primal-dual feasible basis of (P_l) .
- set $S^{(l+1)} = \{j \in S^{(l)} : c_{lj} = \mathbf{c}'_{B^{(l)\top}} A_{B^{(l)}}^{-1} \mathbf{a}_j\}$.

We have in particular $B^{(l)} \subseteq S^{(l+1)} \subseteq S^{(l)}$ for all $l \leq m$.

Note that computing this sequence of primal-dual bases can be easily performed with a standard linear programming solver.

Theorem 1. *The basis $B^{(m)}$ is a primal-dual feasible basis of (LLP).*

The proof of Theorem 1 requires an easy technical lemma. We are not aware of any reference in the literature.

Lemma 3. *Consider a linear program $\max\{\mathbf{c}' \cdot \mathbf{x} : A' \mathbf{x} = \mathbf{b}', \mathbf{x} \geq \mathbf{0}\}$ with A' being full-rank. Let B be a feasible basis. Set $S = \{j : c'_j = \mathbf{c}'_{B\top} A_B^{-1} \mathbf{a}'_j\}$. Let B' be any feasible basis included in S . Then $\mathbf{c}'_{B'\top} A_{B'}^{-1} = \mathbf{c}'_{B\top} A_B^{-1}$.*

Proof. We have $c'_j = \mathbf{c}'_{B\top} A_B^{-1} \mathbf{a}'_j$ for all $j \in S$. Thus, $\mathbf{c}'_{B'\top} = \mathbf{c}'_{B\top} A_B^{-1} A_{B'}$, since $B' \subseteq S$, which can be written as $\mathbf{c}'_{B'\top} A_{B'}^{-1} = \mathbf{c}'_{B\top} A_B^{-1}$. \square

Proof of Theorem 1. Let $j \in [n]$. Denote by $\bar{\mathbf{c}}_j = (\bar{c}_{1j}, \bar{c}_{2j}, \dots, \bar{c}_{mj})^\top$ the j -th reduced cost of (LLP) with respect to $B^{(m)}$. We have $B^{(m)} \subseteq S^{(m+1)} \subseteq S^{(m)} \subseteq S^{(m-1)} \subseteq \dots \subseteq S^{(l+1)}$, and thus Lemma 3 with

$$\mathbf{c}' = \mathbf{c}'_{S^{(l)}}, \quad A' = A_{S^{(l)}}, \quad \mathbf{b}' = \mathbf{b}, \quad B = B^{(l)}, \quad S = S^{(l+1)}, \quad \text{and} \quad B' = B^{(m)},$$

shows that $\mathbf{c}'_{B^{(m)\top}} A_{B^{(m)}}^{-1} = \mathbf{c}'_{B^{(l)\top}} A_{B^{(l)}}^{-1}$. This implies that $\bar{c}_{lj} = c_{lj} - \mathbf{c}'_{B^{(l)\top}} A_{B^{(l)}}^{-1} \mathbf{a}_j$ for all $l \in [m]$.

If $\bar{c}_{lj} = 0$ for all l , we have $\bar{\mathbf{c}}_j \leq_{\text{lex}} \mathbf{0}$, as required. We assume thus that there is at least one l for which this equality does not hold. Define l^* as the smallest l such that $\bar{c}_{lj} \neq 0$.

We prove by induction on l that $j \in S^{(l)}$ for all $1 \leq l \leq l^*$. This is true by definition for $l = 1$. Suppose now that it is true for $1 \leq l < l^*$. Since $\bar{c}_{lj} = c_{lj} - \mathbf{c}'_{B^{(l)\top}} A_{B^{(l)}}^{-1} \mathbf{a}_j$ and $\bar{c}_{lj} = 0$ (by $l < l^*$), we have $j \in S^{(l+1)}$, which concludes the induction.

We also have $\bar{c}_{l^*j} = c_{l^*j} - \mathbf{c}'_{B^{(l^*)\top}} A_{B^{(l^*)}}^{-1} \mathbf{a}_j$. This latter quantity is non-positive because $B^{(l^*)}$ is a primal-dual feasible basis of (P_{l^*}) and $j \in S^{(l^*)}$, as proved just before. Since $\bar{c}_{l^*j} \neq 0$, we have therefore $\bar{c}_{l^*j} < 0$, as required. \square

Remark 1. Denote by $\bar{\mathbf{c}}_j$ the j -th reduced cost of (LLP) with respect to $B^{(m)}$. As seen in the proof of Theorem 1, we have $\bar{c}_{lj} = c_{lj} - \mathbf{c}'_{B^{(l)\top}} A_{B^{(l)}}^{-1} \mathbf{a}_j$. This means that if we have access to the (row) vectors $\mathbf{c}'_{B^{(l)\top}} A_{B^{(l)}}^{-1}$ for every l , we can easily compute the reduced cost associated to any $j \in [n]$. Standard solvers usually give access for free to this vector $\mathbf{c}'_{B^{(l)\top}} A_{B^{(l)}}^{-1}$ once (P_l) has been solved to optimality. Indeed, these are the optimal dual solutions. Actually, we need slightly more than optimality since a primal-dual feasible basis is required, but most solvers provide this possibility. (The simplex algorithm terminates with such a basis.) This is used in our implementation to build efficiently the pricing problem.

Remark 2. The practical computation of $S^{(l)}$ is tricky because it relies on the identification of components equal to 0, and is therefore subject to numerical instability. This must be carefully addressed by performing all equality tests with a nonzero “epsilon” margin.

5. SOLVING THE PRICING PROBLEM

The pricing problem, which corresponds to steps 4 and 7 of Algorithm 1, consists in finding for each pilot i feasible schedules $s \in \mathcal{S}$, if any, with a lexicographically positive reduced costs $\bar{\mathbf{c}}_{is}$. We formulate therefore the pricing problem for pilot i as

$$\text{lexmax}_{s \in \mathcal{S}} \bar{\mathbf{c}}_{is}. \quad (6)$$

With the general notation of Section 3.2, we express the reduced cost $\bar{\mathbf{c}}_{is}$ as $\mathbf{c}_{is} - C_B A_B^{-1} \mathbf{a}_{is}$, where B is a feasible basis of the linear relaxation of (P), and where A is the constraint matrix of this problem (and \mathbf{a}_{is} is its column associated to the pair (i, s)). Hence, this reduced cost can be written under the form

$$\bar{\mathbf{c}}_{is} = \underbrace{\begin{bmatrix} 0 \\ \vdots \\ 0 \\ c_{is} \\ 0 \\ \vdots \\ 0 \end{bmatrix}}_{\substack{\text{specific to the} \\ \text{pricing problem} \\ \text{of pilot } i; \\ \text{only objective } i \\ \text{is non-zero}}} - \underbrace{\begin{bmatrix} \lambda_{li} \\ \vdots \\ \lambda_{mi} \end{bmatrix} - \sum_{p \in s} \begin{bmatrix} \mu_{lp} \\ \vdots \\ \mu_{mp} \end{bmatrix}}_{\substack{\text{shared by the pricing} \\ \text{problems of all pilots}}}, \quad (7)$$

where the first vector in the right-hand term is \mathbf{c}_{is} and has its only non-zero entry located on the i -th row. The real numbers λ_{li} and μ_{lp} are read from $C_B A_B^{-1} \mathbf{a}_{is}$. (Note that the columns of $C_B A_B^{-1}$ are indexed by $I \cup \mathcal{P}$ and its rows by I .) They can actually be obtained from optimal solutions of some dual problems, but we avoid referring to dual notions and build the pricing problem from the reduced cost expression.

Pricing problems of column generation approaches for vehicle and crew scheduling problems are typically modeled as resource constrained path problems, and solved with adequate enumeration algorithms. The main specificity of our pricing problem is that the objective is lexicographic. Section 5.1 introduces the lexicographic resource-constrained longest-path problem, and shows that the usual enumeration algorithms for resource constrained shortest path problems can be extended to that setting. Section 5.2 then models the pricing problem (6) within this framework.

The second specificity of our problem comes from the fact that the i -th lexicographic objective of the master problem involves only variables corresponding to pilot i . In an interpretation of the problem (P) as a Dantzig–Wolfe decomposition, the i -th objective involves only variables from the i -th block. The consequence, which is highlighted in equation (7), is that the objectives of the pricing problem of pilot i are identical to those of all other pilots, except for the i -th one. Section 5.3 shows how a preliminary call to the lexicographic longest-path algorithm—which we call the “reduction” trick—can exploit this property to

solve often the pricing problem for many pilots simultaneously. We will see in the numerical experiments that this trick strongly improves the practical performance of the algorithms.

The rest of the section is technical and can be skipped by a reader that is not interested in the details of the pricing algorithm implementation.

5.1. The lexicographic resource-constrained longest-path problem (RCLPP-Lex).

The problem. We are given a directed graph $D = (V, A)$ with two particular vertices o and d , and a partial ordered set (R, \preceq) of *resources*, which is supposed to have a unique maximal element, denoted by $\hat{\mathbf{1}}$. Each arc a is equipped with a non-decreasing map $f_a: R \rightarrow R$. Moreover, we are given a non-increasing map $c: R \rightarrow \mathbb{R}^m$ (where \mathbb{R} is the set $\mathbb{R} \cup \{-\infty, +\infty\}$). The *resource of a path* P , denoted by r_P , is defined inductively by $r_P = f_a(r_{P \setminus a})$, where a is the last arc of P . The map f_a has to be thought as describing the way the resource of a path is modified when an arc a is added to the path. The resource of a path reduced to a single vertex depends on that vertex and is given as an input of the problem. A path P is *feasible* if $r_P \neq \hat{\mathbf{1}}$. We define the lexicographic resource-constrained longest-path problem (RCLPP-Lex) as the problem of computing a feasible o - d path P with maximal $c(r_P)$.

A natural way to solve this problem consists in enumerating feasible o - v paths and in discarding as many of them as possible by dominance (f is non-decreasing). This might be actually time-consuming, but in many cases longest-path (or shortest-path) problems enjoy extra properties on which algorithms can rely to improve their computational times. We describe now such a property. As we will see, the pricing problem enjoys this property.

When bounds can be used. Suppose that we are given a non-decreasing map $g_a: R \rightarrow R$ for each arc a (“reverse-extension” map) and another component-wise non-decreasing map $h: R \times R \rightarrow R$ (“merge” map). For a path Q , we define inductively r'_Q by $r'_Q = g_a(r'_{Q \setminus a})$, where a is the first arc of Q . When Q is reduced to a single vertex, the definition of r'_Q depends on the vertex and the nature of the problem. Suppose moreover that for every vertex v , every o - v path P and every v - d path Q , we have $h(r_P, r'_Q) \preceq r_{P+Q}$. Then, any b_v satisfying $b_v \preceq r'_Q$ for every v - d path Q is a bound that can be used to discard o - v paths: indeed, if an o - v path P has $c(h(r_P, b_v))$ smaller than the current best solution, we know that P cannot be part of an optimal solution.

A *meet-semilattice* is a partial ordered set in which every finite non-empty subset X has a (unique) greatest lower bound $\wedge X$ (called *meet*). When (R, \preceq) is a meet-semilattice and D is acyclic, any solution $(b_v)_{v \in V}$ of the following dynamic programming equation provides bounds for the problem:

$$\begin{cases} b_d = r'_{\text{path reduced to } d} \\ b_v = \bigwedge_{(v,w) \in \delta^+(v)} g_{(v,w)}(b_w). \end{cases}$$

(A proof of this fact is introduced in [18] and reformulated in [19] with notations closer to those of the present paper.)

An enumeration algorithm for acyclic graphs, when bounds are available. Assuming that the bounds b_v are available (e.g., they have been pre-computed), we propose the following algorithm to solve RCLPP-Lex when the graph D is acyclic. In our case, this assumption on the graph will be satisfied. As far as we know, RCLPP-Lex, or close problems, have not been

studied in the literature. Nevertheless, the algorithm we propose follows a dominance/bound scheme [13].

Algorithm 2 Algorithm for RCLPP-Lex on DAGs when bounds are available

Require: an acyclic digraph $D = (V, A)$, bounds $(b_v)_{v \in V}$;

- 1: `current_best_cost` $\leftarrow (-\infty, \dots, -\infty)$, `current_best_solution` \leftarrow undefined, and $L_v \leftarrow \emptyset$ for all $v \in V$;
- 2: $L_o \leftarrow$ {path reduced to o };
- 3: **while** there exists u such that $L_u \neq \emptyset$ **do**
- 4: $P \leftarrow$ a path in L_u ;
- 5: $L_u \leftarrow L_u \setminus \{P\}$;
- 6: **for all** $a \in \delta^+(u)$ **do**
- 7: **if** $f_a(r_P) \neq \hat{1}$ **then**
- 8: $Q \leftarrow P + a$;
- 9: $w \leftarrow$ last vertex of Q ;
- 10: **if** $w = d$ **then**
- 11: **if** $c(r_Q) >_{\text{lex}} \text{current_best_cost}$ **then**
- 12: `current_best_cost` $\leftarrow c(r_Q)$;
- 13: `current_best_solution` $\leftarrow Q$;
- 14: **else**
- 15: **if** $(c(h(r_Q, b_w)) >_{\text{lex}} \text{current_best_cost})$ and $(r_Q \not\preceq r_{Q'} \text{ for every } Q' \in L_w)$
- 16: **then**
- 17: remove from L_w all paths Q' such that $r_Q \preceq r_{Q'}$;
- 18: $L_w \leftarrow L_w \cup \{Q\}$;
- 19: **if** `current_best_solution` \neq undefined **then**
- 20: **return** `current_best_solution`;
- 21: **else**
- 22: **return** “There is no feasible path.”

The algorithm consists in enumerating implicitly all possible paths originating at o : when an o - u path is considered, then all possible ways of extending this path with an arc starting at u are tried. As soon as a first feasible o - d path has been found, `current_best_solution` is a best solution identified so far, and `current_best_cost` $\in \mathbb{R}^m$ is its cost. Initially, `current_best_cost` is equal to $(-\infty, \dots, -\infty)$, with the convention that it is the objective value of a non-feasible solution, and therefore this variable is always a lower bound on the optimal value.

As discussed above, this enumeration is implicit because the bound is used to discard o - u paths that cannot be part of an optimal solution. The list L_u contains only feasible o - u paths that have successfully passed this test, which is the first inequality of step 15.

In the version shown in Algorithm 2, the list L_u is also cleaned of all “dominated” o - u paths. This is the second test at step 15. More precisely, at any moment, no two paths Q and Q' with $r_Q \preceq r_{Q'}$ are present simultaneously in L_u . Indeed, removing such a path Q' will not affect the correctness of the algorithm. Yet, when several optimal paths are sought, this might lead to inexact solutions, and therefore this property of the list L_u must not be kept: dominated paths must be allowed and the second test at step 15 and step 16 must

be omitted. This is actually the case in our experiments because we add several columns at each iteration of the column generation (steps 4 and 7 of Algorithm 1).

Possible improvements. There are several places in Algorithm 2 where computational time can be spared.

A preliminary test for feasibility, using b_o , can be performed at step 2: if $h(r_{\{o\}}, b_o)$ is equal to $(-\infty, \dots, -\infty)$ (where $\{o\}$ stands for the path reduced to o), then it is not possible to get a better cost (and in general this will coincide with the absence of any feasible solution).

A topological order on the vertices can be used: at step 6, choose a so that its head is the highest according to this order. Indeed, o - d paths will be computed earlier, which increases the chances of improving the current best solution, and hence the number of discarded paths.

A “key” attached to the paths can be used to prioritize the order in which the elements in L_u must be considered: define it as $\text{key}(P) := h(r_P, b_v)$, where v is the last vertex of P ; then

- at line 4, choose $P \in \bigcup_{u \in V} L_u$ maximizing $\text{key}(P)$. Indeed, this choice increases the chances of constructing paths with larger costs.
- before entering the **for** loop of line 6, test whether $\text{key}(P) \leq_{\text{lex}} \text{current_best_cost}$ for the P maximizing $\text{key}(P)$, in which case we can stop.

These improvements have been implemented in the code used in the experiments.

Solving variants. The variant of the pricing problem that is solved in step 4 of Algorithm 1 consists in generating a number of paths, say N (if any), with the best lexicographically positive reduced costs. Algorithm 2 can be adapted to solve this variant, which we call “ N -best-paths.” To do so, we use a plural `current_best_solutions` to denote the list of the best feasible o - d paths identified so far. The smallest cost of these paths is denoted by `current_smallest_cost` $\in \mathbb{R}^m$ (initially equals $(+\infty, \dots, +\infty)$). Then, we replace steps 11 to 13 by

```

if |current_best_solutions| < N then
  current_best_solutions ← current_best_solutions ∪ {Q};
  if c(rQ) <lex current_smallest_cost then
    current_smallest_cost ← c(rQ);
else
  if c(rQ) >lex current_smallest_cost then
    Delete from current_best_solutions a path with cost current_smallest_cost;
    current_best_solutions ← current_best_solutions ∪ {Q};
    current_smallest_cost ← min{c(rP): P ∈ current_best_solutions};

```

and step 15 by

```

if |current_best_solutions| < N or c(h(rQ, bw)) >lex current_smallest_cost then

```

Finally, we omit the dominance check of step 16, and adapt steps 18 to 21 for this variant.

Similarly, Algorithm 2 can be adapted to solve the variant of the pricing problem of step 7 of Algorithm 1. For this variant, we also use a list `current_best_solutions` of selected o - d paths, we replace step 11 by

if $c(r_Q) \geq_{\text{lex}} \ell - \mathbf{u}$ **then**

and step 15 by

if $h(r_Q, b_w) \geq_{\text{lex}} \ell - \mathbf{u}$ **then**

we omit steps 12 and 16, and we adapt steps 18 to 21 for this variant.

5.2. Modeling and solving the pricing problem as an RCLPP-Lex.

Modeling as an RCLPP-Lex. We explain now how to model the pricing problem with the rules given in Section 3.1 as an RCLPP-Lex (see definition in Section 5.1). To each pilot i , we associate a directed acyclic graph $D_i = (V_i, A_i)$. The set of vertices V_i is defined as $\mathcal{P} \cup \{o, d\}$, where the origin o and the destination d represent respectively the beginning and the ending of the month. The arc set A_i is formed by arcs (o, p) and (p, d) for each $p \in \mathcal{P}$, and by arcs (p, p') for every pairings $p, p' \in \mathcal{P}$ such that p' can be operated after p .

By construction of D_i , each feasible schedule for the pilot i can be represented as an o - d path in this graph. However, the opposite is not true since an o - d path may not satisfy all the rules for a feasible schedule. One way to take into account these rules is to model them using resources in the graph, as we explain now. We omit the rule about the 55 working hours for sake of readability. The ideas for taking it into account are not essentially different from those explained for the other rules; yet they are quite technical. Nevertheless, it has been taken into account in the experiments. The rules we deal with are thus (Section 3.1): the number of days on, the seven consecutive days off, and the number of flight hours. Note that the conflicts between the pairings have been encoded in the construction of the arcs of D_i .

We define the set of resources $R = (\mathbb{Z}_+ \times \{0, 1\} \times \mathbb{Z}_+ \times \mathbb{R}^m) \cup \{\hat{\mathbf{1}}\}$. A resource r distinct from $\hat{\mathbf{1}}$ is thus a four-tuple (r^o, r^b, r^f, r^c) where the first component r^o corresponds to the number of days on, the second component r^b is binary and indicates whether there are at least seven consecutive days off, the third component r^f corresponds to the number of flight hours, and the fourth component r^c is used to compute \bar{c}_{is} . For such elements, we define the partial order \preceq on R by

$$(r_1^o, r_1^b, r_1^f, r_1^c) \preceq (r_2^o, r_2^b, r_2^f, r_2^c) \quad \text{if} \quad r_1^o \leq r_2^o, \quad r_1^b \geq r_2^b, \quad r_1^f \leq r_2^f, \quad \text{and} \quad r_1^c \geq_{\text{lex}} r_2^c.$$

The element $\hat{\mathbf{1}}$ is then defined as being greater than any other element in R . Note that (R, \preceq) is a meet-semilattice.

Define the resource r_P of a path P reduced to a single vertex $v \in V_i$ as $(0, 0, 0, \mathbf{0})$ if $v = o$ and $\hat{\mathbf{1}}$ otherwise.

Define for $a \in A_i$, $r^o \in \mathbb{Z}_+$, $r^b \in \{0, 1\}$, $r^f \in \mathbb{Z}_+$, and $r^c \in \mathbb{R}^m$ the following functions.

$$\begin{aligned} f_a^o(r^o) &= r^o + (\text{number of days on in the head pairing of } a,) \\ f_a^b(r^b) &= \begin{cases} 1 & \text{if there are at least seven consecutive days off} \\ & \text{between the tail pairing and the head pairing of } a, \\ r^b & \text{otherwise,} \end{cases} \\ f_a^f(r^f) &= r^f + (\text{number of flight hours in the head pairing of } a), \\ f_a^c(r^c) &= r^c + (\text{cost associated to the head pairing of } a). \end{aligned}$$

If the head of a is not d , the cost associated to the head pairing p is set to

$$(\mu_{1p}, \dots, \mu_{(i-1)p}, g_{ip} + \mu_{ip}, \mu_{(i+1)p}, \dots, \mu_{mp})^\top.$$

In the above definitions, d is treated as a fictitious pairing with the following characteristics: its number of days on is 0 (the starting and ending times are equal to the end of the month), its number of flight hours is 0, and its cost is $(\lambda_{1i}, \dots, \lambda_{mi})^\top$.

We can now define $f_a: R \rightarrow R$ for every arc $a \in A_i$. For $r \in R$, we set

$$f_a(r) = \begin{cases} \rho(f_a^o(r^o), f_a^b(r^b), f_a^f(r^f), f_a^c(r^c)) & \text{if } r \neq \hat{\mathbf{1}} \text{ and (head of } a \neq d \text{ or } f_a^b(r^b) = 1), \\ \hat{\mathbf{1}} & \text{otherwise,} \end{cases}$$

where

$$\rho(x, y, z, t) = \begin{cases} (x, y, z, t) & \text{if } x \leq 17 \text{ and } z \leq 85, \\ \hat{\mathbf{1}} & \text{otherwise.} \end{cases}$$

The map f_a is non-decreasing (with respect to \preceq).

We define $c: R \rightarrow \mathbb{R}^m$ by

$$c(r) = \begin{cases} r^c & \text{if } r \neq \hat{\mathbf{1}}, \\ (-\infty, \dots, -\infty)^\top & \text{otherwise.} \end{cases}$$

It is a non-increasing map.

In this way, the problem RCLPP-Lex we get models exactly the problem of finding a feasible schedule for pilot i with a lexicographically maximal reduced cost. Indeed, by definition of f_a , the resource r_P of an o - d path P in D_i (as defined in Section 5.1) is equal to $\hat{\mathbf{1}}$ precisely when the path P does not correspond to a feasible schedule (one of the three rules is not satisfied). Moreover, the cost of such a path is equal to \bar{c}_{is} when the path encodes the schedule s .

Bounds can be used. The algorithm proposed in Section 5.1 to solve RCLPP-Lex requires extra properties to be applied, namely that D_i be acyclic, and that “reverse-extension” and “merge” maps be available. This is the case. We define $g_a: R \rightarrow R$ for every arc $a \in A_i$. It is exactly the same definition as f_a , except that the vertex d is replaced by the vertex o in the feasibility test, and when a path Q is reduced to a single vertex, we set r'_Q to $(0, 0, 0, \mathbf{0})$ if that vertex is d and $\hat{\mathbf{1}}$ otherwise. For sake of completeness, we write the full definition. We define for every $r \in R$

$$g_a(r) = \begin{cases} \rho(f_a^o(r^o), f_a^b(r^b), f_a^f(r^f), f_a^c(r^c)) & \text{if } r \neq \hat{\mathbf{1}} \text{ and (tail of } a \neq o \text{ or } f_a^b(r^b) = 1), \\ \hat{\mathbf{1}} & \text{otherwise,} \end{cases}$$

The map g is non-decreasing (with respect to \preceq).

With r_P and r'_Q defined as in Section 5.1, we have the following lemma, where $h: R \times R \rightarrow R$ is defined by

$$h(r, r') = \begin{cases} \rho(r^o + r'^o, 1, r^f + r'^f, r^c + r'^c) & \text{if } r \neq \hat{\mathbf{1}} \text{ and } r' \neq \hat{\mathbf{1}} \text{ and } \max(r^b, r'^b) = 1 \\ \hat{\mathbf{1}} & \text{otherwise.} \end{cases}$$

Lemma 4. *For every o-v path P and every v-d path Q , we have $h(r_P, r'_Q) \preceq r_{P+Q}$.*

Proof. If $r_{P+Q} = \hat{\mathbf{1}}$, the inequality is satisfied. We can thus assume that $r_{P+Q} \neq \hat{\mathbf{1}}$. By definition of f_a , we have $f_a(\hat{\mathbf{1}}) = \hat{\mathbf{1}}$, and hence $r_P \neq \hat{\mathbf{1}}$. By the definitions of f_a and g_a , we have $r'_{P+Q} = r_{P+Q}$ and $g_a(\hat{\mathbf{1}}) = \hat{\mathbf{1}}$, and thus similarly $r'_Q \neq \hat{\mathbf{1}}$.

Since r_{P+Q} is different from $\hat{\mathbf{1}}$, it takes the form of a four-tuple. It is straightforward to check that the definition of f_a and g_a ensures that we actually have $r_{P+Q} = (r_P^o + r'_Q^o, \max(r_P^b, r'_Q^b), r_P^f + r'_Q^f, r_P^c + r'_Q^c)$ (the maps g_a counts the resource along an arc in the same way as f_a). The fact that $r_{P+Q} \neq \hat{\mathbf{1}}$ implies that for the last arc a of $P + Q$ we have $f_a^b(r_{(P+Q)\setminus a}^b) = 1$. It means that there is at least one arc a' of $P + Q$ for which there are at least seven consecutive days off between the tail pairing and the head pairing of a' . We have thus $\max(r_P^b, r'_Q^b) = 1$. Hence, $h(r_P, r'_Q) = \rho(r_P^o + r'_Q^o, 1, r_P^f + r'_Q^f, r_P^c + r'_Q^c)$. An argument similar as the one for the seven consecutive days off shows that $r_P^o + r'_Q^o \leq 17$ and $r_P^f + r'_Q^f \leq 85$. Therefore, $h(r_{P+Q}) = r_{P+Q}$, which implies the desired result. \square

Since h is componentwise non-decreasing, this lemma shows that Algorithm 2 can be applied, with the bounds b_v being computed in a pre-processing step relying on dynamic programming, as explained in Section 5.1.

Remark 3. The set of resources R is of dimension 4, which starts to be rather large for dominance. The number of non-dominated paths tends to be large, which means that few paths are cut by dominance, and large sets of non-dominated paths must be stored. In our situation, the CPU time lost performing tests with these sets will be in general larger than the one gained by discarding paths. As mentioned earlier, we are not using dominance for the “N-best-paths” variant (since otherwise the correctness of the algorithm is not ensured); yet, even for the original version of the problem RCLPP-Lex, where a single optimal path is sought, this indicates that dominance should be avoided when solving the pricing problem.

5.3. **The “reduction” trick.** Consider the following minimization problem:

$$\text{lexmin}_{s \in \mathcal{S}} \sum_{p \in s} \begin{bmatrix} \mu_{1p} \\ \vdots \\ \mu_{(m-1)p} \end{bmatrix}. \quad (8)$$

Consider an arbitrary positive integer K . Denote by L the set of the best K feasible solutions of problem (8). Moreover, we define i^* as the smallest index i such that at least two solutions in L provide distinct values for $\sum_{p \in s} \mu_{ip}$. If such an index does not exist, we set $i^* := m + 1$.

Proposition 1. *Every optimal solution of problem (6) for $i > i^*$ is contained in L .*

This proposition can be used to shorten in many cases the computational time for solving problem (6). The following way has been implemented. Determine L with the adaptation of Algorithm 2 for solving the variant “N-best-paths” (with $N := K$) and compute i^* . If

$i^* \leq m - 1$, we simply scan L to find the optimal solutions of problem (6) for $i > i^*$, and we use only Algorithm 2 for $i \leq i^*$. If $i^* \geq m$, then we cannot not conclude anything, and we solve problem (6) for each i with Algorithm 2.

We call it the “reduction” trick.

Proof of Proposition 1. Let s^* be an optimal solution of problem (6) for $i > i^*$. Then s^* is optimal for

$$\operatorname{lexmax}_{s \in \mathcal{S}} \begin{bmatrix} -\lambda_{1i} - \sum_{p \in s} \mu_{1p} \\ \vdots \\ c_{is} - \lambda_{ii} - \sum_{p \in s} \mu_{ip} \\ \vdots \\ -\lambda_{mi} - \sum_{p \in s} \mu_{mp} \end{bmatrix}.$$

By definition of the lexicographic optimization, s^* is also an optimal solution to

$$\operatorname{lexmax}_{s \in \mathcal{S}} \begin{bmatrix} -\lambda_{1i} - \sum_{p \in s} \mu_{1p} \\ \vdots \\ -\lambda_{(i-1)i} - \sum_{p \in s} \mu_{(i-1)p} \end{bmatrix} = \begin{bmatrix} -\lambda_{1i} \\ \vdots \\ -\lambda_{(i-1)i} \end{bmatrix} + \operatorname{lexmax}_{s \in \mathcal{S}} \begin{bmatrix} -\sum_{p \in s} \mu_{1p} \\ \vdots \\ -\sum_{p \in s} \mu_{(i-1)p} \end{bmatrix}.$$

Therefore, s^* is an optimal solution to

$$\operatorname{lexmax}_{s \in \mathcal{S}} \begin{bmatrix} -\sum_{p \in s} \mu_{1p} \\ \vdots \\ -\sum_{p \in s} \mu_{(i-1)p} \end{bmatrix}. \quad (9)$$

Since $i - 1 \geq i^*$, there exist at least two solutions in L providing different values of $-\sum_{p \in s} \begin{bmatrix} \mu_{1p} \\ \vdots \\ \mu_{(i-1)p} \end{bmatrix}$ (at least at row i^*). This implies that L contains all the optimal solutions of problem (9) including s^* , and the result follows. \square

6. NUMERICAL EXPERIMENTS

6.1. Instances and setting. The method proposed in the paper—Algorithm 1 with Algorithm 2 for the pricing problems, together with the “reduction” trick of Section 5.3—has been tested on seven industrial instances provided by Air France. The first column of Table 1 provides the name of these instances. The next two columns present the size of the instances: the number m of pilots and the number of pairings. The last two columns give the size of the graph associated with each pilot: the number of vertices and arcs. All the instances correspond to a horizon of one month with long-haul flights (international flights). The number of days on of the pairings varies from 2 to 8 days.

The experiments were conducted on a server with 192 GB of RAM and 32 cores at 3.30 GHz. The algorithms have not been parallelized. The mathematical models were solved using Gurobi 9.02, with no “presolve,” to ensure a total control on the bases and variables considered by the solver. This is required by the computation of the optimal basis; see Section 4.

Preliminary experiments have shown that the following choices provide good results in general:

- For step 4, we set the number of columns added at each iteration to 10 columns (if any) when the number m of pilots is not larger than 80, and to 16 columns (if any) otherwise. (Algorithm 2 is used with the adaptation for the variant “ N -best-paths” with respectively $N := 10$ and $N := 16$.)
- For the “reduction” trick of Section 5.3, we set $K := m$.

TABLE 1. Problems sizes

	Instance		Graph	
	Number of pilots (m)	Number of pairings	Number of vertices	Number of arcs
I_1	17	69	71	1,769
I_2	25	96	98	3,245
I_3	50	148	150	7,441
I_4	70	209	211	15,130
I_5	80	239	241	18,840
I_6	90	269	272	23,865
I_7	100	298	300	28,891

TABLE 2. Computational times in seconds of the overall method.

Instance	Total	Master problem	Pricing problems	ILLPs
I_1	28.529	12.847	3.437	12.245
I_2	111.175	36.885	13.333	60.956
I_3	1,945.330	1,263.870	63.399	618.057
I_4	7,461.050	3,156.960	1,581.300	2,722.800
I_5	4,626.000	2,265.280	292.459	2,068.260
I_6	27,441.100	17,324.000	1,997.280	8,119.790
I_7	22,503.800	13,968.600	2,495.296	6,039.840

6.2. **Results.** The results are reported in Table 2. The last three columns of Table 2 present respectively the total time needed to solve the master problem, the pricing problems (which is formed by the total time spent in Algorithm 2 plus the small extra time for the “reduction” trick), and the two integer linear lexicographic programs of steps 6 and 8 of Algorithm 1. The overall time spent by Algorithm 1 is given in the second column.

6.3. **Comments.** Table 2 shows that the overall method can solve to optimality all the instances within 8 hours for the hardest one, which makes it relevant for practical applications. We emphasize again that the overall method is conceptually simple, which is an appealing feature when considering implementation aspects and maintenance of the code.

Moreover, our algorithm presents better computational time than the exact approach proposed by Achour et al. [1]. This latter can solve instances of size up to 91 pilots, and the computational time of one of these instances exceeds five days. However, this comment should be taken with care since the two methods have not been tested on the same instances.

The computational time increases rapidly while increasing the size of the instances. The number of pilots has a direct impact on the number of linear programs and pricing problems solved at each iteration of the column generation, whereas increasing the number of pairings increases the size of the graphs and the set of feasible schedules. The results also show that a high proportion of the computational time of the linear relaxation (82.46% on average) is devoted to solving the master problem, which departs from the standard behavior of column generation algorithms. This can be explained by the fact that each iteration requires solving m linear programs (and not a single one as usual) and that the “presolve” of Gurobi has been disabled.

6.4. Further statistics on the method. Table 3 provides more details about the columns added during the resolution of the relaxation of problem (P’) (essentially Step 4 of Algorithm 1).

“Avg. eliminated subproblems (%)” shows the percentage of the average number of problems (6) per column generation iteration that the “reduction” trick solves by a single call to Algorithm 2. Without this trick, the number of such problems to be solved at each iteration is m , the number of pilots. As shown by complementary experiments (see Section 6.5), this might lead to prohibitive computational times. With the above choice of K , this trick is more efficient when the number of pilots is small. Yet, choosing a larger K might lead to prohibitive computational time in Algorithm 2. (For some instances with many equivalent schedules—in terms of scores—experiments have shown that K must be considerably larger to see an increase of the number in this column.)

“Column generation iterations” is the number of times the **repeat-until** loop in Algorithm 1 is repeated.

“Generated columns” is the total number of columns that have been added by step 4 of Algorithm 1.

The statistics of Algorithm 2 are distinguished according to whether it is used to solve the pricing problem (8) or the pricing problem (6) at step 4 of Algorithm 1. The columns “Saved paths” and “Cuts by LB” present respectively the total number of paths that have been saved during the execution of Algorithm 2 for a possible extension, and the total number of paths that have been discarded by lower bounds. The number of paths discarded is in general greater than the number of saved paths, which shows that the lower bounds are important for the efficiency of Algorithm 2.

TABLE 3. Statistics on the column generation.

Instance	Avg. eliminated subproblems (%)	Column generation iterations	Generated columns	Pricing problem (8)		Pricing problem (6)	
				Saved paths	Cuts by LB	Saved paths	Cuts by LB
I_1	90.33	146	38,536	517,415	3,452,012	921,548	4,978,634
I_2	90.76	190	73,062	1,243,524	11,825,689	3,405,690	27,105,000
I_3	62.55	469	320,103	1,203,863	5,064,948	13,155,017	76,587,802
I_4	71.47	515	544,573	33,190,646	125,897,428	419,553,741	1,065,563,476
I_5	66.23	410	285,087	2,476,598	14,573,372	25,764,760	211,888,950
I_6	50.45	1,087	767,957	10,668,239	60,392,412	146,646,412	1,285,787,703
I_7	40.15	907	649,612	13,521,231	73,223,363	201,429,829	2,111,855,852

6.5. Relevance of the “reduction” trick. Experiments on the same instances, but without the “reduction” trick, have been carried out. The settings are the same except that the number of columns added at each iteration is 21 (if any), and that there is of course no K . The number 21 has been determined experimentally to lead to the best possible behavior; yet, despite this choice, Table 4 shows that the performances are very poor when the “reduction” trick is not used. (The information reported in this table is the same as that of Table 2.) The method is not able to solve instances I_5 and I_7 . In these latter instances, many columns have been generated at step 7 which resulted in an “out of memory” error (the computational time of the last column of Table 4 corresponds to the first ILLP). Table 4 shows that the computational time required to solve the remaining instances is always much larger than those reported in Table 2: it is from twice to ten times slower.

Using the “reduction” trick improves as expected the computational time spent solving the pricing problem. Maybe more surprisingly, it also decreases the time spent solving the master problem: it might be related to the fact that the “reduction” trick leads to the addition of the same schedules for the pilots, while without it, there are more variety; but the concrete reason remains elusive.

TABLE 4. Computational times in seconds of the overall method without the “reduction” trick.

Instance	Total	Master problem	Pricing problems	ILLPs
I_1	245.185	116.707	92.464	36.014
I_2	221.893	57.872	94.417	69.604
I_3	6,098.540	4,392.750	232.160	1,473.630
I_4	26,725.000	16,937.400	3,508.760	6,278.880
I_5	-	11,126.800	1,066.980	6,736.420
I_6	274,666.000	247,184.000	5,599.390	21,881.800
I_7	-	65,591.400	4,200.150	16,251.900

7. CONCLUSION

In this work, we propose a lexicographic column generation approach for the PBS that deals directly with the lexicographic objective instead of using a sequence of column generation. Our algorithm can solve to optimality instances with up to 100 pilots in less than 10 hours, which makes it competitive with state-of-the-art approaches. Beyond the generalization of the different algorithmic components of a column generation to the lexicographic setting, two elements are crucial for the performance.

The first element is the ability to find efficiently a lexicographic basic optimal solution of the master problem. Numerical experiments indeed show that it is the most time-consuming phase of the algorithm. Given the importance of the implementation for simplex-like algorithms, this requires using state-of-the-art solvers. Yet, even if such solvers provide the possibility of computing a lexicographic optimal solution using a simple sequential approach, they do not return a lexicographic primal-dual basis, which is a crucial ingredient in any column generation. We have shown in Section 4 that a more elaborate sequential approach provides such a basis with the desired performance.

The second element is the ability to solve efficiently the lexicographic pricing problems. A specificity of the PBS formulation considered in this work is that each objective corresponds to one block of the Dantzig–Wolfe decomposition. With the “reduction” trick introduced in Section 5.3, the resolution of a single lexicographic resource constrained longest-path problem gives the optimal solution of most pilots pricing problems simultaneously. We have seen in numerical experiments that this trick has a huge impact on performance.

REFERENCES

1. A. Achour, M. Gamache, F. Soumis, and G. Desaulniers, *An exact solution approach for the preferential bidding system problem in the airline industry*, *Transportation Science* **41** (2007), no. 3, 354–365.
2. K. Boubaker, G. Desaulniers, and I. Elhallaoui, *Bidline scheduling with equity by heuristic dynamic constraint aggregation*, *Transportation Research Part B: Methodological* **44** (2010), no. 1, 50–61.
3. J. Byrne, *A preferential bidding system for technical aircrew*, 1988 AGIFORS symposium proceedings **28** (1988), 87–99.
4. V. Cacchiani and J-J. Salazar-González, *Optimal solutions to a real-world integrated airline scheduling problem*, *Transportation Science* **51** (2016), no. 1, 250–268.
5. M. Cococcioni, A. Cudazzo, M. Pappalardo, and Y. D. Sergeyev, *Solving the lexicographic multi-objective mixed-integer linear programming problem using branch-and-bound and grossone methodology*, *Communications in Nonlinear Science and Numerical Simulation* **84** (2020), 105177.
6. M. Cococcioni, M. Pappalardo, and Y. D. Sergeyev, *Lexicographic multi-objective linear programming using grossone methodology: Theory and algorithm*, *Applied Mathematics and Computation* **318** (2018), 298 – 311.
7. H. Crowder, E. L. Johnson, and M. Padberg, *Solving Large-Scale Zero-One Linear Programming Problems*, *Operations Research* **31** (1983), no. 5, 803–834 (en).
8. G. Dantzig, R. Fulkerson, and S. Johnson, *Solution of a Large-Scale Traveling-Salesman Problem*, *Journal of the Operations Research Society of America* **2** (1954), no. 4, 393–410, Publisher: INFORMS.
9. M. Gamache, A. Hertz, and J. O. Ouellet, *A graph coloring model for a feasibility problem in monthly crew scheduling with preferential bidding*, *Computers & Operations Research* **34** (2007), no. 8, 2384–2395.
10. M. Gamache, F. Soumis, G. Marquis, and J. Desrosiers, *A column generation approach for large scale aircrew rostering problems*, *Operations Research* **47** (1999), no. 2, 247–262.
11. M. Gamache, F. Soumis, D. Villeneuve, J. Desrosiers, and É. Gélinas, *The preferential bidding system at air canada*, *Transportation Science* **32** (1998), no. 3, 246–255.
12. B. Gopalakrishnan and E. L. Johnson, *Airline crew scheduling: State-of-the-art*, *Annals of Operations Research* volume **140** (2005), 305–337.
13. Stefan Irnich and Guy Desaulniers, *Shortest path problems with resource constraints*, *Column generation*, Springer, 2005, pp. 33–65.
14. H. Isermann, *Linear lexicographic optimization*, *Operations Research Spektrum* **4** (1982), 223–228.
15. N. Kohl and S. E. Karisch, *Airline crew rostering: Problem types, modeling, and optimization*, *Annals of Operations Research* **127** (2004), 223–257.
16. R. Moore, J. Evans, and H. Ngo, *Computerized tailored blocking*, 1978 AGIFORS symposium proceedings **18** (1978), 343–361.
17. G. Nemhauser and L. Wolsey, *Integer and combinatorial optimization*, ch. II.5, pp. 383–432, John Wiley & Sons, Ltd, 1988.
18. A. Parmentier, *Algorithms for non-linear and stochastic resource constrained shortest path*, *Mathematical Methods of Operations Research* **89** (2019), no. 2, 281–317.
19. Julie Pouillet and Axel Parmentier, *Shift Planning Under Delay Uncertainty at Air France: A Vehicle-Scheduling Problem with Outsourcing*, *Transportation Science* (2020).
20. L. Pourkarimi and M. Zarepisheh, *A dual-based algorithm for solving lexicographic multiple objective programs*, *European Journal of Operational Research* **176** (2007), no. 3, 1348 – 1356.

N.E.H. TELLACHE, COLLEGE OF SCIENCE AND ENGINEERING, HAMAD BIN KHALIFA UNIVERSITY,
DOHA, QATAR

Email address: `nour.tellache@gmail.com`

F. MEUNIER, CERMICS, ÉCOLE DES PONTS PARISTECH, 77455 MARNE-LA-VALLÉE CEDEX, FRANCE

Email address: `frederic.meunier@enpc.fr`

A. PARMENTIER, CERMICS, ÉCOLE DES PONTS PARISTECH, 77455 MARNE-LA-VALLÉE CEDEX,
FRANCE

Email address: `axel.parmentier@enpc.fr`