

Conditional entropy minimization principle for learning domain invariant representation features

Thuan Nguyen*, Boyang Lyu*, Prakash Ishwar[†], Matthias Scheutz[‡] and Shuchin Aeron*

*Department of Electrical and Computer Engineering, Tufts University, Medford, MA 02155

[†]Department of Electrical and Computer Engineering, Boston University, Boston, MA 02215

[‡]Department of Computer Science, Tufts University, Medford, MA 02155

Email: Thuan.Nguyen@tufts.edu, Boyang.Lyu@tufts.edu, pi@bu.edu, Matthias.Scheutz@tufts.edu, Shuchin@ece.tufts.edu

Abstract—Invariance principle-based methods, for example, Invariant Risk Minimization (IRM), have recently emerged as promising approaches for Domain Generalization (DG). Despite the promising theory, invariance principle-based approaches fail in common classification tasks due to the mixture of the true invariant features and the spurious invariant features¹. In this paper, we propose a framework based on the conditional entropy minimization principle to filter out the spurious invariant features leading to a new algorithm with a better generalization capability. We theoretically prove that under some particular assumptions, the representation function can precisely recover the true invariant features. In addition, we also show that the proposed approach is closely related to the well-known Information Bottleneck (IB) framework. Both the theoretical and numerical results are provided to justify our approach.

I. INTRODUCTION

A fundamental assumption in most statistical machine learning algorithms is that the training data and the test data are independently and identically distributed (i.i.d). However, it is usually violated in practice due to a phenomenon often referred to as the domain distribution shift where the training domain and the test domain distributions are not the same. This leads to an increased risk/error of the trained classifier on the test domain. Mitigating this issue is the subject of the area broadly referred to as Domain Generalization (DG).

Over the past decade, many methods have been proposed for DG, under different settings [3] [4]. Among these, Invariant Risk Minimization (IRM) [5] [6] has emerged as one of the promising methods. IRM is constructed based on a widely accepted assumption that the representations are general and transferable if the feature representations remain invariant from domain to domain. However, this approach is shown to fail in some simple settings where spurious invariant features exist [2] [7] [8] [9]. A particular example is the problem of classification the cow and the camel images [10] [11] where the label is a deterministic function of the invariant features, for example, the shape of animals, and does not depend on the spurious features such as the background. However, because cows usually appear in a picture with a greenfield while the camels live in a desert with a yellow background, the background becomes the spurious invariant feature. This

can lead to classification errors, for example, if the cow is placed in a yellow field, then it may be misclassified as a camel. Therefore, even though the invariance principle-based approach is able to learn invariant features, it may still fail in the classification task if the extracted features contain not only the true invariant features but also the spurious invariant features. Note that it is possible to eliminate these spurious features, if one can observe a sufficiently large number of domains [1] [2]. For example, if the seen domain contains a picture of a cow walking on a desert, then the greenfield background is obviously not an invariant feature. However, in practice, collecting data from all possible domains is prohibitive.

Several frameworks have been proposed to deal with the presence of spurious invariant features. For example, in [12], the entropy of the extracted features is minimized to filter out the spurious features. This approach has several shortcomings, viz., that it is restricted to linear classifiers and the approach, while motivated by the Information Bottleneck (IB) framework [13], does not directly utilize it in its objective of optimization. A similar approach, directly based on the IB objective function for eliminating the spurious invariant features appears in [14] [15]. Although numerical results in [14] [15] significantly outperform the state-of-the-art methods, the methods are heuristically motivated and lack theoretical justification.

In contrast to the previous works, we make the following novel contributions in this paper.

- We propose a new objective function that is motivated by the conditional entropy minimization principle. In addition, we show that this objective function is explicitly related to the Deterministic Information Bottleneck (DIB) principle [16].
- We theoretically show that under some suitable assumptions, minimizing the proposed objective function leads to filtering out of the spurious features.
- Our approach is general in the sense that it is able to handle non-linear classifiers and may be extended to other DG methods that employ the invariance-principle.

The intuition behind our approach is this - we use the idea behind the IRM for learning a good representation function that can capture both the true invariant features and the

¹In this paper, we use spurious invariant features or spurious features to denote the features that are invariant for all seen domains but variant for unseen domain [1] [2].

spurious invariant features while penalizing the conditional entropy to filter out the spurious invariant features.

The remainder of this paper is structured as follows. In Section II, we summarize relevant work on DG and briefly introduce the IRM algorithm and the IB framework. In Section III, we formally define the problem setup and set-up the notation. Section IV provides the main theoretical results, which motivate our practical approach proposed in Section V. Finally, we provide the numerical results in Section VI and conclude in Section VII.

II. RELATED WORK

A. Domain Generalization

Numerous DG methods have been proposed in the past ten years which can be categorized in some major directions including data manipulation, representation learning, and meta-learning. The performance of a learning model often relies on the quantity and diversity of the training data and data manipulation is one of the cheapest methods to generate samples from a given set of limited data. Data manipulation can be employed via data augmentation [17] [18], domain randomization [19], or adversarial data augmentation [20], [21]. On the other hand, the representation learning approach aims to learn a good representation feature by decomposing the prediction function into a representation function followed by a classifier. Over the past decade, many methods are designed for better representation learning which can be categorized into two different learning principles: domain-invariant representation learning and feature disentanglement. Domain-invariant representation learning is constructed based on the assumption that the representations are general and transferable to different domains if the representation features remain invariant from domain to domain [22]. Notably, domain-invariant representation learning has emerged as one of the most common and efficient approaches in DG and provided many promising results [5] [6] [12] [14] [15] [23]–[27]. Finally, meta-learning methods aim to learn the algorithm itself by learning from previous experience or tasks, i.e., learning-to-learn. Even though meta-learning is a general learning framework, it is recently applied for DG tasks [15] [28] [29]. For more details, we refer the reader to the recent surveys on DG in [3] and [4].

B. Works most related to paper

In this section, we review the IB framework [13] [16] and IRM algorithm [5] which are directly related to our proposed method. We use $f : \mathcal{X} \rightarrow \mathcal{Z}$ to denote a representation function from the input data space \mathcal{X} to the representation space \mathcal{Z} while $g : \mathcal{Z} \rightarrow \mathcal{Y}$ is a classifier/labeling function from the representation space \mathcal{Z} to the label space \mathcal{Y} .

1) *Information Bottleneck Principle*: IB method aims to find the best trade-off between accuracy and complexity (compression) when summarizing a random variable [13]. Particularly, IB aims to find a good representation function f^* via minimizing the following objective function:

$$f^* = \arg \min_f I(X; Z) - \theta I(Y; Z), \quad (1)$$

where $I(X; Z)$ denotes the mutual information between the random variable X that corresponds to input data and its representation $Z = f(X)$, $I(Y; Z)$ denotes the mutual information between the random variable Y corresponding to the label and Z , θ is a positive hyper-parameter that controls the trade off between maximizing $I(Y; Z)$ and minimizing $I(X; Z)$.

Deterministic Information Bottleneck (DIB) [16] generalizes the original IB which aims to minimize the following function:

$$f^* = \arg \min_f H(Z) - \theta I(Y; Z), \quad (2)$$

where $H(Z)$ denotes the entropy of the representation variable $Z = f(X)$. For $\theta = 1$, $H(Z) - \theta I(Y; Z) = H(Z|Y)$ which is the conditional entropy between the representation variable Z and the label Y . Thus, the conditional entropy $H(Z|Y)$ can be considered as a special case of DIB where one wants to keep the balance between compression i.e., minimizing $H(Z)$ and accuracy i.e., maximizing $I(Y; Z)$. In addition, since $H(Z) \geq I(X; Z)$, DIB acts as an upper bound for IB.

The main difference between (1) and (2) comes from their compression terms. Particularly, the compression term in (1) has its origins in rate-distortion theory and channel coding, where $I(X; Z)$ represents the maximum transmission rate, or channel capacity, of the channel. On the other hand, the compression term $H(Z)$ in (2) comes from the source coding literature which measures the number of bits required to encode a random variable. In addition, the optimal representation function of DIB must be a deterministic encoder, in contrast to the stochastic encoder that is optimal under the setting of IB.

2) *Invariant Risk Minimization algorithm*: The IRM algorithm [5] aims to find the representation $Z = f(X)$ for which the optimum classifier g is invariant across all domains. The implicit assumption is that such representations and optimum domain-invariant classifiers exist. In practice, this is approximately realized by solving the following optimization problem [5]:

$$\min_{h \in \mathcal{G} \circ \mathcal{F}} L_{IRM}(h) := \sum_{i=1}^m \left[R^{(i)}(h) + \alpha \|\nabla_{t|t=1.0} R^{(i)}(t \cdot h)\|^2 \right], \quad (3)$$

where \mathcal{F} is a family of representation functions (typically parameterized by weights of a neural network with a given architecture), \mathcal{G} a family of *linear* classifiers (typically the last fully connected classification layer of a classification neural network), $R^{(i)}(g \circ f) := \mathbb{E}_{(X,Y) \sim D_i} [\ell(g(f(X)), Y)]$ denotes a classification risk (e.g., error or cross-entropy loss) of using a representation function f followed by a classifier g in domain i when using loss function ℓ , and α is a hyper-parameter associated with the squared Euclidean norm of the gradients (denoted by ∇) of the risks in different domains. When restricted to the family of linear classifiers and convex differentiable risk functions, Theorem 4 of [5] shows (under certain technical assumptions) that minimizing L_{IRM} will yield a predictor that not only (approximately) minimizes the cumulative risk across all domains (the first term in L_{IRM}), but is also approximately optimum simultaneously across all

domains, i.e., approximately invariant, and this is captured by the sum of squared risk gradients across all domains.

In this paper, we rely on the IRM algorithm [5] to extract the invariant features and use the conditional entropy minimization principle to filter out the spurious invariant features. We note, however, that our approach is applicable to any method that can learn invariant features. We chose IRM due to its popularity and good empirical performance.

III. PROBLEM FORMULATION

In this section, we formulate the minimum conditional entropy principle, which is a special case of the DIB principle, and show that it can be used to filter out spurious features. To do this we first introduce three modeling assumptions underlying our proposed approach. Our assumptions embrace two key ideas (i) the learned features are a linear mixture (superposition) of “true” domain-invariant features and “spurious” domain-specific features, and (ii) the invariant features are conditionally independent of spurious features given the label.

A. Notation

Consider a classification task where the learning algorithm has access to i.i.d. data from the set of m domains $\mathbb{D} = \{D_1, D_2, \dots, D_m\}$. The DG task is to learn a representation function $f : \mathcal{X} \rightarrow \mathcal{Z}$ from the input data space \mathcal{X} to the representation space \mathcal{Z} , and a classifier $g : \mathcal{Z} \rightarrow \mathcal{Y}$ from the representation space \mathcal{Z} to the label space \mathcal{Y} that generalizes well to an unseen domain $D_s \notin \mathbb{D}$.

Let X denote the data random variable, Y denote the label random variable, Z denote the extracted feature random variable in input space, representation space and label space, respectively. Let Z_{inv} denote the invariant feature while Z_{sp} denote the spurious feature. We use $\mathbb{E}[\cdot]$ to denote the expectation, $\text{Var}(\cdot)$ to denote the variance, $H(\cdot)$ to denote both the discrete entropy and the differential entropy and $I(\cdot)$ to denote the mutual information.

B. Assumptions

Ideally, we want to learn a representation function f such that $f(X) = Z_{\text{inv}}$. However, due to a finite number of observed domains, it is possible that the learned features might contain spurious invariant features which are invariant for all observed domains but variant for unseen domain [1] [2]. Specifically, we assume that the representation function is able to extract the features that are (approximately) composed of two elements: the (true) invariant features and the spurious invariant features:

$$f(X) = Z = \Theta(Z_{\text{inv}}, Z_{\text{sp}}). \quad (4)$$

Next, we provide three assumptions on Z_{inv} , Z_{sp} and Θ that will be used in Section IV.

Assumption 1. *The (true) invariant feature Z_{inv} is independent with the spurious invariant feature Z_{sp} for a given label Y . Formally, $Z_{\text{inv}} \perp\!\!\!\perp Z_{\text{sp}}|Y$.*

Assumption 1 is widely accepted in DG literature [10] [12] [2] [30]. For example, in the construction of binary-MNIST dataset [10], the class (label) is first selected, then the color (spurious feature) is independently added to the hand-written digit (invariant feature) picked from the selected class, making $Z_{\text{inv}} \perp\!\!\!\perp Z_{\text{sp}}|Y$. For more details, please see the third constraint in Section 3, page 5 of [10]. In addition, even this assumption is not explicitly stated in [12] [2] [30], Fig. 2 in [12], Fig. 3.1 in [2], and the discussion below Fig. 2 in [30] imply that $Z_{\text{inv}} \perp\!\!\!\perp Z_{\text{sp}}|Y$.

Assumption 2. *The uncertainty of the invariant feature is lower than the uncertainty of the spurious feature when the label is known. Formally, we assume $H(Z_{\text{inv}}|Y) < H(Z_{\text{sp}}|Y)$.*

Conditional entropy is used as a measurement of impurity in clustering algorithm, for example, in the famous C4.5 decision tree [31]–[35]. Since minimizing impurity is equivalent to maximizing the purity, a lower conditional entropy between the data and its cluster (label), a higher purity the cluster is. Therefore, by assuming that $H(Z_{\text{inv}}|Y) < H(Z_{\text{sp}}|Y)$, one assumes the invariant features are well clustered. Under an additional assumption that $H(Z_{\text{inv}}) = H(Z_{\text{sp}})$, $H(Z_{\text{inv}}|Y) < H(Z_{\text{sp}}|Y)$ implies $I(Z_{\text{inv}}; Y) = H(Z_{\text{inv}}) - H(Z_{\text{inv}}|Y) > H(Z_{\text{sp}}) - H(Z_{\text{sp}}|Y) = I(Z_{\text{sp}}; Y)$, or equivalently, the invariant feature Z_{inv} contains more information about label Y than the spurious feature Z_{sp} .

Assumption 3. *$f(X) = Z = \Theta(Z_{\text{inv}}, Z_{\text{sp}}) = aZ_{\text{inv}} + bZ_{\text{sp}}$ and $\text{Var}(Z|Y) = \text{Var}(Z_{\text{inv}}|Y) = \text{Var}(Z_{\text{sp}}|Y) = 1$ where $\text{Var}(\cdot)$ denotes the variance of a random variable.*

Assumption 3 assumes that the extracted (learned) features are a linear combination of invariant features and spurious features i.e., $Z = \Theta(Z_{\text{inv}}, Z_{\text{sp}}) = aZ_{\text{inv}} + bZ_{\text{sp}}$ which is similar to the settings in [5] [12]. This simple linear model allows us to provide some theoretical results in the next section. In the future, to deal with a non-linear function $\Theta(\cdot)$, we intend to use more sophisticated techniques, for example, non-linear Independent Component Analysis (ICA) [36] or non-linear IRM [6] to filter out the spurious features.

On the other hand, the assumption $\text{Var}(Z|Y) = \text{Var}(Z_{\text{inv}}|Y) = \text{Var}(Z_{\text{sp}}|Y) = 1$ is a crucial assumption which originates from the similarity between our proposed method and Blind Source Separation (BSS) methods, for example, ICA, which aim for recovering original sources from their linear mixture model. Particularly, for a given mixture signal M produced by two independent sources S_1, S_2 i.e., $M = aS_1 + bS_2$ and $S_1 \perp\!\!\!\perp S_2$, ICA aims to recover original sources S_1 and S_2 [37]–[39]. However, since $S_1 \perp\!\!\!\perp S_2$, it is also true that $aS_1 \perp\!\!\!\perp bS_2$. Thus, there is no way to tell about the order of sources and their scales, leading to the so-called *permutation ambiguity* and *scaling ambiguity* in ICA [37]–[39]. To fix the arbitrary scaling factor, it is common to require independent components to have unit variance [37]–[39]. Finally, it is worth noting that combining Assumption 1 and Assumption 3 leads to $a^2 + b^2 = 1$ as will be shown later in the proof of Lemma 1.

IV. MAIN RESULTS

Our proposed approach is based on two fundamental steps. The first step is to extract all the invariant features Z from source domains. These extracted invariant features may include both the true invariant feature Z_{inv} and the spurious invariant feature Z_{sp} . The next step is to remove the spurious feature in order to construct a classifier that purely relies on the true invariant features Z_{inv} . For example, in the cow-camel setting, the first step is to learn all extracted invariant features which might contain the color of the background. However, this spurious feature needs to be removed in the second step. In this section, we show that minimizing the conditional entropy principle i.e., minimizing $H(Z|Y)$ supports for filtering the spurious invariant features.

Let $L_{\text{invariant}}$ denote the loss function for a family of invariant algorithms that are capable to learn representation functions f such that $f(X) = Z$ containing both the invariant feature Z_{inv} and the spurious feature Z_{sp} . To filter out Z_{sp} , we want to optimize the following objective function:

$$\begin{aligned} f^* &= \arg \min_f L_{\text{invariant}} \\ \text{s.t. } H(Z|Y) &\leq \gamma. \end{aligned}$$

Next, we show that by adding a constraint on $H(Z|Y)$, or equivalently, by selecting a suitable γ , one is able to extract the (true) invariant feature Z_{inv} .

Lemma 1. *Under the settings in Assumption 1, Assumption 2, and Assumption 3,*

$$H(Z|Y) = H(aZ_{\text{inv}} + bZ_{\text{sp}}|Y) \geq H(Z_{\text{inv}}|Y) \quad (5)$$

and the equality happens if and only if $a = 1$ and $b = 0$.

Proof. First, we want to remind that $H(\cdot)$ is used to denote both the discrete entropy and the differential entropy. Next, under Assumption 1 and Assumption 3, we first show that $a^2 + b^2 = 1$. Indeed,

$$1 = \text{Var}(Z|Y) = \text{Var}(aZ_{\text{inv}} + bZ_{\text{sp}}|Y) \quad (6)$$

$$= a^2 \text{Var}(Z_{\text{inv}}|Y) + b^2 \text{Var}(Z_{\text{sp}}|Y) \quad (7)$$

$$= a^2 + b^2, \quad (8)$$

where (7) due to $Z_{\text{inv}} \perp\!\!\!\perp Z_{\text{sp}}|Y$ and (8) due to the assumption that $\text{Var}(Z_{\text{inv}}|Y) = \text{Var}(Z_{\text{sp}}|Y) = 1$.

Next, we utilize the result in Lemma 1 of [40] which stated that for any two random variables R_1, R_2 , and two scalars a, b , if $R_1 \perp\!\!\!\perp R_2$ and $a^2 + b^2 = 1$, then:

$$H(aR_1 + bR_2) \geq a^2 H(R_1) + b^2 H(R_2). \quad (9)$$

Now, for a given $Y = y \in \mathcal{Y}$, we have:

$$H(aZ_{\text{inv}} + bZ_{\text{sp}}|Y = y) \quad (10)$$

$$\geq a^2 H(Z_{\text{inv}}|Y = y) + b^2 H(Z_{\text{sp}}|Y = y) \quad (11)$$

$$= a^2 H(Z_{\text{inv}}|Y = y) + b^2 H(Z_{\text{inv}}|Y = y) \quad (12)$$

$$+ b^2 H(Z_{\text{sp}}|Y = y) - b^2 H(Z_{\text{inv}}|Y = y) \quad (13)$$

$$= H(Z_{\text{inv}}|Y = y) \quad (14)$$

$$+ b^2 (H(Z_{\text{sp}}|Y = y) - H(Z_{\text{inv}}|Y = y)), \quad (15)$$

with (11) due to (9) and $a^2 + b^2 = 1$, (15) due to $a^2 + b^2 = 1$. Next,

$$H(Z|Y) = H(aZ_{\text{inv}} + bZ_{\text{sp}}|Y) \quad (16)$$

$$= \int_{y \in \mathcal{Y}} p(y) H(aZ_{\text{inv}} + bZ_{\text{sp}}|Y = y) \quad (17)$$

$$\geq \int_{y \in \mathcal{Y}} p(y) H(Z_{\text{inv}}|Y = y) \quad (18)$$

$$+ \int_{y \in \mathcal{Y}} p(y) b^2 (H(Z_{\text{sp}}|Y = y) - H(Z_{\text{inv}}|Y = y)) \quad (19)$$

$$= H(Z_{\text{inv}}|Y) + b^2 (H(Z_{\text{sp}}|Y) - H(Z_{\text{inv}}|Y)) \quad (20)$$

$$\geq H(Z_{\text{inv}}|Y) \quad (21)$$

with (18) due to (15), (19) due to $\int_{y \in \mathcal{Y}} p(y) H(Z_{\text{sp}}|Y = y) = H(Z_{\text{sp}}|Y)$ and $\int_{y \in \mathcal{Y}} p(y) H(Z_{\text{inv}}|Y = y) = H(Z_{\text{inv}}|Y)$, (21) due to $H(Z_{\text{sp}}|Y) > H(Z_{\text{inv}}|Y)$ which is stated in Assumption 2. Even though our proof is constructed for differential entropy, it can be easily extended to discrete entropy.

Obviously that the equality $H(Z|Y) = H(Z_{\text{inv}}|Y)$ happens if and only if $a = 1$ and $b = 0$, or equivalently, $Z = Z_{\text{inv}}$. \square

Lemma 1 points out that $H(Z|Y)$ is always lower bounded by $H(Z_{\text{inv}}|Y)$ and the equality happens if and only if $Z = Z_{\text{inv}}$. Based on Lemma 1, conditional entropy minimization principle is employed to extract the (true) invariant feature Z_{inv} as stated in Theorem 1.

Theorem 1. *Under the settings in Lemma 1, there exists a γ^* such that $f^*(X) = Z = Z_{\text{inv}}$ where:*

$$\begin{aligned} f^* &= \arg \min_f L_{\text{invariant}} \\ \text{s.t. } H(Z|Y) &\leq \gamma^*. \end{aligned}$$

Proof. The proof directly follows from the result in Lemma 1. Indeed, from the Assumption 3, minimizing $L_{\text{invariant}}$ leading to $Z = aZ_{\text{inv}} + bZ_{\text{sp}}$. Now, by selecting a smaller value of γ , it encourages to select f such that $H(Z|Y)$ is minimized. Indeed, from Lemma 1, $H(Z|Y)$ is global lower bounded by $H(Z_{\text{inv}}|Y)$ i.e., $H(Z|Y) \geq H(Z_{\text{inv}}|Y)$, and from the constraint $H(Z|Y) \leq \gamma$, we have $\gamma \geq H(Z|Y) \geq H(Z_{\text{inv}}|Y)$. Thus, for a small enough value of γ i.e., by selecting $\gamma \rightarrow \gamma^* = H(Z_{\text{inv}}|Y)$, $H(Z|Y)$ convergences to $H(Z_{\text{inv}}|Y)$. From Lemma 1, $H(Z|Y) = H(Z_{\text{inv}}|Y)$ if and only if $b = 0$, thus, selecting $\gamma^* = H(Z_{\text{inv}}|Y)$ will lead to a representation function f^* such that $f^*(X) = Z = Z_{\text{inv}}$. \square

In [12], the entropy of the latent variable $H(Z)$ is used to filter out the spurious features. However, $H(Z)$ does not recall about the IB framework which is designed for controlling the trade-off between compression and accuracy [13]. However, since $H(Z|Y) = H(Z) - I(Y; Z)$, minimizing $H(Z|Y)$ is equivalent to minimize the DIB [16], a generalized version of IB [13].

V. PRACTICAL APPROACH

A. Objective Function

Similar to the recent work in [12], [14], we rely on IRM algorithm [5] to optimize $L_{\text{invariant}}$. From the practical objective

function of IRM in (3), we want to optimize the following function:

$$\min_{h \in \mathcal{G} \circ \mathcal{F}} \left[\sum_{i=1}^m R^{(i)}(h) + \alpha \cdot \|\nabla_{t|t=1.0} R^{(i)}(t \cdot h)\|^2 \right] + \beta H(f(X)|Y) \quad (22)$$

where the first two terms are from the IRM framework in (3), the last term is the new conditional entropy term, and α and β are two hyper-parameters that control the trade-off between minimizing the Invariant Risk loss or minimizing the conditional entropy loss. Here, Y denotes the label and $h = g \circ f$ acts as an invariant predictor [5] with $f \in \mathcal{F}$, $g \in \mathcal{G}$, and Z is the output of the penultimate layer of the complete neural network, i.e., the layer just before the output layer. We note that Z and Y represent, respectively, the latent variables and the labels corresponding to the input data X from all seen domains combined.

B. Loss Function Design

In this section, we provide the details of how to minimize the objective function (22) in practice. First, we utilize the implementation from [5] which can be found from [this link](#) to minimize the first two terms in (22). At the same time, we need to optimize the conditional entropy term $H(Z|Y)$. From:

$$H(Z|Y) = H(Z) - I(Z; Y),$$

to minimize $H(Z|Y)$, one looks forward to estimate $H(Z)$ and $I(Z; Y)$.

Approximation of $I(Z; Y)$. Our approach is based on the proposed method in [41]. From the definition:

$$I(Z; Y) = \int p(y, z) \log \frac{p(y|z)}{p(y)} dy dz$$

Since $p(y|z)$ is intractable, one wants to compute $q(y|z)$, a tractable approximation of $p(y|z)$. Follow the proposed method in [41], $I(Z; Y)$ can be approximated via the following lower bound:

$$I(Z; Y) \geq \int p(x)p(y|x)p(z|x) \log q(y|z) dx dy dz.$$

In practice, the reparameterization trick [42] is used to rewrite $z = f(x, \epsilon)$ i.e., the representation variable z is a function of the input x and the Gaussian random variable ϵ to estimate $q(y|z)$ [41]. We refer the reader to a simple implementation of the proposed method in [41] at [this link](#).

Approximation of $H(Z)$. Similar to [12], we use $\text{Var}(Z)$ to estimate $H(Z)$. This is based on the fact that among all continuous random variables with the same variance, Gaussian has the maximum differential entropy and the entropy of Gaussian is directly proportional to its variance.

Finally, the IB term $H(Z|Y)$ can be optimized via minimizing its approximation $\hat{H}(Z|Y)$:

$$\hat{H}(Z|Y) = \text{Var}(Z) - \int p(x)p(y|x)p(z|x) \log q(y|z) dx dy dz. \quad (23)$$

VI. EXPERIMENTS

In this section, we evaluate the efficacy of our proposed method on some DG datasets that contain spurious features.

A. Datasets

AC-CMNIST [5]. Anti-causal-CMNIST dataset is a synthetic binary classification dataset derived from MNIST dataset which is proposed in [5] and also used in [12]. Similar to the CMNIST dataset [44], the images in AC-CMNIST are colored (in red or green) in a way such that the color correlates strongly but spuriously with the label and the goal is to identify whether the colored digit is less than five or more than five. There are three domains in AC-CMNIST: two training domains containing 25,000 data points each, and one test domain containing 10,000 data points. For a fair comparison, we utilize the same construction of AC-CMNIST dataset as in [5] [12].

CS-CMNIST [45]. Covariate-Shift-CMNIST dataset is a synthetic classification dataset derived from CMNIST dataset which is proposed in [45] and also used in [12]. CS-CMNIST relies on selection bias to induce spurious correlations from a synthetic generative model. We follow the same construction method based on [12] to set up a ten-class classification task, where the ten classes are the ten digits from 0 to 9, each digit class is associated with a different color. There are three domains: two training domains containing 20,000 data points each, one test domain also containing 20,000 data points. That said, the color i.e., the spurious feature does not carry any extra information about the label in this dataset. More detail about CS-CMNIST and the model for generating this dataset can be found in Section 7.2.1.A of [45]. For a fair comparison, we utilize the same construction of CS-CMNIST dataset as in [12].

Linear unit dataset (LNU-3/3S) [7]. The linear unit (LNU) dataset is a synthesis dataset that is constructed from a linear low-dimensional model for evaluating out-of-distribution generalization algorithms under the effect of spurious invariant features [7]. There are six sub-datasets in the LNU dataset, each sub-dataset consists of three or six domains, and each domain contains 10,000 data points. Due to the limited time and space, we select two sub-datasets 3 and 3S from the LNU dataset and named LNU-3 and LNU-3S to perform the evaluation. From the numerical results in [12], we note that 3 and 3S are the most challenging sub-datasets in the LNU dataset.

B. Compared Methods

We compare our proposed method, named Conditional Entropy and Invariant Risk Minimization (CE-IRM) against Empirical Risk Minimization (ERM) [43], the original Invariant Risk Minimization (IRM) [5], Information Bottleneck Empirical Risk Minimization (IB-ERM) [12], and Information Bottleneck Invariant Risk Minimization (IB-IRM) [12].

Datasets	#Domains	ERM [43]	IRM [5]	IB-ERM [12]	IB-IRM [12]	CE-IRM (our)
CS-CMNIST	3	60.3 ± 1.2	61.5 ± 1.5	71.8 ± 0.7	71.8 ± 0.7	85.7 ± 0.9
LNU-3	6	67.0 ± 18.0	86.0 ± 18.0	74.0 ± 20.0	81.0 ± 19.0	84.0 ± 19.0
LNU-3S	6	64.0 ± 19.0	86.0 ± 18.0	73.0 ± 20.0	81.0 ± 19.0	90.0 ± 17.0
LNU-3	3	52.0 ± 7.0	52.0 ± 7.0	51.0 ± 6.0	52.0 ± 7.0	52.0 ± 7.0
LNU-3S	3	51.0 ± 6.0	51.0 ± 7.0	51.0 ± 6.0	51.0 ± 7.0	52.0 ± 7.0
AC-CMNIST	3	17.2 ± 0.6	16.5 ± 2.5	17.7 ± 0.5	18.4 ± 1.4	17.5 ± 1.3

TABLE I

Average accuracy in percentage (%) of compared methods. The number of classes in LNU-3/3S and AC-CMNIST datasets is 2 while the number of classes in CS-CMNIST dataset is 10. “#Domains” denotes the number of domains in the dataset.

C. Implementation Details

In this paper, we use the train-domain validation set tuning procedure [12] for hyper-parameters tuning. To construct the validation set, we split seen data into training set and validation set with the ratio of 95% - 5% and choose the model maximizing the accuracy on the validation set.

For AC-CMNIST, we utilize the learning model in [12] which is based on a simple Multi-Layer Perceptron (MLP) with two fully connected layers each having output size 256 followed by an output layer of size two which aims to identify whether the digit is less than 5 or more than 5. Adam optimizer is used for training with a learning rate of 10^{-4} , batch size of 64, and the number of epochs is set to 500. To find the best representation, we perform a search for the weight of Invariant Risk term and the weight of conditional entropy term $\alpha, \beta \in \{0.1, 1, 10, 10^2, 10^3, 10^4\}$.

For CS-CMNIST, we follow the learning model in [12] which is composed of three convolutional layers with feature map dimensions of 256, 128, and 64. Each convolutional layer is followed by a ReLU activation and batch normalization layer. The last layer is a linear layer that aims to classify the digit back to 10 classes. We use SGD optimizer for training with a batch size of 128, learning rate of 10^{-1} and decay every 600 steps with the total number of steps is set to 2,000. Similar to AC-CMNIST, we perform a search for the weight of Invariant Risk term and the weight of conditional entropy term $\alpha, \beta \in \{0.1, 1, 10, 10^2, 10^3, 10^4\}$.

For LNU dataset, we follow the same procedure as described in [12]. Particularly, 20 pairs of α in $[1 - 10^{-0.3}, 1 - 10^{-3}]$, β in $[1 - 10^0, 1 - 10^{-2}]$, learning rate in $[10^{-4}, 10^{-2}]$, and weight of decay in $[10^{-6}, 10^{-2}]$ are randomly sampled and trained. The best model is selected based on the train-domain validation set tuning procedure.

We repeat the whole experiment five times via selecting five random seeds, for each random seed, the whole process of tuning hyper-parameters and selecting models is repeated. Finally, the average accuracy and standard deviation values are reported.

D. Results and Discussion

The numerical results are shown in Table I. As seen, while most of the tested algorithms achieve a decent performance on the CS-CMNIST dataset, CE-IRM (our) algorithm outperforms other methods with a large gap of at least 14%. This

can be explained by the way the CS-CMNIST is generated. Indeed, by construction, the colors (spurious features) are added independently into the digits (invariant features) for a given label, thus, it seems like the assumption $Z_{sp} \perp\!\!\!\perp Z_{inv}|Y$ holds for CS-CMNIST dataset.

For the LNU dataset, we first follow the procedures in [12] to compute the classification error of the tested algorithms. To make the results consistent with other tested datasets, we transform the classification error back to accuracy and report the average accuracy together with its standard deviation. Similar to [12], we compare all algorithms on the LNU-3 dataset and the LNU-3S dataset with the number of domains is set to three or six. Using six domains, CE-IRM (our) algorithm outperforms other methods on LNU-3S but is only the runner-up on LNU-3. Using three domains, CE-IRM provides comparable performance with other methods on both LNU-3 and LNU-3S. In addition, it can be observed that the performance of the tested algorithm is directly proportional to the number of domains available at the training time.

Compare to the CS-CMNIST and the LNU-3/3S datasets, it seems like the AC-CMNIST is the most challenging dataset where none of the tested methods work. Indeed, by construction, AC-CMNIST suffers strong spurious correlations between data and label leading to the failure of all tested algorithms. This situation is also observed in [5], [12], and [14].

It is worth noting that the numerical results of ERM, IRM, IB-ERM, and IB-IRM in Table I are collected from [12]. Finally, our code is released at [this link](#).

VII. CONCLUSIONS

In this paper, we investigate the problem of using the conditional entropy minimization principle for filtering out the spurious features, leading to a new DG approach. Our practical method combines the well-known IRM algorithm and the conditional entropy minimization principle to achieve comparable performances with the state-of-the-art DG methods. In addition, we show that our objective function is closely related to the DIB, and theoretically prove that under certain conditions, our proposed method can truly extract the invariant features. Even though our results are limited by assuming a linear mixture model, the idea of filtering the spurious invariant features is general and can be extended for non-linear models via more sophisticated techniques, for example, the Non-linear Independent Component Analysis.

REFERENCES

- [1] Y. Chen, E. Rosenfeld, M. Sellke, T. Ma, and A. Risteski, "Iterative feature matching: Toward provable domain generalization with logarithmic environments," *arXiv preprint arXiv:2106.09913*, 2021.
- [2] E. Rosenfeld, P. Ravikumar, and A. Risteski, "The risks of invariant risk minimization," *arXiv preprint arXiv:2010.05761*, 2020.
- [3] J. Wang, C. Lan, C. Liu, Y. Ouyang, and T. Qin, "Generalizing to unseen domains: A survey on domain generalization," *arXiv e-prints*, pp. arXiv–2103, 2021.
- [4] K. Zhou, Z. Liu, Y. Qiao, T. Xiang, and C. C. Loy, "Domain generalization: A survey," *arXiv preprint arXiv:2103.02503*, 2021.
- [5] M. Arjovsky, L. Bottou, I. Gulrajani, and D. Lopez-Paz, "Invariant risk minimization," *arXiv preprint arXiv:1907.02893*, 2019.
- [6] C. Lu, Y. Wu, J. M. Hernández-Lobato, and B. Schölkopf, "Nonlinear invariant risk minimization: A causal approach," *arXiv preprint arXiv:2102.12353*, 2021.
- [7] B. Aubin, A. Slowik, M. Arjovsky, L. Bottou, and D. Lopez-Paz, "Linear unit-tests for invariance discovery," *arXiv preprint arXiv:2102.10867*, 2021.
- [8] P. Kamath, A. Tangella, D. Sutherland, and N. Srebro, "Does invariant risk minimization capture invariance?" in *International Conference on Artificial Intelligence and Statistics*. PMLR, 2021, pp. 4069–4077.
- [9] I. Gulrajani and D. Lopez-Paz, "In search of lost domain generalization," *arXiv preprint arXiv:2007.01434*, 2020.
- [10] V. Nagarajan, A. Andreassen, and B. Neyshabur, "Understanding the failure modes of out-of-distribution generalization," *arXiv preprint arXiv:2010.15775*, 2020.
- [11] M.-H. Bui, T. Tran, A. Tran, and D. Phung, "Exploiting domain-specific features to enhance domain generalization," *Advances in Neural Information Processing Systems*, vol. 34, 2021.
- [12] K. Ahuja, E. Caballero, D. Zhang, Y. Bengio, I. Mitliagkas, and I. Rish, "Invariance principle meets information bottleneck for out-of-distribution generalization," *arXiv preprint arXiv:2106.06607*, 2021.
- [13] N. Tishby, F. C. Pereira, and W. Bialek, "The information bottleneck method," *arXiv preprint physics/0004057*, 2000.
- [14] B. Li, Y. Shen, Y. Wang, W. Zhu, C. J. Reed, J. Zhang, D. Li, K. Keutzer, and H. Zhao, "Invariant information bottleneck for domain generalization," *arXiv preprint arXiv:2106.06333*, 2021.
- [15] Y. Du, J. Xu, H. Xiong, Q. Qiu, X. Zhen, C. G. Snoek, and L. Shao, "Learning to learn with variational information bottleneck for domain generalization," in *European Conference on Computer Vision*. Springer, 2020, pp. 200–216.
- [16] D. Strouse and D. J. Schwab, "The deterministic information bottleneck," *Neural computation*, vol. 29, no. 6, pp. 1611–1630, 2017.
- [17] N. H. Nazari and A. Kovashka, "Domain generalization using shape representation," in *European Conference on Computer Vision*. Springer, 2020, pp. 666–670.
- [18] F. C. Borlino, A. D'Innocente, and T. Tommasi, "Rethinking domain generalization baselines," in *2020 25th International Conference on Pattern Recognition (ICPR)*. IEEE, 2021, pp. 9227–9233.
- [19] R. Khirodkar, D. Yoo, and K. Kitani, "Domain randomization for scene-specific car detection and pose estimation," in *2019 IEEE Winter Conference on Applications of Computer Vision (WACV)*. IEEE, 2019, pp. 1932–1940.
- [20] K. Zhou, Y. Yang, T. Hospedales, and T. Xiang, "Deep domain-adversarial image generation for domain generalisation," in *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 34, no. 07, 2020, pp. 13 025–13 032.
- [21] F.-E. Yang, Y.-C. Cheng, Z.-Y. Shiau, and Y.-C. F. Wang, "Adversarial teacher-student representation learning for domain generalization," *Advances in Neural Information Processing Systems*, vol. 34, 2021.
- [22] S. Ben-David, J. Blitzer, K. Crammer, F. Pereira *et al.*, "Analysis of representations for domain adaptation," *Advances in neural information processing systems*, vol. 19, p. 137, 2007.
- [23] Y. Ganin, E. Ustinova, H. Ajakan, P. Germain, H. Larochelle, F. Laviolette, M. Marchand, and V. Lempitsky, "Domain-adversarial training of neural networks," *The journal of machine learning research*, vol. 17, no. 1, pp. 2096–2030, 2016.
- [24] D. Mahajan, S. Tople, and A. Sharma, "Domain generalization using causal matching," in *International Conference on Machine Learning*. PMLR, 2021, pp. 7313–7324.
- [25] F. Zhou, Z. Jiang, C. Shui, B. Wang, and B. Chaib-draa, "Domain generalization with optimal transport and metric learning," *arXiv preprint arXiv:2007.10573*, 2020.
- [26] B. Lyu, T. Nguyen, P. Ishwar, M. Scheutz, and S. Aeron, "Barycentric-alignment and invertibility for domain generalization," *arXiv preprint arXiv:2109.01902*, 2021.
- [27] K. Ahuja, K. Shanmugam, K. Varshney, and A. Dhurandhar, "Invariant risk minimization games," in *International Conference on Machine Learning*. PMLR, 2020, pp. 145–155.
- [28] D. Li, Y. Yang, Y.-Z. Song, and T. Hospedales, "Learning to generalize: Meta-learning for domain generalization," in *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 32, no. 1, 2018.
- [29] Y. Balaji, S. Sankaranarayanan, and R. Chellappa, "Metareg: Towards domain generalization using meta-regularization," *Advances in Neural Information Processing Systems*, vol. 31, pp. 998–1008, 2018.
- [30] E. C. Neto, "Causality-aware counterfactual confounding adjustment for feature representations learned by deep models," *arXiv preprint arXiv:2004.09466*, 2020.
- [31] J. R. Quinlan, *C4. 5: programs for machine learning*. Elsevier, 2014.
- [32] D. Burshtein, V. Della Pietra, D. Kanevsky, and A. Nadas, "Minimum impurity partitions," *The Annals of Statistics*, pp. 1637–1646, 1992.
- [33] D. Coppersmith, S. J. Hong, and J. R. Hosking, "Partitioning nominal attributes in decision trees," *Data Mining and Knowledge Discovery*, vol. 3, no. 2, pp. 197–217, 1999.
- [34] T. Nguyen and T. Nguyen, "Minimizing weighted concave impurity partition under constraints," in *ICASSP 2021-2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*. IEEE, 2021, pp. 3630–3634.
- [35] T. Nguyen, H. Le, and T. Nguyen, "Constant approximation algorithm for minimizing concave impurity," in *ICASSP 2021-2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*. IEEE, 2021, pp. 3635–3639.
- [36] A. Hyvärinen and P. Pajunen, "Nonlinear independent component analysis: Existence and uniqueness results," *Neural networks*, vol. 12, no. 3, pp. 429–439, 1999.
- [37] E. Oja and A. Hyvärinen, "Independent component analysis: A tutorial," *Helsinki University of Technology, Helsinki*, 2004.
- [38] A. Hyvärinen and E. Oja, "Independent component analysis: algorithms and applications," *Neural networks*, vol. 13, no. 4-5, pp. 411–430, 2000.
- [39] G. R. Naik and D. K. Kumar, "An overview of independent component analysis and its applications," *Informatica*, vol. 35, no. 1, 2011.
- [40] S. Verdú and D. Guo, "A simple proof of the entropy-power inequality," *IEEE Transactions on Information Theory*, vol. 52, no. 5, pp. 2165–2166, 2006.
- [41] A. A. Alemi, I. Fischer, J. V. Dillon, and K. Murphy, "Deep variational information bottleneck," *arXiv preprint arXiv:1612.00410*, 2016.
- [42] D. P. Kingma and M. Welling, "Auto-encoding variational bayes," *arXiv preprint arXiv:1312.6114*, 2013.
- [43] V. N. Vapnik, "An overview of statistical learning theory," *IEEE transactions on neural networks*, vol. 10, no. 5, pp. 988–999, 1999.
- [44] Y. LeCun, "The mnist database of handwritten digits," <http://yann.lecun.com/exdb/mnist/>, 1998.
- [45] K. Ahuja, J. Wang, A. Dhurandhar, K. Shanmugam, and K. R. Varshney, "Empirical or invariant risk minimization? a sample complexity perspective," *arXiv preprint arXiv:2010.16412*, 2020.