

On Binary Networked Public Goods Game with Altruism

Arnab Maiti  

Indian Institute of Technology Kharagpur

Palash Dey  

Indian Institute of Technology Kharagpur

Abstract

In the classical Binary Networked Public Goods (BNPG) game, a player can either invest in a public project or decide not to invest. Based on the decisions of all the players, each player receives a reward as per his/her utility function. However, classical models of BNPG game do not consider altruism which players often exhibit and can significantly affect equilibrium behavior. Yu et al. [24] extended the classical BNPG game to capture the altruistic aspect of the players. We, in this paper, first study the problem of deciding the existence of a Pure Strategy Nash Equilibrium (PSNE) in a BNPG game with altruism. This problem is already known to be NP-complete. We complement this hardness result by showing that the problem admits efficient algorithms when the input network is either a tree or a complete graph. We further study the Altruistic Network Modification problem, where the task is to compute if a target strategy profile can be made a PSNE by adding or deleting a few edges. This problem is also known to be NP-complete. We strengthen this hardness result by exhibiting intractability results even for trees. A perhaps surprising finding of our work is that the above problem remains NP-hard even for bounded degree graphs when the altruism network is undirected but becomes polynomial-time solvable when the altruism network is directed. We also show some results on computing an MSNE and some parameterized complexity results. In summary, our results show that it is much easier to predict how the players in a BNPG game will behave compared to how the players in a BNPG game can be made to behave in a desirable way.

2012 ACM Subject Classification Theory of computation → Design and analysis of algorithms → Parameterized complexity and exact algorithms

Keywords and phrases Fixed-Parameter Tractability, W-Hierarchy, Binary Networked Public Goods Game, Nash Equilibrium, Heterogeneous, Fully Homogeneous

Digital Object Identifier 10.4230/LIPIcs.CVIT.2016.23

1 Introduction

In a binary networked public goods (in short BNPG) game, a player can either decide to invest in a public project or decide not to invest in it. Every player however incurs a cost for investing. Based on the decision of all the players, each player receives a reward as per his/her externality function. The net utility is decided based on the reward a player receives and the cost a player incurs. Usually, the externality function and cost of investing differ for every player, making the BNPG game heterogeneous. In some scenarios, the externality function and cost of investing can be the same for every player, making the BNPG game fully homogeneous. Many applications of public goods, for example, wearing a mask [12], getting vaccinated [3], practicing social distancing [5], reporting crimes etc., involve binary decisions. Such domains can be captured using BNPG game. A BNPG game is typically modeled using a network of players which is an undirected graph [11].

We also observe that there are some societies where few people wear masks and/or get themselves vaccinated, and there are some other societies where most people wear masks and get themselves vaccinated [4, 23]. This can be attributed to differences in altruistic behavior among various societies [2, 6]. In an altruistic society, people consider their as



© Arnab Maiti and Palash Dey;
licensed under Creative Commons License CC-BY 4.0

42nd Conference on Very Important Topics (CVIT 2016).

Editors: John Q. Open and Joan R. Access; Article No. 23; pp. 23:1–23:21



Leibniz International Proceedings in Informatics

Schloss Dagstuhl – Leibniz-Zentrum für Informatik, Dagstuhl Publishing, Germany

well as their neighbors' benefit to take a decision. For example, young adults may wear a mask not only to protect themselves but also to protect their elderly parents and young children at home. Altruism can be modeled using an altruistic network which can be either an undirected graph or a directed graph [24]. Symmetric altruism (respectively asymmetric altruism) occurs when the altruistic network is undirected (respectively directed). The utility that a player receives depends on both the input network and the (incoming) incident edges in the altruistic network.

We study the BNPG game with altruism for two different problem settings. First, we look at the problem of deciding the existence of Pure Strategy Nash Equilibrium (PSNE) in the BNPG game with altruism. In any game, determining a PSNE is an important problem as it allows a social planner to predict the behaviour of players in a strategic setting and make appropriate decisions. It is known that deciding the existence of PSNE in a BNPG game (even without altruism) is NP-Complete [25]. This paper mainly focuses on deciding the existence of PSNE in special networks like trees, complete graphs, and graphs with bounded circuit rank. The circuit rank of an undirected graph is the minimum number of edges that must be removed from the graph to make it acyclic.

In the second problem setting, also known as Altruistic Network Modification (in short ANM), we can add or delete an edge from the altruistic network, and each such operation has a non-negative cost associated with it. The aim here is to decide if a target strategy profile can be made a PSNE by adding or deleting edges with certain budget constraints. This problem was first studied by [24] where they showed that ANM is an NP-Complete problem. This problem enables policymakers to strategically run campaigns to make a society more altruistic and achieve desirable outcomes like everyone wearing a mask and getting vaccinated. This paper mainly focuses on ANM in sparse input networks like trees and graphs with bounded degree.

1.1 Contribution

| Input graph type | PSNE existence | ANM symmetric altruism | ANM asymmetric altruism |
|----------------------|----------------|------------------------|-------------------------|
| Tree | P | NP-hard | NP-hard |
| Clique | P | NP-hard (*) | NP-hard (*) |
| Bounded degree | NP-hard (**) | NP-hard | P |
| Bounded circuit rank | P | NP-hard | NP-hard |

■ **Table 1** List of results (our results are in bold). PSNE existence results hold for both symmetric and asymmetric altruism.

We show that the problem of deciding the existence of PSNE in BNPG game with asymmetric altruism is polynomial-time solvable if the input network is either a tree [Theorem 4], complete graph [Theorem 7] or graph with bounded circuit rank [Theorem 6]. Moreover, in Theorem 4, we formulated a non-trivial ILP and depicted a greedy polynomial time algorithm [Algorithm 1] to solve it. This strengthens the tractable results for tree, complete graph and graph with bounded circuit rank in [25, 18] as the previous results were depicted for BNPG games without altruism. However, the problem is open for graphs with bounded

treewidth, and it is known that the problem even without altruism is $W[1]$ -hard for the parameter treewidth [18]. The problem of deciding the existence of PSNE in BNPG game even without altruism is known to be NP-complete [25]. A natural question here is if an MSNE can be computed efficiently. We show that computing an MSNE in BNPG game with symmetric altruism is PPAD-hard [Theorem 8].

ANM with either asymmetric or symmetric altruism is known to be NP-complete when the input network is a clique [24]. We complement this by showing that ANM with either asymmetric or symmetric altruism is NP-complete even when the input network is a tree (the circuit rank of which is zero) and the BNPG game is fully homogeneous [Theorems 12 and 13]. We also show that ANM with symmetric altruism is known to be para-NP-hard for the parameter maximum degree of the input network even when the BNPG game is fully homogeneous and the available budget is infinite [Theorem 16]. However, with asymmetric altruism, the problem is FPT for the parameter maximum degree of the input network [Theorem 15]. To show this result, we designed an $O(2^{n/2})$ time binary search based algorithm [Algorithm 2] for Minimum Knapsack problem. We are the first to provide an algorithm better than $O(2^n)$ time for Minimum Knapsack problem to the best of our knowledge.

We summarize all the main results (including that of prior work) in Table 1. There (\star) denotes the results from [24] and $(\star\star)$ denotes the results from [18]. All the hardness results in the table except for complete graph hold even for fully homogeneous BNPG game. We observe that the PSNE existence problem admits efficient algorithm for many settings compared to ANM. This seems to indicate that enforcing a PSNE is computationally more difficult than finding a PSNE.

1.2 Related Work

Our work is related to [25] who initiated the study of computing a PSNE in BNPG games. Their results were strengthened by [18] who studied the parameterized complexity of deciding the existence of PSNE in BNPG game. Recently, [22] studied about public goods games in directed networks and showed intractibility for deciding the existence of PSNE and for finding MSNE. Our work is also related to [24] who initiated the study of Altruistic Network Modification in BNPG game. [16, 21] also discussed different ways to capture altruism. In the non-altruistic setting, [14] worked on modifying networks to induce certain classes of equilibria in BNPG game. Our work is part of graphical games where the fundamental question is to determine the complexity of finding an equilibrium [8, 9, 13]. Our model is also related to the best-shot games [7] as it is a special case of BNPG game. [11, 17, 20, 15] also discussed some important variations of graphical games.

2 Preliminaries

Let $[n]$ denote the set $\{1, \dots, n\}$. Let $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ be an input network with n vertices (each denoting a player). The input network is always an undirected graph. Let $\mathcal{H} = (\mathcal{V}, \mathcal{E}')$ be an altruistic network on the same set of n vertices. The altruistic network can be directed or undirected graph. An undirected edge between $u, v \in \mathcal{V}$ is represented by $\{u, v\}$. Similarly a directed edge from u to v is represented by (u, v) . N_v is the set of all neighbours (resp. out-neighbours) of the vertex v in an undirected (resp. directed) altruistic network \mathcal{H} . Note that N_v is a subset of neighbours of v in \mathcal{G} . A Binary Networked Public Goods (BNPG) game with asymmetric (resp. symmetric) altruism can be defined on the input graph \mathcal{G} and the directed (resp. undirected) altruistic network \mathcal{H} as follows. We are given a set

of players \mathcal{V} , and the strategy set of every player in \mathcal{V} is $\{0, 1\}$. For a strategy profile $\mathbf{x} = (x_v)_{v \in \mathcal{V}} \in \{0, 1\}^{|\mathcal{V}|}$, let $n_v = |\{u \in \mathcal{V} : \{u, v\} \in \mathcal{E}, x_u = 1\}|$. In this paper, we will be using playing 1 (resp. 0), investing (resp. not investing) and strategy $x_v = 1$ (resp. $x_v = 0$) interchangeably. Now the utility $U_v(\mathbf{x})$ of player $v \in \mathcal{V}$ is defined as follows.

$$U_v(\mathbf{x}) = g_v(x_v + n_v) + a \sum_{u \in N_v} g_u(x_u + n_u) - c_v \cdot x_v$$

where $g_v : \mathbb{N} \cup \{0\} \rightarrow \mathbb{R}^+ \cup \{0\}$ is a non-decreasing externality function in x and $a, c_v \in \mathbb{R}^+ \cup \{0\}$ are constants. c_v can also be interpreted as the cost of investing for player v . We denote a BNPG game with altruism by $(\mathcal{G} = (\mathcal{V}, \mathcal{E}), \mathcal{H} = (\mathcal{V}, \mathcal{E}'), (g_v)_{v \in \mathcal{V}}, (c_v)_{v \in \mathcal{V}}, a)$. We also define $\Delta g(x) = g(x+1) - g(x)$ where $x \in \mathbb{N} \cup \{0\}$. In this paper, we study a general case of BNPG game called *heterogeneous* BNPG game where every player $v \in \mathcal{V}$ need not have the same externality function $g_v(\cdot)$ and constant c_v . If nothing is mentioned, by BNPG game, we are referring to a heterogeneous BNPG game. In this paper, we also study a special case of BNPG game called *fully homogeneous* BNPG game where $g_v = g$ for all $v \in \mathcal{V}$ and $c_v = c$ for all $v \in \mathcal{V}$.

In this paper, we mainly focus on *pure-strategy Nash Equilibrium (PSNE)*. A strategy profile $\mathbf{x} = (x_v)_{v \in \mathcal{V}}$ is said to be a PSNE of a BNPG game with altruism if the following holds true for all $v \in \mathcal{V}$ and for all $x'_v \in \{0, 1\}$

$$U_v(x_v, x_{-v}) \geq U_v(x'_v, x_{-v})$$

where $x_{-v} = (x_u)_{u \in \mathcal{V} \setminus \{v\}}$.

In this paper, we also look at *ε -Nash Equilibrium*. Let Δ_v be a distribution over that strategy set $\{0, 1\}$. We define $\text{Supp}(\Delta_v)$ to be the support of the distribution Δ_v , that is, $\text{Supp}(\Delta_v) = \{x_v : x_v \in \{0, 1\}, \Delta_v(x_v) > 0\}$ where $\Delta_v(x_v)$ denotes the probability of choosing the strategy x_v by player v . Now $(\Delta_v)_{v \in \mathcal{V}}$ is an *ε -Nash Equilibrium* if the following holds true for all $x'_v \in \{0, 1\}$, for all $x_v \in \text{Supp}(\Delta_v)$, for all $v \in \mathcal{V}$:

$$\mathbb{E}_{x_{-v} \sim \Delta_{-v}}[U_v(x_v, x_{-v})] \geq \mathbb{E}_{x_{-v} \sim \Delta_{-v}}[U_v(x'_v, x_{-v})] - \varepsilon$$

where $\Delta_{-v} = (\Delta_u)_{u \in \mathcal{V} \setminus \{v\}}$.

2.1 Altruistic Network Modification

In this paper we study a special case of Altruistic Network Modification (ANM) which was also studied by [24]. If nothing is mentioned, by ANM, we are referring to the special case which we will now discuss. We are given a target profile \mathbf{x}^* , BNPG game on an input graph \mathcal{G} , an initial altruistic network \mathcal{H} , a cost function $C(\cdot)$ and budget B . In this setting, we can add or delete an edge e from \mathcal{H} and each such operation has a non-negative cost $C(e)$ associated with it. We denote an instance of ANM with altruism by $(\mathcal{G} = (\mathcal{V}, \mathcal{E}), \mathcal{H} = (\mathcal{V}, \mathcal{E}'), (g_v)_{v \in \mathcal{V}}, (c_v)_{v \in \mathcal{V}}, a, C(\cdot), B, \mathbf{x}^*)$. The aim of ANM with altruism is to add and delete edges in \mathcal{H} such that \mathbf{x}^* becomes a PSNE and the total cost for adding and delete these edges is at most B . Note that if the altruism is asymmetric (resp. symmetric), then we can add or delete directed (resp. undirected) edges only. Also note that it is not allowed to add any edge between two nodes u, v if $\{u, v\} \notin \mathcal{E}$.

2.2 Standard Definitions

► **Definition 1 (Circuit Rank).** [18] *Let the number of edges and number of vertices in a graph \mathcal{G} be m and n respectively. Then circuit rank is defined to be $m - n + c$ (c is the number*

of connected components in the graph). Note that circuit rank is not the same as feedback arc set.

► **Definition 2 (FPT).** [19] A tuple (x, k) , where k is the parameter, is an instance of a parameterized problem. Fixed parameter tractability (FPT) refers to solvability in time $f(k) \cdot p(|x|)$ for a given instance (x, k) , where p is a polynomial in the input size $|x|$ and f is an arbitrary computable function of k .

► **Definition 3 (para-NP-hard).** [19] We say a parameterized problem is para-NP-hard if it is NP-hard even for some constant values of the parameter.

3 Results for computing equilibrium

In this section, we present the results for deciding the existence of PSNE and finding MSNE in BNPG game with altruism.

[25] showed that the problem of checking the existence of PSNE in BNPG game without altruism is polynomial time solvable when the input network is a tree. We now provide a non-trivial algorithm to show that the problem of checking the existence of PSNE in BNPG game with asymmetric altruism is polynomial time solvable when the input network is a tree.

► **Theorem 4.** *The problem of checking the existence of PSNE in BNPG game with asymmetric altruism is polynomial time solvable when the input network is a tree.*

Proof. For each player $v \in \mathcal{V}$, let d_v denote the degree of v . At each node v with parent u , we maintain a table of tuples (x_u, n_u, x_v, n_v) of valid configurations. A tuple (x_u, n_u, x_v, n_v) is said to be a valid configuration if there exists a strategy profile $\mathbf{x}' = (x'_v)_{v \in \mathcal{V}}$ such that the following holds true:

- ▷ $x'_u = x_u, x'_v = x_v$
- ▷ The number of neighbours of u and v playing 1 in \mathbf{x}' is n_u and n_v respectively
- ▷ None of the players in the sub-tree rooted at v deviate from their strategy in \mathbf{x}'

Note that the root node r doesn't have a parent. Hence, we consider an imaginary parent p with $x_p = 0$ and $g_p(x) = 0$ for all $x \geq 0$. Hence if there is a tuple in the table of root node r then we can conclude that there is a PSNE otherwise we can conclude that there is no PSNE.

Leaf nodes: We add a tuple (x_u, n_u, x_v, n_v) to the table if $n_v = x_u$, v does not deviate if it plays x_v and $x_v \leq n_u \leq d_u + x_v - 1$. Table for the leaf node can be clearly constructed in polynomial time.

Non-leaf nodes: For each tuple (x_u, n_u, x_v, n_v) we do the following. If there is no child u' of v having a tuple of type $(x_v, n_v, x_{u'}, n_{u'})$ in its table, then we don't add (x_u, n_u, x_v, n_v) to the table of v . Similarly if $n_u > d_u + x_v - 1$ or $n_u < x_v$, then we don't add (x_u, n_u, x_v, n_v) to the table of v . Otherwise we do the following. Let U_1 be the set of children u' of v which have tuples of the type $(x_v, n_v, 1, n_{u'})$ in their table but don't have tuples of the type $(x_v, n_v, 0, n_{u'})$. Let U_0 be the set of children u' of v which have tuples of the type $(x_v, n_v, 0, n_{u'})$ in their table but don't have tuples of the type $(x_v, n_v, 1, n_{u'})$. Let U be the set of children u' of v which have tuples of the type $(x_v, n_v, 1, n_{u'})$ and $(x_v, n_v, 0, n_{u'})$ in their table. First let us consider the case when $x_v = 1$. Now for each $u' \in (U_1 \cup U) \cap N_v$, we find the tuple $(1, n_v, 1, n_{u'})$ in its table so that $a \cdot \Delta g_{u'}(n_{u'})$ is maximized and let this value be $y_{u'}$. Similarly for each $u' \in (U_0 \cup U) \cap N_v$, we find the tuple $(1, n_v, 0, n_{u'})$ in the table so that $a \cdot \Delta g_{u'}(n_{u'} - 1)$ is maximized and let this value be $z_{u'}$. Also $\forall u' \in (U_1 \cup U_0 \cup U) \setminus N_v$,

23:6 On Binary Networked Public Goods Game with Altruism

$y_{u'} = z_{u'} = 0$. If $u \in N_v$ then $y_u = a \cdot \Delta g_u(x_u + n_u - 1)$ otherwise $y_u = 0$. Now we include the tuple $(x_u, n_u, x_v = 1, n_v)$ in the table if the optimal value of the following ILP is at least $c_v - \Delta g_v(n_v) - y_u - \sum_{u' \in U_1} y_{u'} - \sum_{u' \in U_0} z_{u'}$.

$$\begin{aligned} \max \quad & \sum_{u' \in U} (x_1^{u'} y_{u'} + x_0^{u'} z_{u'}) \\ \text{s.t.} \quad & x_1^{u'} + x_0^{u'} = 1 \quad \forall u' \in U \\ & \sum_{u' \in U} x_1^{u'} = n_v - x_u - |U_1| \\ & x_1^{u'}, x_0^{u'} \in \{0, 1\} \quad \forall u' \in U \end{aligned}$$

The above ILP can be solved in polynomial time as follows. First sort the values $a_{u'} = |y_{u'} - z_{u'}|$ in non-increasing order breaking ties arbitrarily and order the vertices in U as $\{u_1, \dots, u_{|U|}\}$ as per this order, that is, $a_{u_i} \geq a_{u_j}$ if $i \leq j$. Then we traverse the list of values in non-increasing order and for the u' corresponding to the value, we choose $x_1^{u'} = 1$ if $y_{u'} > z_{u'}$ otherwise we choose $x_0^{u'} = 1$. We do this until $\sum_{u' \in U} x_1^{u'} = n'_v$ or $\sum_{u' \in U} x_0^{u'} = |U| - n'_v$ where $n'_v = n_v - x_u - |U_1|$. Remaining values are chosen in a way such that $\sum_{u' \in U} x_1^{u'} = n_v$ is satisfied. For a more detailed description, please see the Algorithm 1.

Now we show the correctness. Consider an optimal solution x^* . Let i be the smallest number such that $x_1^{u_i} = 1$ as per our algorithm and in optimal solution it is 0. Similarly let i' be the smallest number such that $x_1^{u_{i'}} = 0$ as per our algorithm and in optimal solution it is 1. We now swap the values of the variables $x_1^{u_i}$ and $x_1^{u_{i'}}$ (resp. $x_0^{u_i}$ and $x_0^{u_{i'}}$) in the optimal solution without decreasing the value of the objective function. Let us assume that $i < i'$. Then it must be the case that $y_{u_i} > z_{u_i}$ otherwise $\forall j > i$, we will have $x_1^{u_j} = 1$ as per our algorithm. Hence by swapping in the optimal solution, the value of the objective function increases by at least $a_{u_i} - a_{u_{i'}}$ which is a non-negative quantity. Similarly when $i' < i$, it must be the case that $y_{u_i} \leq z_{u_i}$ otherwise $\forall j > i$, we will have $x_1^{u_j} = 0$ as per our algorithm. Hence by swapping in the optimal solution, the value of the objective function increases by at least $a_{u_{i'}} - a_{u_i}$ which is a non-negative quantity. By repeatedly finding such indices i, i' and then swapping the value of $x_1^{u_i}$ and $x_1^{u_{i'}}$ (resp. $x_0^{u_i}$ and $x_0^{u_{i'}}$) in the optimal solution leads to our solution.

An analogous procedure exists for the case where $x_v = 0$. For each $u' \in (U_1 \cup U) \cap N_v$, we find the tuple $(0, n_v, 1, n_{u'})$ in the table so that $a \cdot \Delta g_{u'}(n_{u'} + 1)$ is minimized and let this value be $y_{u'}$. Similarly for each $u' \in (U_0 \cup U) \cap N_v$, we find the tuple $(1, n_v, 0, n_{u'})$ in the table so that $a \cdot \Delta g_{u'}(n_{u'})$ is minimized and let this value be $z_{u'}$. Also $\forall u' \in (U_1 \cup U_0 \cup U) \setminus N_v$, $y_{u'} = z_{u'} = 0$. If $u \in N_v$ then $y_u = a \cdot \Delta g_u(x_u + n_u)$ otherwise $y_u = 0$. Now we include the tuple $(x_u, n_u, x_v = 0, n_v)$ in the table if the optimal value of the following ILP is at most $c_v - \Delta g_v(n_v) - y_u - \sum_{u' \in U_1} y_{u'} - \sum_{u' \in U_0} z_{u'}$.

$$\begin{aligned} \min \quad & \sum_{u' \in U} (x_1^{u'} y_{u'} + x_0^{u'} z_{u'}) \\ \text{s.t.} \quad & x_1^{u'} + x_0^{u'} = 1 \quad \forall u' \in U \\ & \sum_{u' \in U} x_1^{u'} = n_v - x_u - |U_1| \\ & x_1^{u'}, x_0^{u'} \in \{0, 1\} \quad \forall u' \in U \end{aligned}$$

The above ILP can be solved in polynomial time as follows. First sort the values $a_{u'} = |y_{u'} - z_{u'}|$ in non-increasing order breaking ties arbitrarily and order the vertices in U as

$\{u_1, \dots, u_{|U|}\}$ as per this order, that is, $a_{u_i} \geq a_{u_j}$ if $i \leq j$. Then we traverse the list in non-increasing order and for the u' corresponding to the value, we choose $x_0^{u'} = 1$ if $y_{u'} > z_{u'}$ otherwise we choose $x_1^{u'} = 1$. We do this until $\sum_{u' \in U} x_1^{u'} = n'_v$ or $\sum_{u' \in U} x_0^{u'} = |U| - n'_v$ where $n'_v = n_v - x_u - |U_1|$. Remaining values are chosen in a way such that $\sum_{u' \in U} x_1^{u'} = n_v$ is satisfied.

Now we show the correctness. Consider an optimal solution x^* . Let i be the smallest number such that $x_1^{u_i} = 1$ as per our algorithm and in optimal solution it is 0. Similarly let i' be the smallest number such that $x_1^{u_{i'}} = 0$ as per our algorithm and in optimal solution it is 1. We now swap the values of the variables $x_1^{u_i}$ and $x_1^{u_{i'}}$ (resp. $x_0^{u_i}$ and $x_0^{u_{i'}}$) in the optimal solution without increasing the value of the objective function. Let us assume that $i < i'$. Then it must be the case that $y_{u_i} \leq z_{u_i}$ otherwise $\forall j > i$, we will have $x_1^{u_j} = 1$ as per our algorithm. Hence by swapping in the optimal solution, the value of the objective function decreases by at least $a_{u_i} - a_{u_{i'}}$ which is a non-negative quantity. Similarly when $i' < i$, it must be the case that $y_{u_i} > z_{u_i}$ otherwise $\forall j > i$, we will have $x_1^{u_j} = 0$ as per our algorithm. Hence by swapping in the optimal solution, the value of the objective function increases by at least $a_{u_{i'}} - a_{u_i}$ which is a non-negative quantity. By repeatedly finding such indices i, i' and then swapping the value of $x_1^{u_i}$ and $x_1^{u_{i'}}$ (resp. $x_0^{u_i}$ and $x_0^{u_{i'}}$) in the optimal solution leads to our solution.

As mentioned earlier if there is any tuple in the table of the root r , then we conclude that there is a PSNE otherwise we conclude that there is no such PSNE. ◀

Algorithm 1 ILP Solver

```

1:  $\forall u' \in U, a_{u'} \leftarrow |y_{u'} - z_{u'}|$ .
2: Order the vertices in  $U$  as  $\{u_1, \dots, u_{|U|}\}$  such that  $\forall i, j \in [n]$ , we have  $a_{u_i} \geq a_{u_j}$  if  $i \leq j$ .

3:  $\forall u' \in U, x_0^{u'} \leftarrow 0$  and  $x_1^{u'} \leftarrow 0$ 
4:  $n'_v \leftarrow n_v - x_u - |U_1|$ 
5: for  $i = 1$  to  $|U|$  do
6:   if  $\sum_{u' \in U} x_1^{u'} = n'_v$  then
7:      $x_0^{u_i} \leftarrow 1$  and  $x_1^{u_i} \leftarrow 0$ 
8:   else if  $\sum_{u' \in U} x_0^{u'} = |U| - n'_v$  then
9:      $x_0^{u_i} \leftarrow 0$  and  $x_1^{u_i} \leftarrow 1$ 
10:  else
11:    if  $y_{u_i} > z_{u_i}$  then
12:       $x_0^{u_i} \leftarrow 0$  and  $x_1^{u_i} \leftarrow 1$ 
13:    else
14:       $x_0^{u_i} \leftarrow 1$  and  $x_1^{u_i} \leftarrow 0$ 
15:    end if
16:  end if
17: end for

```

► **Corollary 5.** Given a BNPG game with asymmetric altruism on a tree $\mathcal{G} = (\mathcal{V}, \mathcal{E})$, a set $\mathcal{S} \subseteq \mathcal{V}$ and a pair of tuples $(x'_v)_{v \in \mathcal{S}} \in \{0, 1\}^{|\mathcal{S}|}$ and $(n'_v)_{v \in \mathcal{V}'} \in \{0, 1, \dots, n\}^{|\mathcal{S}|}$, we can decide in polynomial time if there exists a PSNE $\mathbf{x}^* = (x_v)_{v \in \mathcal{V}} \in \{0, 1\}^n$ for the BNPG game with asymmetric altruism such that $x_v = x'_v$ for every $v \in \mathcal{S}$ and the number of neighbors of v playing 1 in \mathbf{x}^* is n'_v for every $v \in \mathcal{S}$.

Proof. In the proof of Theorem 1, just discard those entries from the table of $u \in \mathcal{S}$ which don't have $x_u = x'_u$ and $n_u = n'_u$. ◀

[18] showed that the problem of checking the existence of PSNE in BNPG game without altruism is polynomial time solvable when the input network is a graph with bounded circuit rank. By using the algorithm in Theorem 1 as a subroutine and extending the ideas of [18] to our setting, we show the following.

► **Theorem 6.** *The problem of checking the existence of PSNE in BNPG game with asymmetric altruism is polynomial time solvable when the input network is a graph with bounded circuit rank.*

Proof. Let $(\mathcal{G} = (\mathcal{V}, \mathcal{E}), \mathcal{H} = (\mathcal{V}, \mathcal{E}'), (g_v)_{v \in \mathcal{V}}, (c_v)_{v \in \mathcal{V}}, a)$ be an instance of BNPG game with altruism. Let the circuit rank of \mathcal{G} be d . W.l.o.g. let the graph \mathcal{G} have 1 connected component. First, let us compute the minimum spanning tree $\mathcal{T} = (\mathcal{V}, \mathcal{E}_1)$ of \mathcal{G} . Let $\mathcal{E}'' := \mathcal{E} \setminus \mathcal{E}_1$. Note that $|\mathcal{E}''| = d$. Let $\mathcal{V}' = \{v_1, v_2, \dots, v_\ell\} \subseteq \mathcal{V}$ be the set of endpoints of the edges in \mathcal{E}'' . Note that $|\mathcal{V}'| = \ell \leq 2d$. Let $\mathcal{E}_2 = \{(u, v) : \{u, v\} \in \mathcal{E}_1 \text{ and } (u, v) \in \mathcal{E}'\}$. For all $v \in \mathcal{V}$, let N'_v denote the set of out-neighbours of v in $\mathcal{H}' = (\mathcal{V}, \mathcal{E}_2)$. For every pair of tuples $t = (x'_v)_{v \in \mathcal{V}'} \in \{0, 1\}^\ell$ and $s = (n'_v)_{v \in \mathcal{V}'} \in \{0, 1, \dots, n\}^\ell$, we do the following.

- (i) $\forall v \in \mathcal{V}'$, let n_v^t be the number of neighbours of v in $\mathcal{G}' = (\mathcal{V}, \mathcal{E}'')$ who play 1 in the tuple t . Now below we define g_v^t and c_v^s for all $v \in \mathcal{V}$.

$$g_v^t(x) = \begin{cases} g_v(x + n_v^t) & \text{if } v \in \mathcal{V}' \\ g_v(x) & \text{otherwise} \end{cases}$$

$$c_v^s = \begin{cases} c_v - a \sum_{u \in N_v \setminus N'_v} \Delta g_u(x'_u + n'_u - 1) & \text{if } v \in \mathcal{V}', x'_v = 1 \\ c_v - a \sum_{u \in N_v \setminus N'_v} \Delta g_u(x'_u + n'_u) & \text{if } v \in \mathcal{V}', x'_v = 0 \\ c_v & \text{otherwise} \end{cases}$$

- (ii) Next we decide if there exists a PSNE $(x''_v)_{v \in \mathcal{V}} \in \{0, 1\}^\mathcal{V}$ for the instance $(\mathcal{T}, \mathcal{H}', (g'_v)_{v \in \mathcal{V}}, (c'_v)_{v \in \mathcal{V}}, a)$ of BNPG game with altruism such that

- a. $x''_v = x'_v$ for every $v \in \mathcal{V}'$
- b. $\forall v \in \mathcal{V}'$, the number of neighbours of v in \mathcal{G} whose strategies are 1 in $(x''_v)_{v \in \mathcal{V}}$ is n'_v .

This can be decided by a polynomial time algorithm due to Corollary 5. We return YES if such a PSNE exists.

If no such PSNE exists for every choice of pair of tuples t and s , then we return NO. The running time of our algorithm is $n^{O(d)}$. Now we show that our algorithm returns correct output for every input instance.

In one direction, let there be a PSNE $\mathbf{x}^* = (x_v^*)_{v \in \mathcal{V}}$ for the instance $(\mathcal{G}, \mathcal{H}, (g_v)_{v \in \mathcal{V}}, (c_v)_{v \in \mathcal{V}}, a)$ of BNPG game with altruism. For all $v \in \mathcal{V}$, let n_v^* be the number of neighbours of v in \mathcal{G} whose strategies are 1 in \mathbf{x}^* . We now show that \mathbf{x}^* is a PSNE for the instance $(\mathcal{T}, \mathcal{H}', (g'_v)_{v \in \mathcal{V}}, (c'_v)_{v \in \mathcal{V}}, a)$ of BNPG game with altruism where $t = (x_v^*)_{v \in \mathcal{V}'}$ and $s = (n_v^*)_{v \in \mathcal{V}'}$. Let $n_v^{\mathcal{T}}$ denote the number of neighbors of $v \in \mathcal{V}$ in \mathcal{T}

whose strategies are 1 in \mathbf{x}^* . Due to the definition of n_v^t , we have $n_v^* = n_v^T + n_v^t$ for $v \in \mathcal{V}'$ and $n_v^* = n_v^T$ for $v \in \mathcal{V} \setminus \mathcal{V}'$. Therefore, we have $\Delta g_v^t(n_v^T) = \Delta g_v(n_v^T + n_v^t) = \Delta g_v(n_v^*)$ for $v \in \mathcal{V}'$ and $\Delta g_v^t(n_v^T) = \Delta g_v(n_v^*)$ for $v \in \mathcal{V} \setminus \mathcal{V}'$. Consider a player $v \in \mathcal{V}$. If $x_v^* = 1$, then $\Delta g_v(n_v^*) + a \sum_{u \in N_v} \Delta g_u(x_u^* + n_u^* - 1) \geq c_v$ and hence, we have $\Delta g_v^t(n_v^T) + a \sum_{u \in N_v'} \Delta g_u^t(x_u^* + n_u^T - 1) \geq c_v^s$. Therefore, v does not deviate from its decision of playing 1 in \mathcal{T} . Similarly if $x_v^* = 0$, then $\Delta g_v(n_v^*) + a \sum_{u \in N_v} \Delta g_u(x_u^* + n_u^*) \leq c_v$ and hence, we have $\Delta g_v^t(n_v^T) + a \sum_{u \in N_v'} \Delta g_u^t(x_u^* + n_u^T) \leq c_v^s$. Therefore, v does not deviate from its decision of playing 0 in \mathcal{T} . Hence, \mathbf{x}^* is a PSNE for the instance $(\mathcal{T}, \mathcal{H}', (g_v^t)_{v \in \mathcal{V}}, (c_v^s)_{v \in \mathcal{V}}, a)$ of BNPG game with altruism where $t = (x_v^*)_{v \in \mathcal{V}'}$ and $s = (n_v^*)_{v \in \mathcal{V}'}$. This implies that our algorithm will return YES.

In the other direction, let our algorithm return YES. This means for a pair of tuples $t = (x_v^*)_{v \in \mathcal{V}'}$ and $s = (n_v^*)_{v \in \mathcal{V}'}$, we have a PSNE $(x_v^*)_{v \in \mathcal{V}}$ for the instance $(\mathcal{T}, \mathcal{H}', (g_v^t)_{v \in \mathcal{V}}, (c_v^s)_{v \in \mathcal{V}}, a)$ of BNPG game with altruism. We now show that $(x_v^*)_{v \in \mathcal{V}}$ is a PSNE for the instance $(\mathcal{G}, \mathcal{H}, (g_v)_{v \in \mathcal{V}}, (c_v)_{v \in \mathcal{V}}, a)$ of BNPG game with altruism. Consider a player $v \in \mathcal{V}$. If $x_v^* = 1$, then $\Delta g_v^t(n_v^T) + a \sum_{u \in N_v'} \Delta g_u^t(x_u^* + n_u^T - 1) \geq c_v^s$. Therefore, we have $\Delta g_v(n_v^*) + a \sum_{u \in N_v} \Delta g_u(x_u^* + n_u^* - 1) \geq c_v$. Hence, v does not deviate from its decision of playing 1 in \mathcal{G} . Similarly, if $x_v^* = 0$, then $\Delta g_v^t(n_v^T) + a \sum_{u \in N_v'} \Delta g_u^t(x_u^* + n_u^T) \leq c_v^s$. Therefore, we have $\Delta g_v(n_v^*) + a \sum_{u \in N_v} \Delta g_u(x_u^* + n_u^*) \leq c_v$. Hence, v does not deviate from its decision of playing 0 in \mathcal{G} . Hence, $(x_v^*)_{v \in \mathcal{V}}$ is a PSNE for the instance $(\mathcal{G}, \mathcal{H}, (g_v)_{v \in \mathcal{V}}, (c_v)_{v \in \mathcal{V}}, a)$ of BNPG game with altruism. \blacktriangleleft

[25, 18] showed that the problem of checking the existence of PSNE in BNPG game without altruism is polynomial time solvable when the input network is a complete graph. By extending their ideas to our setting, we show the following.

► **Theorem 7.** *The problem of checking the existence of PSNE in BNPG game with asymmetric altruism is polynomial time solvable when the input network is a complete graph.*

Proof. Let $0 < k < |\mathcal{V}|$ be an integer. First observe that if k players are playing 1, then $x_v + n_v$ for every player $v \in \mathcal{V}$ is k . Let $\mathcal{R}_0(k) := \{v : \Delta g_v(k) + a \cdot \sum_{u \in N_v} \Delta g_u(k) \leq c_v\}$ be the set of players which do not deviate from playing 0 if their k neighbours are playing 1. Let $\mathcal{R}_1(k) := \{v : \Delta g_v(k-1) + a \cdot \sum_{u \in N_v} \Delta g_u(k-1) \geq c_v\}$ be the set of players which do not deviate from playing 1 if their $k-1$ neighbours are playing 1. Now we claim that there is a PSNE where k players are playing 1 iff $|\mathcal{R}_1(k)| \geq k$, $|\mathcal{R}_0(k)| \geq |\mathcal{V}| - k$ and $|\mathcal{R}_0(k) \setminus \mathcal{R}_1(k)| = |\mathcal{V} \setminus \mathcal{R}_1(k)|$.

In one direction, suppose there is a PSNE \mathbf{x}^* with k players playing 1, then there is a subset $\mathcal{I}_1 \subseteq \mathcal{V}$ of at least k players such that $\forall v \in \mathcal{I}_1, c_v \leq \Delta g_v(k-1) + a \cdot \sum_{u \in N_v} \Delta g_u(k-1)$. Therefore, $|\mathcal{R}_1(k)| \geq k$. Now in \mathbf{x}^* we have $|\mathcal{V}| - k$ players who are playing 0. It implies that there is a subset $\mathcal{I}_2 \subseteq \mathcal{V}$ of at least $|\mathcal{V}| - k$ players such that $\forall v \in \mathcal{I}_2, c_v \geq \Delta g_v(k) + a \cdot \sum_{u \in N_v} \Delta g_u(k)$. Therefore, $|\mathcal{R}_0(k)| \geq |\mathcal{V}| - k$. Now observe that a player $v \notin \mathcal{R}_1(k)$ plays 0 in \mathbf{x}^* otherwise v would deviate from its decision. This implies that $v \in \mathcal{R}_0(k)$ as v does not deviate from playing 0 (recall, \mathbf{x}^* is a PSNE). And $\mathcal{R}_0(k) \setminus \mathcal{R}_1(k) \subseteq \mathcal{V} \setminus \mathcal{R}_1(k)$. Hence, $|\mathcal{R}_0(k) \setminus \mathcal{R}_1(k)|$ must be equal to $|\mathcal{V} \setminus \mathcal{R}_1(k)|$.

In the other direction, let it be the case that $|\mathcal{R}_1(k)| \geq k$, $|\mathcal{R}_0(k)| \geq |\mathcal{V}| - k$ and $|\mathcal{R}_0(k) \setminus \mathcal{R}_1(k)| = |\mathcal{V} \setminus \mathcal{R}_1(k)|$. Now let us construct a strategy profile $\mathbf{x}^* = (x_v)_{v \in \mathcal{V}}$ as follows. First, $\forall v \in \mathcal{V} \setminus \mathcal{R}_1(k)$, set $x_v = 0$. Now consider a subset $\mathcal{I} \subseteq \mathcal{R}_1(k) \cap \mathcal{R}_0(k)$ such that $|\mathcal{I}| = |\mathcal{V}| - k - |\mathcal{V} \setminus \mathcal{R}_1(k)|$. We always can choose such a subset \mathcal{I} due to the following:

$$\begin{aligned} |\mathcal{R}_1(k) \cap \mathcal{R}_0(k)| &= |\mathcal{R}_0(k)| - |\mathcal{R}_0(k) \setminus \mathcal{R}_1(k)| \\ &= |\mathcal{R}_0(k)| - |\mathcal{V} \setminus \mathcal{R}_1(k)| \end{aligned}$$

23:10 On Binary Networked Public Goods Game with Altruism

$$\begin{aligned} &\geq |\mathcal{V}| - k - |\mathcal{V} \setminus \mathcal{R}_1(k)| \\ &= |\mathcal{R}_1(k)| - k \geq 0 \end{aligned}$$

Now, $\forall v \in \mathcal{I}$, set $x_v = 0$. For the rest of the k players who are not part of both \mathcal{I} and $\mathcal{V} \setminus \mathcal{R}_1(k)$, we set their strategies as 1. Now we claim that \mathbf{x}^* is a PSNE. A player v with $x_v = 1$ won't deviate as they are part of $\mathcal{R}_1(k)$. Similarly, a player v with $x_v = 0$ won't deviate as they are part of $\mathcal{R}_0(k)$. Hence \mathbf{x}^* is a PSNE.

Having proved our claim, we now present the polynomial time algorithm. First check whether the strategy profile where all players do not invest is PSNE or not. This can be checked in polynomial time. If it is not a PSNE, then check whether the strategy profile where all players invest is PSNE or not. This can also be checked in polynomial time. If it is not a PSNE, then check whether there is a k such that $0 < k < |\mathcal{V}|$, $|\mathcal{R}_1(k)| \geq k$, $|\mathcal{R}_0(k)| \geq |\mathcal{V}| - k$ and $|\mathcal{R}_0(k) \setminus \mathcal{R}_1(k)| = |\mathcal{V} \setminus \mathcal{R}_1(k)|$. If there is such a k , then there exists a PSNE otherwise there is no PSNE. \blacktriangleleft

The problem of deciding the existence of BNPG game with altruism where the altruistic network is empty is known to be NP-Complete[25]. Therefore, we look at the deciding the complexity of finding an ε -Nash equilibrium in BNPG game with symmetric altruism. We show that it is PPAD-Hard. Towards that, we reduce from an instance of Directed public goods game which is known to be PPAD-hard [22]. In directed public goods game, we are given a directed network of players and the utility $U'_u(x_v, x_{-v})$ of a player v is $Y(x_v + n_v^{in}) - p \cdot x_v$. Here $x_v \in \{0, 1\}$, n_v^{in} is the number of in-neighbours of v playing 1 and $Y(x) = 0$ if $x = 0$ and $Y(x) = 1$ if $x > 0$.

► Theorem 8. *It is PPAD-hard to find an ε -Nash equilibrium of the BNPG game with symmetric altruism, for some constant $\varepsilon > 0$.*

Proof. Let $(\mathcal{G}(\mathcal{V}, \mathcal{E}), p)$ be an input instance of directed public goods game. Now we create an instance $(\mathcal{G}' = (\mathcal{V}', \mathcal{E}'), \mathcal{H} = (\mathcal{V}', \mathcal{E}''), (g_v)_{v \in \mathcal{V}'}, (c_v)_{v \in \mathcal{V}'}, a)$ of BNPG game with symmetric altruism.

$$\begin{aligned} \mathcal{V}' &= \{u_{in} : u \in \mathcal{V}\} \cup \{u_{out} : u \in \mathcal{V}\} \\ \mathcal{E}' &= \{\{u_{in}, u_{out}\} : u \in \mathcal{V}'\} \cup \{\{u_{out}, v_{in}\} : (u, v) \in \mathcal{E}\} \\ \mathcal{E}'' &= \{\{u_{in}, u_{out}\} : u \in \mathcal{V}'\} \end{aligned}$$

Let the constant a be 1. $\forall u \in \mathcal{V}$, $c_{u_{in}} = 1 + 2\varepsilon$ and $c_{u_{out}} = p$. Now define the functions $g_w(\cdot)$ as follows:

$$\forall u \in \mathcal{V}, g_{u_{in}}(x) = \begin{cases} 1 & x > 0 \\ 0 & \text{otherwise} \end{cases}$$

$$\forall u \in \mathcal{V}, g_{u_{out}}(x) = 0 \quad \forall x \geq 0$$

Now we show that given any ε -Nash equilibrium of the BNPG game with altruism, we can find an ε -Nash equilibrium of the directed public goods game in polynomial time. Let $(\Delta_u)_{u \in \mathcal{V}'}$ be an ε -Nash equilibrium of the BNPG game with symmetric altruism.

For all $v \in \{u_{in} : u \in \mathcal{V}\}$, we have the following:

$$\begin{aligned} \mathbb{E}_{x_{-v} \sim \Delta_{-v}} [U_v(0, x_{-v})] - \varepsilon &\geq -\varepsilon \\ &> -2\varepsilon \end{aligned}$$

$$\begin{aligned}
&= 1 - c_{u_{in}} \\
&= \mathbb{E}_{x_{-v} \sim \Delta_{-v}} [U_v(1, x_{-v})]
\end{aligned}$$

Hence 1 can't be in the support of Δ_v . Therefore $\forall u \in \mathcal{V}$, $\Delta_{u_{in}}(0) = 1$.

Now we show that $(\Delta_u)_{u \in \mathcal{V}}$ is an ε -Nash equilibrium of the directed public goods game where $\Delta_u = \Delta_{u_{out}} \forall u \in \mathcal{V}$. Now consider a strategy profile $(x_v)_{v \in \mathcal{V}'}$ such that $\forall u \in \mathcal{V}$, we have $x_{u_{in}} = 0$. Now let $(x_v)_{v \in \mathcal{V}}$ be a strategy profile such that $\forall u \in \mathcal{V}$ we have $x_u = x_{u_{out}}$. Then we have the following:

$$\begin{aligned}
&U_{v_{out}}(x_{v_{out}}, x_{-v_{out}}) = g_{v_{in}}(n_{v_{in}}) - p \cdot x_{v_{out}} \\
&= Y(x_v + n_{v_{in}}) - p \cdot x_v = U'_u(x_u, x_{-u})
\end{aligned}$$

Using the above equality and the fact that $\forall u \in \mathcal{V}$, $\Delta_{u_{in}}(0) = 1$, we have $\mathbb{E}_{x_{-u} \sim \Delta_{-u}} [U'_u(x_u, x_{-u})] = \mathbb{E}_{x_{-u_{out}} \sim \Delta_{-u_{out}}} [U_{u_{out}}(x_{u_{out}}, x_{-u_{out}})]$ where $x_u = x_{u_{out}}$. For all $u \in \mathcal{V}$, for all $x'_u \in \{0, 1\}$, for all $x_u \in \text{Supp}(\Delta_u)$, we have the following:

$$\begin{aligned}
&\mathbb{E}_{x_{-u} \sim \Delta_{-u}} [U'_u(x_u, x_{-u})] \\
&= \mathbb{E}_{x_{-u_{out}} \sim \Delta_{-u_{out}}} [U_{u_{out}}(x_{u_{out}} = x_u, x_{-u_{out}})] \\
&\geq \mathbb{E}_{x_{-u_{out}} \sim \Delta_{-u_{out}}} [U_{u_{out}}(x'_{u_{out}} = x'_u, x_{-u_{out}})] - \varepsilon \\
&\geq \mathbb{E}_{x_{-u} \sim \Delta_{-u}} [U_u(x'_u, x_{-u})] - \varepsilon
\end{aligned}$$

Hence, given any ε -Nash equilibrium of the BNPG game with symmetric altruism, we can find an ε -Nash equilibrium of the directed public goods game in polynomial time. This concludes the proof of this theorem. \blacktriangleleft

4 Results for Altruistic Network Modification

In this section, we present the results for Altruistic Network Modification.

First let us call ANM with altruism as heterogeneous ANM with altruism whenever the BNPG game is heterogeneous. Similarly let us call ANM with altruism as fully homogeneous ANM whenever the BNPG game is fully homogeneous. [18] depicted a way to reduce heterogeneous BNPG game to fully homogeneous BNPG game. By extending their ideas to our setting, we show Lemmata 9–11 which will be helpful to prove the theorems on hardness in this section.

► Lemma 9. *Given an instance of heterogeneous ANM with asymmetric altruism such that cost c_v of investing is same for all players v in the heterogeneous BNPG game, we can reduce the instance heterogeneous ANM with asymmetric altruism to an instance of fully homogeneous ANM with asymmetric altruism.*

Proof. Let $(\mathcal{G} = (\mathcal{V} = \{v_i : i \in [n]\}, \mathcal{E}), \mathcal{H} = (\mathcal{V}, \mathcal{E}'), (g_v)_{v \in \mathcal{V}}, (c_v)_{v \in \mathcal{V}}, a, C(\cdot), B, \mathbf{x}^* = (x_v)_{v \in \mathcal{V}})$ be an instance of heterogeneous ANM with asymmetric altruism. $\forall v \in \mathcal{V}$, let $c_v = c$. Using this instance, we create an instance $(\mathcal{G}' = (\mathcal{V}', \mathcal{E}''), \mathcal{H}' = (\mathcal{V}', \mathcal{E}''), (g'_v)_{v \in \mathcal{V}'}, (c'_v)_{v \in \mathcal{V}'}, a', C'(\cdot), B', \mathbf{x}' = (x'_v)_{v \in \mathcal{V}'})$ of fully homogeneous ANM with asymmetric altruism. First we set $a' = a$ and $B' = B$.

Next we construct the graph $\mathcal{G}' = (\mathcal{V}', \mathcal{E}'')$ as follows.

$$\begin{aligned}
\mathcal{V}' &= \bigcup_{i \in [n]} V_i \cup \{u_i : i \in [n]\}, \text{ where} \\
\forall i \in [n], V_i &= \{v_j^i : j \in [2 + n(i - 1)]\}
\end{aligned}$$

23:12 On Binary Networked Public Goods Game with Altruism

$$\mathcal{E}'' = \bigcup_{i \in [n]} E_i \cup \{\{u_i, u_j\} : \{v_i, v_j\} \in \mathcal{E}\}, \text{ where}$$

$$\forall i \in [n], E_i = \{\{u_i, v_j\} : j \in [2 + n(i - 1)]\}$$

Let $f(x) = 1 + \lfloor \frac{x-2}{n} \rfloor$ and $h(x) = x - (2 + n(f(x) - 1))$. We now recursively define a function $g(\cdot)$ as follows.

$$g(x) = \begin{cases} c \cdot x & \text{if } x \in \{0, 1, 2\} \\ g(x-1) + \Delta g_{v_{f(x-1)}}(h(x-1)) & \text{if } x > 2 \end{cases}$$

Now for all $v \in \mathcal{V}'$, we set $g'_v(\cdot) = g(\cdot)$ and $c'_v = c$. Now for all $i \in [n]$, set $x'_{u_i} = x_{v_i}$. For all $v \in \mathcal{V}' \setminus \{u_i : i \in [n]\}$, set $x'_v = 1$. Now we construct the altruistic network $\mathcal{H}' = (\mathcal{V}', E)$ as follows:

$$E = \{(u_i, u_j) : i, j \in [n], (v_i, v_j) \in \mathcal{E}'\}$$

Now we define the cost function $C'(\cdot)$. For all $i, j \in [n]$ such that (u_i, u_j) is allowed to be added to \mathcal{H}' , $C'((u_i, u_j)) = C((v_i, v_j))$. For remaining edges e which are allowed to be added to \mathcal{H}' , $C'(e) = B + 1$.

This completes the description of fully homogeneous ANM with asymmetric altruism. We now claim that the instance of heterogeneous ANM with asymmetric altruism is a YES instance iff the instance of fully homogeneous ANM with asymmetric altruism is a YES instance.

In one direction, let heterogeneous ANM with asymmetric altruism be a YES instance. For all $i, j \in [n]$, if (v_i, v_j) was added to \mathcal{H} , then add (u_i, u_j) to \mathcal{H}' . Similarly for all $i, j \in [n]$, if (v_i, v_j) was removed from \mathcal{H} , then remove (u_i, u_j) from \mathcal{H}' . Now we show that \mathbf{x}' becomes a PSNE. For all $i \in [n]$, let the number of neighbours of v_i playing 1 in \mathbf{x}^* be n_{v_i} . Then the number of neighbours of u_i playing 1 in \mathbf{x}' is $2 + (i - 1)n + n_{v_i}$. Now for all $i \in [n]$ such that $x'_{u_i} = x_{v_i} = 1$, we have $\Delta g(2 + (i - 1)n + n_{v_i}) + a \sum_{u_j \in N_{u_i}} \Delta g(2 + (j - 1)n + n_{v_j} + x'_{u_j} - 1) = \Delta g_{v_i}(n_{v_i}) + a \sum_{v_j \in N_{v_i}} \Delta g_{v_j}(n_{v_j} + x_{v_j} - 1) \geq c$. Hence u_i doesn't deviate from playing 1. Similarly for all $i \in [n]$ such that $x'_{u_i} = x_{v_i} = 0$, we have $\Delta g(2 + (i - 1)n + n_{v_i}) + a \sum_{u_j \in N_{u_i}} \Delta g(2 + (j - 1)n + n_{v_j} + x'_{u_j}) = \Delta g_{v_i}(n_{v_i}) + a \sum_{v_j \in N_{v_i}} \Delta g_{v_j}(n_{v_j} + x_{v_j}) \leq c$. Hence u_i doesn't deviate from playing 0. Remaining nodes u in \mathcal{G}' don't deviate from playing 1 as $\Delta g(0)$ and $\Delta g(1)$ is at least c . Hence fully homogeneous ANM with asymmetric altruism is a YES instance.

In other direction, let fully homogeneous ANM with asymmetric altruism be a YES instance. First observe that an edge not having both the endpoints in the set $\{u_i : i \in [n]\}$ can't be added to \mathcal{H}' otherwise the total cost of the edges added would exceed B . For all $i, j \in [n]$, if (u_i, u_j) was added to \mathcal{H}' , then add (v_i, v_j) to \mathcal{H} . Similarly for all $i, j \in [n]$, if (u_i, u_j) was removed from \mathcal{H}' , then remove (v_i, v_j) from \mathcal{H} . Now we show that \mathbf{x}^* becomes a PSNE. For all $i \in [n]$, let the number of neighbours of v_i playing 1 in \mathbf{x}^* be n_{v_i} . Then the number of neighbours of u_i playing 1 in \mathbf{x}' is $2 + (i - 1)n + n_{v_i}$. Now for all $i \in [n]$ such that $x'_{u_i} = x_{v_i} = 1$, we have $\Delta g_{v_i}(n_{v_i}) + a \sum_{v_j \in N_{v_i}} \Delta g_{v_j}(n_{v_j} + x_{v_i} - 1) = \Delta g(2 + (i - 1)n + n_{v_i}) + a \sum_{u_j \in N_{u_i}} \Delta g(2 + (j - 1)n + n_{v_j} + x'_{u_j} - 1) \geq c$. Hence v_i doesn't deviate from playing 1. Similarly for all $i \in [n]$ such that $x'_{u_i} = x_{v_i} = 0$, we have $\Delta g_{v_i}(n_{v_i}) + a \sum_{v_j \in N_{v_i}} \Delta g_{v_j}(n_{v_j} + x_{v_j}) = \Delta g(2 + (i - 1)n + n_{v_i}) + a \sum_{u_j \in N_{u_i}} \Delta g(2 + (j - 1)n + n_{v_j} + x'_{u_j}) \leq c$. Hence v_i doesn't deviate from playing 0. Hence heterogeneous ANM with asymmetric altruism is a YES instance. \blacktriangleleft

► **Lemma 10.** *Given an instance of heterogeneous ANM with symmetric altruism such that cost c_v of investing is same for all players v in the heterogeneous BNPG game, we can reduce the instance heterogeneous ANM with symmetric altruism to an instance of fully homogeneous ANM with symmetric altruism.*

Proof. Let $(\mathcal{G} = (\mathcal{V} = \{v_i : i \in [n]\}, \mathcal{E}), \mathcal{H} = (\mathcal{V}, \mathcal{E}'), (g_v)_{v \in \mathcal{V}}, (c_v)_{v \in \mathcal{V}}, a, C(\cdot), B, \mathbf{x}^* = (x_v)_{v \in \mathcal{V}})$ be an instance of heterogeneous ANM with symmetric altruism. $\forall v \in \mathcal{V}$, let $c_v = c$. Using this instance, we create an instance $(\mathcal{G}' = (\mathcal{V}', \mathcal{E}''), \mathcal{H}' = (\mathcal{V}', E), (g'_v)_{v \in \mathcal{V}'}, (c'_v)_{v \in \mathcal{V}'}, a', C'(\cdot), B', \mathbf{x}' = (x'_v)_{v \in \mathcal{V}'})$ of fully homogeneous ANM with symmetric altruism. First we set $a' = a$ and $B' = B$.

Next we construct the graph $\mathcal{G}' = (\mathcal{V}', \mathcal{E}'')$ as follows.

$$\begin{aligned} \mathcal{V}' &= \bigcup_{i \in [n]} V_i \cup \{u_i : i \in [n]\}, \text{ where} \\ \forall i \in [n], V_i &= \{v_j^i : j \in [2 + n(i - 1)]\} \\ \mathcal{E}'' &= \bigcup_{i \in [n]} E_i \cup \{\{u_i, u_j\} : \{v_i, v_j\} \in \mathcal{E}\}, \text{ where} \\ \forall i \in [n], E_i &= \{\{u_i, v_j^i\} : j \in [2 + n(i - 1)]\} \end{aligned}$$

Let $f(x) = 1 + \lfloor \frac{x-2}{n} \rfloor$ and $h(x) = x - (2 + n(f(x) - 1))$. We now recursively define a function $g(\cdot)$ as follows.

$$g(x) = \begin{cases} c \cdot x & \text{if } x \in \{0, 1, 2\} \\ g(x-1) + \Delta g_{v_{f(x-1)}}(h(x-1)) & \text{if } x > 2 \end{cases}$$

Now for all $v \in \mathcal{V}'$, we set $g'_v(\cdot) = g(\cdot)$ and $c'_v = c$. Now for all $i \in [n]$, set $x'_{u_i} = x_{v_i}$. For all $v \in \mathcal{V}' \setminus \{u_i : i \in [n]\}$, set $x'_v = 1$. Now we construct the altruistic network $\mathcal{H}' = (\mathcal{V}', E)$ as follows:

$$E = \{\{u_i, u_j\} : i, j \in [n], \{v_i, v_j\} \in \mathcal{E}'\}$$

Now we define the cost function $C'(\cdot)$. For all $i, j \in [n]$ such that $\{u_i, u_j\}$ is allowed to be added to \mathcal{H}' , $C'(\{u_i, u_j\}) = C(\{v_i, v_j\})$. For remaining edges e which are allowed to be added to \mathcal{H}' , $C'(e) = B + 1$.

This completes the description of fully homogeneous ANM with symmetric altruism. We now claim that the instance of heterogeneous ANM with symmetric altruism is a YES instance iff the instance of fully homogeneous ANM with symmetric altruism is a YES instance.

In one direction, let heterogeneous ANM with symmetric altruism be a YES instance. For all $i, j \in [n]$, if $\{v_i, v_j\}$ was added to \mathcal{H} , then add $\{u_i, u_j\}$ to \mathcal{H}' . Similarly for all $i, j \in [n]$, if $\{v_i, v_j\}$ was removed from \mathcal{H} , then remove $\{u_i, u_j\}$ from \mathcal{H}' . Now we show that \mathbf{x}' becomes a PSNE. For all $i \in [n]$, let the number of neighbours of v_i playing 1 in \mathbf{x}^* be n_{v_i} . Then the number of neighbours of u_i playing 1 in \mathbf{x}' is $2 + (i - 1)n + n_{v_i}$. Now for all $i \in [n]$ such that $x'_{u_i} = x_{v_i} = 1$, we have $\Delta g(2 + (i - 1)n + n_{v_i}) + a \sum_{u_j \in N_{u_i}} \Delta g(2 + (j - 1)n + n_{v_j} + x'_{u_j} - 1) = \Delta g_{v_i}(n_{v_i}) + a \sum_{v_j \in N_{v_i}} \Delta g_{v_j}(n_{v_j} + x_{v_j} - 1) \geq c$. Hence u_i doesn't deviate from playing 1. Similarly for all $i \in [n]$ such that $x'_{u_i} = x_{v_i} = 0$, we have $\Delta g(2 + (i - 1)n + n_{v_i}) + a \sum_{u_j \in N_{u_i}} \Delta g(2 + (j - 1)n + n_{v_j} + x'_{u_j}) = \Delta g_{v_i}(n_{v_i}) + a \sum_{v_j \in N_{v_i}} \Delta g_{v_j}(n_{v_j} + x_{v_j}) \leq c$. Hence u_i doesn't deviate from playing 0. Remaining nodes u in \mathcal{G}' don't deviate from playing 1 as $\Delta g(0)$ and $\Delta g(1)$ is at least c . Hence fully homogeneous ANM with symmetric altruism is a YES instance.

23:14 On Binary Networked Public Goods Game with Altruism

In other direction, let fully homogeneous ANM with symmetric altruism be a YES instance. First observe that an edge not having both the endpoints in the set $\{u_i : i \in [n]\}$ can't be added to \mathcal{H}' otherwise the total cost of the edges added would exceed B . For all $i, j \in [n]$, if $\{u_i, u_j\}$ was added to \mathcal{H}' , then add $\{v_i, v_j\}$ to \mathcal{H} . Similarly for all $i, j \in [n]$, if $\{u_i, u_j\}$ was removed from \mathcal{H}' , then remove $\{v_i, v_j\}$ from \mathcal{H} . Now we show that \mathbf{x}^* becomes a PSNE. For all $i \in [n]$, let the number of neighbours of v_i playing 1 in \mathbf{x}^* be n_{v_i} . Then the number of neighbours of u_i playing 1 in \mathbf{x}' is $2 + (i-1)n + n_{v_i}$. Now for all $i \in [n]$ such that $x'_{u_i} = x_{v_i} = 1$, we have $\Delta g_{v_i}(n_{v_i}) + a \sum_{v_j \in N_{v_i}} \Delta g_{v_j}(n_{v_j} + x_{v_i} - 1) = \Delta g(2 + (i-1)n + n_{v_i}) + a \sum_{u_j \in N_{u_i}} \Delta g(2 + (j-1)n + n_{v_j} + x'_{u_j} - 1) \geq c$. Hence v_i doesn't deviate from playing 1. Similarly for all $i \in [n]$ such that $x'_{u_i} = x_{v_i} = 0$, we have $\Delta g_{v_i}(n_{v_i}) + a \sum_{v_j \in N_{v_i}} \Delta g_{v_j}(n_{v_j} + x_{v_j}) = \Delta g(2 + (i-1)n + n_{v_i}) + a \sum_{u_j \in N_{u_i}} \Delta g(2 + (j-1)n + n_{v_j} + x'_{u_j}) \leq c$. Hence v_i doesn't deviate from playing 0. Hence heterogeneous ANM with symmetric altruism is a YES instance. ◀

► **Lemma 11.** *Given an instance of heterogeneous ANM with symmetric altruism such that input network has maximum degree 3, cost c_v of investing is same for all players v in the heterogeneous BNPG game and there are three types of externality functions, we can reduce the instance heterogeneous ANM with symmetric altruism to an instance of fully homogeneous ANM with symmetric altruism such that the input network has maximum degree 13.*

Proof. Let $(\mathcal{G} = (\mathcal{V} = \{v_i : i \in [n]\}, \mathcal{E}), \mathcal{H} = (\mathcal{V}, \mathcal{E}'), (g_v)_{v \in \mathcal{V}}, (c_v)_{v \in \mathcal{V}}, a, C(\cdot), B, \mathbf{x}^* = (x_v)_{v \in \mathcal{V}})$ be an instance of heterogeneous ANM with symmetric altruism. Let us partition \mathcal{V} into three sets $\mathcal{V}_1, \mathcal{V}_2$ and \mathcal{V}_3 such that $\forall i \in [3]$ and $\forall v \in \mathcal{V}_i$, we have $g_v = g_i$ and $c_v = c$. Let $p : [n] \rightarrow [3]$ be a function such that $p(j) = i$ if $v_j \in \mathcal{V}_i$.

Using this instance, we create an instance $(\mathcal{G}' = (\mathcal{V}', \mathcal{E}'), \mathcal{H}' = (\mathcal{V}', E), (g'_v)_{v \in \mathcal{V}'}, (c'_v)_{v \in \mathcal{V}'}, a', C'(\cdot), B', \mathbf{x}' = (x'_v)_{v \in \mathcal{V}'})$ of fully homogeneous ANM with symmetric altruism. First we set $a' = a$ and $B' = B$.

Next we construct the graph $\mathcal{G}' = (\mathcal{V}', \mathcal{E}')$ as follows.

$$\begin{aligned} \mathcal{V}' &= \bigcup_{i \in [3]} V_i \cup \{u_i : i \in [n]\}, \text{ where} \\ \forall i \in [3], V_i &= \{v_j^i : j \in [2 + 4(i-1)]\} \\ \mathcal{E}' &= \bigcup_{i \in [3]} E_i \cup \{\{u_i, u_j\} : \{v_i, v_j\} \in \mathcal{E}\}, \text{ where} \\ \forall i \in [3], E_i &= \{\{u, v_j^i\} : j \in [2 + 4(i-1)], u \in V_i\} \end{aligned}$$

It is easy to observe that the maximum degree of \mathcal{G}' is 13.

Let $f(x) = 1 + \lfloor \frac{x-2}{4} \rfloor$ and $h(x) = x - (2 + 4(f(x) - 1))$. We now recursively define a function $g(\cdot)$ as follows.

$$g(x) = \begin{cases} c \cdot x & \text{if } x \in \{0, 1, 2\} \\ g(x-1) + \Delta g_{f(x-1)}(h(x-1)) & \text{if } x > 2 \end{cases}$$

For all $i \in [n]$, let $c'_{u_i} = c_{v_i}$. For all $v \in \mathcal{V}' \setminus \{u_i : i \in [n]\}$, $c'_v = c$. Now for all $v \in \mathcal{V}'$, we set $g'_v(\cdot) = g(\cdot)$. Now for all $i \in [n]$, set $x'_{u_i} = x_{v_i}$. For all $v \in \mathcal{V}' \setminus \{u_i : i \in [n]\}$, set $x'_v = 1$. Now we construct the altruistic network $\mathcal{H}' = (\mathcal{V}', E)$ as follows:

$$E = \{\{u_i, u_j\} : i, j \in [n], \{v_i, v_j\} \in \mathcal{E}'\}$$

Now we define the cost function $C'(\cdot)$. For all $i, j \in [n]$ such that $\{u_i, u_j\}$ is allowed be added to \mathcal{H}' , $C'(\{u_i, u_j\}) = C(\{v_i, v_j\})$. For remaining edges e which are allowed to be added to \mathcal{H}' , $C'(e) = B + 1$.

This completes the description of fully homogeneous ANM with symmetric altruism. We now claim that the instance of heterogeneous ANM with symmetric altruism is a YES instance iff the instance of fully homogeneous ANM with symmetric altruism is a YES instance.

In one direction, let heterogeneous ANM with symmetric altruism be a YES instance. For all $i, j \in [n]$, if $\{v_i, v_j\}$ was added to \mathcal{H} , then add $\{u_i, u_j\}$ to \mathcal{H}' . Similarly for all $i, j \in [n]$, if $\{v_i, v_j\}$ was removed from \mathcal{H} , then remove $\{u_i, u_j\}$ from \mathcal{H}' . Now we show that \mathbf{x}' becomes a PSNE. For all $i \in [n]$, let the number of neighbours of v_i playing 1 in \mathbf{x}^* be n_{v_i} . Then the number of neighbours of u_i playing 1 in \mathbf{x}' is $2 + 4(p(i) - 1) + n_{v_i}$. Now for all $i \in [n]$ such that $x'_{u_i} = x_{v_i} = 1$, we have $\Delta g(2 + 4(p(i) - 1) + n_{v_i}) + a \sum_{u_j \in N_{u_i}} \Delta g(2 + 4(p(j) - 1) + n_{v_j} + x'_{u_j} - 1) = \Delta g_{p(i)}(n_{v_i}) + a \sum_{v_j \in N_{v_i}} \Delta g_{p(j)}(n_{v_j} + x_{v_j} - 1) \geq c$. Hence u_i doesn't deviate from playing 1. Similarly for all $i \in [n]$ such that $x'_{u_i} = x_{v_i} = 0$, we have $\Delta g(2 + 4(p(i) - 1) + n_{v_i}) + a \sum_{u_j \in N_{u_i}} \Delta g(2 + 4(p(j) - 1) + n_{v_j} + x'_{u_j}) = \Delta g_{p(i)}(n_{v_i}) + a \sum_{v_j \in N_{v_i}} \Delta g_{p(j)}(n_{v_j} + x_{v_j}) \leq c$. Hence u_i doesn't deviate from playing 0. Remaining nodes u in \mathcal{G}' don't deviate from playing 1 as $\Delta g(0)$ and $\Delta g(1)$ is at least c . Hence fully homogeneous ANM with symmetric altruism is a YES instance.

In other direction, let fully homogeneous ANM with symmetric altruism be a YES instance. First observe that an edge not having both the endpoints in the set $\{u_i : i \in [n]\}$ can't be added to \mathcal{H}' otherwise the total cost of the edges added would exceed B . For all $i, j \in [n]$, if $\{u_i, u_j\}$ was added to \mathcal{H}' , then add $\{v_i, v_j\}$ to \mathcal{H} . Similarly for all $i, j \in [n]$, if $\{u_i, u_j\}$ was removed from \mathcal{H}' , then remove $\{v_i, v_j\}$ from \mathcal{H} . Now we show that \mathbf{x}^* becomes a PSNE. For all $i \in [n]$, let the number of neighbours of v_i playing 1 in \mathbf{x}^* be n_{v_i} . Then the number of neighbours of u_i playing 1 in \mathbf{x}' is $2 + 4(p(i) - 1) + n_{v_i}$. Now for all $i \in [n]$ such that $x'_{u_i} = x_{v_i} = 1$, we have $\Delta g_{p(i)}(n_{v_i}) + a \sum_{v_j \in N_{v_i}} \Delta g_{p(j)}(n_{v_j} + x_{v_j} - 1) = \Delta g(2 + 4(p(i) - 1) + n_{v_i}) + a \sum_{u_j \in N_{u_i}} \Delta g(2 + 4(p(j) - 1) + n_{v_j} + x'_{u_j} - 1) \geq c$. Hence v_i doesn't deviate from playing 1. Similarly for all $i \in [n]$ such that $x'_{u_i} = x_{v_i} = 0$, we have $\Delta g_{p(i)}(n_{v_i}) + a \sum_{v_j \in N_{v_i}} \Delta g_{p(j)}(n_{v_j} + x_{v_j}) = \Delta g(2 + 4(p(i) - 1) + n_{v_i}) + a \sum_{u_j \in N_{u_i}} \Delta g(2 + 4(p(j) - 1) + n_{v_j} + x'_{u_j}) \leq c$. Hence v_i doesn't deviate from playing 0. Hence heterogeneous ANM with symmetric altruism is a YES instance. ◀

ANM with asymmetric altruism is known to be NP-complete when the input network is a clique [24]. We show a similar result for trees by reducing from Knapsack problem.

► **Theorem 12.** *For the target profile where all players invest, ANM with asymmetric altruism is NP-complete when the input network is a tree and the BNPG game is fully homogeneous.*

Proof. We reduce from the decision version of the KNAPSACK Problem. In Knapsack problem, we are given a set of items $1, \dots, n$ with profits p_1, \dots, p_n and weights w_1, \dots, w_n . The aim is to check whether there exists a subset S of items such that $\sum_{i \in S} p_i \geq P$ and $\sum_{i \in S} w_i \leq W$. Now we create an instance of ANM with asymmetric altruism. We set $a = 1$. The input graph $\mathcal{G}(\mathcal{V}, \mathcal{E})$ is defined as follows

$$\begin{aligned} \mathcal{V} &= \{u_i : i \in [2n + 1]\} \\ \mathcal{E} &= \{\{u_i, u_{n+i}\}, \{u_i, u_{2n+1}\} : i \in [n]\} \end{aligned}$$

Let the initial altruistic graph $\mathcal{H}(\mathcal{V}, \mathcal{E}')$ be empty. Let the target profile x^* have all the players investing (i.e., playing 1). Now we define the functions $g_u(\cdot)$ for all $u \in \mathcal{V}$. $g_{u_{2n+1}}(x) = 0$ for all $x \geq 0$. For all $i \in [n]$, $g_{u_i}(x) = x \cdot p_i$ for all $x \geq 0$. For all $i \in [n]$, $g_{u_{n+i}}(x) = x \cdot P$ for all $x \geq 0$. For all $i \in [2n + 1]$, $c_{u_i} = P$. Now we define the cost of the introducing an altruistic

23:16 On Binary Networked Public Goods Game with Altruism

edge. The cost of introducing the edge (u_{2n+1}, u_i) is w_i . For remaining edges e which are allowed to be added to \mathcal{H} , cost of adding e is 0. Let the total budget be W . This completes the description of the instance of ANM with asymmetric altruism.

Now we show that KNAPSACK Problem is a yes instance iff ANM with asymmetric altruism is a yes instance. In other direction, let KNAPSACK problem be a yes instance. Then there is a subset S of items such that $\sum_{i \in S} p_i \geq P$ and $\sum_{i \in S} w_i \leq W$. Now if we introduce the set of altruistic edges $\{(u_{2n+1}, u_i) : i \in S\} \cup \{(u_i, u_{n+i}) : i \in [n]\}$, then the target profile becomes a PSNE and the total of introducing these edges is at most B . Hence ANM with asymmetric altruism is a yes instance.

In the other direction, let the ANM with asymmetric altruism be a yes instance. Then there is a set of altruistic edges S' of total cost at most B such that when they are introduced the target profile becomes a PSNE. Let $S := \{i : (u_{2n+1}, u_i) \in S'\}$. Hence if the subset S of items is chosen then we have $\sum_{i \in S} p_i \geq P$ and $\sum_{i \in S} w_i \leq W$. Hence the KNAPSACK problem is a yes instance.

Applying Lemma 9 concludes the proof of this theorem. \blacktriangleleft

ANM with symmetric altruism is known to be NP-complete when the input network is a clique [24]. We show a similar result for trees by reducing from Knapsack problem.

► Theorem 13. *For the target profile where all players invest, ANM with symmetric altruism is NP-complete when the input network is a tree and the BNPG game is fully homogeneous.*

Proof. We reduce from the decision version of the KNAPSACK Problem. In Knapsack problem, we are given a set of items $1, \dots, n$ with profits p_1, \dots, p_n and weights w_1, \dots, w_n . The aim is to check whether there exists a subset S of items such that $\sum_{i \in S} p_i \geq P$ and $\sum_{i \in S} w_i \leq W$. Now we create an instance of ANM with symmetric altruism as follows. We set $a = 1$. The input graph $\mathcal{G}(\mathcal{V}, \mathcal{E})$ is defined as follows

$$\begin{aligned} \mathcal{V} &= \{u_i : i \in [2n+1]\} \\ \mathcal{E} &= \{\{u_i, u_{n+i}\}, \{u_i, u_{2n+1}\} : i \in [n]\} \end{aligned}$$

Let the initial altruistic graph $\mathcal{H}(\mathcal{V}, \mathcal{E}')$ be empty. Let the target profile x^* have all the players investing (i.e., playing 1). Now we define the functions $g_u(\cdot)$ for all $u \in \mathcal{V}$. $g_{u_{2n+1}}(x) = 0$ for all $x \geq 0$. For all $i \in [n]$, $g_{u_i}(x) = x \cdot p_i$ for all $x \geq 0$. For all $i \in [n]$, $g_{u_{n+i}}(x) = x \cdot P$ for all $x \geq 0$. For all $i \in [2n+1]$, $c_{u_i} = P$. Now we define the cost of introducing an altruistic edge. For all $i \in [n]$, the cost of introducing the edge $\{u_{2n+1}, u_i\}$ is w_i . For all $i \in [n]$, the cost of introducing the edge $\{u_{n+i}, u_i\}$ is 0. Let the total budget be W . This completes the description of the instance of ANM with symmetric altruism.

Now we show that KNAPSACK Problem is a yes instance iff ANM with symmetric altruism is a yes instance. In other direction, let KNAPSACK problem be a yes instance. Then there is a subset S of items such that $\sum_{i \in S} p_i \geq P$ and $\sum_{i \in S} w_i \leq W$. Now if we introduce the set of altruistic edges $\{\{u_{2n+1}, u_i\} : i \in S\} \cup \{\{u_{n+i}, u_i\} : i \in [n]\}$, then the target profile becomes a PSNE and the total of introducing these edges is at most B . Hence ANM with symmetric altruism is a yes instance.

In the other direction, let the ANM with symmetric altruism be a yes instance. Then there is a set of altruistic edges S' of total cost at most B such that when they are introduced the target profile becomes a PSNE. Let $S := \{i : \{u_{2n+1}, u_i\} \in S'\}$. Hence if the subset S of items is chosen then we have $\sum_{i \in S} p_i \geq P$ and $\sum_{i \in S} w_i \leq W$. Hence the KNAPSACK problem is a yes instance.

Applying Lemma 10 concludes the proof of this theorem. \blacktriangleleft

We now show that ANM with symmetric altruism is known to be para-NP-hard for the parameter maximum degree of the input network even when the BNPG game is fully homogeneous. Towards that, we reduce from an instance of (3, B2)-SAT which is known to be NP-complete [1]. (3, B2)-SAT is the special case of 3-SAT where each variable x_i occurs exactly twice as negative literal \bar{x}_i and twice as positive literal x_i .

► **Theorem 14.** *For the target profile where all players invest, ANM with symmetric altruism is known to be para-NP-hard for the parameter maximum degree of the input network even when the BNPG game is fully homogeneous.*

Proof. To show the NP-hardness, we reduce from an instance of (3, B2)-SAT which we denote by $(\mathcal{X} = \{x_i : i \in [n]\}, \mathcal{C} = \{C_j : j \in [m]\})$. We define a function $h : \{x_i, \bar{x}_i : i \in [n]\} \rightarrow \{z_i, \bar{z}_i : i \in [n]\}$ as $h(x_i) = z_i$ and $h(\bar{x}_i) = \bar{z}_i$ for all $i \in [n]$. We now create an instance of ANM with symmetric altruism as follows. Let the initial altruistic network \mathcal{H} be empty and $a = 0.5$. Input graph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ for the input BNPG game is as follows:

$$\begin{aligned} \mathcal{V} &= \{z_i, \bar{z}_i, b_i : i \in [n]\} \cup \{y_j : j \in [m]\} \\ \mathcal{E} &= \{\{y_j, h(l_1^j)\}, \{y_j, h(l_2^j)\}, \{y_j, h(l_3^j)\} : C_j = (l_1^j \vee l_2^j \vee l_3^j), j \in [m]\} \\ &\quad \cup \{\{z_i, b_i\}, \{b_i, \bar{z}_i\} : i \in [n]\} \end{aligned}$$

Now observe that the degree of every vertex in \mathcal{G} is at most 3. We now define $(c_v)_{v \in \mathcal{V}}$ and $(g_v)_{v \in \mathcal{V}}$. $\forall v \in \mathcal{V}, c_v = 315$. $\forall j \in [m]$ and $\forall x \in \mathbb{N} \cup \{0\}$, $g_{y_j}(x) = 220x$. $\forall i \in [n]$ and $\forall x \in \mathbb{N} \cup \{0\}$, $g_{z_i}(x) = g_{\bar{z}_i}(x) = 200x$. $\forall i \in [n]$ and $\forall x \in \mathbb{N} \cup \{0\}$, $g_{b_i}(x) = 240x$. Target profile \mathbf{x}^* has all the players investing. Now define the cost of adding edges to \mathcal{H} . Cost of adding an edge from the set $\{\{y_j, h(l_1^j)\}, \{y_j, h(l_2^j)\}, \{y_j, h(l_3^j)\} : C_j = (l_1^j \vee l_2^j \vee l_3^j), j \in [m]\}$ is 1. Cost of adding an edge from the set $\{\{z_i, b_i\}, \{b_i, \bar{z}_i\} : i \in [n]\}$ is $c = 2n + 1$. The budget B is $n(2 + c)$. This completes the construction of the instance of ANM with symmetric altruism.

Now we prove that the instance of (3, B2)-SAT is a YES instance iff the instance of ANM with symmetric altruism is a YES instance. In one direction, let (3, B2)-SAT be a YES instance and its satisfying assignment be $f : \{x_i, \bar{x}_i : i \in [n]\} \rightarrow \{\text{TRUE}, \text{FALSE}\}$. For all $i \in [n]$, we now do the following:

- ▷ Let $h^{-1}(z_i)$ be part of the clauses C_j and $C_{j'}$. Then add the edges $\{z_i, y_j\}, \{z_i, y_{j'}\}$ to \mathcal{H} if $f(x_i) = \text{TRUE}$, otherwise add the edge $\{z_i, b_i\}$.
- ▷ Let $h^{-1}(\bar{z}_i)$ be part of the clauses C_j and $C_{j'}$. Then add the edges $\{\bar{z}_i, y_j\}, \{\bar{z}_i, y_{j'}\}$ to \mathcal{H} if $f(\bar{x}_i) = \text{TRUE}$, otherwise add the edge $\{\bar{z}_i, b_i\}$.

The total cost of adding the above edges is $n(2 + c)$. It is easy to observe that after adding the above edges, \mathbf{x}^* becomes a PSNE. Hence the instance of ANM with symmetric altruism is a YES instance.

In the other direction, let ANM with symmetric altruism be a YES instance. First observe that for all $i \in [n]$, either $\{z_i, b_i\}$ or $\{\bar{z}_i, b_i\}$ must have been added to \mathcal{H} . Also for no $i \in [n]$, both $\{z_i, b_i\}$ and $\{\bar{z}_i, b_i\}$ are added to \mathcal{H} otherwise the total cost of edges added would exceed B . Let $S := \{u : u \in \mathcal{V}, \{u, b_i\} \text{ is added to } \mathcal{H}\}$. Let $S' := \{z_i, \bar{z}_i : i \in [n]\} \setminus S$. Now for all $u \in S'$, $\{u, y_j\}, \{u, y_{j'}\}$ must have been added to \mathcal{H} otherwise u will deviate from playing 1. Here $h^{-1}(u)$ are part of the clauses C_j and $C_{j'}$. No other edge can be added to \mathcal{H} otherwise the total cost of edges added would exceed B . Now consider the following assignment $f : \{x_i, \bar{x}_i : i \in [n]\} \rightarrow \{\text{TRUE}, \text{FALSE}\}$ of (3, B2)-SAT instance. For all $u \in S'$ we have $f(h^{-1}(u)) = \text{TRUE}$ and for all $v \in S$ we have $f(h^{-1}(v)) = \text{FALSE}$. Observe that there is no $i \in [n]$ such that $f(x_i) = f(\bar{x}_i)$. Now we show that f is a satisfying assignment. If not there

23:18 On Binary Networked Public Goods Game with Altruism

is a clause $C_j = (l_1^j \vee l_2^j \vee l_3^j)$ which is not satisfied. Hence $\{h(l_1^j), y_j\}, \{h(l_2^j), y_j\}, \{h(l_3^j), y_j\}$ are not added to \mathcal{H} . But then y_j would deviate from playing 1 which is a contradiction. Hence f is a satisfying assignment. Hence the instance of (3, B2)-SAT is a YES instance.

Applying Lemma 11 concludes the proof of this theorem. \blacktriangleleft

We complement the previous result by showing that ANM with asymmetric altruism is FPT for the parameter maximum degree of the input graph.

► Theorem 15. *For any target profile, ANM with asymmetric altruism can be solved in time $2^{\Delta/2} \cdot n^{O(1)}$ where Δ is the maximum degree of the input graph.*

Proof. [24] showed that solving an instance of asymmetric altruistic design is equivalent to solving n different instances of Minimum Knapsack problem and each of these instances have at most $\Delta + 1$ items. In Minimum Knapsack problem, we are given a set of items $1, \dots, k$ with costs p_1, \dots, p_k and weights w_1, \dots, w_k . The aim is to find a subset S of items minimizing $\sum_{i \in S} w_i$ subject to the constraint that $\sum_{i \in S} p_i \geq P$. We assume that $\sum_{i \in [k]} p_i \geq P$ otherwise we don't have any feasible solution. Let us denote the optimal value by OPT . Let $W := \sum_{i \in [k]} w_i$. Now consider the following integer linear program which we denote by ILP_w :

$$\begin{aligned} \max \quad & \sum_{i \in [k]} x_i p_i \\ \text{s.t.} \quad & \sum_{i \in [k]} x_i w_i \leq w, \quad x_i \in \{0, 1\} \quad \forall i \in [k] \end{aligned}$$

The above integer linear program can be solved in time $2^{k/2} \cdot k^{O(1)}$ [10]. Now observe that for all $w \geq OPT$, the optimal value OPT_w of ILP_w is at least P . Similarly for all $w < OPT$, the optimal value OPT_w of the ILP_w is less than P . Now by performing a binary search for w on the range $[0, W]$ and then solving the above ILP repeatedly, we can compute OPT in time $2^{k/2} \cdot \log W \cdot k^{O(1)}$. See Algorithm 2 for more details.

As discussed earlier, an Instance of asymmetric altruistic design is equivalent to solving n different instances of Minimum Knapsack problem and each of these instances have at most $\Delta + 1$ items. Hence ANM with asymmetric altruism can be solved in time $2^{\Delta/2} \cdot |x|^{O(1)}$ where x is the input instance of ANM with asymmetric altruism. \blacktriangleleft

We conclude our work by discussing about the approximability of ANM with symmetric altruism. [24] showed a $2 + \varepsilon$ approximation algorithm for ANM with symmetric altruism when the target profile has all players investing. However, for arbitrary target profile they showed that ANM with symmetric altruism is NP-complete when the input network is a complete graph and the budget is infinite. We show a similar result for graphs with bounded degree by reducing from (3, B2)-SAT.

► Theorem 16. *For an arbitrary target profile, ANM with symmetric altruism is known to be para-NP-hard for the parameter maximum degree of the input network even when the BNPG game is fully homogeneous and the budget is infinite.*

Proof. To show the NP-hardness, we reduce from an instance of (3, B2)-SAT which we denote by $(\mathcal{X} = \{x_i : i \in [n]\}, \mathcal{C} = \{C_j : j \in [m]\})$. We define a function $h : \{x_i, \bar{x}_i : i \in [n]\} \rightarrow \{z_i, \bar{z}_i : i \in [n]\}$ as $h(x_i) = z_i$ and $h(\bar{x}_i) = \bar{z}_i$ for all $i \in [n]$. We now create an

Algorithm 2 Minimum Knapsack Solver

```

1:  $\ell \leftarrow 0, r \leftarrow W$ 
2:  $w \leftarrow \lfloor \frac{\ell+r}{2} \rfloor$ 
3: while true do
4:   Solve  $ILP_w$  and  $ILP_{w+1}$ .
5:   if  $OPT_w < P$  and  $OPT_{w+1} \geq P$  then
6:     return  $w + 1$ 
7:   else if  $OPT_w < P$  and  $OPT_{w+1} < P$  then
8:      $\ell \leftarrow w + 1$ 
9:      $w \leftarrow \lfloor \frac{\ell+r}{2} \rfloor$ 
10:  else
11:     $r \leftarrow w$ 
12:     $w \leftarrow \lfloor \frac{\ell+r}{2} \rfloor$ 
13:  end if
14: end while

```

instance of ANM with symmetric altruism as follows. Let the initial altruistic network \mathcal{H} be empty and $a = 2$. Input graph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ for the input BNPG game is as follows:

$$\begin{aligned} \mathcal{V} &= \{z_i, \bar{z}_i, b_i : i \in [n]\} \cup \{y_j : j \in [m]\} \\ \mathcal{E} &= \{\{y_j, h(l_1^j)\}, \{y_j, h(l_2^j)\}, \{y_j, h(l_3^j)\} : C_j = \\ &\quad (l_1^j \vee l_2^j \vee l_3^j), j \in [m]\} \cup \{\{z_i, b_i\}, \{b_i, \bar{z}_i\} : i \in [n]\} \end{aligned}$$

Now observe that the degree of every vertex in \mathcal{G} is at most 3. We now define $(c_v)_{v \in \mathcal{V}}$ and $(g_v)_{v \in \mathcal{V}}$. $\forall v \in \mathcal{V}, c_v = 15$. $\forall j \in [m]$ and $\forall x \in \mathbb{N} \cup \{0\}$, $g_{y_j}(x) = x$. $\forall i \in [n]$ and $\forall x \in \mathbb{N} \cup \{0\}$, $g_{z_i}(x) = g_{\bar{z}_i}(x) = 10x$. $\forall i \in [n]$ and $\forall x \in \mathbb{N} \cup \{0\}$, $g_{b_i}(x) = 2x$. Target profile $\mathbf{x}^* = (x_v)_{v \in \mathcal{V}}$ is defined as follows. For all $j \in [m]$, $x_{y_j} = 1$. For all $i \in [n]$, $x_{z_i} = x_{\bar{z}_i} = 0$ and $x_{b_i} = 1$. Now define the cost of adding edges to \mathcal{H} . Cost of adding any edge is 0. The budget B is infinite. This completes the construction of the instance of ANM with symmetric altruism.

Now we prove that the instance of (3,B2)-SAT is a YES instance iff the instance of ANM with symmetric altruism is a YES instance. In one direction, let (3,B2)-SAT be a YES instance and its satisfying assignment be $f : \{x_i, \bar{x}_i : i \in [n]\} \rightarrow \{\text{TRUE}, \text{FALSE}\}$. For all $i \in [n]$, we now do the following:

- ▷ Let $h^{-1}(z_i)$ be part of the clauses C_j and $C_{j'}$. Then add the edges $\{z_i, y_j\}, \{z_i, y_{j'}\}$ to \mathcal{H} if $f(x_i) = \text{TRUE}$, otherwise add the edge $\{z_i, b_i\}$.
- ▷ Let $h^{-1}(\bar{z}_i)$ be part of the clauses C_j and $C_{j'}$. Then add the edges $\{\bar{z}_i, y_j\}, \{\bar{z}_i, y_{j'}\}$ to \mathcal{H} if $f(\bar{x}_i) = \text{TRUE}$, otherwise add the edge $\{\bar{z}_i, b_i\}$.

It is easy to observe that after adding the above edges, \mathbf{x}^* becomes a PSNE. Hence the instance of ANM with symmetric altruism is a YES instance.

In the other direction, let ANM with symmetric altruism be a YES instance. First observe that for all $i \in [n]$, either $\{z_i, b_i\}$ or $\{\bar{z}_i, b_i\}$ must have been added to \mathcal{H} . Let $S := \{u : u \in \mathcal{V}, \{u, b_i\} \text{ is added to } \mathcal{H}\}$. Let $S' := \{z_i, \bar{z}_i : i \in [n]\} \setminus S$. Now for all $u \in S$, there is no $j \in [m]$ such that $\{u, y_j\}$ is added to \mathcal{H} otherwise u will deviate from playing 0. Now consider the following assignment $f : \{x_i, \bar{x}_i : i \in [n]\} \rightarrow \{\text{TRUE}, \text{FALSE}\}$ of (3,B2)-SAT instance. For all $i \in [n]$, if $h(x_i) \in S'$ we have $f(x_i) = \text{TRUE}$ otherwise we have $f(x_i) = \text{FALSE}$. Now we show that f is a satisfying assignment. If not there is a clause $C_j = (l_1^j \vee l_2^j \vee l_3^j)$

which is not satisfied. Hence $\{h(l_1^j), y_j\}, \{h(l_1^j), y_j\}, \{h(l_1^j), y_j\}$ are not added to \mathcal{H} . But then y_j would deviate from playing 1 which is a contradiction. Hence f is a satisfying assignment. Hence the instance of (3, B2)-SAT is a YES instance.

Applying Lemma 11 concludes the proof of this theorem. ◀

5 Conclusion and Future Work

In this paper, we first studied the problem of deciding the existence of PSNE in BNPG game with altruism. We depicted polynomial time algorithms to decide the existence of PSNE in trees, complete graphs and graphs with bounded We also that the problem of finding MSNE in BNPG game with altruism is PPAD-Hard. Next we studied Altruistic Network modification. We showed that ANM with either symmetric or asymmetric altruism is NP-complete for trees. We also showed that ANM with symmetric altruism is para-NP-hard for the parameter maximum degree whereas ANM with asymmetric altruism is FPT for the parameter maximum degree.

One important research direction in ANM is to maximize the social welfare while ensuring that the target profile remains a PSNE. Another research direction is to improve the approximation algorithms of [24] for ANM with asymmetric altruism for trees and graphs with bounded degree. Another interesting future work is to look at other graphical games by considering altruism.

References

- 1 Piotr Berman, Marek Karpinski, and A Scott. Approximation hardness of short symmetric instances of max-3sat. Technical report, 2004.
- 2 Courtney Bir and Nicole Olynk Widmar. Social pressure, altruism, free-riding, and non-compliance in mask wearing by us residents in response to covid-19 pandemic. *Social sciences & humanities open*, 4(1):100229, 2021.
- 3 Dagobert L Brito, Eytan Sheshinski, and Michael D Intriligator. Externalities and compulsory vaccinations. *Journal of Public Economics*, 45(1):69–90, 1991.
- 4 Elisabeth Buchwald. Why do so many Americans refuse to wear face masks? Politics is part of it — but only part. <https://www.marketwatch.com/story/why-do-so-many-americans-refuse-to-wear-face-masks-it-may-have-nothing-to-do-with-politics-2020-06-16>, 2020.
- 5 Susumu Cato, Takashi Iida, Kenji Ishida, Asei Ito, Kenneth Mori McElwain, and Masahiro Shoji. Social distancing as a public good under the covid-19 pandemic. *Public health*, 188:51–53, 2020.
- 6 Maria Cucciniello, Paolo Pin, Blanka Imre, Gregory A. Porumbescu, and Alessia Melegaro. Altruism and vaccination intentions: Evidence from behavioral experiments. *Social Science & Medicine*, 292:114195, 2022. URL: <https://www.sciencedirect.com/science/article/pii/S027795362100527X>, doi:<https://doi.org/10.1016/j.socscimed.2021.114195>.
- 7 Luca Dall’Asta, Paolo Pin, and Abolfazl Ramezanzpour. Optimal equilibria of the best shot game. *Journal of Public Economic Theory*, 13(6):885–901, 2011.
- 8 Constantinos Daskalakis, Paul W Goldberg, and Christos H Papadimitriou. The complexity of computing a nash equilibrium. *SIAM Journal on Computing*, 39(1):195–259, 2009.
- 9 Edith Elkind, Leslie Ann Goldberg, and Paul Goldberg. Nash equilibria in graphical games on trees revisited. In *Proceedings of the 7th ACM Conference on Electronic Commerce*, pages 100–109, 2006.
- 10 Fedor V. Fomin and Dieter Kratsch. *Exact exponential algorithms*. Springer Heidelberg, 2010.
- 11 Andrea Galeotti, Sanjeev Goyal, Matthew O Jackson, Fernando Vega-Redondo, and Leeat Yariv. Network games. *The review of economic studies*, 77(1):218–244, 2010.

- 12 Soumya Kanti Ghosh. Concept of public goods can be experimentally put to use in pandemic for a social cause. <https://indianexpress.com/article/opinion/columns/rbi-nobel-prize-in-economics-coronavirus-new-auction-format-6779782/>, 2020.
- 13 Georg Gottlob, Gianluigi Greco, and Francesco Scarcello. Pure nash equilibria: Hard and easy games. *Journal of Artificial Intelligence Research*, 24:357–406, 2005.
- 14 David Kempe, Sixie Yu, and Yevgeniy Vorobeychik. Inducing equilibria in networked public goods games through network structure modification. AAMAS '20, page 611–619, Richland, SC, 2020. International Foundation for Autonomous Agents and Multiagent Systems.
- 15 Zohar Komarovskiy, Vadim Levit, Tal Grinshpoun, and Amnon Meisels. Efficient equilibria in a public goods game. In *2015 IEEE/WIC/ACM International Conference on Web Intelligence and Intelligent Agent Technology (WI-IAT)*, volume 2, pages 214–219. IEEE, 2015.
- 16 John O Ledyard. *2. Public goods: A survey of experimental research*. Princeton University Press, 2020.
- 17 Vadim Levit, Zohar Komarovskiy, Tal Grinshpoun, and Amnon Meisels. Incentive-based search for efficient equilibria of the public goods game. *Artificial Intelligence*, 262:142–162, 2018.
- 18 Arnab Maiti and Palash Dey. On parameterized complexity of binary networked public goods game. *arXiv preprint arXiv:2012.01880*, 2020.
- 19 Arnab Maiti and Palash Dey. Parameterized algorithms for kidney exchange. *arXiv preprint arXiv:2112.10250*, 2021.
- 20 Vahideh H Manshadi and Ramesh Johari. Supermodular network games. In *2009 47th Annual Allerton Conference on Communication, Control, and Computing (Allerton)*, pages 1369–1376. IEEE, 2009.
- 21 Dominic Meier, Yvonne Anne Oswald, Stefan Schmid, and Roger Wattenhofer. On the windfall of friendship: inoculation strategies on social networks. In *Proceedings of the 9th ACM conference on Electronic commerce*, pages 294–301, 2008.
- 22 Christos Papadimitriou and Binghui Peng. *Public Goods Games in Directed Networks*, page 745–762. Association for Computing Machinery, New York, NY, USA, 2021. URL: <https://doi.org/10.1145/3465456.3467616>.
- 23 Tessa Wong. Coronavirus: Why some countries wear face masks and others don't. <https://www.bbc.com/news/world-52015486>, 2020.
- 24 Sixie Yu, David Kempe, and Yevgeniy Vorobeychik. Altruism design in networked public goods games. In Zhi-Hua Zhou, editor, *Proceedings of the Thirtieth International Joint Conference on Artificial Intelligence, IJCAI-21*, pages 493–499. International Joint Conferences on Artificial Intelligence Organization, 8 2021. Main Track. doi:10.24963/ijcai.2021/69.
- 25 Sixie Yu, Kai Zhou, P Jeffrey Brantingham, and Yevgeniy Vorobeychik. Computing equilibria in binary networked public goods games. In *AAAI*, pages 2310–2317, 2020.