

A theorem prover and countermodel constructor for provability logic in HOL Light

Marco Maggesi   

University of Florence, Italy

Cosimo Perini Brogi   

University of Genoa, Italy

Abstract

We introduce our implementation in HOL Light of a prototype of a general theorem prover for normal modal logics. In the present work, we start by considering Gödel-Löb provability logic (GL). The methodology consists of a shallow embedding of a labelled sequent calculus for GL whose validity relies on our formalised proof in HOL Light of modal completeness for GL w.r.t. possible world semantics, that we present in the first part of the present work.

Our theorem prover for GL is thus implemented as a tactic of HOL Light that formalises the proof search in the corresponding labelled sequent calculus, and works as a decision algorithm for that logic: if the algorithm positively terminates, the tactic succeeds in producing a HOL Light theorem stating that the input formula is a theorem of GL; if the algorithm negatively terminates, the tactic extracts a model falsifying the input formula.

We discuss our code for the formal proof of modal completeness, and the design of our proof search algorithm. Furthermore some examples of both interactive and automated use of the latter are shown.

2012 ACM Subject Classification Theory of computation → Higher order logic; Theory of computation → Modal and temporal logics; Theory of computation → Automated reasoning

Keywords and phrases Provability Logic, Higher-Order Logic, Mechanized Mathematics, HOL Light Theorem Prover

Related Version *Previous Version:* <https://arxiv.org/abs/2102.05945>

Supplementary Material The implementation described in this paper is hosted in the subdirectory GL of the distribution of [HOL Light theorem prover](#).

HOL Light source code, May 2022: <https://github.com/jrh13/hol-light/>
archived at [swh:1:rev:ab57c07ff0105fef75a9fcdd179eda0d26854ba3](https://sw.hawaii.edu/rev/ab57c07ff0105fef75a9fcdd179eda0d26854ba3)

Funding *Marco Maggesi:* Supported by the Italian Ministry of University and Research and by INdAM-GNSAGA

Cosimo Perini Brogi: Supported by the Italian Ministry of University and Research

1 Introduction

This paper deals with two different, but closely related, properties of Gödel-Löb provability logic (GL): its modal completeness, and its decidability.

We present first a formalised proof in HOL Light proof assistant of modal completeness of GL, that we then use to implement within that very proof assistant a theorem prover for the same logic, which, in case of failure of the proof search, produces a countermodel for the formula that is not a theorem of GL.

Our work starts with a deep embedding of the syntax of propositional modal logic together with the corresponding relational semantics. Next, we introduce the traditional axiomatic calculus $\mathbb{G}L$ and prove the validity of the system w.r.t. irreflexive transitive finite frames.

A more interesting part then follows, consisting of the proof of a number of lemmas in \mathbb{GL} which are necessary for proving

► **Theorem 1.** *For any formula A , $\mathbb{GL} \vdash A$ iff A is true in any irreflexive transitive finite frame.*

In order to achieve that, we have to formally verify a series of preliminary lemmas and constructions involving the behaviour of syntactical objects used in the standard proof of the completeness theorem. These unavoidable steps are very often only proof-sketched in wide-adopted textbooks in logic, for they mainly involve “standard” reasoning *within* the proof system we are dealing with. But when we are working in a formal setting like we did with HOL Light, we need to split down the main goal into several subgoals, dealing with both the object- and the meta-level. Sometimes, the HOL Light infrastructure does play a very active role in checking the details of the informal reasoning; in other occasions, we have to make a smart use of our formal tools, and develop alternative (or simpler) proof-strategies, still totally verified by the computer.

As it is known, for any logical calculus, a completeness result w.r.t. finite models –aka finite model property– implies the decidability of that very logic. Therefore, the formal proof for Theorem 1 we discuss in the first part of the present work could be used, in principle, to develop a decision algorithm for \mathbb{GL} . That, in turn, would be a useful tool for automating in HOL Light the proof of theorems of \mathbb{GL} .

As a matter of fact, developing proofs in axiomatic calculi is never an easy task. In our formalisation we had to develop several proofs in the axiomatic calculus for \mathbb{GL} , and only in few cases it has been possible to let the proof search to the automation mechanism of HOL Light.

By having a formal proof of the finite model property, one could hope to solve the goal of checking whether a formula is a theorem of \mathbb{GL} by shifting from the syntactic problem of finding a proof of that formula in the axiomatic calculus to the semantic problem of checking the validity of that formula in any finite model by applying automated first-order reasoning as implemented in the proof assistant.

Such a strategy has many shortcomings, unfortunately. From the complexity theory view-point, the syntax-to-semantic shift is far from being optimal, since testing the validity of a formula A of size n requires to consider all models with cardinality k , for any $k \leq 2^n$. Less technically, from the practical view-point, nothing assures that the semantic problem is always easier to handle by the proof assistant than the original syntactic goal.

A more promising strategy is suggested by structural proof theory for modal logics.

Many sequent calculi for non-classical logics are based on an “internalisation” of possible world semantics in Gentzen’s original formalism.

This internalisation can be achieved by extending the syntax of formulas constituting standard sequents (labelled calculi, e.g., [44],[63],[13]); or by extending the structure of the very sequents, with the aim of mimicking the structure of models the logic is adequate for (e.g., nested sequents [9, 40, 38] or hypersequents [3, 57, 37]).

We opted for the first option, since our formalisation of Kripke semantics for \mathbb{GL} is *per se* a labelling technique in disguise.

Therefore, in the second part of this paper we introduce what might be considered a shallow embedding in HOL Light of Negri’s labelled sequent calculus $\mathbb{G3KGL}$.

To state it clearly: while in the first part we defined the axiomatic system \mathbb{GL} within our proof assistant by means of an inductive definition of the derivability relation for \mathbb{GL} , in the

second part we define *new tactics* of HOL Light in order to perform a proof search in G3KGL by using the automation infrastructure provided by HOL Light itself.

By relying on the meta-theory for G3KGL developed in [45], we can safely claim that such an embedding provides a decision algorithm for GL: if proof search terminates on a modal formula given as input, HOL Light produces a new theorem, stating that the input formula is a theorem of GL; otherwise, our algorithm prints all the information necessary to construct an appropriate countermodel for the input formula.

We can briefly summarise the present paper as follows:

- In Section 2, we introduce the basic ingredients of our development, namely the formal counterparts of the syntax and relational semantics for provability logic, along with some lemmas and general definitions which are useful to handle the implementation of these objects in a uniform way, i.e. without the restriction to the specific modal system we are interested in. The formalisation constitutes large part of the file `modal.ml`;
- In Section 3, we formally define the axiomatic calculus $\mathbb{G}\mathbb{L}$, and prove in a neat way the validity lemma for this system. Moreover, we give formal proofs of several lemmas *in* $\mathbb{G}\mathbb{L}$ ($\mathbb{G}\mathbb{L}$ -lemmas, for short), whose majority is in fact common to all normal modal logics, so that our proofs might be re-used in subsequent implementations of different systems. This corresponds to contents of our code in `gl.ml`;
- In Section 4 we give our formal proof of modal completeness of $\mathbb{G}\mathbb{L}$, starting with the definition of maximal consistent *lists* of formulas. In order to prove their syntactic properties – and, in particular, the extension lemma for consistent lists of formulas to maximal consistent lists – we use the $\mathbb{G}\mathbb{L}$ -lemmas and, at the same time, we adapt an already known general proof-strategy to maximise the gain from the formal tools provided by HOL Light – or, informally, from higher-order reasoning.

At the end of the Section, we give the formal definition of bisimilarity for our setup and we prove the associated bisimulation theorem [59, Ch. 11]. Our notion of bisimilarity is polymorphic, in the sense that it can relate classes of frames sitting on different types. With this tool at hand, we can correctly state our completeness theorem in its natural generality (`COMPLETENESS_THEOREM_GEN`) – i.e. for irreflexive, transitive finite frames over any (infinite) type – this way obtaining the finite model property for GL w.r.t. frames having finite *sets* of formulas as possible worlds, as in the standard Henkin’s construction. These results conclude the first part of the paper, and are gathered in the file `completeness.ml`.

- Section 5 opens the part of the paper describing our original theorem prover for GL. We collect some basic notions and techniques for proof-theoretic investigations on modal logic. In particular, we recall the labelled sequent calculus G3KGL and its main properties. That provides the meta-theory for our decision algorithm.
- Finally, in Section 6, we describe our implementation of G3KGL – documented by the file `decid.ml` – to give a decision procedure for GL. We recover the formalisation of Kripke semantics for GL presented in Section 2 and use it to define new tactics mimicking the rules for G3KGL. Then, we properly define our decision algorithm on the lines of a specific terminating proof search strategy in the labelled sequent calculus. This way, we succeed in extending the HOL Light automation toolbox with an “internal” theorem prover for GL that is also capable to produce a countermodel to any formula for which proof search fails. We propose some hands-on examples of use by considering modal principles that have a certain relevance for meta-mathematical investigations; the interested reader will find further examples in the file `tests.ml`.
- Section 7 closes the paper and compares our results with related works on mechanised

modal logic

We could say that our implementation fluidly moves between two different levels of abstraction: the deep embedding of the axiomatic calculus is adequately reflected in the deep embedding of the possible world semantics by means of the completeness theorem formalised at the meta-level of HOL Light. Such a formal proof, in turn, assures that, at the meta-level, we can safely proceed with a shallow embedding of the labelled sequent calculus by extending the tactics of HOL Light in order to mirror the rules of that calculus. Because of the proof-theoretic property of the “informal” sequent calculus, its formalised counterpart is in fact a real theorem prover and countermodel constructor for the modal logic, built in HOL Light.

Nothing, in the methodology we have just sketched, is specific to GL, so that the procedure we present here can be easily adapted to implement any labelled sequent calculus known in the literature.

Our code is integrated into the current HOL Light distribution, and it is freely available from there.¹

We care to stress that our formalisation does not tweak any original HOL Light tools, and it is therefore “foundationally safe”. Moreover, since we only used that original formal infrastructure, our results can be easily translated into another theorem prover belonging to the HOL family – or, more generally, endowed with the same automation toolbox.

Before presenting our results, in the forthcoming subsections of this introduction we provide the reader with some background material both on provability logic, and on formal theorem proving in HOL Light: further information about modalities and HOL Light can be found in [24] and [27], respectively.

Revision notes.

This article is an expanded version of the conference paper [39], presented at Interactive Theorem Proving (ITP) 2021. Changes include the addition of Sections 5 and 6 on our implementation in HOL Light of the theorem prover and countermodel constructor for GL, and some minor local revisions.

1.1 Developments of Provability Logic

The origin of provability logic dates back to a short paper by Gödel [23] where propositions about provability are formalised by means of a unary operator B with the aim of giving a classical reading of intuitionistic logic.

The resulting system corresponds to the logic $\mathbb{S}4$, and the proposition Bp is interpreted as ‘ p is *informally* provable’ – as claimed by Gödel himself. This implies that $\mathbb{S}4$ can be considered a provability logic lacking an appropriate semantics.

At the same time, that work opened the question of finding an adequate modal calculus for the formal properties of the provability predicate used in Gödel’s incompleteness theorems. That problem has been settled since 1970s for many formal systems of arithmetic by means of Gödel-Löb logic GL.

The corresponding axiomatic calculus $\mathbb{G}L$ consists of the axiomatic system for classical propositional logic, extended by the distributivity axiom schema K , the necessitation rule NR , and the axiom schema GL (see Section 3).

¹ See ‘Supplementary Material’ on the first page of this paper.

The schema GL is precisely a formal version of Löb’s theorem, which holds for a wide class of arithmetical theories satisfying the so-called Hilbert-Bernays-Löb (HBL) provability conditions.

The semantic counterpart of this calculus is – through the Kripke formalism – the logic of irreflexive transitive finite frames. Moreover, the calculus can be interpreted arithmetically in a sound and complete way. In other terms, $\mathbb{G}\mathbb{L}$ solves the problem raised in Gödel’s paper by identifying a propositional formal system for provability in all arithmetical theories that satisfy the previously mentioned HBL conditions.

Published in 1976, Solovay’s arithmetical completeness theorem [64] is in this sense a milestone result in the fields of proof theory and modal logic. As $\mathbb{G}\mathbb{L}$ is arithmetically complete, it is capable of capturing and identifying *all relevant properties of formal provability for arithmetic* in a very simple system, which is decidable and neatly characterised.

Such a deep result, however, uses in an essential way the *modal* completeness of $\mathbb{G}\mathbb{L}$: Solovay’s technique basically consists of an arithmetization of a relational countermodel for a given formula that is not a theorem of $\mathbb{G}\mathbb{L}$, from which it is possible to define an appropriate arithmetical formula that is not a theorem of the mathematical system.

In contemporary research, this is still the main strategy to prove arithmetical completeness for other modalities for provability and related concepts, in particular for interpretability logic. In spite of this, for many theories of arithmetic – including Heyting Arithmetic – this technique cannot be applied, and no alternatives are known.

Therefore, on the one hand, completeness of formal systems w.r.t. the relevant relational semantics is still an unavoidable step in achieving the more substantial result of arithmetical completeness; on the other hand, however, the area of provability logic keeps flourishing and suggesting old and new open problems. Some of them are closely related to the field of proof theory; others point at developing a uniform proof-strategy to establish adequate semantics in formal theories of arithmetic having different strengths and flavours.²

1.2 HOL Light Notation

The HOL Light proof assistant [28] is based on *classical* higher-order logic with polymorphic type variables and where equality is the only primitive notion. From a logical viewpoint, the formal engine defined by the *term-conversions* and *inference rules* underlying HOL Light is the same as that described in [36], extended by an infinity axiom and the classical characterization of Hilbert’s choice operator. From a practical perspective, it is a theorem prover privileging a procedural proof style development – i.e. when using it, we have to solve goals by applying *tactics* that reduce them to (eventually) simpler subgoals, so that the interactive aspect of proving is highlighted. Proof-terms can then be constructed by means of *tacticals* that compact the proof into a few lines of code evaluated by the machine.

Logical operators – defined in terms of equality – and λ -abstraction are denoted by specific symbols in ASCII: for the reader’s sake, we give a partial glossary in the next table. In the third column of the table, we also report the notation used for the object logic GL (introduced at the beginning of Section 2.1).

² The reader is referred to [5] for a survey of open problems in provability logics. As an instance of relevant applications of this kind of formal systems to traditional investigations in proof theory see e.g. [1].

Informal notation	HOL notation	GL notation	Description
\perp	F	False	Falsity
\top	T	True	Truth
$\neg p$	$\sim p$	Not p	Negation
$p \wedge q$	\wedge	&&	Conjunction
$p \vee q$	\vee	 	Disjunction
$p \implies q$	\implies	-->	Implication
$p \iff q$	\iff	<->	Biconditional
$\Box p$		Box p	Modal Operator
$p_1, \dots, p_N \vdash p$	$p_1 \dots p_N \vdash p$		HOL theorem
$\vdash p$		 -- p	Derivability in $\mathbb{G}L$
$\forall x. P(x)$	$!x. P(x)$		Universal quantification
$\exists x. P(x)$	$?x. P(x)$		Existential quantification
$\lambda x. M(x)$	$\backslash x. M(x)$		Lambda abstraction
$x \in s$	$x \text{ IN } s$		Set membership

We recall that a Boolean function $s : \alpha \rightarrow \text{bool}$ is also called a *set on α* in the HOL parlance. The notation $x \text{ IN } s$ is equivalent to $s \ x$ and must not be confused with a type annotation $x : \alpha$.

In the following sections, we will directly state our results as theorems and definitions in the HOL Light syntax. Note that theorems are prefixed by the turnstile symbol, as in $\vdash 2 + 2 = 4$. We often report a theorem with its associated name, that is, the name of its associated OCaml constant, e.g.

```
ADD_SYM
  \vdash !m n. m + n = n + m
```

As expository style, we omit formal proofs at all, but the meaning of definitions, lemmas, and theorems in natural language is hopefully clear after the table we have just given.

We warn the reader that the HOL Light printing mechanism omits type information completely. However in this paper we manually add type annotations when they might be useful, or even indispensable, in order to avoid ambiguity – including the case of our main results, `COMPLETENESS_THEOREM` and `COMPLETENESS_THEOREM_GEN`.

As already told in the introduction, our contribution is now part of the HOL Light distribution. The reader interested in performing these results on her machine – and perhaps building further formalisation on top of it – can run our code with the command

```
loadt "GL/make.ml";;
```

at the HOL Light prompt.

2 Basics of Modal Logic

As we stated previously, we deal with a logic that extends classical propositional reasoning by means of a single modal operator which is intended to capture the abstract properties of the provability predicate for arithmetic.

To reason about and within this logic, we have to “teach” HOL Light – our meta-language – how to identify it, starting with its syntax – the object-language – and semantics – the interpretation of this very object-language.

We want to keep everything neat and clean from a foundational perspective, therefore we will define *both* the object-language and its interpretation with no relation to the HOL Light

environment. In other terms: our formulas and operators are *real* syntactic objects which we keep distinct from their semantic counterparts – and from the logical operators of the theorem prover too.

2.1 Language and Semantics Defined

Let us start by fixing the propositional modal language \mathcal{L} we will use throughout the present work. We consider *all* classical propositional operators – conjunction, disjunction, implication, equivalence, negation, along with the 0-ary symbols \top and \perp – and we add a modal unary connective \Box . The starting point is, as usual, a denumerable infinite set of propositional atoms a_0, a_1, \dots . Accordingly, formulas of this language will have one of the following forms

$$a \mid A \wedge B \mid A \vee B \mid A \rightarrow B \mid A \leftrightarrow B \mid \neg A \mid \top \mid \perp \mid \Box A .$$

The following code extends the HOL system with an the **inductive type of formulas** up to the **atoms** – which we identify with the denumerable type of strings – by using the above **connectives**:

```
let form_INDUCT,form_RECURSION = define_type
  "form = False
    | True
    | Atom string
    | Not form
    | && form form
    | || form form
    | --> form form
    | <-> form form
    | Box form";;
```

Next, we turn to the semantics for our modal language. We use **relational models** – aka Kripke models³. Formally, a **Kripke frame** is made of a non-empty set ‘of possible worlds’ W , together with a binary relation R on W . To this, we add an evaluation function V which assigns to each atom of our language and each world w in W a Boolean value. This is extended to a **forcing relation holds**, defined recursively on the structure of the input formula p , that computes the truth-value of p in a specific world w :

```
let holds = new_recursive_definition form_RECURSION
  '(holds f V False (w:W) <=> F) /\
  (holds f V True w <=> T) /\
  (holds f V (Atom s) w <=> V s w) /\
  (holds f V (Not p) w <=> ~(holds f V p w)) /\
  (holds f V (p && q) w <=> holds f V p w /\ holds f V q w) /\
  (holds f V (p || q) w <=> holds f V p w \/\ holds f V q w) /\
  (holds f V (p --> q) w <=> holds f V p w ==> holds f V q w) /\
  (holds f V (p <-> q) w <=> holds f V p w <=> holds f V q w) /\
  (holds f V (Box p) w <=> !u. u IN FST f /\ SND f w u ==> holds f V p u)';;
```

In the previous lines of code, f stands for a generic Kripke frame – i.e. a pair (W,R) of a set of worlds and an accessibility relation – and V is an evaluation of propositional variables. Then, the **validity** of a formula p with respect to a frame (W,R) , and a class of frames L , denoted respectively $\text{holds_in } (W,R) p$ and $L \models p$, are

³ See [10] for the historical development of this notion.

```

let holds_in = new_definition
  'holds_in (W,R) p <=> !V w. w IN W ==> holds (W,R) V p w';;

let valid = new_definition
  'L |= p <=> !f. L f ==> holds_in f p';;

```

The above formalisation is essentially the one presented in Harrison’s HOL Light Tutorial [27, § 20]. Notice that the usual notion of Kripke frame requires that the set of possible worlds is non-empty: that condition could be imposed by adapting the `valid` relation. We have preferred to stick to Harrison’s original definitions in our code, but in the next section, when we define the classes of frames we are dealing with, the requirement on W is correctly integrated in the corresponding types.

2.2 Frames for GL

For carrying out our formalisation, we are interested in the logic of the (non-empty) frames whose underlying relation R is **transitive** and conversely well-founded – aka **Noetherian** – on the corresponding set of possible worlds; in other terms, we want to study the modal tautologies in models based on an accessibility relation R on W such that

- if xRy and yRz , then xRz ; and
- for no $X \subseteq W$ there are infinite R -chains $x_0Rx_1Rx_2\cdots$.

In HOL Light, `WF R` states that R is a well-founded relation: then, we express the latter condition as `WF(\x y. R y x)`. Here we see a recurrent motif in logic: defining a system from the semantic perspective requires non-trivial tools from the foundational point of view, for, to express the second condition, a first-order language is not enough. However, that is not an issue here, since our underlying system is natively higher order:

```

let TRANSNT = new_definition
  'TRANSNT (W:W->bool,R:W->W->bool) <=>
  ~(W = {}) /\
  (!x y:W. R x y ==> x IN W /\ y IN W) /\
  (!x y z:W. x IN W /\ y IN W /\ z IN W /\ R x y /\ R y z ==> R x z) /\
  WF(\x y. R y x)';;

```

We warn the reader that in the previous statement there occur two interrelated mathematical objects both denoted W (for convenience): one is the type W and the other is the set W on the former (in the sense explained in the introduction about the HOL syntax). From a theoretical point of view, moreover, the question has no deep consequences as we can characterize this class of frames by using a *propositional* language extended by a modal operator \Box that satisfies the *Gödel-Löb axiom schema* (GL) : $\Box(\Box A \rightarrow A) \rightarrow \Box A$. Here is the formal version of our claim:

```

TRANSNT_EQ_LOB
|- !W:W->bool R:W->W->bool.
  (!x y:W. R x y ==> x IN W /\ y IN W)
  ==> ((!x y z. x IN W /\ y IN W /\ z IN W /\ R x y /\ R y z ==> R x z) /\
  WF (\x y. R y x) <=>
  (!p. holds_in (W,R) (Box(Box p --> p) --> Box p)))

```

The informal proof of the above result is standard and can be found in [8, Theorem 10] and in [59, Theorem 5.7]. The computer implementation of the proof is made easy thanks to Harrison’s tactic `MODAL_SCHEMA_TAC` for semantic reasoning in modal logic, documented in [27, § 20.3].

By using this preliminary result, we could say that the frame property of being transitive and Noetherian can be captured by Gödel-Löb modal axiom, without recurring to a higher-order language. Nevertheless, that class of frames is not particularly informative from a logical point of view: a frame in TRANSNT can be too huge to be used in practice – for instance, for checking whether a formula is indeed a theorem of our logic. In particular, when aiming at a completeness theorem, one wants to consider models that are useful for further investigations on the properties of the very logic under consideration – in the present case, decidability of GL, which, as for any other normal modal logic, is an easy corollary of the *finite model property* [59, Ch. 13].

To this aim, we note that, by definition of Noetherianness, our R cannot be reflexive – otherwise $xRxRx\cdots$ would give us an infinite R -chain. This is not enough: following our main reference [8], the frames we want to investigate are precisely those whose W is **finite**, and whose R is both **irreflexive** and **transitive**:

```
let ITF = new_definition
  'ITF (W:W->bool,R:W->W->bool) <=>
    ~(W = {}) /\
    (!x y:W. R x y ==> x IN W /\ y IN W) /\
    FINITE W /\
    (!x. x IN W ==> ~R x x) /\
    (!x y z. x IN W /\ y IN W /\ z IN W /\ R x y /\ R y z ==> R x z)';;
```

Now it is easy to see that ITF is a subclass of TRANSNT:

```
ITF_NT
|- !W R:W->W->bool. ITF(W,R) ==> TRANSNT(W,R)
```

That will be the class of frames whose logic we are now going to define syntactically.

3 Axiomatizing GL

We want to identify the logical system generating all the modal tautologies for transitive Noetherian frames; more precisely, we want to isolate the *generators* of the modal tautologies in the subclass of transitive Noetherian frames which are finite, transitive, and irreflexive. Notice that the lemma ITF_NT allows us to derive the former result as a corollary of the latter.

When dealing with the very notion of tautology – or *theoremhood*, discarding the complexity or structural aspects of *derivability* in a formal system – it is convenient to focus on axiomatic calculi. The calculus we are dealing with here is usually denoted by GL.

It is clear from the definition of the forcing relation that for classical operators any axiomatization of propositional classical logic will do the job. Here, we adopt a basic system in which only \rightarrow and \perp are primitive – from the axiomatic perspective – and all the remaining classical connectives are defined by axiom schemas and by the inference rule of Modus Ponens imposing their standard behaviour.

As anticipated in the Introduction, to this classical engine we add

- the axiom schema K: $\Box(A \rightarrow B) \rightarrow \Box A \rightarrow \Box B$;
- the axiom schema GL: $\Box(\Box A \rightarrow A) \rightarrow \Box A$;
- the necessitation rule NR: $\frac{A}{\Box A}$ NR,

where A, B are generic formulas (not simply atoms). Then, here is the complete definition of the **axiom system** GL. The set of axioms is encoded via the inductive predicate GLaxiom:

```

let GLaxiom_RULES, GLaxiom_INDUCT, GLaxiom_CASES = new_inductive_definition
  `(!p q. GLaxiom (p --> (q --> p))) /\
    (!p q r. GLaxiom ((p --> q --> r) --> (p --> q) --> (p --> r))) /\
    (!p. GLaxiom (((p --> False) --> False) --> p)) /\
    (!p q. GLaxiom ((p <-> q) --> p --> q)) /\
    (!p q. GLaxiom ((p <-> q) --> q --> p)) /\
    (!p q. GLaxiom ((p --> q) --> (q --> p) --> (p <-> q))) /\
    GLaxiom (True <-> False --> False) /\
    (!p. GLaxiom (Not p <-> p --> False)) /\
    (!p q. GLaxiom (p && q <-> (p --> q --> False) --> False)) /\
    (!p q. GLaxiom (p || q <-> Not(Not p && Not q))) /\
    (!p q. GLaxiom (Box (p --> q) --> Box p --> Box q)) /\
    (!p. GLaxiom (Box (Box p --> p) --> Box p))';;

```

The judgment $\mathbb{G}\mathbb{L} \vdash A$, denoted $\vdash\!\!\vdash A$ in the machine code (not to be confused with the symbol for HOL theorems \vdash), is also inductively defined in the expected way:

```

let GLproves_RULES, GLproves_INDUCT, GLproves_CASES = new_inductive_definition
  `(!p. GLaxiom p ==> \vdash\!\!\vdash p) /\
    (!p q. \vdash\!\!\vdash (p --> q) /\ \vdash\!\!\vdash p ==> \vdash\!\!\vdash q) /\
    (!p. \vdash\!\!\vdash p ==> \vdash\!\!\vdash (Box p))';;

```

3.1 $\mathbb{G}\mathbb{L}$ -lemmas

As usual, $\mathbb{G}\mathbb{L} \vdash A$ denotes the existence of a derivation of A from the axioms of $\mathbb{G}\mathbb{L}$; we could also define a notion of derivability from a set of assumptions just by tweaking the previous definitions in order to handle the specific limitations on NR – so that the deduction theorem would hold [26] – but this would be inessential to our intents.

Proving some lemmas in the axiomatic calculus $\mathbb{G}\mathbb{L}$ is a technical interlude necessary for obtaining the completeness result.

In accordance with this aim, we denoted the classical axioms and rules of the system as the propositional schemas used by Harrison in the file `Arithmetic/derived.ml` of the HOL Light standard distribution [28] – where, in fact, many of our lemmas relying only on the propositional calculus are already proven there w.r.t. an axiomatic system for first-order classical logic; our further lemmas involving modal reasoning are denoted by names that are commonly used in informal presentations.

Therefore, the code in `gl.ml` mainly consists of the formalised proofs of those lemmas *in* $\mathbb{G}\mathbb{L}$ that are useful for the formalised results we present in the next section. This file might be thought of as a “kernel” for further experiments in reasoning about axiomatic calculi by using HOL Light. The lemmas we proved are, indeed, standard tautologies of classical propositional logic, along with specific theorems of minimal modal logic and its extension for transitive frames – i.e. of the systems \mathbb{K} and $\mathbb{K}4$ [59] –, so that by applying minor changes in basic definitions, they are – so to speak – take-away proof-terms for extensions of that very minimal system within the realm of normal modal logics.

More precisely, we have given, whenever it was useful, a “sequent-style natural deduction” characterization of classical operators both in terms of an implicit (or internal) deduction – and in that case we named the lemma with the suffix `_th` –, such as

```

GL_modusponens_th
  \vdash\!\!\vdash !p q. \vdash\!\!\vdash ((p --> q) && p --> q)

```

and as a derived rule of the axiomatic system mimicking the behaviour of the connective in Gentzen’s formalism, e.g.,

```

GL_and_elim
|- !p q r. |-- (r --> p && q) ==> |-- (r --> q) /\ |-- (r --> p)

```

We had to prove about 120 such results of varying degrees of difficulty. We believe that this file is well worth the effort of its development, for two main reasons to be considered – along with the just mentioned fact that they provide a (not so) minimal set of internal lemmas which can be moved to different axiomatic calculi at, basically, no cost.

Indeed, on the one hand, these lemmas simplify the subsequent formal proofs involving consistent lists of formulas since they let us work formally within the scope of \vdash , so that we can rearrange subgoals according to their most useful equivalent form by applying the appropriate $\mathbb{G}\mathbb{L}$ -lemma(s).

On the other hand, the endeavour of giving formal proofs of these lemmas of the calculus $\mathbb{G}\mathbb{L}$ has been important for checking how much our proof-assistant is “friendly” and efficient in performing this specific task.

As it is known, any axiomatic system fits very well an investigation involving the notion of *theoremhood* for a specific logic, but its lack of naturalness w.r.t. the practice of developing informal proofs makes it an unsatisfactory model for the notion of *deducibility*. In more practical terms: developing a formal proof of a theorem in an axiomatic system *by pencil and paper* can be a dull and uninformative task.

We therefore left the proof search to the HOL Light toolbox as much as possible. Unfortunately, we have to express mixed feelings about the general experience. In most cases, relying on the automation tools of this specific proof assistant did indeed save our time and resources when trying to give a formal proof in $\mathbb{G}\mathbb{L}$. Nevertheless, there has been a number of $\mathbb{G}\mathbb{L}$ -lemmas for proving which those automation tools did not reveal useful at all. In those cases, actually, we had to perform a tentative search of the specific instances of axioms from which deriving the lemmas,⁴ so that interactive proving them had advantages as well as traditional instruments of everyday mathematicians.

Just to stress the general point: it is clearly possible – and actually useful in general – to rely on the resources of HOL Light to develop formal proofs both *about* and *within* an axiomatic calculus for a specific logic, in particular when the lemmas of the object system have relevance or practical utility for mechanizing (meta-)results on it; however, these very resources – and, as far as we can see, the tools of any other general proof assistant – do not look peculiarly satisfactory for pursuing investigations on derivability within axiomatic systems.

3.2 Soundness Lemma

At this point, we can prove that $\mathbb{G}\mathbb{L}$ is **sound** – i.e. every formula derivable in the calculus is a tautology in the class of irreflexive transitive finite frames. This is obtained by simply unfolding the relevant definitions and applying theorems `TRANSNT_EQ_LOB` and `ITF_NT` of Section 2.2:

```

GL_TRANSNT_VALID
|- !p. (|-- p) ==> TRANSNT:(W->bool)#(W->W->bool)->bool |= p

```

```

GL_ITF_VALID
|- !p. |-- p ==> ITF:(W->bool)#(W->W->bool)->bool |= p

```

⁴ The HOL Light tactics for first-order reasoning `MESON` and `METIS` were unable, for example, to instantiate autonomously the obvious middle formula for the transitivity of an implication, or even the specific formulas of a schema to apply to the goal in order to rewrite it.

From this, we get a model-theoretic proof of **consistency for the calculus**

```
GL_consistent
~ |-- False
```

Having exhausted the contents of file `gl.ml`, we shall move to consider the mechanized proof of completeness for the calculus w.r.t. this very same class of frames.

4 Modal completeness

When dealing with normal modal logics, it is common to develop a proof of completeness w.r.t. relational semantics by using the so-called ‘canonical model method’. This can be summarized as a standard construction of countermodels made of maximal consistent sets of formulas and an appropriate accessibility relation [59].

For $\mathbb{G}L$, we cannot pursue this strategy, since the logic is not compact: maximal consistent sets are (in general) infinite objects, though the notion of derivability involves only a finite set of formulas. We cannot therefore reduce the semantic notion of (in)coherent set of formulas to the syntactic one of (in)consistent set of formulas: when extending a consistent set of formulas to a maximal consistent one, we might end up with a *syntactically* consistent set that nevertheless cannot be *semantically* satisfied.

In spite of this, it is possible to achieve a completeness result by

1. identifying the relevant properties of maximal consistent sets of formulas; and
2. tweaking the definitions so that those properties hold for specific consistent sets of formulas related to the formula we want to find a countermodel to.

That is, basically, the key idea behind the proof given in [8, Ch. 5]. In that monograph, however, the construction of a maximal consistent set from a simply consistent one is only proof-sketched and relies on a syntactic manipulation of formulas. By using HOL Light we do succeed in giving a detailed proof of completeness as direct as that by Boolos. But, as a matter of fact, we can claim something more: we can do that by carrying out in a *very natural way* a tweaked Lindenbaum construction to extend consistent *lists* to maximal consistent ones. This way, we succeed in preserving the standard Henkin-style completeness proofs; and, at the same time, we avoid the symbolic subtleties sketched in [8] that have no real relevance for the argument, but have the unpleasant consequence of making the formalised proof unnecessarily long, so that the implementation would sound rather pedantic – or even dull.

Furthermore, the proof of the main lemma `EXTEND_MAXIMAL_CONSISTENT` is rather general and does not rely on any specific property of $\mathbb{G}L$: our strategy suits all the other normal (mono)modal logics – we only need to modify the subsequent definition of `STANDARD_RELATION` according to the specific system under consideration. Thus, we provide a way for establishing completeness à la Henkin *and* the finite model property without recurring to filtrations [59] of canonical models for those systems.

4.1 Maximal Consistent Lists

Following the standard practice, we need to consider consistent finite sets of formulas for our proof of completeness. In principle, we can employ general sets of formulas in the formalisation, but, from the practical view-point, lists without repetitions are better suited, since they are automatically finite and we can easily manipulate them by structural recursion.

We define first the operation of finite conjunction of formulas in a list:⁵

```
let CONJLIST = new_recursive_definition list_RECURSION
  'CONJLIST [] = True /\
    (!p X. CONJLIST (CONS p X) = if X = [] then p else p && CONJLIST X)';;
```

We proceed by proving some properties on lists of formulas and some $\mathbb{G}\mathbb{L}$ -lemmas involving CONJLIST. In particular, since $\mathbb{G}\mathbb{L}$ is a normal modal logic – i.e. its modal operator distributes over implication and preserves theoremhood – we have that our \Box distributes over the conjunction of X so that we have CONJLIST_MAP_BOX:

$$\mathbb{G}\mathbb{L} \vdash \Box \bigwedge X \leftrightarrow \bigwedge \Box X,$$

where $\Box X$ is an abuse of notation for the list obtained by “boxing” each formula in X .

We are now able to define the notion of **consistent list of formulas** and prove the main properties of this kind of objects:

```
let CONSISTENT = new_definition
  'CONSISTENT (l:form list) <=> ~ (!-- (Not (CONJLIST l)))';;
```

In particular, we prove that:

- a consistent list cannot contain both A and $\neg A$ for any formula A , nor \perp (see theorems CONSISTENT_LEMMA, CONSISTENT_NC, and FALSE_IMP_NOT_CONSISTENT, respectively);
- for any consistent list X and formula A , either $X + A$ is consistent, or $X + \neg A$ is consistent (CONSISTENT_EM), where $+$ denotes the usual operation of appending an element to a list.

Our **maximal consistent lists** w.r.t. a given formula A will be consistent lists that do not contain repetitions and that contain, for any subformula of A , that very subformula or its negation:⁶

```
let MAXIMAL_CONSISTENT = new_definition
  'MAXIMAL_CONSISTENT p X <=>
    CONSISTENT X /\ NOREPETITION X /\
    (!q. q SUBFORMULA p ==> MEM q X \\/ MEM (Not q) X)';;
```

where X is a list of formulas and MEM $q X$ is the membership relation for lists. We then establish the main closure property of maximal consistent lists:

```
MAXIMAL_CONSISTENT_LEMMA
|- !p X A b. MAXIMAL_CONSISTENT p X /\
  (!q. MEM q A ==> MEM q X) /\
  b SUBFORMULA p /\
  |-- (CONJLIST A --> b)
  ==> MEM b X
```

⁵ Notice that in this definition we perform a case analysis where the singleton list is treated separately (i.e., we have CONJLIST [p] = p). This is slightly uncomfortable in certain formal proof steps: in retrospect, we might have used a simpler version of this function. However, since this is a minor detail, we preferred not to change our code.

⁶ Here we define the set of subformulas of A as the reflexive transitive closure of the set of formulas on which the main connective of A operates: this way, the definition is simplified and it is easier to establish standard properties of the set of subformulas by means of general higher-order lemmas in HOL Light for the closure of a given relation.

After proving some further lemmas with practical utility – in particular, the fact that any maximal consistent list behaves like a restricted bivalent evaluation for classical connectives (`MAXIMAL_CONSISTENT_MEM_NOT` and `MAXIMAL_CONSISTENT_MEM_CASES`) – we can finally define the ideal (type of counter)model we are interested in. The type `STANDARD_MODEL` consists, for a given formula p , of:

1. the set of maximal consistent lists w.r.t. p made of *subsences* of p – i.e. its subformulas or their negations – as possible worlds;
2. an irreflexive transitive accessibility relation R such that for any subformula $\text{Box } q$ of p and any world w , $\text{Box } q$ is in w iff, for any x R -accessible from w , q is in x ;
3. an atomic evaluation that gives value T (true) to a in w iff a is a subformula of p .

After defining the relation of *subsences* as

```
let SUBSENTENCE = new_definition
  '!p q. q SUBSENTENCE p <=>
    q SUBFORMULA p \\/ (?q'. q = Not q' /\ q' SUBFORMULA p)';;
```

we can introduce the corresponding code:

```
let GL_STANDARD_FRAME = new_definition
  'GL_STANDARD_FRAME p (W,R) <=>
    W = {w | MAXIMAL_CONSISTENT p w /\ (!q. MEM q w ==> q SUBSENTENCE p)} /\
    ITF (W,R) /\
    (!q w. Box q SUBFORMULA p /\ w IN W
      ==> (MEM (Box q) w <=> !x. R w x ==> MEM q x))';;
```

```
let GL_STANDARD_MODEL = new_definition
  'GL_STANDARD_MODEL p (W,R) V <=>
    GL_STANDARD_FRAME p (W,R) /\
    (!a w. w IN W ==> (V a w <=> MEM (Atom a) w /\ Atom a SUBFORMULA p))';;
```

4.2 Maximal Extensions

What we have to do now is to show that the type `GL_STANDARD_MODEL` is non-empty. We achieve this by constructing suitable maximal consistent lists of formulas from specific consistent ones.

Our original strategy differs from the presentation given in e.g. [8] for being closer to the standard Lindenbaum construction commonly used in proving completeness results. By doing so, we have been able to circumvent both the pure technicalities in formalizing the combinatorial argument sketched in [8, p.79] *and* the problem – apparently inherent to the Lindenbaum extension – due to the non-compactness of the system, as we mentioned before.

The main lemma states then that, from any consistent list X of subsences of a formula A , we can construct a maximal consistent list of subsences of A by extending (if necessary) X :

```
EXTEND_MAXIMAL_CONSISTENT
|- !p X.
  CONSISTENT X /\
  (!q. MEM q X ==> q SUBSENTENCE p)
  ==> ?M. MAXIMAL_CONSISTENT p M /\
    (!q. MEM q M ==> q SUBSENTENCE p) /\
    X SUBLIST M
```

The proof-sketch is as follows: given a formula A , we proceed in a step-by-step construction by iterating over the subformulas B of A not contained in X . At each step, we append to the list X the subformula B – if the resulting list is consistent – or its negation $\neg B$ – otherwise.

This way, we are in the pleasant condition of carrying out the construction by using the HOL Light device efficiently, and, at the same time, we do not have to worry about the non-compactness of \mathbb{GL} , since we are working with finite objects – the type `list` – from the very beginning.

Henceforth, we see that – under the assumption that A is not a \mathbb{GL} -lemma – the set of possible worlds in `STANDARD_FRAME` w.r.t. A is non-empty, as required by the definition of relational structures:

```
NONEMPTY_MAXIMAL_CONSISTENT
|- !p. ~ |-- p
    ==> ?M. MAXIMAL_CONSISTENT p M /\
           MEM (Not p) M /\
           (!q. MEM q M ==> q SUBSENTENCE p)
```

Next, we have to define an R satisfying the condition 2 for a `STANDARD_FRAME`; the following does the job:

```
let GL_STANDARD_REL = new_definition
'GL_STANDARD_REL p w x <=>
  MAXIMAL_CONSISTENT p w /\
  (!q. MEM q w ==> q SUBSENTENCE p) /\
  MAXIMAL_CONSISTENT p x /\
  (!q. MEM q x ==> q SUBSENTENCE p) /\
  (!B. MEM (Box B) w ==> MEM (Box B) x /\ MEM B x) /\
  (?E. MEM (Box E) x /\ MEM (Not (Box E)) w)';;
```

Such an accessibility relation, together with the set of the specific maximal consistent lists we are dealing with, defines a structure in `ITF` with the required properties:

```
ITF_MAXIMAL_CONSISTENT
|- !p. ~ |-- p
    ==> ITF ({M | MAXIMAL_CONSISTENT p M /\
               (!q. MEM q M ==> q SUBSENTENCE p)},
           GL_STANDARD_REL p),
```

```
ACCESSIBILITY_LEMMA
|- !p M w q.
  ~ |-- p /\
  MAXIMAL_CONSISTENT p M /\
  (!q. MEM q M ==> q SUBSENTENCE p) /\
  MAXIMAL_CONSISTENT p w /\
  (!q. MEM q w ==> q SUBSENTENCE p) /\
  MEM (Not p) M /\
  Box q SUBFORMULA p /\
  (!x. GL_STANDARD_REL p w x ==> MEM q x)
  ==> MEM (Box q) w,
```

4.3 Truth Lemma and Completeness

For our ideal model, it remains to reduce the semantic relation of forcing to the more tractable one of membership to the specific world. More formally, we prove – by induction on the

complexity of the subformula B of A – that if $\mathbb{G}\mathbb{L} \not\vdash A$, then for any world w of the standard model, B holds in w iff B is member of w :

```

GL_truth_lemma
|- !W R p V q.
  ~ |-- p /\
  GL_STANDARD_MODEL p (W,R) V /\
  q SUBFORMULA p
  ==> !w. w IN W ==> (MEM q w <=> holds (W,R) V q w),

```

Finally, we are able to prove the main result: if $\mathbb{G}\mathbb{L} \not\vdash A$, then the list $[\neg A]$ is consistent, and by applying `EXTEND_MAXIMAL_CONSISTENT`, we obtain a maximal consistent list X w.r.t. A that extends it, so that, by applying `GL_truth_lemma`, we have that $X \not\vdash A$ in our standard model. The corresponding formal proof reduces to the application of those previous results and the appropriate instantiations:

```

COMPLETENESS_THEOREM
|- !p. ITF:(form list->bool)#(form list->form list->bool)->bool |= p
  ==> |-- p,

```

Notice that the family of frames `ITF` is polymorphic, but, at this stage, our result holds only for frames on the domain `form list`, as indicated by the type annotation. This is not an intrinsic limitation: the next section is devoted indeed to generalise this theorem to frames on an arbitrary domain.

4.4 Generalizing via Bisimulation

As we stated before, our theorem `COMPLETENESS_THEOREM` provides the modal completeness for $\mathbb{G}\mathbb{L}$ with respect to a semantics defined using models built on the type `:form list`. It is obvious that the same result must hold whenever we consider models built on any infinite type. To obtain a formal proof of this fact, we need to establish a *correspondence* between models built on different types. It is well-known that a good way to make rigorous such a correspondence is by means of the notion of *bisimulation* [66].

In our context, given two models (W_1, R_1) and (W_2, R_2) sitting respectively on types `:A` and `:B`, each with an evaluation function V_1 and V_2 , a **bisimulation** is a binary relation $Z:A \rightarrow B \rightarrow \text{bool}$ that relates two worlds $w_1:A$ and $w_2:B$ when they can *simulate* each other. The formal definition is as follows:

```

BISIMIMULATION
|- BISIMIMULATION (W1,R1,V1) (W2,R2,V2) Z <=>
  (!w1:A w2:B.
    Z w1 w2
    ==> w1 IN W1 /\ w2 IN W2 /\
      (!a:string. V1 a w1 <=> V2 a w2) /\
      (!w1'. R1 w1 w1' ==> ?w2'. w2' IN W2 /\ Z w1' w2' /\ R2 w2 w2') /\
      (!w2'. R2 w2 w2' ==> ?w1'. w1' IN W1 /\ Z w1' w2' /\ R1 w1 w1'))

```

Then, we say that two worlds are *bisimilar* if there exists a bisimulation between them:

```

let BISIMILAR = new_definition
  'BISIMILAR (W1,R1,V1) (W2,R2,V2) (w1:A) (w2:B) <=>
    ?Z. BISIMIMULATION (W1,R1,V1) (W2,R2,V2) Z /\ Z w1 w2';;

```

The key fact is that the semantic predicate `holds` respects bisimilarity:

```

BISIMILAR_HOLDS
|- !W1 R1 V1 W2 R2 V2 w1:A w2:B.
    BISIMILAR (W1,R1,V1) (W2,R2,V2) w1 w2
    ==> (!p. holds (W1,R1) V1 p w1 <=> holds (W2,R2) V2 p w2)

```

From this, we can prove that validity is preserved by bisimilarity. The precise statements are the following:

```

BISIMILAR_HOLDS_IN
|- !W1 R1 W2 R2.
    (!V1 w1:A. ?V2 w2:B. BISIMILAR (W1,R1,V1) (W2,R2,V2) w1 w2)
    ==> (!p. holds_in (W2,R2) p ==> holds_in (W1,R1) p)

BISIMILAR_VALID
|- !L1 L2.
    (!W1 R1 V1 w1:A.
        L1 (W1,R1) /\ w1 IN W1
        ==> ?W2 R2 V2 w2:B. L2 (W2,R2) /\
            BISIMILAR (W1,R1,V1) (W2,R2,V2) w1 w2)
    ==> (!p. L2 |= p ==> L1 |= p)

```

In the last theorem, recall that the statement $L(W,R)$ means that (W,R) is a frame in the class of frames L .

Finally, we can explicitly define a bisimulation between ITF-models on the type `:form list` and on any infinite type `:A`. From this, it follows at once the desired generalization of completeness for $\mathbb{G}\mathbb{L}$:

```

COMPLETENESS_THEOREM_GEN
|- !p. INFINITE (:A) /\ ITF:(A->bool)#(A->A->bool)->bool |= p ==> |-- p

```

Furthermore, from the proof that the relation

```

\w1 w2. MAXIMAL_CONSISTENT p w1 /\ (!q. MEM q w1 ==> q SUBSENTENCE p) /\
    w2 IN GL_STDWORLDS p /\
    set_of_list w1 = w2

```

defines a bisimulation between the ITF-standard model based on maximal consistent *lists* of formulae and the model based on corresponding *sets* of formulas we obtain the traditional version of modal completeness, corresponding to theorem `GL_COUNTERMODEL_FINITE_SETS` in our code.

5 Decidability via proof theory

By using our `EXTEND_MAXIMAL_CONSISTENT` lemma, we succeeded in giving a rather neat proof of both completeness and the finite model property for $\mathbb{G}\mathbb{L}$.⁷

As an immediate corollary, we have that the system $\mathbb{G}\mathbb{L}$ is decidable and, in principle, we could implement a decision procedure for it in OCaml. A naive approach would proceed as follows.

We define the tactic `NAIVE_GL_TAC` and its associated rule `NAIVE_GL_RULE` that perform the following steps:

⁷ For the completeness w.r.t. transitive Noetherian frames, it is common – see [8, 59] – to reason on irreflexive transitive structures and derive the result as a corollary of completeness w.r.t. the latter class.

1. Apply the completeness theorem;
2. Unfold some definitions;
3. Try to solve the resulting *semantic* problem using first-order reasoning.

Here is the corresponding code.

```
let NAIVE_GL_TAC : tactic =
  MATCH_MP_TAC COMPLETENESS_THEOREM THEN
  REWRITE_TAC[valid; FORALL_PAIR_THM; holds_in; holds;
              ITF; GSYM MEMBER_NOT_EMPTY] THEN
  MESON_TAC[];;

let NAIVE_GL_RULE tm = prove(tm, REPEAT GEN_TAC THEN GL_TAC);;
```

The above strategy is able to prove automatically some lemmas which are common to normal modal logic, but require some effort when derived in an axiomatic system. As an example, consider the following $\mathbb{G}\mathbb{L}$ -lemma:

```
GL_box_iff_th
|- !p q. |-- (Box (p <-> q) --> (Box p <-> Box q))
```

When developing a proof of it within the axiomatic calculus, we need to “help” HOL Light by instantiating several further $\mathbb{G}\mathbb{L}$ -lemmas, so that the resulting proof-term consists of ten lines of code. On the contrary, our rule is able to check it in few steps:

```
# NAIVE_GL_RULE '!p q. |-- (Box (p <-> q) --> (Box p <-> Box q))';;
0..0..1..6..11..19..32..solved at 39
0..0..1..6..11..19..32..solved at 39
val it : thm = |- !p q. |-- (Box (p <-> q) --> (Box p <-> Box q))
```

In spite of this, the automation offered by MESON tactic is unexpectedly disappointing for some lemmas. For instance, the previous procedure is not even able to prove the basic instance Gödel-Löb scheme

$$\mathbb{G}\mathbb{L} \vdash \Box(\Box\perp \longrightarrow \perp) \longrightarrow \Box\perp.$$

This suggests that NAIVE_GL_TAC is based on a very inadequate strategy. And that is where structural proof theory comes at rescue.

5.1 Bits of structural proof theory

In very abstract terms, a deductive system consists of a set of starting formal expressions together with inference rules. Its principal aim is to find proofs of valid expressions w.r.t. a given logic L . A proof (or derivation) in a deductive system is obtained by application of the inference rules to starting expressions, followed by further application of the inference rules to the conclusion, and so on, recursively. A theorem (or lemma) in such a system is the formal expression obtained after a finite run of the procedure just sketched.

Such a definition captures the system $\mathbb{G}\mathbb{L}$, and the derivability relation formalised in HOL Light by the predicate `|--` of Section 3. Our previous remarks on $\mathbb{G}\mathbb{L}$ -lemmas make explicit that this kind of deductive systems has shortcomings that its computerisation per se is not able to overcome.

The proof-theoretic paradigm behind $\mathbb{G}\mathbb{L}$ and, more generally, axiomatic calculi could be called *synthetic*: proof search in such systems is not guided by the components of the formula one wishes to prove. The human prover – as well as the proof assistant dealing with

a formal derivability relation – has to guess both the correct instances of the axiom schemas and the correct application order of inference rules required in the proof.

A better paradigm is provided by sequent calculi, introduced first in [16, 17]. That work marks the advent of structural proof theory and the definite shift from investigations in synthetic deductive systems to *analytic* ones. Gentzen’s original calculi have been further refined in [31] and [32] into the so-called G3-style systems.

In those systems, a **sequent** is a formal expression with shape

$$\Gamma \Rightarrow \Delta,$$

where Γ, Δ are finite multisets – i.e. finite lists modulo permutations – of formulas of a given language. The symbol \Rightarrow reflects in the object language the deducibility relation at the meta-level. Γ is called the **antecedent** of the sequent; Δ is its **consequent**.

A derivation in a G3-style sequent calculus is a finite rooted tree labelled with sequents such that:

- its leaves are labelled by **initial sequents** (the starting formal expressions of the abstract deductive system);
- its intermediate nodes are labelled by sequents obtained from the sequent(s) labelling the node(s) directly above by a correct application of an inference rule of the calculus;
- its root is the conclusion of the derivation, and it is called the **end-sequent**.

Figure 1 summarises the calculus G3pc for classical propositional logic. For each rule, one distinguishes:

- its **main formula**, which is the formula occurring in the conclusion and containing the logical connective naming the rule;
- its **active formulas**, which are the formulas occurring in the premise(s) of the rule;
- its **context**, which consists of the formulas occurring in the premise(s) *and* the conclusion, untouched by the rule.

G3-style systems are the best available option for (efficiently) automating decision procedures: once an adequate – i.e. sound and complete – G3-calculus for a given logic L has been defined, in order to decide whether a formula is a theorem of L it suffices to start a *root-first* proof search of that very formula in the related G3-calculus.

This is so because, by design, good G3-style systems satisfy the following desiderata:

1. **Analyticity:** each formula occurring in a derivation is a subformula of the formulas occurring lower in the derivation branch. This means that *no guesses are required* to the prover when developing a formal proof in the G3-calculus;
2. **Invertibility of all the rules:** for each rule of the system, derivability of the conclusion implies the derivability of the premise(s). *This property avoids backtracking* on the proof search. It also means that at each step of the proof search procedure *no bit of information gets lost*, so that the tentative construction of *one* derivation tree is enough to decide derivability of a sequent;
3. **Termination:** each proof search must come to an end. If the final state of the procedure does generate a derivation, the end-sequent is a theorem indeed; otherwise, it is generally possible to extract a *refutation* of the sequent from the failed proof search.⁸

⁸ Notice, however, that sometimes invertibility of a rule could break termination of the proof search, as witnessed by $\mathcal{L} \rightarrow$ in G3pi for intuitionistic propositional logic [65].

Initial sequents:

$$p, \Gamma \Rightarrow \Delta, p$$

Propositional rules:

$$\frac{}{\perp, \Gamma \Rightarrow \Delta} \mathcal{L}\perp$$

$$\frac{A, B, \Gamma \Rightarrow \Delta}{A \wedge B, \Gamma \Rightarrow \Delta} \mathcal{L}\wedge \qquad \frac{\Gamma \Rightarrow \Delta, A \quad \Gamma \Rightarrow \Delta, B}{\Gamma \Rightarrow \Delta, A \wedge B} \mathcal{R}\wedge$$

$$\frac{A, \Gamma \Rightarrow \Delta \quad B, \Gamma \Rightarrow \Delta}{A \vee B, \Gamma \Rightarrow \Delta} \mathcal{L}\vee \qquad \frac{\Gamma \Rightarrow \Delta, A, B}{\Gamma \Rightarrow \Delta, A \vee B} \mathcal{R}\vee$$

$$\frac{\Gamma \Rightarrow \Delta, A}{\neg A, \Gamma \Rightarrow \Delta} \mathcal{L}\neg \qquad \frac{A, \Gamma \Rightarrow \Delta}{\Gamma \Rightarrow \Delta, \neg A} \mathcal{R}\neg$$

$$\frac{\Gamma \Rightarrow \Delta, A \quad B, \Gamma \Rightarrow \Delta}{A \rightarrow B, \Gamma \Rightarrow \Delta} \mathcal{L}\rightarrow \qquad \frac{A, \Gamma \Rightarrow \Delta, B}{\Gamma \Rightarrow \Delta, A \rightarrow B} \mathcal{R}\rightarrow$$

■ **Figure 1** Rules of the calculus G3pc

Satisfaction of all those desiderata by a pure Gentzen-style sequent calculus has been considered for long almost a mirage. Times have changed with the advent of *internalisation* techniques of semantic notions in sequent calculi for non-classical logics.

The starting point of that perspective is still the basic G3-paradigm, but the formalism of sequent system is extended either by

- enriching the language of the calculus itself (**explicit internalisation**); or by
- enriching the structure of sequents (**implicit internalisation**).

The implicit approach adds structural connectives to sequents, other than ‘ \Rightarrow ’ and commas.⁹ Most of G3-style calculi obtained this way provide in general very efficient decision procedures for the related logics, but they are sometimes rather hard to design, and might lack an additional and highly valuable desideratum of modularity.

The situation is reversed in the explicit approach. Explicit internalisation uses specific items to represent semantic elements; the formulas of the basic language are then **labelled** by those items, and have shape e.g. $x : A$. That expression formalises the forcing relation we

⁹ **Hypersequents** enrich sequents by the connective ‘ \parallel ’ to handle several sequents in parallel. The rules are defined so that the occurring sequents may interact with each other.¹⁰

Hypersequent calculi were fully exploited first in [3], on the basis of preliminary and embryonic formalisations in [33], [43, 42], and [60]. Further refinements – not limited to modal logics – include [61], [35], [40], and [20].

That formalism naturally generalises to **nested sequents**, that enrich the structure of sequents by the structural connective ‘ $\llbracket \cdot \rrbracket$ ’, allowing the design of inference rules operating at any deep in the entire tree of sequents defined by means of the additional connective itself.

Nested sequents were introduced first in [30], and independently in [9], and in [56]. The latter deals with nested sequents under the name ‘tree-hypersequents’, and a uniform treatment of many normal modal logics is presented in [57].

Nested sequent calculi for other non-classical logics have since then further developed in e.g. [54] and [58].

rephrased in Section 2.2, and classical propositional rules operate within the scope of labels. Furthermore, to handle modal operators, the antecedent of any sequent may now contain **relational atoms** of shape xRy , or any other expression borrowed from the semantics for the logic under investigation.

The rules for the modalities formalise the forcing condition for each modal connective. For instance, the labelled sequent calculus G3K is defined by the rules in Figure 2.

Initial sequents:

$$x : p, \Gamma \Rightarrow \Delta, x : p$$

Propositional rules:

$$\frac{}{x : \perp, \Gamma \Rightarrow \Delta} \mathcal{L}\perp$$

$$\frac{x : A, x : B, \Gamma \Rightarrow \Delta}{x : A \wedge B, \Gamma \Rightarrow \Delta} \mathcal{L}\wedge$$

$$\frac{\Gamma \Rightarrow \Delta, x : A \quad \Gamma \Rightarrow \Delta, x : B}{\Gamma \Rightarrow \Delta, x : A \wedge B} \mathcal{R}\wedge$$

$$\frac{x : A, \Gamma \Rightarrow \Delta \quad x : B, \Gamma \Rightarrow \Delta}{x : A \vee B, \Gamma \Rightarrow \Delta} \mathcal{L}\vee$$

$$\frac{\Gamma \Rightarrow \Delta, x : A, x : B}{\Gamma \Rightarrow \Delta, x : A \vee B} \mathcal{R}\vee$$

$$\frac{\Gamma \Rightarrow \Delta, x : A}{x : \neg A, \Gamma \Rightarrow \Delta} \mathcal{L}\neg$$

$$\frac{x : A, \Gamma \Rightarrow \Delta}{\Gamma \Rightarrow \Delta, x : \neg A} \mathcal{R}\neg$$

$$\frac{\Gamma \Rightarrow \Delta, x : A \quad x : B, \Gamma \Rightarrow \Delta}{x : A \rightarrow B, \Gamma \Rightarrow \Delta} \mathcal{L}\rightarrow$$

$$\frac{x : A, \Gamma \Rightarrow \Delta, x : B}{\Gamma \Rightarrow \Delta, x : A \rightarrow B} \mathcal{R}\rightarrow$$

Modal rules:

$$\frac{y : A, xRy, x : \Box A, \Gamma \Rightarrow \Delta}{xRy, x : \Box A, \Gamma \Rightarrow \Delta} \mathcal{L}\Box$$

$$\frac{xRy, \Gamma \Rightarrow \Delta, y : A}{\Gamma \Rightarrow \Delta, x : \Box A} \mathcal{R}\Box_{(y!)}$$

where the annotation $(y!)$ in $\mathcal{R}\Box$ states that the label y does not occur in Γ, Δ .

■ **Figure 2** Rules of the calculus G3K

Extensions of the minimal normal modal logic K are obtained by rules for relational atoms, formalising the characteristic properties of each specific extension. For instance, the system G3K4 for the logic K4 is defined by adding to G3K the rule

$$\frac{xRz, xRy, yRz, \Gamma \Rightarrow \Delta}{xRy, yRz, \Gamma \Rightarrow \Delta} \text{Trans}$$

Labelled sequent calculi do satisfy in general the basic desiderata of G3-style systems, and are rather modular.¹¹ However, since analyticity holds in a less strict version than the

¹¹Their origin dates back to [29], followed by the refinements in [34], [13], and [15]. However, labelled sequent calculi have established as a well-structured methodology after [44]. Extensions, refinements, and further results have since then obtained for a plethora of logics. Refer to e.g. [46, 47], [58], [12].

subformula principle mentioned in the previous definition, termination of proof search is sometimes hard to prove, and in many cases produces complexity results far from being optimal.

For reasons that will be clear soon to the reader, in the present paper internalisation is considered only in its explicit version, and we decided to adopt the labelled sequent calculus introduced first in [44] to achieve our goal of implementing a decision algorithm for GL.

6 Implementing G3KGL

Let us first make a bit more explicit the methodology behind labelled sequents for normal modal logics.

For those logics, labelled sequent calculi are based on a language \mathcal{L}_{LS} which extends \mathcal{L} with a set **WL** of world labels and a set **RA** of relational atoms of the form xRy for $x, y \in \mathbf{WL}$. formulas of \mathcal{L}_{LS} have only two possible forms

$$x : A \quad \text{or} \quad xRy,$$

where A is a formula of \mathcal{L} .

Sequents are now just pairs $\Gamma \Rightarrow \Delta$ of multisets of formulas of \mathcal{L}_{LS} .

Accordingly, the rules for *all* logical operators are defined on the basis of the inductive definition of the forcing relation between worlds and formulas of \mathcal{L} , here denoted by $x : A$. In particular, the forcing condition for the \Box modality

$$x \Vdash \Box A \quad \text{iff} \quad \text{for all } y, \text{ if } xRy, \text{ then } y \Vdash A$$

determines the following rules:

$$\frac{xRy, \Gamma \Rightarrow \Delta, y : A}{\Gamma \Rightarrow \Delta, x : \Box A} \mathcal{R}\Box_{(y)} \qquad \frac{y : A, xRy, x : \Box A, \Gamma \Rightarrow \Delta}{xRy, x : \Box A, \Gamma \Rightarrow \Delta} \mathcal{L}\Box$$

with the side condition for $\mathcal{R}\Box$ that y does not occur in Γ, Δ .

This is the very general framework behind the labelled sequent calculus G3K for the basic normal modal logic \mathbb{K} we defined in Figure 2. The results presented in [48, Ch. 6] assures that any extension of \mathbb{K} that is semantically characterised by (co)geometric frame conditions can be captured also by an extension of G3K with appropriate (co)geometric rules.

Any of such extensions will keep the good structural properties of the G3pc. Most relevantly, proving termination of the proof search in these calculi provides a neat proof of decidability for the corresponding logics, which allows the direct construction of a countermodel for a given formula generating a failed proof search.

6.1 The calculus G3KGL

The frame conditions characterising GL – i.e. Noetherianity and transitivity, or, equivalently, irreflexivity, transitivity and finiteness – cannot be expressed by a (co)geometric implication, for being finiteness and Noetherianity intrinsically second order.

Therefore it is not possible to define a labelled sequent calculus for GL by simply extending G3K with further semantic rules.

Nevertheless, it is still possible to internalise the possible world semantics by relying on a modified definition of the forcing relation – valid for ITF models – in which the standard condition for \Box is substituted by the following

$$x \Vdash \Box A \quad \text{iff} \quad \text{for all } y, \text{ if } xRy \text{ and } y \Vdash \Box A, \text{ then } y \Vdash A.$$

In [44], this suggests to modify the $R\Box$ rule according to the left-to-right direction of that forcing condition.

The resulting labelled sequent calculus G3KGL is summarised in Figure 1:

Initial sequents:	
$x : p, \Gamma \Rightarrow \Delta, x : p$	
Propositional rules:	
$\frac{}{x : \perp, \Gamma \Rightarrow \Delta} L\perp$	
$\frac{x : A, x : B, \Gamma \Rightarrow \Delta}{x : A \wedge B, \Gamma \Rightarrow \Delta} L\wedge$	$\frac{\Gamma \Rightarrow \Delta, x : A \quad \Gamma \Rightarrow \Delta, x : B}{\Gamma \Rightarrow \Delta, x : A \wedge B} R\wedge$
$\frac{x : A, \Gamma \Rightarrow \Delta \quad x : B, \Gamma \Rightarrow \Delta}{x : A \vee B, \Gamma \Rightarrow \Delta} L\vee$	$\frac{\Gamma \Rightarrow \Delta, x : A, x : B}{\Gamma \Rightarrow \Delta, x : A \vee B} R\vee$
$\frac{\Gamma \Rightarrow \Delta, x : A}{x : \neg A, \Gamma \Rightarrow \Delta} L\neg$	$\frac{x : A, \Gamma \Rightarrow \Delta}{\Gamma \Rightarrow \Delta, x : \neg A} R\neg$
$\frac{\Gamma \Rightarrow \Delta, x : A \quad x : B, \Gamma \Rightarrow \Delta}{x : A \rightarrow B, \Gamma \Rightarrow \Delta} L\rightarrow$	$\frac{x : A, \Gamma \Rightarrow \Delta, x : B}{\Gamma \Rightarrow \Delta, x : A \rightarrow B} R\rightarrow$
Modal rules:	
$\frac{y : A, xRy, x : \Box A, \Gamma \Rightarrow \Delta}{xRy, x : \Box A, \Gamma \Rightarrow \Delta} L\Box$	$\frac{xRy, y : \Box A, \Gamma \Rightarrow \Delta, y : A}{\Gamma \Rightarrow \Delta, x : \Box A} R\Box_{(y^!)}^{Löb}$
Semantic rules:	
$\frac{}{xRx, \Gamma \Rightarrow \Delta} Irref$	$\frac{xRz, xRy, yRz, \Gamma \Rightarrow \Delta}{xRy, yRz, \Gamma \Rightarrow \Delta} Trans$

■ **Figure 3** Rules of the calculus G3KGL

The rule $R\Box^{Löb}$ obeys to the side condition of not being y free in Γ, Δ , on the line with the universal quantifier used in the forcing condition.

In [45], it is proven that G3KGL has good structural properties. Moreover, it is easily shown that the proof search in this calculus is terminating, and its failure allows to construct a countermodel to the formula at the root of the derivation tree: it suffices to consider the top sequent of an open branch, and assume that all the labelled formulas and relational atoms in its antecedent are true, while all the labelled formulas in its consequent are false. This way, a syntactic proof of decidability for GL is obtained.

It is not hard to see how to use both our formalisation of modal completeness and the already known proof theory for G3KGL to the aim of implementing a decision algorithm in HOL Light for GL: our predicate `holds (W,R) V A x` corresponds exactly to the labelled formula $x : A$. Thus we have three different ways of expressing the fact that a world x forces A in a given model $\langle W, R, V \rangle$:

SEMANTIC NOTATION	$x \Vdash A$
LABELLED SEQUENT CALCULUS NOTATION	$x : A$
HOL LIGHT NOTATION	$\text{holds } (W,R) \ V \ A \ x$

Let us call any expression of forcing in HOL Light notation a **holds**-proposition.

This suggests that a *deep* embedding of G3KGL is not necessary at all. Since internalising possible world semantics in sequent calculi is, in fact, a syntactic formalisation of that very semantics, we can use *our own* formalisation in HOL Light of validity in Kripke frames and *adapt* the goalstack mechanism of the theorem prover to develop G3KGL proofs by relying on that very mechanism.

That adaptation starts with a generalisation of the standard tactics for classical propositional logic which are already defined in HOL Light.

As an abstract deductive system, the logical engine underlying the proof development in HOL Light consists of a single-consequent sequent calculus for higher-order logic. We need to work on a multi-consequent sequent calculus made of multisets of **holds**-propositions and (formalised) relational atoms. To handle commas, we recur to the logical operators of HOL Light: a comma in the antecedent is formalised by the connective \wedge , while in the consequent it is formalised by the connective \vee .

Since we cannot directly define multisets, we need to formalise the sequent calculus rules to operate on lists, and to handle permutations by means of standard conversions of a goal that has the general shape of an n -ary disjunction of **holds**-propositions, for $n \geq 0$.

The intermediate tactics we now need to define operate

- on the components of a general goal-term consisting of a finite disjunction of **holds**-propositions: these correspond to the labelled formulas that appear on the right-hand side of a sequent of G3KGL, so that some our tactics can behave as the appropriate right rules of that calculus;
- on the list of hypotheses of the goal-stack, which correspond to the labelled formulas and possible relational atoms that occur on the left-hand side of a sequent of G3KGL, so that some our tactics can behave as the appropriate left rules of that calculus.

In order to make the automation of the process easier, among the hypotheses of each goal-stack we make explicit the assumptions about the transitivity of the accessibility relation (**trans**), the left-to-right direction of the standard forcing condition for the \Box (**boxl1**), (**boxl1**), and the right-to-left direction of the forcing condition for the same modality in ITF models (**boxr1**), (**boxr2**). This way the formal counterparts of *Trans*, $\mathcal{L}\Box$ and $\mathcal{R}\Box^{L\ddot{o}b}$ can be properly executed by combining standard tactics and applying the results to those meta-hypotheses made explicit.

Our classical propositional tactics implement, for purely practical reasons, left and right rules for the (bi)implication free fragment of \mathcal{L} : this implies that the only intermediate tactics determining a branching in the derivation tree – i.e., the generation of subgoals in HOL Light goal-stack – are those corresponding to $\mathcal{L}\vee$ and $\mathcal{R}\wedge$. The translation of a formula of \mathcal{L}_{LS} , given as a goal, to its equivalent formula in the implemented fragment is produced automatically by means of the conversions for the negation and conjunctive normal forms already implemented in the theorem prover:¹²

¹² Here **HOLDS_NNFC_UNFOLD** is the formal theorem stating that the definition of the predicate **holds** can be rephrased, for purely propositional formulas, by using only conjunction, disjunction and negation as operators at the meta-level.

```

let HOLDS_NNFC_UNFOLD_CONV : conv =
  GEN_REWRITE_CONV TOP_DEPTH_CONV
  [HOLDS_NNFC_UNFOLD; OR_CLAUSES; AND_CLAUSES] THENC
  NNFC_CONV

```

A similar conversion is defined for the labelled formulas that appear among the hypotheses, i.e. on the left-hand side of our formal sequents.

Left rules for propositional connectives are handled by specific tactics: each of them is defined by using HOL Light theorem tactic(al)s, which can be thought of as operators on a given goal taking theorems as input to apply a resulting tactic to the latter. For instance, the left rule for negation $\mathcal{L}\neg$ is defined by

```

let NEG_LEFT_TAC : thm_tactic =
  let pth = MESON [] '~P ==> (P \\/ Q) ==> Q' in
  MATCH_MP_TAC o MATCH_MP pth

```

which uses the propositional tautology $\neg P \implies (P \vee Q) \implies Q$ in an MP rule instantiated with a negated `holds`-proposition occurring among the hypotheses; then it adds the `holds`-proposition among the disjuncts of the new goal, as expected. $\mathcal{R}\neg$ is defined analogously by `NEG_RIGHT_TAC`.

On the contrary $\mathcal{L}\vee$ and $\mathcal{R}\wedge$ are implemented by combining theorem tactic(al)s based on the basic operators `CONJ_TAC` and `DISJ_CASES`.

Modal rules are handled by means of the hypotheses `boxr1`, `boxr2`, `boxl1` and `boxl2` that are made explicit in each goal stack. $\mathcal{L}\Box$ is implemented via theorem tactic(al)s instantiating `boxl1` or `boxl2` with the appropriate `holds`-proposition and relational atom; similarly, $\mathcal{R}\Box^{L\ddot{o}b}$ is obtained by instantiating `boxr1` or `boxr2`, to change the current goal term. The same approach works also for the rule `Trans`, implemented by a theorem tactical `ACC_TCL` that instantiates and applies the meta-hypothesis `trans` to each appropriate relational atom among the hypotheses of a current goal stack.

This basically completes the formalisation – or shallow embedding – of G3KGL in HOL Light.

6.2 Design of the proof search

Our efforts turn now to run in HOL Light an automated proof search w.r.t. the implementation of G3KGL we have sketched in the previous section.

We can again rely on theorem tactic(al)s to build the main algorithm, but this time we need to define them recursively.

First, we have to apply recursively the left rules for propositional connectives, as well as the $\mathcal{L}\Box$ rule: this is made possible by the theorem tactic `HOLDS_TAC`. Furthermore, we need to saturate the sequents w.r.t. the latter modal rule, by considering all the possible relational atoms and applications of the rule for transitivity, and, eventually, further left rules: that is the job of the theorem tactic `SATURATE_ACC_TAC`.

After that, it is possible to proceed with the $\mathcal{R}\Box^{L\ddot{o}b}$: that is triggered by the `BOX_RIGHT_TAC`, which operates by applying (the implementation of) $\mathcal{R}\Box^{L\ddot{o}b}$ after `SATURATE_ACC_TAC` and `HOLDS_TAC`.

At this point, it is possible to optimise the application of `BOX_RIGHT_TAC` by applying the latter tactic after a “sorting tactic” `SORT_BOX_TAC`: that tactic performs a conversion of the goal term and orders it so that priority is given to negated `holds`-propositions, followed by those `holds`-propositions formalising the forcing of a boxed formula. Each of these types of `holds`-propositions are sorted furthermore as follows:

holds $WR \ V \ p \ w$ precedes holds $WR \ V \ q \ w$ if p occurs free in q and q does not occur free in p ; or if p is “less than” q w.r.t. the structural ordering of types provided by the OCaml module `Pervasives`.

The complete proof search is performed by the definitive tactic `GL_TAC`, from which we define the expected `GL_RULE`, defined as follows:

```
let GL_RIGHT_TAC : tactic =
  CONV_TAC (HOLDS_NNFC_UNFOLD_CONV) THEN
  PURE_ASM_REWRITE_TAC[AND_CLAUSES; OR_CLAUSES; NOT_CLAUSES] THEN
  CONV_TAC CNF_CONV THEN
  REPEAT CONJ_TAC THEN
  TRY (NEG_RIGHT_TAC HOLDS_TAC)

let GL_STEP_TAC : tactic =
  (FIRST o map CHANGED_TAC)
  [GL_RIGHT_TAC;
   SORT_BOX_TAC THEN BOX_RIGHT_TAC]

let INNER_GL_TAC : tactic = REPEAT GL_STEP_TAC

let GL_TAC : tactic =
  REPEAT GEN_TAC THEN REPEAT (CONV_TAC let_CONV) THEN REPEAT GEN_TAC THEN
  REWRITE_TAC[diam_DEF; dotbox_DEF] THEN MATCH_MP_TAC COMPLETENESS_NUM THEN
  REPEAT GEN_TAC THEN INTRO_TAC "trans boxr1 boxr2 boxl1 boxl2 w" THEN
  REPEAT GEN_TAC THEN Rule_gl.INNER_GL_TAC THEN GL_BUILD_COUNTERMODEL;;

let GL_RULE (tm:term) : thm =
  prove(tm, GL_TAC);;
```

Our tactic works as expected:

1. Given a formula A of \mathcal{L} , OCaml `let`-terms are rewritten together with definable modal operators, and the goal is set to $\vdash\!-\! A$;
2. A model $\langle W, R, V \rangle$ and a world $w \in W$ – where W sits on the type `num` – are introduced. The main goal is now `holds (W,R) V A w`;
3. Meta-hypotheses `trans boxr1 boxr2 boxl1 boxl2 w` are introduced to be able to handle modal and relational rules;¹³
4. all possible propositional rules are applied after unfolding the modified definition of the predicate `holds` given by `HOLDS_NNFC_UNFOLD`. This assures that at each step of the proof search, the goal term is a finite conjunction of disjunctions of positive and negative `holds`-propositions. As usual, priority is given to non-branching rules, i.e. to those that do not generate subgoals. Furthermore, the hypothesis list is checked, and `trans` is applied whenever possible; the same holds for $L\Box$, which is applied any appropriate hypothesis after the tactic triggering `trans`. Each new goal term is reordered by `SORT_BOX_TAC`, which always precedes the implementation of $\mathcal{R}\Box^{Löb}$.

The procedure is repeated starting from step 2. The tactic ruling it is `FIRST o map CHANGED_TAC`, which triggers the correct tactic – corresponding to a specific step of the very procedure – in `GL_STEP_TAC` that does not fail.

At each step, moreover, the following condition is checked by calling `ASM_REWRITE_TAC`:

¹³The meta-hypotheses `w` states that $w \in W$ so that we the labelling at the previous step is justified indeed.

Closing The same holds-proposition occurs both among the current hypotheses *and* the disjuncts of the (sub)goal; or `holds (W,R) V False x` occurs in the current hypothesis list for some label `x`.

This condition states that the current branch is closed, i.e. an initial sequent has been reached, or the sequent currently analysed has a labelled formula $x : \perp$ in the antecedent.

Termination of the proof search is assured by the results presented in [45]. Therefore, we have been authorised to conclude our `GL_TAC` by a `FAIL_TAC` that, when none of the steps 2–4 can be repeated during a proof search, our algorithm terminates, informing us that a countermodel to the input formula can be built.

That is exactly the job of our `GL_BUILD_COUNTERMODEL` tactic: it considers the goal state which the previous tactics of `GL_TAC` stopped at, collects all the hypotheses, discarding the meta-hypotheses, and negates all the disjuncts constituting the goal term. Again, by referring to the results in [49, 45], we know that this information suffices to the user to construct a relational countermodel for the formula A given as input to our theorem prover for GL.

6.3 Some examples

Because of its adequate arithmetical semantics, Gödel-Löb logic reveals an exceptionally simple instrument to study arithmetical phenomenon of self-reference, as well as Gödel's results concerning (in)completeness and (un)provability of consistency.

From a formal view-point, an arithmetical realisation $*$ in Peano arithmetic (PA)¹⁴ of our modal language consists of a function commuting with propositional connectives and such that $(\Box A)^* := Bew(\ulcorner A^* \urcorner)$, where $Bew(x)$ is the formal provability predicate for PA.

Under this interpretation, we will read modal formulas as follows:

$\Box A$	A is provable in PA
$\neg\Box\neg A$	A is consistent with PA
$\neg\Box A$	A is unprovable in PA
$\Box\neg A$	A is refutable in PA
$(\Box A) \vee (\Box\neg A)$	A is decidable in PA
$(\neg\Box A) \wedge (\neg\Box\neg A)$	A is undecidable in PA
$\Box(A \leftrightarrow B)$	A and B are equivalent over PA
$\Box\perp$	PA is inconsistent
$\neg\Box\perp, \Diamond\top$	PA is consistent

We are now going to test our theorem prover on some modal formulas that have a meta-mathematical relevance.

Formalised Gödel's second incompleteness theorem.

In PA, the following is provable: If PA is consistent, it cannot prove its own consistency. The corresponding modal formula is

$$\neg\Box\perp \rightarrow \neg\Box\Diamond\top$$

Here is the running of our prover:

```
# let GL_second_incompleteness_theorem = GL_RULE
  '|-- (Not (Box False) --> Not (Box (Diam True)))';;
```

¹⁴ Actually, we could consider any Σ_1 -sound arithmetical theory T extending $I\Sigma_1$ [67].

```
val GL_second_incompleteness_theorem : thm =
  |- |-- (Not Box False --> Not Box Diam True)
```

Undecidability of consistency.

If PA does not prove its inconsistency, then its consistency is undecidable. The corresponding modal formula is

$$\neg(\Box\Box\perp) \rightarrow \neg(\Box\neg\Box\perp) \wedge \neg(\Box\neg\neg\Box\perp)$$

Here is the running of our prover:

```
# let GL_PA_undecidability_of_consistency = GL_RULE
  ' |-- ( Not (Box (Box False))
        --> Not (Box (Not (Box False))) &&
          Not (Box (Not (Not (Box False)))) ) ';;

val GL_PA_undecidability_of_consistency : thm =
  |- |--
    (Not Box Box False -->
     Not Box Not Box False && Not Box Not Not Box False)
```

Undecidability of Gödel's formula.

The formula stating its own unprovability is undecidable in PA, if the latter does not prove its inconsistency. The corresponding modal formula is

$$\Box(A \leftrightarrow \neg\Box A) \wedge \neg\Box\Box\perp \rightarrow \neg\Box A \wedge \neg\Box\neg A$$

Here is the running of our prover:

```
# let GL_undecidability_of_Godels_formula = GL_RULE
  '!p. |-- ( Box (p <-> Not (Box p)) && Not (Box (Box False))
           --> Not (Box p) && Not (Box (Not p)) ) ';;

val GL_undecidability_of_Godels_formula : thm =
  |- !p. |--
    (Box (p <-> Not Box p) && Not Box Box False -->
     Not Box p && Not Box Not p)
```

Construction of a countermodel.

This is an example of countermodel construction from a failed proof search of the following reflection principle:

$$\Box(\Box p \vee \Box\neg p) \rightarrow (\Box p \vee \neg\Box\neg p)$$

Since such a formula is not a theorem of \mathbb{GL} , we know that there exists an arithmetical sentence ϕ such that it is consistent with PA that both ϕ is undecidable and it is provable that ϕ is decidable.

Here is the interactive running of our prover:

```
# g '!p . |-- (Box (Box p || Box (Not p)) --> (Box p || Box (Not p))) ';;
val it : goalstack = 1 subgoal (1 total)


'!p. |-- (Box (Box p || Box Not p) --> Box p || Box Not p) '

# e GL_TAC;;
Exception: Failure "Contermodel stored in reference the_gl_countermodel.".
```

The tactic notifies that a countermodel as been stored in the memory: all we have to do in order to read it is to run

```
# !the_gl_countermodel;;
val it : term =
  'holds (W,R) V p y' /\
  holds (W,R) V (Box Not p) y' /\
  R w y' /\
  holds (W,R) V (Box p) y' /\
  y' IN W /\
  R w y /\
  holds (W,R) V (Box p) y /\
  y IN W /\
  holds (W,R) V (Box (Box p || Box Not p)) w /\
  w IN W /\
  ~holds (W,R) V p y'
```

As expected, the structure that the countermodel constructor returns can be graphically rendered as



7 Related work

Our formalisation gives a mechanical proof of completeness for $\mathbb{G}\mathbb{L}$ in HOL Light which sticks to the original Henkin's method for classical logic. In its standard version, its nature is synthetic and intrinsically semantic [14], and, as we stated before, it is the core of the canonical model construction for most of normal modal logics.

That very approach does not work for $\mathbb{G}\mathbb{L}$. Nevertheless, the modified extension lemma we proved in our mechanization introduces an analytic flavour to the strategy – for building maximal consistent lists in terms of components of a given non-provable formula in the calculus – and shows that Henkin's idea can be applied to $\mathbb{G}\mathbb{L}$ too modulo appropriate changes.

As far as we know, *no other mechanized proof of modal completeness for $\mathbb{G}\mathbb{L}$* has been given before, despite there exist formalisations of similar results for several other logics, mainly propositional and first-order classical and intuitionistic logic.

Formal proof of semantic completeness for *classical logic* has defined an established trend in interactive theorem proving since [62], where a Hintikka-style strategy is used to define a theoremhood checker for formulas built up by negation and disjunction only.

In fact, a very general treatment of systems for classical propositional logic is given in [41]. There, an axiomatic calculus is investigated along with natural deduction, sequent calculus, and resolution system in Isabelle/HOL, and completeness is proven by Hintikka-style method for sequent calculus first, to be lifted then to the other formalisms by means of translations of each system into the others. Their formalisation is more ambitious than ours, but, at the same time, it is focused on a very different aim. A similar overview of meta-theoretical results for several calculi formalised in Isabelle/HOL is given in [7], where, again, a more general investigation – unrelated to modal logics – is provided.

Concerning the area of intuitionistic modalities, [4] gives a constructive proof of completeness of IS4 w.r.t. a specific relational semantics verified in Agda, but it uses natural

deduction and applies modal completeness to obtain a normalization result for the terms of the associated λ -calculus.

A Henkin-style completeness proof for $\mathbb{S}5$ formalised in Lean is presented in [6]. That work applies the standard method of canonical models – since $\mathbb{S}5$ is compact.

More recently, [68] used the HOL4 theorem prover for a general treatment of model theory of modal systems. For future work, it might be interesting to make use of the formalisation therein along with the main lines of our implementation of axiomatic calculi to merge the two presentations – syntactic and semantic – in an exhaustive way.

Our formalisation, however, has been led by the aim of developing a (prototypical) theorem prover in HOL Light for normal modal logics. The results concerning GL that we have presented here can be thought of as a case study of our original underlying methodology.

Automated deduction for modal logic has become a relevant scientific activity in recent years, and exhaustive comparison of our prover with other implementations of modal systems is beyond our purposes. In spite of this, we care to mention at least three different development lines on that trend.

The work of [25] consists of an extremely efficient hybridism of SAT-solvers, modal clause-learning, and tableaux methods for modal systems. That prover deals with minimal modal logic K, and its extensions T and S4. The current version of their implementation does not produce a proof, nor a countermodel, for the input formula; however, the code is publicly available, and minor tweaks should make it do so.

The conference paper [22] presents a theorem prover for intuitionistic modal logics implementing proof search for Tait-style nested sequent calculi in Prolog. Because of the structural properties of those calculi, that prover returns, for each input formula, a proof in the appropriate calculus, or a countermodel extracted from the failed proof search in the system. Similar remarks could be formulated for the implementation described in [21] concerning several logics for counterfactuals.

The latter formalisations are just two examples of an established *modus operandi* in implementing proof search in extended sequent calculi for non-classical logics by using the mere depth-first search mechanism of Prolog. Other instances of that line are e.g. [2, 18, 19][50, 51, 52, 53], and [11]. None of those provers deals explicitly with GL, but that development approach would find no issue in formalising G3KGL too.

Notice, in any case, that adequacy (soundness and completeness) of all those implementations rely on results that are *informally* proven at the meta-level. Our theorem prover for GL, on the contrary, is *certified* to be sound and complete by our *theorems* in HOL Light `GL_ITF_VALID` and `COMPLETENESS_THEOREM_GEN`, whose correctness, in turn, depends on the LCF approach. Nothing, in principle, prevents the HOL Light user from implementing certified theorem provers for the logics of the Prolog-based development line by proving the appropriate adequacy theorems for the logic under investigation. That proof search is well-behaved would rest, in those cases as well as ours, on the properties of the general proof techniques of HOL Light.

Similar remarks could be made about [55], where a general framework for object-level reasoning with multiset-based sequent calculi in HOL Light is proposed. They present a *deep* embedding of those systems by defining in HOL Light an appropriate relation between multisets and encode two G1 calculi – namely, a fragment of propositional intuitionistic logic and its Curry-Howard analogous type theory. Specific tactics are then defined in order to perform an interactive proof search of a given sequent. For our purposes, it might be interesting to check whether their implementation may be of some help to enhance the

performance and functionality of our prototypical theorem prover.¹⁵

Indeed, moving from the experiment about GL proposed in the present work, we plan to develop in future a more general (and more refined) mechanism – still based on the methodology discussed here – to deal with (ideally) the whole cube of normal modal logic within HOL Light. An immediate step in that direction would be to enhance the implementation of formal proofs in G3KGL, so that a positive answer to a given input formula would produce also a real derivation tree in the labelled sequent calculus of that very formula.

References

- 1 Juan Aguilera and David Fernández-Duque. Strong completeness of provability logic for ordinal spaces. *The Journal of Symbolic Logic*, 82:608–628, 11 2017. doi:10.1017/jsl.2017.3.
- 2 Régis Alenda, Nicola Olivetti, and Gian Luca Pozzato. CSL-lean: A theorem-prover for the logic of comparative concept similarity. *Electronic Notes in Theoretical Computer Science*, 262:3–16, 2010.
- 3 Arnon Avron. The method of hypersequents in the proof theory of propositional non-classical logics. In *Logic: from foundations to applications: European logic colloquium*, pages 1–32, 1996.
- 4 Miętek Bak. Introspective Kripke models and normalisation by evaluation for the λ^\square -calculus. 7th Workshop on Intuitionistic Modal Logic and Applications (IMLA 2017). <https://github.com/mietek/imla2017/blob/master/doc/imla2017.pdf>, 2017.
- 5 Lev Beklemishev and Albert Visser. Problems in the logic of provability. In *Mathematical Problems from Applied Logic I*, pages 77–136. Springer, 2006.
- 6 Bruno Bentzen. A Henkin-style completeness proof for the modal logic S5. *CoRR*, abs/1910.01697, 2019. URL: <http://arxiv.org/abs/1910.01697>, arXiv:1910.01697.
- 7 Jasmin Christian Blanchette. Formalizing the Metatheory of Logical Calculi and Automatic Provers in Isabelle/HOL (Invited Talk). In *Proceedings of the 8th ACM SIGPLAN International Conference on Certified Programs and Proofs, CPP 2019*, page 1–13, New York, NY, USA, 2019. Association for Computing Machinery. doi:10.1145/3293880.3294087.
- 8 George Boolos. *The logic of provability*. Cambridge university press, 1995.
- 9 Kai Brünnler. Deep sequent systems for modal logic. *Archive for Mathematical Logic*, 48(6):551–577, 2009.
- 10 B. Jack Copeland. The genesis of possible worlds semantics. *Journal of Philosophical logic*, 31(2):99–137, 2002.
- 11 Tiziano Dalmonte, Sara Negri, Nicola Olivetti, and Gian Luca Pozzato. Theorem Proving for Non-normal Modal Logics. In *OVERLAY 2020*, Udine, Italy, September 2021. URL: <https://hal.archives-ouvertes.fr/hal-03159954>.
- 12 Tiziano Dalmonte, Nicola Olivetti, and Sara Negri. Non-normal modal logics: Bi-neighbourhood semantics and its labelled calculi. In *Advances in Modal Logic 2018*, 2018.
- 13 Melvin Fitting. *Proof methods for modal and intuitionistic logics*, volume 169. Springer Science & Business Media, 2013.
- 14 Melvin Fitting and Richard L. Mendelsohn. *First-order modal logic*, volume 277. Springer Science & Business Media, 2012.
- 15 Dov M. Gabbay. Labelled Deductive Systems. *Oxford Logic Guides 33*, 1, 1996.
- 16 Gerhard Gentzen. Untersuchungen über das logische Schließen I. *Mathematische zeitschrift*, 39:176–210, 1935.
- 17 Gerhard Gentzen. Untersuchungen über das logische Schließen II. *Mathematische zeitschrift*, 39:405–431, 1935.

¹⁵One might say that the framework of [55] is similar to the works in Prolog for aiming a direct deep embedding of a sequent calculus, but it is also close to our implementation for adopting the LCF approach and for choosing HOL Light as environment.

- 18 Laura Giordano, Valentina Gliozzi, Nicola Olivetti, and Gian Luca Pozzato. Analytic tableaux for KLM preferential and cumulative logics. In *International Conference on Logic for Programming Artificial Intelligence and Reasoning*, pages 666–681. Springer, 2005.
- 19 Laura Giordano, Valentina Gliozzi, and Gian Luca Pozzato. KLMLean 2.0: A theorem prover for KLM logics of nonmonotonic reasoning. In *International Conference on Automated Reasoning with Analytic Tableaux and Related Methods*, pages 238–244. Springer, 2007.
- 20 Marianna Girlando, Bjoern Lellmann, Nicola Olivetti, Gian Luca Pozzato, and Quentin Vitalis. VINTE: an implementation of internal calculi for Lewis’ logics of counterfactual reasoning. In *International Conference on Automated Reasoning with Analytic Tableaux and Related Methods*, pages 149–159. Springer, 2017.
- 21 Marianna Girlando, Björn Lellmann, Nicola Olivetti, Stefano Pesce, and Gian Luca Pozzato. Calculi, countermodel generation and theorem prover for strong logics of counterfactual reasoning. *Journal of Logic and Computation*, 01 2022. exab084. [arXiv:https://academic.oup.com/logcom/advance-article-pdf/doi/10.1093/logcom/exab084/42296490/exab084.pdf](https://academic.oup.com/logcom/advance-article-pdf/doi/10.1093/logcom/exab084/42296490/exab084.pdf), doi: 10.1093/logcom/exab084.
- 22 Marianna Girlando and Lutz Straßburger. Moin: A nested sequent theorem prover for intuitionistic modal logics (system description). In *International Joint Conference on Automated Reasoning*, pages 398–407. Springer, 2020.
- 23 Kurt Gödel. Eine Interpretation des Intuitionistischen Aussagenkalküls. Ergebnisse eines Mathematischen Kolloquiums, 4: 39–40, 1933. english translation, with an introductory note by A.S. Troelstra. *Kurt Gödel, Collected Works*, 1:296–303, 1986.
- 24 Robert Goldblatt. Mathematical modal logic: A view of its evolution. In *Handbook of the History of Logic*, volume 7, pages 1–98. Elsevier, 2006.
- 25 Rajeev Goré and Cormac Kikkert. CEGAR-Tableaux: Improved Modal Satisfiability via Modal Clause-Learning and SAT. In *International Conference on Automated Reasoning with Analytic Tableaux and Related Methods*, pages 74–91. Springer, 2021.
- 26 Raul Hakli and Sara Negri. Does the deduction theorem fail for modal logic? *Synthese*, 187(3):849–867, 2012.
- 27 John Harrison. HOL Light tutorial. <http://www.cl.cam.ac.uk/~jrh13/hol-light/tutorial.pdf>, 2017.
- 28 John Harrison. The HOL Light Theorem Prover. Web site: <https://github.com/jrh13/hol-light>, 2022.
- 29 Stig Kanger. Provability in logic. *Stockholm studies in philosophy*, 1957.
- 30 Ryo Kashima. Cut-free sequent calculi for some tense logics. *Studia Logica*, pages 119–135, 1994.
- 31 Oiva Ketonen. Untersuchungen Zum Prädikatenkalkül. *Journal of Symbolic Logic*, 10(4):127–130, 1945. doi:10.2307/2269018.
- 32 S.C. Kleene. Permutability of inferences in Gentzen’s calculi LK and LJ. *Memoirs of the American Mathematical Society*, 1952.
- 33 Saul A Kripke. A completeness theorem in modal logic 1. *The Journal of Symbolic Logic*, 24(1):1–14, 1959.
- 34 Saul A. Kripke. Semantical analysis of intuitionistic logic I. In *Studies in Logic and the Foundations of Mathematics*, volume 40, pages 92–130. Elsevier, 1965.
- 35 Hidenori Kurokawa. Hypersequent calculi for modal logics extending S4. In *JSAI International Symposium on Artificial Intelligence*, pages 51–68. Springer, 2013.
- 36 Joachim Lambek and Philip J. Scott. *Introduction to higher-order categorical logic*, volume 7. Cambridge University Press, 1988.
- 37 Björn Lellmann. Hypersequent rules with restricted contexts for propositional modal logics. *Theoretical Computer Science*, 656:76–105, 2016.
- 38 Björn Lellmann and Elaine Pimentel. Modularisation of sequent calculi for normal and non-normal modalities. *ACM Transactions on Computational Logic (TOCL)*, 20(2):1–46, 2019.

- 39 Marco Maggesi and Cosimo Perini Brogi. A Formal Proof of Modal Completeness for Provability Logic. In Liron Cohen and Cezary Kaliszyk, editors, *12th International Conference on Interactive Theorem Proving (ITP 2021)*, volume 193 of *Leibniz International Proceedings in Informatics (LIPIcs)*, pages 26:1–26:18, Dagstuhl, Germany, 2021. Schloss Dagstuhl – Leibniz-Zentrum für Informatik. URL: <https://drops.dagstuhl.de/opus/volltexte/2021/13921>, doi:10.4230/LIPIcs.ITP.2021.26.
- 40 Sonia Marin and Lutz Straßburger. Label-free modular systems for classical and intuitionistic modal logics. In *Advances in Modal Logic 10*, 2014.
- 41 Julius Michaelis and Tobias Nipkow. Formalized proof systems for propositional logic. In A. Abel, F. Nordvall Forsberg, and A. Kaposi, editors, *23rd Int. Conf. Types for Proofs and Programs (TYPES 2017)*, volume 104 of *LIPIcs*, pages 6:1–6:16. Schloss Dagstuhl - Leibniz-Zentrum fuer Informatik, 2018.
- 42 G. Mints. *Short Introduction to Modal Logic*. Center for the Study of Language and Information Publication Lecture Notes. Cambridge University Press, 1992. URL: <https://books.google.it/books?id=n1xN2YnYCyGc>.
- 43 Grigori Mints and R. Feys. Sistemy Lyuisa i sistema T (Supplement to the Russian translation). *R. Feys, Modal Logic*, pages 422–509, 1974.
- 44 Sara Negri. Proof analysis in modal logic. *Journal of Philosophical Logic*, 34(5):507–544, 2005.
- 45 Sara Negri. Proofs and countermodels in non-classical logics. *Logica Universalis*, 8(1):25–60, 2014.
- 46 Sara Negri. Proof theory for non-normal modal logics: The neighbourhood formalism and basic results. *IfCoLog Journal of Logics and their Applications*, 4(4):1241–1286, 2017.
- 47 Sara Negri and Edi Pavlović. Proof-theoretic analysis of the logics of agency: The deliberative stit. *Studia Logica*, 109(3):473–507, 2021.
- 48 Sara Negri and Jan von Plato. *Structural proof theory*. Cambridge university press, 2008.
- 49 Sara Negri and Jan von Plato. *Proof analysis: a contribution to Hilbert's last problem*. Cambridge University Press, 2011.
- 50 Nicola Olivetti and Gian Luca Pozzato. CondLean: A theorem prover for conditional logics. In *International Conference on Automated Reasoning with Analytic Tableaux and Related Methods*, pages 264–270. Springer, 2003.
- 51 Nicola Olivetti and Gian Luca Pozzato. CondLean 3.0: Improving CondLean for stronger conditional logics. In *International Conference on Automated Reasoning with Analytic Tableaux and Related Methods*, pages 328–332. Springer, 2005.
- 52 Nicola Olivetti and Gian Luca Pozzato. Theorem proving for conditional logics: CondLean and GoalDuck. *Journal of Applied Non-Classical Logics*, 18(4):427–473, 2008.
- 53 Nicola Olivetti and Gian Luca Pozzato. NESCOND: an implementation of nested sequent calculi for conditional logics. In *International Joint Conference on Automated Reasoning*, pages 511–518. Springer, 2014.
- 54 Nicola Olivetti and Gian Luca Pozzato. A standard internal calculus for Lewis' counterfactual logics. In *International Conference on Automated Reasoning with Analytic Tableaux and Related Methods*, pages 270–286. Springer, 2015.
- 55 Petros Papapanagiotou and Jacques Fleuriot. Object-level reasoning with logics encoded in hol light. In *Fifteenth Workshop on Logical Frameworks and Meta-Languages: Theory and Practice*, pages 18–34. Open Publishing Association, 2021.
- 56 Francesca Poggiolesi. The method of tree-hypersequents for modal propositional logic. In *Towards mathematical philosophy*, pages 31–51. Springer, 2009.
- 57 Francesca Poggiolesi. *Gentzen calculi for modal propositional logic*, volume 32. Springer Science & Business Media, 2010.
- 58 Francesca Poggiolesi. Natural deduction calculi and sequent calculi for counterfactual logics. *Studia Logica*, 104(5):1003–1036, 2016.
- 59 Sally Popkorn. *First steps in modal logic*. Cambridge University Press, 1994.

- 60 Garrel Pottinger. Uniform, cut-free formulations of T, S4 and S5. *Journal of Symbolic Logic*, 48(3):900, 1983.
- 61 Greg Restall. Proofnets for S5: sequents and circuits for modal logic. In *Logic Colloquium*, volume 28, pages 3–1, 2005.
- 62 Natarajan Shankar. Towards mechanical metamathematics. *Journal of Automated Reasoning*, 1(4):407–434, 1985.
- 63 Alex K. Simpson. The Proof Theory and Semantics of Intuitionistic Modal Logic. *PhD thesis, University of Edinburgh. College of Science and Engineering. School of Informatics*, 1994.
- 64 Robert M. Solovay. Provability interpretations of modal logic. *Israel journal of mathematics*, 25(3-4):287–304, 1976.
- 65 Anne Sjerp Troelstra and Helmut Schwichtenberg. *Basic proof theory*. Number 43. Cambridge University Press, 2000.
- 66 Johan van Benthem and Patrick Blackburn. Modal logic: a semantic perspective. In *Handbook of modal logic*, volume 3, pages 1–84. Elsevier, 2007.
- 67 Rineke (L.C.) Verbrugge. Provability Logic. In Edward N. Zalta, editor, *The Stanford Encyclopedia of Philosophy*. Metaphysics Research Lab, Stanford University, fall 2017 edition, 2017.
- 68 Yiming Xu and Michael Norrish. Mechanised modal model theory. In Nicolas Peltier and Viorica Sofronie-Stokkermans, editors, *Automated Reasoning*, pages 518–533, Cham, 2020. Springer International Publishing.