

# The Selectively Adaptive Lasso

Alejandro Schuler, Mark van der Laan

May 24, 2022

## Abstract

Machine learning regression methods allow estimation of functions without unrealistic parametric assumptions. Although they can perform exceptionally in prediction error, most lack theoretical convergence rates necessary for semi-parametric efficient estimation (e.g. TMLE, AIPW) of parameters like average treatment effects. The Highly Adaptive Lasso (HAL) is the only regression method proven to converge quickly enough for a meaningfully large class of functions, independent of the dimensionality of the predictors. Unfortunately, HAL is not computationally scalable. In this paper we build upon the theory of HAL to construct the *Selectively Adaptive Lasso* (SAL), a new algorithm which retains HAL's dimension-free, nonparametric convergence rate but which also scales computationally to massive datasets. To accomplish this, we prove some general theoretical results pertaining to empirical loss minimization in nested Donsker classes. Our resulting algorithm is a form of gradient tree boosting with an adaptive learning rate, which makes it fast and trivial to implement with off-the-shelf software. Finally, we show that our algorithm retains the performance of standard gradient boosting on a diverse group of real-world datasets. SAL makes semi-parametric efficient estimators practically possible and theoretically justifiable in many big data settings.

## 1 Introduction

In regression our task is to find a function that maps features to an outcome or score such that the expected loss is minimized [1]. In the past decades a huge number of flexible regression methods have been developed that effectively search over high- or infinite-dimensional function spaces (these are often collectively called “machine learning” methods for regression).

In statistical inference, our task is more broadly to estimate the value of some aspect of an unknown probability distribution (e.g. a mean) and to quantify a measure of uncertainty about our estimate that comes from having drawn random data from this distribution. Modern statistical theory provides methods for doing this without imposing unrealistic assumptions on the data-generating mechanism (e.g. normality, linearity) [2]. Moreover, under certain conditions, some of these methods provide optimality in the sense that no other estimator has less sampling variance; such estimators are called "efficient", or "semi/non-parametric efficient" when efficiency holds without parametric assumptions [3, 4]. When combined with causal identification results, these methods allow us to most efficiently answer important real-world causal questions from complex data structures: for example, assessing whether a drug improves cancer survival despite self-selection into treatment and some outcome censoring.

In general, however, the beneficial properties of these estimators can only be guaranteed if certain regressions can be made to converge quickly to their true optima. For example, when estimating the average treatment effect from observational data, a sufficient condition for nonparametric efficiency of the TMLE and AIPW estimators is that the propensity score and outcome regression models converge to their respective truths in root-mean-square generalization error at a rate of  $o_P(n^{-1/4})$  [3, 4]. Thus the development of fast-converging, nonparametric regression methods is critical for efficient statistical inference.

Without putting unrealistic smoothness conditions on the regression functions, it is difficult to prove rates faster than  $o_P(n^{-1/4})$ . In fact, there are general theorems that show that attaining such a rate is impossible if we assume unrestricted high-dimensional function spaces without such smoothness conditions [5]. This is often referred to as the *curse of dimensionality* [6, 7].

This curse of dimensionality made efficient inference in observational studies theoretically difficult to guarantee in a general nonparametric setting. In 2016, however, Benkeser and van der Laan [8] showed

that dimension-free  $o_P(n^{-1/4})$  rates (or better) are attainable under nonrestrictive assumptions with a regression method called the *Highly Adaptive Lasso* (HAL). Instead of assuming smoothness, HAL assumes that the true function is cadlag of bounded sectional variation. Roughly speaking, this restricts the amount the true function can go up and down over its domain in a total, global sense, instead of restricting its behavior locally. HAL therefore imposes no scientifically meaningful assumptions because (a) this variation norm bound can be arbitrarily large and (b) cadlag functions are extremely general (e.g. even allowing discontinuities). To our knowledge, HAL is the only method that provides rates fast enough for efficient inference in any realistic nonparametric setting [9].

Unfortunately, as we will shortly see, the HAL algorithm is practically infeasible even for moderately sized problems. So, somewhat ironically, statistical scalability comes at the cost of computational scalability. On the other hand, many popular machine learning methods are massively scalable but come without the required theoretical guarantees. Gradient-boosted trees in particular have proven consistently successful in real-world prediction settings [10, 11, 12].

Our task in this paper is to marry these two kinds of advantages. We build upon the theory of HAL to construct a new gradient-boosted tree algorithm that retains HAL’s convergence rate in the same nonparametric setting but which scales computationally to massive datasets. To accomplish this, we prove two general theoretical results pertaining to empirical loss minimization in nested Donsker classes.

**Outline** We begin by reviewing the mechanics and theory of HAL (section 2). We then motivate and state our new theoretical results (sections 3.1, 3.2) and explore their implications in the construction of a new algorithm (SAL) which retains the HAL rate (section 3.3). Lastly, we demonstrate SAL’s performance in real-world datasets (section 4) and conclude with a brief discussion (section 5).

**Notation and Preliminaries** Throughout the paper we adopt the empirical process notation  $Pf = \int f(Z)dP$  and  $P_n f = \frac{1}{n} \sum_i f(Z_i)$ . In this notation these operators do not average over any potential randomness in  $f$ , so, for example,  $Pf_n$  is a random variable if  $f_n$  is a random function learned from data. We reserve  $\tilde{P}_n f_n$  for the case where  $f_n$  is random, but independent from the random measure  $\tilde{P}_n$  (e.g. when  $\tilde{P}_n$  is the empirical measure of a validation set). We use  $\|f\|$  to indicate an  $L2$  norm  $\sqrt{Pf^2}$  unless otherwise noted. To indicate the probability measure of a set we use braces, e.g.  $P\{Z < c\}$ .

Let  $X_i, Y_i \in \mathcal{X} \times \mathbb{R}$  be IID across  $i$  and with a generic  $X, Y$  that have some joint distribution  $P$ . We will take  $\mathcal{X} = [0, 1]^p$  without loss of generality for applications with bounded covariates. Let  $f = \arg \min_{f: \mathcal{X} \rightarrow \mathbb{R}} PL(f; X, Y)$  for some loss  $L$  (e.g. mean-squared error), which from now on we invoke in abbreviated form  $L(f)$  or  $Lf$ . This is the standard regression setup where our goal is to estimate the function  $f$  from  $n$  samples of the vector of predictors  $X$  and the outcome  $Y$ .

Throughout, we presume that the truth  $f$  is a cadlag function of sectional variation norm (defined in what follows) bounded by  $M$  and refer to this set of functions as  $\mathcal{F}_M$ . We refer to the set of cadlag functions as  $\mathcal{F}$ .

In our theoretical results we give convergence rates of some estimator  $f_n$  in terms of the *divergence* (or “loss-based dissimilarity”)  $P(Lf_n - Lf)$ . However, we are usually interested in the  $L2$  norm  $\|f_n - f\|_2 = \sqrt{P(f_n - f)^2}$  of regressions in order to prove efficiency in estimating some target parameter. The reader should note that convergence in divergence typically implies  $L2$  convergence at the same rate under very mild conditions on the loss function<sup>1</sup> which are satisfied in all standard applications [13].

## 2 Highly Adaptive Lasso (HAL)

We begin with a description of HAL, which is fairly simple in its mechanics yet rich in theory.

### 2.1 Algorithm

Mechanically, HAL is just lasso [14], but using a special, transformed set of covariates. That is, instead of fitting lasso with the data  $(X, Y)_i^n$ , we pass in  $(H_n(X), Y)_i^n$  where  $H_n : \mathcal{X} \rightarrow \{0, 1\}^{K_n}$  is a particular function that expands the covariates  $X$  into a larger set of binary predictors.  $H_n$  is not fixed a-priori (thus the subscript  $n$ ), but is instead adaptively determined by the full dataset  $(X)_i^n$ , as we will describe shortly.

Let  $h_{s,c} : \mathcal{X} \rightarrow \{0, 1\}$  represent one of the  $K_n$  elements of  $H_n$  so that  $H_n(X) = [h_{s_1, c_1}(X), \dots, h_{s_{K_n}, c_{K_n}}(X)]^\top$ . We refer to these  $h_{s,c}$  as basis functions, or just bases. Each basis is indexed by a “section”  $s \subset \{1 \dots p\}$ ,

---

<sup>1</sup>When the loss is mean-squared-error, we see directly that  $P(Lf_n - Lf) = P(f_n - f)^2$  via iterated expectation (conditioning on  $X$ ) and recognizing  $f = E[Y|X]$  in this case.

which is just some subset of the covariates, and a knot point  $c \in \mathcal{X}$ . The  $(s, c)$  basis is given by  $h_{s,c}(X) = \prod_{j \in s} 1(X_j \geq c_j)$ . Geometrically,  $h_{s,c}(X)$  tells us whether or not  $X$  is “up and to the right” of the  $s$ -section of the knot  $c$ . For a single knot  $c$  we can construct up to  $2^p - 1$  bases, each of which corresponds to a different possible subset of the raw covariates.

Alternatively, we can index these bases with a knot point  $c \in \bar{\mathbb{R}} = \mathbb{R} \cup \{\pm\infty\}$  in which case we have  $h_c = 1(c \leq x)$  where the inequality is taken to hold in each dimension. Bases of this kind can be thought of as indicators of the positive orthant in Cartesian space, translated by some (possibly infinite) amount in each coordinate. For that reason, we’ll refer to these as “positive orthant bases”.

For HAL, we define  $H_n$  as the set of bases  $\{h_{s,c} : s \subset \{1 \dots p\}, c \in (X)_i^n\}$ . In other words, we take all bases that can be constructed using each observed  $X_i$  as a knot point, using all possible sections. This generates a maximum of  $K_n = n(2^p - 1)$  unique bases which includes an intercept  $h_{\emptyset, \cdot}$ . In this way the precise set of bases depends on the observed values  $\{X_i\}_1^n$  and is thus data-adaptive.

When we apply the transformation  $H_n$  row-wise to the covariate matrix  $(X)_i^n$  we can represent the output  $(H_n(X))_i^n$  as a binary matrix with  $n$  rows and  $K_n$  columns. These are the transformed predictors that we then feed into the standard lasso algorithm, which produces the estimated function

$$f_n = \arg \min_{f \in \mathcal{F}_{M,n}} P_n L f \quad (1)$$

$$\mathcal{F}_{M,n} = \left\{ \begin{array}{l} H_n(X)^\top \beta \\ \text{s.t. } \|\beta\|_1 \leq M \end{array} \right\} \quad (2)$$

for a vector of coefficients  $\beta \in \mathbb{R}^{K_n}$  and a desired L1 bound  $M$  that directly corresponds to a regularization parameter  $\lambda$  in a penalized regression  $f_n = \arg \min_{f \in \mathcal{F}_{M,n}} (P_n L f + \lambda \|\beta(f)\|)$ . The user must specify the data and the desired regularization  $\lambda$ . HAL can therefore be easily implemented as a wrapper around existing lasso software, e.g. `glmnet` [15].

## 2.2 Theory

Although HAL is beguilingly simple in its mechanics, it is extremely powerful theoretically. To understand this we must return to our class  $\mathcal{F}$  of cadlag functions of bounded sectional variation norm.

“Cadlag” (*continu à droite, limites à gauche*) means right-continuous with left limits. So, for example, all continuous functions are cadlag. Cadlag functions correspond 1-to-1 with signed measures the same way that cumulative distribution functions correspond with probability measures. The sectional variation norm<sup>2</sup> of a cadlag function  $f$  on  $[0, 1]^p$  is given by  $\|f\|_\nu = f(0) + \sum_{s \in \{1 \dots p\}} \int_0^{1_s} |df(x_s)|$  where the  $x_s$  notation means that all elements of  $x$  not in the set of coordinates  $s$  are fixed at 0. Intuitively, a variation norm is a way of measuring how much a function goes up and down in total over its entire domain. For a function of one variable, the variation norm is the total “elevation gain” plus “elevation loss” over the domain, up to a constant.

$\mathcal{F}_M$  is therefore an extremely rich class of functions:  $f \in \mathcal{F}_M$  may be highly nonlinear and even discontinuous. Functions that are not in  $\mathcal{F}_M$  tend to be pathological, e.g.  $f(x) = \cos(1/x)$ . That is why assuming  $f \in \mathcal{F}_M$  generally does not constitute a scientifically meaningful restriction of possibilities for large enough  $M$ . However,  $\mathcal{F}_M$  happens to be “small” enough that it is a *Donsker class*, meaning that empirical processes indexed by this class of functions converge in distribution to a limit that is a tight Gaussian process [2]. This is key to proving HAL’s fast convergence rate.

Benkeser and van der Laan [8] and Fang et al. [7] give a concise argument that the lasso solution  $f_n$  as defined above (eq. 3) is in fact one of the exact solutions of the functional optimization problem:

$$f_n^* = \arg \min_{f \in \mathcal{F}_M} P_n L f \quad (3)$$

$$\mathcal{F}_M = \left\{ \begin{array}{l} f \in \mathcal{F} \\ \text{s.t. } \|f\|_\nu \leq M \end{array} \right\} \quad (4)$$

This result follows from an expanded representation of the sectional variation norm for cadlag functions. Thus HAL elegantly reduces the functional (infinite-dimensional) optimization problem to a finite-dimensional one. If the loss  $L$  corresponds to a negative log-likelihood, HAL is a nonparametric maximum likelihood estimator [16].

---

<sup>2</sup>The *sectional* variation norm is also called “Hardy-Krause variation” and is distinct from, but related to the more common notion of *total* variation norm (also known as “Vitali variation”) [7].

Since  $\mathcal{F}_M$  is Donsker and  $f_n$  is the empirical minimizer of the loss in the class, generic results from empirical process theory establish that  $f_n$  converges in mean-squared error to  $f$  at a root- $n$  rate provided that  $L$  is mean-squared error loss and  $M$  is chosen large enough that  $f \in \mathcal{F}_M$  [8, 2]. Specifically, we have that  $P(f_n - f)^2 = o_P(n^{-1/2})$ . A more involved proof based on the entropy integral of the function class  $\mathcal{F}_M$  shows that this rate can even be improved to  $O_P(n^{-1/3}(\log n)^{2(p-1)/3})$  [13]. These rates also generalize to most other commonly-used loss functions [13]. Astoundingly, the convergence speed does not depend on the covariate dimension  $p$  (or does, but only through a log factor), meaning that HAL effectively breaks the curse of dimensionality.

Moreover, recent work has shown how HAL by itself can be leveraged for inference without the aid of bias-correcting schemes like TMLE [17]. It is well known that unbiased plug-in estimation is generally not possible with other regression methods [18]. HAL succeeds in this task because it asymptotically solves all score equations in a semiparametric model where the functional components are cadlag and of bounded variation.

### 3 Selectively Adaptive Lasso (SAL)

HAL boasts impressive statistical properties that make it stand alone among methods for supervised learning. Unfortunately, it is not computationally feasible to use HAL for high dimensional data because it involves solving a lasso problem with up to  $n(2^p - 1)$  predictors. For example, consider a moderately sized problem where we would like to use electronic health records from 2,000 patients to predict expected survival time from a panel of 20 continuous biomarkers. The number of constructed predictors for this problem numbers over two billion. That makes it difficult to instantiate the required matrix in memory, let alone compute on it.

The point of our new algorithm, which we call the *Selectively Adaptive Lasso* (SAL) is to retain all of the impressive statistical properties of HAL without paying the computational price. The two fundamental ideas that make SAL computationally practical and performant are (1) data-adaptive early-stopping validation and (2) expressive bases. We'll first explore what we mean by these concepts and then state powerful theorems that together let us carry over HAL's impressive convergence rate to SAL despite the algorithmic differences.

#### 3.1 Early-stopping validation is rate-preserving in nested Donsker models

The point of early-stopping validation is to fit a sequence of nested models and to stop once error on a validation set begins to increase. This "early stopping" strategy is commonly employed as a model selection heuristic that prevents having to fit larger and larger models ad infinitum [19, 20]. For example, several popular packages for gradient boosting allow the user to fit models without specifying the number of trees a-priori: given a validation dataset, the software continues adding trees until validation loss begins to increase. More generally this can be done in an ad-hoc fashion: a user might manually expand the upper/lower bound value of a hyperparameter during grid search model selection if it looks like a minimum has not been reached. Often these hyperparameters directly correspond to moving upwards in a series of nested statistical models (e.g. increasing number or depth of trees in tree ensembles, loosening regularization in elastic net).

Our concern here is to propose a sequence of nested models that makes sense in our setting and to prove that early-stopping validation over this sequence does not sacrifice HAL's desirable properties.

As a heuristic, [21] proposed a nested sequence of models for HAL that starts with one-way bases ( $h_{s,c}$  where  $D \equiv |s| = 1$ ), then adds two-way interactions ( $h_{s,c}$  where  $D \equiv |s| = 2$ ), etc. In practice, that means solving a lasso problem with  $np$  predictors, then one with  $n(p + p^2)$ , and so on until validation loss increases. The general theory we develop in what follows covers this case and proves that this algorithm retains HAL's convergence rate. However, we also propose an improved algorithm for data-adaptive basis selection to grow the statistical model which offers better fine-tuning and computational advantages. This algorithm is also covered by the theory we develop here.

Our main analytical result is that early-stopping validation of an estimator that minimizes empirical loss in a nested sequence of models embedded in a Donsker class preserves the convergence rate of that estimator in the parent Donsker class. The proof is given in the appendix and relies only on generic results from empirical process theory.

**Theorem 1** (Early-stopping validation is rate-preserving in nested Donsker models). *Consider a nested, possibly random or data-dependent, sequence of statistical models  $\mathcal{F}_1 \subset \mathcal{F}_2 \subset \dots \mathcal{F}_k \subset \dots \mathcal{F}_{K_n}$  all contained in some Donsker class  $\mathcal{F}$ . The length of the sequence  $K_n$  may be data-dependent or random but must be finite. Let  $f_{k,n} = \arg \min_{f \in \mathcal{F}_k} P_n L f$  be an empirical minimizer of  $L$  in each model, let  $\mathcal{F}_k$ ,  $f_n = \arg \min_{f \in \mathcal{F}_k} P_n L f$  be an empirical minimizer of  $L$  in the parent Donsker class  $\mathcal{F}$ , and let  $f = \arg \min_{\phi \in \mathcal{F}} P_n L \phi$  be the true, unknown minimizer. Assume that  $f_{K_n,n} = f_n$  (i.e. empirical loss minimization in  $\mathcal{F}$  is equivalent to empirical loss minimization in  $\mathcal{F}_{K_n}$ ).*

*Define the difference in validation-set error from one estimate to the next to be  $\Delta_{k,n} = \tilde{P}_n L f_{k+1,n} - \tilde{P}_n L f_{k,n}$  and choose  $k^*$  to be the smallest value  $k$  such that  $\Delta_{k,n} > \epsilon_n$  for some positive  $\epsilon_n$  that is allowed to shrink no faster than  $o(n^{-1/2})$ .*

*If  $P(Lf_n - Lf) = o_P(r_n)$  for some  $r_n \rightarrow 0$ , then  $P(Lf_{k^*,n} - Lf) = o_P(r_n)$ .*

The way the stopping point  $k^*$  is chosen means that the analyst never needs to fit past  $f_{k^*+1,n}$ . In contrast, consider the standard (cross-)validation scheme where  $k^*$  is chosen as the global minimizer of validation loss  $\tilde{P}_n L f_{k,n}$  over all  $k$  in some finite set. Existing results show that this scheme preserves the convergence rate of the fastest estimator in the ensemble, even if it grows at slower than a given rate in  $n$  [22]. The downside is that computing the global minimum means fitting  $f_{k,n}$  for all  $k$ . With early-stopping validation, we are instead satisfied with the first *local* minimum we find as we increase  $k$ . This means we don't have to fit any models past that point, saving computation and allowing us to select among massive numbers of models. This has been heuristically justified in the past by arguing that larger models will continue to overfit more and more, so we are often right in guessing that the first local minimum is also the global minimum. That is not always true in finite samples, but our result establishes that is true in an asymptotic sense.

The trade-off is that standard (cross-)validation can handle completely arbitrary estimators, whereas with early stopping the estimators must be empirical loss minimizers of a nested series of models embedded in a Donsker class. This is mitigated by the fact that we are still perfectly justified in using an outer, standard validation setup to select among a finite ensemble of arbitrary estimators, one of which happens to be the estimator selected via an inner, early-stopping validation procedure of the kind we describe here.

As we previously stated, our result covers the case where higher-order interactions are sequentially added into partial HAL models. Since the sequence  $\mathcal{F}_k$  is allowed to be random, this result also covers other even more sophisticated schemes of the kind we will discuss shortly.

Theorem 1 easily extends to a early-stopping  $V$ -fold *cross-validation* scheme where  $k^*$  is chosen based on the first local minimum of the validation error averaged over the folds  $\frac{1}{V} \sum_v \tilde{P}_n^{(v)} L f_{k,n}^{(-v)}$ . In this setting, the final estimator will typically be re-fit for  $k^*$  iterations using the full data and in general  $\mathcal{F}_{k^*}^{(v_1)} \neq \mathcal{F}_{k^*}^{(v_2)} \neq \mathcal{F}_{k^*}$  for any two validation sets  $v_1, v_2$ . This may seem unsettling, but the fact that our result uniformly covers cases where the sequence of statistical models is chosen adaptively or randomly means that we can select the number of iterations  $k^*$  without regard to the precise models and still obtain our conclusion.

An important corollary of this result (formalized as corollary 2 in the appendix) is that *nested* early stopping schemes in Donsker models are also rate-preserving. For example, consider fixing the sectional variation norm bound  $M$  and then using early stopping to find  $k^*$  for a nested sequence inside the Donsker class  $\mathcal{F}_M$ . One might be unsure that  $M$  is a large enough bound and be tempted to repeat the process with a larger  $M$  (for which  $k^*(M)$  might be different) and continue on in such a fashion until validation error increases from one  $M$  to the next. Corollary 2 establishes that this kind of model selection is asymptotically justified as long as there is some a-priori finite sequence for  $M$ .

This also covers early stopping in interaction depth  $D$  (even jointly with  $M$ ), which bears a little explanation. For this we can consider the parent Donsker class  $\mathcal{F}_{D,M} = \{f \in \mathcal{F} : f(x) = \sum_{\{|s|=D\}} f_s(x_{s_1} \dots x_{s_D})\}$  of variationally-bounded cadlag functions that only have up to  $D$ -way interactions. Since  $\mathcal{F}_{D,M} \subset \mathcal{F}_{D',M'}$  for any  $M \leq M'$ ,  $D \leq D'$ , we can invoke theorem 1 and corollary 2 to prove that an outer early-stopping validation loop in these hyperparameters is rate preserving.

It is also important to point out that  $\epsilon_n$  may be taken as a fixed constant for all  $n$  (e.g. this can be baked into the algorithm as a default setting). But having  $\epsilon_n$  be allowed to shrink with the sample size is extremely beneficial: if we were to use a fixed cutoff  $\epsilon_n = \epsilon$  and apply our early-stopping algorithm to larger and larger samples, we would expect the discovered stopping point  $k^*$  to increase because larger samples combat variance (overfitting). However, we don't want  $k^*$  to get too large in practice because that increases computational intensity. By allowing  $\epsilon_n$  to shrink with sample size, we can be more and more sensitive to increases in validation loss as  $n$  increases. That makes us more aggressive about stopping early in large samples, thus partially slowing down the rate at which  $k^*$  grows while still preserving the asymptotics. We expect users may choose  $\epsilon$  to facilitate computation, meaning that in

different problems they may use different values to keep runtimes reasonable. In other words, users will naturally choose shrinking  $\epsilon_n$ , even if they do not realize it. Allowing  $\epsilon_n$  to shrink (but not too fast) helps protect the statistical properties from this aggressive user behavior. In the appendix (corollary 1) we also cover an extension of theorem 1 that allows  $\epsilon_n$  to shrink even faster (up to  $o(r_n)$ ) if additional conditions are met.

Our theory also trivially covers any early stopping schemes that are less aggressive than checking for the first time that  $\Delta_{k,n} > \epsilon_n$ . For example, to try to get over local minima and improve empirical finite-sample performance we might stop only after  $\Delta_{k,n} > \epsilon_n$  some number of iterations in a row. Schemes of this kind are common in machine learning applications that use early stopping.

### 3.2 Expressive, adaptive basis selection in HAL is rate-preserving

Our early stopping result implies that we could iteratively build up a HAL model, adding a positive orthant base at each iteration and refitting the lasso until validation error begins to increase. However justified in theory, this naive algorithm falls apart computationally and practically because without a sensible ordering of the bases it would take a huge number of iterations before any useful fitting happens at all. Solving each lasso problem becomes an expensive operation as the number of iterations becomes large and this must now be done many times.

To solve that problem, we must therefore ensure that a) the ordering of the bases is good in the sense that training error generally falls “quickly” at first and then “slowly” thereafter and b) that “quickly” in practice means on the order of tens or hundreds of bases so that early stopping kicks in before the size of the lasso problem becomes computationally prohibitive since we have to re-solve it with each new basis added.

Our early-stopping result covers data-adaptive orderings of basis functions, so a good way to achieve (a) is to use a boosting approach: at each iteration  $k$ , choose  $h_{k+1}$  to minimize  $P_n(R - h(X))^2$  where  $R = Y - [h_1 \dots h_k](X)\beta$  is the current residual (or more generally we might minimize  $P_n L(R, h(X))$  and fit the “generalized” residual [10]). This can be done approximately using a “weak learner”, in this case some algorithm that attempts to find the positive orthant basis that best fits the residual (e.g. via recursive partitioning). However, desiderata (b) cannot be satisfied with this idea alone because only very simple functions can be fit well by linear combinations of tens or even hundreds of positive orthant bases. Each basis is simply not expressive enough to do any heavy lifting by itself and as a result the algorithm slows to a near standstill as the number of iterations increases. We therefore require relatively *strong* learners and we need to show that substituting or mixing in these strong learners in the place of the weak positive orthant bases does not compromise the convergence rate. That is the purpose of our second analytical result:

**Theorem 2** (Using bounded linear combinations of positive orthant bases in HAL is rate-preserving). *Let  $\tilde{H}_n(X)$  be a finite (possibly data-adaptive) set of basis functions and let  $\tilde{\mathcal{F}}_{M,n} = \{\tilde{H}_n(x)^\top \tilde{\beta} : \|\tilde{\beta}\|_1 \leq M\}$ . Define  $\tilde{f}_n = \arg \min_{\tilde{\mathcal{F}}_{M,n}} P_n Lf$  to be the empirical minimizer, i.e. the lasso solution given “covariates”  $\tilde{H}_n(x)$  and bound  $M$  and let  $f_n = \arg \min_{\mathcal{F}_{M,n}} P_n Lf$  be the equivalent but with positive orthant bases  $H_n(x)$  and bound  $M$ . Take  $f = \arg \min_{\mathcal{F}_M} PLf$  to be the truth.*

*Presume  $\tilde{H}_n(x)^\top = H_n(x)^\top [I, C_n]$  for some matrix  $C_n$  with  $|c_{n,ij}| < c$  uniformly in  $n$  and a maximum of  $q$  nonzero entries in each column. then, under the same mild conditions in Benkeser and van der Laan [8],  $P(L\tilde{f}_n - Lf)$  attains the same rate as  $P(Lf_n - Lf)$  up to constants that depend on  $M$ .*

The upshot of this result is that we can use HAL with much more expressive bases as long as these are constructed as bounded linear combinations of a fixed number of positive orthant bases and as long as they still include those positive orthant bases.

In particular, we can immediately extend HAL to rectangular bases  $\tilde{h}_{a,b} = 1(a \leq x < b)$  indexed by knot points  $a, b \in \mathbb{R}^p$ . Specifically, let  $\tilde{H}_n = \{h_{a_1, b_1} \dots h_{a_{\tilde{K}_n}, b_{\tilde{K}_n}}\}$  be the set of all  $\tilde{K}_n$  rectangular indicators that can be built by taking the corners  $a$  and  $b$  to be equal to any of the observed data points  $X_i$  with any number of elements replaced by  $\pm\infty$ . Each rectangular basis can be constructed with fewer than  $2^p$  positive orthant bases so our condition on  $C_n$  can be satisfied.

Now note that rectangular indicators are nothing more than the leaves of a regression tree. Any regression tree of given depth with bounded leaf values can therefore be expressed as a bounded linear combination of a fixed number of rectangular indicators. Therefore we can include arbitrary uniformly bounded regression trees in our basis set for HAL. Going even further, any GBT fit with a bounded number of trees is just a linear combination of a finite fixed number of regression trees, meaning that entire GBT fits may be included in HAL basis sets as long as we also keep all our original positive orthant

bases. Note that the depth of the regression trees used either by themselves or as part of a GBM learner correspond exactly to the maximum interaction depth  $D$  of our positive orthant bases.

### 3.3 Algorithm

In the previous sections we’ve explained why early stopping and adaptive, expressive bases are necessary to turn HAL into a computationally feasible algorithm. We presented powerful theoretical results that ensure that the HAL rate is preserved despite these changes to the algorithm in a very broad range of settings. Now we are ready to put it all together and propose a new, practical algorithm that is guaranteed by our theory to achieve HAL’s convergence rate. We call this new algorithm the *Selectively Adaptive Lasso* (SAL) because it *selectively* constructs flexible bases to add into the model on-the-fly; unlike the *Highly* Adaptive Lasso, which includes the full “kitchen sink” of bases.

When implemented, SAL is essentially a gradient-boosted tree ensemble with lasso run over it in chunks and early stopping used for model selection. This can also be understood as a gradient-boosted tree algorithm with a special kind of adaptive learning rate. As a consequence, SAL is trivial to implement with off-the-shelf software.

**Description** SAL works as follows. The user is required to specify

1. training data  $(\mathbf{X}_t, \mathbf{Y}_t)$  and validation data  $(\mathbf{X}_v, \mathbf{Y}_v)$
2. a full set of GBT hyperparameters “ $\gamma$ ” (e.g. number of trees, learning rate, tree depth, etc.)
3. the lasso regularization strength  $\lambda$
4. the number of bases desired.

We begin each iteration with the current residual  $\mathbf{R}_t$ , which for the first iteration is the vector of training outcomes  $\mathbf{Y}_t$ . We fit a GBT model  $h \leftarrow \text{GBT}(\mathbf{X}_t, \mathbf{R}_t; \gamma)$  using the specified hyperparameters  $\gamma$  and append it to the vector of bases  $H^\top \leftarrow [H^\top, h]$ . Now we compute the basis matrix  $H^\top(\mathbf{X}_t)$  for the training data by getting predictions from each basis  $h$  and concatenating them as columns. We use lasso with regularization strength  $\lambda$  to regress  $\mathbf{Y}_t$  onto  $H^\top(\mathbf{X}_t)$  and produce the current coefficients  $\beta \leftarrow \text{COEF}(\text{LASSO}(\mathbf{X}_t, \mathbf{Y}_t; \lambda))$ . Lastly, we update the residual  $\mathbf{R}_t \leftarrow \mathbf{Y}_t - H(\mathbf{X}_t)^\top \beta$  and proceed to the next iteration. After the final iteration, the vector of bases and final coefficients are returned. Predictions for new data  $\mathbf{X}$  are given by  $H(\mathbf{X})^\top \beta$ .

If a maximum number of bases is not given, early stopping may be employed to set this parameter data-adaptively. At the end of each iteration, we compute the validation set loss  $L(\mathbf{Y}_v, H(\mathbf{X}_v)^\top \beta)$ . If this loss is greater than that of the previous iteration plus some small fixed  $\epsilon$  we stop and return the set of bases and coefficients from the previous iteration. An outer early stopping loop can also be used to set the depth of each tree in the GBT fits (increasing) and the lasso regularization strength (decreasing).

Simple example python code implementing SAL can be found at [tinyurl.com/4te5wcb3](https://tinyurl.com/4te5wcb3).

When used with early stopping, this algorithm is guaranteed<sup>3</sup> by the theory presented in the previous sections to attain the HAL rate. The proof is simple: first apply theorem 2 to extend HAL to a set of bases including data-adaptively defined GBT bases and then invoke theorem 1 to justify early stopping, all while preserving the rate.

In order to ensure that theorem 1 applies,  $k$  must be tuned via early-stopping validation. If there is no applicable a-priori knowledge of  $\lambda$  or  $D$ , these parameters must be tuned with early stopping as well. Corollary 2 establishes that this can be done in a separate outer loop.

Readers who are familiar with gradient boosting should recognize SAL as a boosting algorithm. If the line of code implementing  $\beta \leftarrow \text{COEF}(\text{LASSO}(\mathbf{X}_t, \mathbf{Y}_t; \lambda))$  is replaced with  $\beta \leftarrow [1 \dots 1]^\top$  we obtain the standard GBT algorithm. Many existing GBT packages even allow the user to impose an L1 regularization rate on the leaf values of the trees, but this is always approximated in a stagewise fashion [12]. For our theory to hold the lasso solution must be recomputed exactly in each iteration.

---

<sup>3</sup>There are two minor details that were not included in the description above so as to not distract from the main ideas. These details are: 1) the trees used in the GBT implementation must be bounded (to satisfy  $c_{n,ij} \leq c$  in thm. 2) and 2) GBT bases must be alternated with not-already-included positive orthant bases (of appropriate depth  $D$ ) in each iteration (so that  $\hat{H}_n^\top = [H_n^\top \dots]$  as required by thm. 2). Condition (1) is easily satisfied by trimming the tree predictions to an arbitrarily large value. This should generally be a no-op and therefore may be practically omitted. Condition (2) is also practically a no-op because the positive orthant bases can be selected in such an order that their coefficients are 0. We recommend ignoring these details in practice, but note that a fully theory-compliant implementation should attend to them.

By running the lasso over chunks of trees (or single trees, or leaf values), we are effectively introducing a data-adaptive learning rate. For example, imagine the user specifies that the SAL bases will be GBTs with learning rate  $\eta = 0.1$  and 10 trees each. If we denote the prediction of each tree as  $b_j(x)$ , the final prediction after 2 SAL iterations would be  $\beta_1 \sum_{j=1}^{10} \eta b_j(x) + \beta_2 \sum_{j=11}^{20} \eta b_j(x)$ . If we move  $\beta_k$  into each sum, we see that the effect is to obtain a learning rate of  $\beta_1 \eta$  for the first 10 trees and a learning rate of  $\beta_2 \eta$  for the next 10, etc. Since  $\beta$  is determined based on the training data and current predictions, this effectively creates a data-adaptive learning rate that can even look back and modify the learning rate for long-past iterations if necessary. SAL thus elegantly bridges HAL and gradient-boosted trees.

Many variations of this algorithm (e.g. cross-validated early stopping) are possible and are supported by our general theory. However, our goal here is to present a canonical algorithm, support it with rigorous theory, and demonstrate practical utility. Further experimentation is certainly warranted in the future.

## 4 Demonstration

Here we demonstrate how SAL performs relative to GBT and lasso on 12 real-world regression datasets from the UCI Machine Learning Repository [23].

We randomly<sup>4</sup> split each dataset into training-validation (90%) and test sets (10%) and then further randomly split the training-validation into training (80%) and validation (20%). For each learner, we performed model selection using the training and validation data according to the model selection strategy for each learner (detailed shortly). Once optimal hyperparameters were determined we refit each learner using those hyperparameters and the full training-validation data. Finally, we calculated the test-set RMSE for each fit learner. We repeated this entire experiment 10 times<sup>5</sup> for each dataset, averaged the RMSEs across repetitions, and computed the standard deviation of the RMSEs.

For all SAL fits we used GBT bases of 100 trees with a learning rate of 0.2 (fit using the xgboost package [12]). The number of bases ( $k$ ) was determined based on early stopping using the validation data. We used an outer early-stopping loop to jointly set  $\lambda$  and the tree depth  $D$  for the GBT bases.  $\lambda$  was set to  $1e-5$  initially and divided by 10 in each iteration whereas  $D$  was set to 2 initially and incremented by 2 in each iteration. We used histogram-based trees with  $2^7$  bins and all other GBT hyperparameters left to their defaults in xgboost. Lasso solutions were provided by glmnet [15].  $\epsilon$  was set to machine floating-point precision in all early stopping loops.

For all GBT fits we again used a learning rate of 0.2. We set the number of trees with early stopping on the validation data (evaluating validation-set loss every 100 trees). Tree depth  $D$  was set using an outer early-stopping loop, once again set to 2 initially and incremented by 2 in each iteration. Again we used histogram-based trees with  $2^7$  bins and all other GBT hyperparameters left to their defaults in xgboost.

$\lambda$  in our lasso learners was tuned using the built-in cross-validation in the glmnet package using all the default options.

Our results are shown in table 1. SAL and GBT perform almost identically and in all cases are much better than lasso. The pattern is the same across the dimensions of the data  $p$  and  $n$ . All experiments ran on a MacBook Air in a single afternoon.

## 5 Discussion

We have demonstrated a regression algorithm, the Selectively Adaptive Lasso, which is massively scalable while maintaining a  $O_P(n^{-1/3}(\log n)^{2(p-1)/3})$  L2 convergence rate in nonparametric settings. The algorithm is a form of gradient tree boosting with an adaptive learning rate, which makes it trivial to implement with off-the-shelf software and fast-running. We showed that our algorithm retains the performance of standard gradient boosting on a diverse group of real-world datasets. SAL makes semi-parametric efficient estimators practically possible and theoretically justifiable in many settings.

Along the way, we proved several general results pertaining to empirical loss minimization in nested Donsker classes. These may be of independent interest for the development of future statistically-justified machine learning methods.

Our results also shed some light on why GBT is so successful by itself. The standard approach of regularizing via a small learning rate  $\eta$  precisely mimics L1 shrinkage as  $\eta \rightarrow 0$ , assuming a globally optimal tree can be fit in each iteration [24, 25, 19]. Our early-stopping result makes it clear that, at

<sup>4</sup>excepting the yearmsd dataset, which has a temporal ordering implying a fixed test set of the last 51629 rows (~10%)

<sup>5</sup>excepting the two largest datasets (yearmsd, slice) for each of which we only ran a single experiment

dataset	p	n	SAL	GBT	LASSO
yacht	6	308	$0.682 \pm 0.137$	$0.646 \pm 0.127$	$11.4 \pm 1.71$
energy	8	768	$0.325 \pm 0.0544$	$0.325 \pm 0.0529$	$2.96 \pm 0.195$
boston	13	506	$3.25 \pm 0.561$	$3.23 \pm 0.503$	$4.54 \pm 0.577$
concrete	8	1030	$3.75 \pm 0.316$	$3.68 \pm 0.35$	$10.6 \pm 0.41$
wine	11	1599	$0.623 \pm 0.0282$	$0.623 \pm 0.0304$	$0.671 \pm 0.0219$
power	4	9568	$3.08 \pm 0.134$	$3.09 \pm 0.125$	$5 \pm 0.101$
kin8nm	8	8192	$0.115 \pm 0.00333$	$0.114 \pm 0.00313$	$0.748 \pm 0.00305$
naval	17	11934	$0.000818 \pm 2.53e-05$	$0.000818 \pm 2.53e-05$	$0.00266 \pm 3.26e-05$
protein	9	45730	$1.87 \pm 0.053$	$1.87 \pm 0.048$	$4.22 \pm 0.0435$
blog	280	52397	$26.7 \pm 1.56$	$26.5 \pm 1.59$	$33.3 \pm 1.62$
slice	384	53500	$1.34 \pm \text{NaN}$	$1.33 \pm \text{NaN}$	$8.62 \pm \text{NaN}$
yearmsd	90	515345	$9.05 \pm \text{NaN}$	$9.04 \pm \text{NaN}$	$134 \pm \text{NaN}$

Table 1: Mean RMSEs ( $\pm 1.96 \times$  standard deviation of RMSEs) across repetitions for all experiments.

least asymptotically, trees can be added in a suboptimal order without compromising the rate. This helps justify the use of recursive partitioning.

Future experiments are warranted to explore variations of SAL and its performance in different settings. With minor modifications it should also be possible to extend these results to probabilistic classification for categorical outcomes. An interesting open question is whether SAL by itself (like HAL) could be an efficient plug-in estimator for certain estimands given some kind of undersmoothing [17].

## References

- [1] Trevor Hastie, Robert Tibshirani, and Jerome Friedman. 2. Overview of Supervised Learning. In *The Elements of Statistical Learning*, page 1–34. Springer New York, New York, NY, January 2009.
- [2] A W van der Vaart. *Asymptotic Statistics*. Cambridge University Press, June 2000.
- [3] A Tsiatis. Semiparametric theory and missing data, 2007.
- [4] Mark J van der Laan, M J Laan, and James M Robins. *Unified Methods for Censored Longitudinal Data and Causality*. Springer Science & Business Media, January 2003.
- [5] Charles J Stone. Optimal Global Rates of Convergence for Nonparametric Regression. *Ann. Stat.*, 10(4):1040–1053, December 1982.
- [6] James Robins, Lingling Li, Eric Tchetgen, and Aad van der Vaart. Higher order influence functions and minimax estimation of nonlinear functionals. In *Probability and Statistics: Essays in Honor of David A. Freedman*, Probability and Statistics: Essays in Honor of David A. Freedman, pages 335–421. Institute of Mathematical Statistics, Beachwood, Ohio, USA, 2008.
- [7] Billy Fang, Adityanand Guntuboyina, and Bodhisattva Sen. Multivariate extensions of isotonic regression and total variation denoising via entire monotonicity and Hardy-Krause variation. March 2019.
- [8] David Benkeser and Mark van der Laan. The highly adaptive lasso estimator. *Proc Int Conf Data Sci Adv Anal*, 2016:689–696, December 2016.
- [9] Mark van der Laan. A generally efficient targeted minimum loss based estimator based on the highly adaptive lasso. *Int. J. Biostat.*, 13(2), October 2017.
- [10] J H Friedman. Greedy function approximation: a gradient boosting machine. *Ann. Stat.*, 2001.
- [11] Casper Solheim Bojer and Jens Peder Meldgaard. Kaggle forecasting competitions: An overlooked learning opportunity. *Int. J. Forecast.*, 37(2):587–603, April 2021.

- [12] Tianqi Chen and Carlos Guestrin. XGBoost. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, New York, NY, USA, August 2016. ACM.
- [13] Aurélien F Bibaut and Mark J van der Laan. Fast rates for empirical risk minimization over càdlàg functions with bounded sectional variation norm. July 2019.
- [14] Robert Tibshirani. Regression shrinkage and selection via the lasso. *J. R. Stat. Soc. Series B Stat. Methodol.*, 58(1):267–288, 1996.
- [15] Jerome Friedman, Trevor Hastie, and Rob Tibshirani. Regularization paths for generalized linear models via coordinate descent. *J. Stat. Softw.*, 33(1):1–22, 2010.
- [16] Mark J van der Laan and Sherri Rose. Why machine learning cannot ignore maximum likelihood estimation. October 2021.
- [17] Mark J van der Laan, David Benkeser, and Weixin Cai. Efficient estimation of pathwise differentiable target parameters with the undersmoothed highly adaptive lasso. August 2019.
- [18] Peter J Bickel, Chris A J Klaassen, Ya'acov Ritov, and Jon A Wellner. *Efficient and Adaptive Estimation for Semiparametric Models*.
- [19] Ye Luo and Martin Spindler. High-Dimensional  $L_2$ Boosting: Rate of convergence. *arXiv*, 2016.
- [20] Tong Zhang and Bin Yu. Boosting with early stopping: Convergence and consistency. August 2005.
- [21] Nima Hejazi, Jeremy Coyle, and Mark van der Laan. hal9001: Scalable highly adaptive lasso regression in R. *J. Open Source Softw.*, 5(53):2526, September 2020.
- [22] Sandrine Dudoit and Mark J van der Laan. Asymptotics of cross-validated risk estimation in estimator selection and performance assessment. *Stat. Methodol.*, 2(2):131–154, 2005.
- [23] Dheeru Dua and Casey Graff. UCI machine learning repository, 2017.
- [24] Bradley Efron, Trevor Hastie, Iain Johnstone, and Robert Tibshirani. Least angle regression. *aos*, 32(2):407–499, April 2004.
- [25] Peng Zhao and Bin Yu. Boosted lasso. <https://statistics.berkeley.edu/sites/default/files/tech-reports/678.pdf>. Accessed: 2022-1-26.

## A Proof of Theorem 1

Before beginning we sketch the proof for a generic result from empirical process theory that we will use several times:

**Lemma 1.** *If  $\mathcal{F}$  is Donsker,  $(P_n - P)f_n = O_P(n^{-1/2})$  for any (possibly random) sequence  $f_n \in \mathcal{F}$ .*

*Proof.* By definition, since  $\mathcal{F}$  is Donsker,  $\sqrt{n}(P_n - P) \rightsquigarrow G$  where  $G$  is a tight Gaussian process indexed by  $\mathcal{F}$  with sample paths in  $l^\infty(\mathcal{F})$  (bounded functions from  $\mathcal{F}$  to  $\mathbb{R}$ , equipped with supremum norm). Tightness means that with high probability the sample paths of  $G$  are in a compact set and can thus be covered with a *finite* number of balls. The center of each of these balls is a bounded function since all sample paths are bounded. Therefore all functions in this high-probability set are also bounded, and moreover are bounded uniformly since the number of balls is finite.

That establishes the fact that  $\sup_{f \in \mathcal{F}} \sqrt{n}(P_n - P)f = O_P(1)$ , since for any level of probability  $\delta$  we can eventually find a high-probability set where all the contained functions are bounded. From there we get that  $(P_n - P)f \leq \sup_{f \in \mathcal{F}} (P_n - P)f = O_P(n^{-1/2})$  as desired.  $\square$

We also remind ourselves of an elementary asymptotic result:

**Lemma 2.** *Let  $U_n \in \{0, 1\}$  and assume  $P\{U_n = 1\} \rightarrow 0$ . Then  $a_n U_n \xrightarrow{P} 0$  for any  $a_n \rightarrow 0$ .*

*Proof.* By definition of convergence in probability we must show that  $P\{a_n U_n > \epsilon\} \rightarrow 0$  for any fixed  $\epsilon > 0$ . But this is clear because

$$\begin{aligned} P\{a_n U_n > \epsilon\} &= \underbrace{P\{a_n U_n > \epsilon | U_n = 0\}}_0 P\{U_n = 0\} + P\{a_n U_n > \epsilon | U_n = 1\} P\{U_n = 1\} \\ &\leq P\{U_n = 1\} \rightarrow 0 \end{aligned}$$

□

We can now proceed to our proof of theorem 1.

**Theorem 1** (Early-stopping validation is rate-preserving in nested Donsker models). *Consider a nested, possibly random or data-dependent, sequence of statistical models  $\mathcal{F}_1 \subset \mathcal{F}_2 \subset \dots \mathcal{F}_k \subset \dots \mathcal{F}_{K_n}$  all contained in some Donsker class  $\mathcal{F}$ . The length of the sequence  $K_n$  may be data-dependent or random but must be finite. Let  $f_{k,n} = \arg \min_{f \in \mathcal{F}_k} P_n Lf$  be an empirical minimizer of  $L$  in each model, let  $\bar{\mathcal{F}}_k$ ,  $f_n = \arg \min_{f \in \mathcal{F}_k} P_n Lf$  be an empirical minimizer of  $L$  in the parent Donsker class  $\mathcal{F}$ , and let  $f = \arg \min_{\phi \in \mathcal{F}} P_n L\phi$  be the true, unknown minimizer. Assume that  $f_{K_n,n} = f_n$  (i.e. empirical loss minimization in  $\mathcal{F}$  is equivalent to empirical loss minimization in  $\mathcal{F}_{K_n}$ ).*

*Define the difference in validation-set error from one estimate to the next to be  $\Delta_{k,n} = \tilde{P}_n Lf_{k+1,n} - \tilde{P}_n Lf_{k,n}$  and choose  $k^*$  to be the smallest value  $k$  such that  $\Delta_{k,n} > \epsilon_n$  for some positive  $\epsilon_n$  that is allowed to shrink no faster than  $o(n^{-1/2})$ .*

*If  $P(Lf_n - Lf) = o_P(r_n)$  for some  $r_n \rightarrow 0$ , then  $P(Lf_{k^*,n} - Lf) = o_P(r_n)$ .*

*Proof.* Recall that the definition of  $k^*$  is that it is the smallest  $k$  such that  $\Delta_{k,n} > \epsilon_n$ . As such, it is a random quantity, as is  $f_{k^*,n}$  which inherits randomness from the data via both empirical loss minimization and model selection. We can separate these two sources by writing  $f_{k^*,n} = \sum_k^{K_n} 1_k(k^*) f_{k,n}$  which also gives

$$P(Lf_{k^*,n} - Lf) = \sum_k^{K_n} 1_k(k^*) P(Lf_{k,n} - Lf) \quad (5)$$

$$\leq 1(k^* = K_n) P(Lf_{K_n,n} - Lf) + 1(k^* < K_n) \max_{k < K_n} P(Lf_{k,n} - Lf) \quad (6)$$

$$= 1(k^* = K_n) \underbrace{P(Lf_n - Lf)}_{o_P(r_n)} + 1(k^* < K_n) \max_{k < K_n} P(Lf_{k,n} - Lf) \quad (7)$$

The last equality comes by our assumption that  $f_n = f_{K_n,n}$ . Note that  $1(k^* = K_n) = 1 - 1(k^* < K_n)$ . We therefore can establish the following sufficient conditions to ensure that the left-hand side is  $o_P(r_n)$ :

1.  $\max_{k < K_n} P(Lf_{k,n} - Lf) = O_P(1)$
2.  $1(k^* < K_n) = o_P(r_n)$

To establish condition (1), we'll show  $P(Lf_{k,n} - Lf) = O_P(1)$  for all  $k$  since taking the max over a finite number of variables preserves the rate. Let  $f_k = \arg \min_{f \in \mathcal{F}_k} PLf$  be the true loss minimizer in  $\mathcal{F}_k$ . Now we can expand:

$$P(Lf_{k,n} - Lf) = P(Lf_{k,n} - Lf_k) + P(Lf_k - Lf) \quad (8)$$

$$= -(P_n - P)(Lf_{k,n} - Lf_k) + \underbrace{P_n(Lf_{k,n} - Lf_k)}_{\leq 0} + P(Lf_k - Lf) \quad (9)$$

$$\leq - \underbrace{(P_n - P)(Lf_{k,n} - Lf_k)}_{O_P(n^{-1/2})} + \underbrace{P(Lf_k - Lf)}_{\text{bounded}} \quad (10)$$

$$= O_P(1) \quad (11)$$

The inequality in the second line above comes from acknowledging that  $f_{k,n}$  has a smaller empirical loss than any other  $f \in \mathcal{F}_k$  (for example  $f_k$ ) by definition. On the third line,  $(P_n - P)(Lf_{k,n} - Lf_k) = O_P(n^{-1/2})$  follows from lemma 1 because  $Lf_{k,n} - Lf_k$  is in a Donsker class because  $f_{k,n}, f_k \in \mathcal{F}_k \in \mathcal{F}$ .

As for the last term on the third line, for any given  $\mathcal{F}_k$ ,  $f_k$  is fixed so  $P(Lf_k - Lf)$  is a constant. However, we have to contend with the fact that  $\mathcal{F}_k$  is allowed to be random, so we need that  $\sup_{\mathcal{F}_k} Lf_k - Lf$  is bounded, at least stochastically. This will certainly be the case if  $\sup_{g \in \mathcal{F}} Lg - Lf$  is bounded.

Now we can proceed to show condition (2), which was that  $1(k^* < K_n) = o_P(r_n)$ . This follows from lemma 2 as long as  $P\{k^* < K_n\} \rightarrow 0$ , which, by the definition of  $k^*$  is the same as  $P\{\max_{k \leq K_n} \Delta_{k,n} > \epsilon_n\} \rightarrow 0$ . This in turn is implied by  $\epsilon_n^{-1} \max_{k \leq K_n} \Delta_{k,n} = o_P(1)$ , which would follow from knowing that  $\epsilon_n^{-1} \Delta_{k,n} = o_P(1)$  for all  $k \leq K_n$ . This is what we will prove.

Expanding from the definition of  $\Delta_{k,n}$ , we have

$$\Delta_{k,n} = \tilde{P}_n(Lf_{k+1,n} - Lf_{k,n}) \quad (12)$$

$$= -(\tilde{P}_n - P)(Lf_{k+1,n} - Lf_{k,n}) + P(Lf_{k+1,n} - Lf_{k,n}) \quad (13)$$

The first term is  $O_P(n^{-1/2})$  by lemma 1. The second term we expand to

$$P(Lf_{k+1,n} - Lf_{k,n}) = P(Lf_{k+1,n} - Lf_{k+1}) + \underbrace{P(Lf_{k+1} - Lf_k)}_{\leq 0} + P(Lf_k - Lf_{k,n}) \quad (14)$$

$$\leq |P(Lf_{k+1,n} - Lf_{k+1})| + |P(Lf_{k,n} - Lf_k)| \quad (15)$$

$$= P(Lf_{k+1,n} - Lf_{k+1}) + P(Lf_{k,n} - Lf_k) \quad (16)$$

The term  $P(Lf_{k+1} - Lf_k) \leq 0$  by the definition of  $f_k$  and the fact that  $\mathcal{F}_k \subset \mathcal{F}_{k+1}$ . In the last line we exploit the fact that  $P(Lf_{k,n} - Lf_k) > 0$  since  $f_k, f_{k,n} \in \mathcal{F}_k$  and  $f_k$  is the minimizer of the true loss. To contend with the two remaining terms, note that for arbitrary  $k$  we have

$$P(Lf_{k,n} - Lf_k) = -(P_n - P)(Lf_{k,n} - Lf_k) + \underbrace{P_n(Lf_{k,n} - Lf_k)}_{\leq 0} \quad (17)$$

$$\leq -(P_n - P)(Lf_{k,n} - Lf_k) \quad (18)$$

which by lemma 1 is  $O_P(n^{-1/2})$ . However, we can also exploit the fact that  $\mathcal{F}_k \subset F$  to get the better rate  $o_P(r_n)$ , since we know  $P(Lf_n - Lf) = o_P(r_n)$  by assumption. We'll assume without loss of generality that  $r_n$  is a rate faster than  $n^{-1/2}$ .

Therefore we have that  $\Delta_{k,n} = O_P(n^{-1/2}) + o_P(r_n)$ , which gives the rate  $O_P(n^{-1/2})$ . Thus we can afford  $\epsilon_n$  shrinking at any rate slower than  $n^{-1/2}$  and still get  $\epsilon_n^{-1} \Delta_{k,n} = o_P(1)$ . Since this is satisfied by assumption, our proof is concluded.  $\square$

**Corollary 1** (Sample-size dependent early stopping). *If  $\|f_{k+1,n} - f_{k,n}\| < \delta_n \rightarrow 0$  for all  $k$ , we can relax the presumption that  $\epsilon_n$  shrink no faster than  $o(n^{-1/2})$  and instead require that it shrinks no faster than  $O(n^{-1/2} \delta_n^{1/2})$  (presuming that is faster than  $o(n^{-1/2})$ ) and still obtain the conclusion of theorem 1. However, in no case can  $\epsilon$  shrink faster than  $o(r_n)$ .*

*Proof.* In eq. 13 we decompose  $\Delta_{k,n}$  into two terms, one of which is  $O_P(n^{-1/2})$  and the other which is  $o_P(r_n)$ . Again presuming without loss of generality that  $r_n$  is faster than  $n^{-1/2}$ , we immediately see that if the  $O_P(n^{-1/2})$  term is what is gating the speed of convergence. If we could improve that rate, then  $\Delta_{k,n}$  would converge more quickly and that would give more wiggle room for  $\epsilon_n$ . However, once that rate improves past  $o(r_n)$ , it is the other term that gates the convergence, which shows that  $o(r_n)$  is the best we can do by finding fast bounds on  $\delta_n$ .

The  $O_P(n^{-1/2})$  term in question is  $(\tilde{P}_n - P)(Lf_{k+1,n} - Lf_{k,n})$ . Using a bound based on entropy integrals, Bibaut and van der Laan [13] invoke a result that shows  $(\tilde{P}_n - P)(Lg_n - Lf_n) = O_P(n^{-1/2} \delta_n^{1/2})$  for  $g_n, f_n \in \mathcal{F}$  as long as  $\|g_n - f_n\| < \delta_n$ . The result follows immediately.  $\square$

A comment on corollary 1: The condition  $\|f_{k+1,n} - f_{k,n}\| < \delta_n \rightarrow 0$  may be difficult to show for any particular data-adaptive method of constructing the nested models  $\mathcal{F}_1 \subset \dots \mathcal{F}_{K_n}$ . However, one may have intuition that as  $n$  increases, we get  $K_n$  increasing and perhaps the difference between subsequent models becomes smaller and smaller such that the distance between empirical loss minimizers in adjacent models decreases. Alternatively, one might presume that the ordering of the models is good enough that most of the ‘‘fitting’’ happens early on (i.e. validation error decreases sharply and then tapers off), in which case the required condition would hold for  $k$  greater than some  $k_0$ , perhaps.

In any case, the implication is that for sensibly constructed adaptive sequences we may be able to tolerate being slightly more sensitive to increases in validation error in larger and larger samples.

**Corollary 2** (Nested early-stopping validation). *Consider the setting of theorem 1, but replace  $\mathcal{F}$  with a Donsker class  $\mathcal{G}_m$  nested in a finite sequence of Donsker classes  $\mathcal{G}_1 \dots \mathcal{G}_m \dots \mathcal{G}_M$  with  $f \in \mathcal{G}_M$ . We must thus replace  $\mathcal{F}_k$  with  $\mathcal{F}_{k,m}$  and  $k^*$  becomes  $k^*(m)$ .*

*Define the difference in validation-set error from one estimate to the next to be  $\Delta_{m,n} = \tilde{P}_n Lf_{k^*(m+1),n} - \tilde{P}_n Lf_{k^*(m),n}$  with  $k^*(m)$  chosen as in theorem 1. Choose  $m^*$  to be the smallest value  $m$  such that  $\Delta_{m,n} > \epsilon_n$  for some positive  $\epsilon_n$  that is allowed to shrink no faster than  $o(n^{-1/2})$ .*

*If  $P(Lf_n - Lf) = o_P(r_n)$  for some  $r_n \rightarrow 0$ , then  $P(Lf_{k^*(m^*),n} - Lf) = o_P(r_n)$ .*

*Proof.* □

Follow the outline of theorem 1 exactly, substituting  $f_{k^*(m^*),n}^m$  for  $f_{k^*,n}$  and  $f_{K_n}^m$  for  $f_k$ . Whenever the term  $P(Lf_{k^*(m),n}^m - Lf_{K_n}^m)$  arises invoke thm. 2 to prove it is  $o_P(r_n)$  and the result follows.

## B Proof of Theorem 2

**Theorem 2** (Using bounded linear combinations of positive orthant bases in HAL is rate-preserving). *Let  $\tilde{H}_n(X)$  be a finite (possibly data-adaptive) set of basis functions and let  $\tilde{\mathcal{F}}_{M,n} = \{\tilde{H}_n(x)^\top \tilde{\beta} : \|\tilde{\beta}\|_1 \leq M\}$ . Define  $\tilde{f}_n = \arg \min_{\tilde{\mathcal{F}}_{M,n}} P_n Lf$  to be the empirical minimizer, i.e. the lasso solution given ‘‘covariates’’  $\tilde{H}_n(x)$  and bound  $M$  and let  $f_n = \arg \min_{\mathcal{F}_{M,n}} P_n Lf$  be the equivalent but with positive orthant bases  $H_n(x)$  and bound  $M$ . Take  $f = \arg \min_{\mathcal{F}_M} P Lf$  to be the truth.*

*Presume  $\tilde{H}_n(x)^\top = H_n(x)^\top [I, C_n]$  for some matrix  $C_n$  with  $|c_{n,ij}| < c$  uniformly in  $n$  and a maximum of  $q$  nonzero entries in each column. then, under the same mild conditions in Benkeser and van der Laan [8],  $P(L\tilde{f}_n - Lf)$  attains the same rate as  $P(Lf_n - Lf)$  up to constants that depend on  $M$ .*

*Proof.* Our proof follows the arguments in Benkeser and van der Laan [8] that establish the  $P(Lf_n - Lf) = O_p(n^{-1/2})$  rate for HAL. Specifically,

$$P(L\tilde{f}_n - Lf) = -(P_n - P)(L\tilde{f}_n - Lf) + P_n(L\tilde{f}_n - Lf) \quad (19)$$

If  $P_n L\tilde{f}_n \leq P_n Lf$  then the expression above is bounded by just the first term on the right-hand side. If  $\tilde{f}_n$  is guaranteed to fall in a Donsker class, that term is  $O_P(n^{-1/2})$  by lemma 1 and Donsker-preserving transformations and we are done. These two hypotheses are what we seek to show.

Firstly, we establish that  $P_n L\tilde{f}_n \leq P_n Lf$ . We already know that  $P_n Lf_n \leq P_n Lf$  (for any  $f \in \mathcal{F}_M$ ) since  $f_n$  is the empirical minimizer in  $\mathcal{F}_{M,n}$  and that minimizer attains the same loss as minimizing in  $\mathcal{F}_M$ . So it suffices to show that  $P_n L\tilde{f}_n \leq P_n Lf_n$ . But this is clear because  $\tilde{f}_n$  is the empirical minimizer in  $\tilde{\mathcal{F}}_{M,n}$  which is strictly larger than  $\mathcal{F}_{M,n}$  because by assumption any positive orthant basis is also in our basis  $\tilde{H}_n$ . In brief:  $\mathcal{F}_{M,n} \subseteq \tilde{\mathcal{F}}_{M,n} \implies P_n L\tilde{f}_n \leq P_n Lf_n$  as required.

Now we show  $\tilde{\mathcal{F}}_{M,n}$  is Donsker uniformly in  $n$ . Our strategy is to show that  $\tilde{\mathcal{F}}_{M,n} \subseteq \mathcal{F}_{\tilde{M},n}$ , which we know is Donsker uniformly in  $\mathcal{F}_{\tilde{M}}$ . Pick  $\tilde{f} \in \tilde{\mathcal{F}}_{M,n}$ . By definition,  $\tilde{f} = \tilde{H}_n^\top \tilde{\beta} = H_n^\top C \tilde{\beta}$ . Defining  $\beta = C \tilde{\beta}$ , a little algebra shows  $\|\beta\|_1 \leq cqM$ , meaning that any  $\tilde{f} \in \tilde{\mathcal{F}}_{M,n}$  can also be expressed as an element of  $\tilde{\mathcal{F}}_{cqM}$ . Since  $c$  and  $q$  are fixed independent of  $n$ , this shows  $\tilde{\mathcal{F}}_{M,n}$  is Donsker uniformly in  $n$  as desired and inherits the convergence rate that comes from living in  $\tilde{\mathcal{F}}_{cqM}$ . □

This argument is easily generalized. If there exist  $\tilde{M}_1, \tilde{M}_2$  such that  $\mathcal{F}_{\tilde{M}_1,n} \subseteq \tilde{\mathcal{F}}_{M,n} \subseteq \mathcal{F}_{\tilde{M}_2,n}$  then HAL using the bases  $\tilde{H}_n$  attains the same rate up to constants as HAL using positive orthant bases.