

MCD : Marginal Contrastive Discrimination

Benjamin Riu

We consider the problem of conditional density estimation (**CDE**), which is a major topic of interest in the fields of statistical and machine learning. Our method, called Marginal Contrastive Discrimination, **MCD**, reformulates the conditional density function into two factors, the marginal density function of the target variable and a ratio of density functions which can be estimated through binary classification. Like noise-contrastive methods, **MCD** can leverage *state-of-the-art* supervised learning techniques to perform **CDE**, including neural networks. Our benchmark reveals that our method significantly outperforms in practice existing methods on most density models and regression datasets.

1 Introduction

We consider the problem of conditional density estimation (**CDE**), which is a major topic of interest in the fields of statistical and machine learning.

We consider a couple of random variables (X, Y) taking values in $\mathcal{X} \times \mathcal{Y}$ such that $\mathcal{X} \subseteq \mathbb{R}^p$ and $\mathcal{Y} \subseteq \mathbb{R}^k$. We assume in this article that all random variables admit a density function with respect to a dominant measure. We also assume all these densities are proper *i.e.* they integrate to 1. We denote f_X and f_Y the marginal densities of X and Y with respect to a dominant measure. Our goal is to estimate the conditional density function:

$$\begin{aligned} \mathcal{X} \times \mathcal{Y} &\longrightarrow \mathbb{R}_+ \\ (x, y) &\longmapsto f_{Y|X=x}(y) \end{aligned}$$

This problem is at the root of the majority of machine learning tasks, including supervised and unsupervised learning or generative modelling. Supervised learning techniques aims at estimating the conditional mean. Meanwhile, in the binary classification setting, these two tasks are equivalent, since $\mathbb{E}[Y|X=x] = \mathbb{P}[Y=1|X=x]$. In the regression setting where Y is a continuous variable, the conditional density is far more informative than the mean value. This is especially true when the conditional distribution is multi-modal, heteroscedastic or heavy tailed. Moreover, in many fields such as actuarial science, asset management, climatology, econometrics, medicine or astronomy, one is interested in quantities other than expectation, such as higher order moments (variance, skewness kurtosis), prediction intervals, quantile regression, outlier boundaries, etc.

Meanwhile, most unsupervised learning techniques aim to discover relationships and patterns between random variables. This corresponds to the joint density probability function estimation subtask, itself a subtask of **CDE**. Similarly, the field of generative modeling,

whose goal is to generate synthetic data by expressing the joint distribution as a product of univariate conditional distributions with respect to latent variables, can also be considered a **CDE** subtask, as realistic images or sounds correspond to the modes of the distribution.

1.1 Related work

Historically, the first attempts were based on the use of Bayes' formula (1) which transforms the **CDE** into the estimation of two density functions, thus allowing the use of techniques dedicated to density estimation.

$$f_{Y|X=x}(y) = \frac{f_{X,Y}(x,y)}{f_X(x)}, f_X(x) \neq 0 \quad (1)$$

In this article, we address the many real-world applications of supervised learning regressions where we have a one-dimensional target but a large number of features. A major flaw of reformulating a conditional density as the ratio of two densities, is that even if Y is low dimensional, we will still incur the curse of dimensionality if X is high-dimensional. Although techniques exist to alleviate the curse to some extent by leveraging sparsity or other properties of X , it would be far easier to reformulate the **CDE** so that only the estimate of the marginal density f_Y is required instead of f_X .

Nonparametric density estimation. Nonparametric estimation is a powerful tool for density estimation as it does not require any prior knowledge of the underlying density. One of the first intuitions of kernel estimators was proposed by Rosenblatt (1956) and later by Parzen (1962). Kernel estimators were then widely studied ranging from bandwidth selection (Goldenshluger and Lepski (2011)), non linear aggregation (Rigollet and Tsybakov (2006)), computational optimisation (Langrené and Warin (2020)) to the extension to conditional densities (Bertin et al. (2014)). We refer to Silverman (2017) and references therein for interested reader. A very popular and effective nonparametric method is the k -Nearest Neighbors (Fix and Hodges (1989)), but like other nonparametric methods (kernel estimators, histogram Pearson (1895),...), a main limitation is the curse of dimensionality (Nagler and Czado (2016), Scott (1991)). Silverman (2017) showed that, in a density estimation setting, the number of points n , needed to obtain equivalent results when fitting a d -dimensional random variable, grows at a rate of $n^{\frac{4}{4+d}}$. Meanwhile, the impact of dimensionality on the computational time also scales exponentially. To the best of our knowledge, the best performing method for kernel estimation, based on a divide-and-conquer algorithm (Langrené and Warin (2020)), has a complexity of $\mathcal{O}(n \log(n)^{\max(d-1,1)})$. Both of these relationships are compounded, as higher dimensionality means that exponentially more data is required and the computational time relative to the size of the dataset will also grow exponentially.

Noise Contrastive methods. Another important family of techniques for density estimation is noise-contrastive learning (Gutmann and Hyvärinen (2010)). These techniques reformulate the estimation of the density into a binary classification problem (up to a constant). It consists in introducing a known probability density $g(\cdot)$ and sampling from it a synthetic dataset. The latter is concatenated with the original dataset, then a target value Z_i is associated such that Z_i is equal to 1 if the observation comes from the original dataset and 0 otherwise. A **contrast** $q(\cdot)$, which can be, under certain conditions on g , directly related to the density of the original

observations is introduced to obtain an estimation of the density function :

$$q(x) := \mathbb{P}[Z = 1 | X = x] = \frac{f_X(x)}{f_X(x) + g(x)} \quad \text{and} \quad f_X(x) = g(x) \frac{q(x)}{1 - q(x)}. \quad (2)$$

A binary classifier is then trained to predict this target value conditionally on the associated observation.

Contrast learning has been successfully applied in the area of self-supervision learning (He et al. (2020), Jaiswal et al. (2020)), especially on computer vision tasks (Bachman et al. (2019)). Many extensions and improvements have been made, including w.r.t. the learning loss function (Khosla et al. (2021)), data augmentation techniques (Chen et al. (2020)), network architectures (He et al. (2020)) and computational efficiency (Yeh et al. (2021)). Our proposed method is partially based on this technique, with two major differences. First, our technique addresses **CDE** problem and not density estimation or self-supervised learning. Second, the distribution we choose is unknown, potentially intractable, and/or with a large set of highly dependent components, which violates the usual restrictions for performing noise contrastive density estimation but allows us to tailor the noise distribution precisely to the estimated distribution. This allows us to fit the noise distribution precisely to the estimated distribution. To the best of our knowledge, the technique closest to our method is designed to evaluate the deviation from the independence setting, *i.e.* when all random features $\{X_j\}_{j=1, \dots, p}$ are independent, in an unsupervised framework. It has been briefly described in the second edition of Tibshirani et al. (1960) (pages 495-497) where, based on the noise contrastive reformulation given above with $g(\cdot) = \prod_{j=1}^p f_{X_j}(\cdot)$. Note that g is unknown and corresponds to what we will call later the noise distribution. Nevertheless, noise samples can be generated by applying a random permutation on the feature columns of the dataset, which is sufficient to discover association rules between the X features but not to estimate the density function f_X . On the other hand, although each component of X is one-dimensional by definition, the errors made when estimating the marginal densities p will compound when estimating g , which means that the dimensionality of X is again a limiting factor.

CDE reformulation. There are other ways to reformulate the **CDE**, for example Sugiyama et al. (2010) propose a reformulation into a Least-Squares Density Ratio (**LSCond**) and Meinshausen (1960) into a quantile regression task. Still others take advantage of a reformulation of the **CDE** into a supervised learning regression task. Meanwhile, **RFCDE** (Pospisil and Lee (2018)) and **NNKCDE** (Pospisil (2020)) are techniques that adapt methods that have proven to be effective to the **CDE** task. Other methods, such as **Deepcde** (D’Isanto and Polsterer (2018)) and **FlexCode** (Izbicki and B. Lee (2017)), go further and design a surrogate regression task that can be run by an off-the-shelf supervised learning method taking advantage of many mature and well-supported open-source projects, *e.g.* scikit-learn (Pedregosa et al. (2011)), *pytorch* (Paszke et al. (2019)), *fastai* (Howard and Gugger (2020)), *keras* (Chollet and team (2022)), *tensorflow* (Martin Abadi et al. (2015)), **CatBoost** (Prokhorenkova et al. (2018)), **XGboost** (Chen and Guestrin (2016)), etc. Our method implementation also has this advantage, since it can take as arguments any class that follows the scikit-learn *init/fit/predict_proba* API, which includes our off-the-shelf **MLP** implementations, linear grid units (**GLU**, Gorishniy et al. (2021)), **ResBlock** (Gorishniy et al. (2021)) and self-normalizing networks (**SNN**, Klambauer et al. (2017)).

Neural networks and variational inference. Long before the current resurgence of interest in deep learning, there were already neural networks designed specifically to handle **CDE**, *e.g.* Bishop (1994) addressed the problem of estimating a probability density using Mixture Density Networks (**MDN**). More recently, Kernel Mixing Networks (**KMN**, Ambrogioni et al. (2017)) are networks trained to estimate a family of kernels to perform the **CDE** task. Another famous variational inference technique is Flow Normalization (**N.Flow**, Rezende and Mohamed (2016)), designed to solve the problem of finding the appropriate approximation of the posterior distribution. A common challenge with most of these methods is scalability in terms of computation resources, which our experimental benchmark confirmed. A *python* implementation of **MDN**, **KMN** and **N.Flow** is provided by the *freelunchtheorem* package (freelunchtheoremDoc (2022)), which we included in our benchmark.

1.2 Our contributions

Our method, called contrastive marginal discrimination, **MCD**, combines several characteristics of the above methods but without their respective limitations. At a basic level, **MCD** begins by reformulating the conditional density function into two factors, the marginal density function of Y and a ratio of density functions as follows

$$f_{Y|X=x}(y) = f_Y(y) \frac{f_{X,Y}(x,y)}{f_X(x)f_Y(y)}, \quad \forall (x,y) \in \mathcal{X} \times \mathcal{Y} \text{ s.t. } f_X(x) \neq 0, f_Y(y) \neq 0$$

We propose to estimate these two quantities separately. In most real applications of **CDE**, Y is univariate or low-dimensional, while X is not. In these cases, it is much easier to estimate f_Y rather than f_X and $f_{X,Y}$. In this article, we do not focus on how to choose the estimation method for f_Y or introduce new techniques to estimate f_Y . By contrast, our experimental results show that out-of-shelf kernel estimators with default parameters perform very well on both simulated density models and real datasets, as expected for univariate distributions.

The core of our method is the reformulation of the ratio of the density functions $f_{X,Y}/(f_X f_Y)$ into a contrast. In our method, the introduced noise in equation 2 always corresponds to the density function $g(\cdot) = f_X f_Y$. This is akin to the reformulation proposed by Tibshirani et al. (1960), except that we only break the relationship between the two elements of the pair (X, Y) but not between each component of X and Y : $f_{X,Y}(\cdot) = f_X(\cdot)f_Y(\cdot)\frac{q(\cdot)}{1-q(\cdot)}$. To estimate the joint density $f_{X,Y}$ it would be necessary to estimate both f_X and f_Y . But when we apply Bayes' formula (1), we divide by f_X , which disappears from the expression of $f_{Y|X}$, meaning we only need to estimate f_Y and q .

Like noise-contrastive methods, **MCD** can leverage *state-of-the-art* supervised learning techniques to perform **CDE**, especially neural networks. Our numerical experiments reveal **MCD** performances are far superior when using neural networks compared to other popular classifiers like **CatBoost**, **XGboost** or Random Forest. Our benchmark also reveals that our method significantly outperforms in practice **RFCDE**, **NNKCDE**, **MDN**, **KMN**, **N.Flow**, **Deepcde**, **FlexCode** and **LSCond** on most the density models and regression datasets included in our benchmark. Moreover, the **MCD** reformulation enables us to train the binary classifier on a contrast training set much larger than the original dataset. Evermore, **MCD** can easily take advantage of additional data. Unlabeled observations can be directly used to increase the size of the training set, without any drawbacks. Similarly, in the case where each observation is associated with more than one target value, they can all be included in the training dataset.

Our main contributions are as follows:

- We introduce a reformulation of the **CDE** problem into a contrastive learning task which combines a binary classification task and a marginal density estimation task, which are both much easier than **CDE**.
- We prove that given a training set of size n it is always possible to generate a *i.i.d.* training set of size $\lfloor \frac{n}{2} \rfloor$ corresponding to the contrast learning task. We also prove that it is always possible to generate a training set of size at most n^2 in the non *i.i.d.* case.
- We provide the corresponding construction procedures and the *python* implementation. We also provide construction procedures to leverage additional marginal data and multiple targets per observations, which can improve performances significantly.
- We produce a benchmark of 9 density models and 12 datasets. We combine our method with a large set of classifiers and neural networks architectures, and compare ourselves against a large set of **CDE** methods. Our benchmark reveals that **MCD outperforms all the existing methods on the majority of density models and datasets, sometimes by a very significant margin.**
- We provide a *python* implementation of our method compatible with any *pytorch* module or *scikit-learn* classifier, and the complete code to replicate our experiments.

The rest of this article is organised as follows: section 2 provides a theoretical background for the reformulation. Section 4 provides the implementation details and evaluates our method on density models and regression datasets, comparing results with the methods implemented in the *python* frameworks *CDEtools* Dalmasso et al. (2020), Pospisil (2022) and *freelunchtheorem* freelunchtheorem (2022), Rothfuss et al. (2019). Section 5 provides an ablation study of our method. Section 6 provides the proofs for theoretical results and the algorithms to construct the training dataset.

2 Marginal Contrastive Discrimination

2.1 Setting

In this article, we consider three frameworks corresponding to three different situation in practice.

Framework 1 [*Independent Identically Distributed Samples*]

In this most classic setting, we consider $\mathcal{D}_n^{X,Y} = \{(X_i, Y_i)\}_{i=1, \dots, n}$ a training dataset of size $n \in \mathbb{N}^*$ such that $\forall i = 1, \dots, n$, the (X_i, Y_i) are *i.i.d.* of density $f_{X,Y}$.

In practice, it is often the case that additional observations are available but without the associated target values and vice versa (Framework 2). In this article we show that it is possible to take advantage of these additional samples to increase the size of the training dataset without using any additional unsupervised learning techniques.

Framework 2 [Additional Marginal Data]

In this framework, we still consider a i.i.d. training dataset of size $n \in \mathbb{N}^*$ of density $f_{X,Y}$ denoted $\mathcal{D}_n^{X,Y} = \{(X_i, Y_i)\}_{i=1,\dots,n}$. Moreover we assume we have one or two additional datasets.

- Let $\mathcal{D}_{n_x}^X = \{\tilde{X}_i\}_{i=1,\dots,n_x}$ be i.i.d. an additional dataset of size $n_x \in \mathbb{N}$ of density f_X .
- Let $\mathcal{D}_{n_y}^Y = \{\tilde{Y}_i\}_{i=1,\dots,n_y}$ be i.i.d. an additional dataset of size $n_y \in \mathbb{N}$ of density f_Y .

We assume that $\mathcal{D}_n^{X,Y}$, $\mathcal{D}_{n_x}^X$ and $\mathcal{D}_{n_y}^Y$ are independent.

Let us introduce a last framework, the one where more than one target value is associated to the same observation. To our knowledge, the article of (Bott and Kohler (2017)) is the only attempt to deal with this case. We show in this article that our method can exploit and take advantage of these additional targets, again, without requiring an additional learning scheme. This can be the case for example in mechanics when performing fatigue analysis (Bott and Kohler (2017), Manson (1965)).

Framework 3 [Multiple Target per Sample]

Let (X, \mathbb{Y}) be a couple of random variables taking values in $\mathcal{X} \times \mathcal{Y}^m$ of density $f_{X,\mathbb{Y}}$. Let $\mathcal{D}_{n,m}^{X,\mathbb{Y}} = \{(X_i, \mathbb{Y}_i)\}_{i=1}^n$ a training dataset of size $n \in \mathbb{N}^*$ such that

- The $\{X_i\}_{i=1,\dots,n}$ are sampled such that the X_i are i.i.d. of density f_X .
- The $\{\mathbb{Y}_i\}_{i=1,\dots,n}$ are sampled such that the $\mathbb{Y}_i | X_i$ are i.i.d. of density $f_{\mathbb{Y}|X}$.

2.2 Contrast function

Our method, **MCD**, is grounded on a trivial approach based on the successive application of the Bayes' formula (1).

We reformulate the problem differently from the existing noise contrastive methods, focusing on the contrast between the joint law $f_{X,Y}$ and the marginal laws f_X and f_Y . To do this, we define (Definition 1) a new contrast $q(\cdot, \cdot)$, called the marginal contrast function.

Definition 1 [Marginal Contrast function MCF(r)]

Let $r \in (0, 1)$ be a real number. Consider (X, Y) a couple of random variables taking values in $\mathcal{X} \times \mathcal{Y}$. The Marginal Contrast Function with ratio r of the couple (X, Y) , denoted $q(\cdot, \cdot)$, is defined as:

$$\mathcal{X} \times \mathcal{Y} \longrightarrow [0, 1)$$

$$(x, y) \longmapsto q(x, y) := \frac{r f_{X,Y}(x, y)}{r f_{X,Y}(x, y) + (1 - r) f_X(x) f_Y(y)}.$$

This new contrast is motivated by the Fact 1: **CDE** is equivalent to the marginal density of Y and the marginal contrast function q . The **CDE** task is therefore reduced to the estimation of the contrast and a marginal density.

Fact 1 Let $r \in (0, 1)$ be a real number. Consider (X, Y) a couple of random variables taking values in $\mathcal{X} \times \mathcal{Y}$. For all $(x, y) \in \mathcal{X} \times \mathcal{Y}$, we have

$$f_{Y|X=x}(y) = f_Y(y) \frac{q(x, y)}{1 - q(x, y)} \frac{1 - r}{r}$$

where $q(\cdot, \cdot)$ denotes the **MCF**(r).

In the next section, we determine the conditions (Marginal Discrimination Conditions) under which the contrast function estimation can be transformed into an easy supervised learning estimation problem.

2.3 Marginal Discrimination Conditions

To transform the problem of estimating q into a problem of supervised learning, we first need to introduce a couple of random variables (W, Z) satisfying the Marginal Discrimination Condition (MDcond) of the couple (X, Y) with ratio $r \in (0, 1)$.

Definition 2 [Marginal Discrimination Condition MDcond(r)]

Let $r \in (0, 1)$ be a real number. Consider (X, Y) two random variables taking values in $\mathcal{X} \times \mathcal{Y}$. A couple of random variables (W, Z) is said to satisfy the Marginal Discrimination Condition (MDcond) of the couple (X, Y) with ratio r if

(Cd 1) The random variable Z follows a Bernoulli law of parameter r ($Z \sim \mathcal{B}(r)$).

(Cd 2) The support of W is $\mathcal{W} = \mathcal{X} \times \mathcal{Y}$.

(Cd 3) For all $(x, y) \in \mathcal{X} \times \mathcal{Y}$, we have $f_W(x, y) = r f_{X,Y}(x, y) + (1 - r) f_X(x) f_Y(y)$.

(Cd 4) For all $(x, y, z) \in \mathcal{X} \times \mathcal{Y} \times \{0; 1\}$, we have

$$f_{W|Z=z}(x, y) = \mathbb{1}_{z=1} f_{X,Y}(x, y) + \mathbb{1}_{z=0} f_X(x) f_Y(y).$$

Remark that condition (Cd 3) is satisfied if conditions (Cd 1), (Cd 2) and (Cd 4) are verified. These conditions are sufficient to characterise both the joint and marginal laws of the couple (W, Z) .

Estimation of the contrast function through supervised learning The Proposition 1 specifies how the marginal contrast function q problem can be estimated by a supervised learning task, using either a regressor or a binary classifier, provided that we have access to a sample of identically distributed (*i.d.*) of random variables that satisfies the MDcond(r).

Proposition 1 [Contrast Estimation]

Let $r \in (0, 1)$ be a real number. Consider (X, Y) a couple of random variables taking value in $\mathcal{X} \times \mathcal{Y}$. For all $(x, y) \in \mathcal{X} \times \mathcal{Y}$, the Marginal Contrast Function of couple (X, Y) with ratio r denoted by q satisfies the following property:

$$q(x, y) = \mathbb{E}[Z | W = (x, y)] = \mathbb{P}[Z = 1 | W = (x, y)].$$

The proof is given in section 6.2. It remains to prove that it is possible to construct a training set of identically distributed (*i.d.*) samples of (W, Z) using the elements of the original dataset.

3 Contrast datasets construction

3.1 Classical Dataset (Framework 1)

Theorem 1 establishes the existence of an *i.i.d.* sample of (W, Z) satisfying the $\text{MDcond}(r)$ in Framework 1. In its proof (section 6.3), such of construction based on the original data set is derived. From now and for all $\alpha \in \mathbb{R}$, the quantity $\lfloor \alpha \rfloor$ denote the largest integer value smaller or equal to α .

Theorem 1 [Construction of an *i.i.d.* training Set]

Let $r \in (0, 1)$ be a real number. Consider the dataset $\mathcal{D}_n^{X,Y}$ defined in Framework 1.

Then, we can construct a dataset $\mathcal{D}_N^{W,Z} = \{(W_i, Z_i)\}_{i=1, \dots, N}$ of size $N = \lfloor n/2 \rfloor$ of *i.i.d.* observations satisfying the $\text{MDcond}(r)$.

Note that, in practice, having access to a larger data set improves the results considerably. By dispensing with the independence property, it is possible to construct a much larger data set without deteriorating the results (see numerical experiments). This is the purpose of Theorem 2

Theorem 2 [Construction of a larger *i.d.* training Set]

Consider the dataset $\mathcal{D}_n^{X,Y}$ defined in Framework 1. Moreover, assume that $\mathcal{D}_n^{X,Y}$ is such that $\forall (i, j) \in \{1, \dots, n\}^2$ with $i \neq j$

$$X_i \neq X_j \text{ and } Y_i \neq Y_j$$

Then, for any couple of integers (n_J, n_M) such that

$$\begin{cases} 1 \leq n_J \leq n \\ 1 \leq n_M \leq n(n-1) \end{cases}$$

we can construct a dataset $\mathcal{D}_N^{W,Z} = \{(W_i, Z_i)\}_{i=1, \dots, N}$ of size $N = n_J + n_M$ of *i.d.* random observations satisfying the $\text{MDcond}\left(\frac{n_J}{N}\right)$.

Note first that we can at most construct a dataset of size $N = n^2$, with $r = \frac{1}{n}$. On the other hand, if we want to have $r = \frac{1}{2}$, we can generate a dataset of size $N = 2n$. Second, the additional conditions on the dataset are introduced to exclude the trivial case where a larger dataset is constructed by simply repeating the existing samples. In practice, we can always avoid this case by removing redundant samples. Note, however, that the repetition of values occurs with probability 0, almost surely, because we consider continuous densities. Finally, the complete construction of such a dataset is described in section 6.4

3.2 Additional Marginal Data (Framework 2)

Now consider that we have additional features and/or targets for which the target or associated feature is not available. We include this additional data in our training process without using a semi-supervised scheme.

Theorem 3 [Construction of an i.i.d. training set]

Let $r \in (0, 1)$ be a real number. Consider the datasets defined in Framework 2. Set

$$N = \min\left(n, \left\lfloor \frac{n + n_x + n_y}{2} \right\rfloor\right),$$

then, we can construct $\mathcal{D}_N^{W,Z} = \{(W_i, Z_i)\}_{i=1, \dots, N}$ a dataset of size N of i.i.d. observations satisfying the $MDcond(r)$.

This theorem implies that as soon as we have $n_x + n_y \geq n$, we can generate a training set for the discriminator as large as the original set, i.e. $N = n$. In practice, this can happen in many cases. For example, when data annotation is expensive or difficult, we often have $n_x \gg n$. At the same time, to use contrastive marginal discrimination to estimate the conditional density, we need to know or estimate the marginal density f_Y . The proof of this theorem is done in section 6.5

Theorem 4 [Construction of a larger i.d. training set]

Consider the dataset defined in Framework 3. Moreover assume

- The dataset $\mathcal{D}_n^{X,Y}$ is such that $\forall (i, j) \in \{1, \dots, n\}^2$ s.t. $i \neq j$

$$X_i \neq X_j \text{ and } Y_i \neq Y_j.$$

- The datasets $\mathcal{D}_{n_x}^X$ and $\mathcal{D}_{n_y}^Y$ are s.t. $\forall (i, j) \in \{1, \dots, n_x\}^2$ and $\forall (i', j') \in \{1, \dots, n_y\}^2$

$$\tilde{X}_i \neq \tilde{X}_j \text{ and } \tilde{Y}_{i'} \neq \tilde{Y}_{j'}$$

- Moreover, we assume that $\mathcal{D}_n^{X,Y}$, $\mathcal{D}_{n_x}^X$ and $\mathcal{D}_{n_y}^Y$ are such that $\forall (i, i') \in \{1, \dots, n\} \times \{1, \dots, n_x\}$ and $\forall (j, j') \in \{1, \dots, n\} \times \{1, \dots, n_y\}$

$$X_i \neq \tilde{X}_{i'} \text{ and } Y_j \neq \tilde{Y}_{j'}$$

Then, for any couple of integers (n_J, n_M) such that

$$\begin{cases} 1 \leq n_J \leq n \\ 1 \leq n_M \leq (n + n_x)(n + n_y) - n \end{cases}$$

we can a dataset $\mathcal{D}_N^{W,Z} = \{(W_i, Z_i)\}_{i=1, \dots, N}$ of size $N = n_J + n_M$ of i.d. random observations satisfying the $MDcond(\frac{n_J}{N})$.

Here again, it is possible to build a much larger i.d. training dataset under some weak assumption. Indeed, the repetition of values occurs with probability 0, almost surely. The complete construction of such a dataset is described in section 6.6

3.2.1 Multiple targets per observations (Framework 3)

In Framework 3, to each of the n observations X_i , there exists a m -associated target $\mathbb{Y}_i = (Y_{i,1}, \dots, Y_{i,m})$ of i.i.d. components such that the $(Y_{i,j} | X_i)_{j=1, \dots, m}$ are i.i.d.. In this setting, it is still possible to construct, under some weak assumption, a larger i.d. training set satisfying the MDcond. Recall, the repetition of values occurs with probability 0,

almost surely. Note that we can construct, at most, a data set of size $n^2 \times m$, with $r = \frac{1}{n}$. On the other hand, if we want to have a ratio of $r = \frac{1}{2}$, the generated dataset will be of size $2n \times m$.

Theorem 5 [Construction of a larger i.d. training set]

Consider the dataset $\mathcal{D}_{n,m}^{X,Y} = \{(X_i, Y_i)\}_{i=1}^n$ a training dataset of size $n \in \mathbb{N}^*$ defined in Framework 3. Assume that

- For all $(i, i') \in \{1, \dots, n\}^2$ such that $i \neq i'$

$$X_i \neq X_{i'}.$$

- For all $(i, j), (i', j') \in \{1, \dots, n\} \times \{1, \dots, m\}$ such that $i \neq i'$ or $j \neq j'$

$$Y_{i,j} \neq Y_{i',j'}$$

Then, for any couple of integers (n_J, n_M) such that

$$\begin{cases} 1 \leq n_J \leq n \times m \\ 1 \leq n_M \leq n(n-1) \times m \end{cases}$$

we can construct a dataset $\mathcal{D}_N^{W,Z} = \{(W_i, Z_i)\}_{i=1, \dots, N}$ of size $N = n_J + n_M$ of i.d. random observations satisfying the MDcond $\left(\frac{n_J}{N}\right)$.

The complete construction of such a dataset is described in section 6.7

4 Experiments

In this section we detail the implementation of **MCD** in section 4.1 and provide a benchmark to compare **MCD** to other available methods. All our experiments are done in *python* and the random seed is always set such that the results of our method are fully reproducible.

We compare our method **MCD** with other well-known methods presented in section 4.2 on both density models including two new ones, described in section 4.3 and real dataset. Our results are displayed in sections 4.4 and 4.5.

4.1 Method implementation

Training. First describe the procedure used for both parametric and nonparametric estimation, to train our estimator **MCD** on dataset corresponding respectively to Framework 1, 2 or 3. Table 4.1 details which Construction to use in each Framework.

Training | (Step₁). Set r .
 (Step₂). Estimate f_Y using $\{Y_i\}_{i=1, \dots, n}$ from $\mathcal{D}_n^{X,Y}$.
 (Step₃). Generate $\mathcal{D}_N^{W,Z}$.
 (Step₄). Train either a regressor or a binary classifier on $\mathcal{D}_N^{W,Z}$.

The estimators obtained in steps 2 and 4 are called respectively the **marginal estimator** \widehat{f}_Y and the **discriminator** \widetilde{q} . Note that for any $(x, y) \in \mathcal{X} \times \mathcal{Y}$, we have $\widetilde{q}(x, y) \in [0, 1]$ while $q(x, y) \in [0, 1)$. To obtain an appropriate prediction, we introduce a thresholding constant $\epsilon = 10^{-6}$ and set

$$\widehat{q}(x, y) = \min(\widetilde{q}(x, y), 1 - \epsilon) \in [0, 1 - \epsilon] \subset [0, 1).$$

Framework	Available datasets	<i>i.i.d.</i> samples	<i>i.d.</i> samples
Framework 1	$\mathcal{D}_n^{X,Y}$	Construction 1	Construction 2
Framework 2	$\mathcal{D}_n^{X,Y}, \mathcal{D}_{n_x}^X, \mathcal{D}_{n_y}^Y$	Construction 3	Construction 4
Framework 3	$\mathcal{D}_{n,m}^{X,Y}$	Not applicable	Construction 5

Table 1: Look-up table to determine the appropriate construction corresponding to each framework.

Next, underline that **MCD** can be used to perform two different tasks:

- Nonparametric estimation of the conditional density $f_{Y|X=x}(\cdot)$ for all $x \in \mathcal{X}$.
- Pointwise estimation of the conditional density $f_{Y|X=x}(y)$ for any $(x, y) \in \mathcal{X} \times \mathcal{Y}$.

Indeed, using Fact 1 we have: $\forall (x, y) \in \mathcal{X} \times \mathcal{Y}$,

$$\widehat{f}_{Y|X=x}(y) = \widehat{f}_Y(y) \frac{\widehat{q}(x, y)}{1 - \widehat{q}(x, y)} \frac{1 - r}{r}. \quad (3)$$

This implies that it is sufficient to have estimators of both f_Y and q to have a point estimate of $f_{Y|X=x}(y)$. We may also deduce the literal expression of $\widehat{f}_{Y|X=x}(\cdot)$, the nonparametric estimate of the conditional density, provided we know the literal expressions of $\widehat{q}(x, \cdot)$ and $\widehat{f}_Y(\cdot)$. It is the case for \widehat{q} in Deep Learning, as we can write the literal expression of $\widehat{q}(x, \cdot)$ from the **NN** parameters learned in the learning step and a value x . Under certain assumptions on \widehat{q} , $\widehat{f}_{Y|X=x}(\cdot)$ is a true density (Gutmann and Hyvärinen (2010)).

Prediction. For parametric pointwise estimation, at test time, given any new observation $x \in \mathcal{X}$, for any chosen target value $y \in \mathcal{Y}$, we can estimate $f_{Y|X=x}(y)$ the value of the probability density function evaluated on (x, y) :

Prediction | (Step₁). Evaluate $\widehat{q}(x, y)$.
| (Step₂). Apply thresholding: $\widehat{q}(x, y) = \min(\widehat{q}(x, y), 1 - \epsilon)$.
| (Step₃). Evaluate $\widehat{f}_Y(y)$.
| (Step₄). Plug in $f_{Y|X=x}(y)$ by applying equation 3 given above.

Remark that if the discriminator is a classifier, the predicted value should be the probability of class 1, *i.e.* $\mathbb{P}[Z = 1 | W = (x, y)]$.

Choice of parameters. There are 4 major choices to make when implementing our method: the marginal density estimator method, the discriminator method, the construction and the contrast ratio r .

- **Marginal density estimator.** Since the point of our method is to provide an estimation of the conditional density in cases where the marginal density is relatively easy to estimate (meaning $\mathcal{Y} \subseteq \mathbb{R}$), we pick a simple yet effective technique, the univariate kernel density estimation *KDEUnivariate* provided in the *statsmodels* package. We always keep the default parameters, *i.e.* gaussian kernels, bandwidth set using the normal reference, and the fast Fourier transform algorithm to fit the kernels.

Neural Networks architectures	Other supervised learning classifiers
MultiLayerPerceptron (MLP)	Random Forests (RF)
MLP w/o Drop-Out nor Batch-Norm (MLP:no-D.O.)	Elastic-net
ResNet (ResBlock) Gorishniy et al. (2021)	XGboost Chen and Guestrin (2016)
Gated Linear Unit (GLU) Gorishniy et al. (2021)	CatBoost Prokhorenkova et al. (2018)
Self Normalizing Networks (SNN) Klambauer et al. (2017)	LGBM Ke et al. (2017))

Table 2: List of discriminator methods evaluated with **MCD**.

- **Marginal contrast discriminator.** We evaluate the performance of **MCD** combined with Neural Networks, Decision Tree based classifiers and Logistic Elastic-net (see table 4.1 for the exhaustive list).
- **Dataset construction and ratio:** We compare in our ablation study (Section 5) the Constructions 1, 2, 3, 4 and 5 in Frameworks 1, 2 and 3. Following the findings of the ablation study, we use Construction 2 and set $r = 0.05$ in other experiments.

4.2 Other benchmarked methods and Application Programming Interface (API)

There is a small number of **CDE** methods for which a readily available open source implementation in *python* exists. One notable difficulty when introducing a new **CDE** package is that there is no gold standard API in *python* on top of which new packages can build upon. Most existing implementations are standalone, with their own unique syntax for common functions. We choose to include in our benchmark the methods provided by two of the most mature *python* projects, the *freelunchtheorem github* repository by *freelunchtheorem* (2022), Rothfuss et al. (2019), and a network of packages created by Dalmasso et al. (2020) and Pospisil (2022).

The *freelunchtheorem github* provides an implementation of **KMN**, **N.Flow**, **MDN** and **LSCond**. The *freelunchtheorem github* has a quite consistent API across all provided methods. Notably, *freelunchtheorem* (2022), Rothfuss et al. (2019), also provide implementations for several statistical models (**EconDensity**, **ARMAJump**, **JumpDiffusion**, **LinearGauss**, **LinearStudentT**, **SkewNormal** and **GaussianMixt**), which we include in our benchmark (see the density model section 4.3).

Meanwhile, the project of Dalmasso et al. (2020) and Pospisil (2022) is built around the *CDEtools github* repository and consists of several repository of varying maturity and ease of use corresponding to each method they implemented (**RFCDE**, **f-RFCDE**, **FlexCode**, **Deepcde** and **NNKCDE**). Notably, they also provide implementations in Java and R for some of these methods. Their implementation of **Deepcde** allows custom *pytorch* and *tensorflow* architectures to be plugged-in, which gave us the opportunity to adapt the architectures and training schemes used with **MCD** to **Deepcde**. As such, the comparison between **MCD** and **Deepcde** is done on equal ground.

In total, we include in our benchmark 10 other **CDE** methods: **NNKCDE**, **N.Flow**, **LSCond**, **MDN**, **KMN**, **Deepcde**, **RFCDE**, **f-RFCDE**, **FlexCode:NN** and **FlexCode:XGboost**.

Although it is not the main goal of this work, we provide an overhead over these two projects and our method to facilitate the comparison between them. Each evaluated

method is encapsulated in a class which inherits the same unique API from the parent class *ConditionalEstimator*, with same input and output format and global behavior. Similar to *scikit-learn*, the estimator is an instance of the class, with hyper-parameters provided during initialisation (`__init__`), and the observation matrix and target vector provided (as *numpy* arrays) when calling the *fit* function. At predict time however, the estimator prediction is a function called *pdf_from_X* which predicts the probability density function on a grid of target values. This package overhead allows us to compare all methods on equal ground: For density models all methods are trained on the same sampled training set. We also use the same grid of target values and test set of observations to evaluate the probability density function of all compared methods. Likewise, for real-world datasets, we use the same dataset train-test splits for all compared methods.

4.3 Estimation of theoretical models

We first evaluate our method on the core task it aims to handle on theoretical models: numerically estimating a conditional density function with respect to a new observation. We choose to evaluate the quality of the prediction empirically: for each predicted and target functions, we evaluate for a grid of target values the **empirical Kullback-Leibler divergence (KL)**.

Density models The *freelunchtheorem* package provides 7 conditional densities implementations for which we have a function to generate a training dataset and a function to evaluate the theoretical density function on a grid of target values given an observation. These 7 models are **EconDensity**, **ARMAJump**, **JumpDiffusion**, **LinearGauss**, **LinearStudentT**, **SkewNormal** and **GaussianMixt**. We refer to the *freelunchtheorem github* documentation [freelunchtheorem \(2022\)](#) for a detailed description of each model. Although these conditional density models cover a diverse set of cases, we do however introduce two other density models to illustrate the specific drawbacks of some benchmarked methods.

Model 1 [BasicLinear]: Let $p = 10$ and fix p coefficients $\beta = \{\beta_j\}_{j=1,\dots,p}$ drawn independently at random, such that $\forall j = 1, \dots, p, \beta_j$ is uniformly distributed over $(0, 1)$, i.e. $\beta_j \sim \mathcal{U}(0, 1)$.

Construct now our first density model

- Let $X \sim \mathcal{N}(\mathbf{0}_p, \mathbb{I}_p)$ be a gaussian vector.
- Let $Y \in \mathbb{R}$ be a random variable such that $Y = X^\top \beta + \sigma \epsilon$ where $\epsilon \sim \mathcal{N}(0, 1)$ and ϵ and X independent.

BasicLinear is a very simple linear model included to check that sophisticated methods which can estimate complex models are not outperformed in simple cases. We also add a second model, **AsymmetricLinear**, which corresponds to **BasicLinear** with a simple modification: we use asymmetric noise ($|\epsilon|$ instead of ϵ).

Model 2 [AsymmetricLinear]: Let β, X and ϵ be as in **BasicLinear 1**. In our second density model, Y is as follows:

$$Y = X^\top \beta + \sigma |\epsilon|.$$

Here, $|\cdot|$ denotes the absolute value.

//

The major difficulty is that the support of the conditional density of Y with respect to X differs from the support of the marginal density of Y (which is $\mathcal{Y} = \mathbb{R}$) and depends on the observation X .

4.4 Results on density models

Evaluation protocol. We use 9 density models (section 4.3) as ground truth, on which we evaluate the **MCD** with various discriminators and the methods presented in section 4.2. To generate $\mathcal{D}_n^{X,Y}$ for each density model, we sample $n = 100$ observations and for each observation we sample one target value using the conditional law of the density model. We train all benchmarked methods on this same dataset. Next, we sample $n_{test} = 100$ observations from the density model to generate a test set. We also generate a unique grid of 10000 target values, spread uniformly on \mathcal{Y} . For each observation of the test set, we evaluate the true conditional density function on the grid of target values. Then, for all benchmarked method, we estimate the conditional density for each observation on that same grid of target values and evaluate the empirical Kullback-Leibler (**KL**) divergence defined below.

Empirical Kullback-Leibler divergence.

Set $\delta = 10^{-6}$ a numerical stability constant. Let $x \in \mathbb{R}^p$ be an observation of the test set \mathcal{D}_{test} and $y \in \mathbb{R}$ be a point on \mathcal{G} , a grid of target values to be estimated. Then, for the evaluation of the target value $f_x(y) = \max(f_{Y|X=x}(y), \delta)$ and the predicted value $g_x(y) = \max(\widehat{f}_{Y|X=x}(y), \delta)$, we define the empirical \mathbf{KL}_δ divergence as follows:

$$\mathbf{KL} := \mathbf{KL}_\delta(f \parallel g) = \sum_{x \in \mathcal{D}_{test}} \sum_{y \in \mathcal{G}} f_x(y) \times \ln \left(\frac{f_x(y)}{g_x(y)} \right). \quad (4)$$

Benchmark results.

➤ We first combine the **MCD** method with a classic Multi Layer Perceptron (**MLP**) as discriminator and a kernel estimator as marginal density estimator, named **MCD:MLP**. Table 3 depicts the global performance in terms of empirical **KL** divergence over 9 models of **MCD:MLP** compared to 10 others methods, described in section 4.2.

- The main take away is that in 6 out of 9 cases, **MCD:MLP** outperforms all others.
- On 3 density models, **BasicLinear**, **LinearGauss** and **LinearStudentT**, the **KL** empirical divergence is less than half of the second best method. Meanwhile, on **EconDensity**, **N.Flow** and **MCD:MLP** share the first place.
- When **MCD:MLP** is outperformed, which corresponds to **JumpDiffusion** and **SkewNormal**, the best performing methods are **N.Flow** and **MDN**. Otherwise, the second best performing method is either **N.Flow** or **NNKCDE**.

➤ We also assess the performance of **MCD** combined with other popular supervised learning methods. Table 4 depicts the performance of **MCD** with various discriminators on the same benchmark of density models. The classifiers included are listed in Table 2 and described in section 4.1.

Empirical KL	MCD:MLP	NNKCDE	N:Flow	LSCond	MDN	KMIN	Deepcde	RFCDE	f-RFCDE	FlexCode:NN	FlexCode:XGboost
ARMAJump	0.573	0.929	0.196	0.408	<u>0.29</u>	0.312	1.754	0.529	0.526	1.201	2.226
AsymmetricLinear	0.158	<u>0.245</u>	0.498	0.882	<u>0.437</u>	0.338	0.666	0.324	0.328	0.359	0.483
BasicLinear	0.009	<u>0.087</u>	0.313	0.473	0.195	0.167	0.317	0.139	0.139	0.174	0.116
EconDensity	0.006	0.01	0.006	0.021	<u>0.013</u>	0.022	0.068	0.049	0.045	0.034	0.048
GaussianMixt	0.005	<u>0.008</u>	0.012	0.023	<u>0.016</u>	0.018	0.127	0.026	0.028	0.048	0.023
JumpDiffusion	1.352	<u>1.632</u>	4.481	9.371	4.576	5.568	22.45	10.45	10.45	6.347	4.363
LinearGauss	0.189	1.742	<u>0.868</u>	3.15	2.318	2.892	14.71	15.88	15.88	13.75	3.571
LinearStudentT	0.141	<u>0.301</u>	6.238	9.09	3.109	3.136	7.583	2.363	2.363	1.686	0.821
SkewNormal	0.722	0.089	<u>0.019</u>	0.1	0.014	0.036	18.94	0.551	0.551	0.636	2.255

Table 3: Evaluation of the empirical **KL** divergence of different **CDE** methods, for 9 density models with $n = 100$. **Best performance** is in bold print, second best performance is underlined. Lower values are better. Column 2 corresponds to the performance of **MCD** combined with the classic **MLP**. Columns 3 to 12 show the results of the 10 other benchmarked methods.

- In density model **ARMAJump** where **MCD:MLP** is outperformed by other methods, simply removing the Batch-Normalization and Drop-Out is sufficient to obtain the best performance.
- In density models **BasicLinear**, **EconDensity**, **GaussianMixt**, **JumpDiffusion**, **LinearGauss** and **LinearStudentT**, the results for **MCD:MLP** are very close to other **NN** architectures performances. This means that in most cases, **MCD** does not require heavy tuning to perform well.
- The best discriminator besides **NN** is always either **CatBoost** or **E.Net**.
- **NN** discriminators are outperformed by other classifiers in only one case, the **SkewNormal** density model. This corresponds to the density model included in our benchmark where all versions of **MCD** are outperformed by another method.

Empirical KL	MLP	SNN	GLU	ResBlock	no-D.O.	CatBoost	E.Net	XGboost	LGBM	RF	XRF
ARMAJump	0.573	1.047	0.731	<u>0.224</u>	0.1	0.241	1.09	0.598	0.953	2.265	4.469
AsymmetricLinear	0.158	0.05	0.05	<u>0.055</u>	0.318	0.2	0.262	0.274	0.28	0.279	0.319
BasicLinear	<u>0.009</u>	0.008	0.01	<u>0.009</u>	0.108	0.059	0.083	0.113	0.098	0.094	0.106
EconDensity	<u>0.006</u>	0.007	0.005	0.005	<u>0.006</u>	0.012	0.016	0.06	0.07	0.305	0.444
GaussianMixt	0.005	<u>0.006</u>	<u>0.006</u>	0.005	0.007	0.01	0.007	0.057	0.061	0.297	0.422
JumpDiffusion	1.352	<u>1.353</u>	1.352	1.352	1.352	1.485	1.352	5.694	5.11	10.17	19.99
LinearGauss	0.189	0.189	0.19	0.19	0.19	1.274	0.19	9.33	10.99	67.46	94.76
LinearStudentT	0.141	0.141	0.141	0.141	0.141	<u>0.236</u>	0.141	1.58	1.027	0.912	1.617
SkewNormal	0.722	0.796	0.669	0.356	0.155	0.083	0.833	0.223	<u>0.12</u>	5.036	7.289

Table 4: Evaluation of the empirical **KL** divergence of different **MCD** discriminators, for 9 density models with $n = 100$. **Best performance** is in bold print, second best performance is underlined. Lower values are better. Columns 2 to 6 correspond to the performance of **MCD** combined with **NN** architectures. Columns 7 to 12 show the results of **MCD** combined with other popular classifiers.

Impact of dimensionality.

➤ Then, we check if in cases where **MCD** outperforms all others, our method maintains its

good performances when p , the number of features, changes. Table 5 depicts the impact of the dimensionality of X on the performances of each method in **BasicLinear**, the density model where the performance gap in our benchmark between **MCD** and other methods is the largest.

- Performances decrease across the board when p increases. Although **BasicLinear** is a setting where a larger p corresponds to a higher signal to noise ratio, this is not enough to counter the curse of dimensionality.
- **MCD :MLP** outperforms all others at all ranges of p . Note that at $p = 300$, the empirical **KL** of **MCD :MLP** is equivalent to that of f_Y , the marginal density of the target value. This means that in this high-dimensional case, where **MCD :MLP** is not able to capture the link between X and Y , it does not overfit the training set, and instead takes a conservative approach.
- **NNKCDE** maintains good results across the board. Meanwhile, **MCD** combined with **CatBoost** performs almost as well as **MCD :MLP** when $p = 3$, but its relative performances are average at best when $p = 300$.

Empirical KL	MCD MLP	MCD CatBoost	NNKCDE	FlexCode XGboost	KMN	RFCDE	FlexCode NN
$p = 3$	0.008	<u>0.009</u>	*0.022*	0.093	0.067	0.037	0.094
$p = 10$	0.036	<u>0.042</u>	*0.063*	0.076	0.096	0.105	0.106
$p = 30$	0.115	0.202	<u>0.154</u>	0.196	*0.181*	0.238	0.22
$p = 100$	0.162	*0.224*	<u>0.173</u>	0.264	0.401	0.238	0.234
$p = 300$	0.244	0.308	*0.282*	0.302	0.304	0.507	<u>0.253</u>

Table 5: Evaluation of the **KL** divergence values for various feature sizes p , on the **BasicLinear** density model, with $n = 100$. **Best** performance is in bold print, second best performance is underlined, *third best* performance is between asterisks. Lower is better. Methods depicted achieve top 4 performances for at least one feature size regime.

Execution time and scalability.

➤ Next, we evaluate the scalability with respect to the size of the dataset of **MCD** combined with either **MLP** or **CatBoost**, two classifiers known to be efficient but slow. We include as reference other methods belonging to the same categories, meaning those based on supervised learning **NN** and Decision Trees respectively. We also include **NNKCDE** and the methods based on variational inference, as they perform well in our benchmark. Table 6 depicts the computation time of **MCD** and other **CDE** methods for $n = 30, 100, 300$ and 1000 , on **BasicLinear**, the density model where it is most beneficial to use **MCD** instead of another method. The reported computation times include all steps (initialization, training, prediction). For **MCD**, this includes both the time taken by the discriminator and the time taken by the estimator. Note also that for **MCD**, we use the ratio $r = 0.05$, meaning the actual training set size is 20 times larger.

- The main take away is that **MCD** mostly scales like its discriminator would in a supervised learning setting.
- Regarding methods based on supervised learning with neural networks, we compare **MCD :MLP** with **FlexCode :NN** and **Deepcde**. **FlexCode :NN** is much faster than **Deepcde** and **MCD :MLP**. When using equivalent architectures, **Deepcde** is slower than **MCD** when $n = 1000$ (which corresponds to $N = \frac{n}{r} = 20000$ for **MCD**). This can be partly explained by the fact that **Deepcde** uses a transformation of the target

which corresponds to an output layer width of 30, while **MCD** increases the input size of the network by 1, since observations and target values are concatenated.

- Regarding methods based on supervised learning with decision trees, we compare **MCD :CatBoost** with **RFCDE** and **FlexCode :XGboost**. **RFCDE** is the only method which does not leverage *GPU* acceleration, yet, it is faster than **MCD :CatBoost** and **FlexCode :XGboost**.
- Among the best performing methods in our benchmark, **NNKCDE** is by far the fastest. Meanwhile, the 3 variational inference methods included, **MDN**, **KMN** and **N.Flow**, are much slower, which is to be expected.

Category	Decision Tree Based Methods			NN based Methods			Kernel	Variational inference		
Method	RFCDE	MCD	FlexCode	FlexCode	MCD	Deeptide	NNKCDE	MDN	N.Flow	KMN
Based on:	RF	CatBoost	XGboost	NN	MLP	MLP	N.Neighbor	NN	NN	NN
$n = 30$	0.044	0.46	9.574	0.018	3.133	1.943	0.01	35.46	50.74	47.92
$n = 100$	0.149	0.369	9.57	0.017	3.149	2.11	0.022	35.45	50.72	102.7
$n = 300$	0.448	0.446	13.19	0.017	3.132	3.225	0.04	35.65	50.62	150.6
$n = 1000$	0.952	0.689	25.24	0.02	3.296	6.388	0.043	35.73	51.12	143.6

Table 6: Training Time in seconds for various training set sizes n , on the **BasicLinear** density model. Row 1 corresponds to the method category, row 2 corresponds to the benchmarked **CDE** method and row 3 corresponds to the underlying supervised learning method used. Column 1 corresponds to the training set size. Columns 2, 3 and 4 correspond to methods which leverage a supervised learning method based on Decision trees. Columns 5, 6 and 7 correspond to methods which leverage a supervised learning method based on **NN**. Column 8 corresponds to nearest neighbors kernels. Columns 9, 10 and 11 correspond to three variational inference methods.

4.5 Real-world datasets

Dataset origins and methodology.

➤ We include in our benchmark 12 datasets, taken from two sources:

- The *CDEtools* framework provides the dataset "Teddy" (see Beck et al. (2017) for a description). We follow the pre-processing used in the given packages.
- The *freelunchtheorem* framework provides 2 toy datasets, 7 datasets from the UCI (Asuncion and Newman (2007) repository, and one dataset from the kaggle platform Kaggle (2000) which includes 2 targets, for a total of 11 datasets. Here again, we follow the pre-processing used in the given package.

Evaluation protocol.

➤ For all datasets, we standardize the observations and target values, then we perform the same train-test split for all methods benchmarked (manually setting the random seed for reproductibility). Because datasets are of varying sizes and as some methods are extremely slow for large datasets, we only take a subset of observations to include in the training set, doing the split as such. Let n_{\max} be the original size of the dataset, the trainset is of size $n = \min(300, \lfloor n_{\max} \times 0.8 \rfloor)$ and the test set is of size $n_{\text{rest}} = \min(300, n_{\max} - n)$.

One challenge when benchmarking **CDE** methods is that real-world datasets almost never provide the conditional density function associated to an observation, but instead only one realisation. This means that the usual metrics for **CDE** (eg.: **KL**) cannot be evaluated on these datasets. We nonetheless evaluate our method on real-world datasets, using the negative log-likelihood metric, denoted **NLL**, to compare the estimated probability density function against the target value.

Empirical Negative Log-likelihood.

Set $\delta = 10^{-6}$ a numerical stability constant. Let $(x, y) \in \mathbb{R}^p \times \mathbb{R}$ be a sample from the test set \mathcal{D}_{test} , and $g_x(y) = \max(\widehat{f}_{Y|X=x}(y), \delta)$ be the predicted value, we define the NLL metric as follows:

$$\text{NLL} := \text{NLL}_\delta(g) = - \sum_{(x,y) \in \mathcal{D}_{test}} \ln(g_x(y)). \quad (5)$$

Results.

➤ Table 7 depicts the global performance in terms of negative log-likelihood for the 12 datasets.

- The main take away is that this time, **MCD:MLP** outperforms existing methods in 7 out of 12 cases, including the popular datasets BostonHousing and Concrete.
- On the WineRed and WineWhite datasets, **MCD** lags far behind **NNKCDE** and **FlexCode**. One possible cause is that for these two datasets, the target variable Y takes discrete values: $\mathcal{Y} = \{3, 4, 5, 6, 7, 8\}$, which does not correspond to the regression task for which **MCD** was designed.
- Besides **MCD**, the top performing methods are **NNKCDE**, **N.Flow**, **FlexCode** (both versions) and **KMN**.
- Regarding the choice of the discriminator, **MCD:MLP** is not outperforming **MCD:CatBoost** to the same extent it does on density models. The difference in negative log-likelihood between **MCD:MLP** and **MCD:CatBoost** is below 0.1 in 7 out of 12 cases.
- Besides, **MCD:CatBoost** obtains Top 2 performances in 3 of the 5 cases where **MCD:MLP** is outperformed by other methods. Notably, on the Yacht dataset where **MCD:MLP** performs poorly, **MCD:CatBoost** outperforms all others by a wide margin. This indicates that this time, **MLP** and **CatBoost** are complementary, as together they can obtain at least Top 2 performances in all cases besides the WineRed and WineWhite datasets.

Empirical NLL	MCD MLP	MCD CatBoost	NNKCDE	FlexCode NN	FlexCode XGboost	KMN	N.Flow
BostonHousing	<u>-0.64</u>	-0.59	-0.81	-1.99	-1.84	-1.22	-1.63
Concrete	-0.86	<u>-1.02</u>	-1.23	-2.26	-1.25	-2.30	-2.13
NCYTaxiDropoff:lon.	<u>-1.30</u>	-1.28	-1.68	-2.05	-2.17	-2.51	-2.85
NCYTaxiDropoff:lat.	-1.31	<u>-1.31</u>	<u>-1.44</u>	-1.67	-6.18	-2.45	-2.96
Power	-0.06	-0.36	-0.73	-1.09	-0.75	<u>-0.35</u>	-0.39
Protein	-0.09	<u>-0.42</u>	-0.77	-0.83	-1.38	-0.68	-0.54
WineRed	-0.89	-0.89	3.486	<u>1.062</u>	0.965	-0.90	-2.43
WineWhite	-1.18	-1.13	2.99	-0.73	<u>-0.63</u>	-1.7	-4.18
Yacht	0.14	0.822	-0.46	-1.23	0.144	0.025	<u>0.401</u>
teddy	-0.47	<u>-0.51</u>	-0.83	-0.83	-1.34	-0.76	-0.94
toy dataset 1	-0.99	<u>-0.47</u>	-0.63	-0.88	-1.46	-0.35	-0.71
toy dataset 2	-1.40	<u>-1.33</u>	-1.31	-1.54	-1.43	<u>-1.33</u>	-1.39

Table 7: Evaluation of the negative log-likelihood (NLL) for 12 datasets. **Best performance** is in bold print, second best performance is underlined. Higher values are better. Methods included outperform all others besides **MCD** on at least one dataset.

5 Ablation

We now present an ablation study of the impact of the construction strategy used to build $\mathcal{D}_N^{W,Z}$ and the chosen value for ratio r . We also assess the impact of additional data on performances in Framework 2 and 3. Our experiments are done on the **AsymmetricLinear** density model, which corresponds to a case where **MCD** is performing well but there is still room for improvement.

- The main take away is that in Framework 1, *i.d.*-Construction 2 is far better than *i.i.d.*-Construction 1.
- The appropriate ratio r for the *i.d.*-Construction 2 should be around 0.05, meaning $N = 20 \times n$.
- In Framework 3, as soon as two target values are associated to each observation, the *i.d.*-Construction 5 can massively improve the performances of **MCD**, which are already very good when using *i.d.*-Construction 2.

Construction strategy and ratio r

➤ Table 8 depicts the impact of the construction strategy and ratio r on the performance in terms of empirical **KL** divergence in the classical Framework 1 on the **AsymmetricLinear** density model.

- The appropriate ratio r for the *i.i.d.*-Construction 1 is 0.5 which corresponds to a balanced distribution between the two classes.
- It seems clear that the *i.d.*-Construction 2 produces much better results than the *i.i.d.*-Construction 1. For the latter, the performances are worse than those obtained with the concurrent method **NNKCDE** (see Table 3: **KL**=0.245). On the other hand, the *i.d.*-Construction 2 obtains Top 1 performances on our benchmark, by a wide margin.
- For the *i.d.*-Construction 2, it seems preferable to choose a ratio of 0.15 or 0.05, which corresponds respectively to a 6 or 20 times larger dataset. Indeed, in that case since $N = \frac{n}{r}$, we have to make a trade-off between the size of the training dataset and the imbalance between the classes.
- Following these findings, in our benchmark, we choose to use the *i.d.*-Construction 2 with a ratio of 0.05.

Construction	Ratio r	N	KL
<i>i.i.d.</i> -Construction 1	0.05	50	0.3284
	0.15	50	0.2865
	0.5	50	0.2771
	0.85	50	0.4211
<i>i.d.</i> -Construction 2	0.01	10000	0.0563
	0.015	6666	0.0546
	0.05	2000	0.0550
	0.15	666	0.0551
	0.5	200	0.0996

Table 8: Evaluation of the **KL** divergence of the **MCD:MLP** method on the **AsymmetricLinear** density model in Framework 1 with various values for ratio r , with *i.i.d.* and *i.d.* constructions. **Best** performance for each construction is in bold print.

Additional marginal data

➤ Table 9 depicts the impact on **KL** performance when using Constructions 3 and 4 (corresponding to the *i.i.d.* and *i.d.* case respectively) in Framework 2 where additional marginal data is available. We compare the respective benefit of adding only marginal observations ($n_x > 0, n_y = 0$), only marginal target values ($n_x = 0, n_y > 0$), and both marginal observation and marginal target values ($n_x > 0, n_y > 0$).

- In the *i.i.d.* case, using *i.i.d.*-Construction 3 instead of *i.i.d.*-Construction 1 produces substantial improvements in terms of performances, but not enough to outperform the *i.d.*-Construction 2. When using the *i.d.*-Construction 4 instead of the *i.d.*-Construction 2, the performance gain is smaller, but bear in mind that performances are already very satisfying at that point.
- In the *i.i.d.* case, having access to $n_y = n$ marginal target values also allows the marginal estimator to be trained on a sample size of $n_y + n = 2n$, which may explain why the performance gain is larger with marginal target values $\mathcal{D}_{n_y}^Y$ than with marginal observations $\mathcal{D}_{n_x}^X$ when using the *i.i.d.*-Constructions 3.
- Meanwhile, in the *i.d.* case, the size of the training dataset $\mathcal{D}_N^{W,Z}$ when $\max(n_x, n_y) > 0$ is at most $(n + n_x)(n + n_y) > n^2$, which allows to build an even larger data set ($N > n^2$). However, in that case, the choice of N is constrained by the choice of ratio r : $N = \frac{n}{r}$. Here the appropriate ratio is $r = 0.05$ and $n = 100$, meaning $N = 2000 \leq n^2$. As such, using Construction 4 to increase N beyond n^2 is not useful in that setting.
- The Construction 4 does, however, increase the amount of information present in the dataset $\mathcal{D}_N^{W,Z}$. Here, the performance gain is higher in the presence of marginal observations $\mathcal{D}_{n_x}^X$ than marginal target values $\mathcal{D}_{n_y}^Y$. This may be partly due to the fact that in the **AsymmetricLinear** model, $X \in \mathbb{R}^{10}$ and $Y \in \mathbb{R}$, meaning the observations contain more information than the target values.

Setting				Construction			Results	
Available datasets	n	n_x	n_y	Strategy	Construction	N	KL	
$\mathcal{D}_n^{X,Y}$	100	0	0	<i>i.i.d.</i>	Construction 1	50	0.3456	
$\mathcal{D}_n^{X,Y}, \mathcal{D}_{n_x}^X$	100	100	0		Construction 3	100	0.1204	
$\mathcal{D}_n^{X,Y}, \mathcal{D}_{n_y}^Y$	100	0	100		$r = 0.5$	Construction 3	100	0.1203
$\mathcal{D}_n^{X,Y}, \mathcal{D}_{n_x}^X, \mathcal{D}_{n_y}^Y$	100	25	25		Construction 3	75	0.2058	
$\mathcal{D}_n^{X,Y}$	100	0	0	<i>i.d.</i>	Construction 2	2000	0.0551	
$\mathcal{D}_n^{X,Y}, \mathcal{D}_{n_x}^X$	100	500	0		Construction 4	2000	0.0541	
$\mathcal{D}_n^{X,Y}, \mathcal{D}_{n_y}^Y$	100	0	500		$r = 0.05$	Construction 4	2000	0.0546
$\mathcal{D}_n^{X,Y}, \mathcal{D}_{n_x}^X, \mathcal{D}_{n_y}^Y$	100	150	150		Construction 4	2000	0.0639	

Table 9: Evaluation of the **KL** divergence values of the **MCD:MLP** method on the **AsymmetricLinear** density model in Framework 1 and 2 with various values for n, n_x and n_y , with *i.i.d.* and *i.d.* constructions. **Best** performance for *i.i.d.* and *i.d.* are in bold print.

Multiple target values per observations

➤ Table 10 compares the **KL** performances of *i.d.*-Construction 5 in Framework 3, when more than one target is associated to each observation in the dataset $\mathcal{D}_{n,m}^{X,Y}$. Here we

denote m the number of observations associated to each target. Remark that when $m = 1$, *i.d.*-Construction 5 is strictly equivalent to *i.d.*-Construction 2.

- In the presence of multiple target values per observation, *i.d.*-Construction 5 allows for unparalleled performances. This can probably be explained by the fact that the goal of the **CDE** task is to determine the relationship between X and Y beyond the conditional expectation, and thus multiple realizations for a single observation better quantify the variance.
- Besides, it seems that when $m > 1$, the appropriate ratio is higher, since the performances for $r = 0.15$ are better than with $r = 0.05$, which is not the case when $m = 1$.

Construction	m	Ratio r	N	KL
<i>i.d.</i> -Construction 2	1	0.5	200	0.0620
		<u>0.15</u>	666	0.0502
		<u>0.05</u>	2000	0.0501
<i>i.d.</i> -Construction 5	2	0.5	400	0.0520
		<u>0.15</u>	1333	0.0438
		<u>0.05</u>	4000	0.0461
<i>i.d.</i> -Construction 5	10	0.5	2000	0.0179
		<u>0.15</u>	6666	0.0167
		<u>0.05</u>	20000	0.0191

Table 10: Evaluation of the **KL** divergence values of the **MCD:MLP** method on the **AsymmetricLinear** density model in Framework 1 and 3 with various values for ratio r and m . **Best** performance is in bold print. Best performance ratio for each value of m is underlined. Column 2 corresponds to the number of target values associated to each observation.

6 Proofs and dataset constructions

6.1 Proof Fact 1

Let $(x, y) \in \mathcal{X} \times \mathcal{Y}$ be any couple of values for which we need to prove Fact 1. We have by the *Bayes's* formula:

$$\frac{f_{Y|X=x}(y)}{f_Y(y)} = \frac{f_{X,Y}(x,y)}{f_X(x)f_Y(y)}, f_X(x) > 0, f_Y(y) > 0 \quad (6)$$

Then, for any $r \in (0, 1)$:

$$\frac{f_{X,Y}(x,y)}{f_X(x)f_Y(y)} = \frac{rf_{X,Y}(x,y)}{rf_{X,Y}(x,y) + (1-r)f_X(x)f_Y(y)} \times \frac{rf_{X,Y}(x,y) + (1-r)f_X(x)f_Y(y)}{rf_X(x)f_Y(y)}$$

Let $q(x, y) := \frac{rf_{X,Y}(x,y)}{rf_{X,Y}(x,y) + (1-r)f_X(x)f_Y(y)}$ the marginal constrast function with ratio r defined on Definition 1

$$\begin{aligned} \frac{f_{X,Y}(x,y)}{f_X(x)f_Y(y)} &= q(x,y) \times \left(\frac{f_{X,Y}(x,y)}{f_X(x)f_Y(y)} + \frac{1-r}{r} \right) \\ \Leftrightarrow (1-q(x,y)) \frac{f_{X,Y}(x,y)}{f_X(x)f_Y(y)} &= q(x,y) \frac{1-r}{r} \\ \Leftrightarrow \frac{f_{Y|X=x}(y)}{f_Y(y)} &= \frac{1-r}{r} \frac{q(x,y)}{1-q(x,y)} \end{aligned}$$

The last equation is deduced using equation (6).

6.2 Proof Proposition 1

By condition **(Cd 1)** of Definition 2 we have $Z \sim \mathcal{B}(r)$, then

$$\mathbb{P}[Z = 1] = r \text{ and } f_Z(z) = p^z(1-p)^{1-z}.$$

Moreover, by condition **(Cd 3)** of Definition 2, we have $\forall(x, y) \in \mathcal{X} \times \mathcal{Y}$, $f_W(x, y) = rf_{X,Y}(x, y) + (1-r)f_X(x)f_Y(y)$. By condition **(Cd 4)** of Definition 2 we have

$$\begin{aligned} f_{W|Z=1}(x, y) &= f_{X,Y}(x, y) \\ f_{W|Z=0}(x, y) &= f_X(x)f_Y(y) \end{aligned}$$

By Definition 1 we have

$$\begin{aligned} q(x, y) &= \frac{r \times f_{X,Y}(x, y)}{rf_{X,Y}(x, y) + (1-r)f_X(x)f_Y(y)} = \frac{\mathbb{P}[Z = 1] \times f_{W|Z=1}(x, y)}{rf_{W|Z=1}(x, y) + (1-r)f_{W|Z=0}(x, y)} \\ &= \frac{\mathbb{P}[Z = 1] \times f_{W|Z=1}(x, y)}{f_W(x, y)} = \frac{\mathbb{E}_Z[\mathbb{1}_{Z=1}] \times [1 \times f_{W|Z=1}(x, y) + 0 \times f_{W|Z=0}(x, y)]}{f_W(x, y)} \\ &= \frac{\mathbb{E}_Z[\mathbb{1}_{Z=1}] \times \mathbb{E}_Z[f_{W|Z=z}(x, y)]}{f_W(x, y)} = \frac{\mathbb{E}_Z[\mathbb{1}_{Z=1}f_{W|Z=z}(x, y)]}{f_W(x, y)} = \frac{\mathbb{E}_Z[\mathbb{1}_{Z=1}f_{W,Z}(x, y, z)]}{f_W(x, y)f_Z(z)} \\ &= \mathbb{E}_Z \left[\mathbb{1}_{Z=1} \times \frac{f_{Z|W=(x,y)}(z)}{f_Z(z)} \right] = \mathbb{E}_Z \left[\mathbb{1}_{Z=1} \times \frac{\mathbb{P}[Z = z | W = (x, y)]}{\mathbb{P}[Z = z]} \right] \\ &= \mathbb{E}_Z \left[\mathbb{1}_{Z=1} \times \frac{\mathbb{P}[Z = 1 | W = (x, y)]}{\mathbb{P}[Z = 1]} \right] = \mathbb{E}_Z[\mathbb{1}_{Z=1}] \frac{\mathbb{P}[Z = 1 | W = (x, y)]}{\mathbb{P}[Z = 1]} \\ &= \mathbb{P}[Z = 1 | W = (x, y)] = \mathbb{E}[Z | W = (x, y)] \end{aligned}$$

6.3 Proof Theorem 1 and Construction in the i.i.d. case

First construct a random vector (W, Z) satisfying the MDcond(r) with $r \in (0, 1)$.

- Consider the random vector (X, Y) admitting $f_{X,Y}$ as density of probability.
- Let \tilde{Y} be a random variable independent of X and Y and of same law f_Y of Y ($\tilde{Y} \stackrel{\mathcal{D}}{=} Y$).
- Let r be a real number in $(0, 1)$ and $Z \sim \mathcal{B}(r)$.
- Set $W = (X, Y\mathbb{1}_{Z=1} + \tilde{Y}\mathbb{1}_{Z=0})$.

Then, for all $(x, y, \tilde{y}) \in \mathcal{X} \times \mathcal{Y} \times \mathcal{Y}$ we have

$$\forall z \in \{0; 1\} f_{W|Z=z}(x, y, \tilde{y}) = \begin{cases} f_{X,Y}(x, y) & \text{if } z = 1 \\ f_X(x)f_Y(\tilde{y}) & \text{if } z = 0 \end{cases}$$

Therefore, $\forall(x, y, z) \in \mathcal{X} \times \mathcal{Y} \times \{0; 1\}$, $f_{W|Z=z}(x, y) = f_{X,Y}(x, y)\mathbb{1}_{z=1} + f_X(x)f_Y(y)\mathbb{1}_{z=0}$.

Moreover, $\forall(x, y) \in \mathcal{X} \times \mathcal{Y}$

$$\begin{aligned} f_W(x, y) &= \int f_{W|Z=z}(x, y)f_Z(z) dz \\ &= f_{W|Z=1}(x, y)\mathbb{P}[Z = 1] + f_{W|Z=0}(x, y)\mathbb{P}[Z = 0] \\ &= f_{W|Z=1}(x, y)r + f_{W|Z=0}(x, y)(1-r) \\ &= rf_{X,Y}(x, y) + (1-r)f_X(x)f_Y(y). \end{aligned}$$

Therefore Z, W satisfies Definition 2. Now, consider the original n -sample $\mathcal{D}_n^{X,Y}$ and set $N = \lfloor n/2 \rfloor$. We can now construct the $\mathcal{D}_N^{W,Z}$ sample.

Construction 1 [*i.i.d.* $\mathcal{D}_N^{W,Z}$]

Consider the original n -sample $\mathcal{D}_n^{X,Y}$ and set $N = \lfloor n/2 \rfloor$. We can now construct the $\mathcal{D}_N^{W,Z}$ sample:

Step (1): | First sample N independent observations Z_1, \dots, Z_N with respect to $\mathcal{B}(r)$.

Step (2): | Next, $\forall i = 1, \dots, N$, set $W_i = (X_i, Y_i \mathbb{1}_{Z_i=1} + Y_{i+N} \mathbb{1}_{Z_i=0})$.

Since $N > 0$ and the N couples $(W_i, Z_i)_i$ are constructed from the N -*i.i.d.* quadruplets $(X_i, Y_i, Y_{i+N}, Z_i)_i$, they are *i.i.d.*.

6.4 Proof Theorem 2 and Construction in the i.d. case

Let n_J and n_M two integers such that $1 \leq n_J \leq n$ and $1 \leq n_M \leq n(n-1)$.

Construction 2 [*i.d.* $\mathcal{D}_N^{W,Z}$]

Step (1): | Construct n^2 observations $\{(\tilde{W}_i, \tilde{Z}_i)\}_{i=1, \dots, n^2}$ such that: $\forall j = 0, \dots, n-1, \forall k = 1, \dots, n$:

$$\begin{cases} \tilde{W}_{jn+k} = (X_{j+1}, Y_k) \\ \tilde{Z}_{jn+k} = \mathbb{1}_{j+1=k} \end{cases} \quad (7)$$

Note that the n^2 observations are neither independent nor identically distributed and do not satisfy yet the MDcond.

Step (2): | Split the n^2 couple of observations $\{(\tilde{W}_i, \tilde{Z}_i)\}_{i=1, \dots, n^2}$ into two:

$$\begin{cases} S_J = \{(\tilde{W}_i, \tilde{Z}_i) : \tilde{Z}_i = 1 \forall i \\ S_M = \{(\tilde{W}_i, \tilde{Z}_i) : \tilde{Z}_i = 0 \forall i. \end{cases}$$

Step (3): | Sample at random uniformly without replacement n_J observations $(\tilde{W}_i, \tilde{Z}_i)$ from S_J and denote \tilde{S}_J this n_J sample.

Note that since $\tilde{Z}_i = 1$ if and only if $j+1 = k$ in equation(7), we have

$$\forall (\tilde{W}_i, \tilde{Z}_i) \in \tilde{S}_J, \tilde{Z}_i = 1 \text{ and } f_{\tilde{W}_i | \tilde{Z}_i=1} \equiv f_{X,Y} \quad (8)$$

This means that $\tilde{W}_{j(n+1)+1} = (X_{j+1}, Y_{j+1})$.

Step (4): | Sample at random uniformly without replacement n_M observations $(\tilde{W}_i, \tilde{Z}_i)$ from S_M and denote \tilde{S}_M this n_M sample.

Note that since $\tilde{Z}_i = 0$ if and only if $j+1 \neq k$ in equation(7), we have

$$\forall (\tilde{W}_i, \tilde{Z}_i) \in \tilde{S}_M, \tilde{Z}_i = 0 \text{ and } f_{\tilde{W}_i | \tilde{Z}_i=0} \equiv f_X f_Y \quad (9)$$

This means that $\widetilde{W}_{jn+k} = (X_{j+1}, Y_k)$ (recall $X_l \perp\!\!\!\perp X_k \forall l \neq k$).

Step (5): Concatenate the samples \widetilde{S}_J and \widetilde{S}_M and shuffle uniformly to obtain a N sample $\mathcal{D}_N^{W,Z} = \mathcal{U}nif.\mathcal{S}huffle(\{\widetilde{S}_J, \widetilde{S}_M\})$.

Prove now that $\forall i = 1, \dots, N$, the couple $(W_i, Z_i) \in \mathcal{D}_N^{W,Z}$ satisfies $\text{MDcond}(\frac{\eta}{N})$.

((Cd 1)) As we shuffle uniformly the indices, we have $\forall i = 1, \dots, N$, $Z_i \in \mathcal{D}_N^{W,Z}$, $Z_i \sim \mathcal{B}(\frac{\eta}{N})$.

((Cd 2)) By **Step (1)**, it is obvious that all the W_i admit $\mathcal{X} \times \mathcal{Y}$ as support.

((Cd 4)) Let (W_i, Z_i) be any element of $\mathcal{D}_N^{W,Z}$, then by equation (8)

$$\begin{cases} f_{W_i|Z_i=1} \equiv f_{X,Y} & \text{if } Z_i = 1 \\ f_{W_i|Z_i=0} \equiv f_X f_Y & \text{if } Z_i = 0 \end{cases}$$

((Cd 3)) Moreover, it comes $f_{W_i}(x, y) = r f_{X,Y}(x, y) + (1-r) f_X f_Y$ with $r = \frac{\eta}{N}$.

6.5 Proof Theorem 3 and i.i.d. Construction in the Additional data setting

To construct $\mathcal{D}_N^{W,Z} = \{(W_i, Z_i)\}_{i=1, \dots, N}$ a training set of N *i.i.d.* observations, we concatenate 3 datasets denoted $\mathcal{D}_{|N_X}^{W,Z}$, $\mathcal{D}_{|N_Y}^{W,Z}$ and $\mathcal{D}_{|N_{X,Y}}^{W,Z}$ of respective size N_X , N_Y and $N_{X,Y}$ such that

$$\mathcal{D}_N^{W,Z} = \mathcal{D}_{|N_X}^{W,Z} \cup \mathcal{D}_{|N_Y}^{W,Z} \cup \mathcal{D}_{|N_{X,Y}}^{W,Z}$$

and $\begin{cases} N_X = \min(n, n_x), & N_Y = \min(n_y, n - N_X) \\ N_{X,Y} = \lfloor \frac{n - N_X - N_Y}{2} \rfloor, & N = N_X + N_Y + N_{X,Y} \end{cases}$

To construct these 3 preliminary datasets, we first split

$$\mathcal{D}_n^{X,Y} = \underbrace{\mathcal{D}_{|2N_{X,Y}}^{X,Y}}_{\text{the first } 2N_{X,Y} \text{ obs.}} \cup \underbrace{\mathcal{D}_{|N_Y}^{X,Y}}_{\text{the next } N_Y \text{ obs.}} \cup \underbrace{\mathcal{D}_{|N_X}^{X,Y}}_{\text{the next } N_X \text{ obs.}} \cup \underbrace{\mathcal{D}}_{\text{the rest.}}$$

We consider $\mathcal{D}_{|N_X}^X$ and $\mathcal{D}_{|N_Y}^Y$ the observations in datasets $\mathcal{D}_{n_x}^X$ and $\mathcal{D}_{n_y}^Y$ restricted to the N_X and N_Y first observations respectively.

Construction 3 [*i.i.d.* $\mathcal{D}_N^{W,Z}$ Additional data]

Step (1): **Construction of $\mathcal{D}_{|N_{X,Y}}^{W,Z}$.** If $N_{X,Y} = 0$, then $\mathcal{D}_{|N_{X,Y}}^{W,Z} = \emptyset$, otherwise we construct $\mathcal{D}_{|N_{X,Y}}^{W,Z}$ from the initial dataset $\mathcal{D}_{|N_X}^X$ as described in Construction 1.

Step (2): **Construction of $\mathcal{D}_{|N_Y}^{W,Z}$.** First note that if $N_Y = 0$, then $\mathcal{D}_{|N_Y}^{W,Z} = \emptyset$. If $N_Y \neq 0$, we proceed as follows:

(i) Sample N_Y independent observations $(Z_i)_{i=1, \dots, N_Y}$ according to a Bernoulli law of parameter $r \in (0, 1)$.

(ii) For all $i = 1, \dots, N_Y$; $\forall (X_i, Y_i) \in \mathcal{D}_{|N_Y}^{X,Y}$ and $\forall \widetilde{Y}_i \in \mathcal{D}_{|N_Y}^Y$, set

$$W_i = (X_i, Y_i \mathbb{1}_{Z_i=1} + \widetilde{Y}_i \mathbb{1}_{Z_i=0}).$$

Note that by construction, $(W_i, Z_i)_{i=1}^{N_Y}$ are *i.i.d.* and follow $f_{W,Z}$. Moreover, following the same arguments as in proof of Theorem 1, the $\{(W_i, Z_i)\}_{i=1}^{N_Y}$ satisfy the MDcond(r).

Step (3): **Construction of $\mathcal{D}_{|N_X}^{W,Z}$.**

(i) Sample N_X independent observations $(Z_i)_{i=1, \dots, N_X}$ according to a Bernoulli law of parameter $r \in (0, 1)$.

(ii) For all $i = 1, \dots, N_X$; $\forall (X_i, Y_i) \in \mathcal{D}_{|N_X}^{X,Y}$ and $\forall \tilde{X}_i \in \mathcal{D}_{|N_X}^X$, set

$$W_i = (X_i \mathbb{1}_{Z_i=1} + \tilde{X}_i \mathbb{1}_{Z_i=0}, Y_i)$$

Note that, by construction $\mathcal{D}_{|N_X}^{W,Z} = (W_i, Z_i)_{i=1}^{N_X}$ are *i.i.d.* and follow $f_{W,Z}$. Indeed, the reasoning is similar as in proof of Theorem 1. First construct a random vector (W, Z) satisfying the MDcond(r) with $r \in (0, 1)$:

- Let (X, Y) be a random variable admitting $f_{X,Y}$ as probability density function.
- Let Z be a random variable following a Bernoulli of parameter $r \in (0, 1)$.
- Let \tilde{X} be a random variable independent of (X, Y) following the law f_X .
- Set $W = (X_i \mathbb{1}_{Z_i=1} + \tilde{X}_i \mathbb{1}_{Z_i=0}, Y_i)$.

Then, $\forall (x, \tilde{x}, y) \in \mathcal{X} \times \mathcal{Y} \times \mathcal{Y}$ we have $\forall z \in \{0, 1\}$,

$$g_{W|Z=z}(x, \tilde{x}, y) = \begin{cases} f_{X,Y}(x, y) & \text{if } z = 1 \\ f_X(\tilde{x})f_Y(y) & \text{if } z = 0 \end{cases}$$

Then $\forall (x, y, z) \in \mathcal{X} \times \mathcal{Y} \times \{0, 1\}$, it comes

$$f_{W|Z=z}(x, y) = g_{W|Z=z}(x, x, y) = f_{X,Y}(x, y) \mathbb{1}_{z=1} + f_X(x)f_Y(y) \mathbb{1}_{z=0}.$$

Moreover, $\forall (x, y) \in \mathcal{X} \times \mathcal{Y}$; we have by equation (8):

$$f_W(x, y) = rf_{X,Y}(x, y) + (1-r)f_X(x)f_Y(y).$$

So (W, Z) satisfies the MDcond(r).

Step (4): **Concatenation.** Concatenate the 3 datasets $\mathcal{D}_{|N_X}^{W,Z}$, $\mathcal{D}_{|N_Y}^{W,Z}$ and $\mathcal{D}_{|N_{X,Y}}^{W,Z}$

To conclude our proof, note that :

- Since $\mathcal{D}_{|2N_{X,Y}}^{X,Y}$, $(\mathcal{D}_{|N_X}^{X,Y}, \mathcal{D}_{|N_X}^X)$ and $(\mathcal{D}_{|N_Y}^{X,Y}, \mathcal{D}_{|N_Y}^Y)$ are independent, the datasets $\mathcal{D}_{|N_X}^{W,Z}$, $\mathcal{D}_{|N_Y}^{W,Z}$ and $\mathcal{D}_{|N_{X,Y}}^{W,Z}$ are independent by construction.

- Moreover, since $\mathcal{D}_{|N_X}^{W,Z}$, $\mathcal{D}_{|N_Y}^{W,Z}$ and $\mathcal{D}_{|N_{X,Y}}^{W,Z}$ are composed by *i.i.d.* random variables following the law $f_{W,Z}$, the sample of size $N = N_{X,Y} + N_X + N_Y$,

$$\mathcal{D}_N^{W,Z} = \mathcal{D}_{|N_X}^{W,Z} \cup \mathcal{D}_{|N_Y}^{W,Z} \cup \mathcal{D}_{|N_{X,Y}}^{W,Z}$$

is composed by *i.i.d.* random variables following the law $f_{W,Z}$.

Construction of $\mathcal{D}_{|N_{X,Y}}^{W,Z}$.

If $N_{X,Y} = 0$, then $\mathcal{D}_{|N_{X,Y}}^{W,Z} = \emptyset$, otherwise we construct $\mathcal{D}_{|N_{X,Y}}^{W,Z}$ from the initial dataset $\mathcal{D}_{|N_X}^X$ as described in Construction 1 (see the proof of Theorem 1).

Construction of $\mathcal{D}_{|N_Y}^{W,Z}$.

First note that if $N_Y = 0$, then $\mathcal{D}_{|N_Y}^{W,Z} = \emptyset$. If $N_Y \neq 0$, we proceed as follows:

- (i) Sample N_Y independent observations $(Z_i)_{i=1,\dots,N_Y}$ according to a Bernoulli law of parameter $r \in (0, 1)$.
- (ii) For all $i = 1, \dots, N_Y$; $\forall (X_i, Y_i) \in \mathcal{D}_{|N_Y}^{X,Y}$ and $\forall \tilde{Y}_i \in \mathcal{D}_{|N_Y}^Y$, set

$$W_i = (X_i, Y_i \mathbb{1}_{Z_i=1} + \tilde{Y}_i \mathbb{1}_{Z_i=0}).$$

Note that by construction, $(W_i, Z_i)_{i=1}^{N_Y}$ are *i.i.d.* and follow $f_{W,Z}$. Moreover, following the same arguments as in proof of Theorem 1, the $\{(W_i, Z_i)\}_{i=1}^{N_Y}$ satisfy the MDcond(r).

Construction of $\mathcal{D}_{|N_X}^{W,Z}$.

First note that if $N_X = 0$, then $\mathcal{D}_{|N_X}^{W,Z} = \emptyset$. If $N_X \neq 0$, we consider the datasets $\mathcal{D}_{|N_X}^{X,Y}$ and $\mathcal{D}_{|N_X}^X$, and proceed as follows:

First construct a random vector (W, Z) satisfying the MDcond(r) with $r \in (0, 1)$ following a similar reasoning as in proof of Theorem 1:

- Let (X, Y) be a random variable admitting $f_{X,Y}$ as probability density function.
- Let Z be a random variable following a Bernoulli of parameter $r \in (0, 1)$.
- Let \tilde{X} be a random variable independent of (X, Y) following the law f_X .
- Set $W = (X_i \mathbb{1}_{Z_i=1} + \tilde{X}_i \mathbb{1}_{Z_i=0}, Y_i)$.

Then, $\forall (x, \tilde{x}, y) \in \mathcal{X} \times \mathcal{Y} \times \mathcal{Y}$ we have $\forall z \in \{0, 1\}$,

$$g_{W|Z=z}(x, \tilde{x}, y) = \begin{cases} f_{X,Y}(x, y) & \text{if } z = 1 \\ f_X(\tilde{x})f_Y(y) & \text{if } z = 0 \end{cases}$$

Then $\forall (x, y, z) \in \mathcal{X} \times \mathcal{Y} \times \{0, 1\}$, it comes

$$f_{W|Z=z}(x, y) = g_{W|Z=z}(x, x, y) = f_{X,Y}(x, y) \mathbb{1}_{z=1} + f_X(x)f_Y(y) \mathbb{1}_{z=0}.$$

Moreover, $\forall (x, y) \in \mathcal{X} \times \mathcal{Y}$; we have by equation (8):

$$f_W(x, y) = rf_{X,Y}(x, y) + (1-r)f_X(x)f_Y(y).$$

So (W, Z) satisfies the MDcond(r).

- (i) Sample N_X independent observations $(Z_i)_{i=1, \dots, N_X}$ according to a Bernoulli law of parameter $r \in (0, 1)$.
- (ii) For all $i = 1, \dots, N_X$; $\forall (X_i, Y_i) \in \mathcal{D}_{|N_X}^{X,Y}$ and $\forall \tilde{X}_i \in \mathcal{D}_{|N_X}^X$, set

$$W_i = (X_i \mathbb{1}_{z=1} + \tilde{X}_i \mathbb{1}_{z=0}, Y_i)$$

Note that, by construction $\mathcal{D}_{|N_X}^{W,Z} = (W_i, Z_i)_{i=1}^{N_X}$ are *i.i.d.* and follow $f_{W,Z}$.

Concatenation.

Now to conclude our proof, note that $\mathcal{D}_{|N_X}^{W,Z}$, $\mathcal{D}_{|N_Y}^{W,Z}$ and $\mathcal{D}_{|N_{X,Y}}^{W,Z}$ are independent by construction, since $\mathcal{D}_{|2N_{X,Y}}^{X,Y}$, $(\mathcal{D}_{|N_X}^{X,Y}, \mathcal{D}_{|N_X}^X)$ and $(\mathcal{D}_{|N_Y}^{X,Y}, \mathcal{D}_{|N_Y}^Y)$ are independent. Moreover, since $\mathcal{D}_{|N_X}^{W,Z}$, $\mathcal{D}_{|N_Y}^{W,Z}$ and $\mathcal{D}_{|N_{X,Y}}^{W,Z}$ samples are *i.i.d.* random variables following the law $f_{W,Z}$ we have $\mathcal{D}_N^{W,Z} = \mathcal{D}_{|N_X}^{W,Z} \cup \mathcal{D}_{|N_Y}^{W,Z} \cup \mathcal{D}_{|N_{X,Y}}^{W,Z}$ a training set of $N = N_{X,Y} + N_X + N_Y$ *i.i.d.* samples following the law $f_{W,Z}$.

6.6 Proof Theorem 4 and i.d. Construction in the Additional data setting

Let n_J and n_M two integers such that $1 \leq n_J \leq n$ and $1 \leq n_M \leq (n + n_x)(n + n_y) - n$.

Construction 4 [*i.d.* $\mathcal{D}_N^{W,Z}$ Additional data]

The construction is the same as in the proof of Theorem 2, except we replace **Step (1)** in Construction 2 with **Step (1-bis)** detailed below.

Step (1-bis):

We first generate $(n + n_x)(n + n_y)$ observations $\{(W_i, Z_i)\}_{i=1, \dots, (n+n_x)(n+n_y)}$ by concatenating 4 sets of samples denoted \mathcal{S} , $\mathcal{S}^{\tilde{X}}$, $\mathcal{S}^{\tilde{Y}}$ and $\mathcal{S}^{\tilde{X}, \tilde{Y}}$ of size n^2 , $n \times n_x$, $n \times n_y$ and $n_x \times n_y$ respectively.

(A) || Generate the set of samples \mathcal{S} exactly like in **Step (1)** of the Construction 2.

(B) || Construct the set of samples $\mathcal{S}^{\tilde{X}} = \{(W_i, Z_i)\}_{i=1, \dots, n \times n_x}$ of size $n \times n_x$ as follows: $\forall j = 0, \dots, n-1, \forall k = 1, \dots, n_x$,

$$\begin{cases} W_{jn_x+k} = (\tilde{X}_k, Y_{n^2+j+1}) \\ Z_{jn_x+k} = 0 \end{cases}$$

Since $\mathcal{D}_{n_x}^X$ and $\mathcal{D}_n^{X,Y}$ are independent and their respective elements are *i.i.d.*, we have $\forall i = 1, \dots, n^2, f_{W_i} \equiv f_X f_Y$.

(C) || Construct the set of samples $\mathcal{S}^{\tilde{Y}} = \{(W_i, Z_i)\}_{i=1, \dots, n \times n_y}$ of size $n \times n_y$ as follows: $\forall j = 0, \dots, n-1, \forall k = 1, \dots, n_y$,

$$\begin{cases} W_{jn_y+k} = (X_{j+1}, \tilde{Y}_k) \\ Z_{jn_y+k} = 0 \end{cases}$$

Since $\mathcal{D}_{n_y}^Y$ and $\mathcal{D}_n^{X,Y}$ are independent and their respective elements are *i.i.d.*, we have $\forall i = 1, \dots, n \times n_y, f_{W_i} \equiv f_X f_Y$.

$$\left(\text{D} \right) \left\| \left\| \begin{array}{l} \text{Construct the set of samples } \mathcal{S}^{\bar{X}, \bar{Y}} = \{(W_i, Z_i)\}_{i=1, \dots, n \times n_y} \text{ of size } \\ n_x \times n_y \text{ as follows: } \forall j = 0, \dots, n_x - 1, \forall k = 1, \dots, n_y, \\ \left\{ \begin{array}{l} W_{jn_y+k} = (\bar{X}_{j+1}, \bar{Y}_k) \\ Z_{jn_y+k} = 0 \end{array} \right. \end{array} \right.$$

Since $\mathcal{D}_{n_x}^X$ and $\mathcal{D}_{n_y}^Y$ are independent and their respective elements are *i.i.d.*, we have $\forall i = 1, \dots, n_x n_y, f_{W_i} \equiv f_X f_Y$.

$$\left(\text{E} \right) \left\| \left\| \text{Finally, concatenate } \mathcal{S}, \mathcal{S}^{\bar{X}}, \mathcal{S}^{\bar{Y}} \text{ and } \mathcal{S}^{\bar{X}, \bar{Y}} \text{ which ends the } \mathbf{Step} \right. \right.$$

(1-bis).

(Next-Step): Next, do **Step (2)**, **Step (3)**, **Step (4)** and **Step (5)** of the Construction 2.

Using the same arguments as in the proof of Theorem 2, $\mathcal{D}_N^{W,Z}$ satisfies the MDcond(r). Since $\forall i = n^2 + 1, \dots, (n_x + n)(n_y + n)$, we have $f_{W_i} \equiv f_X f_Y$ and $Z_i = 0$. Therefore $\forall i = 1, \dots, (n_x + n)(n_y + n), f_{W_i} \equiv f_{X,Y} \mathbb{1}_{Z_i=1} + f_X f_Y \mathbb{1}_{Z_i=0}$.

6.7 Proof Theorem 5 and Construction in the non-independent case

Let n_J and n_M two integers such that $1 \leq n_J \leq n \times m$ and $1 \leq n_M \leq n(n-1)m$. We construct the final dataset similary to Construction 2, except we replace **Step (1)** with **Step (1-ter)**:

Construction 5 [*i.d.* $\mathcal{D}_N^{W,Z}$ Framework 3]

Step (1-ter): Construct $n^2 m$ observations $\{(W_i, Z_i)\}_{i=1, \dots, n^2 m}$ such that:

$$\forall j = 0, \dots, n-1, \quad \forall k = 1, \dots, n \quad \forall l = 1, \dots, m, \\ \left\{ \begin{array}{l} W_{(jn+k)m+l} = (X_{j+1}, Y_l^k) \\ Z_{(jn+k)m+l} = \mathbb{1}_{j+1=k} \end{array} \right.$$

(Next-Step): Next, do **Step (2)**, **Step (3)**, **Step (4)** and **Step (5)** of the Construction 2.

Since $\forall j = 0, \dots, n-1, \forall k = 1, \dots, n, \forall l = 1, \dots, m,$

$$X_{j+1} \perp\!\!\!\perp Y_l^k \text{ iff } j+1 \neq k,$$

we can use the same arguments as in the proof of Theorem 2 to show that $\forall i = 1, \dots, N$, the couple $(W_i, Z_i) \in \mathcal{D}_N^{W,Z}$ satisfies the MDcond($\frac{n}{N}$).

7 Conclusion

In this article, we consider the problem of conditional density estimation. We introduce a new method, **MCD** inspired by contrastive learning. **MCD** reformulates the initial task into a problem of supervised learning. We present construction techniques to produce contrast

dataset of *i.i.d.* or *i.d.* samples with far more observations than in the original dataset. We also provided construction techniques to take advantage of unlabeled observations and more than one target value per observation. We evaluate our method on a benchmark of both density models and real-world datasets, and obtain excellent results in most cases, especially when **MCD** is combined with Neural Networks.

There are still many questions left open with regard to the appropriate choice of discriminator and construction strategy, notably the ratio r . Besides, assessing the performances of **MCD** on down-stream tasks such as quantile regression, variance estimation or outlier detection is also a promising future avenue of research.

References

- Luca Ambrogioni, Umut Güçlü, Marcel A. J. van Gerven, and Eric Maris. The Kernel Mixture Network: A Nonparametric Method for Conditional Density Estimation of Continuous Random Variables. *arXiv:1705.07111 [stat]*, May 2017. URL <http://arxiv.org/abs/1705.07111>. arXiv: 1705.07111.
- Arthur Asuncion and David Newman. UCI machine learning repository, 2007.
- Philip Bachman, R. Devon Hjelm, and William Buchwalter. Learning Representations by Maximizing Mutual Information Across Views. *arXiv:1906.00910 [cs, stat]*, July 2019. URL <http://arxiv.org/abs/1906.00910>. arXiv: 1906.00910.
- R. Beck, C.-A. Lin, E. E. O. Ishida, F. Gieseke, R. S. de Souza, M. V. Costa-Duarte, M. W. Hattab, and A. Krone-Martins. On the realistic validation of photometric redshifts, or why Teddy will never be Happy. *Monthly Notices of the Royal Astronomical Society*, 468(4): 4323–4339, July 2017. ISSN 0035-8711, 1365-2966. doi: 10.1093/mnras/stx687. URL <http://arxiv.org/abs/1701.08748>. arXiv: 1701.08748.
- Karine Bertin, Claire Lacour, and Vincent Rivoirard. Adaptive pointwise estimation of conditional density function. *arXiv:1312.7402 [math, stat]*, December 2014. URL <http://arxiv.org/abs/1312.7402>. arXiv: 1312.7402.
- Christopher M. Bishop. Mixture density networks. Technical report, NA, 1994.
- Ann-Kathrin Bott and Michael Kohler. Nonparametric estimation of a conditional density. *Annals of the Institute of Statistical Mathematics*, 69(1):189–214, February 2017. ISSN 0020-3157, 1572-9052. doi: 10.1007/s10463-015-0535-8. URL <http://link.springer.com/10.1007/s10463-015-0535-8>.
- Tianqi Chen and Carlos Guestrin. XGBoost: A Scalable Tree Boosting System. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, KDD '16, pages 785–794, New York, NY, USA, 2016. Association for Computing Machinery. ISBN 978-1-4503-4232-2. doi: 10.1145/2939672.2939785. URL <https://doi.org/10.1145/2939672.2939785>. event-place: San Francisco, California, USA.
- Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A Simple Framework for Contrastive Learning of Visual Representations. *arXiv:2002.05709 [cs, stat]*, June 2020. URL <http://arxiv.org/abs/2002.05709>. arXiv: 2002.05709.

- François Chollet and The Keras team. Keras: Deep Learning for humans, April 2022. URL <https://github.com/keras-team/keras>. original-date: 2015-03-28T00:35:42Z.
- Niccolò Dalmaso, Taylor Pospisil, Ann B. Lee, Rafael Izbicki, Peter E. Freeman, and Alex I. Malz. Conditional Density Estimation Tools in Python and R with Applications to Photometric Redshifts and Likelihood-Free Cosmological Inference. *Astronomy and Computing*, 30:100362, January 2020. ISSN 22131337. doi: 10.1016/j.ascom.2019.100362. URL <http://arxiv.org/abs/1908.11523>. arXiv: 1908.11523.
- A. D’Isanto and K. L. Polsterer. Photometric redshift estimation via deep learning - Generalized and pre-classification-less, image based, fully probabilistic redshifts. *Astronomy & Astrophysics*, 609:A111, January 2018. ISSN 0004-6361, 1432-0746. doi: 10.1051/0004-6361/201731326. URL <https://www.aanda.org/articles/aa/abs/2018/01/aa31326-17/aa31326-17.html>. Publisher: EDP Sciences.
- Evelyn Fix and J. L. Hodges. Discriminatory Analysis. Nonparametric Discrimination: Consistency Properties. *International Statistical Review / Revue Internationale de Statistique*, 57(3):238–247, 1989. ISSN 0306-7734. doi: 10.2307/1403797. URL <https://www.jstor.org/stable/1403797>. Publisher: [Wiley, International Statistical Institute (ISI)].
- freelunchtheorem. Conditional Density Estimation (CDE), March 2022. URL https://github.com/freelunchtheorem/Conditional_Density_Estimation. original-date: 2017-12-18T17:52:01Z.
- freelunchtheoremDoc. Conditional Density Estimation Documentation — Conditional Density Estimation 0.1 documentation, 2022. URL https://freelunchtheorem.github.io/Conditional_Density_Estimation/docs/html/index.html.
- Alexander Goldenshluger and Oleg Lepski. BANDWIDTH SELECTION IN KERNEL DENSITY ESTIMATION: ORACLE INEQUALITIES AND ADAPTIVE MINIMAX OPTIMALITY. *Annals of Statistics*, 39(3):1608–1632, 2011. doi: 10.1214/11-AOS883. URL <https://hal.archives-ouvertes.fr/hal-01265258>. Publisher: Institute of Mathematical Statistics.
- Yury Gorishniy, Ivan Rubachev, Valentin Khruikov, and Artem Babenko. Revisiting Deep Learning Models for Tabular Data. In A. Beygelzimer, Y. Dauphin, P. Liang, and J. Wortman Vaughan, editors, *Advances in Neural Information Processing Systems*, 2021. URL https://openreview.net/forum?id=i_Q1yrOegLY.
- Michael Gutmann and Aapo Hyvärinen. Noise-contrastive estimation: A new estimation principle for unnormalized statistical models. In *Proceedings of the Thirteenth International Conference on Artificial Intelligence and Statistics*, pages 297–304. JMLR Workshop and Conference Proceedings, March 2010. URL <https://proceedings.mlr.press/v9/gutmann10a.html>. ISSN: 1938-7228.
- Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum Contrast for Unsupervised Visual Representation Learning. *arXiv:1911.05722 [cs]*, March 2020. URL <http://arxiv.org/abs/1911.05722>. arXiv: 1911.05722.
- Jeremy Howard and Sylvain Gugger. Fastai: A Layered API for Deep Learning. *Inf.*, 11(2):108, 2020. doi: 10.3390/info11020108. URL <https://doi.org/10.3390/info11020108>.

- Rafael Izbicki and Ann B. Lee. Converting high-dimensional regression to high-dimensional conditional density estimation. *Electronic Journal of Statistics*, 11(2), January 2017. ISSN 1935-7524. doi: 10.1214/17-EJS1302. URL <https://projecteuclid.org/journals/electronic-journal-of-statistics/volume-11/issue-2/>
- Ashish Jaiswal, Ashwin Ramesh Babu, Mohammad Zaki Zadeh, Debapriya Banerjee, and F. Makedon. A Survey on Contrastive Self-supervised Learning. *Technologies*, 2020. doi: 10.3390/technologies9010002.
- Kaggle. Kaggle, 2000. URL <https://www.kaggle.com>.
- Guolin Ke, Qi Meng, Thomas Finley, Taifeng Wang, Wei Chen, Weidong Ma, Qiwei Ye, and Tie-Yan Liu. LightGBM: A Highly Efficient Gradient Boosting Decision Tree. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017. URL <https://proceedings.neurips.cc/paper/2017/file/6449f44a102fde848669bdd9eb6b76fa-Paper.pdf>
- Prannay Khosla, Piotr Teterwak, Chen Wang, Aaron Sarna, Yonglong Tian, Phillip Isola, Aaron Maschiot, Ce Liu, and Dilip Krishnan. Supervised Contrastive Learning. *arXiv:2004.11362 [cs, stat]*, March 2021. URL <http://arxiv.org/abs/2004.11362>. arXiv: 2004.11362.
- Günter Klambauer, Thomas Unterthiner, Andreas Mayr, and Sepp Hochreiter. Self-Normalizing Neural Networks. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017. URL <https://proceedings.neurips.cc/paper/2017/file/5d44ee6f2c3f71b73125876103c8f6c4-Paper.pdf>
- Nicolas Langrené and Xavier Warin. Fast multivariate empirical cumulative distribution function with connection to kernel density estimation. NA, August 2020. URL <https://hal.archives-ouvertes.fr/hal-02910373>.
- S. S. Manson. Fatigue: A complex subject—Some simple approximations. *Experimental Mechanics*, 5(4):193–226, July 1965. ISSN 1741-2765. doi: 10.1007/BF02321056. URL <https://doi.org/10.1007/BF02321056>.
- Martin Abadi, Ashish Agarwal, Paul Barham, Eugene Brevdo, Zhifeng Chen, Craig Citro, Greg S. Corrado, Andy Davis, Jeffrey Dean, Matthieu Devin, Sanjay Ghemawat, Ian Goodfellow, Andrew Harp, Geoffrey Irving, Michael Isard, Yangqing Jia, Rafal Jozefowicz, Lukasz Kaiser, Manjunath Kudlur, Josh Levenberg, Dandelion Mane, Rajat Monga, Sherry Moore, Derek Murray, Chris Olah, Mike Schuster, Jonathon Shlens, Benoit Steiner, Ilya Sutskever, Kunal Talwar, Paul Tucker, Vincent Vanhoucke, Vijay Vasudevan, Fernanda Viegas, Oriol Vinyals, Pete Warden, Martin Wattenberg, Martin Wicke, Yuan Yu, and Xiaoqiang Zheng. TensorFlow: Large-Scale Machine Learning on Heterogeneous Systems, 2015. URL <https://www.tensorflow.org/>.
- Nicolai Meinshausen. Quantile Regression Forests. NA, page 17, 1960.
- Thomas Nagler and Claudia Czado. Evading the curse of dimensionality in nonparametric density estimation with simplified vine copulas. *Journal of Multivariate Analysis*, 151:69–89, October 2016. ISSN 0047259X. doi: 10.1016/j.jmva.2016.07.003. URL <http://arxiv.org/abs/1503.03305>. arXiv: 1503.03305.

- Emanuel Parzen. On Estimation of a Probability Density Function and Mode. *The Annals of Mathematical Statistics*, 33(3):1065–1076, 1962. ISSN 0003-4851. URL <https://www.jstor.org/stable/2237880>. Publisher: Institute of Mathematical Statistics.
- Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, and others. PyTorch: An imperative style, high-performance deep learning library. In *Advances in Neural Information Processing Systems*, pages 8024–8035, 2019.
- Karl Pearson. Contributions to the Mathematical Theory of Evolution. II. Skew Variation in Homogeneous Material. *NA*, January 1895. doi: 10.1098/rsta.1895.0010. URL <https://zenodo.org/record/1432104>.
- F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, J. Vanderplas, A. Passos, D. Cournapeau, M. Brucher, M. Perrot, and E. Duchesnay. Scikit-learn: Machine Learning in Python. *Journal of Machine Learning Research*, 12:2825–2830, 2011.
- Taylor Pospisil. NNKCDE: Nearest Neighbor Conditional Density Estimation, June 2020. URL <https://github.com/tpospisi/NNKCDE>. original-date: 2018-02-19T15:10:04Z.
- Taylor Pospisil. cdetools: Tools for Conditional Density Estimates, March 2022. URL <https://github.com/tpospisi/cdetools>. original-date: 2018-02-05T19:40:05Z.
- Taylor Pospisil and Ann B. Lee. RFCDE: Random Forests for Conditional Density Estimation. *arXiv:1804.05753 [cs, stat]*, May 2018. URL <http://arxiv.org/abs/1804.05753>. arXiv: 1804.05753.
- Liudmila Prokhorenkova, Gleb Gusev, Aleksandr Vorobev, Anna Veronika Dorogush, and Andrey Gulin. CatBoost: unbiased boosting with categorical features. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 31. Curran Associates, Inc., 2018. URL <https://proceedings.neurips.cc/paper/2018/file/14491b756b3a51daac41c24863285549-Paper.pdf>
- Danilo Jimenez Rezende and Shakir Mohamed. Variational Inference with Normalizing Flows. *arXiv:1505.05770 [cs, stat]*, June 2016. URL <http://arxiv.org/abs/1505.05770>. arXiv: 1505.05770.
- Philippe Rigollet and Alexandre Tsybakov. Linear and convex aggregation of density estimators. *arXiv:math/0605292*, May 2006. URL <http://arxiv.org/abs/math/0605292>. arXiv: math/0605292.
- Murray Rosenblatt. Remarks on Some Nonparametric Estimates of a Density Function. *The Annals of Mathematical Statistics*, 27(3):832–837, September 1956. ISSN 0003-4851, 2168-8990. doi: 10.1214/aoms/1177728190. URL <https://projecteuclid.org/journals/annals-of-mathematical-statistics/volume-27/issue-3/F>. Publisher: Institute of Mathematical Statistics.
- Jonas Rothfuss, Fabio Ferreira, Simon Walther, and Maxim Ulrich. Conditional Density Estimation with Neural Networks: Best Practices and Benchmarks. *arXiv:1903.00954 [cs, q-fin, stat]*, April 2019. URL <http://arxiv.org/abs/1903.00954>. arXiv: 1903.00954.

David W. Scott. Feasibility of multivariate density estimates. *Biometrika*, 78(1):197–205, 1991. ISSN 0006-3444, 1464-3510. doi: 10.1093/biomet/78.1.197. URL <https://academic.oup.com/biomet/article-lookup/doi/10.1093/biomet/78.1.197>.

B. W. Silverman. *Density Estimation for Statistics and Data Analysis*. Routledge, New York, October 2017. ISBN 978-1-315-14091-9. doi: 10.1201/9781315140919.

Masashi Sugiyama, Ichiro Takeuchi, Taiji Suzuki, Takafumi Kanamori, Hirotaka Hachiya, and Daisuke Okanohara. Conditional Density Estimation via Least-Squares Density Ratio Estimation. In *Proceedings of the Thirteenth International Conference on Artificial Intelligence and Statistics*, pages 781–788. JMLR Workshop and Conference Proceedings, March 2010. URL <https://proceedings.mlr.press/v9/sugiyama10a.html>. ISSN: 1938-7228.

Sami Tibshirani, Harry Friedman, and Trevor Hastie. *The elements of statistical learning*. NA, 1960.

Chun-Hsiao Yeh, Cheng-Yao Hong, Yen-Chi Hsu, Tyng-Luh Liu, Yubei Chen, and Yann LeCun. Decoupled Contrastive Learning. *arXiv:2110.06848 [cs]*, October 2021. URL <http://arxiv.org/abs/2110.06848>. arXiv: 2110.06848.

8 Appendix

8.1 Method to rescale estimated densities

If we want our estimation to correspond to a proper probability density function, that is $\int_{\mathcal{Y}} \widehat{f}_{Y|X=x}(y) dy \approx 1$, we can numerically estimate the integral using the trapezoidal rule on a grid of m target values $\{y_i\}_{i=1,\dots,m}$ such that its values are evenly distributed between the quantiles 0.001 and 0.999 of f_Y (which we can always estimate through the marginal density estimator) and then rescale the predicted value, doing as follows:

MCD.rescale (pdf)	<ul style="list-style-type: none"> • Generate a grid of m target values $\{y_i\}_{i=1,\dots,m}$. • Estimate $\{f_{Y X=x}(y_i)\}_{i=1,\dots,m}$. • Use the trapezoidal rule to estimate $\int_{\mathcal{Y}} \widehat{f}_{Y X=x}(y) dy$. • Divide the predicted value by the estimation of $\int_{\mathcal{Y}} \widehat{f}_{Y X=x}(y) dy$.
-------------------	---

Note that this step must be repeated for each observation x for which we want to estimate a conditional density function, but given a set observation x , we can reuse the computed integral for any number of target values. This technique will also be used for the other benchmarked methods which do not yield proper integrals by default.

8.2 Python code for training set construction

We provide extracts of the *python* code used to construct $\mathcal{D}^{W,Z}$, the training set for the discriminator.

```

1 import numpy as np
2 from sklearn.model_selection import train_test_split as tts
3 from sklearn.utils import shuffle
4 ...
5 n_obs, p = X.shape
6 n_extraobs, n_extrasamples = min(len(extraobs),n_obs), min(len(extrasamples
   ),n_obs)
7 n_extra = min(max(n_extraobs, n_extrasamples),n_obs)
8 n_contrast = int((n_obs + n_extra )/2)
9 if n_extra == 0:
10     X_joint, X_discarded, y_joint, y_marginal = tts(X, y, train_size =
       n_contrast, random_state = self._random_state)
11     X_marginal = X_joint
12 elif n_extra == n_obs:
13     if n_extraobs <= n_extrasamples:
14         X_joint, X_marginal = X, X
15         y_joint, y_marginal = y, extrasamples[:n_obs]
16     else:
17         y_joint, y_marginal = y, y
18         X_joint, X_marginal = X, extraobs[:n_obs]
19 elif n_extraobs <= n_extrasamples:
20     X_joint, X_discarded, y_joint, y_marginal_partial = tts(X,y, train_size
       = n_contrast, random_state = self._random_state)
21     X_marginal = X_joint
22     y_marginal = np.concatenate([y_marginal_partial, extrasamples[:2 *
       n_contrast - n_obs]], axis= 0)
23 elif n_extraobs > n_extrasamples:
24     X_joint, X_marginal_partial, y_joint, y_discarded = tts(X, y,
       train_size = n_contrast, random_state = self._random_state)
25     y_marginal = y_joint
26     X_marginal = np.concatenate([X_marginal_partial, extraobs[:2 *
       n_contrast - n_obs]], axis= 0)
27 z = self._random_state.binomial(1, self.contrast_ratio, size = (n_contrast
   )
28 X_joint, X_marginal, y_joint, y_marginal = X_joint[:n_contrast], X_marginal
   [:n_contrast], y_joint[:n_contrast].reshape((n_contrast,-1)),
       y_marginal[:n_contrast].reshape((n_contrast,-1))
29 W_X = X_joint * z.reshape((-1,1)) + X_marginal * (1 - z.reshape((-1,1)))
30 W_y = y_joint * z.reshape((-1,1)) + y_marginal * (1 - z.reshape((-1,1)))
31 W = self._build_W(W_X, W_y)
32 ...
33 def _build_W(self, X, y):
34     if len(X.shape)!= len(y.shape):
35         y = y.reshape((len(X), -1))
36     return np.concatenate([X, y], axis = -1)

```

Listing 1: Python code extract corresponding to Constructions 1 and 3.

```

1 import numpy as np
2 from sklearn.model_selection import train_test_split as tts
3 from sklearn.utils import shuffle
4 ...
5 n_obs, p = X.shape
6 n_joint = n_obs
7 if self.contrast_ratio < 1. / n_obs: self.contrast_ratio = 1. / n_obs #does
   not consider the case where  $p < 1 / n \iff n_J < n$ , as there is no
   practical reason to make this choice
8 n_marginal = int(n_joint / self.contrast_ratio - n_joint)
9 n_marginal_extra = min(len(extraobs) * len(extrasamples), n_marginal)
10 n_marginal_x = min(len(extraobs) * n_obs, n_marginal - n_marginal_extra)
11 n_marginal_y = min(n_obs * len(extrasamples), n_marginal - n_marginal_extra
   - n_marginal_x)

```

```

12 n_marginal_both = min(n_obs * (n_obs - 1), n_marginal - n_marginal_extra -
    n_marginal_y - n_marginal_x)
13
14 W_joint = self._build_W( X, y)
15
16 W_marginal = np.zeros((0, W_joint.shape[1]))
17 for n_added_marginal, X_added, y_added, remove_same_index in [(
    n_marginal_extra, extraobs, extrasamples, False),
18                                     (n_marginal_x, extraobs, y,
    False),
19                                     (n_marginal_y, X, extrasamples,
    False),
20                                     (n_marginal_both, X, y, True)]:
21     if n_added_marginal:
22         W_marginal_added = self._shuffle_and_sample(X_added, y_added,
    n_added_marginal, remove_same_index = remove_same_index)
23         W_marginal = np.concatenate([W_marginal, W_marginal_added], axis =
    0)
24
25 W = np.concatenate([W_joint, W_marginal], axis = 0)
26 z = (np.arange(n_joint + n_marginal) < n_joint).astype(int)
27 shuffled_indexes = shuffle(np.arange(n_joint + n_marginal), random_state =
    self._random_state)
28 W, z = W[shuffled_indexes], z[shuffled_indexes]
29 #to insure we use the same distribution the discriminator has seen during
    training
30 true_contrast_ratio = z.mean()
31 ...
32 def _shuffle_and_sample(self, X, y, n_samples, remove_same_index = False):
33     len_x, len_y = len(X), len(y)
34     x_indexes = np.arange(len_x * len_y) % len_x
35     y_indexes = np.arange(len_x * len_y) // len_x
36     if remove_same_index:
37         isnot_joint = x_indexes != y_indexes
38         x_indexes, y_indexes = x_indexes[isnot_joint], y_indexes[
    isnot_joint]
39     if n_samples < len(x_indexes):
40         sampled_indexes = self._random_state.choice(np.arange(len(x_indexes)
    )), size = n_samples, replace= False)
41         x_indexes, y_indexes = x_indexes[sampled_indexes], y_indexes[
    sampled_indexes]
42     return self._build_W( X[x_indexes], y[y_indexes])

```

Listing 2: Python code extract corresponding to Constructions 2 and 4.

```

1 import numpy as np
2 from sklearn.model_selection import train_test_split as tts
3 from sklearn.utils import shuffle
4 ...
5 n_obs, p = X.shape
6 n_joint = n_obs
7 #target values are stored in extrasamples
8 #extrasamples.shape = (n, m)
9 multi_sample_size = extrasamples.shape[-1]
10 if self.contrast_ratio < 1. / (n_obs * multi_sample_size) : self.
    contrast_ratio = 1. / (n_obs * multi_sample_size) #does not consider
    the case where  $r < 1 / n \iff n_J < n$ , as there is no practical reason
    to make this choice
11 n_joint = n_obs * multi_sample_size
12 n_total = int(n_joint / self.contrast_ratio)
13 n_marginal = n_total - n_joint
14

```

```

15 X_joint = X.repeat(multi_sample_size,axis=0)
16 y_joint = extrasamples.reshape((n_obs * multi_sample_size,-1))
17 W_joint = self._build_W(X_joint, y_joint)
18
19 X_marginal_max = []
20 y_marginal_max = []
21 for i in range(n_obs):
22     for j in range(n_obs):
23         if i != j:
24             X_marginal_max.append(X[i:i+1].repeat(multi_sample_size,axis=0)
25 )
26             y_marginal_max.append(extrasamples[j:j+1].reshape((
27 multi_sample_size,-1)))
28 X_marginal_max = np.concatenate(X_marginal_max, axis = 0)
29 y_marginal_max = np.concatenate(y_marginal_max, axis = 0)
30 X_marginal, X_discarded, y_marginal, y_discarded = tts(X_marginal_max,
31 y_marginal_max, train_size = n_marginal, random_state = self.
32 _random_state)
33 W_marginal = self._build_W(X_marginal, y_marginal)
34
35 W = np.concatenate([W_joint, W_marginal], axis = 0)
36 z = (np.arange(n_joint + n_marginal) < n_joint).astype(int)
37 shuffled_indexes = shuffle(np.arange(n_joint + n_marginal), random_state =
38 self._random_state)
39 W, z = W[shuffled_indexes], z[shuffled_indexes]
40 #to insure we use the same distribution the discriminator has seen during
41 training
42 true_contrast_ratio = z.mean()

```

Listing 3: Python code extract corresponding to Construction 5.

8.3 Exhaustive experimental results

In this section, we present the exhaustive results corresponding to Tables 5, 6 and 7.

Empirical KL	MCD:MLP	MCD:CatBoost	NNKDE	MDN	KMN	N:Flow	LSCond	RFCDE	FlexCode:MLP	FlexCode:XGboost	Deepede
$p = 3$	0.008	0.009	0.022	0.109	0.067	0.189	0.342	0.037	0.094	0.093	0.152
$p = 10$	0.036	0.042	0.063	0.229	0.096	0.228	0.61	0.105	0.106	0.076	0.205
$p = 30$	0.115	0.202	0.154	0.396	0.181	0.432	0.369	0.238	0.22	0.196	0.385
$p = 100$	0.162	0.224	0.173	0.45	0.401	0.411	1.059	0.238	0.234	0.264	0.36
$p = 300$	0.244	0.308	0.282	0.506	0.304	0.67	0.783	0.507	0.253	0.302	0.306

Table 11: Evaluation of the **KL** divergence values for various feature sizes p , on the **BasicLinear** density model, with $n = 100$.

Time in sec.	MCD:MLP	MCD:CatBoost	NNKDE	MDN	KMN	N:Flow	LSCond	RFCDE	FlexCode:MLP	FlexCode:XGboost	Deepede
$n = 30$	3.133	0.46	0.01	35.46	47.92	50.74	12.01	0.044	0.018	9.574	1.943
$n = 100$	3.149	0.369	0.022	35.45	102.7	50.72	37.14	0.149	0.017	9.57	2.11
$n = 300$	3.132	0.446	0.04	35.65	150.6	50.62	100.5	0.448	0.017	13.19	3.225
$n = 1000$	3.296	0.689	0.043	35.73	143.6	51.12	167.9	0.952	0.02	25.24	6.388

Table 12: Training Time in seconds for various training set sizes n , on the **BasicLinear** density model.

Empirical NLL	MCD:MLP	CatBoost	NNKCODE	MDN	KMN	N.Flow	LSComd	FlexCode:MLP	FlexCode:XGboost	Deepede
BostonHousing	-0.64	-0.59	-0.81	-1.17	-1.22	-1.63	-2.19	-1.99	-1.84	-7.09
Concrete	-0.86	-1.02	-1.23	-2.02	-2.30	-2.13	-4.00	-2.26	-1.25	-10.1
NCYTaxiDropoff:lon.	-1.30	-1.28	-1.68	-2.51	-2.51	-2.85	-3.90	-2.05	-2.17	-11.2
NCYTaxiDropoff:lat.	-1.31	-1.31	-1.44	-2.51	-2.45	-2.96	-4.72	-1.67	-6.18	-9.35
Power	-0.06	-0.36	-0.73	-0.55	-0.35	-0.39	-0.70	-1.09	-0.75	-8.97
Protein	-0.09	-0.42	-0.77	-0.54	-0.68	-0.54	-1.09	-0.83	-1.38	-10.5
WineRed	-0.89	-0.89	3.486	-1.27	-0.90	-2.43	-6.25	1.062	0.965	-10.1
WineWhite	-1.18	-1.13	2.99	-2.24	-1.7	-4.18	-5.41	-0.73	-0.63	-13.2
Yacht	0.14	0.822	-0.46	0.083	0.025	0.401	-2.79	-1.23	0.144	-7.52
teddy	-0.47	-0.51	-0.83	-0.87	-0.76	-0.94	-0.91	-0.83	-1.34	-9.59
toy dataset 1	-0.99	-0.47	-0.63	-0.40	-0.35	-0.71	-0.70	-0.88	-1.46	-6.10
toy dataset 2	-1.40	-1.33	-1.31	-1.40	-1.33	-1.39	-1.35	-1.54	-1.43	-3.53

Table 13: Evaluation of the negative log-likelihood (NLL) for 12 datasets.

This figure "MNIST_pire_diff.png" is available in "png" format from:

<http://arxiv.org/ps/2206.01592v1>