

Fast synchronization of inhomogenous random automata

Balázs Gerencsér*, Zsombor Várkonyi†

June 13, 2022

Abstract

We examine the reset threshold of randomly generated deterministic automata. We claim that an automaton with a random mapping and two random permutation letters has a reset threshold of $\mathcal{O}(\sqrt{n \log^3 n})$ with high probability. Our observation is motivated by the breakthrough of Nicaud [5] providing a near-linear bound in a similar case, among multiple other results. Recent numerical analyses have conjectured that the expected reset threshold is closer to $\mathcal{O}(\sqrt{n})$ but not even a sublinear bound was confirmed for any variant.

1 Introduction

The synchronization of automata has been intensively studied in the literature since the sixties. Recently, a related area has been spotlighted, namely synchronizing random automata, viewing automata theory in a probabilistic way.

For a complete finite automaton, a word is called a *synchronizing word* if it maps to a state independent of the initial state. The *reset threshold* of an automaton with a synchronizing word is the length of its shortest synchronizing word. In 1964, Černý conjectured [1] that if an n -state automaton can be synchronized, then its reset threshold is at most $(n - 1)^2$. This is an open question ever since, however some partial results were proven over the years. Firstly, this is a strict bound, meaning that for all $n \in \mathbb{N}$ there is an n -state automaton with reset threshold exactly $(n - 1)^2$. The best known upper bound was attained by Shitov [6] which improved the previous upper bound of Szykula

*B. Gerencsér is with the Alfréd Rényi Institute of Mathematics, Budapest, Hungary and Eötvös Loránd University, Department of Probability and Statistics, Budapest, Hungary, gerencser.balazs@renyi.hu He was supported by NRD (National Research, Development and Innovation Office) grant KKP 137490 and the János Bolyai Research Scholarship of the Hungarian Academy of Sciences.

†Zs. Várkonyi is with the Eötvös Loránd University, Budapest, Hungary, zsvarkonyi@student.elte.hu Supported by the ÚNKP-21-6-ELTE-1153 New National Excellence Program of the Ministry for Innovation and Technology from the source of the NRD Fund.

[8]. Both of these results provide a bound of $\Theta(n^3)$ and only differ by the leading coefficient. The first cubic upper bound was reached by Pin and Frankl [2].

A strongly related area of study is the investigation of randomly generated deterministic automata, in which the aim is to prove statements that hold with high probability for a certain class of automata. On the analytical side, Nicaud [5] showed that an automaton with at least two random mapping letters in its alphabet has reset threshold of $\mathcal{O}(n \log^3 n)$ with high probability. From a numerical perspective, Skvortsov and Tipikin performed an experimental study [7] and conjectured that the expected value of the reset threshold of an n -state finite automaton is sublinear, more precisely $\mathcal{O}(n^{0.55})$. Kisielewicz et al. examined [4] a large number of random automata up to at most 300 states and conjectured that the expected reset threshold of a random automata with two random mappings is $\mathcal{O}(\sqrt{n})$. These results show that there is a chance to obtain an even better upper bound than the one in [5].

In this paper, we are going to examine a class of letter-inhomogenous random automata and prove that for an n -state automaton of this class, its reset threshold is $\mathcal{O}(\sqrt{n \log^3 n})$ with high probability. This result remains interesting on its own even in view of a possible worst-case quadratic bound of the Černý conjecture as the target typical bound is substantially lower.

2 Definitions and Notations

A deterministic finite automaton is denoted by $\mathcal{A} = (Q, \Sigma, \delta)$ where the set of states is Q , the set of letters is Σ and the transition function of letters over the states is $\delta : Q \times \Sigma \rightarrow Q$. A *word* is a finite series of not necessarily distinct letters, formally words are the elements of Σ^k for arbitrary $k \in \mathbb{N}$. The transition function δ extends to words in a natural way. Automaton \mathcal{A} is called *synchronizing* if a word u exists such that the action of word u leaves the automaton in a state independent of the initial state, that is $\exists S \in Q, \forall T \in Q : S = \delta(T, u)$. A word u with this property is called a *synchronizing word*.

Definition 1. Let T denote a binary property for automata. Let S be an infinite set of finite automata. For $k \in \mathbb{N}$ let S_k denote the elements of S which have exactly k states. p_k is the probability that an automaton chosen uniformly randomly from S_k has property T . Statement T is true for automata in set S with *high probability* if $\lim_{k \rightarrow \infty} p_k = 1$.

A randomly generated deterministic automaton can be built up by random letters of different nature. We now define some random letters to be used.

Definition 2. Let us define *random mapping*, *random p -mapping* and *random permutation* as possible letters of a finite automaton. Let $Q = \{1, 2, \dots, n\}$.

- $f \in \Sigma$ is called a *random mapping* if $f(i)$ is chosen uniformly randomly from Q , independently for all $i = 1, 2, \dots, n$.

- Given a probability mass function p on Q , $g \in \Sigma$ is a *random p -mapping* if $g(i)$ is chosen from Q according to the probability p independently for all $i = 1, 2, \dots, n$.
- $h \in \Sigma$ is a *random permutation* if it is chosen uniformly randomly from the permutation group S_n .

Note that an automaton with random mapping or random permutation letters still has deterministic actions for every realisation.

Considering the structure of random letters, we introduce the following concepts. For a random mapping f a state S is a *cyclic point* if $f^i(S) = S$ for some $i > 0$. The *height* of a state T is the smallest $i \geq 0$ such that $f^i(T)$ is a cyclic point. The height of f is maximal height among all states.

3 Tools

Before presenting our main result, let us cite two important lemmas which will be useful for us. The first one is about random mappings from Nicaud [5]:

Lemma 3 (Lemma 4 in [5]). *The probability that a random p -mapping of size n has more than $2\sqrt{n \log n}$ cyclic points or that it has height greater than $2\sqrt{n \log n}$ is $\mathcal{O}(\frac{1}{n})$.*

In [5] this lemma was used to prove that a random automaton with at least two random mapping letters in its alphabet has a reset threshold at most $\mathcal{O}(n \log^3 n)$ with high probability. Note that by repeating the same random permutation letter several times, the number of possible states can be significantly decreased.

In their paper [3], Friedman and his coauthors proved a general statement about the transitivity of random permutations. Their result is the following:

Lemma 4. *For every r and $d \geq 2$ there is a C such that for uniformly random choices of d permutations $\pi_1, \pi_2, \dots, \pi_d$ of S_n , the following holds with high probability: for any two r -tuples of distinct elements in $\{1, \dots, n\}$, there is a product of at most $C \log n$ of the given permutations which map the first r -tuple to the second.*

4 Main Result

We claim that a certain type of finite automata has a sublinear reset threshold with high probability.

Theorem 5. *Let \mathcal{A} be a randomly generated deterministic complete n -state automaton with its alphabet containing at least 3 letters such that one is a random mapping letter and two of them are random permutation letters. The reset threshold of \mathcal{A} is $\mathcal{O}(\sqrt{n \log^3 n})$ with high probability.*

Proof. Firstly, as we are going to use Lemma 3 and Lemma 4 together, we rely on the fact that for an automaton \mathcal{A} with a random mapping letter and two random permutation letters, both of the conclusions of the lemmas hold true with high probability. Fixing $d = r = 2$, let the constant of Lemma 4 be C . For simplicity, let us use the notation $H(n) = 2\sqrt{n \log n}$. Let $S(m)$ denote the set of possible states of the automaton after performing m operations.

Let a be the random mapping letter and b and c be the random permutations. Firstly, apply $a^{H(n)}$. By Lemma 3, $|S(H(n))| \leq H(n)$ holds. Now consider the remaining at most $H(n)$ states. Thanks to a contracting the original set of possible states, we may choose two states (P_1 and P_2) that are being merged by a . Precisely: $\exists P_1, P_2 \in Q : \delta(P_1, a) = \delta(P_2, a)$.

We repeat the following procedure until the automaton is synchronized:

- Firstly, we search for two different possible states of the automaton. If there is only one, then the automaton is synchronized and we are done. Let these two different states be named S_1, S_2 .
- Now we will map (S_1, S_2) pair to (P_1, P_2) pair. By Lemma 4 and our initial assumption, we can do this step in $C \log n$ transitions.
- Now apply letter a and this reduces the number of possible states by at least one, since P_1 and P_2 are merged by a .

We have to repeat this process at most $H(n) - 1$ times as there were at most $H(n)$ possible states after applying $a^{H(n)}$. The upper bound for the number of letters needed is: $H(n) + (H(n) - 1)(C \log n + 1) \sim H(n) \log n = \mathcal{O}(\sqrt{n \log^3 n})$. As the initial assumptions of the proof hold with high probability, this confirms the claim. \square

References

- [1] Ján Černý. Poznámka k homogénnym experimentom s konečnými automatmi. *Matematicko-fyzikálny časopis*, 14(3):208–216, 1964.
- [2] P. Frankl. An extremal problem for two families of sets. *European Journal of Combinatorics*, 3(2):125–127, 1982.
- [3] Joel Friedman, Antoine Joux, Yuval Roichman, Jacques Stern, and Jean-Pierre Tillich. The action of a few permutations on r -tuples is quickly transitive. *Random Structures & Algorithms*, 12(4):335–350, 1998.
- [4] Andrzej Kisielewicz, Jakub Kowalski, and Marek Szykuła. A fast algorithm finding the shortest reset words. In *International Computing and Combinatorics Conference*, pages 182–196. Springer, 2013.
- [5] Cyril Nicaud. The Černý conjecture holds with high probability. *Journal of Automata, Languages and Combinatorics*, 24(2-4):343–365, 2019.

- [6] Yaroslav Shitov. An improvement to a recent upper bound for synchronizing words of finite automata. *Journal of Automata, Languages and Combinatorics*, 24(2-4):367–373, 2019.
- [7] Evgeny Skvortsov and Evgeny Tipikin. Experimental study of the shortest reset word of random automata. In *International Conference on Implementation and Application of Automata*, pages 290–298. Springer, 2011.
- [8] Marek Szykuła. Improving the upper bound on the length of the shortest reset words. In *35th Symposium on Theoretical Aspects of Computer Science*, 2018.