
A THEORETICAL UNDERSTANDING OF NEURAL NETWORK COMPRESSION FROM SPARSE LINEAR APPROXIMATION

Wenjing Yang*
School of Statistics
University of Minnesota
Minneapolis, MN 55455
yang2987@umn.edu

Ganghua Wang*
School of Statistics
University of Minnesota
Minneapolis, MN 55455
wang9019@umn.edu

Enmao Diao
Department of ECE
Duke University
Durham, NC 27708
enmao.diao@duke.edu

Vahid Tarokh
Department of ECE
Duke University
Durham, NC 27708
vahid.tarokh@duke.edu

Jie Ding
School of Statistics
University of Minnesota
Minneapolis, MN 55455
dingj@umn.edu

Yuhong Yang
School of Statistics
University of Minnesota
Minneapolis, MN 55455
yangx374@umn.edu

ABSTRACT

The goal of model compression is to reduce the size of a large neural network while retaining a comparable performance. As a result, computation and memory costs in resource-limited applications may be significantly reduced by dropping redundant weights, neurons, or layers. There have been many model compression algorithms proposed that provide impressive empirical success. However, a theoretical understanding of model compression is still limited. One problem is understanding if a network is more compressible than another of the same structure. Another problem is quantifying how much one can prune a network with theoretically guaranteed accuracy degradation. In this work, we propose to use the sparsity-sensitive ℓ_q -norm ($0 < q < 1$) to characterize compressibility and provide a relationship between soft sparsity of the weights in the network and the degree of compression with a controlled accuracy degradation bound. We also develop adaptive algorithms for pruning each neuron in the network informed by our theory. Numerical studies demonstrate the promising performance of the proposed methods compared with standard pruning algorithms.

1 Introduction

Since the recent revival of neural networks by deep learning [LeCun et al., 2015], the approach of over-parameterized network has achieved a huge success in a wide range of areas such as computer vision [Krizhevsky et al., 2012; He et al., 2016; Redmon et al., 2016] and nature language processing [Devlin et al., 2018; Radford et al., 2018]. The size of neural networks has grown enormously. For example, LeNet-5 model [LeCun et al., 1998] for digit classification in 1998 had 60 thousand parameters, while in 2020, the GPT-3 language model [Brown et al., 2020] has 175 billion parameters, requiring a vast amount of computation, storage, and energy resource for training and prediction. The large model size may also prohibit the deployment to edge devices such as cell phones due to hardware constraints.

Interestingly, researchers have empirically shown that one can often build a much simpler network with similar performance based on a pre-trained network, which can save a considerable amount of resources [Han et al., 2015; Frankle and Carbin, 2018]. For example, Han et al. [2015] show that on the ImageNet dataset, AlexNet can be compressed to retain only 3% of the original parameters without impacting classification accuracy. As a result, a rising interest is to compress an over-parameterized neural network to a simpler model with comparable prediction accuracy.

The study of neural network compression has a long history and various methods have been proposed. One of the most popular and effective ways to obtain a simplified model is by pruning the original network [LeCun et al.,

*Equal contribution.

1989; Hagiwara, 1993; Han et al., 2015; Hu et al., 2016; Luo et al., 2017; Frankle and Carbin, 2018; Lee et al., 2018; He et al., 2017], which means dropping some neuron connections, neurons, or neuron-like structures such as filters and layers. The general intuition is that in an over-parameterized model, many connections are redundant and the removal of them will have little impact on prediction. To prune a pre-trained network, a standard procedure consists of a pruning criterion and a stopping criterion. A number of pruning criteria have been proposed from different interpretations of redundancy. For example, one may postulate that weights with small magnitudes are non-influential and thus can be eliminated [Hagiwara, 1993; Han et al., 2015], or one may prune the edges/neurons that have the least influence on the network output [LeCun et al., 1989; Lee et al., 2018; Hu et al., 2016; Soltani et al., 2021]. A comprehensive survey of the existing literature on model compression can be found in [Hoeffler et al., 2021]. A commonly used stopping criterion is to terminate pruning when the test accuracy on the validation dataset starts to drop significantly.

Most existing pruning algorithms are heuristic. In practice, the compressibility of different networks and tasks may vary, the efficiency of pruning methods may be unpredictable, and a lot of ad hoc fine-tuning may be involved during pruning. Thus, it is critical to develop a theoretical understanding of compressibility. There have been some recent works in this regard. For example, Arora et al. [2018] relate the compressibility and generalization error of a model through its noise stability. They show that the stability of a neural network against noise injection in the input implies the existence of a smaller network with similar performance. Another line towards the provable existence of a sparser network with similar performance is to look for a coreset of parameters. A coreset means a small subset of parameters that can preserve the output of the original network. Baykal et al. [2018] propose to sample the parameters based on their importance, quantified by the sensitivity of the output due to parameter changes, and approximated using the training data. Mussay et al. [2019] use the same idea of constructing coresets, but calculate the sensitivity in a data-free manner. Ye et al. [2020] propose to reconstruct a network by greedily adding the neurons that decrease the prediction risk the most. They show the generalization error of the constructed model with m parameters is at the order of $O(1/m)$ for two-layer neural networks. However, the prediction risk is intractable in practice, and the greedy selection is done by evaluating the training loss, causing a gap from the theory. Malach et al. [2020]; Orseau et al. [2020] prove that any network can be arbitrarily well approximated by a subnetwork pruned from another deeper and wider network. Zhang et al. [2021] show why the pruned network often has a better test accuracy and easier to train than the original network.

In this paper, we aim to study two fundamental but under-explored problems: for a pre-trained neural network, when can one perform a successful pruning, and how much can one compress with little accuracy degradation. We are motivated by the idea that an essentially sparse network has fewer important weights and can be pruned more without affecting the performance. An immediate example of sparsity indicator is the number of non-zero weights in a network, also known as the ℓ_0 -norm or hard sparsity. However, it is common in practice that the network has many weights with small magnitudes. We propose to use the ℓ_q -norm ($0 < q < 1$) of weights as a soft sparsity measure to characterize the compressibility of a network. In particular, we will provide an upper bound for the approximation and generalization errors of the pruned model for any given pruning ratio. This bound indicates that a network with larger soft sparsity is more compressible. It also guides the selection of a proper pruning ratio that produces allowed accuracy degradation. We then propose a novel adaptive backward pruning procedure based on our theory, which has two specific implementations. The first implementation prunes the network based on the magnitude of weights, while the pruning ratio of each neuron is adaptively determined by its soft sparsity level. The second implementation alternatively determines the pruning ratio of each neuron by using LASSO [Tibshirani, 1996] with the same penalty parameter. A neuron that is essentially sparse will be pruned more by this way. Experiments show their promising performance when compared with the baseline method that prunes a fixed proportion of weights with the smallest magnitude neuron-wisely.

2 Problem formulation

We start with the standard regression learning framework. We will extend the results to classification learning in Section 3. Suppose that the data generation distribution is $(X, Y) \sim \mu$, where $X = (x_1, \dots, x_p)^T \in \mathbb{R}^p$ denotes the predictor/input variable, $Y \in \mathbb{R}$ is the response/output that is square-integrable with respect to μ . The target function is $f^* : x \rightarrow E(Y | X = x)$, and the loss function is the mean squared error loss throughout the paper unless otherwise specified. The risk, or generalization error, of a function $f : \mathbb{R}^p \rightarrow \mathbb{R}$ is given by $R(f) = E[f(X) - f^*(X)]^2$.

Table 1: A summary of frequently used notations.

Notation	Meaning
$f_j^{(k)}, g_j^{(k)}$	The j -th function (also named neuron) and its linear part (before activation) in the k -th layer
$f_j^{(k),s}, g_j^{(k),s}$	The approximation of $f_j^{(k)}, g_j^{(k)}$ after s steps
$f^*, f_T, f_T^{(s)}$	The target function, the pre-trained network, and the approximation of f_T after s steps
$w_{ij}^{(k-1)}$ or $w_{i,j}^{(k-1)}$	The i -th coefficient of the j -th function's weight vector in the k -th layer
n_k, m_k, q_k, t_k	The number of neurons, number of neurons preserved, the norm, and the largest ℓ_{q_k} -norm of weights in the k -th layer
$\sigma(\cdot)$	A ρ -Lipschitz activation function

A pre-trained L -layer fully connected neural network, denoted by f_T , is given as follows. The initial input layer is considered as the 0-th layer, and the output layer is the L -th layer.

$$\begin{aligned}
f_i^{(0)} &= x_i, \quad i = 1, \dots, p, \\
g_i^{(k)} &= \sum_{j=1}^{n_{k-1}} w_{ij}^{(k-1)} f_j^{(k-1)}, \quad f_i^{(k)} = \sigma(g_i^{(k)}), \quad i = 1, \dots, n_k, \quad k = 1, \dots, L, \\
f_T &= g_1^{(L)}.
\end{aligned}$$

Here, we call $f_i^{(k)}$ the i -th function, or neuron, in the k -th layer, $g_i^{(k)}$ the linear part of $f_i^{(k)}$, n_k is the number of neurons in the k -th layer ($n_0 = p$, $n_L = 1$), $w_{ij}^{(k-1)}$'s are the weights or parameters², and $\sigma(\cdot)$ is a ρ -Lipschitz activation function. Common activation functions include the ReLU function $\sigma(x) = \max\{x, 0\}$, tanh function $\sigma(x) = (e^x + e^{-x}) / (e^x - e^{-x})$, and sigmoid function $\sigma(x) = 1 / (1 + e^{-x})$.

We are interested in finding a sparsified network f_S of f_T , such that f_S has a similar generalization error as f_T . In other words, f_S has the same structure as f_T , but the weights include many zeros. The non-zero elements of f_S do not have to remain the same as those in f_T . Suppose that a vector w has M coefficients in total, and after pruning, it has only m non-zero coefficients. We define the compression ratio and pruning ratio for this vector as M/m and $1 - m/M$, respectively. This definition naturally generalizes to a layer or the whole network. Thus, the problem is cast into the following: what is the best generalization error of a subnetwork f_S with a given pruning ratio?

Notation. We use E for expectation and pr for probability. For a vector $w = (w_1, \dots, w_d)^T \in \mathbb{R}^d$, the ℓ_0 -norm and ℓ_q -norm with $0 < q \leq 1$ of w is

$$\|w\|_0 = \sum_{i=1}^d \mathbb{1}_{w_i \neq 0}, \quad \text{and} \quad \|w\|_q = \left[\sum_{i=1}^d |w_i|^q \right]^{1/q},$$

where $\mathbb{1}_{(\cdot)}$ is the indicator function. Note that the ℓ_q -norm with $0 < q < 1$ is actually a quasinorm, and ℓ_0 -norm is not even a quasinorm, though we still call them norms by convention. Define the $L_p(\mu_X)$ -norm of any function f for $p \geq 1$ as

$$\|f\|_p = \left(\int |f|^p \mu_X(dx) \right)^{1/p},$$

where μ_X is the marginal distribution of X . The generalization error of f can be written as $R(f) = \|f - f^*\|_2^2$. The $L_\infty(\mu_X)$ -norm of f is $\|f\|_\infty = \text{ess sup}|f|$. Other frequently used notations are summarized in Table 1.

3 Theoretical characterization of compressibility using ℓ_q norm

We next provide an upper bound of the generalization error for some pruned model f_S .

Our study is motivated by sparse linear approximation. For any function in $f = \sum_{i=1}^n w_i f_i$ that is square-integrable, we hope to approximate f by a linear combination of a small subset of basis functions $\mathcal{F} = \{f_1, \dots, f_n\}$. Specifically,

²Without loss of generality, the bias term is absorbed into the weights since we can add a constant neuron to each layer.

we would like to choose m functions $\mathcal{F}_m = \{f_{s_1}, \dots, f_{s_m}\}$ such that $\hat{f} = \sum_{i=1}^m \tilde{w}_{s_i} f_{s_i}$ is close to f , where \tilde{w}_{s_i} 's are new coefficients. We note that this is model compression of the one layer neural network scenario when f is considered as the output layer and f_i 's are functions of neurons in the hidden layer.

It is intuitive that if the weight vector w of f is sparse, then f can be well approximated by a small subset of f_i 's. For example, suppose w has the hard sparsity of $\|w\|_0 = m$, we can simply retain f_i with $w_i \neq 0$. However, hard sparsity is unrealistic. In practice, a much more common situation is that the network has a large number of small-valued coefficients. A notable approach to study sparse linear approximation in the latter case is via the ℓ_q -norm ($0 < q < 1$) of w [Wang et al., 2014]. For a vector w with fixed dimension, a small $\|w\|_q$ implies that the number of relatively large parameters is also limited. Therefore, ℓ_q -norm can be regarded as the soft sparsity indicator. In particular, for a given subset cardinality m , [Wang et al., 2014] provides an upper bound of the approximation error for the best linear combination of m basis functions under some mild conditions.

This paper utilizes the above result and extends to any fully connected neural network. Specifically, we approximate each neuron by a small number of neurons from the previous layer, hence obtaining a simpler model, and establish its error bound. In other words, each neuron in the previous layer is regarded as a basis function for current layer's neurons, and we compress the connections between them by using a sparse linear combination. The overall compressibility of a network is evaluated by the aggregation of compressibility for all neurons.

Next, we describe how to apply the sparse linear approximation to the whole network in detail. We consider a backward approximation scheme. Let S index the step of approximations starting from the output layer. The first-step approximation step, $S = 1$, is to select m_{L-1} neurons from the $(L-1)$ -th layer to obtain a linear combination of $f_j^{(L-1)}$, $j = 1, \dots, n_{L-1}$ as the approximation for f_T , which is denoted by $f_T^{(1)}$. Without loss of generality, we assume the first m_{L-1} neurons are selected, since we can always reorder the indices. Thus,

$$f_T^{(1)} = \sum_{i=1}^{m_{L-1}} \tilde{w}_{1,i}^{(L-1)} f_i^{(L-1)}, \quad (1)$$

where $\tilde{w}_{1,i}^{(L-1)}$ is the new weights for the sparse approximation. The second-step approximation of $S = 2$ is to approximate each of the $f_j^{(L-1)}$, $j = 1, \dots, n_{L-1}$, by selecting m_{L-2} neurons from the $(L-2)$ -th layer. Here, we assume the pruning ratio for the neurons in the same layer is fixed for simplicity. For each $f_j^{(L-1)}$, suppose the indices of functions selected to approximate it are $\{s_1, \dots, s_{m_{L-2}}\}$, we have the one-step approximation of $f_j^{(L-1)}$ as

$$f_j^{(L-1),1} = \sigma(g_j^{(L-1),1}), \quad g_j^{(L-1),1} = \sum_{i=1}^{m_{L-2}} \tilde{w}_{j,s_i}^{(L-2)} f_{s_i}^{(L-2)}. \quad (2)$$

Note that the neurons selected for approximating different $f_j^{(L-1)}$ are different. To ease the notation, we do not distinguish the index sets for different neurons and use $\{s_1, \dots, s_{m_k}\}$, which should be self-explanatory in the context. Plugging the approximation above into $f_T^{(1)}$, we obtain the two-step approximation of f_T as follows.

$$f_T^{(2)} = \sum_{i=1}^{m_{L-1}} \tilde{w}_{1,i}^{(L-1)} f_i^{(L-1),1}.$$

Iteratively, after the S -step approximation, the output function is approximated S times, denoted by $f_T^{(S)}$.

In summary, each neuron in the $(k+1)$ -th layer of the pre-trained network f_T has n_k inputs from the previous layer, and we prune the number of inputs to m_k (and tune the weights correspondingly). For all such sub-networks, we give an upper bound of the generalization error for the best sub-network as follows.

Theorem 1 (Error bound of the pruned model). *Let f be any square-integrable function and $t_k = \max_{1 \leq i \leq n_k} \|w_i^{(k)}\|_{q_k}$ for $k = 0, \dots, L-1$, where $w_i^{(k)} = (w_{i,1}^{(k)}, \dots, w_{i,n_k}^{(k)})$ is the weight vector of i -th function of $(k+1)$ -th layer. For any $1 \leq S \leq L$, $1 \leq m_k \leq n_k$, and $0 < q_k \leq 1$, $k = 0, \dots, L-1$, we have*

$$\begin{aligned} \|f - f_T^{(S)}\|_2 &\leq \|f - f_T\|_2 + Ct_{L-1}(m_{L-1})^{1/2-1/q_{L-1}} \max_{1 \leq j \leq n_{L-1}} \|f_j^{(L-1)}\|_2 \\ &+ \rho Ct_{L-1}t_{L-2}(m_{L-2})^{1/2-1/q_{L-2}} \max_{1 \leq j \leq n_{L-2}} \|f_j^{(L-2)}\|_2 + \dots \\ &+ \rho^{S-1} Ct_{L-1}t_{L-2} \dots t_{L-S}(m_{L-S})^{1/2-1/q_{L-S}} \max_{1 \leq j \leq n_{L-S}} \|f_j^{(L-S)}\|_2, \end{aligned} \quad (3)$$

where C is a universal constant.

The proofs of Theorem 1 and subsequent results are included in the Appendixs.

Remark 1. Note that if we take $f = f^*$, then the left hand side of (3) is exactly the generalization error of the pruned model $f_T^{(S)}$, and is upper bounded by the generalization error of the original network $\|f^* - f_T\|_2$ plus the approximation error.

Remark 2. Theorem 1 indicates that there exists a sub-network $f_T^{(S)}$ such that the accuracy degradation is properly upper bounded. The bound (3) further implies that there is a trade-off between the generalization error and the compression ratio. Namely, the smaller m_k , the higher compression ratio, and the larger upper bound of the generalization error.

Remark 3. The compressibility, or the generalization error bound, is characterized by the ℓ_q -norm of the original network. As mentioned at the beginning of this section, a small ℓ_q -norm (t_k) indicates that the number of important weights are limited and the network is sparse, and thus one can compress more. This characterization can be used to understand the two fundamental issues proposed in the introduction. In particular, for the first question of when one can prune a network, we know a network with smaller soft sparsity can be pruned more. For the second question that how much one can prune with controlled accuracy drop, we can derive a lower bound for the pruning ratio via (3).

Remark 4. Theorem 1 assumes the pruning ratio and ℓ_q -norm are fixed for all neurons in the same layer for technical convenience. In practice, one may allow them to differ for each neuron. To illustrate this point, we will propose adaptive neuron-level pruning techniques in Section 4. Additionally, Theorem 1 can be generalized to give an upper bound for pruning certain layers, not necessarily in this backward form.

Remark 5. The condition that $t_k = \max_{1 \leq i \leq n_k} \|w_i^{(k)}\|_{q_k}$ can be relaxed to $t_k = \max_{i \in \mathcal{I}_k} \|w_i^{(k)}\|_{q_k}$, where \mathcal{I}_k contains the index of neurons that connect to the $(k+1)$ -th layer of the pruned model.

Next, we present a more parsimonious form of Theorem 1 with specific activation functions and pruning ratios.

Corollary 2 (Homogeneous pruning). For activation function such as tanh and sigmoid, we have $\rho = 1$ and $\|f_j^{(i)}\|_2 \leq 1$. Then, the bound (3) can be replaced with a simpler one

$$\begin{aligned} \|f - f_T^{(S)}\|_2 &\leq \|f - f_T\|_2 + Ct_{L-1}(m_{L-1})^{1/2-1/q_{L-1}} + \dots \\ &\quad + Ct_{L-1}t_{L-2} \dots t_{L-S}(m_{L-S})^{1/2-1/q_{L-S}}. \end{aligned}$$

Furthermore, when $q_k = q$ and $m_k = m$ for all k , we have

$$\|f - f_T^{(S)}\|_2 \leq \|f - f_T\|_2 + C(t_{L-1} + \dots + t_{L-1}t_{L-2} \dots t_{L-S})m^{\frac{1}{2}-\frac{1}{q}}. \quad (4)$$

As an application of Corollary 2, we provide an example to illustrate how one may decide the pruning ratio to achieve a desired generalization error rate.

Example 1. Suppose that f_T is trained with data of sample size N , and take $n_{L-1} = \dots = n_1 = N^\alpha$ for some $\alpha > 0$. Suppose that $t_{L-1} = \dots = t_1 = t = O(N^\gamma)$ for some small $\gamma > 0$, where O is the standard big O notation. Then, by choosing $f = f^*$ in Eq. (4), we have

$$\begin{aligned} \|f^* - f_T^{(S)}\|_2 &\leq \|f^* - f_T\|_2 + Cm^{\frac{1}{2}-\frac{1}{q}}(t + t^2 + \dots + t^S) \\ &= \|f^* - f_T\|_2 + O(N^{S\gamma})m^{\frac{1}{2}-\frac{1}{q}}. \end{aligned}$$

For any $0 < \tau \leq \alpha(1/q - 1/2) - S\gamma$, choosing $m = N^{(S\gamma+\tau)2q/(2-q)}$ yields

$$\|f^* - f_T^{(S)}\|_2 \leq \|f^* - f_T\|_2 + O(N^{-\tau}),$$

which guarantees an error bound of $O(N^{-\tau})$. The associated compression rate is N^α/m .

Extension to classification learning. We consider a binary classification task for simplicity. Suppose that $Y \in \{-1, 1\}$. For any function $f : \mathbb{R}^d \rightarrow [0, 1]$, let the classification rule be $\delta_f : x \rightarrow \text{sign}(2f(x) - 1)$, where $\text{sign}(x) = 1$ if $x > 0$ otherwise $\text{sign}(x) = -1$. Suppose we use the zero-one loss function, so the classification error probability of f is given by

$$R(f) = \text{pr}(\delta_f(X) \neq Y).$$

Note that $f^* : x \rightarrow E(Y | X = x)$ is still a minimizer of the error. The following well-known inequality connects the classification error of δ_f and the regression error of f [Devroye et al., 2013].

Lemma 1. For any function $f : \mathbb{R}^d \rightarrow [0, 1]$, we have

$$R(f) - R(f^*) \leq 2\|f - f^*\|_1 \leq 2\|f - f^*\|_2.$$

Combining the above result with Theorem 1, we immediately have the following result.

Corollary 3 (Classification). For a binary classification task described above, we have

$$\begin{aligned} R(f_T^{(S)}) - R(f^*) &\leq 2\|f^* - f_T\|_2 + Ct_{L-1}(m_{L-1})^{1/2-1/q_{L-1}} \max_{1 \leq j \leq n_{L-1}} \|f_j^{(L-1)}\|_2 \\ &+ C\rho t_{L-1}t_{L-2}(m_{L-2})^{1/2-1/q_{L-2}} \max_{1 \leq j \leq n_{L-2}} \|f_j^{(L-2)}\|_2 + \dots \\ &+ C\rho^{S-1}t_{L-1}t_{L-2} \dots t_{L-S}(m_{L-S})^{1/2-1/q_{L-S}} \max_{1 \leq j \leq n_{L-S}} \|f_j^{(L-S)}\|_2. \end{aligned}$$

4 Adaptive pruning algorithms

4.1 Overview of the pruning procedure

Based on the developed theory in Section 3, we propose an adaptive backward pruning procedure (‘ABP’). Specifically, we start from the last layer, which is the L -th layer of one function, and approximate it by constructing a sparse linear combination of the functions in the $(L - 1)$ -th layer, as presented in Eq. (1). We then proceed to the second last layer, and apply a similar procedure to the linear part of each neuron there, as presented in Eq. (2). We repeat approximating neurons from back to the front until reaching the first layer of the network. Additionally, we choose the pruning ratio of each neuron in an adaptive manner according to its soft sparsity level. In particular, a neuron has larger soft sparsity will be pruned more. We summarize the overall pruning procedure in Algorithm 1.

Since Theorem 1 only shows the existence of a pruned model that satisfies the error bound, we need a practical algorithm to find the sparse linear approximation for each neuron. To this end, we propose two particular adaptive pruning strategies, also summarized in Algorithm 2 and Algorithm 3 as subroutines of Algorithm 1, respectively.

4.2 Adaptive pruning strategies for each neuron

Magnitude-based pruning (‘ABP-M’). This algorithm to find sparse linear approximation is based on the magnitude of the weights. Let I_m be the largest m components (in absolute values) of a vector w . Since the energy of w is concentrated in the coefficients indexed by I_m , a natural idea is to prune all the coefficients not in I_m . The question is how to decide the pruning ratio, or equivalently, m . To address that, we first introduce a tolerance parameter η that satisfies $\sum_{i \notin I_m} |w_i|^q \leq \eta \sum_{i \in I_m} |w_i|^q$. We use η to control the overall pruning degree, since a smaller η requires a larger m . For any fixed η , we propose to decide m by each neuron’s soft sparsity. In particular, we define the sparsity index for $w \in \mathbb{R}^d$ and any $0 < q < 1$ as

$$\text{SI}_q(w) = \|w\|_1 / \|w\|_q.$$

We will write $\text{SI}_q(w)$ as SI for short in the rest of the paper when there is no ambiguity. We can derive the following inequality (with more details in the Appendix).

$$m \geq \text{SI}^{-q/(1-q)}(1 + \eta)^{-1/(1-q)}. \quad (5)$$

We propose to choose m as the lower bound in (5). The corresponding algorithm is summarized in Algorithm 2.

Remark 6. Note that $\text{SI} \in [d^{1-1/q}, 1]$, and a larger SI indicates a sparser vector. Aligned with our motivation, Eq. (5) indicates that if w is soft-sparse and SI is relatively large, then m can be small and we prune more.

Similar to Theorem 1, we can show an upper bound for the pruned model produced by Algorithm 2 as follows.

Theorem 4. Suppose $f_T^{(S)}$ is obtained by Algorithm 2, with m_k defined as the smallest m obtained for the k th layer. The other notation and conditions are the same as Theorem 1. Then, we have

$$\begin{aligned} \|f - f_T^{(S)}\|_2 &\leq \|f - f_T\|_2 + t_{L-1}(m_{L-1})^{1-1/q_{L-1}} \max_{1 \leq j \leq n_{L-1}} \|f_j^{(L-1)}\|_2 \\ &+ \rho t_{L-1}t_{L-2}(m_{L-2})^{1-1/q_{L-2}} \max_{1 \leq j \leq n_{L-2}} \|f_j^{(L-2)}\|_2 + \dots \\ &+ \rho^{S-1}t_{L-1}t_{L-2} \dots t_{L-S}(m_{L-S})^{1-1/q_{L-S}} \max_{1 \leq j \leq n_{L-S}} \|f_j^{(L-S)}\|_2. \end{aligned}$$

Algorithm 1 One-shot adaptive backward pruning procedure (‘ABP’)

Input: Pre-trained network to be pruned f_T

- 1: $k = L$
- 2: **while** $k > 0$ **do**
- 3: **for** j in $1, \dots, n_k$ **do**
- 4: Get the weights vector $w_j^{(k-1)}$ for j -th neuron in k -th layer of f_T
- 5: Adaptively find its sparse linear approximation $\tilde{w}_j^{(k-1)}$, such as using Algorithm 2 or 3
- 6: **end for**
- 7: $k = k - 1$
- 8: **end while**

Output: The pruned model f_S with weights $\tilde{w}_j^{(k-1)}, j = 1, \dots, n_k, k = 1, \dots, L$.

Algorithm 2 (Subroutine of Algorithm 1, ‘ABP-M’) Sparse approximation based on magnitude

Input: Weight vector $w_j^{(k-1)}, \eta, q$ ▷ Approximate the j -th neuron in k -th layer

- 1: Calculate $SI = \|w_j^{(k-1)}\|_1 / \|w_j^{(k-1)}\|_q$
- 2: Calculate $m = SI^{q/(q-1)}(1 + \eta)^{1/(q-1)}$
- 3: Select m indices of $w_j^{(k-1)}$ that have the largest magnitudes as $J_m = \{s_1, \dots, s_m\}$
- 4: Calculate $X_i^{(k)} = (f_{s_1}^{(k-1)}(X_i), \dots, f_{s_m}^{(k-1)}(X_i)), Y_i^{(k)} = g_j^{(k)}(X_i)$ for $i = 1, \dots, N$
- 5: Perform linear regression on $X_i^{(k)}, Y_i^{(k)}, i = 1, \dots, N$.

Output: The retrained weights \tilde{w} from the linear regression

Remark 7. We note that the upper bound of Theorem 4 is looser than Theorem 1, since pruning based on magnitude is a simple but possibly crude choice of the sparse linear combination, while Theorem 1 prunes the network based on the best sparse approximation. This also motivates us to use other strategies to find a better sparse approximation, such as the application of LASSO discussed next.

LASSO-based pruning (‘ABP-L’). As an alternative, we may find sparse linear approximations using LASSO [Tibshirani, 1996]. To approximate the j -th neuron in the k -th layer using the functions in the $(k - 1)$ -th layer, we first obtain the input and output of this neuron using the training data. They are denoted by $X_i^{(k)} = (f_1^{(k-1)}(X_i), \dots, f_{n_{k-1}}^{(k-1)}(X_i))$ and $Y_i^{(k)} = g_j^{(k)}(X_i)$ for $i = 1, \dots, N$, respectively. The approximation weight vector \tilde{w} is obtained from applying LASSO to $X_i^{(k)}, Y_i^{(k)}, i = 1, \dots, N$ with penalty parameter λ . We note that LASSO adds a ℓ_1 penalty on the weight vector, which enforces the learned \tilde{w} to be sparse. Furthermore, an essentially sparser nature (larger soft sparsity) leads to a sparser \tilde{w} . This algorithm is summarized in Algorithm 3.

5 Experiments

We compare our proposed pruning procedure using magnitude-based approximation Algorithm 2 (‘ABP-M’) and LASSO-based Algorithm 3 (‘ABP-L’) with a standard pruning algorithm (‘Mag’), which prunes a fixed proportion p of weights with the smallest magnitude for each neuron. We train a four-layer fully connected ReLU neural network f_T on the California Housing dataset [Pace and Barry, 1997], which is a regression task with eight continuous predictors and about 20 thousand instances. The evaluation criterion is mean squared error (MSE). For ‘ABP-M’, we choose hyper-parameters $q = 0.3, 0.5, 0.7$ and $\eta = 0, 0.1, 0.2, 0.3$. For ‘ABP-L’, we use penalty parameter $\lambda = 10^{-5}, 10^{-4}, 10^{-3}$. For ‘Mag’, we choose pruning ratio $p = 0.3, 0.5, 0.7$. Each time, we prune f_T using all

Algorithm 3 (Subroutine of Algorithm 1, ‘ABP-L’) Sparse approximation using LASSO

Input: Weight vector $w_j^{(k-1)}, \lambda$ ▷ Approximate the j -th neuron in k -th layer

- 1: Calculate $X_i^{(k)} = (f_1^{(k-1)}(X_i), \dots, f_{n_{k-1}}^{(k-1)}(X_i)), Y_i^{(k)} = g_j^{(k)}(X_i)$ for $i = 1, \dots, N$
- 2: Perform LASSO with $X_i^{(k)}, Y_i^{(k)}, i = 1, \dots, N$ and penalty parameter λ

Output: The retrained weights \tilde{w} from LASSO

Table 2: Mean compression ratio, pruning ratio, and MSE increase ratio for three methods with different hyper-parameters. The stand errors are reported in the parentheses.

Method	Compression Ratio	Pruning Ratio	MSE Increase Ratio
ABP-L ($\lambda = 10^{-3}$)	12.97 (0.22)	0.92 (0.00)	0.30 (0.02)
ABP-L ($\lambda = 10^{-4}$)	4.68 (0.07)	0.79 (0.00)	0.05 (0.00)
ABP-L ($\lambda = 10^{-5}$)	2.33 (0.04)	0.57 (0.01)	0.03 (0.00)
ABP-M ($\eta = 0, q = 0.3$)	1.52 (0.01)	0.34 (0.00)	0.01 (0.00)
ABP-M ($\eta = 0, q = 0.5$)	1.80 (0.02)	0.44 (0.01)	0.01 (0.00)
ABP-M ($\eta = 0, q = 0.7$)	2.10 (0.02)	0.52 (0.01)	0.02 (0.00)
ABP-M ($\eta = 0.1, q = 0.5$)	2.46 (0.03)	0.59 (0.01)	0.04 (0.01)
ABP-M ($\eta = 0.2, q = 0.5$)	3.12 (0.06)	0.68 (0.01)	0.17 (0.06)
ABP-M ($\eta = 0.3, q = 0.5$)	3.88 (0.08)	0.74 (0.01)	0.31 (0.09)
Mag ($p = 0.3$)	1.55 (0.00)	0.35 (0.00)	0.07 (0.01)
Mag ($p = 0.5$)	2.32 (0.01)	0.57 (0.00)	0.41 (0.06)
Mag ($p = 0.7$)	4.71 (0.10)	0.79 (0.00)	0.85 (0.10)

methods under different settings, and then evaluate the compression ratio, pruning ratio (both defined in Section 2), and the MSE increase ratio, which is the increase of MSE (the MSE difference between the pruned and the original networks) divided by the MSE of f_T . The procedure is replicated 20 times, and the results are summarized in Table 2.

From Table 2, both ‘ABP-M’ and ‘ABP-L’ have a significantly smaller accuracy degradation ratio compared to ‘Mag’, when the compression ratio is similar, which supports our intuition that an adaptive pruning scheme is more efficient than pruning a fixed portion of weights. Furthermore, ‘ABP-L’ outperforms ‘ABP-M’ in general.

For ‘ABP-M’, we note that the sparsity index-inspired pruning in Eq. (5) with $\eta = 0$ (or small) works very well for preserving accuracy, although it may be conservative in terms of the pruning ratio. Regarding the choice of q , a large q tends to increase the pruning ratio, but as long as η is chosen appropriately, q is relatively insensitive. As for ‘ABP-L’, a larger penalty parameter λ leads to a larger pruning ratio. Since both methods are one-time pruning, we suggest selecting hyper-parameters through cross-validation to balance deep pruning and accuracy protection. The code is included in the Appendix.

6 Conclusion

This paper provides a theory that characterizes the compressibility of a neural network in terms of the ℓ_q -norm of its weights. The ℓ_q -norm, or soft sparsity, can be used to compare the compressibility of different models with the same structure. Furthermore, it reveals the relationship between the degree of compression and accuracy degradation, which guides us in selecting an appropriate pruning ratio. The theory also motivates a new pruning scheme by finding a sparse linear approximation of neurons in a backward manner. The developed algorithms produce pruned models with significantly better performance than some standard pruning algorithms.

There are some limitations of the current study that we leave for future work. First, our pruning procedure is one-shot pruning, so we may rely on cross-validation to select the hyper-parameters for optimal performance. It will be interesting to study the stopping criterion and develop an iteratively pruning algorithm that can stop intelligently with maximal pruning ratio and little accuracy drop. Second, how to fairly compare the compressibility between two networks with different structures remains a challenge. Third, we focused exclusively on fully connected feed forward neural networks. Generalizations of our results to other networks are of interest.

Acknowledgements

This paper is based upon work supported by the Office of Naval Research under grant number N00014-21-1-2590.

Appendices

A Proof of Theorem 1

We first introduce the following lemma.

Lemma 2 (Gao et al. [2013]; Wang et al. [2014]). *Let f be any function with $\|f\|_2 < \infty$. Suppose $\mathcal{F} = \{f_1, \dots, f_M\}$ with $\max_{1 \leq j \leq M} \|f_j\|_2 < \infty$. For any $0 < q \leq 1$ and $t > 0$, define the $l_{q,t}$ -hull of \mathcal{F} to be the class of linear combinations of functions in \mathcal{F} with the ℓ_q -constraint*

$$\mathcal{F}_q(t) = \left\{ f_\theta = \sum_{j=1}^m \theta_j f_j : \|\theta\|_q \leq t, f_j \in \mathcal{F} \right\}.$$

For any $1 \leq m \leq M$ and $t > 0$, there exist a subset $J_m = \{s_1, \dots, s_m\}$ of $\{1, \dots, M\}$ and

$$f_{\theta^m} = \sum_{j=1}^m \theta_j^m f_{s_j} \in \mathcal{F}_{J_m} = \text{span of } f_j (j \in J_m)$$

with $\|\theta^m\|_1 \leq t$ such that

$$\|f - f_{\theta^m}\|_2 \leq \|f - f_{\theta^*}\|_2 + t C m^{\frac{1}{2} - \frac{1}{q}} \max_{1 \leq j \leq M} \|f_j\|_2, \quad (6)$$

where $f_{\theta^*} = \arg \min_{f_\theta \in \mathcal{F}_q(t)} \|f - f_\theta\|_2$ and C is an absolute constant.

The sketch proof idea of Theorem 1 is applying Lemma 2 from the last layer of f_T to the first layer step-wisely. We use the induction for the proof.

When $S = 1$, we try to approximate the last layer f_T , or $g_1^{(L)}$, using the linear combination of functions $\mathcal{F}^{(L-1)} = \{f_1^{(L-1)}, \dots, f_{n_{L-1}}^{(L-1)}\}$ in the $(L-1)$ -th layer. Invoke Lemma 2 with $m = m_{L-1}$, $q = q_{L-1}$ and $t = t_{L-1} = \max_{1 \leq i \leq n_{L-1}} \|w_i^{(L-1)}\|_{q_k}$, there exists $J_{m_{L-1}} = \{s_1, \dots, s_{m_{L-1}}\} \subset \{1, \dots, n_{L-1}\}$ and $f_T^{(1)} = \sum_{j=1}^{m_{L-1}} \tilde{w}_{1,s_j}^{(L-1)} f_{s_j}^{(L-1)}$ such that

$$\begin{aligned} \|f - f_T^{(1)}\|_2 &\leq \|f - f_{\theta^*}\|_2 + C t_{L-1} (m_{L-1})^{\frac{1}{2} - \frac{1}{q_{L-1}}} \max_{1 \leq j \leq n_{L-1}} \|f_j^{(L-1)}\|_2, \\ &\leq \|f - f_T\|_2 + C t_{L-1} (m_{L-1})^{\frac{1}{2} - \frac{1}{q_{L-1}}} \max_{1 \leq j \leq n_{L-1}} \|f_j^{(L-1)}\|_2. \end{aligned} \quad (7)$$

where

$$f_{\theta^*} = \arg \min_{f_\theta \in \mathcal{F}_{q_{L-1}}^{(L-1)}(t_{L-1})} \|f - f_\theta\|_2$$

and

$$\|(\tilde{w}_{1,s_1}^{(L-1)}, \dots, \tilde{w}_{1,s_{m_{L-1}}}^{(L-1)})\|_1 \leq t_{L-1}. \quad (8)$$

The last inequality of (7) holds since $f_T \in \mathcal{F}_{q_{L-1}}^{(L-1)}(t_{L-1})$.

For $S = 2$, we are going to approximate each $f_j^{(L-1)}$ by functions in the $(L-2)$ -th layer. In particular, we invoke Lemma 2 to $g_j^{(L-1)}$, the linear part of $f_j^{(L-1)}$, with $m = m_{L-2}$, $q = q_{L-2}$, $t = t_{L-2} = \max_{1 \leq i \leq n_{L-2}} \|w_i^{(L-2)}\|_{q_k}$ and $\mathcal{F}^{(L-2)} = \{f_j^{(L-2)}, 1 \leq j \leq n_{L-2}\}$. For any $1 \leq j \leq m_{L-1}$, there exists a subset $J_{m_{L-2}} = \{s_1, \dots, s_{m_{L-2}}\}$ (note that this subset varies for different j) and a sparse linear approximation

$$g_j^{(L-1),1} = \sum_{i=1}^{m_{L-2}} \tilde{w}_{j,s_i}^{(L-2)} f_{s_i}^{(L-2)},$$

such that

$$\begin{aligned} &\|g_j^{(L-1)} - g_j^{(L-1),1}\|_2 \\ &\leq \|g_j^{(L-1)} - g_{j,\theta^*}^{(L-1)}\|_2 + C t_{L-2} (m_{L-2})^{\frac{1}{2} - \frac{1}{q_{L-2}}} \max_{1 \leq j \leq n_{L-2}} \|f_j^{(L-2)}\|_2 \\ &\leq C t_{L-2} (m_{L-2})^{\frac{1}{2} - \frac{1}{q_{L-2}}} \max_{1 \leq j \leq n_{L-2}} \|f_j^{(L-2)}\|_2, \end{aligned} \quad (9)$$

where $g_{j,\theta^*}^{(L-1)} = \arg \min_{g_\theta \in \mathcal{F}_{q_{L-2}}^{(L-2)}(t_{L-2})} \|g_j^{(L-1)} - g_\theta\|_2$. The last inequality is due to $g_j^{(L-1)} \in \mathcal{F}_{q_{L-2}}^{(L-2)}(t_{L-2})$, which implies $\|g_j^{(L-1)} - g_{j,\theta^*}^{(L-1)}\|_2 = 0$.

Let $f_j^{(L-1),1} = \sigma(g_j^{(L-1),1})$ be the approximation function for $f_j^{(L-1)}$ after one step approximation. Plugging in this into $f_T^{(1)}$, we obtain the approximation of f_T after two steps as

$$f_T^{(2)} = \sum_{j=1}^{m_{L-1}} \tilde{w}_{1s_j}^{(L-1)} f_{s_j}^{(L-1),1},$$

and the approximation error is

$$\|f - f_T^{(2)}\|_2 \leq \|f - f_T^{(1)}\|_2 + \|f_T^{(1)} - f_T^{(2)}\|_2,$$

where

$$\begin{aligned} \|f_T^{(1)} - f_T^{(2)}\|_2 &= \left\| \sum_{j=1}^{m_{L-1}} \tilde{w}_{1s_j}^{(L-1)} (f_{s_j}^{(L-1)} - f_{s_j}^{(L-1),1}) \right\|_2 \\ &\leq \sum_{j=1}^{m_{L-1}} |\tilde{w}_{1s_j}^{(L-1)}| \|f_{s_j}^{(L-1)} - f_{s_j}^{(L-1),1}\|_2 \\ &= \sum_{j=1}^{m_{L-1}} |\tilde{w}_{1s_j}^{(L-1)}| \|\sigma(g_{s_j}^{(L-1)}) - \sigma(g_{s_j}^{(L-1),1})\|_2 \\ &\leq \rho \sum_{j=1}^{m_{L-1}} |\tilde{w}_{s_j}^{(L-1)}| \|g_{s_j}^{(L-1)} - g_{s_j}^{(L-1),1}\|_2 \end{aligned}$$

$$\text{Eq.s (8) and (9)} \leq \rho t_{L-1} t_{L-2} C(m_{L-2})^{\frac{1}{2} - \frac{1}{q_{L-2}}} \max_{1 \leq j \leq n_{L-2}} \|f_j^{(L-2)}\|_2.$$

This completes the case for $S = 2$. After S steps, we have approximated k steps for neurons or functions in the $(L - S + k)$ -th layer for $1 \leq k \leq S$. Let $g_j^{(k),s}$ be the $g_j^{(k)}$ approximated s time and $g_j^{(k),0} = g_j^{(k)}$. In particular,

$$f_j^{(k),s} = \sigma(g_j^{(k),s}), \quad g_j^{(k),s+1} = \sum_{i=1}^{m_{k-1}} \tilde{w}_{j,s_i}^{(k-1)} f_{s_i}^{(k-1),s}, \quad 0 \leq s \leq k < L. \quad (10)$$

For $S \geq 3$, suppose we have finished $S - 1$ steps, now we need to approximate functions in the $(L - S + 1)$ -th layer. With the same argument as the case $S = 2$, for any $1 \leq j \leq n_{L-S+1}$, we have a sparse linear approximation for $g_j^{(L-S+1)}$ as

$$g_j^{(L-S+1),1} = \sum_{i=1}^{m_{L-S}} \tilde{w}_{j,s_i}^{(L-S)} f_{s_i}^{(L-S)},$$

such that

$$\|g_j^{(L-S+1)} - g_j^{(L-S+1),1}\|_2 \leq C t_{L-S} (m_{L-S})^{\frac{1}{2} - \frac{1}{q_{L-S}}} \max_{1 \leq j \leq n_{L-S}} \|f_j^{(L-S)}\|_2,$$

with $\sum_{i=1}^{m_{L-S}} |\tilde{w}_{j,s_i}^{(L-S)}| \leq t_{L-S}$.

Therefore, the approximation error for the functions of the nodes in the $(L - S + 1)^{th}$ layer after one step approximation is bounded by

$$\begin{aligned} \|f_j^{(L-S+1)} - f_j^{(L-S+1),1}\|_2 &\leq \rho \|g_j^{(L-S+1)} - g_j^{(L-S+1),1}\|_2 \\ &\leq \rho t_{L-S} C(m_{L-S})^{\frac{1}{2} - \frac{1}{q_{L-S}}} \max_{1 \leq j \leq n_{L-S}} \|f_j^{(L-S)}\|_2. \end{aligned} \quad (11)$$

Furthermore, for $1 \leq k \leq S-2$, we have

$$\begin{aligned}
& \max_{1 \leq j \leq n_{L-S+k-1}} \left\| f_j^{(L-S+k+1),k+1} - f_j^{(L-S+k+1),k} \right\|_2 \\
&= \max_{1 \leq j \leq n_{L-S+k-1}} \left\| \sigma(g_j^{(L-S+k+1),k+1}) - \sigma(g_j^{(L-S+k+1),k}) \right\|_2 \\
&\leq \rho \max_{1 \leq j \leq n_{L-S+k-1}} \left\| g_j^{(L-S+k+1),k+1} - g_j^{(L-S+k+1),k} \right\|_2 \\
&\leq \rho \max_{1 \leq j \leq n_{L-S+k-1}} \left[\sum_{i=1}^{m_{L-S+k}} |\tilde{w}_{j,s_i}^{(L-S+k)}| \left\| f_{s_i}^{(L-S+k),k} - f_{s_i}^{(L-S+k),k-1} \right\|_2 \right] \\
&\leq \rho t_{m_{L-S+k}} \max_{1 \leq j \leq n_{L-S+k}} \left\| f_j^{(L-S+k),k} - f_j^{(L-S+k),k-1} \right\|_2.
\end{aligned} \tag{12}$$

Repeating Eq. (12) from $k = S-2$ to $k = 1$, along with Eq. (11), we have

$$\left\| f_j^{(L-1),S-1} - f_j^{(L-1),S-2} \right\|_2 \leq \rho^{S-1} t_{L-2} \dots t_{L-S} C(m_{L-S})^{\frac{1}{2} - \frac{1}{q_{L-S}}} \max_{1 \leq j \leq n_{L-S}} \left\| f_j^{(L-S)} \right\|_2.$$

Finally,

$$\begin{aligned}
\left\| f_T^{(S)} - f_T^{(S-1)} \right\|_2 &= \left\| \sum_{j=1}^{m_{L-1}} \tilde{w}_{1s_j}^{(L-1)} (f_{s_j}^{(L-1),S-1} - f_{s_j}^{(L-1),S-2}) \right\|_2 \\
&\leq \sum_{j=1}^{m_{L-1}} |\tilde{w}_{1s_j}^{(L)}| \left\| f_{s_j}^{(L),S-1} - f_{s_j}^{(L),S-2} \right\|_2 \\
&\leq t_{L-1} \left\| f_{s_j}^{(L),S-1} - f_{s_j}^{(L),S-2} \right\|_2 \\
&\leq \rho^{S-1} t_{L-1} \dots t_{L-S} C(m_{L-S})^{\frac{1}{2} - \frac{1}{q_{L-S}}} \max_{1 \leq j \leq n_{L-S}} \left\| f_j^{(L-S)} \right\|_2,
\end{aligned}$$

which completes the proof by induction.

B Sparsity index

For $q \in (0, 1)$ and a vector $w \in \mathbb{R}^d$, we define the *sparsity index* (SI) as

$$\text{SI}(w) = \|w\|_1 / \|w\|_q.$$

We show some basis properties of the sparsity index. By Jensen's inequality, we have

$$d^{-\frac{1}{q}} \|w\|_q = \left(d^{-1} \sum_{i=1}^d |w_i|^q \right)^{\frac{1}{q}} \leq \frac{1}{d} \sum_{i=1}^d |w_i| = \frac{1}{d} \|w\|_1,$$

so

$$\|w\|_q \leq d^{\frac{1}{q}-1} \|w\|_1.$$

Furthermore, it is well-known that $\|w\|_1 \leq \|w\|_q$. As a result, $\text{SI}(w) \in [d^{1-\frac{1}{q}}, 1]$, and a larger SI indicates a sparser vector.

For a near-hard sparsity scenario, let I_m be the largest m components of w , and assume η is a constant such that $\sum_{i \notin I_m} |w_i|^q \leq \eta \sum_{i \in I_m} |w_i|^q$, we have

$$\begin{aligned}
\|w\|_q &= \left(\sum_{1 \leq i \leq d} |w_i|^q \right)^{\frac{1}{q}} = \left(\sum_{i \in I_m} |w_i|^q + \sum_{i \notin I_m} |w_i|^q \right)^{\frac{1}{q}} \\
&\leq \left(\sum_{i \in I_m} |w_i|^q + \eta \sum_{i \in I_m} |w_i|^q \right)^{\frac{1}{q}} = \left(\sum_{i \in I_m} |w_i|^q \right)^{\frac{1}{q}} (1 + \eta)^{\frac{1}{q}} \\
&\leq \left(\sum_{i \in I_m} |w_i| \right) m^{\frac{1}{q}-1} (1 + \eta)^{\frac{1}{q}} \leq \|w\|_1 m^{\frac{1}{q}-1} (1 + \eta)^{\frac{1}{q}}.
\end{aligned}$$

Rearranging the above inequality gives

$$m \geq [\text{SI}(w)]^{-q/(1-q)} (1 + \eta)^{-1/(1-q)}.$$

C Proof of Theorem 4

We only need to prove the following counter part of the Lemma 2. The rest of the proof exactly follows the proof of Theorem 1.

Lemma 3. *Let f be any function with $\|f\|_2 < \infty$. Suppose $\mathcal{F} = \{f_1, \dots, f_M\}$ with $\max_{1 \leq j \leq M} \|f_j\|_2 < \infty$. For any $0 < q \leq 1$ and $t > 0$, define the $l_{q,t}$ -hull of \mathcal{F} to be the class of linear combinations of functions in \mathcal{F} with the l_q -constraint*

$$\mathcal{F}_q(t) = \left\{ f_\theta = \sum_{j=1}^m \theta_j f_j : \|\theta\|_q \leq t, f_j \in \mathcal{F} \right\}.$$

For any $1 \leq m \leq M$ and $t = \|w\|_q$, let $f_{\theta^*} = \arg \min_{f_\theta \in \mathcal{F}_q(t)} \|f - f_\theta\|_2 = \sum_{j=1}^m w_j f_j$, $J_m = \{j : |w_j| > tm^{-1/q}\}$, and $\hat{f} = \sum_{j \in J_m} w_j f_j$. Then, we have

$$\|f - \hat{f}\|_2 \leq \|f - f_{\theta^*}\|_2 + tm^{1-1/q} \max_{1 \leq j \leq M} \|f_j\|_2. \quad (13)$$

Additionally, $\sum_{j \in J_m} |w_j| \leq t$ and the cardinality of J_m is no more than m .

Proof. First, we know $\sum_{j \in J_m} |w_j| \leq \|w\|_1 \leq \|w\|_q = t$, thus the cardinality of J_m is no more than m since

$$\sum_{j \in J_m} t^q/m \leq \sum_{j \in J_m} |w_j|^q \leq \|w\|_q^q = t^q.$$

Second, we have

$$\sum_{j \notin J_m} |w_j| \leq \sum_{j \notin J_m} |w_j|^q (tm^{-1/q})^{1-q} \leq \|w\|_q^q (tm^{-1/q})^{1-q} = tm^{1-1/q},$$

hence

$$\|f_{\theta^*} - \hat{f}\|_2 = \left\| \sum_{j \notin J_m} w_j f_j \right\|_2 \leq \sum_{j \notin J_m} |w_j| \max_{1 \leq j \leq M} \|f_j\|_2 \leq tm^{1-1/q} \max_{1 \leq j \leq M} \|f_j\|_2.$$

We finish the proof by plugging in the above inequality into the following triangle inequality

$$\|f - \hat{f}\|_2 \leq \|f - f_{\theta^*}\|_2 + \|f_{\theta^*} - \hat{f}\|_2. \quad \square$$

References

- Sanjeev Arora, Rong Ge, Behnam Neyshabur, and Yi Zhang. Stronger generalization bounds for deep nets via a compression approach. In *International Conference on Machine Learning*, pages 254–263. PMLR, 2018.
- Çenk Baykal, Lucas Liebenwein, Igor Gilitschenski, Dan Feldman, and Daniela Rus. Data-dependent coresets for compressing neural networks with applications to generalization bounds. *arXiv preprint arXiv:1804.05345*, 2018.
- Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901, 2020.
- Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.
- Luc Devroye, László Györfi, and Gábor Lugosi. *A probabilistic theory of pattern recognition*, volume 31. Springer Science & Business Media, 2013.
- Jonathan Frankle and Michael Carbin. The lottery ticket hypothesis: Finding sparse, trainable neural networks. *arXiv preprint arXiv:1803.03635*, 2018.
- Fuchang Gao, Ching-Kang Ing, and Yuhong Yang. Metric entropy and sparse linear approximation of l_q -hulls for $0 < q \leq 1$. *Journal of Approximation Theory*, 166:42–55, 2013.
- Masafumi Hagiwara. Removal of hidden units and weights for back propagation networks. In *Proceedings of 1993 International Conference on Neural Networks (IJCNN-93-Nagoya, Japan)*, volume 1, pages 351–354. IEEE, 1993.

- Song Han, Huizi Mao, and William Dally. Deep compression: Compressing deep neural networks with pruning, trained quantization and huffman coding. *arXiv preprint arXiv:1510.00149*, 2015.
- Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Identity mappings in deep residual networks. In *European conference on computer vision*, pages 630–645. Springer, 2016.
- Yihui He, Xiangyu Zhang, and Jian Sun. Channel pruning for accelerating very deep neural networks. In *Proceedings of the IEEE international conference on computer vision*, pages 1389–1397, 2017.
- Torsten Hoefler, Dan Alistarh, Tal Ben-Nun, Nikoli Dryden, and Alexandra Peste. Sparsity in deep learning: Pruning and growth for efficient inference and training in neural networks. *Journal of Machine Learning Research*, 22(241): 1–124, 2021.
- Hengyuan Hu, Rui Peng, Yu-Wing Tai, and Chi-Keung Tang. Network trimming: A data-driven neuron pruning approach towards efficient deep architectures. *arXiv preprint arXiv:1607.03250*, 2016.
- Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. *Advances in neural information processing systems*, 25, 2012.
- Yann LeCun, John Denker, and Sara Solla. Optimal brain damage. *Advances in neural information processing systems*, 2, 1989.
- Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.
- Yann LeCun, Yoshua Bengio, and Geoffrey Hinton. Deep learning. *nature*, 521(7553):436–444, 2015.
- Namhoon Lee, Thalaiyasingam Ajanthan, and Philip HS Torr. Snip: Single-shot network pruning based on connection sensitivity. *arXiv preprint arXiv:1810.02340*, 2018.
- Jian-Hao Luo, Jianxin Wu, and Weiyao Lin. Thinet: A filter level pruning method for deep neural network compression. In *Proceedings of the IEEE international conference on computer vision*, pages 5058–5066, 2017.
- Eran Malach, Gilad Yehudai, Shai Shalev-Schwartz, and Ohad Shamir. Proving the lottery ticket hypothesis: Pruning is all you need. In *International Conference on Machine Learning*, pages 6682–6691. PMLR, 2020.
- Ben Mussay, Margarita Osadchy, Vladimir Braverman, Samson Zhou, and Dan Feldman. Data-independent neural pruning via coresets. *arXiv preprint arXiv:1907.04018*, 2019.
- Laurent Orseau, Marcus Hutter, and Omar Rivasplata. Logarithmic pruning is all you need. *Advances in Neural Information Processing Systems*, 33:2925–2934, 2020.
- R Kelley Pace and Ronald Barry. Sparse spatial autoregressions. *Statistics & Probability Letters*, 33(3):291–297, 1997.
- Alec Radford, Karthik Narasimhan, Tim Salimans, and Ilya Sutskever. Improving language understanding by generative pre-training. 2018.
- Joseph Redmon, Santosh Divvala, Ross Girshick, and Ali Farhadi. You only look once: Unified, real-time object detection. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 779–788, 2016.
- Mohammadreza Soltani, Suyu Wu, Jie Ding, Robert Ravier, and Vahid Tarokh. On the information of feature maps and pruning of deep neural networks. In *2020 25th International Conference on Pattern Recognition (ICPR)*, pages 6988–6995. IEEE, 2021.
- Robert Tibshirani. Regression shrinkage and selection via the lasso. *Journal of the Royal Statistical Society: Series B (Methodological)*, 58(1):267–288, 1996.
- Zhan Wang, Sandra Paterlini, Fuchang Gao, and Yuhong Yang. Adaptive minimax regression estimation over sparse l_q -hulls. *The Journal of Machine Learning Research*, 15(1):1675–1711, 2014.
- Mao Ye, Chengyue Gong, Lizhen Nie, Denny Zhou, Adam Klivans, and Qiang Liu. Good subnetworks provably exist: Pruning via greedy forward selection. In *International Conference on Machine Learning*, pages 10820–10830. PMLR, 2020.
- Shuai Zhang, Meng Wang, Sijia Liu, Pin-Yu Chen, and Jinjun Xiong. Why lottery ticket wins? a theoretical perspective of sample complexity on sparse neural networks. *Advances in Neural Information Processing Systems*, 34, 2021.