

Intractable Group-theoretic Problems Around Zero-knowledge Proofs

Cansu Betin Onur*
Institute of Applied Mathematics
Middle East Technical University
06800 Ankara Turkey

Abstract

While the amount of data created and stored continues to increase at striking rates, data protection and concealment increases its importance as a field of scientific study that requires more effort. It is essential to protect critical data at every stage while it is being stored and transferred. One cryptographic tool that is of interest and can be widely used in this medium is zero-knowledge proof systems. This cryptographic structure allows one party to securely guarantee the authenticity and accuracy of the data at hand, without leaking any confidential information during communication. The strength of zero-knowledge protocols is mostly based on a few hard-to-solve problems. There is a need to design more secure and efficient zero-knowledge systems. This need brings the necessity of determining suitable difficult problems to design secure zero-knowledge schemes. In this study, after a brief overview of zero-knowledge proof systems, the relationship of these structures to group-theoretic algorithmic problems and an annotated list of intractable algorithmic problems in group theory are given.

*EMail: cbetin@metu.edu.tr

Contents

1	Introduction	3
2	Zero Knowledge Proof Systems	5
2.1	Basic Concept	5
2.2	A Brief History of ZKP	6
2.3	Group Theory in ZKP	7
3	Group Theoretic Algorithmic Problems	8
3.1	Basic Decision Problems Defined on Groups	9
3.2	Word Problem	10
3.3	Generalizations of the Word Problem	11
3.4	Knapsack type problems:	12
3.5	The Conjugacy Problem	13
3.6	The Generalizations of The Conjugacy Problem	15
3.7	Intersection Problems	17
3.8	Miscellaneous Problems	18
3.9	The Post's Correspondence Problem in Groups	19
3.10	The Endomorphism Problem	19
3.11	The Group Isomorphism Problem	20
3.12	The Hidden Subgroup Problem	20
4	Conclusion	23

1 Introduction

Data privacy and security are of paramount importance. While keeping and transferring critical data, it is a must to protect it at every stage. For example, the General Data Protection Regulation (GDPR) entered into force in Europe on May 25, 2018. Thanks to the GDPR, privacy has become a fundamental right of European citizens. When personal data needs to be shared, they must be anonymized or encrypted. In financial, health, demographic applications where data must be processed or shared by more than one legal entity, special precautions should be taken. Even for research purposes, data needs to be protected to ensure the fundamental rights of individuals. When data has to cross borders, the process becomes much more complex due to the heterogeneity of countries' policies; this requires adaptability of privacy measures taken based on the policies of different countries. We call this challenge as data sharing challenge that can be solved even without sharing data in some applications.

Zero-knowledge proof (ZKP) systems are a technology that can be vastly employed for privacy preservation and data ownership. In a data-based world, we are living in, privacy can be maintained by ZKP systems using cryptographic algorithms that help principals verify the veracity of a piece of information without sharing the data. The data-sharing challenge mentioned above can be addressed to an extent with zero-knowledge proofs. Validating data without revealing them has many applications, such as identification, key exchange, digital signature, the design of anonymous cryptocurrencies and more. Quantum computers, absence of standards, and the computational costs are the barriers to ZKP.

Classical cryptographic primitives will be insecure after the realization of quantum computers, machines that exploit the quantum mechanical phenomenon to solve intractable or difficult problems for conventional computers. Should a large-scale quantum computer be built, the difficult problems we employ for building the security protocols will be easily solved, and the protocols will be broken seriously, compromising the confidentiality and integrity of communication systems. The strength of zero-knowledge protocols is mostly based on a few hard-to-solve problems such as discrete logarithm problem or factoring large numbers that we will present in Section 3. These widely-used problems can be solved efficiently (quickly) by using quantum computers. Therefore, the cryptographic protocols relying on these presently-difficult problems will be broken. We will need secure zero-knowledge protocols without leaking any secret information during the communication. This need brings the necessity of determining suitable dif-

difficult problems to design secure zero-knowledge schemes. In 1991, Goldreich, Micali, and Wigderson showed that any NP problem could be used to implement a zero-knowledge proof system [1]. In this article, we explore candidate group theoretic algorithmic problems for a secure and efficient zero-knowledge proof protocol.

The paper is organized as follows. In Section 2, we give a background on zero-knowledge proof systems and its relation with group theory. Section 3 is devoted to group theoretic algorithmic problems. Namely, we overview the basic decision problems defined on groups; word, conjugacy and isomorphism problems with their generalizations such as subgroup membership, order, power, root, Knapsack types (subset sum, knapsack, submonoid membership), twisted conjugacy, decomposition, double coset membership, factorization, Diffie-Hellman-like conjugacy, power conjugacy, intersection problems (subgroup intersection, coset intersection, setwise stabilizer). The problems centralizer, centralizer in another subgroup, set transporter, restricted graph automorphism, which we consider worthy to be listed, are also given in this section. The interesting problems Post's correspondence, endomorphism, hidden subgroup and hidden shift in cryptographic structure design are also discussed in this section. Finally, Section 4 provides a summary and concluding remarks.

2 Zero Knowledge Proof Systems

In this section, an overview of zero knowledge systems is given. The concern of group theoretic problems in zero knowledge proofs is given intuitively.

2.1 Basic Concept

Zero-knowledge proofs (ZKP) are cryptographic protocols where a party (called the prover) may convince the other party (called the verifier) that a certain statement is true revealing no additional information about that knowledge [2]. The requirements for ZKP are

- *Completeness*: Whenever the statement is TRUE, the prover convinces the verifier.
- *Soundness*: Whenever the statement is FALSE, a dishonest prover will not be able to convince the verifier.
- *Zero-knowledge*: The verifier will not learn anything from the proof procedure but the statement is true.

The zero knowledge property, the verifier will not gain any extra information from the interaction, is formulated by means of a simulator (a probabilistic polynomial-time algorithm). The simulation paradigm [3] postulates that “whatever a party can do by itself cannot be considered a gain from interaction with the outside.” The simulator’s output and the verifier’s output are expected to be indistinguishable.

For practical purposes, the definition of zero knowledge is relaxed by allowing the simulator to fail. Mainly there are three variants of zero knowledge property; **perfect** (no information is leaked), **statistical** (some information is leaked to the verifier but it is a negligible amount regardless of the computational resources the verifier) and **computational** (the amount of information leaked is negligible if the verifier is a probabilistic polynomial-time Turing machine). That is to say, in perfect and statistical (a.k.a. almost-perfect) zero knowledge, it is not possible to notice the difference in outputs of the verifier and the simulator in information-theoretic sense. On the other hand, in computational zero-knowledge this distinction cannot be done not theoretically but by any computationally efficient procedure. A zero-knowledge protocol without any of these attributes is used for the most general class computational zero-knowledge.

2.2 A Brief History of ZKP

Zero-knowledge proof systems are a technology that can be vastly employed for privacy preservation and data ownership. Goldwasser, Micali and Rackoff introduced this concept in [4]. Originally ZKP systems are designed to be interactive; the messages are sent between the prover and the verifier back and forth. Efficiency considerations leads a variant of ZKP that require no interaction, namely non-interactive zero-knowledge proofs (NIZKP). In this case, the prover conveys only to the verifier.

Blum et al. showed that a common reference string (CRS) shared by a trusted party to the prover and the verifier is sufficient to achieve computational-NIZKP [5]. An alternative to the CRS model is the Random Oracle (RO) model which assumes that a perfect random function is available to both the prover and the verifier. Fiat and Shamir [6] introduced a method that can transform any sigma protocol into a NIZK proof by the use of a hash function as a simulator. Goldreich and Oren showed that NIZKP is impossible to achieve (in the standard model) without any further assumption, like the CRS model or the RO model [7].

In the literature, the most popular protocol which is one of the first examples of zero knowledge proof is Fiat-Shamir (1987) protocol. This protocol is based on the RSA encryption system. In other words, it is based on the difficulty of the prime factorization problem. Since then, a variety of protocols were developed following the Fiat-Shamir protocol such as the Chaum-Evertse-van de Graaf [8], the Feige-Fiat-Shamir [9], the Beth [10], the Guillou-Quisquater [11], the Desmedt [12] and the Schnorr [13] protocol. These protocols rely on computational hardness of either RSA algorithm, finding square-root in composite modulo with unknown factorization or discrete logarithm problem.

State-of-the-art new generation ZKP systems are mainly zk-SNARKs [14], BulletProofs [15], zk-STARKs [16] and “MPC-in-the-head” approach [17]. These are non-interactive or can be realized as non-interactive through Fiat-Shamir transform. Constructions of SNARKs mostly rely on bilinear maps or lattices. They require trusted setup. An improvement from SNARKs to STARKs is removing the need for a trusted setup. STARKs rely on collision-resistant hash functions. STARK friendly hash function [18] [19] is the subject of extensive research. A prominent disadvantage of STARKs is the proof size compared to SNARKs. In the MPC-in-the-head approach, a ZKP-protocol designed for NP-relations from secure multiparty computation (MPC) protocols. Bulletproof relies on the hardness of discrete logarithm problem and has no trusted setup.

2.3 Group Theory in ZKP

In 1991, Goldreich, Micali, and Wigderson showed that any NP problem could be used to implement a zero-knowledge proof system [1], and this result made ZKP central. A decision problem is in NP when a possible solution to the problem is given, one can efficiently (in polynomial time) check whether it is correct. Note that finding a solution is not always easy for an NP problem, but verification is straightforward.

Studies in the literature related to the application of group theoretic problems in ZKP either provide complexity analysis and classification of problems, or protocol designs. For instance, Fenner and Zhang [20] showed that the group intersection and double coset membership problems have honest verifier zero knowledge proof systems. In particular, they proved that these problems are in the statistical zero-knowledge proof class. Arvind and Das classified several algorithmic problems in group theory with perfect and statistical zero-knowledge proofs [21]. They showed that the permutation group problems Coset Intersection, Double Coset Membership, Group Conjugacy are in perfect zero-knowledge class. Sdroievski et al. showed that the hidden subgroup problem has a statistical zero-knowledge proof [22].

In the next section we enumerate group theoretic algorithmic problems as candidates for ZKP protocols.

3 Group Theoretic Algorithmic Problems

The security of open cryptographic structures relies heavily on the difficulty of the underlying mathematical problem. Commonly used among these problems are the discrete logarithm problem and the prime factorization problem of an integer. Since the subject of this study is group theoretic problems, we will not examine the later problem.

Discrete Logarithm Problem (DLP) Given a finite single-generator (cyclic) group $G = \langle g \rangle$ and an element h from this group. The question is finding an integer x that will satisfy the equality $h = g^x$.

Note that the definition is written in multiplicative notation. One may prefer to use additive notation instead, as in the case G is the group of multiples of a point P on an elliptic curve defined over a finite field.

The first public key cryptosystem, the Diffie-Hellman key exchange, is based on the computational difficulty of DLP [23]. Following this protocol, RSA [24] and ElGamal [25] cryptosystems were developed in chronological order. While RSA is based on the difficulty of prime factorization of an integer, ElGamal again uses the discrete logarithm problem. Although, from a group theoretical perspective, two cyclic groups of the same order are isomorphic, the existence of an algorithm that efficiently computes the discrete logarithm problem in one of these groups does not imply that there is an algorithm which solves the problem efficiently in the other group. For this reason, the trend to develop efficient cryptographic methods where discrete logarithms are difficult on a cyclic group has been adopted by various researchers. For example; cyclic subgroups of matrix groups (the problem is not more difficult on these group than on the multiplicative group of finite fields [26]), critical groups of graphs (shown to be unsafe [27], [28]), the group of multiples of a point on an elliptic curve defined over a finite field is used. Among these examples, elliptic curve cryptography is an actively studied research area, distinguished from other candidates by its efficiency in application and high security in small key size.

DLP draws attention in the literature with its structure suitable for creating efficient zero knowledge systems. Discrete-log based ZKP schemes include the Groth's protocol [29], the work of Bayer and Groth [30], a scheme of Bootle et al. [31] and Bulletproof [15].

The variant of DLP involved in the Diffie-Hellman key exchange protocol later named as Diffie-Hellman Problem.

Diffie-Hellman Problem (DHP) Given a finite cyclic group $G = \langle g \rangle$ and two elements $h = g^x, k = g^y$ from this group where x and y are randomly chosen secret integers. Find the element $s = g^{xy}$.

The above problem is sometimes called as the Computational Diffie-Hellman problem to distinguish it from its decision version.

Decision Diffie-Hellman Problem Given a cyclic group $G = \langle g \rangle$ of order n and three elements h, k, s from this group satisfying $h = g^x, k = g^y, s = g^z$ where x, y, z are secret integers. Determine whether $z = xy \pmod n$.

In [32], Koblitz and Menezes examine several variants of and the reductions between the DHP and DLP. Clearly, to solve DLP implies the ability to solve DHP. Also over many groups the DHP is almost as hard as the DLP [33]. In the literature, groups on which cryptographic protocols are defined are called *platform groups*. On a well chosen platform group, DLP and DHP are classical intractable problems.

In 1994, Shor [34] developed a quantum algorithm that solves the factorization and discrete logarithm problems in polynomial time. Following this development, the necessity of creating alternative methods to design encryption systems has emerged. One of these methods is to develop non-commutative cryptographic structures. The complexity of algorithmic problems defined on non-commutative groups has made these algebraic structures suitable tools for cryptographic protocols.

3.1 Basic Decision Problems Defined on Groups

A problem that can be answered with Yes or No is called **Decision Problem**. Three basic decision problems defined on groups were proposed by Max Dehn in 1911 [35]. These problems are called word problem, conjugate problem and isomorphism problem.

- Word decision problem: Let a group G with finite presentation and $g \in G$ be given. Decide if $g = 1$.
- Conjugacy decision problem: Given a finitely presented group G and two elements a, b from G . Determine whether a and b are conjugate in G ? In other words, is there $x \in G$ that satisfies $x^{-1}ax = b$?
- (Group) Isomorphism decision problem: Let two groups with finite presentations G_1, G_2 be given. Decide if these groups are isomorphic.

These problems, which are defined on groups with finite presentation, can be generalized to countable groups by numbering their generators. In the most general sense, Dehn's decision problems given above are undecidable.

In other words, they are not algorithmically solvable (Novikov [36], Adian [37])

In the case where the answer to the decision problem is yes, the question of searching for values satisfying the questioned property is called **Search Problem**. Search problems have a large place in the construction of cryptographic structures. Below, the problems are defined in the categories of decision problems and search problems and their place in the literature is given.

3.2 Word Problem

We have defined the word decision problem above and stated that there is no algorithm to solve the word problem in general. On the other hand, group classes where the word problem is NP (can be solved in polynomial time with a non-deterministic Turing machine) are quite broad. For example, finitely generated matrix groups defined on a field, polycyclic groups, finitely generated metabelian groups, Automatic groups, Thompson group, finitely generated subgroups of diagram groups, free Burnside groups $B(m, n)$ for a large enough number n is in this class [38]. There are also groups with finite presentations on which the word problem is NP-complete [39] or coNP-complete. Birget et al [38] obtained a group theoretic characterization of NP-problems. They observed that the word problem on a finitely generated group G is in NP if and only if the group G can be embedded into a finitely presented group with polynomial Dehn function.

Word search problem: Let it be known that $g = 1$ for $g \in G$ in a given group G . Express this element g as the product of the conjugates of the descriptive relations given in the group presentation.

To the best of our knowledge, there is no ZKP relying on the word problem. The first attempt to establish an encryption system using the word problem was given in 1984 by Magyarik-Wagner [40]. This approach is also the first example of using non-commutative groups. The method used here is based on a problem that is actually easier to secure since it restricts the word problem. In [41], Vasco and Steinwandt show that for the group proposed the secret key can be found by monitoring the performance of a legitimate buyer, on the other hand, it is emphasized that the word problem in groups with finite presentation is an attractive candidate for deriving one-way functions and thus establishing a public key system. Then, Birget et al. [42] analyzed the Magyarik-Wagner system and proposed a new public-key encryption system inspired by it. In the new method, the deciphering phase uses the group actions on the words.

One of the early attempts to use the problem was to obtain a one-way function by repeatedly adding new relations to the word produced by the two elements[43]. This method has remained cumbersome in practice.

The system proposed by Garzon and Zalcstein used the word problem on Grigorchuk groups. It is similar to the Magyarik-Wagner system. The security of this example, which is the first application of the Grigorchuk groups in cryptography, is known to be weak.[44]

Panagopoulos [45] has developed a (t, n) -threshold secret sharing scheme using group presentations and the word problem. A (t, n) -threshold secret sharing is a method of distributing a confidential information to n participants in a way that while any t participants can reach the secret, less than t participants cannot. In the first part of the two-stage scheme, the confidential information to be used in solving the word problem, such as the defining relations of the group, is distributed to the participants over the secure channel. In the second stage, the actual secret is sent over open channels. The prominent difference of this method from the previously developed (t, n) -threshold secret sharing schemes is that the real secret does not have to be transmitted over the secure channel. Habeeb et al. [46] make this method more practical and gave schemes for sharing confidential information based on group presentations and word problem.

3.3 Generalizations of the Word Problem

Various generalizations of the word problem have been presented in the literature. The main ones are subgroup membership problem, order problem, power problem and root problem.

- **The Subgroup Membership Problem:**

Given a group G , an element $g \in G$ and a finitely generated subgroup $H = \langle h_1, \dots, h_k \rangle$ of G .

Decision problem: Decide whether g is an element of H .

Search problem: It is known that $g \in H$. Express g as a product of powers of generators of H .

This problem is also known as **the uniform generalized word problem** or **occurrence problem**.

- **The Order Problem:** McCool

Given a group G in terms of generators and defining relations and an element $g \in G$.

Decision problem: Determine whether g has a finite order.

Search problem: It is known that g has a finite order. Find the order of g .

- **The Power Problem:** McCool

Given a group G and two elements $x, y \in G$.

Decision problem: Determine whether there exists an integer n that satisfies $y = x^n$?

Search problem: It is known that there is an integer n that satisfies $y = x^n$. Find a value of n that satisfies this equation.

The power problem is a special case of the subgroup membership problem. This is clear when the subgroup is taken as $H = \langle x \rangle$.

- **The Root Problem:** Lipschutz-Miller

If the pair a, b given from a group G satisfies $b = a^n$ for a natural number n , then the element a is said to be the n th root of b . Given a group G , an element $b \in G$ and a natural number n .

Decision problem: Is there an element a in the group G that satisfies $b = a^n$?

Search problem: It is known that such element exists. Find an element a in group G that satisfies $b = a^n$.

Word problem can be reduced from the order problem by considering the order of the element as one. Again, taking the element $x = 1$ in the power problem and choosing $n = 0$ in the root problem, one gets the word problem [47]. These generalizations are harder than the word problem [48], [49], [47].

In [50] a key exchange protocol is given based on the difficulty of finding the square root in 2-Engel groups. 2-Engel groups are nilpotent groups. The difficulty of the n th root problem in nilpotent groups is given in [50] by Sze et al. As emphasized here, the difficulty of the problem in nilpotent groups comes from the difficulty of embedding the studied group in the group of upper-triangular matrices defined on rational numbers.

A zero knowledge scheme relying on the root problem [51] is mentioned in 3.5.

3.4 Knapsack type problems:

The knapsack problem is one of the most well-known NP-complete problems. The classic knapsack and subset sum problems are discrete optimization problems concerning integers. Myasnikov et al. [52] generalized these problems to arbitrary groups by calling them knapsack-type problems. They

examined the computational complexity of these problems and their variations.

It turns out that such problems are indeed variations of the subgroup membership problem. In each of the below problems a group G , an element a and a subset $S = \{g_1, g_2, \dots, g_n\}$ from the group G are given.

- **The Subset Sum Problem:**

Decision problem: Determine whether $a = g_1^{k_1} \dots g_n^{k_n}$ for some $k_i \in \{0, 1\}$

Search problem: It is known that answer of the decision problem is Yes. Find the values of the exponents.

- **The Knapsack Problem:**

This is a one step generalization of the subset sum problem. The exponents are allowed to be chosen from non-negative integers.

Decision problem: Determine whether $a = g_1^{k_1} \dots g_n^{k_n}$ for some $k_i \in \{0\} \cup \mathbb{Z}^+$

Search problem: It is known that such exponents exists. Find the values of the exponents.

- **The Submonoid Membership Problem:**

Decision problem: Determine whether $a = g_{i_1} \dots g_{i_s}$ for some $g_{i_k} \in S$ with repetition allowed.

Search problem: It is known that there exists such elements. Find values of g_{i_k} 's that satisfies this equation.

Note that if the given group G is abelian, the last two problems are equivalent.

3.5 The Conjugacy Problem

In the conjugacy decision problem, one is asked to determine whether the given elements a, b from a group G are conjugate. Notice that if there exists an algorithm which can decide the conjugacy problem, then that algorithm decides whether a given element g is conjugate to identity. In other words, solving the conjugacy problem implies solving the word problem. Therefore, we deal this problem under the restriction that the word problem is solvable on the considered group. Let us state the search version of the problem. A computably presented group with NP-complete conjugacy problem given in [53].

The Conjugacy Search Problem: Let it be known that in a given group G , the elements a, b are conjugates of each other. Find an element $x \in G$ that satisfies the equality $b = xax^{-1}$.

The computational difficulty of this problem in appropriately selected groups has enabled it to be used in various public-key protocols. The most popular platform used in the conjugacy problem is the braid group. Braid groups are non-commutative infinite groups that arise naturally from geometric braids. While the group operations on it can be easily calculated, the difficulty of various algorithmic problems such as the conjugacy search problem makes braid groups attractive.

The idea to implement the braid group as a platform for cryptosystems was introduced in 1999 by Ansel-Ansel-Goldfeld. Then, various cryptographic schemes such as Ko-Lee and Sibert-Dehornoy-Girault used the conjugacy search problem on braid groups.

The Ansel-Ansel-Goldfeld (AAG) key exchange protocol is based on the conjugacy search problem on non-commutative groups [54]. Although this protocol can be applied to any non-commutative group, the authors specifically emphasize that braid groups are promising. In the proposed scheme, in order to exchange information between Alice and Bob over the public channel, the word problem must be solved efficiently. The security of this scheme is based on the difficulty of solving the system of conjugates $xu_1x^{-1} = v_1, \dots, xu_mx^{-1} = v_m$ given from the group simultaneously.

In 2019, Grigorchuk and Grigoriev proposed some automaton groups, where the word problem is in polynomial time complexity and it is difficult to solve their conjugate systems, as the platform group for the AAG scheme [55]. These are Grigorchuk group, Basilica group, Universal Grigorchuk group, Three Towers Hanoi group, affine group $Aff_4(\mathbb{Z})$ and certain subgroups of $Aff_6(\mathbb{Z})$.

Ko, Lee et al. have proposed a key agreement protocol based on the conjugacy search problem on [56] braid groups. Shpilrain and Ushakov [57] showed that an adversary need not to solve the conjugacy search problem to get the common secret key. They showed that it is enough to solve the decomposition problem, which is a comparatively easier problem. A heuristic attack solving the decomposition problem in Ko-Lee protocol has been developed in [58], which is much more efficient than any known attack based on solving the conjugacy search problem.

Sibert, Dehornoy, and Girault have proposed three authentication schemes designed for braid groups [51]. The first one is a two-step (challenge - response) authentication scheme based on the (Diffie-Hellman-Like) conjugacy problem, while the other two are authentication schemes based on the con-

jugacy search problem, which repeats a three-step process several times to guarantee the required level of security. The root finding problem is also used in Scheme III. The authors demonstrated that these schemes they designed are zero-knowledge proofs. On the other hand, Mosina and Ushakov [59] show that the Scheme II given here is practically not a computational zero-knowledge proof.

An algorithmic solution to the conjugacy decision and search problems in braid groups was first given by Garside [60]. Although this algorithm is not efficient, it has opened the door to the solution of this problem. Then, many deterministic algorithms have been developed to solve the conjugacy search problem in braid groups [61, 62, 63, 64]. In addition, in [65], a polynomial time algorithm is given for the Diffie-Hellman type conjugacy search problem in braid groups, and an efficient solution to this problem under certain conditions is proposed in [66]. Apart from that, notable success has been achieved in various length-based or heuristic attacks [67, 68]. However, braid groups are still one of the alternatives with potential advantages against quantum attacks.

3.6 The Generalizations of The Conjugacy Problem

- **The Twisted Conjugacy Problem:**

Given a group G , an endomorphism φ defined on G and given two elements $a, b \in G$.

Decision problem: Determine whether the equality $b = x^{-1}a\varphi(x)$ holds for some $x \in G$.

Search problem: It is known that answer of the decision problem is Yes. Find the element x .

This problem is a generalization of the conjugacy problem. When the function $\varphi = id$ is taken, the conjugacy problem is obtained. The problem is decidable for a polycyclic groups[69], for automorphisms of finitely generated free groups[70], for closed surface groups [71] etc. The set of twisted conjugates of an element in a group is called the twisted conjugacy (Reidemeister) class. The twisted conjugacy classes are based on the Nielsen-Reidemeister fixed point theory. We can also ask the problem as: Is the element b in the Reidemeister class of a ? (decision) Find a value x that allows b to belong to this class (search). In [72] an iterative three-pass authentication scheme is proposed, such as the Fiat-Shamir protocol, based on the difficulty of the twisted conjugacy problem. Here, they named the problem as **the double-**

twisted conjugacy problem and defined it for endomorphism pairs as follows:

Given a group G , two endomorphisms φ, ψ on G and two elements $a, b \in G$.

Decision problem: Determine if the equality $b = \psi(x^{-1})a\varphi(x)$ holds for some $x \in G$.

Search problem: It is known that such element exists. Find the element x .

The protocol proposed by Ushakov and Shpilrain is given on the semi-group of all 2×2 matrices over truncated one-variable polynomials over F_2 . However, a successful attack was developed for the proposed protocol [73], and then another study [74] showed that this protocol is vulnerable in both theoretical and practical terms.

- **The Decomposition Problem:**

Let two elements a, b and two subsets H, K from a group G be given.
Decision problem: Is the equality $hak = b$ holds for some $h \in H$ and $k \in K$.

Search problem: It is known that $hak = b$ holds for some $h \in H$ and $k \in K$. Find such elements.

In this problem, when subsets are selected as subgroups, the problem is called as the double coset problem.

- **Double Coset Membership Problem:** (Hoffmann)

Let two subgroups H, K and two elements a, b from a group G be given.
Decision problem: Decide whether the double coset HaK contains the element b .

Search problem: It is known that $b \in HaK$. Find elements $h \in H$ and $k \in K$ such that $hak = b$.

In the double coset problem choose $a = 1$, you get the factorization problem.

- **The Factorization Problem:** (Hoffmann)

Let two subgroups H, K and an element g from a group G be given.
Decision problem: Decide whether the equality $g = hk$ holds for some $h \in H$ and $k \in K$.

Search problem: Given that g is an element in the set HK . Find elements $h \in H$ and $k \in K$ such that $g = hk$.

- **The Number of Factorizations Problem:** (Hoffmann)
Let two subgroups H, K and an element g from a group G be given. Determine the number $n \geq 0$ of distinct factorizations $g = hk$ of g where $h \in H$ and $k \in K$.
- **The Diffie-Hellman-Like Conjugacy Problem:** Given a group G and elements $g, h, k \in G$ such that $h = a^{-1}ga$ and $k = b^{-1}gb$ for some commuting secret elements $a, b \in G$. Find the element $b^{-1}a^{-1}gab$.
- **The Power Conjugacy Problem:** Two elements a, b in a group G are said to be power-conjugate if there exists integers n, m such that a^n and b^m are conjugate in G . Given a group G and two elements $a, b \in G$.
Decision problem: Decide whether a^n and b^m are conjugate in G for some integers n, m .
Search problem: Given that a and b are power-conjugate in G . Find two integers n, m and an element $x \in G$ such that $b^m = x^{-1}a^n x$.

3.7 Intersection Problems

- **Subgroup Intersection Problem:** (Hoffmann) Given a group G and its two finitely generated subgroups H, K by generating sets.
Decision problem: Is the intersection of subgroups H and K finitely generated?
Search problem: Given that $H \cap K$ is finitely generated. Find a generating set of the intersection.
- **Coset Intersection Problem:** (Hoffmann) A group G , an element $a \in G$ and generating sets of two subgroups H, K of G are given.
Decision problem: Decide whether the intersection $Ha \cap K$ is empty.
Search problem: Given that $Ha \cap K$ is non-empty. Find a generating set of the intersection.

It is easy to see that the factorization problem and the coset intersection problems are equivalent. For the convince of the reader, the observation of the equivalence is given: an element $a \in G$ is of the form $a = hk$ for some $h \in H$ and $k \in K$ only if $k = h^{-1}a \in Ha \cap K$.

- **Setwise Stabilizer Problem:** Let a group G act on a finite set Ω . For a given subset Δ of Ω , find the set $Stab_G(\Delta) = \{g \in G \mid \Delta^g = \Delta\}$.

3.8 Miscellaneous Problems

- Centralizer Problem: Given a group G with an element x and a subgroup H . Find the centralizer $C_H(x) = \{h \in H \mid hx = xh\}$ of the element x in H .
- Centralizer in Another Subgroup Problem: Let a group G , and two subgroups $H, K \leq G$ be given. Find a generating set for the centralizer $C_H(K) = \{h \in H \mid hk = kh \text{ for all } k \in K\}$.
- Set Transporter Problem: Let a group G act on the set Ω . Determine whether there is an element $g \in G$ that satisfies $\Delta_1^g = \Delta_2$ for the given subsets Δ_1, Δ_2 of Ω .
- Restricted Graph Automorphism: Given a graph $G = (V, E)$ and a permutation group $H \leq \text{Sym}(V)$. Find a generating set for $A \cap \text{Aut}(X)$.

In [75], Hoffmann presented eight group theoretic problems defined on permutation groups. These are double coset membership, group factorization, number of factorizations, coset intersection, subgroup intersection, setwise stabilizer, centralizer in another subgroup, restricted graph automorphism problem. We give these problems above in generic sense. The problems that Hoffmann introduced are translated from combinatorial problems including graph isomorphism. It is given that all of these problems are **NP**. He also proved that finding generating set for intersection of commuting permutation group given by generating set is the class **NP** \cap **coNP**

E.M. Luks stated that with the Karp reduction method, the group isomorphism decision problem on permutation groups in polynomial time can be reduced to the graph isomorphism problem and this problem can be reduced to the set stabilizer problem; He also demonstrated the equivalence of various problems in polynomial time over permutation groups named as Luk's equivalent class [76]. This class includes the subgroup intersection problem, the set stabilizer problem, the centralizer problem, the set transporter problem, the double coset decision problem and many more. In 2016, it was shown that these problems can be solved in quasipolynomial $\exp(\log n)^{O(1)}$ time [77].

3.9 The Post's Correspondence Problem in Groups

Another classic undecidable problem that Myasnikov et al. [52] generalized to arbitrary groups is the Post's correspondence problem (PCP)[78]. It is known that bounded PCP is **NP**-complete (SR11 in [79]). They study this problem together with its variations and examined the computational complexity of these problems.

- **The Post's Correspondence Problem in a Group PCP(G):** Given a finitely generated group G and a finite set of pairs $(g_1, h_1), \dots, (g_n, h_n)$ of elements in G . Determine if there is a word $w(x_1, \dots, x_n)$ in the free group $F(X)$ with basis $X = \{x_1, \dots, x_n\}$, which is not identity of G , such that $w(g_1, \dots, g_n) = w(h_1, \dots, h_n)$ in G .
- **The non-homogeneous Post's Correspondence Problem in a Group NPCP(G):** Given a finitely generated group G and a finite set of pairs $(g_1, h_1), \dots, (g_n, h_n), (a_1, a_2), (b_1, b_2)$ of elements in G . Determine if there is a word $w(x_1, \dots, x_n)$ in the free group $F(X)$ with basis $X = \{x_1, \dots, x_n\}$, such that $a_1 w(g_1, \dots, g_n) b_1 = a_2 w(h_1, \dots, h_n) b_2$ in G . Here the pairs $(a_1, a_2), (b_1, b_2)$ are called the constants of the instance.

Notice that in NPCP(G), w need not to be non-identity. As in the original PCP, the problems PCP(G) and NPCP(G) are also considered in the case where the number of pairs given from the group is bounded above.

Specifically in [52], it is given that the bounded NPCP(G) is **NP**-complete in the case that G is a non-abelian free group of finite rank. As a corollary, it is given that NPCP(G) is **NP**-hard if G contains a free abelian subgroup F_2 .

3.10 The Endomorphism Problem

Given a group G and two elements $g, h \in G$.

Decision problem: Determine whether there is an endomorphism ϕ of G such that $\phi(g) = h$.

Search problem: It is known that there is an endomorphism ϕ sending g to h . Find ϕ .

The endomorphism decision problem is unsolvable for a number of groups [80, 81]. It is observed that [82] for well-chosen platform groups, like free metabelian group of rank two, the problem is NP-hard. In [82] general framework for a zero-knowledge authentication scheme in the form Feige-Fiat-Shamir-like construction is given. Here the idea is to use a hard-to-invert action of a semigroup on a set. In particular, when a free metabelian group is used as the platform this study gives a zero-knowledge proof relying on the hardness of endomorphism problem. Later Roman'kov and Erofeev [83] present a method for constructing a possibly one-way function on a group with the decidable word problem and undecidable endomorphism problem. As an application, a zero-knowledge authentication protocol is given.

3.11 The Group Isomorphism Problem

The last Dehn's decision problem we discuss is the group isomorphism problem. This problem has been proved to be undecidable in general. On the other hand, when the groups are given in other ways the problem arises with different complexities. For example, if the groups are given in multiplication tables, this problem can be reduced by polynomial reduction to well known NP-problem the graph isomorphism problem [84].

3.12 The Hidden Subgroup Problem

Let G be a group, H be a subgroup of G , S be a finite set. A function $f : G \rightarrow S$ is said to **hide** H if for any $g_1, g_2 \in G$, the equality $f(g_1) = f(g_2)$ is true if and only if $g_1H = g_2H$.

The Hidden Subgroup Problem - HSP: Given a group G and oracle access to a function $f : G \rightarrow S$ which hides a subgroup H of G . Find a generating set for H .

HSP has very interesting instances like well known computational hard problems on which today's cryptographic structures are based: the integer factorization problem, the discrete logarithm problem, the period-finding problem, the graph isomorphism problem, the shortest vector problem, etc. It appears in most of the quantum algorithms developed to date. For example, Simon's problem is the problem of distinguishing the trivial subgroup from an order two subgroup in the

group Z_2^n and can be solved on quantum computers. Shor's algorithm is inspired by Simon's problem. Shor's integer factorization and discrete logarithm quantum algorithm solves a special case of the HSP. Shor's algorithm for integer factorization is basically equivalent to the Abelian HSP problem. Shor's applications to the graph isomorphism problem and the shortest vector problem on the lattice are equivalent to the HSP problem over other non-Abelian groups.

There are polynomial-time efficient quantum solutions for the Abelian HSP [85]. The solution of the HSP problem in non-Abelian groups will revolutionize the quantum world. Because this solution will also solve the graph isomorphism problem and the shortest vector problem on lattices. As is known, lattice-based problems are used in most of the methods proposed by NIST as quantum-safe. If the shortest vector problem on lattices is solved, the quantum security of most solutions submitted to NIST's competition will also be questioned. For this reason, HSP is a well-studied problem among quantum researchers.

The complexity of problems such as HSP can be measured in two ways. The first metric is query complexity. The query complexity of an algorithm is the number of times the function f is evaluated by an oracle, which is developed as a black box. The other measure is computational (or time) complexity. Computational complexity indicates how many times basic operations such as addition and multiplication are performed in the algorithm. An algorithm developed for solving HSP is accepted as efficient if its both query and computational complexity is polynomial in $\log(|G|)$ [86].

Ettinger et al. [87] gave a quantum algorithm which identifies a hidden subgroup of an arbitrary finite group in polynomial query complexity. But it has exponential time complexity. Yet, it is an open problem whether there is an efficient solution for HSP on arbitrary non-abelian group. Instances of the non-Abelian HSP that are not known to have efficient quantum algorithms includes the dihedral hidden subgroup problem (DHSP) and the symmetric hidden subgroup problem.

Regev[88] gave a solution to the unique shortest vector problem (SVP), which lies in **NP** and **coNP**, under the assumption that there exists an algorithm that solves DHSP by coset sampling. The best results for DHSP is the Kuperberg's quantum algorithm [89], which runs in time and query complexity $2^{O(\sqrt{\log|G|})}$ where $|G|$ is the order of the group. In other words, it is subexponential. Also the space requirement of

this algorithm is also subexponential. Regev [90] described a modified algorithm whose space requirement is polynomial and running time is still subexponential and but slightly higher than Kuperberg's algorithm. It is known that efficient quantum algorithm for the symmetric hidden subgroup problem implies to an efficient quantum algorithm for graph isomorphism [91],[92].

Hidden Shift Problem:

Given a finite group G , a set X and oracle access to two injective functions $f, g : G \rightarrow X$ with the property that there exists an element $s \in G$ such that the equality $g(x) = f(xs)$ holds for all $x \in G$. Find the secret shift element s .

The hidden shift problem is also known as **the hidden subgroup problem**. For the abelian group $G = \mathbb{Z}_n$ this problem is equivalent to DHSP. For arbitrary non-Abelian group G , the hidden shift problem on G with secret s gives HSP on the wreath product $G \wr S_2$ with the hidden subgroup $H = \langle (s, s^{-1}, 1) \rangle$. Indeed symmetric groups, the hidden shift and the hidden subgroup problems are equivalent [93].

4 Conclusion

Zero knowledge proof (ZKP) systems are vastly employed cryptographic primitives. While designing ZKP systems, security protection relies on computational hardness of one or more mathematical problems. This study aims to discover intractable problem candidates in the area of group theoretic algorithmic problems for such construction. In this paper, we introduced ZKP systems along with their connection to group theory and reviewed intractable group theoretic problems. The well-known popular problem used in ZKP construction is the discrete logarithm problem, and its variant, the Diffie-Hellman problem on cyclic groups. Early studies show that group intersection, double coset membership, coset intersection, group conjugacy and hidden subgroup problems are also in zero knowledge class. There are also zero knowledge schemes on non-commutative groups relying on the root problem, the conjugacy problem and the endomorphism problem. We believe that some of the problems we reviewed in this paper can be used to design a more efficient ZKP scheme which is less quantum-susceptible than commonly used zero-knowledge schemes.

Acknowledgement

This study is partially funded by the NLnet foundation under the MoU number 2021-12-510.

References

- [1] O. Goldreich, S. Micali, and A. Wigderson, “Proofs that yield nothing but their validity or all languages in np have zero-knowledge proof systems,” *J. ACM*, vol. 38, no. 3, p. 690–728, Jul. 1991.
- [2] J. Bootle, A. Cerulli, P. Chaidos, and J. Groth, “Efficient zero-knowledge proof systems,” in *Foundations of security analysis and design VIII*. Springer, 2016, pp. 1–31.
- [3] G. Oded, *Foundations of cryptography basic tools*. Cambridge University Press, 2001.
- [4] S. Goldwasser, S. Micali, and C. Rackoff, “The knowledge complexity of interactive proof systems,” *SIAM Journal on computing*, vol. 18, no. 1, pp. 186–208, 1989.
- [5] M. Blum, P. Feldman, and S. Micali, “Non-interactive zero-knowledge and its applications. stoc 1988,” 1988.
- [6] A. Fiat and A. Shamir, “How to prove yourself: Practical solutions to identification and signature problems,” in *Conference on the theory and application of cryptographic techniques*. Springer, 1986, pp. 186–194.
- [7] O. Goldreich and Y. Oren, “Definitions and properties of zero-knowledge proof systems,” *Journal of Cryptology*, vol. 7, no. 1, pp. 1–32, 1994.
- [8] D. Chaum, J.-H. Evertse, and J. Van De Graaf, “An improved protocol for demonstrating possession of discrete logarithms and some generalizations,” in *Workshop on the Theory and Application of Cryptographic Techniques*. Springer, 1987, pp. 127–141.
- [9] U. Feige, A. Fiat, and A. Shamir, “Zero-knowledge proofs of identity,” *Journal of cryptology*, vol. 1, no. 2, pp. 77–94, 1988.
- [10] T. Beth, “A fiat-shamir-like authentication protocol for the el-gamal-scheme,” in *Advances in Cryptology-proceedings of EUROCRYPT*, vol. 88, 1988, pp. 77–86.
- [11] L. C. Guillou and J.-J. Quisquater, “A practical zero-knowledge protocol fitted to security microprocessor minimizing both transmission and memory,” in *Workshop on the theory and application of cryptographic techniques*. Springer, 1988, pp. 123–128.

- [12] Y. Desmedt, “Subliminal-free authentication and signature,” in *Workshop on the Theory and Application of Cryptographic Techniques*. Springer, 1988, pp. 23–33.
- [13] C.-P. Schnorr, “Efficient signature generation by smart cards,” *Journal of cryptology*, vol. 4, no. 3, pp. 161–174, 1991.
- [14] E. Ben-Sasson, A. Chiesa, E. Tromer, and M. Virza, “Succinct {Non-Interactive} zero knowledge for a von neumann architecture,” in *23rd USENIX Security Symposium (USENIX Security 14)*, 2014, pp. 781–796.
- [15] B. Bünz, J. Bootle, D. Boneh, A. Poelstra, P. Wuille, and G. Maxwell, “Bulletproofs: Short proofs for confidential transactions and more,” in *2018 IEEE Symposium on Security and Privacy (SP)*. IEEE, 2018, pp. 315–334.
- [16] E. Ben-Sasson, I. Bentov, Y. Horesh, and M. Riabzev, “Scalable, transparent, and post-quantum secure computational integrity,” *Cryptology ePrint Archive*, 2018.
- [17] Y. Ishai, E. Kushilevitz, R. Ostrovsky, and A. Sahai, “Zero-knowledge from secure multiparty computation,” in *Proceedings of the thirty-ninth annual ACM symposium on Theory of computing*, 2007, pp. 21–30.
- [18] E. Ben-Sasson, L. Goldberg, and D. Levit, “Stark friendly hash–survey and recommendation,” *Cryptology ePrint Archive*, 2020.
- [19] A. Canteaut, T. Beyne, I. Dinur, M. Eichlseder, G. Leander, G. Leurent, M. Naya-Plasencia, L. Perrin, Y. Sasaki, Y. Todo *et al.*, “Report on the security of stark-friendly hash functions (version 2.0),” *HAL Id: hal-02883253*, 2020.
- [20] S. A. Fenner and Y. Zhang, “Quantum algorithms for a set of group theoretic problems,” in *Italian Conference on Theoretical Computer Science*. Springer, 2005, pp. 215–227.
- [21] V. Arvind and B. Das, “SZK proofs for black-box group problems,” *Theory of Comp. Sys.*, vol. 43, no. 2, 2008.
- [22] N. M. Sdroievski, M. V. da Silva, and A. L. Vignatti, “The hidden subgroup problem and MKTP,” *Theoretical Computer Science*, vol. 795, pp. 204 – 212, 2019.

- [23] W. Diffie and M. Hellman, “New directions in cryptography,” *IEEE transactions on Information Theory*, vol. 22, no. 6, pp. 644–654, 1976.
- [24] R. L. Rivest, A. Shamir, and L. Adleman, “A method for obtaining digital signatures and public-key cryptosystems,” *Communications of the ACM*, vol. 21, no. 2, pp. 120–126, 1978.
- [25] T. ElGamal, “A public key cryptosystem and a signature scheme based on discrete logarithms,” *IEEE transactions on information theory*, vol. 31, no. 4, pp. 469–472, 1985.
- [26] A. J. Menezes and S. A. Vanstone, “A note on cyclic groups, finite fields, and the discrete logarithm problem,” *Applicable Algebra in Engineering, communication and computing*, vol. 3, no. 1, pp. 67–74, 1992.
- [27] S. R. Blackburn, “Cryptanalysing the critical group: efficiently solving biggs’s discrete logarithm problem,” *Journal of Mathematical Cryptology*, vol. 3, no. 3, pp. 199–203, 2009.
- [28] F. Shokrieh, “The monodromy pairing and discrete logarithm on the jacobian of finite graphs,” *Journal of Mathematical Cryptology*, vol. 4, no. 1, pp. 43–56, 2010.
- [29] J. Groth, “Linear algebra with sub-linear zero-knowledge arguments,” in *Annual International Cryptology Conference*. Springer, 2009, pp. 192–208.
- [30] S. Bayer and J. Groth, “Efficient zero-knowledge argument for correctness of a shuffle,” in *Annual International Conference on the Theory and Applications of Cryptographic Techniques*. Springer, 2012, pp. 263–280.
- [31] J. Bootle, A. Cerulli, P. Chaidos, J. Groth, and C. Petit, “Efficient zero-knowledge arguments for arithmetic circuits in the discrete log setting,” in *Annual International Conference on the Theory and Applications of Cryptographic Techniques*. Springer, 2016, pp. 327–357.
- [32] N. Koblitz and A. Menezes, “Intractable problems in cryptography,” in *Proceedings of the 9th Conference on Finite Fields and Their Applications. Contemporary Mathematics*, vol. 518, 2010, pp. 279–300.
- [33] U. M. Maurer and S. Wolf, “The diffie–hellman protocol,” *Designs, Codes and Cryptography*, vol. 19, no. 2, pp. 147–171, 2000.

- [34] P. W. Shor, “Algorithms for quantum computation: discrete logarithms and factoring,” in *Proceedings 35th annual symposium on foundations of computer science*. Ieee, 1994, pp. 124–134.
- [35] M. Dehn, “Über unendliche diskontinuierliche gruppen,” *Mathematische Annalen*, vol. 71, no. 1, pp. 116–144, 1911.
- [36] P. S. Novikov, “Algorithmic unsolvability of the word problem in group theory,” *Journal of Symbolic Logic*, vol. 23, no. 1, 1958.
- [37] S. Adian, “Unsolvability of several algorithmic problems in group theory,” *Tr. Mos. Mat. Obshch*, vol. 6, pp. 231–298, 1957.
- [38] J.-C. Birget, A. Y. Ol’shanskii, E. Rips, and M. V. Sapir, “Isoperimetric functions of groups and computational complexity of the word problem,” *Annals of Mathematics*, pp. 467–518, 2002.
- [39] M. V. Sapir, J.-C. Birget, and E. Rips, “Isoperimetric and isodiametric functions of groups,” *Annals of Mathematics*, pp. 345–466, 2002.
- [40] N. R. Wagner and M. R. Magyarik, “A public-key cryptosystem based on the word problem,” in *Workshop on the Theory and Application of Cryptographic Techniques*. Springer, 1984, pp. 19–36.
- [41] M. I. G. Vasco and R. Steinwandt, “A reaction attack on a public key cryptosystem based on the word problem,” *Applicable Algebra in Engineering, Communication and Computing*, vol. 14, no. 5, pp. 335–340, 2004.
- [42] J.-C. Birget, S. S. Magliveras, and M. Sramka, “On public-key cryptosystems based on combinatorial group theory.” *IACR Cryptol. ePrint Arch.*, vol. 2005, p. 70, 2005.
- [43] A. J. Do Long Van, R. Siromony, and K. Subramanian, “Public key cryptosystems based on word problems,” in *ICOMIDC Symp. Math. of Computations, Ho Chi Minh City*, 1988.
- [44] G. Petrides, “Cryptanalysis of the public key cryptosystem based on the word problem on the grigorchuk groups,” in *IMA International Conference on Cryptography and Coding*. Springer, 2003, pp. 234–244.
- [45] D. Panagopoulos, “A secret sharing scheme using groups,” *arXiv preprint arXiv:1009.0026*, 2010.

- [46] M. Habeeb, D. Kahrobaei, and V. Shpilrain, “A secret sharing scheme based on group presentations and the word problem,” *Contemp. Math., Amer. Math. Soc.*, vol. 582, pp. 143–150, 2012.
- [47] S. Lipschutz and C. F. Miller III, “Groups with certain solvable and unsolvable decision problems,” *Communications on Pure and Applied Mathematics*, vol. 24, no. 1, pp. 7–15, 1971.
- [48] K. Mikhailova, “The occurrence problem for direct products of groups,” *Matematicheskii Sbornik*, vol. 112, no. 2, pp. 241–251, 1966.
- [49] J. McCool, “Unsolvable problems in groups with solvable word problem,” *Canadian Journal of Mathematics*, vol. 22, no. 4, pp. 836–838, 1970.
- [50] S. Sze, D. Kahrobaei, R. Dambreville, and M. Dupas, “Finding n -th roots in nilpotent groups and applications in cryptology,” *International Journal of Pure and Applied Mathematics*, vol. 70, no. 4, p. 571, 2011.
- [51] H. Sibert, P. Dehornoy, and M. Girault, “Entity authentication schemes using braid word reduction,” *Discrete Applied Mathematics*, vol. 154, no. 2, pp. 420–436, 2006.
- [52] A. Myasnikov, A. Nikolaev, and A. Ushakov, “Knapsack problems in groups,” *Mathematics of Computation*, vol. 84, no. 292, pp. 987–1016, 2015.
- [53] A. Miasnikov and P. Schupp, “Computational complexity and the conjugacy problem,” *Computability*, vol. 6, no. 4, pp. 307–318, 2017.
- [54] I. Anshel, M. Anshel, and D. Goldfeld, “An algebraic method for public-key cryptography,” *Mathematical Research Letters*, vol. 6, no. 3, pp. 287–291, 1999.
- [55] R. Grigorchuk and D. Grigoriev, “Key agreement based on automaton groups,” *Groups Complexity Cryptology*, vol. 11, no. 2, pp. 77–81, 2019.
- [56] K. H. Ko, S. J. Lee, J. H. Cheon, J. W. Han, J.-s. Kang, and C. Park, “New public-key cryptosystem using braid groups,” in *Annual International Cryptology Conference*. Springer, 2000, pp. 166–183.
- [57] V. Shpilrain and A. Ushakov, “The conjugacy search problem in public key cryptography: unnecessary and insufficient,” *Applicable Algebra in Engineering, Communication and Computing*, vol. 17, no. 3-4, pp. 285–289, 2006.

- [58] A. Myasnikov, V. Shpilrain, and A. Ushakov, “A practical attack on a braid group based cryptographic protocol,” in *Annual International Cryptology Conference*. Springer, 2005, pp. 86–96.
- [59] N. Mosina and A. Ushakov, “Mean-set attack: cryptanalysis of sibert et al. authentication protocol,” *Journal of Mathematical Cryptology*, vol. 4, no. 2, pp. 149–174, 2010.
- [60] F. A. Garside, “The braid group and other groups,” *The Quarterly Journal of Mathematics*, vol. 20, no. 1, pp. 235–254, 1969.
- [61] J. Birman, K. H. Ko, and S. J. Lee, “A new approach to the word and conjugacy problems in the braid groups,” *Advances in Mathematics*, vol. 139, no. 2, pp. 322–353, 1998.
- [62] E. A. Elrifai and H. R. Morton, “Algorithms for positive braids,” *The Quarterly Journal of Mathematics*, vol. 45, no. 4, pp. 479–497, 1994.
- [63] N. Franco and J. González-Meneses, “Conjugacy problem for braid groups and garside groups,” *Journal of Algebra*, vol. 266, no. 1, pp. 112–132, 2003.
- [64] V. Gebhardt, “A new approach to the conjugacy problem in garside groups,” *Journal of Algebra*, vol. 292, no. 1, pp. 282–302, 2005.
- [65] J. H. Cheon and B. Jun, “A polynomial time algorithm for the braid diffie-hellman conjugacy problem,” in *Annual International Cryptology Conference*. Springer, 2003, pp. 212–225.
- [66] E. Lee and J. H. Park, “Cryptanalysis of the public-key encryption based on braid groups,” in *International Conference on the Theory and Applications of Cryptographic Techniques*. Springer, 2003, pp. 477–490.
- [67] D. Garber, S. Kaplan, M. Teicher, B. Tsaban, and U. Vishne, “Length-based conjugacy search in the braid group,” *arXiv preprint math/0209267*, 2002.
- [68] D. Hofheinz and R. Steinwandt, “A practical attack on some braid group based cryptographic primitives,” in *International Workshop on Public Key Cryptography*. Springer, 2003, pp. 187–198.
- [69] V. Roman’kov, “The twisted conjugacy problem for endomorphisms of polycyclic groups,” *Journal of Group Theory*, vol. 13, no. 3, pp. 355–364, 2010.

- [70] O. Bogopolski, A. Martino, O. Maslakova, and E. Ventura, “The conjugacy problem is solvable in free-by-cyclic groups,” *Bulletin of the London Mathematical Society*, vol. 38, no. 5, pp. 787–794, 2006.
- [71] J.-P. Préaux, “The conjugacy problem in groups of non-orientable 3-manifolds,” *Groups, Geometry, and Dynamics*, vol. 10, no. 1, pp. 473–522, 2016.
- [72] V. Shpilrain and A. Ushakov, “An authentication scheme based on the twisted conjugacy problem,” in *International Conference on Applied Cryptography and Network Security*. Springer, 2008, pp. 366–372.
- [73] M. Grassl and R. Steinwandt, “Cryptanalysis of an authentication scheme using truncated polynomials,” *Information processing letters*, vol. 109, no. 15, pp. 861–863, 2009.
- [74] M. N. Gornova, E. G. Kukina, and V. A. Roman’kov, “Cryptanalysis of ushakov–shpilrain’s authentication protocol based on the twisted conjugacy problem,” *Prikladnaya Diskretnaya Matematika*, vol. 2, pp. 46–53, 2015.
- [75] C. M. Hoffmann, “Subcomplete generalizations of graph isomorphism,” *Journal of Computer and System Sciences*, vol. 25, no. 3, pp. 332–359, 1982.
- [76] E. M. Luks, “Permutation groups and polynomial-time computation,” *DIMACS Series in Discrete Mathematics and Theoretical Computer Science*, vol. 11, pp. 139–175, 1993.
- [77] L. Babai, “Graph isomorphism in quasipolynomial time,” in *Proceedings of the forty-eighth annual ACM symposium on Theory of Computing*, 2016, pp. 684–697.
- [78] E. L. Post, “A variant of a recursively unsolvable problem,” *Bulletin of the American Mathematical Society*, vol. 52, no. 4, pp. 264–268, 1946.
- [79] M. R. Garey and D. S. Johnson, *Computers and intractability: A Guide to the Theory of NP-Completeness*. Freeman San Francisco, 1978, vol. 174.
- [80] V. Roman’kov, “Unsolvability of the endomorphic reducibility problem in free nilpotent groups and in free rings,” *Algebra and Logic*, vol. 16, no. 4, pp. 310–320, 1977.

- [81] V. A. Roman'kov, "Equations in free metabelian groups," *Siberian Mathematical Journal*, vol. 20, no. 3, pp. 469–471, 1979.
- [82] D. Grigoriev and V. Shpilrain, "Zero-knowledge authentication schemes from actions on graphs, groups, or rings," *arXiv preprint arXiv:0802.1661*, 2008.
- [83] S. Y. Erofeev and V. A. Roman'kov, "On constructing possibly one-way functions based on the non-decidability of the endomorphism problem in groups," *Prikladnaya Diskretnaya Matematika*, vol. 3, pp. 13–24, 2012.
- [84] G. L. Miller, "Graph isomorphism, general remarks," *Journal of Computer and System Sciences*, vol. 18, no. 2, pp. 128–142, 1979.
- [85] S. Hallgren, A. Russell, and A. Ta-Shma, "The hidden subgroup problem and quantum computation using group representations," *SIAM Journal on Computing*, vol. 32, no. 4, pp. 916–934, 2003.
- [86] P. Koiran, V. Nese, and N. Portier, "The quantum query complexity of the abelian hidden subgroup problem," *Theoretical computer science*, vol. 380, no. 1-2, pp. 115–126, 2007.
- [87] M. Ettinger, P. Høyer, and E. Knill, "The quantum query complexity of the hidden subgroup problem is polynomial," *Information Processing Letters*, vol. 91, no. 1, pp. 43–48, 2004.
- [88] O. Regev, "Quantum computation and lattice problems," *SIAM Journal on Computing*, vol. 33, no. 3, pp. 738–760, 2004.
- [89] G. Kuperberg, "A subexponential-time quantum algorithm for the dihedral hidden subgroup problem," *SIAM Journal on Computing*, vol. 35, no. 1, pp. 170–188, 2005.
- [90] O. Regev, "A subexponential time algorithm for the dihedral hidden subgroup problem with polynomial space," *arXiv preprint quant-ph/0406151*, 2004.
- [91] D. Boneh and R. J. Lipton, "Quantum cryptanalysis of hidden linear functions," in *Annual International Cryptology Conference*. Springer, 1995, pp. 424–437.
- [92] M. Ettinger and P. Hoyer, "A quantum observable for the graph isomorphism problem," *arXiv preprint quant-ph/9901029*, 1999.

- [93] S. Hallgren, C. Moore, M. Rötteler, A. Russell, and P. Sen, “Limitations of quantum coset states for graph isomorphism,” *Journal of the ACM (JACM)*, vol. 57, no. 6, pp. 1–33, 2010.