

Patents Phrase to Phrase Semantic Matching Dataset

Grigor Aslanyan
aslanyan@google.com
Google Inc.

Ian Wetherbee
wetherbee@google.com
Google Inc.

ABSTRACT

There are many general purpose benchmark datasets for Semantic Textual Similarity but none of them are focused on technical concepts found in patents and scientific publications. This work aims to fill this gap by presenting a new human rated contextual phrase to phrase matching dataset. The entire dataset contains close to 50,000 rated phrase pairs, each with a CPC (Cooperative Patent Classification) class as a context. This paper describes the dataset and some baseline models.

ACM Reference Format:

Grigor Aslanyan and Ian Wetherbee. 2022. Patents Phrase to Phrase Semantic Matching Dataset. In *Proceedings of SIGIR PatentSemTech Workshop*. ACM, New York, NY, USA, 2 pages. <https://doi.org/10.1145/nnnnnnn.nnnnnnn>

1 INTRODUCTION AND RELATED WORK

Semantic Textual Similarity (STS) measures how similar two pieces of text are. STS is one of the most important tasks in Natural Language Processing (NLP) and there has been a significant amount of research in recent years in this domain. Benchmark datasets play the important role of allowing to consistently and fairly measure model improvements. There are multiple benchmark datasets for STS that are commonly used to measure the performance of state of the art models. Some notable examples are STS-B [1], SICK [5], MRPC [3], and PIT [13]. However, these datasets are fairly general purpose, and to the best of our knowledge there are currently no datasets that are focused on technical concepts found in patents and scientific publications. The somewhat related BioASQ challenge contains a biomedical question answering task [12].

This paper introduces a new human rated contextual phrase to phrase matching dataset focused on technical terms from patents. In addition to similarity scores that are typically included in other benchmark datasets we include granular rating classes similar to WordNet [8], such as synonym, antonym, hypernym, hyponym, holonym, meronym, domain related.

The dataset was generated with focus on the following:

- **Phrase disambiguation:** certain keywords and phrases can have multiple different meanings. For example, the phrase "mouse" may refer to an animal or a computer input device. We have included a context CPC class that can help disambiguate the anchor and target phrase.
- **Adversarial keyword match:** there are phrases that have matching keywords but are otherwise unrelated (e.g. "container

Permission to make digital or hard copies of part or all of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for third-party components of this work must be honored. For all other uses, contact the owner/author(s).

SIGIR PatentSemTech Workshop, July 15, 2022, Madrid, Spain

© 2022 Copyright held by the owner/author(s).

ACM ISBN 978-x-xxxx-xxxx-x/YY/MM.

<https://doi.org/10.1145/nnnnnnn.nnnnnnn>

anchor	target	context	rating	score
acid absorption	absorption of acid	B08	exact	1.00
acid absorption	acid immersion	B08	synonym	0.75
acid absorption	chemically soaked	B08	domain	0.25
acid absorption	acid reflux	B08	not rel.	0.00
gasoline blend	petrol blend	C10	synonym	0.75
gasoline blend	fuel blend	C10	hypernym	0.50
gasoline blend	fruit blend	C10	not rel.	0.00
faucet assembly	water tap	A22	hyponym	0.50
faucet assembly	water supply	A22	holonym	0.25
faucet assembly	school assembly	A22	not rel.	0.00

Table 1: A small sample of the data.

section" → "kitchen container", "offset table" → "table fan"). Many models will not do well on such data (e.g. bag of words models). Our dataset is designed to include many such examples.

- **Hard negatives:** We created our dataset with the aim to improve upon current state of the art language models. Specifically, we have used the BERT model [2] to generate target phrases. So our dataset contains many human rated examples of phrase pairs that BERT may identify as very similar but in fact they may not be.

The full dataset is publicly available through Kaggle¹. This dataset was used in the *U.S. Patent Phrase to Phrase Matching* Kaggle competition² from March 21 - June 20, 2022.

2 DATASET DESCRIPTION

Each entry of the dataset contains two phrases - anchor and target, a context CPC class, a rating class, and a similarity score. A small sample of the dataset is shown in Table 1.

The entire dataset contains 48,548 entries with 973 unique anchors, split into a training (75%), validation (5%), and test (20%) sets. When splitting the data all of the entries with the same anchor are kept together in the same set. There are 106 different context CPC classes and all of them are represented in the training set.

We have used the following steps for generating the data. For each patent in the corpus we first extract important (salient) phrases. These are typically noun phrases (e.g. "fastener", "lifting assembly") or functional phrases (e.g. "food processing", "ink printing"). Next, we keep only phrases that appear in at least 100 patents. We randomly sample around 1,000 phrases from the remaining phrases which become our anchor phrases. For each anchor phrase we find all of the matching patents and all of the CPC classes for those patents. From all of the matching CPC classes we randomly sample up to four. These become the context CPC classes for that anchor phrase. The target phrases come from two sources - pre-generated and rater generated.

¹<https://www.kaggle.com/datasets/google/google-patent-phrase-similarity-dataset>

²<https://www.kaggle.com/c/us-patent-phrase-to-phrase-matching>

Model	Dim.	Pearson cor.	Spearman cor.
GloVe	300	0.429	0.444
FastText	300	0.402	0.467
Word2Vec	250	0.437	0.483
BERT	1024	0.418	0.409
Patent-BERT	1024	0.528	0.535
Sentence-BERT	768	0.598	0.577

Table 2: Baseline model metrics.

We use two different methods for pre-generating target phrases - partial matching and a masked language model (MLM). For partial match we randomly select phrases from the entire corpus that partially match with the anchor phrase. This means that one or more of the tokens matches, but the whole phrase is different (e.g. “abatement” → “noise abatement”, “material formation” → “formation material”). For MLM we select sentences from the patents that contain a given anchor phrase, mask it out, and use a BERT model [2] to predict candidates for the masked portion of the text. All of the phrases are cleaned up before sending to the raters. This includes lowercasing and removal of punctuation and certain stopwords (e.g. “and”, “or”, “said”).

The raters were asked to determine the similarity level between the two phrases given the context CPC class. They choose between five different levels of similarity - very high, high, medium, low, and not related. Each similarity level is further divided into different subclasses, such as hyponym (broad-narrow), hypernym (narrow-broad), antonym, domain related. The detailed description of the similarity levels and subclasses will be included with the public release of the data.

All of the pre-generated target phrases were independently rated by two raters. After completing the ratings they met and went over all of the non-matching ratings to discuss and agree on a final rating. Each rater separately generated new target phrases and gave ratings to them. We have merged all of the rater generated phrases together. We have left out the rare cases where the two raters generated the same target phrase with different ratings.

3 BASELINES

Table 2 describe the performance of some common off the shelf models on the test data. We have only included dual-tower model architectures that perform an embedding of the anchor and target phrases separately and compute similarity using cosine distance. All of the models use mean pooling of individual keyword embeddings to get the full phrase embedding.

For GloVe [9] we have used the *Wikipedia 2014 + Gigaword 5* model³, for FastText [4] the *wiki-news-300d-1M* model⁴ [7], and for Word2Vec [6] the *Wiki-words-250* model from TensorFlow Hub⁵. For BERT [2] we have used the BERT-Large model from TensorFlow Hub⁶. For comparison, we have also included the publicly available BERT model pre-trained on patent data [11] of the same size as BERT-Large. Finally, for Sentence-BERT [10] we have used the *all-mpnet-base-v2* pretrained model⁷.

³<https://nlp.stanford.edu/projects/glove/>

⁴<https://fasttext.cc/docs/en/english-vectors.html>

⁵<https://tfhub.dev/google/Wiki-words-250/2>

⁶https://tfhub.dev/tensorflow/bert_en_uncased_L-24_H-1024_A-16/4

⁷https://www.sbert.net/docs/pretrained_models.html

The bag-of-words models do not perform very well, which is expected given the dataset structure (e.g. many matching terms with different meanings). The Patent-BERT model significantly outperforms the regular BERT model, which implies that generic pre-trained models are not optimal for technical terms found in patents. However, we get the best results from the Sentence-BERT model. This is not entirely surprising since Sentence-BERT has been specifically fine tuned for the dual-tower architecture we are using for similarity.

REFERENCES

- [1] Daniel Cer, Mona Diab, Eneko Agirre, Iñigo Lopez-Gazpio, and Lucia Spezia. 2017. SemEval-2017 Task 1: Semantic Textual Similarity Multilingual and Crosslingual Focused Evaluation. In *Proceedings of the 11th International Workshop on Semantic Evaluation (SemEval-2017)*. Association for Computational Linguistics, Vancouver, Canada, 1–14. <https://doi.org/10.18653/v1/S17-2001>
- [2] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*. Association for Computational Linguistics, Minneapolis, Minnesota, 4171–4186. <https://doi.org/10.18653/v1/N19-1423>
- [3] William B. Dolan and Chris Brockett. 2005. Automatically Constructing a Corpus of Sentential Paraphrases. In *Proceedings of the Third International Workshop on Paraphrasing (IWP2005)*. <https://aclanthology.org/I05-5002>
- [4] Armand Joulin, Edouard Grave, Piotr Bojanowski, and Tomas Mikolov. 2017. Bag of Tricks for Efficient Text Classification. In *Proceedings of the 15th Conference of the European Chapter of the Association for Computational Linguistics: Volume 2, Short Papers*. Association for Computational Linguistics, Valencia, Spain, 427–431. <https://aclanthology.org/E17-2068>
- [5] Marco Marelli, Stefano Menini, Marco Baroni, Luisa Bentivogli, Raffaella Bernardi, and Roberto Zamparelli. 2014. A SICK cure for the evaluation of compositional distributional semantic models. In *Proceedings of the Ninth International Conference on Language Resources and Evaluation (LREC’14)*. European Language Resources Association (ELRA), Reykjavik, Iceland, 216–223. http://www.lrec-conf.org/proceedings/lrec2014/pdf/363_Paper.pdf
- [6] Tomas Mikolov, Kai Chen, Greg Corrado, and Jeffrey Dean. 2013. Efficient Estimation of Word Representations in Vector Space. *arXiv e-prints*, Article arXiv:1301.3781 (Jan. 2013), arXiv:1301.3781 pages. arXiv:cs.CL/1301.3781
- [7] Tomas Mikolov, Edouard Grave, Piotr Bojanowski, Christian Puhrsch, and Armand Joulin. 2018. Advances in Pre-Training Distributed Word Representations. In *Proceedings of the International Conference on Language Resources and Evaluation (LREC 2018)*.
- [8] George A. Miller. 1995. WordNet: A Lexical Database for English. *Commun. ACM* 38, 11 (nov 1995), 39–41. <https://doi.org/10.1145/219717.219748>
- [9] Jeffrey Pennington, Richard Socher, and Christopher Manning. 2014. GloVe: Global Vectors for Word Representation. In *Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing (EMNLP)*. Association for Computational Linguistics, Doha, Qatar, 1532–1543. <https://doi.org/10.3115/v1/D14-1162>
- [10] Nils Reimers and Iryna Gurevych. 2019. Sentence-BERT: Sentence Embeddings using Siamese BERT-Networks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics. <http://arxiv.org/abs/1908.10084>
- [11] Rob Srebrovic and Jay Yonamine. [n.d.]. Leveraging the BERT algorithm for Patents with TensorFlow and BigQuery. ([n.d.]). https://services.google.com/fh/files/blogs/bert_for_patents_white_paper.pdf
- [12] George Tsatsaronis, Georgios Balikas, Prodromos Malakasiotis, Ioannis Patalas, Matthias Zschunke, Michael R Alvers, Dirk Weissenborn, Anastasia Krithara, Sergios Petridis, Dimitris Polychronopoulos, Yannis Almirantis, John Pavlopoulos, Nicolas Baskiotis, Patrick Gallinari, Thierry Artieres, Axel Ngonga, Norman Heino, Eric Gaussier, Liliana Barrio-Alvers, Michael Schroeder, Ion Androutsopoulos, and Georgios Paliouras. 2015. An overview of the BIOASQ large-scale biomedical semantic indexing and question answering competition. *BMC Bioinformatics* 16 (2015), 138. <https://doi.org/10.1186/s12859-015-0564-6>
- [13] Wei Xu, Chris Callison-Burch, and Bill Dolan. 2015. SemEval-2015 Task 1: Paraphrase and Semantic Similarity in Twitter (PIT). In *Proceedings of the 9th International Workshop on Semantic Evaluation (SemEval 2015)*. Association for Computational Linguistics, Denver, Colorado, 1–11. <https://doi.org/10.18653/v1/S15-2001>