

PAC Verification of Statistical Algorithms

Saachi Mutreja

Computer Science Division

University of California, Berkeley

saachi@berkeley.edu

Jonathan Shafer

Computer Science Division

University of California, Berkeley

shaferjo@berkeley.edu

July 2022

Abstract

Goldwasser et al. (2021) recently proposed the setting of PAC verification, where a hypothesis (machine learning model) that purportedly satisfies the agnostic PAC learning objective is verified using an interactive proof. In this paper we develop this notion further in a number of ways. First, we prove a lower bound for PAC verification of $\Omega(\sqrt{d})$ i.i.d. samples for hypothesis classes of VC dimension d . Second, we present a protocol for PAC verification of unions of intervals over \mathbb{R} that improves upon their proposed protocol for that task, and matches our lower bound. Third, we introduce a natural generalization of their definition to verification of general statistical algorithms, which is applicable to a wider variety of practical algorithms beyond agnostic PAC learning. Showcasing our proposed definition, our final result is a protocol for the verification of statistical query algorithms that satisfy a combinatorial constraint on their queries.

Contents

1	Introduction	1
1.1	Our Contributions	2
1.2	Related Works	2
1.3	Preliminaries	3
2	Technical Overview	4
2.1	A Tight Lower Bound	4
2.2	Verification of Statistical Algorithms	5
2.3	Examples	6
3	A Lower Bound for PAC Verification of VC classes	7
4	Verification of Unions of Intervals	9
5	Verification of Statistical Query Algorithms	12
5.1	Definitions	12
5.1.1	Statistical Query Algorithms	12
5.1.2	The Partition Size	12
5.2	Formal Statements	13
5.3	Proofs	14

1 Introduction

Comparing what can be computed in a given model of computation versus what can be verified in that model is a recurring theme throughout the fields of computability and computational complexity. The most notorious example is of course the P vs. NP problem, which asks whether the set of decision problems that can be solved in polynomial time equals the set of decision problems whose solution can be verified in polynomial time given a suitable proof string. But the same question has been studied for many other settings and models of computation as well, with prominent examples including L vs. NL (for logspace computation), IP = PSPACE (polytime computation, with an interactive proof) and MIP* = RE (ditto, with multiple quantum provers). The existence of a gap between computing and verifying is often interpreted as capturing the notion of *creativity*, in the sense that finding a solution to a problem might require discovery or inventiveness, while verifying a formal proof for the same is merely rote work.

While this theme has deep roots in the literature and an appealing interpretation, its parallels for learning have only recently been explored for the first time. In the context of PAC¹ learning, Goldwasser, Rothblum, Shafer, and Yehudayoff (2021) introduced the setting of *PAC verification*, in which an untrusted prover attempts to convince a verifier that a certain predictor has nearly-optimal loss with respect to a fixed unknown distribution from which the verifier can take random samples. Specifically, they work in the agnostic PAC setting, where the objective is to find a hypothesis h that has nearly-optimal loss in the sense

$$L_D^{0-1}(h) \leq \inf_{h' \in \mathcal{H}} L_D^{0-1}(h') + \varepsilon, \quad (1)$$

where L_D^{0-1} denotes 0-1 population loss and \mathcal{H} is some fixed and known hypothesis class (formal definitions appear in Sections 1.3 and 2 below).

Seeing as computational gaps are already well-studied, the main novelty in this setting concerns sample complexity gaps. They show that for some hypothesis classes (but not for others) the number of i.i.d. samples necessary to find a hypothesis with nearly-optimal loss is strictly greater than the number of i.i.d. samples necessary for verifying, with the help of an untrusted prover, that a proposed hypothesis has nearly-optimal loss.

Beyond the (substantial) theoretical motivation, this setting could have meaningful (and timely) real-world applications. First, if a sample complexity gap exists then “verifiable data collection + ML as a service” becomes a viable business model. The provider would collect suitable training data from the desired population distribution, execute a chosen ML algorithm, and subsequently prove to the client that the end result is good with respect to the population. The client would only need a small amount of independent data from the population distribution to determine the veracity of the claim. Beyond this, Goldwasser et al. (2021) envision a variety of other applications, such as more efficient schemes for replicating scientific results in the empirical sciences.

¹Probably Approximately Correct (PAC) is the standard theoretical model for supervised learning, introduced by Vapnik and Chervonenkis (1968) and Valiant (1984). Agnostic PAC learning is a generalization to the non-realizable case, introduced by Haussler (1992). See also Shalev-Shwartz and Ben-David (2014).

1.1 Our Contributions

PAC verification is novel territory, and very little is currently known. The current paper aims to make some modest steps towards charting this landscape. We focus on studying sample complexity gaps between learning and verifying specifically in terms of the dependence on the VC (Vapnik–Chervonenkis) dimension. We start with showing a lower bound for the sample complexity gap. Prior to our work, one could imagine that some classes would give rise to very large gaps, e.g., $O(\log(d))$ i.i.d. samples for verifying vs. the $\Theta(d)$ samples that are known to be necessary and sufficient for learning, where $d = \text{VC}(\mathcal{H})$. Our first result shows that the gap can be at most quadratic. Namely, for any hypothesis class, PAC verification requires that the verifier use at least $\Omega(\sqrt{d})$ i.i.d. random samples.

Second, we show that our lower bound is tight, by improving upon a result of Goldwasser et al. (2021) to obtain a PAC verifier for the class of unions of intervals on \mathbb{R} that uses $\tilde{O}(\sqrt{d})$ i.i.d. random samples. The previous result was an upper bound for a weaker notion of verification, that guarantees only that $L_D^{0-1}(h) \leq 2 \cdot \text{Opt} + \varepsilon$, where $\text{Opt} = \inf_{h' \in \mathcal{H}} L_D^{0-1}(h') + \varepsilon$ (instead of $\text{Opt} + \varepsilon$ as in Eq. (1)). Their result applied only to a specific restriction of the class of unions of intervals, while our technique works for the restricted and for the unrestricted versions of the class.

Third, we take a step towards making the notion of PAC verification more applicable in practical settings. Many ML and data science algorithms that people use in practice, and might like to delegate to an untrusted service, do not obtain (or provably obtain) the objective of agnostic PAC learning as in Eq. (1). Instead, they obtain some quantity of loss which is typically good enough in practice. With this reality in mind, we introduce a generalization of PAC verification that guarantees that the outcome is competitive with a specific algorithm. Namely, the verifier guarantees that with high probability, the hypothesis h satisfies $L_D^{0-1}(h) \leq \mathbb{E}[L_D^{0-1}(h^*)] + \varepsilon$, where h^* is the (possibly randomized) output of the algorithm (see Definition 2.3).

Fourth, we study PAC verification of statistical query algorithms. For a batch \mathbf{q} of statistical queries, we define a notion of *partition size*, denoted $\text{PS}(\mathbf{q})$, which is the number of atoms in the σ -algebra generated by \mathbf{q} . We show that whenever this quantity is sufficiently small, there is a sample complexity gap between execution and verification of the statistical query algorithm.

Lastly, we show that there exists a sample complexity gap for a natural example we present, of optimizing a portfolio with advice. Both our lower bound and our upper bound apply to this example.

1.2 Related Works

The study of interactive proofs for properties of distributions was initiated by Chiesa and Gur (2018). They showed general bounds in terms of the support size. However, they did not consider tighter bounds that depend on combinatorial characterizations of the property of interest (e.g., bounds that depend on the VC dimension).

The study of PAC verification of a hypothesis class was introduced by Goldwasser, Rothblum, Shafer, and Yehudayoff (2021), who considered interactive proofs for properties of distributions in the specific context of machine learning. In particular, they also considered the relationship between the VC dimension of the class and the sample complexity of verification. They showed

a lower bound that is incomparable with our lower bound, and they showed an upper bound for union of intervals which is weaker than our upper bound. Our definition of PAC verification of an algorithm is closely modeled on their definition.

Recently, there have been a number of works on the general theme of distribution testing and interactive proofs for properties of distributions in the context of machine learning. These include [Canetti and Karchmer \(2021\)](#), [Anil, Zhang, Wu, and Grosse \(2021\)](#), [Rubinfeld and Vasilyan \(2022\)](#) and [Herman and Rothblum \(2022\)](#), among others.

1.3 Preliminaries

Notation 1.1. $\mathbb{N} = \{1, 2, 3, \dots\}$, i.e., $0 \notin \mathbb{N}$. For any $n \in \mathbb{N}$, we denote $[n] = \{1, 2, 3, \dots, n\}$.

Notation 1.2. For a set \mathcal{X} , we write $\Delta(\mathcal{X})$ to denote the set of all distributions with support contained in \mathcal{X} (with respect to some fixed implicit σ -algebra).

PAC Learning

Definition 1.3. Let \mathcal{X} be a set, and let $\mathcal{H} \subseteq \{0, 1\}^{\mathcal{X}}$ be a set of functions. Let $k \in \mathbb{N}$, $X = \{x_1, x_2, \dots, x_k\} \subseteq \mathcal{X}$. We say that \mathcal{H} shatters X if for any $y_1, y_2, \dots, y_k \in \{0, 1\}$ there exists $h \in \mathcal{H}$ such that $h(x_i) = y_i$ for all $i \in [k]$. The Vapnik–Chervonenkis (VC) dimension of \mathcal{H} , denoted $\text{VC}(\mathcal{H})$, is the largest $d \in \mathbb{N}$ for which there exist a set $X \subseteq \mathcal{X}$ of cardinality d that is shattered by \mathcal{H} . If \mathcal{H} shatters sets of cardinality arbitrarily large, we say that $\text{VC}(\mathcal{H}) = \infty$.

Definition 1.4. Let Ω and \mathcal{H} be sets. A loss function is a function $L : \Omega \times \mathcal{H} \rightarrow [0, 1]$. Let $h \in \mathcal{H}$, and let $S = (z_1, \dots, z_m) \in \Omega^m$ be a vector. The empirical loss of h with respect to S is $L_S(h) = \frac{1}{m} \sum_{i \in [m]} L(z_i, h)$. For any distribution $\mathcal{D} \in \Delta(\Omega)$, the loss of h with respect to \mathcal{D} is $L_{\mathcal{D}}(h) = \mathbb{E}_{Z \sim \mathcal{D}}[L(Z, h)]$. The loss of \mathcal{H} with respect to \mathcal{D} is $L_{\mathcal{D}}(\mathcal{H}) = \inf_{h \in \mathcal{H}} L_{\mathcal{D}}(h)$.

The 0-1 loss, denoted L^{0-1} , is the special case in which \mathcal{X} is a set, $\Omega = \mathcal{X} \times \{0, 1\}$, $\mathcal{H} \subseteq \{0, 1\}^{\mathcal{X}}$, and $L((x, y), h) = \mathbb{1}(h(x) \neq y)$.

Definition 1.5. Let \mathcal{X} be a set, and let $\mathcal{H} \subseteq \{0, 1\}^{\mathcal{X}}$ be a class of hypotheses. We say that \mathcal{H} is agnostically PAC learnable if there exist an algorithm A and a function $m_A : [0, 1]^2 \rightarrow \mathbb{N}$ such that for any $\varepsilon, \delta > 0$ and any distribution $\mathcal{D} \in \Delta(\mathcal{X} \times \{0, 1\})$, if A receives as input a tuple of $m_A(\varepsilon, \delta)$ i.i.d. samples from \mathcal{D} , then A outputs a function $h \in \mathcal{H}$ satisfying

$$\mathbb{P}\left[L_{\mathcal{D}}^{0-1}(h) \leq L_{\mathcal{D}}^{0-1}(\mathcal{H}) + \varepsilon\right] \geq 1 - \delta.$$

In words, this means that h is probably (with confidence $1 - \delta$) approximately correct (has loss at most ε worse than optimal). The point-wise minimal such function m_A is called the sample complexity of \mathcal{H} .

PAC Verification of a Hypothesis Class

Definition 1.6 (PAC Verification of a Hypothesis Class; a special case of [Goldwasser et al. \(2021\)](#), Definition 4). Let \mathcal{X} be a set, let $\mathbb{D} \subseteq \Delta(\mathcal{X} \times \{0, 1\})$ be a set of distributions, and let $\mathcal{H} \subseteq \{0, 1\}^{\mathcal{X}}$ be a class of hypotheses. We say that \mathcal{H} is PAC verifiable with respect to \mathbb{D} using random samples if there

exist an interactive proof system consisting of a verifier V and an honest prover P such that for any $\varepsilon, \delta \in (0, 1)$ there exist $m_v, m_p \in \mathbb{N}$ such that for any $\mathcal{D} \in \mathbb{D}$, the following conditions are satisfied:

- **Completeness.** Let the random variable

$$h = [V(S_V, \varepsilon, \delta), P(S_P, \varepsilon, \delta)] \in \mathcal{H} \cup \{\text{reject}\}$$

denote the output of V after receiving input $(S_V, \varepsilon, \delta)$ and interacting with P , which received input $(S_P, \varepsilon, \delta)$. Then

$$\mathbb{P}_{S_V \sim \mathcal{D}^{m_v}, S_P \sim \mathcal{D}^{m_p}} \left[h \neq \text{reject} \wedge \left(L_{\mathcal{D}}^{0-1}(h) \leq L_{\mathcal{D}}^{0-1}(\mathcal{H}) + \varepsilon \right) \right] \geq 1 - \delta.$$

- **Soundness.** For any (possibly malicious and computationally unbounded) prover P' (which may depend on \mathcal{D} , ε , and δ), the verifier's output $h = [V(S_V, \varepsilon, \delta), P']$ satisfies

$$\mathbb{P}_{S_V \sim \mathcal{D}^{m_v}, S_P \sim \mathcal{D}^{m_p}} \left[h = \text{reject} \vee \left(L_{\mathcal{D}}^{0-1}(h) \leq L_{\mathcal{D}}^{0-1}(\mathcal{H}) + \varepsilon \right) \right] \geq 1 - \delta.$$

In both conditions the probability is over the randomness of the samples S_V and S_P , as well as the randomness of V , P and P' .

2 Technical Overview

2.1 A Tight Lower Bound

Our first result is a lower bound for the number of i.i.d. random samples the verifier must receive to successfully PAC verify a class.

Theorem 2.1. *Let $d \in \mathbb{N}$, let \mathcal{X} be a set, let $\mathcal{H} \subseteq \{0, 1\}^{\mathcal{X}}$ be a hypothesis class, and assume that $d = \text{VC}(\mathcal{H})$ is finite. Let (V, P) be an interactive proof system that PAC verifies \mathcal{H} with parameters $\varepsilon = \delta = 1/3$ where the verifier uses m_v i.i.d. labeled samples. Then $m_v \geq \Omega(\sqrt{d})$.*

Proof Idea. This is an application of Le Cam's 'point vs. mixture' method (see Yu, 1997), together with a reduction from distribution testing to PAC verification. The intuition is that to PAC verify with respect to a uniform distribution over a shattered set, it is necessary to distinguish the case of truly random labels (where the loss of the class is $1/2$), from the case where the labels come from a random function (where the loss of the class is 0). This requires seeing a collision (sampling the same x twice). The quadratic lower bound for a collision follows from the 'birthday paradox'. \square

Our second result shows that the lower bound is tight.

Theorem 2.2. *Let $d \in \mathbb{N}$, and let*

$$\mathcal{H}_d = \left\{ \mathbb{1}_X : X = \bigcup_{i \in [d]} [a_i, b_i] \wedge (\forall i \in [d] : 0 \leq a_i \leq b_i \leq 1) \right\} \subseteq \{0, 1\}^{[0,1]}$$

be the class of boolean-valued functions over the domain $[0, 1]$ that are indicator functions for a union of d intervals. There exists an interactive proof system that PAC verifies the class \mathcal{H}_d with respect

to the set of all distributions over $[0, 1] \times \{0, 1\}$, such that the verifier uses $m_v = O(\sqrt{d} \log(1/\delta) \varepsilon^{-2.5})$ random samples, the honest prover uses $m_p = O((d^2 \log(d/\varepsilon) + \log(1/\delta)) \varepsilon^{-4})$ random samples, and both the verifier and the honest prover run in time polynomial in their number of samples.

Proof Idea. A discretization of the population distribution is induced by partitioning the domain $[0, 1]$ into d/ε intervals, each of which has weight ε/d according to the population distribution. In the discretized distribution, the probability mass from each interval is lumped together into a single arbitrary point in that interval. We show that to find an ε -sub-optimal union of intervals, it suffices to know this discretized distribution. The prover sends the (purported) discretized distribution to the verifier. The verifier uses a distribution identity tester to verify that the provided distribution is a correct discretization of the population distribution. This requires $O(\sqrt{d})$ samples, because the support of the discretized distribution is of size $O(d)$. \square

It is worthwhile to note that the main property of the hypothesis class utilized in the proof is that it has low ‘surface area’ or noise sensitivity (cf. Balcan et al., 2012). Thus, a similar proof technique could apply to other classes as well.

2.2 Verification of Statistical Algorithms

Our next contribution is a new definition of PAC verification of an *algorithm*. This generalizes the definition of PAC verification of a *hypothesis class* (Definition 1.6, introduced by Goldwasser et al., 2021), which corresponds to the special case of PAC verifying an algorithm that is an agnostic PAC learner for the class.

Definition 2.3 (PAC Verification of an Algorithm). *Let Ω be a set, let $\mathbb{D} \subseteq \Delta(\Omega)$ be a set of distributions, let \mathcal{H} be a set (called the set of possible outputs), and for each $\mathcal{D} \in \mathbb{D}$ let $\mathcal{O}_{\mathcal{D}}$ be an oracle. Let A be a (possibly randomized) algorithm that takes no inputs, has query access to $\mathcal{O}_{\mathcal{D}}$, and outputs a value $h_A = A^{\mathcal{O}_{\mathcal{D}}} \in \mathcal{H}$. For each $\mathcal{D} \in \mathbb{D}$, let $L : \Omega \times (\mathcal{H} \cup \{\text{reject}\}) \rightarrow [0, 1]$ be a loss function, and let $L_{\mathcal{D}}(A) = \mathbb{E}[L_{\mathcal{D}}(h_A)]$, where the expectation is over the randomness of A and of the oracle $\mathcal{O}_{\mathcal{D}}$. We say that the algorithm A with access to oracles $\{\mathcal{O}_{\mathcal{D}}\}_{\mathcal{D} \in \mathbb{D}}$ is PAC verifiable with respect to \mathbb{D} by a verification protocol that uses random samples if there exist an interactive proof system consisting of a verifier V and an honest prover P such that for any $\varepsilon, \delta \in (0, 1)$ there exist $m_v, m_p \in \mathbb{N}$ such that for any $\mathcal{D} \in \mathbb{D}$, the following conditions are satisfied:*

- **Completeness.** *Let the random variable*

$$h = [V(S_V, \varepsilon, \delta), P(S_P, \varepsilon, \delta)] \in \mathcal{H} \cup \{\text{reject}\}$$

denote the output of V after receiving input $(S_V, \varepsilon, \delta)$ and interacting with P , which received input $(S_P, \varepsilon, \delta)$. Then

$$\mathbb{P}_{S_V \sim \mathcal{D}^{m_v}, S_P \sim \mathcal{D}^{m_p}} [h \neq \text{reject} \wedge L_{\mathcal{D}}(h) \leq L_{\mathcal{D}}(A) + \varepsilon] \geq 1 - \delta.$$

- **Soundness.** *For any deterministic or randomized (possibly malicious and computationally unbounded) prover P' (which may depend on \mathcal{D} , ε , δ and $\{\mathcal{O}_{\mathcal{D}}\}_{\mathcal{D} \in \mathbb{D}}$), the verifier’s output $h = [V(S_V, \varepsilon, \delta), P']$ satisfies*

$$\mathbb{P}_{S_V \sim \mathcal{D}^{m_v}} [h = \text{reject} \vee L_{\mathcal{D}}(h) \leq L_{\mathcal{D}}(A) + \varepsilon] \geq 1 - \delta.$$

The probabilities are over the randomness of V , P and P' and of the samples S_V and S_P .

As an application of this new definition, we show that some statistical query algorithms (see Definitions 5.1 and 5.3) can be PAC verified via a protocol in which the verifier uses less i.i.d. samples than would be required for simulating the statistical query oracle used by the algorithm. Specifically, for a batch \mathbf{q} of statistical queries, the *partition size* $\text{PS}(\mathbf{q})$ is the number of atoms in the σ -algebra generated by \mathbf{q} . If the algorithm uses only batches with small partition size then verification is cheap, as in the following theorem.

Theorem 5.8 (Informal version). *Let A be a statistical query algorithm that adaptively generates at most b batches of queries with precision τ such that each batch \mathbf{q} satisfies $\text{PS}(\mathbf{q}) \leq s$. Then A is PAC verifiable by an interactive proof system where the verifier uses*

$$m_v = \tilde{\Theta} \left(\frac{\sqrt{s} \log(b/\varepsilon\delta)}{\tau^2} + \frac{\log(1/\varepsilon\delta)}{\varepsilon^2} \right)$$

i.i.d. samples.

Proof Idea. The verifier simulates algorithm A . Each time A sends a batch of queries to be evaluated by the statistical query oracle, the verifier sends the queries to the prover, and the prover sends back a vector of purported evaluations. The verifier uses $O(\sqrt{s}/\tau^2)$ i.i.d. random samples to execute a distribution identity tester (Theorem 4.1) to verify that the prover's evaluations are correct up to the desired accuracy τ . \square

In particular, Theorem 5.8 implies the following separation:

Corollary 5.9 (Informal version). *Let $d \in \mathbb{N}$ and let A be a statistical query algorithm such that each batch of queries generated by A corresponds precisely to a σ -algebra with d atoms. Then simulating A using random samples requires $\Omega(d/\tau^2)$ random samples, but there exists a PAC verification protocol for A where the verifier uses $\tilde{O}(\sqrt{d}/\tau^2)$ random samples.*

2.3 Examples

Example 2.4 (Optimizing a portfolio with advice). Consider a task in which an agent selects a subset S consisting of n items from a set $\Omega = \{1, 2, \dots, N\}$ such that $2n \leq N$. Subsequently, an item $i \in \Omega$ is chosen at random according to a distribution $\mathcal{D} \in \Delta(\Omega)$ that is unknown to the agent, and the agent experiences loss $L(i, S) = \mathbb{1}(i \notin S)$.

To help make an optimal decision, the agent has access to an i.i.d. sample $Z = (z_1, \dots, z_m) \sim \mathcal{D}^m$. Let $\mathcal{H} = \binom{\Omega}{n}$ denote the collection of subsets of size n that the agent could select. $\text{VC}(\mathcal{H}) = n$, and therefore estimating the expected loss $L_{\mathcal{D}}(S)$ of each possible choice $S \in \mathcal{H}$ up to precision $\varepsilon > 0$ requires $m_A = \Omega((n + \log(1/\delta))/\varepsilon^2)$ samples.

By Corollary 5.9, if the agent can receive advice from an untrusted prover, it can make an ε -optimal choice using $m_v = O(\sqrt{n} \log(1/\delta\varepsilon)/\varepsilon^2)$ i.i.d. samples. Note that $m_v \ll m_A$ for large n . Furthermore, our expression for m_v is tight in the sense that, by Theorem 2.1, $\Omega(\sqrt{n})$ samples are necessary for verifying the advice of an untrusted prover. \square

3 A Lower Bound for PAC Verification of VC classes

Proof of Theorem 2.1. The first step of the proof is essentially an application of Le Cam’s ‘point vs. mixture’ method (see Yu, 1997), but we develop it here from first principles. Let $X = \{x_1, \dots, x_d\} \subseteq \mathcal{X}$ be a set of size d that is shattered by \mathcal{H} (such a set exists because $\text{VC}(\mathcal{H}) = d$). Let $\mathcal{D}_U = \mathcal{U}(X \times \{0, 1\})$. Let $\mathcal{H}' = \{0, 1\}^X$ be the set of all functions $X \rightarrow \{0, 1\}$. For each $h \in \mathcal{H}'$ let

$$\mathcal{D}_h = \mathcal{U}(\{(x, y) \in X \times \{0, 1\} : y = h(x)\}).$$

For each $k \in \mathbb{N}$ let $\mathcal{D}_{\mathcal{H}', k}$ be the distribution over $(X \times \{0, 1\})^k$ generated by selecting a hypothesis $h \in \mathcal{H}'$ uniformly at random, and then taking k i.i.d. samples from \mathcal{D}_h .

Let T be a (possibly randomized) testing algorithm that takes t i.i.d. samples from an unknown distribution \mathcal{D} and decides correctly with probability at least $7/12$ whether $\mathcal{D} = \mathcal{D}_U$ or whether $\mathcal{D} = \mathcal{D}_h$ for some $h \in \mathcal{H}'$ (if \mathcal{D} is not one of these $|\mathcal{H}'| + 1$ options then we make no assumptions regarding the behavior of T).

First, we show that $t \geq \Omega(\sqrt{d})$. Let $S = ((x_1, y_1), \dots, (x_t, y_t))$ be the input to T . Assume for contradiction that $t = o(\sqrt{d})$. T is a correct tester, which in particular implies that if T is executed on a sample $S \sim \mathcal{D}_{\mathcal{H}', t}$, then with probability at least $7/12$, T outputs “ $\mathcal{D} \in \{\mathcal{D}_h : h \in \mathcal{H}'\}$ ”, and if $S \sim \mathcal{D}_U^t$ then with probability at least $7/12$, T outputs “ $\mathcal{D} = \mathcal{D}_U$ ”. Let

$$E = \left\{ ((x'_1, y'_1), \dots, (x'_t, y'_t)) \in (X \times \{0, 1\})^t : |\{x'_1, \dots, x'_t\}| = t \right\}$$

be the event where S is collision free (i.e., the x_i ’s are distinct), and let $E^C = (X \times \{0, 1\})^t \setminus E$ be the complement. The marginals of $\mathcal{D}_{\mathcal{H}', t}$ and \mathcal{D}_U^t over X^t are uniform. This implies that

$$\mathcal{D}_{\mathcal{H}', t}(E) = \mathcal{D}_U^t(E), \tag{2}$$

and

$$(\mathcal{D}_{\mathcal{H}', t}|_E) \stackrel{d}{=} (\mathcal{D}_U^t|_E) \stackrel{d}{=} \mathcal{U}(E), \tag{3}$$

namely, the probability of collisions is equal for both distributions, and given that there are no collisions both distributions are uniform over E . Combining Eqs. (2) and (3) implies that

$$\forall S' \in E : \mathcal{D}_{\mathcal{H}', t}(S') = \mathcal{D}_U^t(S'). \tag{4}$$

The ‘birthday paradox’ implies that $\Omega(\sqrt{d})$ independent uniform samples from a set X of size d are necessary for collisions to occur with constant probability. Seeing as $t = o(\sqrt{d})$,

$$\mathcal{D}_{\mathcal{H}', t}(E^C) = \mathcal{D}_U^t(E^C) = o(1). \tag{5}$$

Putting this together,

$$\begin{aligned}
\text{TV}(\mathcal{D}_U^t, \mathcal{D}_{\mathcal{H}',t}) &= \frac{1}{2} \sum_{S' \in (X \times \{0,1\})^t} |\mathcal{D}_U^t(S') - \mathcal{D}_{\mathcal{H}',t}(S')| \\
&= \frac{1}{2} \sum_{S' \in E^C} |\mathcal{D}_U^t(S') - \mathcal{D}_{\mathcal{H}',t}(S')| \\
&\quad + \frac{1}{2} \sum_{S' \in E} |\mathcal{D}_U^t(S') - \mathcal{D}_{\mathcal{H}',t}(S')| \\
&= \frac{1}{2} \sum_{S' \in E^C} |\mathcal{D}_U^t(S') - \mathcal{D}_{\mathcal{H}',t}(S')| && \text{(By Eq. (4))} \\
&\leq \mathcal{D}_U^t(E^C) + \mathcal{D}_{\mathcal{H}',t}(E^C) = o(1). && \text{(By Eq. (5))}
\end{aligned}$$

This implies that T can distinguish between $\mathcal{D}_{\mathcal{H}',t}$ and \mathcal{D}_U^t with probability at most $o(1)$, in contradiction to our assumption that T is correct. We conclude that $t \geq \Omega(\sqrt{d})$, as desired.

The second step of the proof is a reduction from the testing problem of \mathcal{D}_U vs. $\{\mathcal{D}_h : h \in \mathcal{H}'\}$ to PAC verification of \mathcal{H} . Let (V, P) be an interactive proof system (as in the theorem's statement) that PAC verifies \mathcal{H} such that the verifier V and honest prover P use m_v and m_p i.i.d. samples from the unknown distribution respectively, and satisfy Definition 1.6 with parameter $\varepsilon = \delta = 1/3$. We construct a tester T for the testing problem. Given sample access to an unknown distribution \mathcal{D} for the testing problem, T operates as follows:

1. Compute $h = [V(\mathcal{D}), P(\mathcal{D}_U)]$. Namely, simulate an execution of the PAC verification protocol as follows. Take a sample $S_V \sim \mathcal{D}^{m_v}$ of m_v i.i.d. samples from \mathcal{D} , and take a sample $S_P \sim \mathcal{D}_U^{m_p}$ of m_p i.i.d. samples from \mathcal{D}_U (seeing as the specification of \mathcal{D}_U is completely known to T , T can generate as many samples from \mathcal{D}_U as necessary using truly random coins). Execute the PAC verification protocol such that V receives input S_V , P receives input S_P , and the output of the verifier at the end of the protocol is $h \in \mathcal{H} \cup \{\text{reject}\}$.
2. Take a sample $S_{\text{test}} \sim \mathcal{D}^c$ of $c = \lceil 18^2 \log(12) \rceil$ i.i.d. samples from \mathcal{D} .
3. If $h = \text{reject} \vee (h \neq \text{reject} \wedge L_{S_{\text{test}}}^{0-1}(h) \leq 1/3)$ then output " $\mathcal{D} \in \{\mathcal{D}_h : h \in \mathcal{H}'\}$ ". Otherwise, output " $\mathcal{D} = \mathcal{D}_U$ ".

We argue that the tester T defined in this manner solves the testing problem correctly with probability at least $7/12$. If $\mathcal{D} = \mathcal{D}_U$ for some h , then $L_{\mathcal{D}}^{0-1}(h') = \frac{1}{2}$ for any $h' \in \mathcal{H}$. In particular, if $h \neq \text{reject}$ then $L_{S_{\text{test}}}^{0-1}(h) \geq 1/2 - 1/18 = 8/18$ with probability at least $11/12$ (by Hoeffding's inequality and the choice of c). Thus, if $\mathcal{D} = \mathcal{D}_U$ then T outputs " $\mathcal{D} = \mathcal{D}_U$ " with probability at least $11/12$.

Conversely, if $\mathcal{D} = \mathcal{D}_{h'}$ for some $h' \in \mathcal{H}$, then $L_{\mathcal{D}}^{0-1}(h') = 0$. From the correctness of the PAC verification protocol, with probability at least $2/3$, either $h = \text{reject}$, or $L_{\mathcal{D}}^{0-1}(h) \leq 1/3$, and in that case with probability at least $11/12$, $L_{S_{\text{test}}}^{0-1}(h) \leq 1/3 + 1/18 = 7/18$ (again by Hoeffding's inequality and choice of c). A union bound implies that if $\mathcal{D} = \mathcal{D}_{h'}$ for some $h' \in \mathcal{H}$ then T outputs " $\mathcal{D} \in \{\mathcal{D}_h : h \in \mathcal{H}'\}$ " with probability at least $1 - 1/3 - 1/12 = 7/12$.

We conclude that T correctly solves the \mathcal{D}_U vs. $\{\mathcal{D}_h : h \in \mathcal{H}'\}$ testing problem with probability at least $7/12$ using m_v i.i.d. samples from the unknown distribution \mathcal{D} . By the first part of the proof, this implies that $m_v \geq \Omega(\sqrt{d})$, as desired. \square

4 Verification of Unions of Intervals

Theorem 4.1 (Canonne et al. 2022, Theorem 1²). *Let $\varepsilon, \delta \in (0, 1)$, let $n \in \mathbb{N}$, and let $\mathcal{P}, \tilde{\mathcal{P}} \in \Delta([n])$ be distributions. There exists a tolerant distribution identity tester that, given a complete description of $\tilde{\mathcal{P}}$ and $m = O(\sqrt{n} \log(1/\delta) \varepsilon^{-2})$ i.i.d. samples from \mathcal{P} , satisfies the following:*

- **Completeness.** *If $\text{TV}(\mathcal{P}, \tilde{\mathcal{P}}) \leq \varepsilon/\sqrt{n}$ then the tester accepts with probability at least $1 - \delta$.*
- **Soundness.** *If $\text{TV}(\mathcal{P}, \tilde{\mathcal{P}}) > \varepsilon$ then the tester rejects with probability at least $1 - \delta$.*

Definition 4.2. *Let $\varepsilon \in [0, 1]$, let \mathcal{X} be a set and let $\mathcal{F} \subseteq \{0, 1\}^{\mathcal{X}}$ be a set of functions. Let $\mathcal{D} \in \Delta(\mathcal{X})$, and let $S \in \mathcal{X}^m$ for some $m \in \mathbb{N}$. We say that S is an ε -sample for \mathcal{D} with respect to \mathcal{F} if*

$$\forall f \in \mathcal{F} : \left| \frac{|\{x \in S : f(x) = 1\}|}{m} - \mathbb{P}_{x \sim \mathcal{D}}[f(x) = 1] \right| \leq \varepsilon.$$

Theorem 4.3 (Vapnik and Chervonenkis, 1968³). *Let $d \in \mathbb{N}$ and $\varepsilon, \delta \in (0, 1)$. Let \mathcal{X} be a set and let $\mathcal{F} \subseteq \{0, 1\}^{\mathcal{X}}$ be a set of functions with $\text{VC}(\mathcal{F}) = d$. Let $\mathcal{D} \in \Delta(\mathcal{X})$, and let $S \sim \mathcal{D}^m$, where*

$$m = \Omega\left(\frac{d \log(d/\varepsilon) + \log(1/\delta)}{\varepsilon^2}\right).$$

Then with probability at least $1 - \delta$, S is an ε -sample for \mathcal{D} with respect to \mathcal{F} .

Proof of Theorem 2.2. We show that Protocol 1 satisfies the requirements of the theorem. For completeness, note that if the prover follows the protocol then $\tilde{P}_{j,0} + \tilde{P}_{j,1} = 1/k$ for all j , so the verifier will never reject at the first ‘if’ statement. Let $\mathcal{B} = \{I_j \times \{y\} : j \in [k] \wedge y \in \{0, 1\}\}$, and let $\mathcal{F} = \{\mathbb{1}_E : E \in \sigma(\mathcal{B})\} \subseteq \{0, 1\}^{[0,1] \times \{0,1\}}$. In words, \mathcal{F} is the set of indicator functions for events in the σ -algebra generated by \mathcal{B} . $\text{VC}(\mathcal{F}) = 2k = O(d/\varepsilon)$, so Theorem 4.3 and the choice of m_p imply that with probability at least $1 - \delta/2$, S_p is an $\varepsilon/(6\sqrt{2k})$ -sample for \mathcal{D} with respect to \mathcal{F} . By the definitions of total variation distance and of an ε -sample, this implies that $\mathbb{P}[\text{TV}(\mathcal{P}, \tilde{\mathcal{P}}) \leq \varepsilon/(6\sqrt{2k})] \geq 1 - \delta/2$. From the correctness of the tester from Theorem 4.1 and a union bound we conclude that with probability at least $1 - \delta$, the verifier does not reject. This establishes completeness.

For soundness, consider two cases.

- The prover is too dishonest, such that $\text{TV}(\mathcal{P}, \tilde{\mathcal{P}}) > \varepsilon/6$. Then by the correctness of Theorem 4.1, the verifier rejects with probability at least $1 - \delta/2$.
- The prover is sufficiently honest, such that $\text{TV}(\mathcal{P}, \tilde{\mathcal{P}}) \leq \varepsilon/6$. Then for any $h' \in \mathcal{H}_d$,

$$\begin{aligned} \left| L_{\mathcal{D}}^{0-1}(h') - L_{\tilde{\mathcal{P}}}^{0-1}(h') \right| &\leq \left| L_{\mathcal{D}}^{0-1}(h') - L_{\mathcal{P}}^{0-1}(h') \right| + \left| L_{\mathcal{P}}^{0-1}(h') - L_{\tilde{\mathcal{P}}}^{0-1}(h') \right| \\ &\leq \left| L_{\mathcal{D}}^{0-1}(h') - L_{\mathcal{P}}^{0-1}(h') \right| + \varepsilon/6, \end{aligned} \tag{6}$$

where the last inequality follows from $\text{TV}(\mathcal{P}, \tilde{\mathcal{P}}) \leq \varepsilon/6$.

²See also Goldreich and Ron (2011) and the discussion following Theorem 5.4 in Canonne (2020).

³Cf. Alon and Spencer (2000), Theorem 13.4.4.

Fix $h' \in \mathcal{H}_d$. We argue that $|L_D^{0-1}(h') - L_P^{0-1}(h')| \leq \varepsilon/3$. Let $Q = \{x \in [0, 1] : h'(x) \neq h'(x^*)\}$, where for each $x \in [0, 1]$, we define $x^* = x_j^*$ such that $x \in I_j$. Namely, Q is the set of points for which applying the discretization procedure alters the output of h' . Then

$$\begin{aligned} |L_D^{0-1}(h') - L_P^{0-1}(h')| &= \left| \mathbb{P}_{(x,y) \sim \mathcal{D}}[h'(x) \neq y] - \mathbb{P}_{(x,y) \sim \mathcal{D}}[h'(x^*) \neq y] \right| \\ &= \left| \mathbb{P}_{(x,y) \sim \mathcal{D}}[h'(x) \neq y \wedge x \in Q] \right. \\ &\quad \left. - \mathbb{P}_{(x,y) \sim \mathcal{D}}[h'(x^*) \neq y \wedge x \in Q] \right| \end{aligned} \tag{7}$$

$$\leq \mathcal{D}(Q') \quad (Q' = Q \times \{0, 1\})$$

$$\leq \sum_{j \in [k]: I_j \cap Q \neq \emptyset} \mathcal{D}(I'_j) \quad (I'_j = I_j \times \{0, 1\})$$

$$= \sum_{j \in [k]: I_j \cap Q \neq \emptyset} \mathcal{P}(I'_j) \quad (\mathcal{D}(I'_j) = \mathcal{P}(I'_j))$$

$$= \mathcal{P}\left(\bigcup \{I'_j : I_j \cap Q \neq \emptyset\}\right)$$

$$\leq \tilde{\mathcal{P}}\left(\bigcup \{I'_j : I_j \cap Q \neq \emptyset\}\right) + \text{TV}(\mathcal{P}, \tilde{\mathcal{P}})$$

$$\leq 2d/k + \text{TV}(\mathcal{P}, \tilde{\mathcal{P}}) \tag{8}$$

$$\leq 2d/k + \varepsilon/6 = \varepsilon/3, \tag{9}$$

where Eq. (7) holds since the loss of h' can differ between \mathcal{D} and \mathcal{P} only for points in Q ; Eq. (8) holds because h' consists of d intervals, which together have $2d$ endpoints, $I_j \cap Q \neq \emptyset$ only if I_j contains one of these endpoints, and if the verifier did not reject then $\tilde{\mathcal{P}}(I'_j) = 1/k$ for all j ; finally Eq. (9) holds by the assumption (in the current case) that the prover is sufficiently honest.

Combining Eq. (9) with Eq. (6) yields $|L_D^{0-1}(h') - L_{\tilde{\mathcal{P}}}^{0-1}(h')| \leq \varepsilon/2$. This implies that a hypothesis h that has minimum loss with respect to $\tilde{\mathcal{P}}$ satisfies $L_D^{0-1}(h) \leq L_D^{0-1}(\mathcal{H}) + \varepsilon$.

We conclude that regardless of the prover's behavior, with probability at least $1 - \delta/2$ the verifier either rejects or outputs a hypothesis with excess loss at most ε , as desired. \square

Assumptions:

- $d, 1/\varepsilon \in \mathbb{N}$ (this can always be achieved by making ε smaller if necessary), $k = 12d/\varepsilon$.
- $m_p = O((d^2 \log(d/\varepsilon) + \log(1/\delta))/\varepsilon^4)$ is a multiple of k .
- $m_v = O(\sqrt{d} \log(1/\delta) \varepsilon^{-2.5})$.
- $S_V \sim \mathcal{D}^{m_v}, S_P \sim \mathcal{D}^{m_p}$.
- $\mathcal{D} \in \Delta([0, 1] \times \{0, 1\})$ is an unknown target distribution.

PROVER($T, S_P, \delta, \varepsilon$):

$I_1, I_2, \dots, I_k \leftarrow$ a partition of $[0, 1]$ into disjoint intervals such that $\cup_{i \in [k]} I_i = [0, 1]$
and $\forall j \in [k] : |\{x_1^P, \dots, x_{m_p}^P\} \cap I_j| = m_p/k$.

for $j \in [k]$:

for $b \in \{0, 1\}$:

$\tilde{P}_{j,b} \leftarrow |\{(x, y) \in S_P : x \in I_j \wedge y = b\}|/m_p$ ▷ Counted as a multiset

send (I_1, \dots, I_k) and $(\tilde{P}_{j,y})_{j \in [k], y \in \{0,1\}}$ to the verifier

VERIFIER($T, S_V, \delta, \varepsilon$):

receive (I_1, \dots, I_k) and $(\tilde{P}_{j,y})_{j \in [k], y \in \{0,1\}}$ from the prover

if $\exists j \in [k]$ s.t. $\tilde{P}_{j,0} + \tilde{P}_{j,1} \neq 1/k$:

output reject and terminate

$x_1^*, \dots, x_k^* \leftarrow$ arbitrary points such that $\forall j \in [k] : x_j^* \in I_j$

execute the tester of Theorem 4.1 with parameters $\varepsilon/6, \delta/2$ where $\mathcal{P}, \tilde{\mathcal{P}} \in \Delta([0, 1] \times \{0, 1\})$ are as follows:

- \mathcal{P} is the distribution generated by sampling $(x, y) \sim \mathcal{D}$ and then outputting (x^*, y) where $x^* = x_j^*$ such that $x \in I_j$
- $\tilde{\mathcal{P}}$ is the distribution such that $\mathbb{P}[(x_j^*, y)] = \tilde{P}_{j,y}$ for all $j \in [k], y \in \{0, 1\}$

if distribution identity tester rejects:

output reject and terminate

$h \leftarrow \operatorname{argmin}_{h' \in \mathcal{H}_d} L_{\tilde{\mathcal{P}}}^{0-1}(h')$

output h

Protocol 1: Verification protocol for unions of d -intervals.

5 Verification of Statistical Query Algorithms

5.1 Definitions

5.1.1 Statistical Query Algorithms

Definition 5.1 (Kearns (1998)). Let Ω be a set, let $\mathcal{D} \in \Delta(\Omega)$ be a distribution, and let $\tau \geq 0$. A statistical query is an indicator function $q : \Omega \rightarrow \{0, 1\}$. An oracle \mathcal{O} is a statistical query oracle for \mathcal{D} with precision τ , denoted $\mathcal{O} \in \text{SQ}(\mathcal{D}, \tau)$, if at each invocation \mathcal{O} takes a statistical query q as input and produces an arbitrary evaluation $\mathcal{O}(q) \in [0, 1]$ as output such that

$$|\mathcal{O}(q) - \mathbb{E}_{X \sim \mathcal{D}}[q(X)]| \leq \tau. \quad (10)$$

In particular, the oracle's evaluations may be adversarial and adaptive, as long as each of them satisfies Eq. (10).

Remark 5.2. The notion of PAC verification of an algorithm (Definition 2.3) requires that the verifier's output be competitive with $L_{\mathcal{D}}(A) = \mathbb{E}[L_{\mathcal{D}}(A^{\mathcal{O}})]$, the expected loss of algorithm A when executed with access to oracle \mathcal{O} . For this expectation to be defined, throughout this paper we only consider oracles whose behavior can be described by a probability measure. In particular, oracles may be adaptive and adversarial in a deterministic or randomized manner, but they cannot be arbitrary.

Definition 5.3. A statistical query algorithm is a (possibly randomized) algorithm A that takes no inputs and has access to a statistical query oracle \mathcal{O} . At each time step $t = 1, 2, 3, \dots$:

- A chooses a finite batch $\mathbf{q}_t = (q_t^1, \dots, q_t^{n_t})$ of statistical queries and sends it to the oracle \mathcal{O} .
- \mathcal{O} sends a batch of evaluations $\mathbf{v}_t = (v_t^1, \dots, v_t^{n_t}) \in [0, 1]^{n_t}$ to A , such that $v_t^i = \mathcal{O}(q_t^i)$ for all $i \in [n_t]$.
- A either produces an output and terminates, or continues to time step $t + 1$.

The resulting sequence $\mathbf{r} = (\mathbf{q}_1, \mathbf{v}_1, \mathbf{q}_2, \mathbf{v}_2, \dots)$ is called a transcript of the execution.

Note that for each t , the choice of \mathbf{q}_t is a deterministic function of $(\mathbf{r}_{<t}, \rho)$, where

$$\mathbf{r}_{<t} = (\mathbf{q}_1, \mathbf{v}_1, \mathbf{q}_2, \mathbf{v}_2, \dots, \mathbf{q}_{t-1}, \mathbf{v}_{t-1}),$$

and ρ denotes the randomness of A . If A terminates, its final output is a deterministic function of (\mathbf{r}, ρ) .

5.1.2 The Partition Size

Definition 5.4. Let Ω be a set, and let $\mathcal{S} \subseteq 2^{\Omega}$ be a collection of subsets. We say that \mathcal{S} is a σ -algebra for Ω if it satisfies the following properties:

- $\Omega \in \mathcal{S}$.
- $\forall S \in \mathcal{S} : \Omega \setminus S \in \mathcal{S}$.
- For any countable sequence $S_1, S_2, \dots \in \mathcal{S} : \cup_{i=1}^{\infty} S_i \in \mathcal{S}$.

Definition 5.5. Let Ω be a set.

- Let $\mathcal{A} \subseteq 2^\Omega$ be a collection of subsets. The σ -algebra generated by \mathcal{A} for Ω , denoted $\sigma(\mathcal{A})$, is the intersection of all σ -algebras for Ω that are supersets of \mathcal{A} .
- Let $\mathcal{F} \subseteq \{0, 1\}^\Omega$ be a set of indicator functions. The σ -algebra generated by \mathcal{F} for Ω is $\sigma(\mathcal{F}) = \sigma(\{A \subseteq \Omega : \mathbb{1}_A \in \mathcal{F}\})$.

Definition 5.6. Let \mathcal{S} be a σ -algebra. The set of atoms of \mathcal{S} is

$$\text{Atoms}(\mathcal{S}) = \{S \in \mathcal{S} : (\forall S' \in \mathcal{S} \setminus \emptyset : S' \not\subseteq S)\}.$$
⁴

Definition 5.7. Let Ω be a set and let $\mathcal{F} = \{f_1, f_2, \dots, f_k\} \subseteq \{0, 1\}^\Omega$ be a finite set of indicator functions. The partition size of \mathcal{F} is $\text{PS}(\mathcal{F}) = |\text{Atoms}(\sigma(\mathcal{F}))| \in \mathbb{N}$, i.e., the number of atoms in the σ -algebra generated by \mathcal{F} for Ω .

5.2 Formal Statements

Theorem 5.8 (PAC Verification of SQ Algorithm). Let $b, s \in \mathbb{N}$, let Ω be a set and \mathcal{H} be a discrete set. Let A be a statistical query algorithm that adaptively and randomly generates some number T of batches $\mathbf{q}_1, \dots, \mathbf{q}_T$ of statistical queries $\Omega \rightarrow \{0, 1\}$ such that with probability 1, $T \leq b$ and $\text{PS}(\mathbf{q}_t) \leq s$ for each $t \in [T]$, and the algorithm outputs a random value $h \in \mathcal{H}$. Let $\mathbb{D} \subseteq \Delta(\Omega)$ be a set of distributions, let $\tau > 0$, and let $L : \Omega \times \mathcal{H} \rightarrow [0, 1]$ be a loss function.

Then there exists a collection of oracles $\mathbb{O} = \{\mathcal{O}_D\}_{D \in \mathbb{D}}$ where $\mathcal{O}_D \in \text{SQ}(D, \tau)$ for all $D \in \mathbb{D}$, such that algorithm A with access to oracles \mathbb{O} is PAC verifiable with respect to \mathbb{D} by a verification protocol that uses random samples, where the verifier and honest prover respectively use

$$m_v = \Theta\left(\frac{\sqrt{s} \log(bk/\delta)}{\tau^2} + \frac{\log(k/\delta)}{\varepsilon^2}\right),$$

and

$$m_p = \Theta\left(\frac{s^3 \log(sbk/\delta\tau)}{\tau^2}\right)$$

i.i.d. samples, with $k = \lceil 8 \log(4/\delta)/\varepsilon \rceil$.

As a corollary, we obtain that for statistical query algorithms of a particular type, the sample complexity of PAC verification has a quadratically lower dependence on the VC dimension of the batches of statistical queries compared to simulating the algorithm using random samples.

Corollary 5.9. Let A be a statistical query algorithm as in Theorem 5.8, and let $d \in \mathbb{N}$. Assume that in each time step $t \in [T]$, $\text{VC}(\mathbf{q}_t) = d$ and $|\mathbf{q}_t| = 2^d$. Namely, \mathbf{q}_t is the set of indicator functions of a σ -algebra with d atoms. Consider an implementation of A that uses random samples to simulate the SQ oracle accessed by A , such that the implementation uses random samples only and does not use any oracles. Simulating an oracle $\mathcal{O} \in \text{SQ}(D, \tau)$ requires

$$m = \Omega\left(\frac{d + \log(1/\delta)}{\tau^2}\right)$$

⁴ $S' \not\subseteq S$ denotes that S' is not a strict subset of S .

i.i.d. samples from \mathcal{D} . In contrast, there exists a protocol that PAC verifies A such that the verifier uses only

$$m_v = \Theta\left(\frac{\sqrt{d} \log(bk/\delta)}{\tau^2} + \frac{\log(k/\delta)}{\varepsilon^2}\right)$$

i.i.d. samples from \mathcal{D} , with $k = \lceil 8 \log(4/\delta)/\varepsilon \rceil$.

The lower bound in the corollary is the standard VC lower bound (Vapnik and Chervonenkis, 1968).

5.3 Proofs

Definition 5.10. Let A be a statistical query algorithm, let \mathbb{D} be a collection of distributions, and let $\varepsilon, \tau > 0$. We say that a collection of oracles $\mathcal{O} = \{\mathcal{O}_D\}_{D \in \mathbb{D}}$ is ε -maximizing with respect to A and \mathbb{D} if for each $D \in \mathbb{D}$, $\mathcal{O}_D \in \text{SQ}(\mathcal{D}, \tau)$ and $\mathbb{E}[L_D(A^{\mathcal{O}_D})] \geq \sup_{\mathcal{O} \in \text{SQ}(\mathcal{D}, \tau)} \mathbb{E}[L_D(A^{\mathcal{O}})] - \varepsilon$.

Assumptions:

- Ω is a set, $\mathcal{D} \in \Delta(\Omega)$ is the population distribution.
- $m_v = \Theta(\sqrt{s} \log(bk/\delta)/\tau^2 + \log(k/\delta)/\varepsilon^2)$.
- $m_p = \Theta((s^3 \log(skb/\delta\tau)) \tau^{-2})$.
- $S_V, S'_V \sim \mathcal{D}^{m_v}, S_P \sim \mathcal{D}^{m_p}$ are independent sets of i.i.d. samples.
- A is a statistical query algorithm to be verified.
- $\tau > 0$ is the accuracy parameter for statistical queries used by A .
- $b \in \mathbb{N}$ is an upper bound on the number of batches generated by A .
- $k = \lceil 8 \log(4/\delta)/\varepsilon \rceil$.

VERIFIER(S_V, S'_V):

for $i \in [k]$:

$h_i \leftarrow \text{VERIFIERITERATION}(S_V)$

▷ Protocol 3

$i^* \leftarrow \text{argmin}_{i \in [k]} L_{S'_V}(h_i)$

output h_{i^*}

PROVER(S_P):

loop forever:

$q \leftarrow \text{receive}$ query from verifier

$v \leftarrow \frac{1}{m_p} \sum_{i \in [m_p]} q(z_i^p)$

send v to verifier

Protocol 2: A PAC verification protocol for statistical query algorithms.

Assumptions: As in Protocol 2.

VERIFIERITERATION(S_V):

for $t \leftarrow 1, 2, \dots$:
 simulate A until it sends a batch of queries or produces an output
 if A sends a batch of queries \mathbf{q}_t :
 if $t \geq b$:
 output reject and terminate
 $\mathbf{a}_t \leftarrow \text{Atoms}(\sigma(\mathbf{q}_t))$
 send \mathbf{a}_t to prover
 receive $\tilde{\mathbf{p}}_t$ from prover
 IDENTITYTEST($S_V, \mathbf{a}_t, \tilde{\mathbf{p}}_t, \tau$)
 $\tilde{\mathbf{v}}_t \leftarrow$ evaluations for \mathbf{q}_t induced by $\tilde{\mathbf{p}}_t$
 send $\tilde{\mathbf{v}}_t$ to A
 else if A produces output h :
 return h

IDENTITYTEST($S_V, \mathbf{a}_t, \tilde{\mathbf{p}}_t, \tau$):

for $i \in [m_V]$:
 $z'_i \leftarrow j$ such that $a_t^j(z_i) = 1$
 execute the distribution identity tester of Theorem 4.1
 with sample $S' = (z'_1, \dots, z'_{m_V})$ to distinguish with
 probability at least $1 - \varepsilon\delta/4b$ between

$$\text{TV}(\tilde{\mathbf{p}}_t, \mathbf{p}_t) \leq \frac{\tau}{2\sqrt{|\mathbf{a}_t|}} \text{ and } \tau \leq \text{TV}(\tilde{\mathbf{p}}_t, \mathbf{p}_t)$$

where \mathbf{p}_t is the distribution that generated S'

if identity tester rejects:
 output reject and terminate

Protocol 3: A subroutine of Protocol 2.

Proof of Theorem 5.8. Fix a collection of oracles $\mathcal{O} = \{\mathcal{O}_D\}_{D \in \mathbb{D}}$ that is $\varepsilon/4$ -maximizing with respect to A and \mathbb{D} . We show that algorithm A with access to the oracles \mathcal{O} is PAC verified by Protocol 2.

To establish completeness, notice that each batch \mathbf{a}_t of queries sent to the prover by VERIFIERITERATION satisfies $\text{VC}(\mathbf{a}_t) = 1$, and there are at most $b \cdot k$ such batches. Hence, by Theorem 4.3 and a union bound, taking m_p as in the statement is sufficient to guarantee that with probability at least $1 - \delta/4$,

$$\forall \text{ iteration } i \in [k] \forall t \in [T] : \|\tilde{\mathbf{p}}_t - \mathbf{p}_t\|_\infty \leq \frac{\tau}{s\sqrt{s}},$$

where \mathbf{p}_t is the vector of correct evaluations, with components $p_t^j = \mathbb{E}_{Z \sim \mathcal{D}}[a_t^j(Z)]$. Hence, with

probability at least $1 - \delta/4$,

$$\forall \text{ iteration } i \in [k] \forall t \in [T] : \|\tilde{\mathbf{p}}_t - \mathbf{p}_t\|_1 \leq \frac{\tau}{\sqrt{s}}. \quad (11)$$

By Eq. (11), Theorem 4.1, and the choice of m_v , with probability at least $1 - \delta/4$, none of the executions of `IDENTITYTEST` cause the verifier to reject.

By a union bound, with probability at least $1 - \delta/2$, Eq. (11) holds and the verifier does not reject. Then, by Lemma 5.11,

$$\forall i \in [k] : \mathbb{P}\left[L_{\mathcal{D}}(h_i) \leq L_{\mathcal{D}}(A) + \frac{\varepsilon}{2}\right] \geq \frac{\varepsilon}{8} \quad (12)$$

By the choice of k ,

$$\mathbb{P}\left[\forall i \in [k] : L_{\mathcal{D}}(h_i) > L_{\mathcal{D}}(A) + \frac{\varepsilon}{2}\right] \leq \left(1 - \frac{\varepsilon}{8}\right)^k \leq e^{-\varepsilon k/8} \leq \frac{\delta}{4}. \quad (13)$$

By Hoeffding's inequality, a union bound, and the choice of m_v ,

$$\mathbb{P}\left[\forall i \in [k] : \left|L_{S'_v}(h_i) - L_{\mathcal{D}}(h_i)\right| \leq \frac{\varepsilon}{2}\right] \geq 1 - \frac{\delta}{4}. \quad (14)$$

Combining Eqs. (11), (13) and (14) via a union bound, we conclude that with probability $1 - \delta$, the verifier does not reject and it outputs $h \in \mathcal{H}$ such that $L_{\mathcal{D}}(h) \leq L_{\mathcal{D}}(A) + \varepsilon$. This establishes completeness.

To establish soundness, consider an interaction between the verifier of Protocol 2 and any deterministic or randomized (possibly malicious and computationally unbounded) prover P' , and examine the following two events.

- Event I: the evaluations provided by P' satisfy

$$\forall \text{ iteration } i \in [k] \forall t \in [T] : \|\tilde{\mathbf{p}}_t - \mathbf{p}_t\|_1 \leq \tau. \quad (15)$$

If the verifier does not reject then Lemma 5.11 implies that Eq. (12) holds. As we saw in the proof for the completeness requirement, this implies that with probability at least $1 - \delta$, the verifier outputs $h \in \mathcal{H}$ such that $L_{\mathcal{D}}(h) \leq L_{\mathcal{D}}(A) + \varepsilon$.

- Event II: there exists an iteration $i \in [k]$ containing a time step $t^* \in [T]$ such that $\|\tilde{\mathbf{p}}_{t^*} - \mathbf{p}_{t^*}\|_1 > \tau$. By Theorem 4.1 and the choice of m_v , with probability at least $1 - \delta/4$ the verifier rejects in time step t^* .

We conclude that in both cases,

$$\mathbb{P}_{S'_v \sim \mathcal{D}^{m_v}}[h = \text{reject} \vee L_{\mathcal{D}}(h) \leq L_{\mathcal{D}}(A) + \varepsilon] \geq 1 - \delta,$$

and this establishes soundness. \square

Lemma 5.11. *In the context of Theorem 5.8, fix a distribution $\mathcal{D} \in \mathbb{D}$ and let $\mathcal{O}_{\mathcal{D}} \in \text{SQ}(\mathcal{D}, \tau)$ be an oracle such that*

$$\mathbb{E}[L_{\mathcal{D}}(A^{\mathcal{O}_{\mathcal{D}}})] \geq \sup_{\mathcal{O} \in \text{SQ}(\mathcal{D}, \tau)} \mathbb{E}[L_{\mathcal{D}}(A^{\mathcal{O}})] - \varepsilon/4.$$

Consider an execution of *VERIFIERITERATION* (Protocol 3). Let G denote the event in which the verifier does not reject, and the query evaluations $\tilde{\mathbf{p}}_t$ provided by the prover satisfy

$$\forall t \in [T] : \|\tilde{\mathbf{p}}_t - \mathbf{p}_t\|_1 \leq \tau, \quad (16)$$

where \mathbf{p}_t is the vector of correct evaluations $p_t^i = \mathbb{E}_{Z \sim D}[a_t^i(Z)]$. Then the output $h_i \in \mathcal{H}$ returned by *VERIFIERITERATION* satisfies

$$\mathbb{P}\left[L_D(h_i) \leq \mathbb{E}[L_D(A^{\mathcal{O}_D})] + \frac{\varepsilon}{2} \mid G\right] \geq \frac{\varepsilon}{8}. \quad (17)$$

Proof. Let \mathcal{O}_G denote the oracle with evaluations that are equal in distribution to the evaluations provided by the prover conditioned on event G occurring. Then

$$\mathbb{E}[L_D(h_i) \mid G] = \mathbb{E}[L_D(A^{\mathcal{O}_G})] \leq \mathbb{E}[L_D(A^{\mathcal{O}_D})] + \varepsilon/4.$$

By Markov's inequality,

$$\begin{aligned} \mathbb{P}\left[L_D(h_i) > \mathbb{E}[L_D(A^{\mathcal{O}_D})] + \varepsilon/2 \mid G\right] &\leq \mathbb{P}\left[L_D(h_i) > \mathbb{E}[L_D(h_i) \mid G] + \varepsilon/4 \mid G\right] \\ &\leq \frac{\mathbb{E}[L_D(h_i) \mid G]}{\mathbb{E}[L_D(h_i) \mid G] + \varepsilon/4} \\ &\leq \frac{1}{1 + \varepsilon/4}, \end{aligned}$$

Hence,

$$\mathbb{P}\left[L_D(h_i) \leq \mathbb{E}[L_D(A^{\mathcal{O}_D})] + \frac{\varepsilon}{2} \mid G\right] \leq \frac{\varepsilon/4}{1 + \varepsilon/4} \leq \frac{\varepsilon}{8},$$

as desired. \square

References

- [1] Noga Alon and Joel H. Spencer. *The Probabilistic Method, Second Edition*. John Wiley, 2000. ISBN 978-0-47137046-8. doi: 10.1002/0471722154. URL <https://doi.org/10.1002/0471722154>.
- [2] Cem Anil, Guodong Zhang, Yuhuai Wu, and Roger B. Grosse. Learning to give checkable answers with prover-verifier games. *CoRR*, abs/2108.12099, 2021. URL <https://arxiv.org/abs/2108.12099>.
- [3] Maria-Florina Balcan, Eric Blais, Avrim Blum, and Liu Yang. Active property testing. In *53rd Annual IEEE Symposium on Foundations of Computer Science, FOCS 2012, New Brunswick, NJ, USA, October 20-23, 2012*, pages 21–30. IEEE Computer Society, 2012. doi: 10.1109/FOCS.2012.64. URL <https://doi.org/10.1109/FOCS.2012.64>.
- [4] Ran Canetti and Ari Karchmer. Covert learning: How to learn with an untrusted intermediary. In Kobbi Nissim and Brent Waters, editors, *Theory of Cryptography - 19th International Conference, TCC 2021, Raleigh, NC, USA, November 8-11, 2021, Proceedings, Part III*, volume 13044 of *Lecture Notes in Computer Science*, pages 1–31. Springer, 2021. doi: 10.1007/978-3-030-90456-2_1. URL https://doi.org/10.1007/978-3-030-90456-2_1.

- [5] Clément L. Canonne. A survey on distribution testing: Your data is big. But is it blue? *Theory of Computing*, pages 1–100, 2020.
- [6] Clément L. Canonne, Ayush Jain, Gautam Kamath, and Jerry Li. The price of tolerance in distribution testing. In Po-Ling Loh and Maxim Raginsky, editors, *Conference on Learning Theory, 2-5 July 2022, London, UK*, volume 178 of *Proceedings of Machine Learning Research*, pages 573–624. PMLR, 2022. URL <https://proceedings.mlr.press/v178/canonne22a.html>.
- [7] Alessandro Chiesa and Tom Gur. Proofs of proximity for distribution testing. In Anna R. Karlin, editor, *9th Innovations in Theoretical Computer Science Conference, ITCS 2018, January 11-14, 2018, Cambridge, MA, USA*, volume 94 of *LIPIcs*, pages 53:1–53:14. Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 2018. doi: 10.4230/LIPIcs.ITCS.2018.53. URL <https://doi.org/10.4230/LIPIcs.ITCS.2018.53>.
- [8] Oded Goldreich and Dana Ron. On testing expansion in bounded-degree graphs. In Oded Goldreich, editor, *Studies in Complexity and Cryptography. Miscellanea on the Interplay between Randomness and Computation - In Collaboration with Lidor Avigad, Mihir Bellare, Zvika Brakerski, Shafi Goldwasser, Shai Halevi, Tali Kaufman, Leonid Levin, Noam Nisan, Dana Ron, Madhu Sudan, Luca Trevisan, Salil Vadhan, Avi Wigderson, David Zuckerman*, volume 6650 of *Lecture Notes in Computer Science*, pages 68–75. Springer, 2011. doi: 10.1007/978-3-642-22670-0_9. URL https://doi.org/10.1007/978-3-642-22670-0_9.
- [9] Shafi Goldwasser, Guy N. Rothblum, Jonathan Shafer, and Amir Yehudayoff. Interactive proofs for verifying machine learning. In James R. Lee, editor, *12th Innovations in Theoretical Computer Science Conference, ITCS 2021, January 6-8, 2021, Virtual Conference*, volume 185 of *LIPIcs*, pages 41:1–41:19. Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 2021. doi: 10.4230/LIPIcs.ITCS.2021.41. URL <https://doi.org/10.4230/LIPIcs.ITCS.2021.41>.
- [10] David Haussler. Decision theoretic generalizations of the PAC model for neural net and other learning applications. *Inf. Comput.*, 100(1):78–150, 1992. doi: 10.1016/0890-5401(92)90010-D. URL [https://doi.org/10.1016/0890-5401\(92\)90010-D](https://doi.org/10.1016/0890-5401(92)90010-D).
- [11] Tal Herman and Guy N. Rothblum. Verifying the unseen: interactive proofs for label-invariant distribution properties. In Stefano Leonardi and Anupam Gupta, editors, *STOC '22: 54th Annual ACM SIGACT Symposium on Theory of Computing, Rome, Italy, June 20 - 24, 2022*, pages 1208–1219. ACM, 2022. doi: 10.1145/3519935.3519987. URL <https://doi.org/10.1145/3519935.3519987>.
- [12] Michael J. Kearns. Efficient noise-tolerant learning from statistical queries. *J. ACM*, 45(6):983–1006, 1998. doi: 10.1145/293347.293351. URL <https://doi.org/10.1145/293347.293351>.
- [13] Ronitt Rubinfeld and Arsen Vasilyan. Testing distributional assumptions of learning algorithms. *CoRR*, abs/2204.07196, 2022. doi: 10.48550/arXiv.2204.07196. URL <https://doi.org/10.48550/arXiv.2204.07196>.

- [14] Shai Shalev-Shwartz and Shai Ben-David. *Understanding Machine Learning - From Theory to Algorithms*. Cambridge University Press, 2014. ISBN 978-1-10-705713-5. URL <http://www.cambridge.org/de/academic/subjects/computer-science/patt>
- [15] Leslie G. Valiant. A theory of the learnable. *Commun. ACM*, 27(11):1134–1142, 1984. doi: 10.1145/1968.1972. URL <https://doi.org/10.1145/1968.1972>.
- [16] V. N. Vapnik and A. Ya. Chervonenkis. The uniform convergence of frequencies of the appearance of events to their probabilities. *Dokl. Akad. Nauk SSSR*, 181(4):781–783, 1968. URL <http://www.ams.org/mathscinet-getitem?mr=0231431>.
- [17] Bin Yu. Assouad, Fano, and Le Cam. In *Festschrift for Lucien Le Cam*, pages 423–435. Springer, 1997.