

# Two-sided Delay Constrained Scheduling: Managing Fresh and Stale Data

Mustafa Can Gursoy and Urbashi Mitra

Department of Electrical and Computer Engineering, University of Southern California, Los Angeles, CA, USA

E-mails: {mgursoy, ubli}@usc.edu

**Abstract**—Energy or time-efficient scheduling is of particular interest in wireless communications, with applications in sensor network design, cellular communications, and more. In many cases, wireless packets to be transmitted have deadlines that upper bound the times before their transmissions, to avoid staleness of transmitted data. In this paper, motivated by emerging applications in security-critical communications, age of information, and molecular communications, we expand the wireless packet scheduling framework to scenarios which involve strict limits on the time *after* transmission, in addition to the conventional pre-transmission delay constraints. As a result, we introduce the scheduling problem under two-sided individual deadlines, which captures systems wherein transmitting too late (stale) and too early (fresh) are both undesired. Subject to said two-sided deadlines, we provably solve the optimal (energy-minimizing) offline packet scheduling problem. Leveraging this result and the inherent duality between rate and energy, we propose and solve the completion-time-optimal offline packet scheduling problem under the introduced two-sided framework. Overall, the developed theoretical framework can be utilized in applications wherein packets have finite lifetimes both before and after their transmission (*e.g.*, security-critical applications), or applications with joint strict constraints on packet delay and information freshness.

**Index Terms**—Scheduling, post-transmission delay constraints, two-sided delay constraints, energy minimization, completion time minimization.

## I. INTRODUCTION

Energy-efficient scheduling is a classical problem in wireless communications, which seeks to characterize and exploit the fundamental trade-off between transmission rate and packet delay [2]–[4]. In particular, for scheduling wireless communication packets over a single hop link, [5] addresses optimal offline scheduling with a single common transmission deadline, before which all packets should be transmitted. Expanding the single-deadline system, [6]–[11] consider each packet having its own individual delay constraint (deadline), before which it needs be processed. Energy-efficient scheduling under similar deadlines is also extended to multi-hop systems in [12]. As each delay constraint relates to, and limits, the time interval before the end of a packet’s transmission [6], [13], we refer to this conventional delay constraint as a *pre-transmission delay constraint*, which ensures that the data is not *stale*.

Portions of this paper have been submitted to the IEEE International Conference on Communications (ICC 2023) [1]. This work is funded in part by one or more of the following grants: NSF CCF-1817200, ARO W911NF1910269, DOE DE-SC0021417, Swedish Research Council 2018-04359, NSF CCF-2008927, NSF CCF-2200221, ONR 503400-78050, ONR N00014-15-1-2550, and the USC Amazon Trust Center.

In this paper, we introduce an additional, alternative delay constraint that limits the time *after* a packet has been processed by the scheduler. Vis-à-vis its conventional pre-transmission counterpart, we call this new deadline the *post-transmission* delay constraint. Modern applications, which will be described in the sequel, necessitate ensuring that the data is not only not too stale, but also *not too fresh*. In addition to bounding delay for time-sensitive applications (*e.g.*, video streaming), a conventional (pre-transmission) delay constraint can also be interpreted as “expiration” at the scheduler node after which the packet becomes unusable. Thus, the scheduler needs to transmit it before its expiry. Using this interpretation, the post-transmission delay constraint arises from expiry at the *destination* of the packet. In other words, a post-transmission delay constraint arises in scenarios wherein processing a packet “too early” is undesirable, as it causes the packet to expire/become unusable at the next node that utilizes it. Combining the conventional pre-transmission deadlines with their post-transmission counterparts, we arrive at scheduling problems that are subject to *two-sided delay constraints*. Several scenarios which incur two-sided delay constraints, wherein transmitting too late and too early are both undesirable include:

**Security-critical relaying:** Suppose a sender (S) is to send information towards a destination (D) that requires restricted access (*e.g.*, a hash, private key, *etc.*), through a relay-aided communication link. To ensure security, S transmits the information by fragmenting it into  $M$  packets due reassembly at D. The goal of the relay (R, the scheduler) is to transmit each of the  $M$  packets so that they are available at D at a certain desired time  $t_R$  for successful reassembly. In case any node is compromised, the security protocol requires each packet to have a limited time it can spend at any node, after which it expires and its content is erased. Thus, R needs to transmit each packet before its individual deadline to avoid expiration (*i.e.*, a pre-transmission delay constraint). As a similar finite lifetime is also employed at D, each packet needs to depart R *later* than a certain deadline to avoid early expiry and ensure availability at  $t_R$ , yielding a post-transmission delay constraint on each packet.

**Information Freshness:** A central controlling unit (the scheduler) seeks to achieve coordinated action among  $M$  agents at a certain time  $t_R$ , via sending each agent a packet of instructions and status information regarding the system of interest. The packets need to be transmitted sufficiently in advance to allow for preparation prior to action, or due to packet delay limitations (pre-transmission delay constraints).

Furthermore, the need for ensuring the agents to have fresh/up-to-date information regarding the system at  $t_R$  requires avoiding transmitting “too early”, which corresponds to a post-transmission delay constraint on each packet<sup>1</sup>.

**Molecular communication:** In a physical layer molecular communication (MC) setup, a transmitter receives stimulus/input molecules in a time sequence [15]–[17], converts them through a chemical reaction, and releases them as its output signal (akin to processing a job, with a molecule being the fundamental job unit and the transmitter being the scheduler). Input molecules exhibit degradation thus have finite lifetimes [18]–[20], thus the MC transmitter is subject to pre-transmission delay constraints. The output molecules are also subject to molecular degradation, thus processing too early may cause the molecule to degrade before providing utility, corresponding to a post-transmission delay constraint.

Herein, we first address the energy-efficient scheduling problem under this new two-sided constrained framework. In addition, we shall also consider the “dual” problem, completion time minimization, which seeks to minimize the total time of the required packet transmissions subject to a fixed energy budget [21]. The version of this problem without individual delay constraints is addressed in [21], wherein iterative and dynamic programming-based approaches are developed and empirically demonstrated to converge to the optimal offline allocation. The solutions of [21] are generalized in [22] to a scheduler with energy harvesting capabilities (*i.e.*, the energy budget is refueled over time), and to packets with varying sizes. In [23], [24], completion time minimization with energy harvesting is considered in the context of wireless powered communication networks, wherein an increased waiting time increases harvested energy and allows for a higher rate of data transmission. Thus, a trade-off between harvested energy and communication delay is considered and exploited for system optimization. In [23], [25], a similar problem to the transmission completion time problem is formulated, which seeks to optimize the average throughput within a fixed time interval. In addition, [25] considers individual transmission deadlines, similar to pre-transmission delay constraints, in its formulation. None of these works consider strict deadlines that limit the time intervals *after* transmission (*i.e.*, “not too fresh”), nor two-sided bounds on allowable departure times. Overall, to the best of our knowledge, energy- or time-efficient scheduling have not been previously considered under the two-sided delay constrained framework, which we treat herein.

The contributions of this paper can be summarized as follows:

- 1) We expand the current energy-efficient packet scheduling framework by incorporating the newly considered post-transmission delay constraints, and formulate the energy-efficient scheduling problem under two-sided delay constraints.
- 2) We discuss the feasibility of the scheduling problem, and provide a provably optimal offline scheduling algorithm

<sup>1</sup>Assuming freshness-critical information is updateable until the departure time of a packet, this interpretation of a post-transmission delay constraint relates to constraining (upper bounding) the so-called *age* of said packet ([14]) at the time of activation.

that minimizes energy consumption under two-sided individual deadlines.

- 3) We formulate and address the dual problem, in which the goal is to minimize the total transmission completion time subject to a fixed energy budget and the two-sided delay constraints.
- 4) We provide an algorithm that achieves provably optimal scheduling under the newly considered post-transmission delay constraints only.
- 5) Following this, we cover pre-transmission delay constraints as well, and provide an offline algorithm that provably minimizes completion time under two-sided individual delay constraints.

In our preliminary work [1], we formulated the energy-efficient scheduling problem under two-sided delay constraints, discussed its feasibility and provided the optimal offline scheduling algorithm. This paper extends and completes [1] by formulating the dual, time-minimization problem under two-sided delay constraints, providing the optimal offline scheduling algorithm and its accompanying optimality proof, as well as providing the full versions of the proofs in [1].

The rest of the paper is organized as follows: Section II presents the two-sided delay constrained problem formulation and provides the definitions used throughout the paper. Section III recites prior literature on scheduling with no individual delays [5] in order to motivate the developed scheduling strategy. Section IV presents our proposed offline scheduling algorithm under two-sided delay constraints, whose optimality is proved in Appendix A. Section V addresses the dual problem, where the scheduler seeks to minimize the total completion time subject to an energy cost. The section provides algorithms subject to post-delays only (whose optimality proof is in Appendix B), as well as to two-sided delays (optimality proof in-line). Section VI concludes the paper.

## II. SYSTEM MODEL

In this section, we describe the theoretical problem of interest in this paper: packet scheduling under two-sided individual delay constraints. However, although the discussion throughout the paper is presented through a particular packet scheduling scenario, we note that the developed framework is presented in a purely theoretical manner, and is abstracted from a specific application.

Herein, we consider a scheduler that inputs packets in a certain temporal sequence<sup>2</sup> with arrival times denoted by  $t_i$ ,  $i = 1, \dots, M$ , where  $M$  is the total number of arriving packets. Without loss of generality, we assume  $t_1 \doteq 0$  throughout the paper. Arriving packets are processed and transmitted by the scheduler, or if the scheduler is busy serving another packet, wait in queue until transmission. Throughout the paper, we assume first-in, first-out (FIFO) processing, which implies that the packets are processed in the order they are received<sup>3</sup>. To illustrate the setup, Figure 1 is presented to provide an instantiation of packet arrival and departure times.

<sup>2</sup>We assume packets of equal sizes in this paper.

<sup>3</sup>We leave scheduling under arbitrary, non-FIFO ordering for future work.




Fig. 1. The system model of interest with  $M = 4$ . Packet arrival times at scheduler  $t = [1, 2, 5, 7.5]$  due to some source(s), and end of transmission (departure) times  $[2, 3.5, 7, 9.5]$ , possibly towards one or many destination(s).

The vector  $\tau = [\tau_1, \dots, \tau_M]^T$  is defined as the vector that holds the processing times of packets. That is, for each packet  $i$ ,  $\tau_i$  denotes the time it takes for the scheduler to transmit the packet. For FIFO ordering, the departure time of packet  $i$  is then equal to  $\sum_{i=1}^M \tau_i$ .

In the model we consider herein, it is assumed that each packet has a finite lifetime that can spend on i) the scheduler, and ii) the destination after it is transmitted. We assume that after this lifetime has expired, the content of the packet is erased from the node and the packet becomes unusable due to expiry. The goal of the scheduler is then to:

- transmit every packet by a specified *end time*  $t_E$ ,
- optimize a certain cost associated with transmission durations  $w(\tau)$  (e.g., energy consumption of transmitting the packet),
- and satisfy each packet's expiry-induced deadlines at both the scheduler and destination.

**The Cost:** Throughout the paper, we assume that the total cost incurred by all  $M$  packet transmissions,  $w(\tau)$ , to have the following properties:

- 1) The overall cost incurred by the system is the sum of individual costs of each transmission  $w(\tau) = \sum_{i=1}^M w(\tau_i)$ .
- 2) For a particular argument  $\tau$ ,  $w(\tau)$  is strictly convex and decreasing in  $\tau$ .<sup>4</sup>
- 3)  $w(\tau_i) > 0$  for all  $i$ .

Bullet Point 2 implies that transmitting a packet faster incurs an increasingly higher cost. Throughout the manuscript, we will use the words cost and energy interchangeably.

**Delay Constraints:** We consider the communication link to be successful with respect to a chosen reference time  $t_R$ , if the following criteria are met at time  $t_R$ :

- 1) Before any packet expires, the scheduler has successfully transmitted them to the destination,
- 2) All transmitted packets have successfully arrived at the destination by the reference time  $t_R$ ,
- 3) At  $t_R$ , all packets are active (i.e., have survived and are not yet expired) at the destination.

Given a packet's arrival time  $t_i$ , the first and second constraints together impose a hard deadline on the time at which packet  $i$  departs the scheduler. In particular, to avoid either expiry at the scheduler or ensure that it successfully arrives to the destination by  $t_R$ , the scheduler has to upper bound the

<sup>4</sup>For wireless applications, the convexity of  $w(\tau)$  can be motivated by inverting the Shannon's capacity formula (see [26, Equation (1.1)] and the discussion therein for further details).




Fig. 2. The valid departure time region induced by pre- and post-delay constraints. The packet arrives at time  $t = 0$ , and the reference time is  $t_R = 12$ . Pre- and post-delay constraints are  $T_{pre} = 6$  and  $T_{post} = 9$ , respectively, resulting in a valid departure time region of  $[3, 6]$ .

packet's allowed time for processing. As this phenomenon relates to the time interval *before* transmission, we call this constraint a *pre-transmission delay constraint*, and denote it by  $T_{pre,i}$ , also referred to as a *pre-delay constraint* for brevity. As will be detailed in Section IV, we assume  $T_{pre,i} > 0$ , as otherwise, the scheduling problem becomes ill-posed. Furthermore, we consider the end time of the scheduling frame  $t_E = t_M + T_{pre,M}$  throughout the paper.

In contrast to the first two conditions, the third constraint imposes a *lower* bound on the departure time of packet  $i$ . Note that if a packet is transmitted too early, the transmitted packet would not survive until  $t_R$  due to expiry. As this time interval limits the time interval *after* a packet's transmission, we call this constraint a *post-transmission delay constraint*, and denote it by  $T_{post,i}$ . Similar to its pre-delay counterpart, throughout the paper, we also refer to this constraints as the *post-delay constraint* for brevity. Overall, Figure 2 depicts the feasible region of transmission imposed by these two constraints.

As a convention, we define  $t_{M+1} \doteq t_E$ , and define the time between two packet arrivals (i.e., the inter-arrival time) as  $d_i = t_{i+1} - t_i$ . Thus, for energy minimization, we consider the following optimization problem:

$$\min_{\tau} w(\tau) = \sum_{i=1}^M w(\tau_i) \quad (1a)$$

$$\text{s.t.} \quad \sum_{i=1}^k \tau_i \geq \sum_{i=1}^k d_i, \quad k \in \{1, \dots, M-1\}, \quad (1b)$$

$$\sum_{i=1}^M \tau_i = t_E = \sum_{i=1}^M d_i, \quad (1c)$$

$$\sum_{i=1}^k \tau_i - \sum_{i=1}^{k-1} d_i \leq T_{pre,k}, \quad k \in \{1, \dots, M\} \quad (1d)$$

$$\sum_{i=1}^k \tau_i \geq t_R - T_{post,k}, \quad k \in \{1, \dots, M\}. \quad (1e)$$

Here, Conditions (1d) and (1e) refer to the aforementioned pre- and post-transmission delay constraints, respectively. Conditions (1b) and (1c) are referred to as the *non-idling* constraints [6] and they follow from the cost function  $w(\tau)$  being decreasing in  $\tau$ . Note that, if we have  $\sum_{i=1}^k \tau_i < \sum_{i=1}^k d_i$  for some  $i$ , this implies that the time interval  $[\sum_{i=1}^k (d_i - \tau_i), \sum_{i=1}^k d_i]$  is unused. Then,  $w(\tau)$  can be further decreased by using this unused interval, which implies that  $\tau$  cannot be optimal. Thus, in order to be eligible for optimality, an allocation has to satisfy the non-idling constraints ((1b)-(1c)).

Throughout the paper, we consider optimal *offline* scheduling, in which an idealized scheduler is assumed to have non-causal and perfect information on the arrival times  $t_i$  for all  $i$ ,

**Algorithm 1** Optimal offline scheduling for the single deadline scenario (Uysal-Biyikoglu *et al.* [5]).

**Inputs:**  $M$ ,  $\mathbf{d}$ ,  $t_E = t_R$

- 1: For the first packet,  $m_1 = \max_{k \in [1, \dots, M]} \left\{ \frac{1}{k} \sum_{i=1}^k d_i \right\}$
  - 2: The maximizing index  $k_1 = \max \left\{ k : \frac{1}{k} \sum_{i=1}^k d_i = m_1 \right\}$
  - 3: Set  $\tau_i = m_1$ , for all  $i \in \{1, \dots, k_1\}$
  - 4:  $j \leftarrow 1$
- For rest of the packets, until the end of batch, **do**
- 5:  $m_{j+1} = \max_{k \in [1, \dots, M-k_j]} \left\{ \frac{1}{k} \sum_{i=1}^k d_{i+k_j} \right\}$
  - 6:  $k_{j+1} = k_j + \max \left\{ k : \frac{1}{k} \sum_{i=1}^k d_{i+k_j} = m_{j+1} \right\}$
  - 7:  $\tau_i = m_j$ , for all  $i \in \{k_{j-1} + 1, \dots, k_j\}$
  - 8:  $j \leftarrow j + 1$
- return**  $\tau$




Fig. 3. A demonstration of Algorithm 1 on two toy problems with  $M = 4$  and  $t_R = t_E = 32$ , under different  $\mathbf{d}$  vectors.

as well as perfect information on the delay constraints  $T_{\text{pre},i}$  and  $T_{\text{post},i}$ . We note that solutions to our formulation lower bounds  $w(\tau)$  that can be achieved by a practical scheduler that is imperfect in delay constraint/arrival information, or is an online scheduling algorithm.

### III. OPTIMAL SCHEDULING WITH A SINGLE COMMON DEADLINE

To provide insight, we first address the special case of the problem in (1), wherein all packets are only subject to a single common deadline (no individual pre- or post-delay constraints). The goal of the scheduler is then to minimize  $w(\tau) = \sum_{i=1}^M w(\tau_i)$  subject only to the non-idling constraints described by (1b)-(1c). Due to the absence of pre-delays (*i.e.*,  $T_{\text{pre},i} = t_R - t_i$  for all  $i$ ), the end time (also referred to as the “single delay” in this section) is  $t_E = t_R$ . The optimal offline scheduling under a single delay has been addressed by [5], whose strategy to compute the optimal  $\tau$  is presented in Algorithm 1.

As also mentioned in [5], [6], an interesting observation is that the optimal  $\tau$  is not dependent on the specific  $w(\tau)$  function, as long as the cost is strictly convex, decreasing, and non-negative. To illustrate the approach of Algorithm 1, we present two toy problems in Figure 3.

- *Example 1:* When feasible in terms of the non-idling constraints, fully balancing each  $\tau_i = 8$  minimizes a strictly convex, non-increasing  $w(\tau)$ .
- *Example 2:* Fully balancing with  $\tau_i = 8$  for all  $i$  violates the non-idling constraint for  $i = 4$ , because of the late arrival of the fourth packet. Note that in

Line 2 of Algorithm 1, index  $k = 3$  yields the largest  $\frac{1}{k} \sum_{i=1}^k d_i$ . Thus, the algorithm sets  $\tau_i = \frac{4+8+18}{3} = 10$  for  $i = 1, 2, 3$ , and proceeds to the next iteration. In the second iteration,  $\tau_4 = d_4 = 2$  is set and the algorithm terminates.

Overall, Algorithm 1 seeks to balance  $\tau_i$  as much as possible, while still satisfying the non-idling constraints. The non-idling constraints and the strict convexity of  $w(\tau)$  jointly imply that the scheduler should maximally exploit the late arrivals of future packets (if applicable), but no more. Overall, a rule of thumb is to maximally balance transmission durations in order to minimize a strictly convex cost function, which we will also leverage to devise our proposed algorithms herein.

### IV. ENERGY-EFFICIENT SCHEDULING UNDER TWO-SIDED DELAY CONSTRAINTS

In this section, we address the full problem with two-sided delay constraints. We first present the conditions that allow for a feasible solution to exist, as the two-sided problem is not guaranteed to have one.

#### A. Feasibility

In order to successfully transmit each packet, each packet needs to have a valid, non-negative region for its departure time (*e.g.*, Figure 2). In other words, the two-sided problem is infeasible whenever there exists a packet with index  $i \in \{1, \dots, M\}$  whose the pre- and post-delay induced bounds do not yield a valid interval. Therefore, in order to ensure a feasible solution, a necessary condition is to have

$$t_i + T_{\text{pre},i} \geq t_R - T_{\text{post},i}, \quad \text{for all } i \in \{1, \dots, M\}. \quad (2)$$

Furthermore, FIFO ordering leads to an additional criterion for feasibility. Assume  $j < i$ . By definition, the post-delay-induced lower bound on the departure time of  $j$  is  $t_R - T_{\text{post},j}$ . If the pre-delay-induced departure deadline of  $i$  ( $t_i + T_{\text{pre},i}$ ) is smaller than  $t_R - T_{\text{post},j}$ , the mandatory waiting for packet  $j$  violates the pre-delay constraint of packet  $i$ , which results in packet loss/drop. Therefore, assuming instantaneous processing with zero duration ( $\tau_i = 0$ ) is infeasible, FIFO ordering tightens the feasibility criteria for each  $i \in \{1, \dots, M\}$  to

$$\begin{aligned} t_i + T_{\text{pre},i} &> t_R - T_{\text{post},j}, \quad \text{for all } j = 1, \dots, i-1 \\ t_i + T_{\text{pre},i} &\geq t_R - T_{\text{post},i}. \end{aligned} \quad (3)$$

Lastly, we need to have  $T_{\text{pre},i} > 0$  and  $T_{\text{post},i} > 0$  for all  $i$  as the trivial validity conditions on pre- and post-delays. Throughout the paper, we assume the problem is well-posed with a feasible solution.

#### B. Definitions

Herein, we provide some definitions to classify individual packets, as well as consecutive collections of packets. We note that these definitions will be used in the sequel to both present the scheduling algorithm, as well as prove its optimality.

**Definition 1 (Regular end packet).** Packet  $i$  is a *regular end packet* if its transmission ends precisely at the arrival of the

$(i+1)$ th packet in the sequence. That is, a regular end packet satisfies  $\sum_{j=1}^i \tau_j = t_{i+1} = \sum_{j=1}^i d_j$ .

**Definition 2 (Pre-critical packet).** Packet  $i$  is a *pre-critical packet* if its transmission ends precisely at its pre-transmission delay constraint. That is,  $\sum_{j=1}^i \tau_j = t_i + T_{\text{pre},i}$ , and the packet  $i$  is said to critically satisfy its pre-delay.

**Definition 3 (Post-critical packet).** Packet  $i$  is a *post-critical packet* if its transmission ends precisely at its post-transmission delay constraint. That is,  $\sum_{j=1}^i \tau_j = t_R - T_{\text{post},i}$  and the packet  $i$  is said to critically satisfy its post-delay.

**Definition 4 (Group).** A *group* is the (smallest) collection of consecutive packets  $\{i_1, \dots, i_2\}$  whose transmission durations satisfy  $\sum_{j=1}^{i_1-1} \tau_j = \sum_{j=1}^{i_1-1} d_j$  and  $\sum_{j=1}^{i_2} \tau_j = \sum_{j=1}^{i_2} d_j$ . That is,  $\{\tau_{i_1}, \dots, \tau_{i_2}\}$  describes the time interval  $[\sum_{j=1}^{i_1-1} \tau_j, \sum_{j=1}^{i_2} \tau_j]$  that begins and ends with a packet arrival.

Referring to Figure 3, Example 2 has two groups,  $\{\tau_1, \tau_2, \tau_3\}$  and  $\{\tau_4\}$ , where the first group's interval ends with the arrival of the fourth packet. Example 1 has only a single group  $\{\tau_1, \tau_2, \tau_3, \tau_4\}$ .

**Definition 5 (Subgroup).** A *subgroup* is a collection of consecutive packets within a group that have equal transmission durations.

**Definition 6 (Regular subgroup).** A *regular subgroup* is a subgroup that ends with a regular end packet (*i.e.*, leaves an empty buffer for the next subgroup).

**Definition 7 (Critical subgroups).** A *pre-critical (post-critical) subgroup* is a subgroup that ends with a pre-critical (post-critical) packet.

**Definition 8 (Type-R group).** A *regular group (type-R group)* is a group in which no pre- or post-critical packets are present.

**Definition 9 (Type-H group).** A *heterogeneous group (type-H group)* is a group that contains at least one pre- or post-critical packet.

Note that by definition, the last subgroup of any group is a regular subgroup. Furthermore, if a group contains a single subgroup, then the group is regular (*i.e.*, does not contain any delay-critical packets). We refer the reader to Figure 4 and its discussion in Subsection IV-C for exemplification on these definitions.

### C. Optimal Offline Scheduling under Two-Sided Constraints

Herein, we present an algorithm that computes the optimal offline schedule that minimizes a convex energy cost under two-sided delay constraints and solves the problem described by (1). Prior to providing the algorithm, we note for a certain packet  $i$ , the inter-arrival time  $d_i$  may be longer than the pre-transmission delay of the packet (*i.e.*,  $d_i > T_{\text{pre},i}$ ), in which case a pre-transmission delay-induced idling has to occur. We note that for a well-posed problem with a feasible solution, very similar to [6, Proposition 3.1], a case with  $d_i > T_{\text{pre},i}$  for some  $i$  would generate two completely separated scheduling

intervals (for packets  $\{1, \dots, i\}$  and  $\{i+1, \dots, M\}$ , corresponding to time intervals  $[0, t_i + T_{\text{pre},i}]$  and  $[t_{i+1}, t_E]$ ), which essentially yields two independent sub-problems that do satisfy  $d_i \leq T_{\text{pre},i}$  for all  $i$ .<sup>5</sup> Since solving these two sub-problems separately is equivalent to finding the optimal  $\tau$  of the overall system, we assume  $d_i \leq T_{\text{pre},i}$  for all  $i$  throughout the rest of the paper.

Algorithm 2 presents the proposed optimal offline scheduling algorithm for the two-sided problem defined by (1). Similar to the single deadline scenario in Section III, Algorithm 2 also seeks to balance the transmission durations as much as possible. However, the natural differences in the two-sided delay scenario are the strict limits induced by the pre- and post-transmission delay constraints. We first note that the min operation executed when computing  $\tau_{[k]}$  and  $n_{[k]}$  circumvent any pre-delay constraint violations (for the pre-delay-only scenario, see the approach in [6]), and the max operation when computing  $A_{[k]}$ ,  $\max \left\{ \frac{\sum_{i=1}^k d_i}{k}, \frac{t_E - T_{\text{post},k}}{k} \right\}$ , alongside the overall arg max operation in Line 4, together avoid post-delay constraint violations. Thus, Algorithm 2 provides an algorithm that yields a valid solution.

Herein, we present a toy problem in Figure 4 to demonstrate the operating principles of the algorithm<sup>6</sup>. We first note that although equalizing all  $\tau_i$  is optimal to minimize a convex cost, it is not feasible due to multiple pre-/post-delay constraints. In particular, the pre-delay constraint of the second packet strictly upper bounds the departure of the packet by  $\tau_1 + \tau_2 \leq t_2 + T_{\text{pre},2} = 20$ . Allocating these two packets equally within said interval is indeed valid for both their pre-/post-delays, thus the algorithm allocates  $\tau_1 = \tau_2 = 10$  in its first iteration. Note that in the meantime, packets 3 and 4 have arrived, but are waiting in queue for processing due to FIFO. At time  $t = 20$ , the allocation of these packets begins. Due to convexity of  $w(\tau)$ , the remaining time of 21 units is best allocated by equalizing  $\tau_3$  and  $\tau_4$ , however this is infeasible due to the late post-delay of packet 3. To satisfy  $T_{\text{post},3} = 10$ , the algorithm allocates  $\tau_3 = 13$ , and the remaining duration is left to the last packet  $\tau_4 = 8$ . Overall, the resultant  $\tau$  for this toy example consists of a single type-H group, with three subgroups: The first subgroup  $\{\tau_1, \tau_2\}$  is pre-critical, the second subgroup  $\{\tau_3\}$  is post-critical, and the last one  $\{\tau_4\}$  is regular. Furthermore, we observe that in cases where pre- or post-delays are constraining fully balancing the durations, Algorithm 2 allocates the durations critically. That is, if the constraining deadline is a pre-delay of packet  $i$ , then  $\sum_{j=1}^i \tau_j = t_i + T_{\text{pre},i}$ , or if it is a post-delay of packet  $i'$ , then  $\sum_{j=1}^{i'} \tau_j = t_R - T_{\text{post},i'}$ .

### D. Optimality of Algorithm 2

Prior to proving the output of Algorithm 2 is the optimal one, we first provide a needed lemma.

**Lemma 1.** *For an optimal allocation  $\tau$  for the two-sided delay case, we have the following relations:*

<sup>5</sup>Note that if there exists multiple such packets, this argument can be recursively generalized.

<sup>6</sup>Unlike the single delay scenario,  $t_E < t_R$  is possible under two-sided deadlines, in cases where  $T_{\text{pre},M} < t_R - t_M$ .




Fig. 4. A demonstration of Algorithm 2, with  $M = 4$  packets. The pre- and post-delay constraints  $\mathbf{T}_{\text{pre}} = [24, 16, 34, 23]$  and  $\mathbf{T}_{\text{post}} = [37, 31, 8, 24]$ , and the reference time  $t_R = 41$ . Blue/red marks on departure times represent pre-/post-criticality of the marked packet, respectively.

- 1) A regular subgroup has a transmission duration that is **greater than or equal to** the subsequent subgroup.
- 2) A post-critical subgroup has a transmission duration that is **greater than or equal to** the subsequent subgroup.
- 3) A pre-critical subgroup has a transmission duration that is **less than or equal to** the subsequent subgroup.

*Proof.* The first two items follow from Lemma 3 and [5, Lemma 2]. Note that if they did not hold, then one could simply yield a smaller energy cost by further *balancing* the transmission durations through decreasing the durations of the subsequent subgroup and increasing the durations of the subgroup of interest, without violating the delay constraints (similar to Lemma 3). Similarly, if the third condition did not hold, the scheduler could decrease the cost by further balancing, via increasing the durations of the subsequent subgroup and decreasing the durations of the subgroup of interest, again without violating the (pre-)delay constraints (also see [6, Lemma 3.2]).<sup>7</sup>  $\square$

Herein we present Lemma 2, which shows that the regular and post-critical subgroups produced by Algorithm 2 satisfies the comparative relations dictated by Lemma 1 (conditions 1 and 2). The proof for a pre-critical subgroup follows an identical procedure, and is omitted for conciseness.

**Lemma 2.** *Let  $\tau$  denote the output of Algorithm 2. For a pair of consecutive subgroups in  $\tau$  where the prior subgroup is regular or post-critical, let  $\tau_1$  and  $\tau_2$  be their transmission durations, respectively. Then,  $\tau_1 \geq \tau_2$ .*

*Proof.* Let the algorithm's output be such that the former subgroup has  $n_1$  packets of  $\tau_1$  duration, and the latter subgroup has  $n_2$  packets with  $\tau_2$  duration. Suppose we have  $\tau_1 < \tau_2$ . Then, the total time interval covered by both subgroups,

$(n_1\tau_1 + n_2\tau_2)$ , satisfies

$$\begin{aligned} \frac{n_1\tau_1 + n_2\tau_2}{n_1 + n_2} &= \frac{n_1}{n_1 + n_2}\tau_1 + \frac{n_2}{n_1 + n_2}\tau_2 \\ &> \frac{n_1}{n_1 + n_2}\tau_1 + \frac{n_2}{n_1 + n_2}\tau_1 = \tau_1. \end{aligned} \quad (4)$$

Let the index of the first packet of the first subgroup have the index  $(k + 1)$ . Equation (4) implies that from the algorithm's perspective, allocating  $\frac{n_1\tau_1 + n_2\tau_2}{n_1 + n_2}$  for packets  $\{k + 1, \dots, k + n_1 + n_2\}$  would yield a larger value than allocating  $\tau_1$  for packets  $\{k + 1, \dots, k + n_1\}$ . Thus, given the option of allocating for packets  $\{k + 1, \dots, k + n_1 + n_2\}$  a duration of  $\frac{n_1\tau_1 + k n_2\tau_2}{n_1 + n_2}$ , the maximizer at Line 4 of Algorithm 2 cannot choose allocating  $\tau_1$  for packets  $\{k + 1, \dots, k + n_1\}$  (*i.e.*, there is a larger value<sup>8</sup>), which yields a contradiction. Thus, consecutive subgroups have to have non-increasing durations.  $\square$

Overall, in light of Lemmas 1-2, we provide the main result for the two-sided case in the theorem below.

**Theorem 1.** *Algorithm 2 yields an optimal  $\tau$  that minimizes any cost that is strictly convex, decreasing, and positive.*

*Proof.* See Appendix A.  $\square$

We emphasize that similar to the single deadline case ([5]) and the pre-delay only case ([12]), the optimal solution for the two-sided case is also independent of the particular energy function  $w(\tau)$ . That is, regardless of the particular function, as long as  $w(\tau)$  is strictly convex and decreasing, the output of Algorithm 2 is the optimal schedule.

A special case of the scheduling problem under two-sided delay constraints is the case wherein only post-delays are relevant, and pre-delays are  $T_{\text{pre},i} = t_R - t_i$  for all  $i$  (thus unconstraining). For this so-called *one-sided*, post-delay constrained case, we have the following lemma:

**Lemma 3.** *Having  $\tau_i \geq \tau_{i+1}$  for all  $i$  is a necessary condition for optimality in the one-sided, post-transmission delay-constrained scenario.*

<sup>7</sup>Though it is unlikely to occur in practice, the problem formulation theoretically allows for cases with coinciding pre-/post-delay induced bounds on departure times, that is  $t_i + T_{\text{pre},i} = t_R - T_{\text{post},i}$  for some  $i$ . This forces the departure time of packet  $i$  to a single point, essentially dividing the problem into two sub-problems for packets  $\{1, \dots, i\}$  and  $\{i + 1, \dots, M\}$ . In such cases, the pre-/post-criticality of the subgroup ending with  $i$  can be determined in compliance with this lemma.

<sup>8</sup>For simplicity of presentation, this argument implicitly assumes such an increase does not violate any pre-delays. That said, if there is a pre-delay constraint that prevents this, a critical allocation for said pre-delay constraint also satisfies the same argument.



**Algorithm 2** Optimal (energy-minimizing) offline scheduling for two-sided transmission delays.

---

**Inputs:**  $M$ ,  $\{T_{\text{post},1}, \dots, T_{\text{post},M}\}$ ,  $\{T_{\text{pre},1}, \dots, T_{\text{pre},M}\}$ ,  $t$ ,  $t_R$   
Set pre-delay-induced departure deadlines  $\nu_i = t_i + T_{\text{pre},i}$ , for  $i = 1, \dots, M$   
The end time  $t_E = t_M + T_{\text{pre},M}$   
.....  
For the first packet:  
1:  $\tau_{[1]} = \max\{d_1, t_R - T_{\text{post},1}\}$ ,  $n_{[1]} \doteq 1$   
2:  $\tau_{[2]} = \min\{T_{\text{pre},1}, \max\{\frac{d_1+d_2}{2}, \frac{t_R-T_{\text{post},2}}{2}\}\}$   
 $n_{[2]} = \arg \min\{T_{\text{pre},1}, \max\{\frac{d_1+d_2}{2}, \frac{t_R-T_{\text{post},2}}{2}\}\}$   
3:  

$$A_{[k]} = \left\{ T_{\text{pre},1}, \frac{d_1 + T_{\text{pre},2}}{2}, \dots, \frac{T_{\text{pre},k-1} + \sum_{i=1}^{k-2} d_i}{k-1}, \right.$$

$$\left. \max\left\{ \frac{\sum_{i=1}^k d_i}{k}, \frac{t_R - T_{\text{post},k}}{k} \right\} \right\}$$
  
 $\tau_{[k]} = \min A_{[k]}$   
 $n_{[k]} = \arg \min A_{[k]}$   
4:  $i^* = \arg \max \tau_{[i]}$   
 $\tau_1 \leftarrow \tau_{[i^*]}$   
 $\tau_1 = \dots = \tau_{n_{[i^*]}} \leftarrow \tau_1$   
.....  
For the remaining packets:  
5: **if**  $n_{[i^*]} = i^*$  and  $\sum_{i=1}^{i^*} d_i \geq t_R - T_{\text{post},i^*}$  **then**  
6:   %%The last packet in the allocated batch is regular.  
7:   Move to packet  $n_{[i^*]} + 1 = i^* + 1$ , and proceed the same as Lines 1-4.  
8: **else if**  $n_{[i^*]} = i^*$  and  $\sum_{i=1}^{i^*} d_i < t_R - T_{\text{post},i^*}$  **then**  
9:   The last packet in the allocated batch is post-critical.  
10:   **for**  $i = i^* + 1$  to  $M$  **do**  
11:     Set  $t_i = \max\{t_R - T_{\text{post},i^*}, t_i\}$   
12:     **if**  $t_i = t_E - T_{\text{post},i^*}$  **then**  
13:        $T_{\text{pre},i} = \nu_i - (t_R - T_{\text{post},i^*})$   
14:     **end if**  
15:   **end for**  
16:   Update  $d_i = t_{i+1} - t_i$  for  $i = i^* + 1, \dots, M$   
17:   Move to packet  $n_{[i^*]} + 1 = i^* + 1$ , and proceed the same as Lines 1-4.  
18: **else if**  $n_{[i^*]} \neq i^*$  **then**  
19:   The last packet in the allocated batch is pre-critical.  
20:   **for**  $i = n_{[i^*]} + 1$  to  $M$  **do**  
21:     Set  $t_i = \max\{\nu_{n_{[i^*]}}, t_i\}$   
22:     **if**  $t_i = t_R - T_{\text{post},i^*}$  **then**  
23:        $T_{\text{pre},i} = \nu_i - \nu_{n_{[i^*]}}$   
24:     **end if**  
25:   **end for**  
26:   Update  $d_i = t_{i+1} - t_i$  for  $i = n_{[i^*]} + 1, \dots, M$   
27:   Move to packet  $n_{[i^*]} + 1$ , and proceed the same as Lines 1-4.  
28: **end if**  
29: **return**  $\tau$

---

The proof is identical to [5, Lemma 2]. In the sequel, this lemma will motivate our design of the transmission completion time minimizing algorithm (Subsection V-A).

## V. ENERGY CONSTRAINED COMPLETION TIME MINIMIZATION

Section IV introduces strategies that minimize the incurred cost (e.g., energy consumption) while subjecting each packet

to pre- and post-transmission delay constraints. However, the ‘‘dual’’ problem may also be of interest, where the scheduler seeks to minimize the total transmission completion time  $T_c = \sum_{i=1}^M \tau_i$ , with a fixed energy budget  $w_{\text{max}}$ . Herein, we seek to find the optimal offline allocation that yields said shortest transmission completion time, while transmitting all  $M$  packets until a reference time  $t_R$ , as well as having all  $M$  packets received and active (i.e., not expired) at  $t_R$  (similar to Sections II-IV). In addition to an energy budget constraint  $w_{\text{max}}$ , this problem setup again yields *pre-delay* and *post-delay constraints* as well. The overall problem can be formulated as

$$\begin{aligned} \min_{\tau} \quad & T_c = \sum_{i=1}^M \tau_i \\ \text{s.t.} \quad & \sum_{i=1}^k \tau_i \geq \sum_{i=1}^k d_i, \quad k \in \{1, \dots, M-1\}, \\ & w(\tau) = \sum_{i=1}^M w(\tau_i) \leq w_{\text{max}}, \\ & \sum_{i=1}^k \tau_i \geq t_R - T_{\text{post},k}, \quad k \in \{1, \dots, M\}, \\ & \sum_{i=1}^k \tau_i - \sum_{i=1}^{k-1} d_i \leq T_{\text{pre},k}, \quad k \in \{1, \dots, M\}. \end{aligned} \quad (5)$$

### A. Completion Time Minimization under Post-Delays

Though the ultimate goal is addressing the two-sided problem (presented in the next subsection), we note that pre- and post-delays need to be treated differently for the completion time minimization framework. To provide insight into the role of post-delays in the completion time problem, as well as build the results in a cumulative manner, we first address the one-sided, post-delay only case. Recall that the post-delay only case corresponds to having  $T_{\text{pre},i} = t_R - t_i$  for all  $i$ . Furthermore, note that depending on the relationship between  $t_R$ ,  $w(\tau)$ ,  $w_{\text{max}}$ ,  $d$ , and  $T_{\text{post}}$ , there can be scenarios in which  $T_c \leq t_R$  is not feasible (e.g., not enough energy to complete transmissions until  $t_R$ ). Herein, we assume the problem is well-posed and a feasible solution exists.

To motivate algorithm design, we provide the following lemma that provides necessary conditions for the optimal duration vector  $\tau$  that achieves the minimum completion time under two-sided delays (denoted by  $T_c^*$  throughout the paper). Note that if the strict post-delay lower bound of packet  $M$ ,  $T_c = t_R - T_{\text{post},M}$ , is achievable with the available budget  $w_{\text{max}}$ , all  $\tau$  that satisfy  $w(\tau) \leq w_{\text{max}}$  and  $\sum_{i=1}^M \tau_i = t_R - T_{\text{post},M}$  yield the smallest possible completion time, making the smallest completion time  $T_c^* = t_R - T_{\text{post},M}$ . When presenting Lemmas 4-5, we will consider the more general case where  $T_c^* > t_R - T_{\text{post},M}$ .

**Lemma 4** (Necessary conditions for completion time optimality). *Let  $T_c^* > t_R - T_{\text{post},M}$  be the minimum completion time, achieved by some duration vector  $\tau$ . Then, the following are true:*

- 1)  $w(\tau) = w_{\text{max}}$ .
- 2) The vector  $\tau$  is the optimal vector for the energy minimization problem with end time  $t_E = T_c^*$ , and its achieved minimum energy is  $w_{\text{max}}$ .

*Proof.* We show the statements in their order of presentation:

- 1) Suppose  $w(\tau) < w_{\max}$ . Then,  $\tau$  leaves unused energy that could have been used to further decrease  $\tau_M$ , thereby decreasing  $T_c$ . Hence,  $T_c^* < \sum_{i=1}^M \tau_i$ , yielding a contradiction. Thus,  $w(\tau) = w_{\max}$  is true.
- 2) Suppose otherwise. Then, there exists a feasible  $\tau' \neq \tau$  such that  $\sum_{i=1}^M \tau'_i = \sum_{i=1}^M \tau_i = T_c^*$ , that achieves  $w(\tau') < w(\tau)$ . Thus,  $w(\tau') < w_{\max}$ , meaning  $T_c^*$  cannot be the minimum completion time due to Condition 1, yielding a contradiction.  $\square$

**Corollary 1.** For any  $T_c^* > t_R - T_{\text{post},M}$ , the optimal  $\tau$  that achieves  $T_c^* = \sum_{i=1}^M \tau_i$  for the post-delay only case satisfies  $\tau_i \geq \tau_{i+1}$  for all  $i$ .

*Proof.* Follows directly from Lemmas 3 and 4.  $\square$

Motivated by Lemma 4 and Corollary 1, we present Algorithm 3 that achieves the minimum transmission completion time. Note that according to the post-delay-induced departure time lower bounds, the approach taken by Algorithm 3 changes, hence the algorithm is presented in a case-by-case manner. Herein, to describe the operations of Algorithm 3, we address Case 1, where all post-delay induced lower limits on departure times reside within the interval  $[0, t_M)$ . We note that the rest of the cases (e.g., Case 2 and its subcases) follow a similar logic, with the exception of accounting for post-delays occurring after  $t_M$ .

For Case 1, Algorithm 3 exploits the fact that the completion time  $T_c$  cannot be made smaller than the arrival time of the last packet due to causality. Thus, if one were to allocate the first  $M - 1$  packets between the interval  $[0, t_M]$  via Algorithm 2 such that their incurred energy consumption is minimized, the largest possible energy would be left for the last packet's allocation. Given  $w(\tau)$  is decreasing in  $\tau$ , the largest energy budget would yield the shortest possible  $\tau_M$ , thereby minimizing  $T_c = \sum_{i=1}^M \tau_i$ .

Now suppose that using the construction in the above paragraph, the resultant  $\tau$  yields  $\tau_M > \tau_{M-1}$ . Then, using the argument in Corollary 1, such a  $\tau$  cannot be optimal. To handle this case, we first note that Algorithm 2 is employed for packets  $[1, \dots, M - 1]$  and outputs transmission durations that come in subgroups (say its last subgroup is  $\{\tau_{k_e+1}, \dots, \tau_{M-1}\}$ ). We know from the optimality of Algorithm 2, that the packets  $\{1, \dots, k_e\}$  are allocated such that their energy consumption is minimized within the interval  $[0, \sum_{i=1}^{k_e} \tau_i]$ . Thus, the remaining energy  $w_{\max} - \sum_{i=1}^{k_e} w(\tau_i)$  to be allocated for the durations  $\{\tau_{k_e+1}, \dots, \tau_M\}$  is as large as possible. Since the energy function  $w(\tau)$  is strictly convex and decreasing in  $\tau$ , in cases where  $\tau_M > \tau_{M-1}$  in the initial attempt, Algorithm 3 adds another iteration and equalizes the transmission durations of packets  $\{k_e + 1, \dots, M\}$ , so that the sum duration is minimized. Using this principle, Algorithm 3 runs in a backwards manner, subgroup by subgroup, until the requirement of non-increasing  $\tau_i$  required by Corollary 1 is met. Figure 5 presents an illustrative example for the argument made herein. Overall, the principle of Algorithm 3 relies on

- partitioning the set of packets into two subsets as  $\{1, \dots, k\}$  and  $\{k + 1, \dots, M\}$  for some  $k$ ,

**Algorithm 3** Offline scheduling algorithm for transmission completion time minimization under post-transmission delay constraints.

---

**Inputs:**  $M, d, w(\tau), t_R, \mathbf{T}_{\text{post}}$ , and for all packets  $T_{\text{pre},i} = t_R - t_i$

- 1:  $i^* = \arg \max t_R - T_{\text{post},i}$
- 2: **if**  $t_R - T_{\text{post},i^*} \leq t_M$  **then**
- 3:   *%% Case 1: All post-delay deadlines occur before the last packet's arrival.*
- 4:   Run Algorithm 2 for packets  $1, \dots, M - 1$  with inter-arrival times  $\{d_1, \dots, d_{M-1}\}$ . Obtain  $\{\tau_1^{(b)}, \dots, \tau_{M-1}^{(b)}\}$   
 $n_g$ : the number of subgroups.  
 $\mathbf{n}_{n_g \times 1}^{(m)}$ : vector that holds the number of packets in each subgroup.
- 5:    $k = \sum_{i=1}^{n_g} n_i^{(m)} = M - 1$
- 6:   **while** 1 **do**
- 7:     Set  $\tau_i = \tau_i^{(b)}$ , for  $i = 1, \dots, k$
- 8:     Compute remaining energy  $w_r = w_{\max} - \sum_{i=1}^k w(\tau_i^{(b)})$
- 9:     Assign equal duration for the remaining packets:  
 $\tau_{k+1} = \dots = \tau_M = w_r^{-1}(\frac{w_r}{M-k})$
- 10:     **if**  $\tau_i \geq \tau_{i+1}$  for all  $i$  **then**
- 11:       **break**
- 12:     **else**
- 13:        $n_g = n_g - 1$
- 14:        $k = \sum_{i=1}^{n_g} n_i^{(m)}(n_g)$
- 15:     **end if**
- 16:   **end while**
- 17: **else**
- 18:   *%% Case 2: There exists a post-delay deadline after the last packet's arrival.*
- 19:   **if**  $i^* \neq M$  **then**
- 20:     *%% Case 2a: Although occurring after  $t_M$ , the latest post delay is one of the earlier packets.*
- 21:     Run Algorithm 2 for packets  $1, \dots, i^*$ , with end time  $t_R - T_{\text{post},i^*}$ . Obtain  $\tau_1^{(b)}, \dots, \tau_{i^*}^{(b)}$
- 22:     Proceed as in Lines 6-16, with initializing  $k = i^*$  and  $n_g$  as the subgroup index of packet  $i^*$ .
- 23:   **else if**  $i^* = M$  **then**
- 24:     Run Algorithm 2 for packets  $1, \dots, M$ , with end time  $t_R - T_{\text{post},M}$ . Obtain  $\tau_1, \dots, \tau_M$
- 25:     **if**  $w(\tau) \leq w_{\max}$  **then**
- 26:       Minimum possible completion time  $t_R - T_{\text{post},M}$  is achievable. Algorithm done. *%% Case 2b-i*
- 27:     **else if**  $w(\tau) > w_{\max}$  **then**
- 28:       *%% Case 2b-ii*
- 29:       **if**  $\forall i \in \{1, \dots, M-1\}$ , we have  $t_R - T_{\text{post},i} < t_M$  **then**
- 30:         Proceed as in Case 1.
- 31:       **else if**  $\exists i \in \{1, \dots, M-1\}$ , such that  $t_R - T_{\text{post},i} \geq t_M$  **then**
- 32:         Proceed as in Case 2a, with  $i^*$  equal to the index of the second largest  $t_R - T_{\text{post},i}$ .
- 33:       **end if**
- 34:     **end if**
- 35:   **end if**
- 36: **end if**
- 37: **return**  $\tau$

---

- performing energy minimization on the left hand side, and
- using the maximized remaining energy to minimize completion time by equalizing durations on the right hand



side.

Here, as also discussed in the above paragraph, determining the index of separation ( $k$ ) is motivated by Corollary 1.

Prior to proving the optimality of Algorithm 3, we provide the following lemma that gives sufficient conditions for optimality. Note that similar to Lemma 4, we again consider the more general case of  $T_c^* > t_R - T_{\text{post},M}$ .

**Lemma 5** (Converse of Lemma 4). *If a vector  $\tau$  minimizes the energy cost within the time interval  $[0, \sum_{i=1}^M \tau_i]$  with the achieved minimum energy cost  $w(\tau) = w_{\text{max}}$ , then it is completion-time-optimal with  $\sum_{i=1}^M \tau_i = T_c^*$ .*

*Proof.* Suppose  $\sum_{i=1}^M \tau_i$  is energy-optimal in  $[0, \sum_{i=1}^M \tau_i]$  with  $w(\tau) = w_{\text{max}}$ , but the optimal duration vector is  $\tau' \neq \tau$ , that is  $\sum_{i=1}^M \tau'_i = T_c^* < \sum_{i=1}^M \tau_i$ . From Lemma 4, we necessarily have  $w(\tau') = w_{\text{max}}$ . Then, due to  $w(\tau)$  being decreasing in  $\tau$ , by increasing only  $\tau'_M$  so that  $\sum_{i=1}^M \tau'_i = \sum_{i=1}^M \tau_i$  is met, one can achieve  $w(\tau') < w_{\text{max}}$ . Hence,  $\tau'$  cannot be the energy-minimizing duration vector for the interval  $[0, T_c]$ , which yields a contradiction.  $\square$

**Theorem 2.** *The output of Algorithm 3 (say  $\tau$ ) yields the optimal transmission duration vector that minimizes  $T_c$ .*

*Proof.* The proof is presented in Appendix B.  $\square$

Note that unlike the energy-minimization problem, the values of the optimal duration vector  $\tau$  changes with the particular energy function  $w(\tau)$ . That said, as long as  $w(\tau)$  is strictly convex and decreasing, the optimal  $\tau$  is guaranteed to be found by Algorithm 3.

### B. Completion Time Minimization under Two-Sided Constraints

Herein, we extend the approach for the post-delay only case to the more generalized, two-sided case. The algorithm that yields the optimal  $\tau$  is presented in Algorithm 4. Note that when presenting Algorithm 4, we only provided the explicit algorithm for the case where all post-delay deadlines occur before the last packet's arrival (*i.e.*, corresponds to Case 1 of Algorithm 3 for the post-delay only scenario), for brevity. We emphasize that similar to Case 1, Cases 2a and 2b are both identical extensions of their post-delay only counterparts, with the only difference arising when handling pre-delay violations. For all cases, said pre-delay violations are again handled as described in Lines 23-35 of Algorithm 4.

Algorithm 4 operates in a similar fashion to Algorithm 3. However, unlike the post-delay only case, this need not translate to having non-increasing  $\tau_i$  for all  $i$ . This follows from the fact that in a two-sided system, the optimal  $\tau$  would not have non-increasing  $\tau_i$  for all  $i$ , in case there are pre-critical packets (see Lemma 1). This is a direct result of energy optimality being a necessity for completion time optimality (Lemma 4), and Lemma 1. Thus, instead of looking at the whole vector for non-increasing durations (as was done in Algorithm 3), Algorithm 4 seeks to ensure non-increasing durations between the last subgroup of the “left side” and the equalized durations on the “right side”, if the equal allocation

**Algorithm 4** Optimal offline scheduling for transmission completion time minimization under two-sided delay constraints.

---

**Inputs:**  $M, d, w(\tau), t_R, T_{\text{post}}, T_{\text{pre}}$

- 1: *%% Case 1: All post-delay deadlines occur before the last packet's arrival ( $t_R - T_{\text{post},i} \leq t_M$ ).*
- 2: Run Algorithm 2 for packets  $1, \dots, M - 1$  with inter-arrival times  $[d_1, \dots, d_{M-1}]$ . Obtain  $\tau_1^{(b)}, \dots, \tau_{M-1}^{(b)}$   
 $n_g$ : the number of subgroups.  
 $\mathbf{n}_{n_g \times 1}^{(m)}$ : vector that holds the number of packets in each subgroup.
- 3:  $k = \sum_{i=1}^{n_g} n_i^{(m)} = M - 1$
- 4: **while** 1 **do**
- 5:   Set  $\tau_i = \tau_i^{(b)}$ , for  $i = 1, \dots, k$
- 6:   Compute remaining energy  $w_r = w_{\text{max}} - \sum_{i=1}^k w(\tau_i^{(b)})$
- 7:   Assign equal duration for the remaining packets:  
 $\tau_{k+1} = \dots = \tau_M = w^{-1}(\frac{w_r}{M-k})$
- 8:   Check among  $[k+1, \dots, M]$  for pre-delay violations
- 9:   **if**  $\sum_{j=1}^i \tau_j \leq t_i + T_{\text{pre},i}$  for all  $i = k+1, \dots, M$  **then**
- 10:    *%% No pre-delay violations, check for non-increasing ordering in the last subgroup*
- 11:    **if**  $\tau_k \geq \tau_{k+1}$  **then**
- 12:      **break**
- 13:    **else**
- 14:       $n_g = n_g - 1$
- 15:       $k = \sum_{i=1}^{n_g} n_i^{(m)}(n_g)$
- 16:    **end if**
- 17:    **else**
- 18:      *%% There is a pre-delay violation. Let  $k_v$  denote the minimum index among violating packets*
- 19:      Allocate  $\tau_i = \frac{(t_{k_v} - T_{\text{pre},k_v}) - \sum_{i=1}^k \tau_i}{k_v - k}$  for  $i = k+1, \dots, k_v$
- 20:      **break** and go to Line 23
- 21:    **end if**
- 22:   **end while**

---

.....

- 23: *%% The Case with a Pre-Delay Violation*
- 24: **while** 1 **do**
- 25:    $k \leftarrow k_v$
- 26:    $w_r = w_{\text{max}} - \sum_{i=1}^k w(\tau_i)$
- 27:    $\tau_i = w^{-1}(\frac{w_r}{M-k})$ , for  $i = k+1, \dots, M$
- 28:   Check among  $[k+1, \dots, M]$  for pre-delay violations
- 29:   **if**  $\sum_{j=1}^i \tau_j \leq t_i + T_{\text{pre},i}$  for all  $i = k+1, \dots, M$  **then**
- 30:    **break**
- 31:   **else**
- 32:      *%% There is a pre-delay violation. Let  $k_v$  denote the minimum index among violating packets*
- 33:      Allocate  $\tau_i = \frac{(t_{k_v} - T_{\text{pre},k_v}) - \sum_{i=1}^k \tau_i}{k_v - k}$  for  $i = k+1, \dots, k_v$
- 34:    **end if**
- 35:   **end while**

---

**return**  $\tau$

---

on the right side complies with all pre-delay constraints of their respective packets.

In the existence of a pre-delay violation on the right side, Algorithm 4 records the first (smallest index) of such violations (say  $k_v$ ), and allocates equal durations for  $\{k+1, \dots, k_v\}$  between  $[\sum_{i=1}^k \tau_i, t_{k_v} + T_{\text{pre},k_v}]$ , where  $k$  is the last packet of the previous subgroup. Note that for packets  $\{1, \dots, k_v\}$ , the time interval  $[0, \sum_{i=1}^{k_v} \tau_i]$  cannot be made larger than




Fig. 5. Demonstrative toy example for Algorithm 3 under different  $w_{\max}$  for  $\mathbf{T}_{\text{post}} = [\infty, 11, \infty, \infty]$  and  $t_R = 26$ . The energy cost function  $w(\tau) = \frac{1}{\tau}$ . Blue/red marks on departure times represent pre-/post-criticality of the marked packet, respectively.




Fig. 6. Demonstrative toy example for Algorithm 4 under different  $w_{\max}$  for  $\mathbf{T}_{\text{post}} = [\infty, 11, \infty, \infty]$ ,  $\mathbf{T}_{\text{pre}} = [\infty, \infty, 4.5, \infty]$ , and  $t_R = 26$ . The energy cost function  $w(\tau) = \frac{1}{\tau}$ . Blue/red marks on departure times represent pre-/post-criticality of the marked packet, respectively.

$t_{k_v} + T_{\text{pre}, k_v}$ , and this equal allocation, alongside the “left side” (i.e., packets  $\{1, \dots, k\}$ ), ensure energy optimality (follows identical from Appendix A). For the remaining packets  $\{k_v + 1, \dots, M\}$ , we equalize their durations with the remaining energy budget and check their pre-delay violations once again. We repeat this process until there are no pre-delay violations in the last batch, which finishes the algorithm’s operation and terminates it. Figure 6 presents a toy example to illustrate the effects of a pre-critical packet. Note that Figure 6 considers the identical problem as Figure 5, with the added pre-delay of  $T_{\text{pre}, 3} = 4.5$  for demonstrative purposes.

**Theorem 3.** *The output of Algorithm 4 (say  $\tau$ ) yields the optimal transmission duration vector that minimizes  $T_c$  under two-sided delay constraints.*

*Sketch of Proof.* The proof strategy is identical to the proof for the post-delay only case in Appendix B.

- For all cases except Case 2b-i, the proof follows from Lemma 5. In particular, by design, Algorithm 4 uses all available energy (i.e.,  $w_{\max}$ ). Showing the second requirement of the lemma, that is, the energy optimality of the resultant  $\tau$  within the interval  $[0, \sum_{i=1}^M \tau_i]$ , directly follows from the energy optimality proof in Appendix

A. Thus, the sufficient conditions in Lemma 5 are met, implying  $\tau$  minimizes the completion time.

- Similar to the post-delay only case, Case 2b-i corresponds to the case where i)  $t_R - T_{\text{post}, M} > t_R - T_{\text{post}, i}$  for all  $i \neq M$ , ii)  $t_R - T_{\text{post}, M} > t_M$ , and iii) running Algorithm 2 between  $[0, t_R - T_{\text{post}, M}]$  consumes  $w(\tau) \leq w_{\max}$  can achieve  $\sum_{i=1}^M \tau_i = t_R - T_{\text{post}, M}$ . Thus, the available energy can satisfy  $T_c = t_R - T_{\text{post}, M}$ , which is the smallest possible completion time under FIFO.  $\square$

## VI. CONCLUSIONS

In this paper, the theoretical framework of packet scheduling under two-sided delay constraints has been addressed, wherein transmitting a packet too late (too stale) and too early (too fresh) are both undesired. To this end, firstly the energy-efficient packet scheduling problem under two-sided individual delay constraints has been introduced, which generalizes the conventional one-sided delay constrained scheduling. For the newly posed two-sided problem, an algorithm that yields the provably optimal transmission duration vector has been provided. Furthermore, the “dual” problem has been formulated, which seeks to minimize transmission completion time subject to an energy budget, again under individual two-sided delay constraints. The algorithm that provably minimizes the transmission duration has been developed and presented.

The developed algorithms assume perfect and non-causal knowledge of arrival times and delay constraints, and are offline algorithms. Depending on the application, the necessary information of delay constraints or arrival times might be available or be accurately estimated. However, for some applications, these critical information or perfect control of transmission rates/durations may not be feasible. The primary future work of our study is devising more robust algorithms against aforementioned imperfections, while extending and adapting the developed framework to our motivating applications. Other future works include considering non-FIFO ordering and non-convex cost functions, and expanding the two-sided delay constrained framework to multi-hop systems.

APPENDIX A  
PROOF OF THEOREM 1

The proof is similar in spirit as the pre-delay-only ([6]) case, in that the proof for the two-sided case also follows from the concept of majorization. Compared to the post-delay-only case, as the subsequent subgroups need not be of non-increasing order, they need to be taken into account for the two-sided case (similar to the pre-delay-only case). Furthermore, compared to the pre-delay-only case, herein, the deadline constraints introduced by both pre- and post-delays need to be considered, which will be reflected in Claims 1-3.

**Definition 10 (Majorization).** An  $M$ -element, non-increasing sequence  $\mathbf{x}_1$  is said to be majorized by another  $M$ -element, non-increasing sequence  $\mathbf{x}_2$  if

- $\sum_{i=1}^M x_{1,i} = \sum_{i=1}^M x_{2,i}$ , and
- $\sum_{i=1}^m x_{1,i} \leq \sum_{i=1}^m x_{2,i}$ , for all  $m = 1, \dots, M-1$ .

Note that  $\mathbf{x}_1$  being majorized by  $\mathbf{x}_2$  implies that summing up to the same value,  $\mathbf{x}_1$  is more “balanced” than  $\mathbf{x}_2$  [27].

Recalling from Section II, the cost  $w(\boldsymbol{\tau}) = \sum_{i=1}^M w(\tau_i)$  does not depend on the order of the  $M$ -element sequence  $\boldsymbol{\tau}$  and is strictly convex in each  $\tau_i$ , which makes it Schur-convex (order-preserving). Therefore, if a transmission vector  $\boldsymbol{\tau}_1$  is majorized by another transmission vector  $\boldsymbol{\tau}_2$ , it is guaranteed to have  $\sum_{i=1}^M w(\tau_{1i}) \leq \sum_{i=1}^M w(\tau_{2i})$ . Motivated by this, we will show herein that the output of Algorithm 2 (say  $\boldsymbol{\tau}$  throughout the proof) gets majorized by any other feasible sequence  $\boldsymbol{\tau}'$ , which guarantees that  $\boldsymbol{\tau}$  incurs the lowest cost among all feasible transmission durations. In particular, we will show the statement by showing the contrapositive “if some  $\boldsymbol{\tau}'$  does not majorize  $\boldsymbol{\tau}$ , then it is not feasible”.

We first start by ordering  $\boldsymbol{\tau}'$  and  $\boldsymbol{\tau}$  in a non-increasing manner, and define  $\boldsymbol{\tau}'^\downarrow$  and  $\boldsymbol{\tau}^\downarrow$  as the non-increasingly ordered versions of  $\boldsymbol{\tau}'$  and  $\boldsymbol{\tau}$ , respectively. Let  $j$  be the smallest index such that  $\sum_{i=1}^m \tau'_i > \sum_{i=1}^m \tau_i^\downarrow$ . Then, we know  $\tau'_j > \tau_j^\downarrow$ . Let  $j_c$  be the largest index such that  $\tau_j = \tau_{j_c}$ . Essentially,  $\tau_{j_c}$  “completes” the last incomplete group/subgroup in the batch, yielding an *integer multiple of completed subgroups*. Since  $\boldsymbol{\tau}'^\downarrow$  is ordered in a non-increasing manner, we have

$$\tau'_{j_c} \leq \dots \leq \tau'_j < \tau_j^\downarrow = \dots = \tau_{j_c}^\downarrow,$$

which implies

$$\sum_{i=1}^{j_c} \tau'_i > \sum_{i=1}^{j_c} \tau_i^\downarrow.$$

Let the collection of packets  $\{1, \dots, j_c\}$  of the ordered  $\boldsymbol{\tau}^\downarrow$  correspond to packets  $\{k_1, \dots, k_{j_c}\}$  of the un-ordered, original  $\boldsymbol{\tau}$ . Now let us consider the whole set of packets  $\{1, \dots, k_{j_c}\}$  of the original  $\boldsymbol{\tau}$ . We have two cases:

**Case 1:** The first case is where no pre-critical subgroups are among the subgroups in  $\{1, \dots, k_{j_c}\}$  of  $\boldsymbol{\tau}$ . For this case, as a corollary of Lemma 1, the set  $\{1, \dots, j_c\}$  of the ordered  $\boldsymbol{\tau}^\downarrow$  corresponds to the set  $\{1, \dots, j_c\}$  of the un-ordered,

original  $\boldsymbol{\tau}$ , with  $k_{j_c} = j_c$ .<sup>9</sup> Since there are no pre-critical subgroups in the batch, the last subgroup is either a regular or a post-critical one.

*Case 1a:* If index  $j_c$  corresponds to the last packet of a regular subgroup, then by definition we have  $\sum_{i=1}^{j_c} \tau_i = \sum_{i=1}^{j_c} d_i$ , which yields  $\sum_{i=1}^{j_c} \tau'_i < \sum_{i=1}^{j_c} d_i$ . This is in violation of the non-idling constraints in (1b)-(1c), and implies  $\boldsymbol{\tau}'$  is infeasible.

*Case 1b:* If index  $j_c$  corresponds to the last packet of a post-critical subgroup, then by definition we have  $\sum_{i=1}^{j_c} \tau_i = t_R - T_{\text{post},j_c}$ , which yields  $\sum_{i=1}^{j_c} \tau'_i < t_R - T_{\text{post},j_c}$ . This is in violation of the post-transmission delay constraint in (1e), and implies  $\boldsymbol{\tau}'$  is infeasible.

**Case 2:** The second case is where there are pre-critical subgroups among the subgroups in  $\{1, \dots, k_{j_c}\}$  of  $\boldsymbol{\tau}$ . We first make the following claim, with accompanying proof in Footnote 10.

*Claim 1:* The last the last subgroup in  $\{1, \dots, k_{j_c}\}$  of  $\boldsymbol{\tau}$  cannot be a pre-critical subgroup.<sup>10</sup>

We partition  $\{1, \dots, k_{j_c}\}$  of  $\boldsymbol{\tau}$  into two subsets, noting

$$\sum_{i=1}^{k_{j_c}} \tau_i = \sum_{i \in \{k_1, \dots, k_{j_c}\}} \tau_i + \sum_{i \notin \{k_1, \dots, k_{j_c}\}} \tau_i \quad (6)$$

We first note that by definition of the set  $\{k_1, \dots, k_{j_c}\}$  of  $\boldsymbol{\tau}$ , every element in the first subset is strictly greater than every element in the second subset. For the first subset, we have

$$\sum_{i \in \{1, \dots, k_{j_c}\}} \tau_i = \sum_{i=1}^{j_c} \tau_i^\downarrow > \sum_{i=1}^{j_c} \tau'_i \geq \sum_{i=1}^{j_c} \tau'_i. \quad (7)$$

For the second subset, we first observe that it consists of collections that contain one or more, integer multiple of consecutive subgroups. Furthermore, we make the following claims, with proofs in Footnotes 11-12:

*Claim 2:* Each collection ends with a pre-critical subgroup.<sup>11</sup>

*Claim 3:* A subgroup that is the immediate prior to a collection cannot be a pre-critical subgroup.<sup>12</sup>

Combining Claims 2-3, each collection within the second subset starts at either the arrival of the first packet in the collection (if prior subgroup is regular), or the post-transmission

<sup>9</sup>Note that if a subgroup exists in  $\{1, \dots, k_{j_c}\}$  that is not in  $\{1, \dots, j_c\}$  of the ordered  $\boldsymbol{\tau}^\downarrow$ , then the duration of the subsequent subgroup (the first one that is in  $\{1, \dots, j_c\}$  of  $\boldsymbol{\tau}^\downarrow$ ) would need to have a larger transmission duration than the one that is not in  $\{1, \dots, j_c\}$  of  $\boldsymbol{\tau}^\downarrow$ . This would require an *increase* in transmission duration from one subgroup to the subsequent, which can only be achievable by a pre-critical subgroup, yielding a contradiction.

<sup>10</sup>Suppose the last subgroup was pre-critical. Then the subsequent subgroup would have had to have a larger transmission duration than it, following Item 3 of Lemma 1. Hence, the subsequent subgroup would also have been included in  $\{1, \dots, j_c\}$  of the ordered  $\boldsymbol{\tau}^\downarrow$ , hence the initial subgroup would not have been the last one, yielding a contradiction.

<sup>11</sup>Assume otherwise. Then, by Items 1 and 2 of Lemma 1, the subsequent subgroup of a post-critical or regular subgroup would have a smaller transmission duration, hence would also be included in the second subset, yielding a contradiction.

<sup>12</sup>Assume the prior subgroup is pre-critical. Then, by Item 3 of Lemma 1, the prior subgroup would have a smaller transmission duration, hence would also be included in the second subset hence the collection, yielding a contradiction.

constraint of the last packet of the prior subgroup (if prior subgroup is post-critical). Furthermore, each collection ends with a pre-critical subgroup. Thus, the sums of the transmission durations in each collection are at their maximum possible and cannot be increased further. Otherwise, either a pre-/post-transmission constraint would be violated, or a packet's transmission would start before its arrival, which is clearly a violation. Therefore, we know that for any  $\tau'$ , we have to have

$$\sum_{i \notin \{1, \dots, k_{j_c}\}} \tau_i \geq \sum_{i \notin \{1, \dots, k_{j_c}\}} \tau'_i. \quad (8)$$

Combining equations (6)-(8), we have  $\sum_{i=1}^{k_{j_c}} \tau_i > \sum_{i=1}^{k_{j_c}} \tau'_i$ . From Claim 1, the last subgroup in  $\{1, \dots, k_{j_c}\}$  of  $\tau$  is either regular or post-critical. With a similar argument to Case 1, if the last subgroup is regular, then  $\sum_{i=1}^{k_{j_c}} \tau'_i$  violates the non-idling constraint; and if the last subgroup is post-critical, then  $\sum_{i=1}^{k_{j_c}} \tau'_i$  violates the post-transmission constraint of the  $k_{j_c}$ th packet, which makes  $\tau'$  infeasible in both scenarios.

Overall, whenever  $\tau'$  does not majorize  $\tau$ , all possible scenarios yield  $\tau'$  infeasible. Thus,  $\tau$  gets majorized by all other feasible sequences, which concludes the proof.

#### APPENDIX B PROOF OF THEOREM 2

We will proceed in a case-by-case manner.

**Case 2b-i:** This is the case where the post-delay-induced departure lower bound of the  $M$ th packet occurs last,  $t_M < t_R - T_{\text{post},M}$ , and the available  $w_{\text{max}}$  can achieve  $\sum_{i=1}^M \tau_i = t_R - T_{\text{post},M}$ . Since  $T_c \geq t_R - T_{\text{post},M}$  for a FIFO system, critically achieving it achieves the smallest possible completion time, which makes  $\tau$  optimal.

**Cases 1, 2a, and 2b-ii:** These are the cases where  $\sum_{i=1}^M \tau_i > t_R - T_{\text{post},M}$ . Leveraging Lemma 5, it suffices to show that i)  $w(\tau) = w_{\text{max}}$ , and ii)  $\tau$  minimizes the energy cost within  $[0, \sum_{i=1}^M \tau_i]$ .

- 1) Showing  $w(\tau) = w_{\text{max}}$  is trivial for all Cases 1, 2a, and 2b-ii, as the algorithm is guaranteed to allocate all available  $w_{\text{max}}$  in all cases.
- 2) **Energy Optimality of Case 1:** As we are proving energy optimality, the proof will again follow by the majorization argument, similar to the proof of Algorithm 2.

Let  $\tau' \neq \tau$  with  $\sum_{i=1}^M \tau'_i = \sum_{i=1}^M \tau_i$ . Note that by design of Algorithm 3 and Corollary 1, both  $\tau'$  and  $\tau$  are of non-increasing order. We will show that if  $\tau'$  does not majorize  $\tau$ , then it has to be infeasible or cause a contradiction.

Suppose  $\tau'$  does not majorize  $\tau$ , and let  $j$  be the smallest index such that  $\sum_{i=1}^j \tau_i > \sum_{i=1}^j \tau'_i$ . Similar to Appendix A, we know  $\tau_j > \tau'_j$ . Again, denote  $j_c$  as the largest index such that  $\tau_j = \tau_{j_c}$ , thereby yielding  $\tau'_{j_c} \leq \dots \leq \tau'_j < \tau_j = \dots = \tau_{j_c}$ , and hence

$$\sum_{i=1}^{j_c} \tau_i > \sum_{i=1}^{j_c} \tau'_i. \quad (9)$$

We have two cases:

- **The case with  $j_c < M$ :** Say Algorithm 3 stops at packet index  $k$ . By design, the algorithm partitions the set of packets, as well as the time axis  $[0, \sum_{i=1}^M \tau_i]$  into two parts (we will call them left and right sides): packets  $\{1, \dots, k\}$  and  $\{k+1, \dots, M\}$ , with corresponding intervals  $[0, \sum_{i=1}^k \tau_i]$  and  $[\sum_{i=1}^k \tau_i, \sum_{i=1}^M \tau_i]$ , respectively. The case with  $j_c < M$  implies that  $j_c$  is on the left side. Then, by the design of Algorithm 3, we have either  $\sum_{i=1}^{j_c} \tau_i < \sum_{i=1}^{j_c} d_i$  or  $\sum_{i=1}^{j_c} \tau_i < t_R - T_{\text{post},j_c}$ . Under both these cases, having (9) implies  $\tau'$  violates either a non-idling or post-delay constraint at packet  $j_c$ , which makes it infeasible.
- **The case with  $j_c = M$ :** For this case, we then have  $\sum_{i=1}^M \tau'_i < \sum_{i=1}^M \tau_i$ , which violates the proof's initial supposition of having  $\sum_{i=1}^M \tau'_i = \sum_{i=1}^M \tau_i$ , yielding a contradiction.

Overall, for any  $j_c$ , we have showed that whenever  $\tau'$  does not majorize  $\tau$ , it is either infeasible or causes a contradiction.

Since we showed both  $w(\tau) = w_{\text{max}}$  and the energy optimality of  $\tau$  between  $[0, \sum_{i=1}^M \tau_i]$ , from Lemma 5,  $\tau$  is the completion time minimizing vector with the optimal completion time  $T_c^* = \sum_{i=1}^M \tau_i$ . The proofs for Cases 2a and 2b-ii follow identically.

#### REFERENCES

- [1] M. C. Gursoy and U. Mitra, "Energy-efficient packet scheduling under two-sided delay constraints," in *submitted to IEEE Int. Conf. Commun. (ICC)*, 2023.
- [2] B. S. Tsybakov, "File transmission over wireless fast fading downlink," *IEEE Trans. Inf. Theory*, vol. 48, no. 8, pp. 2323–2337, Aug. 2002.
- [3] R. A. Berry and R. G. Gallager, "Communication over fading channels with delay constraints," *IEEE Trans. Inf. Theory*, vol. 48, no. 5, pp. 1135–1149, May 2002.
- [4] A. Fu, E. Modiano, and J. N. Tsitsiklis, "Optimal transmission scheduling over a fading channel with energy and deadline constraints," *IEEE Trans. Wireless Commun.*, vol. 5, no. 3, pp. 630–641, Mar. 2006.
- [5] E. Uysal-Biyikoglu, B. Prabhakar, and A. El Gamal, "Energy-efficient packet transmission over a wireless link," *IEEE/ACM Trans. Netw.*, vol. 10, no. 4, pp. 487–499, Aug. 2002.
- [6] W. Chen, M. J. Neely, and U. Mitra, "Energy-efficient transmissions with individual packet delay constraints," *IEEE Trans. Inf. Theory*, vol. 54, no. 5, pp. 2090–2109, May 2008.
- [7] F. Shan, J. Luo, and X. Shen, "Optimal energy efficient packet scheduling with arbitrary individual deadline guarantee," *Comput. Netw.*, vol. 75, pp. 351–366, Dec. 2014.
- [8] M. A. Zafer and E. Modiano, "A calculus approach to energy-efficient data transmission with quality-of-service constraints," *IEEE/ACM Trans. Netw.*, vol. 17, no. 3, pp. 898–911, Jun. 2009.
- [9] W. Chen, U. Mitra, and M. J. Neely, "Energy-efficient scheduling with individual packet delay constraints over a fading channel," *Wireless Netw.*, vol. 15, no. 5, pp. 601–618, Jul. 2009.
- [10] Z. Nan, T. Chen, X. Wang, and W. Ni, "Energy-efficient transmission schedule for delay-limited bursty data arrivals under nonideal circuit power consumption," *IEEE Trans. Veh. Technol.*, vol. 65, no. 8, pp. 6588–6600, Aug. 2016.
- [11] S. Xu, T.-H. Chang, S.-C. Lin, C. Shen, and G. Zhu, "Energy-efficient packet scheduling with finite blocklength codes: Convexity analysis and efficient algorithms," *IEEE Trans. Wireless Commun.*, vol. 15, no. 8, pp. 5527–5540, Aug. 2016.
- [12] W. Chen, M. J. Neely, and U. Mitra, "Delay-constrained energy-efficient scheduling over a multihop link," in *Proc. IEEE Int. Symp. Inf. Theory (ISIT)*, Jun. 2007, pp. 1406–1410.
- [13] F. Fu and M. Van Der Schaar, "A systematic framework for dynamically optimizing multi-user wireless video transmission," *IEEE J. Sel. Areas Commun.*, vol. 28, no. 3, pp. 308–320, Apr. 2010.

- [14] S. Kaul, R. Yates, and M. Gruteser, “Real-time status: How often should one update?” in *Proc. IEEE INFOCOM*. IEEE, Mar. 2012, pp. 2731–2735.
- [15] V. Elgart, T. Jia, and R. V. Kulkarni, “Applications of Little’s law to stochastic models of gene expression,” *Phys. Rev. E*, vol. 82, no. 2, p. 021901, Aug. 2010.
- [16] S. Tsitkov, T. Pesenti, H. Palacci, J. Blanchet, and H. Hess, “Queueing theory-based perspective of the kinetics of “channeled” enzyme cascade reactions,” *ACS Catalysis*, vol. 8, no. 11, pp. 10 721–10 731, Oct. 2018.
- [17] J. Peccoud and B. Ycart, “Markovian modeling of gene-product synthesis,” *Theo. Pop. Biol.*, vol. 48, no. 2, pp. 222–234, 1995.
- [18] S. Gupta, T. D. Ross, M. M. Gomez, J. L. Grant, P. A. Romero, and O. S. Venturelli, “Investigating the dynamics of microbial consortia in spatially structured environments,” *Nat. Commun.*, vol. 11, no. 1, pp. 1–15, May 2020.
- [19] A. C. Heren, H. B. Yilmaz, C.-B. Chae, and T. Tugcu, “Effect of degradation in molecular communication: Impairment or enhancement?” *IEEE Trans. Mol. Biol. Multi-Scale Commun.*, vol. 1, no. 2, pp. 217–229, Nov. 2015.
- [20] A. Noel, K. C. Cheung, and R. Schober, “Improving receiver performance of diffusive molecular communication with enzymes,” *IEEE Trans. Nanobiosci.*, vol. 13, no. 1, pp. 31–43, Mar. 2014.
- [21] J. Yang and S. Ulukus, “Delay-minimal transmission for energy constrained wireless communications,” in *Proc. IEEE Int. Conf. Commun. (ICC)*, May 2008, pp. 3531–3535.
- [22] —, “Optimal packet scheduling in an energy harvesting communication system,” *IEEE Trans. Commun.*, vol. 60, no. 1, pp. 220–230, Jan. 2011.
- [23] X. Kang, C. K. Ho, and S. Sun, “Full-duplex wireless-powered communication network with energy causality,” *IEEE Trans. Wireless Commun.*, vol. 14, no. 10, pp. 5539–5551, Oct. 2015.
- [24] M. S. Iqbal, Y. Sadi, and S. Coleri, “Minimum length scheduling for full duplex time-critical wireless powered communication networks,” *IEEE Trans. Wireless Commun.*, vol. 19, no. 9, pp. 5993–6006, Sep. 2020.
- [25] X. Li, A. Ortiz, H. Al-Shatri, A. Klein, and T. Weber, “Delay-constrained data transmission for energy harvesting transmitter,” in *Proc. Int. ITG Conf. Sys. Commun. Coding (SCC)*, Jun. 2017, pp. 1–6.
- [26] W. Chen, “Energy-efficient packet transmissions with delay constraints for wireless communications,” Ph.D. dissertation, University of Southern California, 2007.
- [27] A. W. Marshall and I. Olkin, “Inequalities via majorization—an introduction,” in *General Inequalities 3*. Springer, 1983, pp. 165–187.