

Succinct Planar Encoding with Minor Operations

Frank Kammer ✉ 

THM, University of Applied Sciences Mittelhessen, Giessen, Germany

Johannes Meintrup ✉ 

THM, University of Applied Sciences Mittelhessen, Giessen, Germany

Abstract

Let G be an unlabeled planar and simple n -vertex graph. We present a succinct encoding of G that provides induced-minor operations, i.e., edge contraction and vertex deletions. Any sequence of such operations is processed in $O(n)$ time. In addition, the encoding provides constant time per element neighborhood access and degree queries. Using optional hash tables the encoding additionally provides constant expected time adjacency queries as well as an edge-deletion operation (thus, all minor operations are supported) such that any number of such edge deletions are computed in $O(n)$ expected time.

Constructing the encoding requires $O(n)$ bits and $O(n)$ time. The encoding requires $\mathcal{H}(n) + o(n)$ bits of space with $\mathcal{H}(n)$ being the entropy of encoding a planar graph with n vertices. Our data structure is based on the recent result of Holm et al. [ESA 2017] who presented a linear time contraction data structure that allows to maintain parallel edges and works for labeled graphs, but uses $O(n \log n)$ bits of space. We combine the techniques used by Holm et al. with novel ideas and the succinct encoding of Blelloch and Farzan [CPM 2010] for arbitrary separable graphs. Our result partially answers the question raised by Blelloch and Farzan if their encoding can be modified to allow modifications of the graph.

2012 ACM Subject Classification Theory of computation → Graph algorithms analysis

Keywords and phrases planar graph, r -partition, separator, succinct encoding, graph minors

Funding *Johannes Meintrup*: Funded by the Deutsche Forschungsgemeinschaft (DFG, German Research Foundation) – 379157101.

1 Introduction

Graphs are used to model systems as entities and relationships between these entities. Many graphs that arise in real-world application are very large. This has given rise to an area of research with the aim of reducing the required space [1, 7, 8, 10, 15]. Practical examples include large road-networks [23] or social-network graphs [9]. This has spawned research inquiries into compact representation of graphs, especially those that possess certain structural properties. The arguably most well-known such structural property is planarity. A graph is planar if it can be drawn in the plane without crossings. In this work we consider the problem of maintaining a succinct encoding of a given graph under edge contractions and vertex deletions, referred to as *induced-minor operations*. An edge contraction in a graph $G = (V, E)$ consists of removing an edge $\{u, v\} \in E$ from the graph and merging its endpoints to a new vertex x and adding all neighbors of u and v to the neighborhood of x . Edge contractions are a vital technique in a multitude of algorithms, prominent examples include computing minimum cuts [16], practical treewidth computations [24] and maximum matchings [6]. At the end of the paper we extend our result from induced-minor operations to support all *minor operations*, which in addition to edge contractions and vertex deletions includes edge deletions. There is a famous series of over 20 publications focused on graph minors by Robertson and Seymour. For the latest paper released as part of this series see [22].

Related Work. For encoding planar graphs without regards to providing fast access operations, Keeler et al. [17] showed an $O(n)$ bits representation. For a compression within the information theoretic lower bound refer to He et al. [11]. Due to Munro and Raman [20] there exists an encoding using $O(n)$ bits that allows constant-time queries which has subsequently been improved by Chiang et al. [5]. We build on the succinct representation due to Blelloch and Farzan, which allows encoding arbitrary separable graphs and subsequently allows constant-time queries [3], which builds on the work of Blanford et al. [2]. Recently it was shown that the encoding of Blelloch and Farzan can be constructed using $O(n)$ bits in $O(n)$ time [14]. Our work can be thought of as extending the encoding of Blelloch and Farzan to allow contraction operations.

For edge contractions in planar graphs without regard to space-usage, Klein and Mozes [18] presented an algorithm that runs in $O(\log n)$ time per contraction. Their work is based on techniques by Brodal and Fagerberg [4], who showed that a bound out-degree orientation of a planar graph can be maintained under edge insertions and deletions in $O(\log n)$ time per update. For edge and vertex deletions Holm and Rotenberg showed a data structure that provides any number of such deletions in $O(n)$ time [13]. The state-of-the-art by Holm et al. [12] provides edge contractions in $O(n)$ time total. Their data structure allows constant time (per element) neighborhood and degree queries and (optionally) maintains parallel edges that occur due to merges, while also allowing to view the graph as "simple", i.e., skipping parallel edges when querying the neighborhoods. Using optional hashing techniques they provide expected constant time adjacency queries. Their data structure is based on the well-known notion of r -partitions [19], a technique we use as well. The data structure of Holm et al. uses $\Theta(n \log n)$ bits to store various mapping data structures between vertex labels and initially applies graph transformations. For this and other reasons, their data structure is not succinct. Even assuming these steps could trivially be adapted to use $o(n)$ bits when encoding unlabeled graphs, they additionally construct a lookup table for storing small graphs such that each index encoding a graph with k vertices uses $\mathcal{H}(k) + \Theta(\mathcal{H}(k))$ bits of space, with $\mathcal{H}(k)$ the entropy of encoding planar graphs with k vertices. They then encode graphs of at least n total vertices using such indices, i.e., they use $\mathcal{H}(n) + \Theta(\mathcal{H}(n))$ bits for storing all such small graph, i.e., their data structure is not succinct.

Our result. Let G be an unlabeled planar and simple graph with n vertices. We present a succinct encoding of G that is able to process edge contractions and vertex deletions in $O(n)$ time for any number of such modifications. The data structure allows constant time (per element) neighborhoods and degree queries. Using optional hashing techniques, we provide constant expected time adjacency queries and can process any number of edge deletions in $O(n)$ expected time. This partially answers a question posed by Blelloch and Farzan if their encoding for arbitrary separable graphs can be extended to allow graph modifications [3]. Our data structure maintains the running time of the state-of-the-art solution by Holm et al. [12] for labeled planar graphs, while using significantly less space. The data structure of Holm requires the input graph to be transformed such that each vertex has constant degree, which increases the number of vertices by a linear factor. Such a transformation is not necessary using our techniques. The caveat of our data structure is that it only works for unlabeled graphs and we are not able to maintain parallel edges that occur due to contractions, i.e., our graph is at all times simple. In the next section we present our main result in an intuitive fashion. Our new result is based on several previous data structures (Section 3) and on a table-lookup technique (Section 4). In Section 5, we describe and slightly extend the succinct encoding technique due to Blelloch and Farzan [3]. To obtain our new result, one of our challenges was to extend Blelloch and Farzan's mappings by constant-time update

operations while maintaining the space bound. Interestingly, we use here also Holm et al.'s datastructure [12] as a subroutine. The dynamic mappings are described in Section 6, which are needed in Section 7 to combine the results of all the previous sections to achieve our dynamic encoding. We end this publication by extending our encoding to provide vertex and edge deletions as well as adjacency queries.

2 A succinct graph encoding for edge contractions

We now give an overview of our new data structure for succinctly encoding a simple unlabeled planar graph $G = (V, E)$ with n vertices and maintaining this encoding under edge contractions while allowing neighborhood and degree queries in constant time per element output. Vertex deletions and edge deletions are discussed in Section 7. The intuitive idea is to construct a set $X \subset V$ of *boundary vertices* such that $G[V \setminus X]$ (the vertex-induced graph on $V \setminus X$) contains multiple connected components C_1, \dots, C_k of "small" size at most r (r is defined later) with $k = O(n/r)$, and X of size $O(n/\sqrt{r})$. Based on this, we distinguish edges of three types: edges between vertices of X (called *boundary edges*) edges between vertices of one C_i (called *simple edges*) and edges between a vertex of X and a vertex of some C_i (called *mixed edges*). For each C_i denote with P_i the graph induced by all simple edges between vertices of C_i and all mixed edges with one endpoint in C_i . The set of all these P_i is known as an r -*partition*, and each P_i is called a *piece*.

Note that a boundary vertex is contained in multiple P_i . A key characteristic of this r -partition is that each P_i contains only $O(\sqrt{r})$ boundary vertices, and therefore is of size $O(|C_i| + \sqrt{r}) = O(r)$. Precise definitions of these terms follow in Section 3, for now this intuition suffices. Assume that there is a data structure that is able to easily contract any number of edges in graphs of size $O(r)$ in time $O(r)$. As long as contractions are only carried out between simple edges, we would be able to easily construct a data structure that results in $O(n)$ runtime for any number of contractions by simply constructing this data structure for each piece individually. Problems occur when contracting boundary or mixed edges because contractions are no longer able to be carried out locally in a single piece as they affect vertices in multiple pieces. For example, when contracting a boundary edge $\{u, v\}$ this affects every P_i with $i \in \{1, \dots, k\}$ that contains both u and v . To provide such contractions we construct a data structure sketched in the following. Note that we distinguish between vertex merges of two vertices u, v and edge contractions between an edge $\{u, v\}$, with the latter being equal to the first with the distinction that u must be adjacent to v .

For edges between vertices of the boundary X we construct a *boundary graph* $F = G[X]$, which at all times contains all boundary edges, including edges that occur due to contractions. A key invariant that we uphold is that the "status" of a vertex, i.e., if it is a boundary or a non-boundary vertex, never changes due to contractions. For each $u \in X$ we maintain a mapping containing all i with $u \in V(P_i)$, i.e., the pieces that contains u . Now, when we contract a boundary edge $\{u, v\}$ we firstly merge v to u in all P_i that contain both u and v . We do this by setting $N(u) := N(u) \cup N(v) \setminus \{u, v\}$ in P_i and removing v from P_i , where $N(\cdot)$ denotes the neighborhood of a vertex. In all P_i that contain only v , we simply relabel v to be u . In all P_i that do not contain v (but can contain u) we do not have to make modifications. Finally, $\{u, v\}$ is contracted in the boundary graph F as well. To maintain F we can use a "slow" data structure, as there are only a few vertices in F and our total runtime maintains $O(n)$.

To contract a mixed edge $\{u, v\}$ with $u \in X$ we know there is only one P_i that contains v , where we execute the contraction. This might result in u now being adjacent to some

$x \in X \cap V(P_i)$, for which we add the respective edge $\{u, x\}$ to F . It helps to achieve our runtime goal of $O(n)$ for processing any number of edge contractions if we do not add this edge $\{u, x\}$ to all other pieces that contain both u and x . We therefore maintain a second invariant: that edges between boundary vertices are only contained in the boundary graph (for now ignoring the specifics of how this is maintained).

So far we assumed there was a data structure that handles contractions within the pieces. Intuitively, we build the same data structure we outlined here to handle the contractions in each piece one more time, splitting each piece in tiny pieces of size at most r' , specified later. We are able to categorize all graphs of size at most r' by a small lookup table, which allows us to encode every such tiny piece as an index into the lookup table (Section 4). For each graph of the lookup table we pre-compute all possible planarity preserving vertex merges. Afterwards, we can contract edges in constant time by simply retrieving (the index of) the contracted graph from the lookup table. Such a framework was previously used by Holm et al. [12] to maintain a planar graph under contractions, but with a space usage of $\Theta(n \log n)$ bits and a total runtime of $O(n)$ for any number of contractions.

To output the neighborhood of a vertex we distinguish between two cases. First, to output the neighborhood of a vertex u that is not a boundary vertex, we can simply output the neighborhood in the only P_i that contains u . For a boundary vertex u we first output the neighborhood of u in F , which are all neighbors being boundary vertices. We then iterate over each P_i that contains u (and where u has non-boundary neighbors) and output the neighbors that are not boundary vertices.

To achieve a succinct data structure we make use of the succinct encoding for planar and other separable graphs described by Blelloch and Farzan [3], outlined in detail in Section 5. They use the same framework of constructing r -partitions in a two-level fashion as an encoding scheme. In detail, they construct an r -partition for the input graph $G = (V, E)$, and for each piece P_i of the r -partition construct another r' -partition. Each piece $P_{i,j}$ of this r' -partition is categorized by an index in a lookup table, referencing an isomorphic graph $P_{i,j}^*$ which uses "local" labels from $1 \dots r'$, instead of a subset of the "global" labels $1 \dots n$. Furthermore, they use translation data structures that allow us to translate such local labels to global labels. These translation data structures and the lookup table can be realized with $o(n)$ bits. The majority of the space to store the encoding is taken up by storing one index into the lookup table for each graph of size $O(r')$. Blelloch and Farzan show that storing these indices uses $\mathcal{H}(n) + o(n)$ bits, with $\mathcal{H}(n)$ being the entropy of encoding a planar graph with n vertices. We use the same data structure as a basis for our graph encoding, but enhance it with dynamic qualities (Section 5 and Section 6). This (partially) answers the question posed by Blelloch and Farzan [3], if modifications of the succinctly encoded graph are possible. A key notion is that most of the novel "building blocks" pertain only the boundary vertices, of which there are so few that even using non-space efficient data structures for these vertices we are able to maintain succinctness.

► **Theorem 1.** *Let $\mathcal{H}(n)$ be the entropy of encoding a planar graph with n vertices and G an unlabeled simple n -vertex planar graph. There exists an encoding of G that provides induced-minor operations (i.e., vertex deletions and edge contractions) with the following properties: The encoding requires $O(n)$ time to execute any number of induced-minor operations and provides neighborhood and degree operations in constant time (per element). Storing the encoding requires $\mathcal{H}(n) + o(n)$ bits and initializing the encoding can be done in $O(n)$ time with $O(n)$ bits.*

Using optional hashing techniques adapted from the data structure of Holm et al. [12, Lemma 5.15] we provide edge deletion and adjacency queries.

► **Corollary 2.** *The encoding of Theorem 1 can be extended to provide expected $O(1)$ time adjacency queries and process any number of minor operations in expected $O(n)$ time.*

3 Preliminaries

Let k be a positive integer. We denote by $[k] = \{1, \dots, k\}$. Our model of computation is the word RAM with a word length of $w = \Omega(\log n)$ bits. We work with unlabeled graphs, which means that we are free to use an arbitrary labeling for our final encoding. In the following let $G = (V, E)$. We use $G[V']$ with $V' \subseteq V$ to denote the vertex induced subgraph on V' of G . We also write $V(G)$ for the vertices V of G and $E(G)$ for E . Furthermore, we assume that all graphs are simple. A merge of a pair of two vertices $u, v \in V$ means replacing both vertices u, v with a new vertex x with $N(x) = N(u) \cup N(v) \setminus \{u, v\}$. In our data structures we merge u and v by setting $N(u) := N(u) \cup N(v) \setminus \{u, v\}$ and removing v from V . We then say that v is merged to u . Note that merging u to v is a different operation. If the two vertices that are being merged are adjacent, we also say that we *contract the edge* $\{u, v\}$. We denote by n the number of vertices of the graph G under consideration. If there are multiple graphs in a context we use subscript notation to distinguish between graphs, i.e., when talking about a graph G_i for some integer i we use n_i as the number of its vertices.

Planar graph. A graph is planar exactly if it can be drawn in the plane such that no two edges cross. The family of planar graphs is closed under taking minors. Any planar graph G has $O(n)$ edges. An operation that modifies a planar graph under consideration is *planarity preserving* if afterwards the graph is still planar. We denote with $\mathcal{H}(\cdot)$ the entropy to encode a planar graph, a function dependent on the number of vertices of the graph under consideration. It is known that $\mathcal{H}(n) = \Theta(n)$ [25].

All following results assume that w.l.o.g. all given planar graphs are connected. If this is not the case, we add a dummy vertex and connected it to an arbitrary vertex in each connected component. After our final dynamic encoding of Theorem 1 is constructed, we can simply ignore the dummy vertex and all its incident edges during any output of the provided operations. As we require this modification to be space-efficient, concretely that it only uses $O(n)$ bits of additional space and runs in $O(n)$ time during the construction, we provide an explicit lemma for the construction of this modification. Note that our final encoding only uses $O(1)$ extra bits due to this.

► **Lemma 3.** *Let G be a simple planar graph. We can add a dummy vertex v_d to V and all edges $\{v_d, u\}$ to E with u being one vertex in each connected component of G using $O(n)$ bits in $O(n)$ time.*

Proof. Identify an arbitrary vertex in each connected components using a breadth-first search (BFS). Denote with S the set of all these vertices. This set is exactly the neighborhood of the dummy vertex v_d we add to G , i.e., $N(v_d) = S$. We represent the set S with a bit-array of length n with a bit set to 1 at an index u exactly if the vertex u is in S . Using a space-efficient BFS that runs in $O(n)$ time and uses $O(n)$ bits [7] we arrive at our desired runtime and space-usage. It is easy to see that this modification preserves planarity. To support standard access operations, we construct an indexable dictionary (Lemma 6) for the set S , which uses $O(n)$ bits total. This allows us to iterate over the neighborhood of v_d in constant time per element. When iterating over the neighborhood of any vertex $u \in V \setminus \{v_d\}$ first check if $S[u] = 1$ (in the bit-vector representing S), in which case output v_d as the first neighbor of u . Afterwards, continue with the neighborhood iteration in G normally, i.e., output all other neighbors of u . ◀

Graph partitions Let $G = (V, E)$ be a planar graph and r some integer. An r -partition $\mathcal{R} = \{P_1, \dots, P_k\}$ of G is a partition of G into $k = O(n/r)$ edge-disjoint subgraphs called *pieces*. Each piece has $O(r)$ vertices. For each $P \in \mathcal{R}$ there exists a set of *boundary vertices* $\delta P \subset V(P)$ such that $u \in \delta P$ exactly if u is incident to an edge $\{u, v\} \in E$ with $v \notin V(P)$. For each P it holds that $|\delta P| = O(\sqrt{r})$. We denote with $\delta \mathcal{R} = \bigcup_{P \in \mathcal{R}} \delta P$ the set of boundary vertices of \mathcal{R} . For any r -partition \mathcal{R} we denote by k the number of pieces, and assume they are numbered from $[k]$ as $\mathcal{R} = P_1, \dots, P_k$. Sometimes we use a subscript numbering to distinguish between multiple r -partitions, in this case we use the same subscript numbering to refer to the number of parts of the r -partition, i.e., we use k_i when talking about an r -partition \mathcal{R}_i for some integer i . To give some context, we later construct r' -partitions for each piece P_i of a given r -partition \mathcal{R} , for which we use the notation $\mathcal{R}_i = \{P_{i,j}, \dots, P_{i,k_i}\}$.

Forbidden-vertex graph data structure. We use a data structure that is initialized for a simple planar graph $G = (V, E)$ and an arbitrary set $B \subseteq V$ of *forbidden vertices* that allows modifications of G in the form of edge insertions and deletions, and in the form of vertex merges while maintaining two invariants: no edges between vertices of B exist and G is simple and planar. This data structure was described by Holm et al. [12] as a building block for their contraction data structure. We slightly modify their data structure and change some notation to match our use-cases. We later use this data structure for (among other things) maintaining edges between so-called boundary vertices, as sketched in Section 2. The operations are more precisely defined in the next paragraph. We refer to this data structure as *forbidden-vertex graph data structure*. For each vertex and edge managed by the data structure we can access and modify auxiliary data, which takes constant time if a reference to the vertex or edge in question is given. When contracting two vertices u, v some edge $\{u, x\}$ might be removed and inserted again as $\{v, x\}$. We view this as the same edge, but with different endpoints. Meaning, auxiliary data of $\{u, x\}$ is now stored at $\{v, x\}$. If $\{v, x\}$ already existed before the merge, we can decide what to do with the data of the discarded parallel edge. All operations are only permitted if they preserve planarity. In the following we more precisely define the available modifications:

- **Merge.** Given are two vertices u, v with $u \neq v$. Merge v to u by setting $N(u) := N(u) \cup N(v) \setminus \{u, v\}$ and removing v and all incident edges from V . Returns a reference to u and reports and discards all parallel edges during the merge, and reports all non-parallel edges inserted to $N(u)$ during the merge. Edges that would occur between vertices of B are discarded.
- **Insert.** Given are two vertices u, v with $u \neq v$ and $\{u, v\} \notin E$. Insert the edge $e = \{u, v\}$ into E if $u, v \notin B$.
- **Delete.** Let $\{u, v\}$ be a given edge. Remove the edge $\{u, v\}$ from E .

In addition to these operations the data structure provides adjacency, neighborhood and degree queries in constant time (per element).

► **Lemma 4** ([12]). *Let $G = (V, E)$ be a simple planar graph and $B \subseteq V$. A forbidden vertex graph data structure can be initialized for G and B in $O(n \log n)$ time. It provides constant time (per element) neighborhood and adjacency queries and access to the label mappings. An edge insertion and an edge deletion takes $O(\log n)$ time. Any number of (planarity preserving) vertex merges are executed in $O(n \log^2 n)$ time. The data structure uses $O(n \log n)$ bits.*

To achieve the runtime outlined in Lemma 4 for vertex merges, each merge of two vertices $u, v \in V$ is processed by merging the vertex with the lowest degree to the vertex with the highest degree, i.e., we can not freely choose which vertex is merged. A simple mapping

using standard data structures allows us to label the vertex $x \in \{u, v\}$ that remains after the merge either u or v . We refer to a merge of two vertices where we are able to freely decide the labeling of the remaining vertex after the merge as *free-assignment merge*. We henceforth assume that all merges of the data structure are free assignment merges. The following lemma summarizes this.

► **Lemma 5.** *Let $G = (V, E)$ be a simple planar graph and $B \subseteq V$ managed by the forbidden-vertex graph data structure of Lemma 4. Using $O(n)$ additional time for initialization and $O(n \log n)$ bits we are able to process any number of free-assignment merges in $O(n \log^2 n)$ time on G .*

Proof. Let $G_0 = (V_0, E_0)$ be the graph managed by the data structure before any contractions, edge insertions or deletions are processed. Construct a mapping **internal** : $V_0 \rightarrow V$ and a mapping **external** : $V \rightarrow V_0$, both initially equal to the identity function. Assume we merge two vertices u and v and denote with $x \in \{u, v\}$ the vertex that remains after the merge. Denote with $y \in \{u, v\}$ the label we want to assign to x , i.e., the labeling that turns the merge into a free assignment merge. For this, set **internal**(y) := x and **external**(x) := y . Given a user-assigned label u of a vertex, find the internal labeling via **internal**(u). All internal labels are translated via the **external** mapping before output during any of the operations provided by the simple dynamic graph data structure. Both mappings can be implemented with a simple array of length $|V_0|$ in time $O(n)$ using $O(n \log n)$ bits. ◀

Indexable dictionaries. We use a data structure called *indexable dictionary* (ID), which is initialized for a fixed universe U of consecutive integers and a set $S \subseteq U$ and supports membership, rank and select queries. A rank query for some $x \in U$ returns $|\{y \in S : y < x\}|$. A select query for some integer i returns the value of $x \in U$ such that x is stored at rank i .

► **Lemma 6** ([21]). *Let $s \leq u$ be two integers. Given a set S of size s , which is a subset of a universe $U = [u]$, there is a succinct indexable dictionary (ID) on S that requires $\log \binom{u}{s} + o(s) + O(\log \log u)$ bits and supports rank/select on elements of S in constant time.*

We use IDs with $u = n$ and $s = O(n/\Lambda(n))$ for some function $\Lambda(n) = \omega(1)$, therefore each ID requires $o(n)$ bits, a characteristic already used by Blelloch and Farzan [3]. It is mentioned in [21] that the ID of Lemma 6 can be constructed in $O(u)$ time using $O(u)$ bits.

4 Table lookup for small planar graphs

In this section we present our table lookup data structure for small graphs. Given an integer r the table lists for every positive integer $r' \leq r$ every possible planar graph with vertex set $V = [r']$. Such a lookup table was used by Blelloch and Farzan [3] as a building block for succinctly encoding planar and other separable graphs, which we outline Section 5. For every graph G encoded by the table, they provide adjacency queries and neighborhood iteration in constant time (per element). The table can be realized using $O(2^{\text{poly}(r)})$ bits and time, including the data structures needed to provide the queries. To distinguish between all graphs with r' vertices we use $\mathcal{H}(r') + O(1)$ bits. This corresponds to an index into the computed table. The table contains $2^{\mathcal{H}(r)}$ entries. Everything mentioned so far was shown by Blelloch and Farzan. We provide additional operations, outlined in the following.

- Range filtered neighborhood iteration: Takes as input an index i into the lookup table, three vertices $u, a, b \in V$, with $G = (V, E)$ being the graph encoded at index i and $u \neq a \neq b$. Provides an iterator over all neighbors v of u with $a \leq v \leq b$.

- Batch edge deletion: Takes as input an index i into the lookup table, three vertices $u, a, b \in V$ with $G = (V, E)$ the graph encoded at index i . Returns the index j encoding the graph $G' = (V, E \setminus X)$ with $X = \{\{u, v\} : v \in N(u) \text{ and } a \leq v \leq b\}$.
- Label-preserving merge: Takes as input an index i into the lookup table and two vertices $u, v \in V$, with $G = (V, E)$ being the graph encoded at index i . Returns the index j encoding the graph G' obtained from G by setting $N(u) := N(u) \cup N(v) \setminus \{u, v\}$, setting $N(v) := \emptyset$ and marking v as deleted (see the next paragraph for details on this). Maintains the invariant that $V(G') = V(G)$. The operation is only permitted if it preserves planarity.

All these operations can easily be pre-computed for one entry of the table in time $O(\text{poly}(r))$ using the same amount of bits. The sum of computations over every entry of the table is $O(2^{\text{poly}(r)})$. As a note on the label-preserving merge operation, vis-à-vis keeping the vertex v , but marking it deleted, consider the following example. We want to merge the vertices u and v in some graph $G = (V, E)$ encoded by the table with r' vertices. If we would simply merge them, the vertex v no longer exists. In particular, the vertex set after the merge is $V' = V \setminus \{v\}$. As the vertex set for each graph encoded by the table is consecutively numbered from $[r']$, graphs with vertex set V' are possibly not encoded by the table. To remedy this, we simply keep the vertex v in the graph but mark it deleted. It remains to show how to handle 'mark v as deleted'. To each graph encoded by the table we add a dummy vertex called `deleted`. The table lists every possible planar graph with at most $r + 1$ vertices, where the vertex with the largest label is our dummy vertex `deleted`. To mark v as deleted during the label preserving merge, we set $N(\text{deleted}) := N(\text{deleted}) \cup \{v\}$ (and $N(v) := \{\text{deleted}\}$). We are now able to check if a vertex is deleted, by checking if it is adjacent to `deleted`. When we later encode a graph $G = (V, E)$ via an index into this lookup table, we encode it as the graph $G' = (V \cup \{\text{deleted}\}, E)$, i.e., with no vertices marked as deleted initially.

It remains to observe how one additional extra vertex increases the size of the table. The size of each entry encoded by the table stays asymptotically the same, and is thus of no concern to us. The number of entries in the table is $O(2^{\mathcal{H}(r+1)})$, and therefore each index into the lookup table encoding a graph with r' vertices requires $\mathcal{H}(r' + 1) + O(1)$ bits to be stored. As $\mathcal{H}(r' + 1) = \Theta(r' + 1)$ [25] it holds that $\mathcal{H}(r' + 1) = \mathcal{H}(r') + O(1)$, which is negligible for our purpose. Therefore, our table uses $2^{\text{poly}(r)}$ bits, which is asymptotically the same as the original table of Blelloch and Farzan. Each index of the table uses only a constant number of additional bits over the theoretical lower bound. Note that indices into the original unmodified table of Blelloch and Farzan also require this additional $O(1)$ bits (albeit with a smaller factor).

► **Lemma 7.** *Let r be a positive integer. There exists a table that encodes all planar graphs with vertex set $\{1, \dots, r'\}$ for all integers $r' \leq r$ with the following properties. For every graph encoded by the table, (range filtered) neighborhood iteration, adjacency queries and label-preserving merge operations and batch edge deletion are provided in constant time (per element). The table can be constructed in $O(2^{\text{poly}(r)})$ time using $O(2^{\text{poly}(r)})$ bits. Every index of the table referencing a graph with r' vertices requires $\mathcal{H}(r') + O(1)$ bits.*

5 Succinct encoding of planar graphs

In this section we describe the succinct encoding of unlabeled planar (and other separable) graphs due to Blelloch and Farzan [3]. We use their data structure as a basis for our encoding.

Our work can be thought of as extending their encoding with (induced-) minor operations. For these extensions we need to give a technical overview of their encoding. Let $G = (V, E)$ be an unlabeled planar graph, $\mathcal{R} = \{P_1, \dots, P_k\}$ an r -partition with $r = \log^4 n$, and for each P_i with $i \in [k]$, let $\mathcal{R}_i = \{P_{i,1}, \dots, P_{i,k}\}$ be an r' -partition of P_i with $r' = \log^4 \log^4 n$.¹ The encoding assigns three labels to each vertex $u \in V$. A label in the entire graph (called *global label*) a label in each piece $P_i \in \mathcal{R}$ (called a *mini label*) and a label in each piece $P_{i,j} \in \mathcal{R}_i$ (called a *micro label*). We refer to G with the newly assigned labels as the *global graph*, each labeled $P_i \in \mathcal{R}$ as a *mini graph*, and each labeled $P_{i,j} \in \mathcal{R}_i$ as a *micro graph*. Note that boundary vertices of $\delta\mathcal{R}$ receive multiple mini labels, and analogous boundary vertices of $\delta\mathcal{R}_i$ receive multiple micro labels. We refer to the boundary vertices of $\delta\mathcal{R}$ with their assigned global labels as δG , and the set of boundary vertices of $\delta\mathcal{R}_i$ with their assigned mini labels in P_i as δP_i . For a given boundary vertex u identified by its global label, we refer to all occurrences u' (as a mini label) of u in a mini graph P_i as *duplicates*, and the same for boundary vertices of mini graphs P_i in regard to their occurrences in micro graphs. We refer to the set of (mini labels of) duplicate vertices in a mini graph P_i as ΔP_i , and analogous the set of (micro labels of) duplicate vertices in a micro graph $P_{i,j}$ as $\Delta P_{i,j}$. Global labels are assigned, starting from 1 in increments of 1, first to all non-boundary vertices and then to boundary vertices. Analogous for mini labels in mini graphs. Micro labels are assigned arbitrarily. When we discuss operations, vertices are identified by their respective label. E.g., a neighborhood query of a vertex $u \in V$ is executed with the global label of u as an input, and it outputs the global labels of all $v \in N(u)$, analogous for neighborhood queries in a mini or micro graph. Every micro graph is encoded as an index into a lookup table \mathcal{T} , which lists all possible planar graphs of at most r' vertices. Technically this is realized by an array with one entry for each micro graph, which can be indexed by (i, j) when retrieving the entry for micro graph $P_{i,j}$. For our use case we replace the table of Blelloch and Farzan with the table described in Section 4, which provides additional operations. We now describe operations that the encoding provides, which are used by Blelloch and Farzan in their original publication, but are not defined outside of proofs. Let $u \in V$ be a vertex identified by its global label. For each such u , the encoding provides a mapping to access a list $\phi(u)$ that contains tuples (i, u') with i the index of a mini graph P_i that contains mini label u' of u . The lists are sorted in increasing order by i . Note that if u is a non-boundary vertex the mapping contains only a single tuple. For each such tuple (i, u') we can access a mapping $\phi_i^{-1}(u') = u$. For vertices u' in each mini graph P_i (identified by their mini label) analogous mappings $\phi_i(u')$ containing tuples (j, u'') with j the index of a micro graph $P_{i,j}$ that contains micro label u'' of u' , and the analogous mappings $\phi_{i,j}^{-1}(u'') = u'$ are provided. We refer to all these mappings as *static translation mappings*.

Recall that Blelloch and Farzan assign micro labels in an arbitrary fashion. We instead assign the labels according to a coloring we define in the following. Let $P_{i,j}$ be the micro graph we want to label. We first assign labels to vertices that are neither a boundary vertex of $\delta\mathcal{R}$ nor of $\delta\mathcal{R}_i$, which we assign the color **simple**. Then we assign labels to vertices that are in the boundary $\delta\mathcal{R}$, but not in $\delta\mathcal{R}_i$, which we assign the color **global boundary**. Then to vertices that are not in the boundary $\delta\mathcal{R}$, but in the boundary $\delta\mathcal{R}_i$, colored **mini boundary**, and finally to vertices in both the boundary $\delta\mathcal{R}$ and in $\delta\mathcal{R}_i$, colored **double-boundary**. Consequently, for any four vertices of $P_{i,j}$ it holds that $a < b < c < d$ if a is colored **simple**, b is colored **global boundary**, c is colored **mini boundary** and d is colored **double-boundary**.

¹ Blelloch and Farzan use $r' = \log n / \log \log n$ in their publication, but make it clear that there is a large degree in freedom as long as the choice is of size $o(\log n)$.

For each mini graph we store the lowest labeled vertex of each color, which uses negligible space of $O((n/\log^4 \log^4 n) \log \log^4 \log^4 n) = o(n)$ bits overall.

Combined with our novel way of assigning micro labels to vertices of micro graphs, the range-filtered neighborhood operation provided by our table allows us to implement the *color-filtered neighborhood* operation that outputs all neighbors x of a vertex u (in a micro graph $P_{i,j}$) such that all x are colored with $c \in \{\text{simple}, \text{global boundary}, \text{mini boundary}, \text{double-boundary}\}$. The operation runs in constant time (per element output).

Using the label preserving merge operation of the lookup table from Lemma 7 we can easily provide such merges for every micro graph. The same holds for the vertex and (batch) edge deletion operation.

For a given unlabeled planar graph G we refer to the encoding described in this section as *basic encoding of G* . Recently Kammer and Meintrup [14] have shown that the encoding can be constructed in $O(n)$ time using $O(n)$ bits during the construction phase when an unlabeled simple planar graph is given as the input. Our two modifications (assigning micro labels in a non-arbitrary way and extensions to the lookup table) have negligible impact on the runtime and space usage of the construction. The result is summarized in the following theorem.

► **Theorem 8.** *Let G be an unlabeled planar graph and $\mathcal{H}(n)$ the entropy of encoding a planar graph with n vertices. There exists a basic encoding of G into a global graph, mini graphs and micro graphs that uses $\mathcal{H}(n) + o(n)$ bits total. The basic encoding provides static translation mappings for the global graph, each mini graph and each micro graph. For each micro graph the encoding provides degree, adjacency, (color-filtered) neighborhood, (batch) edge/vertex deletion and label-preserving merge operations in $O(1)$ time. The basic encoding can be constructed in $O(n)$ time using $O(n)$ bits.*

6 Dynamic mapping data structures

For the rest of this section assume a planar graph G is given via the basic encoding of Theorem 8. In this section we describe a set of dynamic mapping structures, for which we outline the use-case in the following. An important invariant we already mentioned in Section 2, is the following: a vertex that is initially a boundary vertex (globally or/and in mini graphs) will never become a non-boundary vertex, and a non-boundary vertex will never become a boundary vertex due to any of our edge contractions. We construct dynamic variants of the static translation mappings for boundary vertices (in the global or in mini graphs). We ensure that the static translation mappings remain valid for all non-boundary vertices. Later these mappings are concretely constructed for the vertices of the initial graph (i.e., before any contractions are processed) and are maintained for all of these vertices throughout. I.e., the sets for which the mappings and data structures of this section are defined never change after initialization. Recall from Section 2 that when contracting an edge $\{u, v\} \in E$ we effectively forward the contraction operation to mini graphs that contain mini labels u' and v' of u and v respectively, where we again forward the contraction to micro graphs in an analogous way. I.e., we contract an edge on the global level via merges on the mini graph level, which are executed via merges on the micro graph. It is important for our solution that these cascading merge operations are handled independently without interfering with each other.

Consider for example the case where we contract an edge $\{u, v\} \in E$ with u being a boundary vertex and v a non-boundary vertex. In this case we want to contract v to u (technical reasons for this are outlined in the next section). To fulfill this contraction, we

forward a request to the mini graph P_i to merge the vertices u' and v' , the respective mini labels of u and v in P_i . In the case that v' is a boundary vertex in P_i , but u' is a non-boundary vertex in P_i , we want to merge u' to v' , which is in conflict with our desire to merge v to u in the global graph. The idea is to support free-assignment merges, whose realization is described in the next paragraph. This sort of conflict only pertains to vertices u that are part of the boundary δG (thus, a duplicate ΔP_i in P_i) and/or have a mini label u' in some P_i that is part of the boundary δP_i , i.e., we need to provide free-assignment merges for vertices of $\delta P_i \cup \Delta P_i$. We construct a dynamic mapping that allows us to decide, when merging two vertices $u', v' \in \Psi P_i$, if the vertex that remains after the merge is labeled u' or v' . This is realized by assigning each such vertex an *external mini label* and an *internal mini label* label. Effectively we have no free choice on which internal mini label the vertex has after a merge, but we are free to assign a new external label. We construct a mapping $\mathbf{internal}_i : \delta P_i \cup \Delta P_i \rightarrow \delta P_i \cup \Delta P_i$ that maps a given external label of a vertex of $\delta P_i \cup \Delta P_i$ to its internal label, and a mapping $\mathbf{external}_i : \delta P_i \cup \Delta P_i \rightarrow \delta P_i \cup \Delta P_i$ that maps a given internal mapping of a vertex $\delta P_i \cup \Delta P_i$ to its external label. For all other vertices of P_i we ensure that the external and internal mini labels are identical, and therefore do not need to construct an explicit mapping. This is more explicitly defined in Invariant 2 at the end of this section.

► **Lemma 9.** *All mappings $\mathbf{internal}_i$ and $\mathbf{external}_i$ can be constructed in $O(n)$ time using $o(n)$ bits of space. They provide read/write access in $O(1)$ time.*

Proof. The mapping $\mathbf{internal}$ is realized as follows. For each mini graph P_i construct an ID (Lemma 6) I_i over the universe $V(P_i)$ which manages the set $\delta P_i \cup \Delta P_i$. Additionally, construct an array A_i that stores for each $u \in \delta P_i \cup \Delta P_i$ at index $I_i.\mathbf{rank}(u')$ a value from universe $\delta P_i \cup \Delta P_i$. Each ID is constructed in linear time and the bits required for all IDs is $o(n)$. The arrays use $o(n)$ bits in total as they store $O(n/\log^2 \log^4 n)$ entries, each of size $O(\log \log^4 n)$ bits and are initialized in $O(n)$ time. To read a value $\mathbf{internal}_i(u')$ for $u' \in \delta P_i \cup \Delta P_i$ simply read the value stored at $A_i[x]$ with $x = I_i.\mathbf{rank}(u')$ and to write the value $\mathbf{internal}_i(u') := v'$ for some $v' \in \delta P_i \cup \Delta P_i$ simply set $A_i[x] := v'$. Clearly this runs in constant time. For the inverse mappings $\mathbf{external}_i$ we construct the same data structures with the same runtime and bits. ◀

We also have the need for a dynamic version of the static translation mappings ϕ and ϕ_i for boundary vertices δG in the global graph and boundary vertices δP_i in mini graphs, and the mappings ϕ_i^{-1} and $\phi_{i,j}^{-1}$ for the duplicate vertices ΔP_i in mini graphs and $\Delta P_{i,j}$ micro graphs, outlined in the following paragraphs. Initially these are equal to the static mappings. We first describe the dynamic versions of the mappings ϕ_i^{-1} and $\phi_{i,j}^{-1}$, which we refer to as Φ_i^{-1} and $\Phi_{i,j}^{-1}$ respectively. Afterwards we describe the dynamic versions of the mappings ϕ and ϕ_i , referred to as Φ and Φ_i . To give an intuition for the use-case of these mappings, consider a contraction of an edge $e = \{u, v\} \in E$ with $u, v \in \delta G$. We contract this edge by first merging all u' and v' in the mini graphs P_i that contain both the duplicate u' of u and v' of v . In all P_i that contain only a duplicate of v' of v we need to know that the global label of v' is now (i.e., after the contraction) u instead of v , for which we use the described mappings. I.e., we insert the tuple (i, v') to $\Phi(u)$ and set $\Phi_i^{-1}(v') := u$. In all other mini graphs no changes must be made. Technically these mappings are realized almost exactly as the mappings of Lemma 9. They are initialized to be equal to the analogous static mappings.

► **Lemma 10.** *All mappings $\Phi_i^{-1} : \Delta P_i \rightarrow \delta G$ and $\Phi_{i,j}^{-1} : \Delta P_{i,j} \rightarrow \delta P_i$ can be constructed in $O(n)$ time using $o(n)$ bits of space. They provide read/write access in $O(1)$ time.*

Proof. The mappings are realized as follows. For each mini graph P_i construct an ID I_i (Lemma 6) over the universe $V(P_i)$ which manages the set ΔP_i . Additionally, construct an array A_i that stores for each $u \in \Delta P_i$ at index $I_i.\text{rank}(u)$ any value from universe δG . Each ID is constructed in linear time and the bits required for all IDs is $o(n)$. The IDs and arrays use $o(n)$ bits in total as they store $O(n/\log^2 n)$ entries, each of size $O(\log n)$ bits and are initialized in $O(n)$ time. To read a value $\Phi^{-1}(u')$ for $u' \in \Delta P_i$ simply read the value stored at $A_i[x]$ with $x = I_i.\text{rank}(u')$ and to write the value $\Phi^{-1}(u') := v$ for some $v \in \delta G$ simply set $A_i[x] := v$. Clearly this runs in constant time. For the analogous mappings $\Phi_{i,j}^{-1}$ constructed for all micro graphs $P_{i,j}$ construct the same data structures. All IDs and arrays constructed for the micro graphs store $O(n/\log^2 \log^4 n)$ entries, each of size $O(\log \log^4 n)$, i.e., $o(n)$ bits total. \blacktriangleleft

We now describe the dynamic mappings Φ and Φ_i . As mentioned, we initially require all mappings $\Phi(u)$ to be equal to $\phi(u)$ for $u \in \delta G$ and analogously all mappings $\Phi_i(u')$ to be initially equal to $\phi_i(u')$ for $u' \in \delta P_i$ for all mini graphs P_i . To represent these mappings we construct a graph H that contains all boundary vertices $u \in \delta G$ and, for each mini graph P_i , a vertex p_i , with edges $\{u, p_i\}$ added to H exactly if u has a duplicate u' in P_i . At each such edge we store the tuple (i, u') . We construct H using the forbidden vertex graph data structure of Lemma 4. The tuples stored at the incident edges of a vertex $u \in \delta G$ in H are exactly the set $\phi(u)$. Note that H is a minor of G and therefore planar. We can provide for all $u \in \delta G$: iteration over all elements $\Phi(u)$ (by iterating over $N(u)$ in H), insertion and removal of elements in $\Phi_i(u)$ (by inserting or removing edges in H), the merge of two sets $\Phi(u)$ and $\Phi(v)$ for some $v \in \delta G$ (by merging u to v or v to u in H). Some other similar operations are provided, outlined in detail in the next section where we concretely describe our edge contraction algorithm. For each mini graph P_i the analogous graph H_i is constructed, which manages the mappings Φ_i . An important note is that for each tuple $(i, u') \in \Phi(u)$ for $u \in \delta G$ the vertex u' is the external mini label of some vertex in P_i . As no external or internal micro labels are defined for micro graphs, each tuple $(j, u'') \in \Phi_i(u')$ for all mini graphs P_i contains the concrete micro label u'' in $P_{i,j}$. In the next section we describe our neighborhood operation, for which we require a special version of the mappings Φ , which we first motivate with an intuition. To output the neighborhood of a vertex $u \in \delta G$ we (intuitively) iterate over all $(i, u') \in \Phi(u)$ and, for each such (i, u') , iterate (and translate to global labels) over all neighbors of u' in P_i . To achieve a runtime of $O(|N(u)|)$ for this operation, we require that each tuple (i, u') "contributes" at least one such neighbor. While this is true initially, due to edge contractions (and other modifications) the degree of each such u' can become 0. To remedy this, we store a special version of the mappings $\Phi(u)$ which we refer to as $\Phi^{>0}$, containing only tuples $(i, u') \in \Phi(u)$ such that the degree of u' is > 0 . We construct the analogous mappings $\Phi_i^{>0}$ for all P_i . During contractions, we update the mappings $\Phi^{>0}$ and $\Phi_i^{>0}$ to uphold the aforementioned characteristic, which is formalized in Invariant 1. How this invariant is upheld, is discussed in the next section. We realize these mappings exactly as Φ and Φ_i , respectively, i.e., as graphs $H^{>0}$ and $H_i^{>0}$. Note that initially $H^{>0} = H$ and all $H_i^{>0} = H_i$, by the definition of boundary vertices in r -partitions (Section 3).

► **Invariant 1** (non-zero-degree invariant). *For all $u \in \delta G$, each entry $(i, u') \in \Phi^{>0}(u)$ guarantees that u' has degree > 0 in mini graph P_i . For all $u' \in \delta P_i$ over all mini graphs P_i , each entry $(j, u'') \in \Phi_i^{>0}(u')$ guarantees that u'' has degree > 0 in micro graph $P_{i,j}$.*

► **Lemma 11.** *Graphs H , $H^{>0}$ and H_i , $H_i^{>0}$ for all mini graphs P_i can be constructed in $O(n)$ time using $o(n)$ bits.*

Proof. The graph H contains $O(n/\log^2 n)$ nodes as per construction. The data structure of Lemma 4 is used to construct and manage H , which results in a construction time of $O(n/\log n) = o(n)$ and the same number of bits. There are $O(n/\log^4 n)$ graphs H_i , each containing $O(\log^4 n/\log \log^4 n)$ vertices. This results in a total construction time of $O(n/\log^4 n \cdot \log^4 n/\log^2 \log^4 n \cdot \log \log^4 n) = o(n)$ for all H_i and the same number of bits. The graphs $H^{>0}$ and $H_i^{>0}$ are constructed in the same way. To uphold Invariant 1 initially, simply do not add edges to $H^{>0}$ or $H_i^{>0}$ that would violate this invariant. ◀

Using all data structures described in this section we uphold invariants below while running contractions on G —the details on this are described in the next section. For better readability we slightly abuse the definition of our **internal** and **external** mappings of Lemma 9 by assuming they are also available for vertices $u' \notin \delta P_i \cup \Delta P_i$, but always return the identity function.

► **Invariant 2** (label-translation invariants).

a. **Global to external mini label and vice-versa:**

- I. For each $u \in V \setminus \delta G$ and $(i, u') = \phi(u)$ it holds that u' is the external mini label of u in P_i and $\phi^{-1}(u') = u$.
- II. For each $u \in \delta G$ and $(i, u') \in \Phi(u)$ (Φ is the dynamic version of ϕ) it holds that u' is the external mini label of u in P_i and $\Phi^{-1}(u') = u$.

b. **Internal to external mini label and vice-versa:**

For each vertex $u' \in V(P_i)$ identified by its external mini label, it holds that $u^* = \mathbf{internal}(u')$ is the internal mini label of u' and $\mathbf{external}(u^*) = u'$.

c. **Mini to micro label and vice-versa:**

- I. For each $u' \in V(P_i) \setminus \delta P_i$ (identified by its internal mini label) and $(j, u'') = \phi_i(u')$ it holds that u'' is the micro label of u' in $P_{i,j}$ and $\phi_{i,j}^{-1}(u'') = u'$.
- II. For each $u^* \in \delta P_i$ (identified by its internal mini label) and for each $(j, u'') \in \Phi_i(u^*)$ it holds that u'' is the micro label of u^* in $P_{i,j}$ and $\Phi_{i,j}^{-1}(u'') = u^*$.

7 Towards a succinct dynamic encoding

For the rest of this section let $G = (V, E)$ be a graph encoded by the basic encoding of Theorem 8. Additionally, assume that the mappings of Lemma 9, 10 and 11 are constructed and available. In this section we describe our solution to support modifications of G . We denote by $\bar{G} = (\bar{V}, \bar{E})$ the graph G before any modifications are processed, e.g., contractions of edges. Analogously we define by $\bar{P}_i, \bar{P}_{i,j}$ the initial mini and micro graphs, respectively, with its initial vertices (as mini/micro labels). As sketched in Section 2 to handle contractions between so-called boundary edges we construct a data structure we call *boundary graph* $F = G[\delta G]$ and analogously a *mini boundary graph* $F_i = P_i[\delta P_i]$ for each mini graph P_i . These graphs are realized via the forbidden vertex graph data structure (Lemma 4). For F we use as the set of forbidden vertices the empty set. For each F_i we use the duplicate vertices ΔP_i of P_i as the set of forbidden vertices—recall that this means that no edges between these forbidden vertices are allowed to exist. During initialization these edges are removed if they exist. The forbidden-vertex graph data structure makes sure that this remains true after initialization. Let $\{u, v\} \in E$ be an edge. We say $\{u, v\}$ is *managed by* F if $\{u, v\} \in E(F)$, $\{u, v\}$ is *managed by* F_i if $\{u', v'\} \in E(F_i)$ with u' and v' the mini labels of u and v respectively, and finally we say $\{u, v\}$ is *managed by* $P_{i,j}$ if it contains the edge $\{u'', v''\}$ with u'', v'' being the micro labels of u and v , respectively. We uphold the following invariant:

► **Invariant 3** (edge-singleton invariant).

- a. An edge $\{u, v\}$ is managed by F exactly if $u, v \in \delta G$.
- b. An edge $\{u, v\}$ is managed by F_i exactly if $u', v' \in \delta P_i \setminus \Delta P_i$, with u', v' the respective mini labels of u and v in P_i . In this case, no other F_j ($j \neq i$) also manages $\{u, v\}$.
- c. All edges $\{u, v\}$ not managed by F or some F_i are managed by one micro graph $P_{i,j}$.

Our construction of F and each F_i is the first step to achieve this invariant. We now give an intuition why this invariant is useful. Due to some edge contractions new edges $\{u, v\}$ might occur in G between boundary vertices (either global boundary vertices or vertices that are boundary vertices in a mini graph). We can not afford to add this edge to all mini and micro graphs that contain mini and micro labels of both u and v , respectively. Instead, we only add this edge to F or some F_i . Moreover, having an edge $e \in E$ be managed multiple times can increase the runtime of the neighborhood operation by more than a constant factor.

An important note is that the basic encoding of G does not adhere to the edge-singleton invariant from the get-go, i.e., edges managed by some F or F_i might be contained in one or more micro graphs initially. Using the batch edge deletion operation provided for micro graphs (Theorem 8) we can easily delete all edges that would initially violate our invariant in $O(n)$ time. We therefore assume from now that these edges are initially removed. If this would result in a violation of Invariant 1, we simply remove the respective entries from $\Phi^{>0}$ or $\Phi_i^{>0}$ in $O(n)$ total time.

We refer to the combination of the basic encoding of G , the mappings of Lemma 9, Lemma 10 and Lemma 11, the boundary graph F and each mini boundary graph F_i as *succinct dynamic encoding of G* , summarized in the following corollary.

► **Corollary 12.** *The succinct dynamic encoding of G can be constructed in $O(n)$ time using $O(n)$ bits. After construction the encoding requires $\mathcal{H}(n) + o(n)$ bits. The encoding upholds the label-translation, edge-singleton and non-zero degree invariant.*

We now give an intuition how we implement the neighborhood operation for a vertex $u \in V$ identified by its global label. We first output all neighbors of u in F (which is \emptyset if u is not a boundary vertex) and then, for all P_i that contain a mini label u' of u , compute all neighbors v' of u' in F_i (which is again \emptyset if u' is not a boundary vertex) and output the respective global label v of v' . We then go to all micro graphs $P_{i,j}$ that contain a mini label u'' of u' , compute all neighbors v'' of u'' in $P_{i,j}$ and output the respective global label v of v'' . By the edge singleton invariant it is easy to see that each neighbor v of u in G is output exactly once by this algorithm. To translate between the different types of labels we make use of Invariant 2. The missing details are discussed in the proof of the following lemma.

► **Lemma 13.** *For any $u \in V$ the neighborhood operation runs in constant time (per element output).*

Proof. We describe the neighborhood operation on three levels: neighborhood of a vertex in a micro graph, in a mini graph and in the global graph. First, to output all neighbors of a vertex u'' in a micro graph $P_{i,j}$ simply use the neighborhood operation provided for micro graphs (Theorem 8). This takes constant time per element output. To output the neighborhood of a vertex $u^* \in V(P_i)$, identified by its internal mini label, we distinguish between two cases: (NM1) $u^* \in \delta P_i$ and (NM2) $u^* \notin \delta P_i$. For Case NM1 proceed as follows: first output all neighbors of u^* in F_i . Then, for each $(j, u'') \in \Phi_i^{>0}(u^*)$ iterate over all neighbors v'' of u'' in $P_{i,j}$. Translate each such v'' to its respective internal mini label v^* with either $\Phi_{i,j}^{-1}(v'') = v^*$ if $v'' \in \Delta P_{i,j}$, or with $\phi_{i,j}^{-1}(v'') = v^*$ if $v'' \notin \Delta P_{i,j}$, as per Invariant 2.

Due to Invariant 1, iterating over all $(j, u'') \in \Phi_i^{>0}(u^*)$ runs in $O(d_{u^*})$ time with d_{u^*} the degree of u^* in $P_{i,j}$. Translating and outputting all neighbors of all u'' in all $P_{i,j}$ can be done in constant time per element output. Outputting all neighbors of u^* in F_i runs in constant time per element output as well. In Case NM2 simply determine the micro graph $P_{i,j}$ that contains the micro label u'' of u^* via $\phi_i(u'') = (j, u'')$ (Invariant 2). Translating and outputting all neighbors of u'' in $P_{i,j}$ is analogous to Case NM1. The runtime is again constant per element output. This is sufficient to provide a neighborhood operation for any $u^* \in V(P_i)$ in constant time per element output. To provide the neighborhood operation for a vertex $u \in V$ we again distinguish between two cases: (NG1) $u \in \delta G$ and (NG2) $u \notin \delta G$. For Case NG1 we first output all neighbors of u in F . Secondly, for each $(i, u') \in \Phi^{>0}(u)$ we determine the internal label u^* of u' in P_i via $\mathbf{internal}[u'] = u^*$, iterate over all neighbors v^* of u^* in P_i and translate each $v' = \mathbf{external}[v^*]$ to its global label v via $\Phi_i^{-1}(v') = v$ (if $v' \in \Delta P_i$) or $\phi_i^{-1}(v') = v$ (if $v' \notin \Delta P_i$). All reads of the various mappings are correct as per Invariant 2. The runtime analysis works analogous to Case NM1 in mini graphs, i.e., constant time per element output. For Case NG2 simply determine the mini graph P_i that contains a duplicate u' of u via $\phi(u) = (i, u')$ and continue analogous to Case NG1. The correctness follows again from Invariant 2. The runtime is constant per element output. Due to Invariant 4 we have output each neighbor of u exactly once. \blacktriangleleft

We now focus on our edge-contraction algorithm. For this we introduce one last invariant, which we call the *status invariant*. As sketched in Section 2 we require that for every vertex being a boundary vertex (either globally or in a mini graph) to remain a boundary vertex, and for every non-boundary vertex to remain a non-boundary vertex. For this we slightly abuse the definition of boundary vertices. As by the definition of r -partition (Section 3) a vertex is a boundary vertex of δG if it has neighbors in more than one mini graph. Due to contractions (or other modifications) this might at some point no longer be true. Nonetheless, we still consider such a vertex to be a boundary vertex. More precisely: a vertex $u \in V$ is a boundary vertex exactly if (1) $u \in \delta \bar{G}$ or if (2) there are multiple mini-graphs that contain a mini-label u' of u . Otherwise, it is a non-boundary vertex. Effectively, we require that no vertex that is initially a non-boundary vertex becomes a boundary vertex, i.e., we avoid that requirement (2) ever become true for an initial non-boundary vertex. We use the analogous definition for boundary/non-boundary vertices in mini graphs P_i . By definition, this invariant is guaranteed after initialization.

► Invariant 4 (status invariant). *For every $u \in V$ and every $u' \in V(P_i)$ over all mini graphs P_i , it holds $u \in \delta G$ if and only if $u \in \delta \bar{G}$ as well as $u' \in \delta P_i$ if and only if $u' \in \delta \bar{P}_i$.*

We now give an overview of our edge-contraction algorithm, which we describe in three levels: vertex merges in micro graphs, vertex merges in mini graphs and edge contractions in the global graph. We guarantee the four invariants (Invariants 1, 2, 3 and 4) before and after each edge contraction. Technically, merges are executed in (mini) boundary graph(s) and micro graphs. Everything else is to maintain the mappings of Section 6. An edge $\{u, v\} \in E$ is contracted by determining all micro graphs $P_{i,j}$ that contain (micro labels of) u and v , all mini boundary graphs F that contain (mini labels of) u and v and determine if F contains u and v . In all these structures that contain u and v we merge v to u and update the various mappings of Section 6. An important fact we make use of is that during this contraction algorithm anytime a pair of vertices is merged in a mini or micro graph, an edge between this pair exists that is managed exactly once (Invariant 3). To guarantee the invariants we split the responsibilities among the three levels (micro/mini/global) as follows.

- **Global Graph-Responsibility.** Edge contractions in the global graph maintain Invariant 1 regarding the mappings $\Phi^{>0}$, Invariant 2.a., Invariant 3.a and Invariant 4 regarding all $u \in V$.
- **Mini Graph-Responsibility.** Vertex merges in a mini graph P_i maintain Invariant 1 regarding the mappings $\Phi_i^{>0}$, Invariant 2.b-c, Invariant 3.b, and Invariant 4 regarding all $u' \in V(P_i)$.
- **Micro Graph-Responsibility.** Vertex merges in a micro graph maintain Invariant 3.c.

Our entire contraction algorithm is built up from bottom-to-top, i.e., we first describe merges in micro graphs, then mini graphs (and mini boundary graphs) and finally edge contractions in G (and merges in F). To uphold the responsibilities delegated to micro graphs we implement a variant of the forbidden-vertex graph data structure (Lemma 4) for micro graphs, which is summed up in the following lemma. To uphold Invariant 4 we are not allowed to merge a vertex v'' to a vertex u'' in a micro graph $P_{i,j}$ if $v'' \in \Delta P_{i,j}$ and $u'' \notin \Delta P_{i,j}$, which we formulate explicitly.

► **Lemma 14.** *For all micro graphs $P_{i,j}$ we can provide (planarity preserving) free assignment merges for each $P_{i,j}$ such that no edges $\{u'', v''\}$ exists that should be managed by F or F_i . If such an edge would occur due to the merge, it is not inserted to $P_{i,j}$ and instead returned. Computing any number of such merges among all micro graphs can be done in $O(n)$ total time. The operation upholds the micro graph-responsibility. Merging a vertex v'' to a vertex u'' is not allowed if $v'' \notin \Delta P_{i,j}$ and $u'' \in \Delta P_{i,j}$. All other (planar preserving) merges are allowed.*

Proof. In this proof we discuss how to uphold Invariant 3.c regarding micro graphs, i.e., the micro graph responsibility. Denote with u'', v'' the two vertices we want to merge in micro graph $P_{i,j}$, with u' and v' the mini labels of u'' and v'' in P_i , respectively. W.l.o.g., assume we want to merge v'' to u'' . Recall from Section 5 that the vertices in micro graphs are assigned colors $\mathcal{C} = \{\text{simple}, \text{global-boundary}, \text{mini-boundary}, \text{double-boundary}\}$ and that we are able to iterate over all neighbors of a given color in constant time per element via the color-filtered neighborhood operation. As a refresher, we outline the meaning of the coloring again. Let u'' be a vertex in $P_{i,j}$. Denote with u' the mini label of u'' in P_i and with u the global label of u' in G . The vertex u'' is colored **simple** exactly if $u' \notin \delta P_i$ and $u \notin \delta G$. It is colored **global-boundary** exactly if $u' \notin \delta P_i$ and $u \in \delta G$. It is colored **mini-boundary** exactly if $u' \in \delta P_i$ and $u \notin \delta G$. Finally, it is colored **double-boundary** if it $u' \in \delta P_i$ and $u \in \delta G$. Due to Invariant 3 we know that all edges that should be managed by $P_{i,j}$ must not be managed by F_i or F . We denote a pair of vertices for which no edge is allowed to exist in $P_{i,j}$ as *forbidden edges*. We can categorize forbidden edges $\{u'', v''\}$ of $P_{i,j}$ by the coloring of u'' and v'' . The following combinations form a forbidden edge: (1) u'' is colored **double-boundary** and v'' is colored with any $c' \in \mathcal{C} \setminus \{\text{simple}\}$ (or vice-versa) or (2) both u'' and v'' are colored with the same color $c \in \mathcal{C} \setminus \{\text{simple}\}$. Note that this excludes pairs of vertices for which u'' is colored **mini-boundary** and v'' is colored **global-boundary** (or vice-versa), as clearly such an edge can not exist in either F_i or F . We denote the set of all forbidden edges that exist in $P_{i,j}$ as actual edges with $E_{i,j}^f$.

To merge two vertices $u'', v'' \in V(P_{i,j})$ we first merge them using the merge operation provided for micro graphs due to Theorem 8. Assume we merged v'' to u'' . Note that before this merge it holds that $E_{i,j}^f = \emptyset$ (Invariant 3) and after the merge it holds that $E_{i,j}^f = E_{i,j}^f \cap N(u'')$, i.e., all forbidden edges that now exist as actual edges are contained in the neighborhood of u'' . Iterating over these forbidden edges in constant time per element can thus be reduced to a constant number of color-filtered neighborhood operations executed

for u'' . We use this to store $E_{i,j}^f$ in a list L followed by removing $E_{i,j}^f$ from the graph using the batch edge-deletion operation. Afterwards we return the list L as outlined in the lemma.

We now discuss the runtime, for which we do a runtime analysis. Recall that we merge v'' to u'' by setting $N(u'') := (N(u'') \cup N(v'')) \setminus \{\{v'', u''\}\}$. This means that we can view such a merge as changing one endpoint each of all edges incident to v'' to become incident to u'' instead. Self-loops and parallel edges are discarded during this process. Note that each edge of $P_{i,j}$ can become a forbidden edge only once, since we remove all such edges that occur from $P_{i,j}$.

Due to the color-filtered neighborhood operation we only iterate over edges we insert to L . Thus the time to build all lists L in one $P_{i,j}$ is bound by $O(|V(P_{i,j})|)$. Over all $P_{i,j}$ this sums up to $O(n)$ time among all $P_{i,j}$. ◀

We now describe merges in mini graphs P_i and how these merges uphold their respective responsibilities, the latter is described in the next paragraph. We first note, whenever we call the merge operation of Lemma 14 for a micro graph $P_{i,j}$ in the next paragraphs, the operation returns edges $\{u'', v''\}$ that should be managed by F_i or F , but not $P_{i,j}$. We then translate $\{u'', v''\}$ to $\{u', v'\}$ with u' and v' the respective mini labels of u'' and v'' . If the edge $\{u', v'\}$ should be managed by F_i , we insert it to F_i . Returned edges that should not be managed by F_i are instead returned after the merge operation in P_i is executed. This upholds Invariant 3 (restricted to micro and mini graphs). To uphold Invariant 1 (for mini graphs) we check, after any call to a merge of a vertex v'' to u'' in a micro graph $P_{i,j}$ if the degree of u'' changed from 0 to non-zero or vice-versa. If it does, we must possibly update the mapping $\Phi_i^{>0}(u')$ to either include the tuple (j, u'') or remove it, with u' the mini label of u'' . Note that this is only done in the case that u' is a boundary vertex, as otherwise no mapping $\Phi_i^{>0}(u')$ exists. The technical details regarding guaranteeing Invariants 1 and 3 is discussed in the proof of Lemma 16. For now, we assume the necessary steps are executed during merges.

Let $u', v' \in V(P_i)$ be two vertices identified by their external mini label. To provide a merge of u' and v' we distinguish between three cases: (M1) $u', v' \notin \delta P_i$, (M2) $u' \in \delta P_i$ and $v' \notin \delta P_i$ and (M3) $u', v' \in \delta P_i$. In Case M1 we determine the micro graph $P_{i,j}$ that contains micro labels u'' and v'' of u' and v' , respectively, via the static mappings $\phi_i(u') = (j, u'')$ and $\phi_i(v') = (j, v'')$ as per Invariant 2. In $P_{i,j}$ we merge v'' to u'' exactly if v' should be merged to u' , and otherwise merge u'' to v'' (Lemma 14). By this congruent choice of merge we uphold Invariant 2.c without having to modify any mappings. Since the merged vertex remains a non-boundary vertex, Invariant 4 is guaranteed. This concludes all responsibilities of merges in mini graphs. All operations take constant time. Note that all merges of Case M1 are free-assignment merges.

Denote with $u^* = \mathbf{internal}[u']$ and $v^* = \mathbf{internal}[v']$ the internal mini labels of v' and u' respectively. For Case M2 we are forced to merge v^* to u^* to uphold Invariant 4, i.e., internally this merge is not a free-assignment merge. To execute the merge we determine the micro graph $P_{i,j}$ containing the micro label v'' of v^* via $\phi_i(v^*) = (j, v'')$. In $P_{i,j}$ we merge v'' to u'' (Lemma 14) with u'' the micro label of u^* in $P_{i,j}$. Note that merging u'' to v'' is not allowed. We determine u'' via an operation we call *micro-label search procedure*, which searches for u'' by iterating over all $x'' \in N(v'') \cap \Delta P_{i,j}$ (the neighbors of v'' that are duplicates) and testing if $\Phi_{i,j}^{-1}(x'') = u^*$. If this is the case, we have found the duplicate $u'' := x''$ of u^* . Note that this operation can fail, as u'' and v'' are not guaranteed to be adjacent. In this *special case*, we instead iterate over all $x'' \in \Delta P_{i,j}$. A key characteristic to get a good runtime is that the special case only occurs if the edges $\{u, v\}$ exists in F , with u and v the global labels of u' and v' , respectively, which allows us to upperbound the number

of encountered special cases by $|E(F)| = O(n/\log^2 n)$.

► **Lemma 15.** *All executions of the micro-label search procedure are processed in $O(n)$ time over any number of vertex merges of Case M2 in all P_i .*

Proof. Let $u' \in \delta P_i$ and $v' \notin \delta P_i$ for some mini graph P_i and assume that we want to merge v' to u' . As sketched, we determine the micro graph $P_{i,j}$ and the micro label v'' of v' therein with $(j, v'') = \phi_i(v')$. Denote with u'' the micro label of u' in $P_{i,j}$, which we are yet to determine. In the following if we say we *check* if a vertex $x'' \in \Delta P_{i,j}$ is the micro label of u' by testing if $\Phi_{i,j}^{-1}(x'')$ equals u' , in which case we found the micro label u'' of u' . Clearly a single check takes $O(1)$ time. We analyze the runtime of the micro label search procedure in two cases: (1) $u'' \in N(v'')$ and (2) $u'' \notin N(v'')$. We always assume that Case 1 is true, and if it then turns out to be false, we fall back to Case 2. In Case 1 we proceed as follows: iterate over all elements $x'' \in N(v'') \cap \Delta P_{i,j}$ via the color-filtered neighborhood operation (Section 5) and check if $\phi_{i,j}^{-1}(x'') = u'$, in which case we have found the micro label $u'' := x''$ of u' . If this search procedure was successful, we are done, otherwise continue to Case 2 and simply check all $x'' \in \Delta P_i$ in the same fashion, i.e., finding the x'' for which $\phi_{i,j}^{-1}(x'') = u'$ holds. We first analyze the runtime of Case 1. All $x'' \in N(v'') \cap \Delta P_{i,j}$ constitute edges $\{v'', x''\}$ that after the merge constitute edges $\{u'', x''\}$ that are being discarded in $P_{i,j}$, and then managed by F_i . Thus, any edge in each $P_{i,j}$ participates in such a search procedure at most once and the total cost of searches of Case 1 is bounded by $O(n)$.

As for Case 2, we only enter it exactly if we failed our search in Case 1. As we call the merge operation in a micro graph only as a sub-routine when contracting some edge $\{u, v\}$ in the global graph, this edge must be managed by either F , some F_i or $P_{i,j}$ (Invariant 3). As we enter Case 2, we know it is not managed by $P_{i,j}$ (otherwise we would have found it during Case 1). As we enter the micro-label search procedure only during case M2, i.e., when merging a non-boundary v' to a boundary u' in P_i , we know the edge can not be managed by F_i . This means the edge must be managed by F (as $\{u, v\}$). We can therefore bound the number of times we enter Case 2 via the number of possible edge contractions executed on edges that are managed by F —which is $O(n/\log^2 n)$. Any time we contract such an edge $\{u, v\} \in F$ we may iterate over all mini graphs P_i that contain a duplicate v' of v and a duplicate u' of u , where we then merge v' to u' (or vice-versa) for which the specified micro-label search procedure is executed as a subroutine in exactly one micro graph $P_{i,j}$. As the total number of duplicates among mini graphs is $O(n/\log^2 n)$, the number of such search procedures is $O(n/\log^2 n)$ as well. One run of such a search procedure can be done in $O(|V(P_{i,j})|) = O(\log^4 \log^4 n)$ time. This results in a total runtime of $o(n)$ over all micro label search procedures. ◀

Once the merge is executed in $P_{i,j}$ we must possibly update the mappings that translate between the internal and external mini labels. Recall that the mappings **internal** and **external** are only available for vertices of $\delta P_i \cup \Delta P_i$. In the case that $v' \in \delta P_i \cup \Delta P_i$ we are able to provide a free assignment merge as follows: if the request was to merge u' to v' , we set **internal** $[v'] = u^*$ and **external** $[u^*] = v'$. Otherwise, no update is necessary. If $v' \notin \delta P_i \cup \Delta P_i$ we are not able to provide a free assignment merge, instead we are forced to merge v' to u' . We refer to this situation as the *M2 special case*. If the merge was called with the request to merge u' to v' , and we are in this M2 special case, the operation is not allowed. When we discuss edge contractions of edges $\{u, v\}$ in G we show that this situation never arises.

As for Invariant 2.c, it is easy to see that it is still correct as we have merged v'' to u'' and v^* to u^* so that we do not need to update mappings $\Phi_i(u^*)$ and $\Phi_{i,j}^{-1}(u'')$. Our (possible)

updates to the internal/external mappings uphold Invariant 2.b, and our exclusion of the invalid request for a free-assignment merge ensures that this can always be done if needed. Besides the micro-label search procedure, all other operations take constant time per merge.

Finally, we consider Case M3. In this case both u' and v' are boundary vertices with $u^* = \text{internal}[u']$ and $v^* = \text{internal}[v']$ being the internal mini labels of v' and u' respectively. As sketched in Section 2, our intuition for merging v' to u' is that we first merge all v'' to u'' in all micro graphs $P_{i,j}$ that contain both a duplicate u'' of u^* and v'' of v^* . Secondly, for all micro graphs $P_{i,j}$ that contain only a duplicate v'' of v^* , but not of u^* , we update the mappings $\Phi_{i,j}^{-1}(v'') := u^*$ and insert (i, v'') to $\Phi_i(u^*)$. Finally, we merge v^* to u^* in F_i . To describe the realization technically we introduce some additional notation. Denote with $Z_i^{u^* \cap v^*}$ the set of all triples (j, u'', v'') with $(j, u'') \in \Phi_i(u^*)$ and $(j, v'') \in \Phi_i(v^*)$, with $Z_i^{u^* \setminus v^*}$ the set of all tuples (j, u'') with $(j, u'') \in \Phi_i(u^*)$ such that no tuple (j, \cdot) is contained in $\Phi_i(v^*)$, and with $Z_i^{u^* \oplus v^*}$ all tuples $(j, u'') \in \Phi_i(u^*)$ together with all tuples $(j', v'') \in \Phi_i(v^*)$ for which it holds that no tuple (j', \cdot) exists in $\Phi_i(u^*)$. To execute a merge of v^* to u^* in P_i , first iterate over all triples $(j, u'', v'') \in Z_i^{u^* \cap v^*}$ and merge v'' to u'' in $P_{i,j}$, then iterate over all tuples $(j, v'') \in Z_i^{v^* \setminus u^*}$ and update all mappings $\Phi_{i,j}^{-1}(v'') := u^*$. Finally, set $\Phi_i(u^*) := Z_i^{u^* \oplus v^*}$ and merge v^* to u^* in F_i .

As mentioned in the previous section, each Φ_i is implemented as a graph H_i using the forbidden vertex data structure (Lemma 4) such that for all $u \in \delta P_i$, the auxiliary data stored at edges incident to u in H_i make up the set $\Phi_i(u)$, with each edge corresponding to exactly one entry in $\Phi_i(u)$. Computing the previously defined sets and updating the mappings is done automatically when merging v^* to u^* in H_i : Setting $\Phi_i(u^*) := Z_i^{u^* \oplus v^*}$ is exactly the merge of v^* to u^* in H_i . The sets $Z_i^{v^* \setminus u^*}$ are exactly the edges that are inserted to $N(u^*)$ in H_i due to the merge, and the set $Z_i^{u^* \cap v^*}$ is exactly the set of parallel edges that are being discarded. All these sets are output due to a merge of u^* and v^* in H_i , as outlined in Section 3. Even though both H_i and F_i provide free assignment merges, we are forced to merge v^* to u^* exactly if $|\Phi_i(u^*)| > |\Phi_i(v^*)|$, as otherwise we are not able to achieve our runtime goal of $O(n)$ time, with the bottleneck being the computation and iteration over the set $Z_i^{v^* \setminus u^*}$. Since we have the mappings `internal/external` and merges in F_i are always free assignment, this causes no problems for us. We simply update the mappings `internal` and `external` for u^* , v^* and u' , v' analogous to Case M2, ensuring that the merge of u' and v' is a free assignment merge as well. Thus, Invariant 2.b holds. Invariant 2.c is managed by the update of $\Phi_i(u^*)$, which correctly inserts all needed values due to merging of v^* to u^* in H_i . Regarding Invariant 4, as we merge two boundary vertices the vertex that remains after the merge is still a boundary vertex. Denote with n_i the number of vertices in H_i . Due to the use of Lemma 4 for H_i , any number of merges in H_i can be processed in $O(n_i \log^2 n_i)$ time. Computing and iterating over all elements of the sets $Z_i^{u^* \cap v^*}$, $Z_i^{v^* \setminus u^*}$, and computing the sets $Z_i^{u^* \oplus v^*}$ due to any number of merges of Case M3 can be done in $O(n_i \log^2 n_i)$ time as well. For each element in the computed sets, a constant number of operations are executed resulting in $O(|E(H_i)|) = O(n_i)$ time. Over all H_i this sums up to a total runtime of $O(n)$. What we have yet to address is updating the mapping $\Phi_i^{>0}(u^*)$, which is done by simply merging v^* to u^* in $H_i^{>0}$, with the same runtime as merging v^* to u^* in H_i .

Combining Cases M1, M2 and M3 we are able to show that any number of merges in mini graphs can be processed in $O(n)$ time while upholding their responsibilities.

► **Lemma 16.** *All (planarity preserving) vertex merges in all mini graphs P_i are processed in $O(n)$ time and uphold their responsibilities. Edges that would occur due to a merge in P_i , but should be managed by F are returned. All merges excluding the M2 special case are free*

assignment merges.

Proof. In this proof we discuss how merges in a mini graph uphold Invariant 1 and 3. We first discuss Invariant 3. Denote with $u', v' \in V(P_i)$ two vertices that should be merged, and assume that v' is merged to u' . Denote with u'' and v'' the micro labels in a micro graph $P_{i,j}$ of u' and v' , respectively.

Any time a merge of u'' and v'' in some $P_{i,j}$ is executed as a sub-routine, all edges $\{x'', y''\}$ that should not be managed by $P_{i,j}$ are returned, with $x'', y'' \in P_{i,j}$. Using the label translation mappings $\phi_{i,j}^{-1}$ or $\Phi_{i,j}^{-1}$ we translate x'', y'' to their respective mini labels x' and y' . If $x', y' \in V(F_i)$ we first check if the edge $\{x', y'\} \in E(F_i)$. If this is not the case, we insert the edge. If one of x' or y' is not contained in $V(F_i)$ we know that the edge $\{x', y'\}$ should be managed by F . For this, we add all such $\{x', y'\}$ to a list L which we return after the merge of v' to u' is executed. To analyze the runtime, note that in total there are at most $O(n)$ edges returned due to merges in micro graphs. This is due to the fact that all merges in micro graphs can be done in $O(n)$ time, which includes returning the aforementioned edges (Lemma 14). For each such returned edge we first spend $O(1)$ time to translate its endpoints to their respective mini labels, and then $O(1)$ time to check if this edge is contained in F_i (constant time adjacency queries are provided due to Lemma 4). We only call the insertion operation if this is not the case. The runtime of an insertion is logarithmic. Adding the edge to L if it should not be managed by F_i takes $O(1)$ time. As each F_i is planar, at most a linear number of edges can be inserted to F_i due to this, i.e., $O(\log^4 n / \log^2 \log^4 n)$ edges can be inserted to each F_i . Each insert takes logarithmic time, resulting in a total runtime of $O(n / \log^4 n \cdot \log^4 n / \log^2 \log^4 n \cdot \log \log^4 n) = O(n)$ over all P_i and F_i respectively.

We now discuss how to uphold Invariant 1. Let $u' \in V(F)$ and $(j, u'') \in \Phi_i^{>0}$. We first analyze the situations in which the degree of u'' switches between zero and non-zero.. First note that no merge of two vertices $a'', b'' \notin \Delta P_{i,j}$ can result in the degree of u'' to change (i.e., Case M1). Secondly, in the case we merge a vertex $v' \in V(F)$ to u' (i.e., case M3), we know that the Invariant 1 is upheld without any extra operations as u' is merged into v' in $H_i^{>0}$ to update $\Phi_i^{>0}(u')$. After this merge, tuples (j, u'') that are inserted to $\Phi_i^{>0}(u')$ indicate that u' had no duplicate u'' with degree > 0 in $P_{i,j}$ before the merge. Thus, we are only interested in Case M2, where we merge a non-boundary vertex $v' \notin V(F)$ to u' , and therefore merge the mini-label v'' of v' to u'' in $P_{i,j}$. Recall that in Case M2 we apply the micro-label search operation as a sub-routine to determine the micro label u'' of u' . This routine first searches for u'' in the neighborhood of v'' in $P_{i,j}$, described as Case 1. We first view this case, i.e., the edge $\{u'', v''\}$ exists. In this case, the degree of u'' is > 0 before the merge by assumption and the degree of u'' can become 0 when $\{u'', v''\}$ is the only edge incident to u'' , and the (possibly empty) set of edges incident to v'' are discarded during the merge to uphold Invariant 1. Let us now view Case 2, i.e., edge $\{u'', v''\}$ does not exist. In the proof of Lemma 15 it was shown that in Case 2 the edge $\{u, v\}$ (with u and v the global labels of u' and v') must be managed by F (as $\{u, v\}$) and therefore Case 2 occurs $O(n / \log n)$ times over any number of merges in any number of micro graphs $P_{i,j}$. Let us assume the worst case, i.e., every time we are in Case 2 the degree of u'' changes in $P_{i,j}$. Each time we must update $\Phi_i^{>0}(u')$. We therefore know that at most $O(n / \log^2 n)$ such swaps can occur total. In Case 1 the degree can only change from non-zero to zero, but no vice-versa. We can therefore bound this by $O(n / \log^2 n + n / \log^2 \log^4 n)$ total. Each update takes $O(\log \log^4 n)$ time, and we arrive at a total runtime of $o(n)$. ◀

Contracting edges $\{u, v\}$ in G effectively works exactly as the vertex merges in mini graphs P_i , with the exception that we do not need to maintain the translation between

internal and external labels and we do not need to provide free assignment merges for any case. We again distinguish between three cases: (G1) $u, v \notin \delta G$, (G2) $u \in \delta G$ and $v \notin \delta G$ and (G3) $u, v \in \delta G$. For Case G2 we employ a procedure we call *mini-label search procedure*, analogous to the micro-label search procedure for Case M2. The proof of Lemma 17 shows that the M2 special case for merges in mini graphs never occurs. The following lemma summarizes the edge contraction operation in G .

► **Lemma 17.** *After $O(n)$ initialization time, any number of edge contractions in G can be computed in $O(n)$ time and uphold the mini-graph responsibility.*

Proof. Contraction of an edge $\{u, v\} \in E$ works mostly analogous to a merge of two vertices $u', v' \in V(P_i)$ with P_i some mini graph. We give a quick overview of the three cases, mentioning the differences between the analogous cases in mini graphs and how we avoid the forbidden M2 special case, outlined in Section 7.

Case G1. In Case G1 we determine the mini graph P_i that contains (external) mini labels of u and v , respectively. This is done via $\phi(u) = (i, u')$ and $\phi(v) = (i, v')$. In P_i we contract u' and v' , with the choice of which vertex to merge to which being determined by constraints in P_i : simply put, we have no preferences, and can therefore easily avoid the forbidden M2 special case.

Case G2. In Case G2 we merge a non-boundary vertex $v \notin \delta G$ to a boundary vertex $u \in \delta G$. We therefore require to merge v to u (Invariant 4). We determine the mini graph P_i and the mini label v' of v with $\phi(v) = (i, v')$. We then must determine the mini label u' of u in P_i with an operation previously described as mini-label search procedure, described in the next paragraph. Assuming we have determined u' , we then simply merge v' to u' in P_i . In the case that $v' \in \delta P_i$, this is a free assignment merge. In the case that $v' \notin \delta P_i$, we are either free to merge v' to u' , or are forced to merge v' to u' due to constraints in P_i . Thus, we are able to avoid the forbidden M2 special case.

We now discuss the mini-label search procedure needed to determine u' . Intuitively, this works analogous to the micro-label search procedure, i.e., we simply search in the neighborhood of v' for u' . There is a key difference to the micro-label search procedure: u' is guaranteed to be in $N(v')$ in P_i , as the edge $\{u, v\}$ is not contained in F . To determine u' we iterate over all $x' \in N(v') \cap \Delta P_i$ and test with $\Phi_i^{-1}(x') = x$ if $x = u$. If this is the case, we have found $u' = x'$. We discuss the technical realization of iterating over $N(v') \cap \Delta P_i$ in the next paragraph. Under the assumption this iteration takes constant time per element the runtime analysis works exactly as the runtime analysis in the proof of Lemma 15. Each edge iterated during this procedure is removed afterwards during the merge process (these edges constitute edges that after the merge become edges managed by F), i.e., each edge is output due to this process only once, resulting in a runtime of $O(n)$ total.

We now describe the technical implementation of this procedure. We need additional data structures to implement iteration over $N(v') \cap \Delta P_i$ as we need to avoid iterating over neighbors of v' that are not in ΔP_i , as otherwise our runtime goal of $O(n)$ can not be upheld. First, we distinguish between two cases: (1) $v' \notin \delta P_i$ and (2) $v' \in \delta P_i$. In Case 1 we simply determine the micro graph $P_{i,j}$ that contains a micro label v'' of v' with $(j, v'') = \phi_i(v')$. We then iterate over all neighbors of v'' in $P_{i,j}$ that are colored **boundary** or **double-boundary**, which are exactly micro labels of vertices in ΔP_i . We translate all such neighbors x'' to mini-labels x' in P_i via $\Phi_{i,j}^{-1}$ or $\phi_{i,j}^{-1}$, depending on the color of x'' . This exactly gives us all neighbors $x' \in N(v') \cap \Delta P_i$. For Case 2 we construct additional data structures that avoids unnecessary iteration over vertices in $N(v') \setminus \Delta P_i$. For this we initially (i.e., before any contractions are processed in G) construct for each F_i a subgraph F'_i that contains all vertices of F_i , but only edges $\{a', b'\} \in E(F_i)$ with $b' \in \Delta P_i$ (and $a' \in V(F_i)$). Then, for

all $a' \in V(F_i)$ we construct sets $\Phi'_i(a') \subseteq \Phi_i(a')$ which contain all tuples $(j, a'') \in \Phi_i(a')$ such that a'' has neighbors of color **boundary** or **double-boundary** in $P_{i,j}$. Using these data structures we can simply implement the desired mini-label search operation by iterating over neighbors of v' in F'_i and then iterating over all $(j, v'') \in \Phi'_i(v')$. We maintain F'_i by simply merging two vertices in F'_i exactly when we merge two vertices in F_i , and adding edges to F'_i exactly when edges are added to F_i (and the edges should be contained in F'_i). To maintain the sets Φ'_i we construct subgraphs H'_i of H_i that maintain exactly these sets. We maintain an analogous invariant to Invariant 1 for the sets Φ'_i , i.e., for all $(j, a'') \in \Phi'_i(a')$ for all $a' \in V(F_i)$ it holds that a'' has neighbors colored **boundary** or **double-boundary** in $P_{i,j}$. Guaranteeing this modified invariant for all Φ'_i works exactly as Invariant 3 for all $\Phi_i^{>0}$, shown in the proof of Lemma 16. Managing all F'_i works exactly as managing all F_i . In summary, maintaining these additional data structures requires $O(n)$ time over any number of edge contractions.

Case G3. In case G3 both u and v are boundary vertices. This case works effectively the same as case M3 in mini graphs. We first iterate over all $(i, u', v') \in Z^{u \cap v}$ where we merge v' to u' . Note that all these merges are free assignment merge in $P_{i,j}$ as $u', v' \in \Delta P_i$ for which the mappings **internal/external** are available. We define sets $Z^{v \setminus u}, Z^{v \setminus u} \oplus Z^{u \oplus v}$ analogous to the definitions of sets $Z_i^{v^* \setminus u^*}, Z_i^{v^* \setminus u^*} \oplus Z_i^{v^* \oplus u^*}$ used in case M3 for merges of two mini-labels u^*, v^* in mini graphs P_i .

We then iterate over all $(i, v') \in Z^{v \setminus u}$ and set all mappings $\Phi_i^{-1}(v') := u'$. Finally, we set $\Phi(u') := Z^{u \oplus v}$ and update $\Phi^{>0}(u')$ analogously. The algorithmic realization of this works exactly as in case M3 in mini graphs, i.e., the computation of these sets (and updates to $\Phi(u')/\Phi^{>0}(u')$) is realized via a merge of u and v in the graph H and $H^{>0}$. To maintain a runtime of $O(n)$ over any number of edge contractions we merge v to u exactly if $|\Phi_i(u)| > |\Phi_i(v)|$, analogous to case M3. Clearly any number of such edge contractions can be processed in $O(n)$ time in F, H and $H^{>0}$, and the runtime of merges in all P_i is already stated in Lemma 16.

This concludes all three cases, with each case taking $O(n)$ total time for contractions. It remains to show how the global graph responsibility is upheld. Invariant 4 is simply upheld by always merging a non-boundary vertex to a boundary vertex in case G3, analogous to the same invariant regarding mini graphs. To uphold Invariant 3.a, recall that all merges in mini graphs P_i return a list L of edges that should be maintained by F that occurred due to a merge in P_i . We simply insert these edges to F if they are not yet contained in F , and ignore them otherwise. The number of edge insertions is $O(n/\log^2 n)$ with each insertion taking $O(\log n)$ time. To test if an edge is already contained in F we use the $O(1)$ time adjacency query operation provided by Lemma 4. As the runtime of returning all lists L due to merges in mini graphs is $O(n)$ time (Lemma 16), we arrive at $O(n)$ time to maintain Invariant 3. Maintaining Invariant 4 works analogously to maintaining the same invariant in mini graphs. After the contraction of an edge $\{u, v\}$ with $u \in \delta G$ and $v \notin \delta G$ (executed by contracting v' to u' , the respective mini labels of v' and u' in some P_i), we simply test if u' has neighbors in P_i . If this is not the case, we remove (i, u') from $\Phi(u')$. The runtime analysis works analogously to the runtime analysis in mini graphs for maintaining the same invariant, i.e., $O(n)$ time to maintain Invariant 1. Invariant 2.a is upheld by correctly updating the specified mappings during the contraction, again analogously to maintaining Invariant 2.c in mini graphs.

In summary: any number of edge contractions in G can be processed in $O(n)$ time and uphold the global graph responsibility. ◀

We additionally provide constant time degree queries. Intuitively, we store the degree

for boundary vertices (in G and each P_i) concretely, while for all other vertices Theorem 8 provides us with a degree query.

► **Lemma 18.** *After $O(n)$ initialization time the degree of any $u \in V$ can be queried in constant time.*

Proof. To maintain the degree of vertices $u \in \delta G$ store in an array Deg the degree of each such $u \in G$. Use an analogous array Deg_i for each P_i that stores the degree of $u' \in P_i$. For now assume these are correctly maintained. How this is done, is outlined in the next paragraph. To query the degree of a vertex $u \in \delta G$ simply output $\text{Deg}[u]$. To query the degree of a vertex $u \notin \delta G$ determine the mini graph P_i that contains the mini label u' of u via $(i, u') := \phi(u)$. Note that in this case all incident edges of u are incident to u' . In P_i query the degree of u' via $\text{Deg}_i[u']$ if $u' \in \delta P_i$, or otherwise determine the micro graph $P_{i,j}$ that contains the micro label u'' of u' via $(j, u'') := \phi_i(u')$ and execute the degree query with Theorem 8.

To initialize Deg and each Deg_i use the neighborhood iteration (Lemma 13) and simply count the number of neighbors. The degree of a vertex only changes if it is involved in a merge, i.e., when a vertex v is merged to u (or the analogous merges in mini and micro graphs). We only maintain the arrays Deg and Deg_i for boundary vertices, all other vertices are automatically handled via Theorem 8. We now describe how to maintain Deg_i , maintaining Deg then works analogously. Any time a vertex v' is merged to some $u' \in \Delta P_i$ we distinguish between two cases: (1) $v' \notin \delta P_i$ and $v' \in \delta P_i$. Recall that in Case 1 we merge v' to u' by merging v'' to u'' in $P_{i,j}$, with v'' and u'' the respective mini labels of v' and u' in $P_{i,j}$. To update $\text{Deg}_i[u']$ store in d_0 the degree of u'' in $P_{i,j}$ before the merge and in d_1 the degree of u'' in $P_{i,j}$ after the merge. Update $\text{Deg}_i[u'] := \text{Deg}_i[u'] + (d_1 - d_0)$. In Case 2 we first merge v' to u' in F_i , then secondly merge each v'' to u'' in all $P_{i,j}$ that contain both v'' and u'' (micro labels of u' and v' , respectively), and thirdly map each v'' to be the micro label of u' in all $P_{i,j}$ that contain only v'' , but not u'' . To update $\text{Deg}_i[u']$ first set $\text{Deg}_i[u'] := \text{Deg}_i[u'] + (d_1 - d_0)$, with d_0, d_1 the degree of u' in F before and after the merge, respectively. Secondly, for each $P_{i,j}$ where v'' is merged to u'' , update $\text{Deg}_i[u'] := \text{Deg}_i[u'] + (d_1 - d_0)$ with d_0, d_1 the degree of u'' in $P_{i,j}$ before and after the merge, respectively. Thirdly, for $P_{i,j}$ where v'' is remapped to be a micro label of u' , update $\text{Deg}_i[u'] := \text{Deg}_i[u'] + d$ with d the degree of v'' in $P_{i,j}$.

Each update to the arrays Deg and each Deg_i takes constant time for each entry. As we only update an entry in these arrays exactly when some other operation is also executed that relates to this entry, this is a negligible overhead. The number of bits used to store Deg is $O(n/\log^2 n \cdot \log n) = o(n)$ bits and for all Deg_i it is $O((n/\log^4 n) \cdot (\log^4 n/\log^2 \log^4 n) \cdot (\log \log n)) = o(n)$ bits. ◀

Using the same data structures we use for edge contractions, we can process any number of vertex deletions in $O(n)$ time. To delete a vertex u we delete all mini labels u' of u and all micro labels u'' of all u' . This mostly works analogously to the contraction algorithm.

► **Lemma 19.** *Any number of vertex deletions in G can be processed in $O(n)$ time and uphold the mini-graph responsibility.*

Proof. Let $u \in V$ be a vertex we want to delete. Denote with u' the mini label of u in the mini graph $P_{i,j}$ under consideration, and with u'' the micro label of u' in the micro graph $P_{i,j}$ under consideration. To delete u we distinguish between two cases: (1) $u \in \delta G$ and (2) $u \notin \delta G$. In Case 1 iterate over all $(i, u') \in \Phi(u)$ and delete u' in P_i (specified in the next paragraph). Then delete u in F , H and $H^{>0}$ by deleting all incident edges and adding a boolean flag to u that it is marked deleted. In Case 2 delete u' in P_i with $(i, u') := \phi(u)$.

To delete a vertex u' in a mini graph P_i we distinguish between analogous two cases: (1) $u' \in \delta P_i$ and (2) $u' \notin \delta P_i$. In Case 1 iterate over all $(j, u'') \in \Phi_i(u')$ and delete u'' in $P_{i,j}$ (specified in the next paragraph). Then delete u' in F_i , H_i and $H_i^{>0}$ by deleting all incident edges and by storing a boolean flag for u indicating that it is marked deleted. In Case 2 delete u'' in $P_{i,j}$ with $(j, u'') := \phi_i(u)$.

All boolean flags mentioned above can be stored in a simple bit vector of length $|V(F)| + \sum_i |V(F_i)| = o(n)$.

To delete vertices u'' in micro graphs $P_{i,j}$ use the batch edge deletion of Theorem 8 by deleting all incident edges (in constant time). Afterwards mark u'' as deleted in $P_{i,j}$, analogous to the same process when merging two vertices in $P_{i,j}$ (Section 4). ◀

We are now able to proof Theorem 1.

► **Theorem 1.** *Let $\mathcal{H}(n)$ be the entropy of encoding a planar graph with n vertices and G an unlabeled simple n -vertex planar graph. There exists an encoding of G that provides induced-minor operations (i.e., vertex deletions and edge contractions) with the following properties: The encoding requires $O(n)$ time to execute any number of induced-minor operations and provides neighborhood and degree operations in constant time (per element). Storing the encoding requires $\mathcal{H}(n) + o(n)$ bits and initializing the encoding can be done in $O(n)$ time with $O(n)$ bits.*

Proof. Construct the dynamic encoding due to Corollary 12. Lemma 13 gives us the desired neighborhood operation and Lemma 18 the desired degree operation, Lemma 17 the desired contraction operation and Lemma 19 the desired vertex deletions. ◀

Using hash tables to implement the mappings Φ , $\Phi^{>0}$, Φ_i and $\Phi_i^{>0}$ we are able to provide expected constant time adjacency queries and is able to process any number of edge deletions in $O(n)$ expected time. Holm et al. used the same argument of replacing a mapping data structure with a hash table to show Lemma 5.15 in their work [12].

► **Corollary 2.** *The encoding of Theorem 1 can be extended to provide expected $O(1)$ time adjacency queries and process any number of minor operations in expected $O(n)$ time.*

Proof. Assume Φ , $\Phi^{>0}$, Φ_i and $\Phi_i^{>0}$ are implemented as hash tables [12, Lemma 5.15], i.e., we can determine for any $u \in \delta G$ the mini label u' in some P_i (if it exists) in expected constant time. Let $u, v \in V$ be two vertices for which we want test adjacency. Denote with u', v' their respective mini labels in some mini graph P_i and with u'', v'' their respective micro labels in some micro graph $P_{i,j}$. By Invariant 3, if the edge $\{u, v\}$ exists, is either managed (1) by F , (2) by some F_i (as edge $\{u', v'\}$) or by $P_{i,j}$ (as edge $\{u'', v''\}$). Case 1 occurs exactly if both u and v are boundary vertices, i.e., a simple adjacency query in F suffices to answer the query. In Case 2, one of (or both) u and v are not contained in δG . Assume $v \notin \delta G$. We then determine the mini graph P_i that contains v' and u' via $(i, v') = \phi_v$, we then determine u' either via $\phi(u)$ or $\Phi(u)$ in expected constant time. If both $u', v' \in \delta P_i$ we can query their adjacency in F_i . Otherwise determine the micro graph $P_{i,j}$ analogous to determining the mini graph in Case 2, where we then query the adjacency of u'' and v'' . Effectively, we are able to find in expected constant time the structure (F , some F_i or some $P_{i,j}$) that manages the edge $\{u, v\}$ (with the respective mini/micro labels of u and v as the endpoints), if it exists.

To delete an edge, first use the adjacency query to find the edge in F , F_i or $P_{i,j}$. Subsequently delete the edge there. Deleting all edges in F can be done in $O((n/\log^2 n) \cdot$

$\log n = o(n)$ time, deleting all edges in all F_i can be done in $O((n/\log^4 n) \cdot (\log^4 / \log^2 \log^4 n) \cdot (\log \log^4 n)) = o(n)$ time, and deleting all edges in all $P_{i,j}$ can be done in $O(n)$ time. ◀



References

- 1 Joyce Bacic, Saeed Mehrabi, and Michiel Smid. Shortest Beer Path Queries in Outerplanar Graphs. In *32nd International Symposium on Algorithms and Computation (ISAAC 2021)*, volume 212 of *Leibniz International Proceedings in Informatics (LIPIcs)*, pages 62:1–62:16. Schloss Dagstuhl – Leibniz-Zentrum für Informatik, 2021. doi:10.4230/LIPIcs.ISAAC.2021.62.
- 2 Daniel K. Blandford, Guy E. Blelloch, and Ian A. Kash. Compact representations of separable graphs. In *Proceedings of the Fourteenth Annual ACM-SIAM Symposium on Discrete Algorithms*, SODA '03, page 679–688, USA, 2003. Society for Industrial and Applied Mathematics. doi:https://doi.org/10.5555/644108.644219.
- 3 Guy E. Blelloch and Arash Farzan. Succinct representations of separable graphs. In Amihood Amir and Laxmi Parida, editors, *Combinatorial Pattern Matching*, pages 138–150. Springer Berlin Heidelberg, 2010.
- 4 Gerth Stølting Brodal and Rolf Fagerberg. Dynamic representations of sparse graphs. In *In Proc. 6th International Workshop on Algorithms and Data Structures (WADS 99)*, pages 342–351. Springer-Verlag, 1999.
- 5 Yi-Ting Chiang, Ching-Chi Lin, and Hsueh-I Lu. Orderly spanning trees with applications to graph encoding and graph drawing. In *Proceedings of the Twelfth Annual ACM-SIAM Symposium on Discrete Algorithms*, SODA '01, page 506–515. Society for Industrial and Applied Mathematics, 2001.
- 6 Jack Edmonds. Paths, trees, and flowers. *Canadian Journal of Mathematics*, 17:449–467, 1965. doi:10.4153/CJM-1965-045-4.
- 7 Amr Elmasry, Torben Hagerup, and Frank Kammer. Space-efficient Basic Graph Algorithms. In *32nd International Symposium on Theoretical Aspects of Computer Science (STACS 2015)*, volume 30 of *Leibniz International Proceedings in Informatics (LIPIcs)*, pages 288–301. Schloss Dagstuhl–Leibniz-Zentrum für Informatik, 2015. doi:10.4230/LIPIcs.STACS.2015.288.
- 8 Amr Elmasry and Frank Kammer. Space-efficient plane-sweep algorithms. In *27th International Symposium on Algorithms and Computation, ISAAC 2016*, volume 64 of *LIPIcs*, pages 30:1–30:13. Schloss Dagstuhl – Leibniz-Zentrum für Informatik, 2016. doi:10.4230/LIPIcs.ISAAC.2016.30.
- 9 Volodymyr Floreskul, Konstantin Tretyakov, and Marlon Dumas. Memory-efficient fast shortest path estimation in large social networks. *Proceedings of the International AAAI Conference on Web and Social Media*, 8:91–100, 2014. URL: <https://ojs.aaai.org/index.php/ICWSM/article/view/14532>.
- 10 Torben Hagerup. Space-efficient DFS and applications to connectivity problems: Simpler, leaner, faster. *Algorithmica*, 82(4):1033–1056, 2020. doi:10.1007/s00453-019-00629-x.
- 11 Xin He, Ming-Yang Kao, and Hsueh-I Lu. A fast general methodology for information-theoretically optimal encodings of graphs. *SIAM Journal on Computing*, 30(3):838–846, 2000. doi:10.1137/S0097539799359117.
- 12 Jacob Holm, Giuseppe F. Italiano, Adam Karczmarz, Jakub Lacki, Eva Rotenberg, and Piotr Sankowski. Contracting a Planar Graph Efficiently. In *25th Annual European Symposium on Algorithms (ESA 2017)*, volume 87 of *Leibniz International Proceedings in Informatics (LIPIcs)*, pages 50:1–50:15. Schloss Dagstuhl–Leibniz-Zentrum für Informatik, 2017. doi:10.4230/LIPIcs.ESA.2017.50.
- 13 Jacob Holm and Eva Rotenberg. Good r-Divisions Imply Optimal Amortized Decremental Biconnectivity. In Markus Bläser and Benjamin Monmege, editors, *38th International Symposium on Theoretical Aspects of Computer Science (STACS 2021)*, volume 187 of *Leibniz International Proceedings in Informatics (LIPIcs)*, pages 42:1–42:18. Schloss Dagstuhl – Leibniz-Zentrum für Informatik, 2021. doi:10.4230/LIPIcs.STACS.2021.42.
- 14 Frank Kammer and Johannes Meintrup. Space-Efficient Graph Coarsening with Applications to Succinct Planar Encodings. In *33rd International Symposium on Algorithms and Computation (ISAAC 2022)*, volume 248 of *Leibniz International Proceedings in Informatics (LIPIcs)*, pages

- 62:1–62:15. Schloss Dagstuhl – Leibniz-Zentrum für Informatik, 2022. doi:10.4230/LIPIcs.ISAAC.2022.62.
- 15 Frank Kammer, Johannes Meinrup, and Andrej Sajenko. Space-efficient vertex separators for treewidth. *Algorithmica*, 84(9):2414–2461, 2022. doi:10.1007/s00453-022-00967-3.
 - 16 David R. Karger. Global min-cuts in RNC, and other ramifications of a simple min-cut algorithm. In *Proceedings of the Fourth Annual ACM-SIAM Symposium on Discrete Algorithms, SODA '93*, page 21–30. Society for Industrial and Applied Mathematics, 1993.
 - 17 Kenneth Keeler and Jeffery Westbrook. Short encodings of planar graphs and maps. *Discrete Applied Mathematics*, 58(3):239–252, 1995. doi:https://doi.org/10.1016/0166-218X(93)E0150-W.
 - 18 Philip N. Klein and Shay Mozes. Optimization algorithms for planar graphs. 2017.
 - 19 Philip N. Klein, Shay Mozes, and Christian Sommer. Structured recursive separator decompositions for planar graphs in linear time. Association for Computing Machinery, 2013. doi:10.1145/2488608.2488672.
 - 20 J. Ian Munro and Venkatesh Raman. Succinct representation of balanced parentheses and static trees. *SIAM Journal on Computing*, 31(3):762–776, 2001. doi:10.1137/S0097539799364092.
 - 21 Rajeev Raman, Venkatesh Raman, and Srinivasa Rao Satti. Succinct indexable dictionaries with applications to encoding k-ary trees, prefix sums and multisets. *ACM Trans. Algorithms*, 3(4):43–es, nov 2007. doi:10.1145/1290672.1290680.
 - 22 Neil Robertson and Paul D. Seymour. Graph minors. XXII. irrelevant vertices in linkage problems. *J. Comb. Theory, Ser. B*, 102(2):530–563, 2012. doi:10.1016/j.jctb.2007.12.007.
 - 23 Ben Strasser, Dorothea Wagner, and Tim Zitz. Space-Efficient, Fast and Exact Routing in Time-Dependent Road Networks. In *28th Annual European Symposium on Algorithms (ESA 2020)*, volume 173 of *Leibniz International Proceedings in Informatics (LIPIcs)*, pages 81:1–81:14. Schloss Dagstuhl–Leibniz-Zentrum für Informatik, 2020. doi:10.4230/LIPIcs.ESA.2020.81.
 - 24 Hisao Tamaki. Positive-instance driven dynamic programming for treewidth. *J. Comb. Optim.*, 37(4):1283–1311, 2019. doi:10.1007/s10878-018-0353-z.
 - 25 György Turán. On the succinct representation of graphs. *Discret. Appl. Math.*, 8(3):289–294, 1984. doi:10.1016/0166-218X(84)90126-4.