

Deterministic Massively Parallel Symmetry Breaking for Sparse Graphs

Jeff Giliberti
ETH Zurich
jeff.giliberti@inf.ethz.ch

Manuela Fischer
ETH Zurich
manuela.fischer@inf.ethz.ch

Christoph Grunau*
ETH Zurich
cgrunau@inf.ethz.ch

Abstract

We consider the problem of designing deterministic graph algorithms for the model of Massively Parallel Computation (MPC) that improve with the sparsity of the input graph, as measured by the standard notion of arboricity. For the problems of maximal independent set (MIS), maximal matching (MM), and vertex coloring, we improve the state of the art as follows. Let λ denote the arboricity of the n -node input graph with maximum degree Δ .

MIS and MM: We develop a deterministic fully-scalable algorithm that reduces the maximum degree to $\text{poly}(\lambda)$ in $O(\log \log n)$ rounds, improving and simplifying the randomized $O(\log \log n)$ -round $\text{poly}(\max(\lambda, \log n))$ -degree reduction of Ghaffari, Grunau, Jin [DISC'20]. Our approach when combined with the state-of-the-art $O(\log \Delta + \log \log n)$ -round algorithm by Czumaj, Davies, Parter [SPAA'20, TALG'21] leads to an improved deterministic round complexity of $O(\log \lambda + \log \log n)$ for MIS and MM in low-space MPC.

The above MIS and MM algorithms however work in the setting where the global memory allowed, i.e., the number of machines times the local memory per machine, is superlinear in the input size. We extend them to obtain the first fully-scalable MIS and MM algorithms that work with linear global memory. Specifically, we show that both problems can be solved in deterministic time $O(\min(\log n, \log \lambda \cdot \log \log n))$, and even in $O(\log \log n)$ time for graphs with arboricity at most $\log^{O(1)} \log n$. In this setting, only a $O(\log^2 \log n)$ -running time bound for trees was known due to Latypov and Uitto [ArXiv'21].

Vertex Coloring: We present a $O(1)$ -round deterministic algorithm for the problem of $O(\lambda)$ -coloring in the linear-memory regime of MPC, with relaxed global memory of $n \cdot \text{poly}(\lambda)$. This matches the round complexity of the state-of-the-art randomized algorithm by Ghaffari and Sayyadi [ICALP'19] and significantly improves upon the deterministic $O(\lambda^\epsilon)$ -round algorithm by Barenboim and Khazanov [CSR'18]. Our algorithm solves the problem after just *one* single graph partitioning step, in contrast to the involved local coloring simulations of the above state-of-the-art algorithms. We also extend our algorithm to the CONGESTED-CLIQUE model of distributed computing for certain ranges of λ .

In linear-space MPC with linear global memory, we derive a $O(\log \lambda)$ -round algorithm by combining the constant-round $(\Delta + 1)$ -list-coloring algorithm by Czumaj, Davies, Parter [PODC'20, SIAM J. Comput.'21] with that of Barenboim and Khazanov.

*Supported by the European Research Council (ERC) under the European Unions Horizon 2020 research and innovation programme (grant agreement No. 853109).

1 Introduction

One of the most fundamental tasks in decentralized networks are symmetry breaking problems such as electing a set of leaders or resolving conflicts for the allocation of shared resources. In recent years, the ever-increasing amount of data rendered traditional graph algorithms inefficient, or even inapplicable. Inspired by popular large-scale computing frameworks such as MapReduce [DG08] and Spark [ZCF⁺10], the Massively Parallel Computation (MPC) model [FMS⁺10, KSV10] has emerged as a standard theoretical abstraction for the algorithmic study of large-scale graph processing.

In the sublinear and linear regime of MPC, there has recently been a plethora of work on fundamental combinatorial and optimization problems on graphs (see, e.g., [BKM20, BBD⁺19, BDE⁺19, CC22, CDP21b, CDP21c, GGK⁺18, GU19, KPP20]). As many real-world graphs are believed to be sparse, it would be desirable to develop algorithms that improve with the sparsity of graphs [CLM⁺18]. An established measure of sparsity is the *arboricity* λ of a graph: It captures a *global* notion of sparsity, as it does not impose any *local* constraints such as bounded maximum degree. Over the last decade, a series of *arboricity-dependent* algorithms [BE10, BE11, BEPS16, BK18, BFU19, GGJ20, GL17, GS19, LU21] has shown that for sparse graphs there exist far more efficient algorithms than for general graphs.

In this paper, we focus on the *deterministic* complexity of maximal independent set (MIS), maximal matching (MM), and vertex coloring, parameterized by the graph arboricity, although without imposing any upper bound on the value of λ .

The MPC Model: In the MPC model, the distributed network consists of \mathbf{M} machines with memory \mathbf{S} each. The input is distributed across the machines and the computation proceeds in synchronous rounds. In each round, each machine performs an arbitrary *local computation* and then communicates up to \mathbf{S} data with the other machines. All messages sent and received by each machine in each round have to fit into the machine’s local memory. The main complexity measure of an algorithm is its *round complexity*, that is, the number of rounds needed by the algorithm to solve the problem. Secondary complexity measures are the *global memory* usage—i.e., the number of machines times the local memory per machine—as well as the *total computation* required by the algorithm, i.e., the (asymptotic) sum of all local computation performed by each machine.

For the MIS and MM problems, we focus on the design of fully scalable graph algorithms in the *low-memory* MPC model (a.k.a. low-space MPC model), where each machine has strongly sublinear memory. More precisely, an input graph $G = (V, E)$ with n vertices and m edges is distributed arbitrarily across machines with local memory $\mathbf{S} = O(n^\alpha)$ each, for constant $0 < \alpha < 1$, so that the global space is $\mathbf{S}_{Global} = \Omega(n + m)$.

For vertex coloring, we consider the *linear-memory* MPC model, where machines have local memory $\mathbf{S} = O(n)$. This model is closely linked to the CONGESTED-CLIQUE model [LPSP05], where the communication graph is complete but the message size is restricted to $O(\log n)$ bits. By a result of Lenzen [Len13], linear MPC results can often be extended to CONGESTED-CLIQUE [BDH18].

Maximal Independent Set and Maximal Matching: These two problems have been studied extensively since the very beginning of the area [ABI86, BEPS16, Gha16, II86, Lub85] and are defined as follows. A *maximal independent set* is a set $\mathcal{I} \subseteq V$ such that no two vertices in \mathcal{I} are adjacent and every vertex $u \in V \setminus \mathcal{I}$ has a neighbor in \mathcal{I} . A *maximal matching* is a set $\mathcal{M} \subseteq E$ such that no two edges in \mathcal{M} are adjacent and every edge $e \in V \setminus \mathcal{M}$ has a neighbor in \mathcal{M} .

Randomized MIS and MM One of the recent highlights in low-memory MPC has been a sequence of fast algorithms for *bounded-arboricity graphs*. The authors in [BFU19] were the first to break the linear memory barrier devising an $O(\log^3 \log n)$ -time algorithm for trees. This result was improved by [BBD⁺19] who gave a general $O(\log^2 \log n)$ -time algorithm that reduces the max-

imum degree to $\text{poly}(\max(\lambda, \log n))$ for graphs of arbitrary arboricity. The subsequent algorithm of [GGJ20] obtains the same degree reduction in $O(\log \log n)$ rounds. This result combined with the $O(\sqrt{\log \Delta} \log \log \Delta + \log \log n)$ -round randomized MIS and MM algorithm [GU19] for general graphs yields an $O(\sqrt{\log \lambda} \log \log \lambda + \log \log n)$ running time, i.e., a round complexity of $O(\log \log n)$ on graphs of polylogarithmic arboricity.

Deterministic MIS and MM The fastest deterministic MIS and MM algorithm for general graphs runs in $O(\log \Delta + \log \log n)$ by a result of [CDP21b]. When restricting our attention to deterministic algorithms in terms of the arboricity, only an $O(\log^2 \log n)$ -time bound for MIS and MM on trees (i.e., $\lambda = 1$) is known due to Latypov and Uitto [LU21].

On the hardness side, there is a component-stable conditional lower bound of $\Omega(\log \log n)$ for MM, which holds even on trees, by the works of [CDP21a, GKU19].

Arboricity Coloring: The problem of coloring a graph is a corner-stone *local* problem, with numerous applications, that has been studied extensively. A K -coloring of vertices is a function $\phi: V \rightarrow \{1, \dots, K\}$ such that for every edge $\{u, v\} \in E$ vertices u and v are assigned distinct colors, i.e., $\phi(u) \neq \phi(v)$. There has been a long succession of results based on recursive graph partitioning procedures in CONGESTED-CLIQUE and linear-memory MPC [BKM20, CFG⁺19, HP15, Par18, PS18]. The randomized complexity of $(\Delta + 1)$ -coloring and $(\Delta + 1)$ -list-coloring was settled to $O(1)$ by [CFG⁺19], and [CDP20] achieved the same result deterministically.

Much of the research on this topic has focused on coloring with $\Delta + 1$ colors. However, for sparse graphs, the maximum degree Δ may be much larger than the arboricity λ , and thus an arboricity-dependent coloring would be more satisfactory. Note that any graph admits a 2λ -coloring, and that this bound is tight. In this regard, Barenboim and Khazanov [BK18] observed that any problem can be solved in $O(\lambda)$ deterministic time (since there are at most λn edges), and proved a deterministic upper bound of λ^ε to $O(\lambda)$ -color vertices, for any constant $\varepsilon > 0$. On the randomized side, Ghaffari and Sayyadi [GS19] show that an $O(\lambda)$ -coloring can be solved in $O(1)$ time, settling its complexity.

1.1 Deterministic Algorithms and Derandomization

The derandomization of local algorithms has recently attracted much attention in the distributed setting (see, e.g., [BKM20, CC22, CDP20, CDP21b, CDP21c, FGG22, PP22]). The clever derandomization scheme introduced by [CHPS20] enhances classic derandomization methods [Lub93, MSN94] with the power of local computation and global communication, in spite of the limited bandwidth. Specifically, a randomized process that works under limited independence is derandomized, i.e., the right choice of (random) bits is found, by either brute-forcing all possible bit sequences or using the method of conditional expectation, computing the conditional expectations in a distributed fashion. There, one divides the seed into several parts and fixes one part at a time in a way that does not decrease the conditional expectation via global communication in a voting-like manner. In addition, to reduce the size of the search space, one can color the graph such that dependent entities are assigned distinct colors, i.e., their random decisions are decoupled, and entities that do not depend on each other can be safely assigned the same color. Interestingly, a good result is returned by the derandomized process even when concentration bounds fail to hold with high probability. On the other hand, the *shattering effect* no longer appears under limited independence. The lack of this phenomena poses major challenges in obtaining deterministic algorithms with complexities that match those of randomized algorithms, most of which crucially rely on shattering to have n -dependencies in their running time replaced by Δ . To overcome these challenges, current derandomization solutions often require large global memory (e.g., superlinear in the input size) or long local running time (e.g., large polynomial in n or even exponential).

1.2 Our Contribution

We introduce several improved deterministic algorithms for the three fundamental graph problems presented above in the MPC setting.

MIS and MM: We develop a deterministic fully scalable MPC algorithm that reduces the maximum degree of the input graph to $\text{poly}(\lambda)$.

Theorem 1.1. *There is a $O(\log \log n)$ -round deterministic low-space MPC algorithm with linear global memory that computes an independent set \mathcal{I} (or a matching \mathcal{M}) of a λ -arboricity input graph G such that the resulting graph $G \setminus \mathcal{I}$ (or $G \setminus \mathcal{M}$) has degree at most $\text{poly}(\lambda)$.*

This algorithm (Section 3) is obtained by derandomizing the $O(\log \log n)$ -time algorithm of [GGJ20], which achieves a reduction of $\text{poly}(\max(\lambda, \log n))$. Our approach not only attains a stronger guarantee deterministically, but it also dramatically simplifies the intricate pipelined MPC simulation [GGJ20] of an arboricity-based LOCAL degree reduction by [BEPS16]. Our end result is an $O(\log \lambda + \log \log n)$ -round algorithm by invoking the $O(\log \Delta + \log \log n)$ deterministic algorithm of [CDP21b] on the resulting $\text{poly}(\lambda)$ -degree graph. This proves that MIS and MM can be solved deterministically in $O(\log \log n)$ rounds on polylogarithmic arboricity graphs, implying up to an exponential speed up. Prior to our work, a deterministic $O(\log \log n)$ -round complexity was known only for $\text{poly}(\log n)$ -maximum degree graphs.

Theorem 1.2. *There is a deterministic low-space MPC algorithm that computes a maximal independent set and a maximal matching in $O(\log \lambda + \log \log n)$ rounds using $O(n^\alpha)$ local space and $O(n^{1+\varepsilon} + m)$ global space, for any constant $\varepsilon > 0$.*

When restricting our attention to the near-linear global memory regime (Section 4), we obtain the first deterministic fully scalable MIS and MM algorithms for general graphs. Each of the following round complexities is superior for different ranges of λ .

Theorem 1.3. *There is a MPC algorithm that deterministically computes a MIS and a MM with round complexity on the order of*

$$\min \left\{ \begin{array}{l} \log n, \\ \log \lambda \cdot \log \log n, \\ \lambda^{1+\varepsilon} + \log \log n \quad \text{for MM,} \\ \lambda^{2+\varepsilon} + \log \log n \quad \text{for MIS} \end{array} \right\},$$

for any constant $\varepsilon > 0$, using $O(n^\alpha)$ local space and $O(m + n)$ global space.

The key ingredient for the first two running time bounds is an improved derandomization scheme of the low-space MPC algorithm by [CDP21b]. We reduce the global memory usage of the $O(\log n)$ -round algorithm of [CDP21b] from $O(n^{1+\varepsilon} + m)$ to $O(n + m)$ by devising a pessimistic estimator that does not require knowledge of the two-hop neighborhood, i.e., it relies only on the one-hop neighborhoods to find a partial solution that decreases the problem size by a constant factor. Combined with the above degree reduction and a simple graph exponentiation process, we obtain the second runtime bound, where the $O(\log \lambda)$ -multiplicative factor essentially stems from the linear global memory constraint, as opposed to the $O(\log \lambda)$ -additive term of Theorem 1.2. For low-arboricity graphs, i.e., in the $(\log^{O(1)} \log n)$ -range, we apply our $\text{poly}(\lambda)$ -degree reduction followed by a fast reduction to arboricity coloring, and adapt coloring algorithms by Barenboim and Elkin [BE10] and Panconesi and Rizzi [PR01] to achieve the last two round complexities. Even for trees ($\lambda = 1$) the best deterministic result had $O(\log^2 \log n)$ running time [LU21].

Arboricity Coloring: We design a simple constant-round deterministic algorithm for the problem of computing a vertex coloring with $O(\lambda)$ colors in the linear memory regime of MPC, with relaxed global memory $n \cdot \text{poly}(\lambda)$.

Theorem 1.4. *Given a graph G with arboricity λ , a legal $O(\lambda)$ vertex coloring of G can be computed deterministically in $O(1)$ on a linear-memory MPC using $n \cdot \text{poly}(\lambda)$ global memory.*

Our constant-round algorithm is strikingly simple: After one single step of graph partitioning, all induced subgraphs are of linear size and can thus be collected and solved locally. We also extend this algorithm to the CONGESTED-CLIQUE model when $\text{poly}(\lambda) = O(n^2)$. For the linear-memory MPC setting with linear global memory, we show an $O(\lambda)$ -coloring algorithm running in $O(\log \lambda)$ time. Both results (Section 5) improve exponentially upon the deterministic $(\lambda^{\Omega(1)})$ -round algorithm of [BK18].

1.3 Comparison with the State-of-the-Art

We review the main ideas behind our arboricity-dependent MIS, MM, and coloring algorithms.

Arboricity-Dependent MIS and MM Algorithms: Our algorithm is based on a key ingredient common to the randomized MPC arboricity-dependent algorithms of [BBD⁺19, GGJ20], that is, a degree reduction routine by [BEPS16] that essentially reduces the number of nodes of degree at least β by a $(\beta^{\Omega(1)})$ -factor in $O(1)$ LOCAL rounds for any $\beta \geq \text{poly}(\log n, \lambda)$ with high probability.

Randomized Approaches. The $O(\log \log n \cdot \log \log \Delta)$ -round algorithm of [BBD⁺19] shows that a black-box simulation of the above degree-reduction routine can be performed on a low-memory MPC in $O(\log \log n)$ rounds to achieve a (Δ^ϵ) -degree reduction, for any constant $\epsilon > 0$. Therefore, the repeated application of this routine for $O(\log \log \Delta)$ phases on quadratically-spaced degree classes leads to the claimed round complexity. By using a pipelining idea, [GGJ20] shows that these $O(\log \log \Delta)$ phases can be simulated concurrently in $O(\log \log n)$ rounds. The idea being that as more vertices become irrelevant in the current phase, the next phase can be started concurrently with the current phase which has not necessarily finished completely. However, in their framework, directly lifting multiple LOCAL degree-reduction routines to low-space MPC, which operate in conflicting parts of the same graph, results in a quite involved MPC simulation and analysis, e.g., by requiring phases to be asynchronous, a non-uniform graph exponentiation process, the concept of pending vertices, and keeping track of the message history of certain nodes.

Our Deterministic Approach. We first inspect the internal details of the LOCAL degree reduction [BEPS16] to extract a subgraph with a certain structure, on which we achieve the same expected degree reduction as under full independence solely relying on pairwise independence. We then show how to extract multiple subgraphs, one for each degree class, in a way that we can make progress on all degree classes simultaneously. In doing so, we spell out the *local* details of the pipeline framework of [GGJ20] bringing it at the LOCAL level. This locality makes the MPC simulation and its analysis significantly simpler. In fact, our carefully-designed LOCAL procedure can be easily simulated and derandomized efficiently on a low-space MPC for multiple stages, and a simple preprocessing step, which achieves an initial progress for all degree classes, makes it possible to carry out all phases synchronously with a uniform graph exponentiation process, i.e., nodes can store their k -hop neighborhoods with the same k . Our algorithm overcomes also several other challenges such as reducing the maximum degree of the input graph deterministically to $O(n^\delta)$, for any constant $\delta > 0$, and limiting the random bits for the derandomization of $O(\log \log \Delta)$ degree-class procedures to $O(\log \Delta)$. On a qualitative level, our LOCAL procedure based on shared random

bits may provide a more intuitive way to convert LOCAL randomized experiments to deterministic MPC algorithms. Moreover, we hope that the cleaner pipeline framework that we introduce may facilitate pipelining approaches for other problems.

Arboricity-Coloring Algorithms: Our approach builds upon the graph partitioning techniques introduced by [CFG⁺19, CDP20, GS19]. We derandomize a binning procedure that partitions the vertices of the input graph in k subsets, each of which induces a subgraph of arboricity at most $O(\lambda/k)$ so that the product of number of bins and induced arboricity is linear. We then color each of the k parts with $O(\lambda/k)$ colors separately and independently. Moreover, bad-behaving nodes, which were excluded by the partitioning algorithm due to their high degree, will induce a subgraph of size $O(n)$ that can be colored locally using a fresh color palette of size 2λ .

Our key technical contribution is a derandomization scheme that overcomes the inapplicability of the distributed method of conditional expectation. In fact, as opposed to the derandomization scheme for $(\Delta + 1)$ -coloring of [CDP20], arboricity is a global quality measure that cannot be decomposed into functions computable by gathering neighbors of each node on a single machine. To circumvent this, we find a subset of candidate partitions whose k parts are of linear size and can be checked by a single machine, yet allowing only a $\text{poly}(\lambda)$ overhead factor in the global space.

We note that the randomized constant-round arboricity-coloring of [GS19] uses a similar graph partitioning approach as a preprocessing step, which allows them to work with bins of arboricity $O(\log n)$ whenever $\lambda = \Omega(\log n)$. Therefore, the main challenge there is to solve the problem for $O(\log n)$ -arboricity graphs. They solve that taking an orthogonal approach, that is, a topology-gathering idea that simulates a $O(\log^2 \beta)$ -round CONGEST coloring algorithm for $\beta = \text{poly}(\log \log n)$ -arboricity graphs in $O(1)$ time.

For the second algorithm, we observe that [BK18] computes $O(\log \lambda)$ layers of a graph decomposition known as H -partition, after which the graph has linear size. We show that applying the $(\Delta + 1)$ -list coloring algorithm of [CDP20] on each layer yields an $O(\lambda)$ -coloring.

2 Preliminaries

This section introduces the notation and the algorithmic routines frequently used in the subsequent sections. The derandomization techniques applied in all-to-all communication models are described in more detail in [Appendix B](#). We explain arboricity properties used to analyze λ -dependent algorithms and a useful graph-theoretic structure known as H -partition [BE10] in [Appendix A](#). For a broader overview of these techniques, we refer to [BE13, Fis21].

Notation: For an integer $k \geq 1$, we use $[k]$ to denote the set $\{1, 2, \dots, k\}$. Let $G = (V, E)$ be the undirected n -node m -edge graph given in input with maximum degree Δ . Denote $\deg_G(u)$ as the degree of vertex u in graph G and $N_G(u)$ as the set of neighbors of u in G (when G is clear from the context, we may omit it). The distance from u to v , $\text{dist}_G(u, v)$, is the length of the shortest path from u to v in G . For a vertex subset $U \subseteq V$ or edge subset $U \subseteq E$, we use $\deg_U(u)$ and $N_U(u)$ to refer to the subgraph of G induced by U denoted by $G[U]$. For a vertex subset $V' \subseteq V$, let $N_G(V')$ be the union of the neighbors of each $v \in V'$. Let $\text{dist}_G(u, V')$ be the minimum distance from u to any vertex in V' . Further, we denote G^k , for $k \geq 2$, as the graph where each pair of vertices at distance at most k in G is connected. The k -hop neighborhood of a vertex v in G is the subgraph containing all vertices u satisfying $\text{dist}_G(u, v) \leq k$ and the k -hop neighborhood of a vertex set $V' \subseteq V$ is the union of the k -hop neighbors of $v \in V'$. Finally, we denote by $G \setminus \mathcal{I}$ the graph obtained by removing the nodes in \mathcal{I} and their neighbors. Similarly, $G \setminus \mathcal{M}$ denotes the graph where nodes in \mathcal{M} are removed.

Primitives in Low-Space MPC: We use the MPC primitives of the following lemma as black-box tools, which allow us to perform basic computations on graphs deterministically in $O(1)$ rounds. These include the tasks of computing the degree of every vertex, ensuring neighborhoods of all vertices are stored on contiguous machines, collecting the 2-hop neighborhoods, etc.

Lemma 2.1 ([Goo99,GSZ11]). *For any positive constant α , sorting, filtering, prefix sum, predecessor, duplicate removal, and colored summation task on a sequence of n tuples can be performed deterministically in MapReduce (and therefore in the MPC model) in a constant number of rounds using $\mathbf{S} = n^\alpha$ space per machine, $O(n)$ global space, and $\tilde{O}(n)$ total computation.*

Graph Exponentiation: A central technique to simulate LOCAL algorithms exponentially faster via all-to-all communication is that of letting each node send its r -hop neighborhood to each of the nodes in it, so that in one round every node learns the topology of the ball of radius $2r$ around itself [LW10]. Then, each node can simulate $2r$ rounds by computing the choices made by its $2r$ -hop neighbors. The repeated application of this process often leads to an exponential speed up provided that the exchanged information respects bandwidth and both local and global space constraints. Our MIS and MM algorithms are based on this technique, which will be explained case by case.

3 Deterministic Arboricity-Based Degree Reduction

Our degree-reduction procedure operates on multiple degree classes simultaneously. Section 3.1 is devoted to our degree-reduction algorithm in the LOCAL model. The single-class degree reduction (Lemma 3.2) is based on a key LOCAL algorithmic primitive for bounded arboricity graphs of [BEPS16] explained in Lemma 3.3. In Lemma 3.4, we extend this primitive to work on multiple degree classes with limited randomness. We then proceed to derandomize and simulate multiple LOCAL runs efficiently on an MPC with strongly sublinear memory in Section 3.2.

3.1 The LOCAL Algorithm

It turns out that so-called β -high graphs play an important role in finding partial MIS and MM solutions.

Definition 3.1 (β -high-graph). *Let β be a parameter. Let H be a graph on vertices $V(H) = V^{high} \sqcup V^{low}$. We say that H is a β -high graph if the following holds:*

- a) $\deg_{V^{low}}(v) \geq \beta^4$ for every $v \in V^{high}$, and
- b) $\deg_{V^{high}}(v) \leq \beta$ and $\deg_{V^{low}}(v) \leq \beta^2$ for every $v \in V^{low}$.

We use a β -high graph to find an MIS (or a MM) on low-degree nodes such that only a β -fraction of high-degree nodes remain in expectation, as the following lemma shows. The proof is based on a novel pairwise independent analysis of the bounded-arboricity algorithmic primitive of [BEPS16].

Lemma 3.2. *Let H be a β -high graph. There is a LOCAL algorithm running in $O(1)$ rounds that computes an independent set \mathcal{I} (or a matching \mathcal{M}) of H such that in the remaining graph $H' = H \setminus \mathcal{I}$ (or $H \setminus \mathcal{M}$) the following holds*

$$\mathbb{E}[|V^{high}(H')|] \leq \frac{|V^{high}(H)|}{\beta^{\Omega(1)}}.$$

Moreover, the only source of randomness in the algorithm is $O(\log C)$ shared random bits with $C \geq \text{poly}(\beta)$, where C is an upper bound on the number of colors (or IDs) assigned to vertices in V^{low} such that any two nodes whose random choices are assumed to be independent are given different colors.

Proof of Lemma 3.2. We analyze a pairwise independent random sampling approach that builds an independent set \mathcal{I} on the vertex set V^{low} (or matching $\mathcal{M} \subseteq E(H)$). For MIS, we sample each node $u \in V^{low}$ with probability $p = 1/\beta^3$ using pairwise independent random variables. Then, u joins \mathcal{I} if none of its neighbors is sampled. Consider now an arbitrary node v in V^{high} . Let $\{X_u\}_{u \in N_{V^{low}}(v)}$ be the random variables denoting the event that u joins \mathcal{I} and define $X = \sum_{u \in N_{V^{low}}(v)} X_u$ to be their sum. We have

$$\Pr[X_u = 1] \geq \Pr[u \text{ sampled}] - \sum_{u' \in N_{V^{low}}(u)} \Pr[u, u' \text{ sampled}] \geq p - \beta^2 p^2, \quad (1)$$

where the second inequality follows from pairwise independence. It follows that the expected number of neighbors of v in the MIS is at least $\mathbb{E}[X] = \sum_{u \in N_{V^{low}}(v)} \Pr[X_u = 1] \geq \beta^4 \cdot (p - \beta^2 p^2) \stackrel{\text{def}}{=} \mu$. Our goal is now to prove that $\Pr[X = 0] \leq \frac{\text{Var}[X]}{\mu^2} \leq \frac{5}{\beta}$ by applying Chebyshev's inequality (Theorem B.3). For any two vertices $u, u' \in N(v)$, we have that $\mathbb{E}[X_u X_{u'}] \leq p^2$ by pairwise independence. This combined with (1) yields

$$\begin{aligned} \text{Var}[X_u] &= \mathbb{E}[X_u^2] - \mathbb{E}[X_u]^2 \leq p - p^2(1 - \beta^2 p)^2 \leq p, \\ \text{Cov}[X_u, X_{u'}] &= \mathbb{E}[X_u X_{u'}] - \mathbb{E}[X_u] \mathbb{E}[X_{u'}] \leq p^2 - p^2(1 - \beta^2 p)^2 \leq 2\beta^2 p^3, \end{aligned}$$

where we use that $p \leq \frac{1}{2\beta^2}$. Then, by observing that $\mu^2 = \beta^8 \cdot (p - \beta^2 p^2)^2 \geq \frac{1}{2} \beta^8 \cdot p^2$ since $p \leq \frac{1}{4\beta^2}$, we get

$$\frac{\text{Var}[X]}{\mu^2} \leq \frac{\sum_{w \in N_{V^{low}}(v)} \text{Var}[X_w] + \sum_{w, w' \in N_{V^{low}}(v)} \text{Cov}[X_w, X_{w'}]}{\mu^2} \leq \frac{2}{\beta^4 p} + 4\beta^2 p \leq \frac{5}{\beta},$$

where the last inequality follows from our choice of $p = 1/\beta^3$. Therefore, the expected number of V^{high} -nodes that do not have a neighbor in the MIS is at most $5|V^{high}|/\beta$.

For the case of MM, we let each $u \in V^{low}$ propose that a randomly chosen edge $\{u, v\}$ with $v \in V^{high}$ is added to the matching. Any $v \in V^{high}$ receiving a proposal accepts one arbitrarily. A node $v \in V^{high}$ has at least β^4 neighbors $u \in V^{low}$ with $\deg_{V^{low}}(u) < \beta$. Thus, the number of proposals that v receives in expectation is at least β^3 . By Chebyshev's inequality for pairwise independent random variables (Corollary B.4), v is unmatched with probability at most $\frac{5}{\beta}$.

Next, we prove the bound on the amount of randomness required by the above process. Let us assume that nodes in V^{low} are assigned colors (or IDs), $\phi: V \rightarrow [C]$, such that nodes whose (random) choices are assumed to be pairwise independent are given different colors. The set of colors is mapped to $\{0, 1\}^k$, for some integer $k > 0$, using a 2-wise independent hash family \mathcal{H} of size $O(\log C + \log \beta) = O(\log C)$ using Lemma B.2. For MIS, let $\mathcal{H} = \{h: [C] \mapsto \{0, 1\}^{3 \log \beta}\}$. Every $h \in \mathcal{H}$ induces an independent set \mathcal{I}_h . If a vertex $v \in V^{low}$ with $h(\phi(v)) = 0$ has no neighbors $w \in V^{low}$ with $h(\phi(w)) = 0$, then v is in \mathcal{I}_h . Similarly, for MM, let $\mathcal{H} = \{h: [C] \mapsto \{0, 1\}^{\log \beta}\}$. Each $v \in V^{low}$ selects an arbitrary neighboring vertex $u \in V^{high}$ with $h(\phi(v)) = u$ by mapping in an arbitrary but consistent manner its neighbors to $\{0, \dots, \beta - 1\}$. Then, \mathcal{M}_h includes each V^{high} -node with at least one proposal. By the above analysis, there is one hash function $h^* \in \mathcal{H}$ that achieves the expected result. \square

Next, we introduce a preparation phase used to construct a β -high-subgraph of a graph G for a certain degree class Δ_i by appointing a subset of high-degree nodes with many low-degree neighbors.

Lemma 3.3 (Single-Class Preparation [BEPS16]). *Let $\Delta_i \geq \text{poly}(\lambda)$ be a parameter and $V(G, \Delta_i) := \{v : \deg_G(v) > \sqrt{\Delta_i}\}$ denote the set of high-degree vertices in G . There is a deterministic constant-round LOCAL algorithm that finds a β -high-subgraph H of G with $\beta = \Delta_i^{0.03}$, such that:*

- a) $V^{\text{high}}(H) \subseteq V(G, \Delta_i)$.
- b) $\text{dist}(u, V(G, \Delta_i)) \leq 3$ for every $u \in V(H)$, i.e., no vertex outside the 3-hop neighborhoods of $V(G, \Delta_i)$ is in H .
- c) $|V(G, \Delta_i) \setminus V^{\text{high}}(H)| \leq \frac{|V(G, \Delta_i)|}{\Delta_i^{\Omega(1)}}$.

The proof can be found in [Appendix E](#). We extend the above preparation phase to work on multiple degree classes concurrently. Let $i_{\min} = \log \log(\lambda^{\Theta(1)})$ and $i_{\max} = \lceil \log \log \Delta \rceil$ be two parameters. We define $\Delta_i = 2^{2^i}$ for $i \in [i_{\min}, i_{\max}]$ and the following degree classes $V_i(G) = \{v \in V(G) : \deg_G(v) \in (\Delta_{i-1}, \Delta_i]\}$ for a given graph G . We also define the following sets $V_{\geq i}(G) = \bigcup_{j \geq i} V_j(G)$ and $V_{> i}(G) = \bigcup_{j > i} V_j(G)$. The idea used in the following lemma is to cluster nodes based on their highest-degree vertex at distance at most 4. This step is crucial to make progress on all degree classes concurrently.

Lemma 3.4 (Multi-Class Preparation). *There is a deterministic LOCAL algorithm running in $O(1)$ rounds that constructs a $(\Delta_i^{\Omega(1)})$ -high-subgraph H_i of a given graph G for every $i \geq i_{\min}$ such that:*

- a) $V^{\text{high}}(H_i) \subseteq V_i(G)$.
- b) $|V_{\geq i}(G) \setminus V^{\text{high}}(H_i)| \leq |V_i(G)| / \Delta_i^{\Omega(1)} + \sum_{j > i} \Delta_j^{O(1)} |V_j(G)|$.
- c) $\text{dist}_G(V(H_j), V(H_i)) \geq 2$ for every $j \geq i_{\min}$ with $j \neq i$.

Proof of Lemma 3.4. Let $D_G(v) = \max_{\text{dist}_G(u,v) \leq 4} \deg_G(u)$ for every $v \in V(G)$. Then, denote

$$G_i = G[\{u \in V(G) \mid D_G(u) \in (\Delta_{i-1}, \Delta_i] \text{ and } \text{dist}(u, V_i(G)) \leq 3\}]$$

as the subgraph of G induced by vertices whose highest-degree vertex in their 3-hop neighborhood is in $V_i(G)$, for every i . Consider now any $j > i$. It holds that $\text{dist}_G(V(G_j), V(G_i)) \geq 2$. To see why, consider any $u \in V(G_i)$ and $v \in V(G_j)$. We have

$$\begin{aligned} 5 &\leq \text{dist}_G(u, V_{> i}(G)) \leq \text{dist}_G(u, V_j(G)) \\ &\leq \text{dist}_G(u, v) + \text{dist}(v, V_j(G)) \leq \text{dist}_G(u, v) + 3 \end{aligned}$$

and therefore $\text{dist}_G(u, v) \geq 2$, proving Property 3. Also, note that $V(G_i) \cap V_{> i}(G) = \emptyset$ and therefore $\Delta(G_i) \leq \Delta_i$. Now, let H_i be the subgraph of G_i that we obtain by invoking [Lemma 3.3](#) with input G_i and Δ_i . The graph H_i is a $(\Delta_i^{\Omega(1)})$ -high-graph. Observe that $V_i(G_i) = \{v \in V(G_i) \mid \deg_{G_i}(v) > \sqrt{\Delta_i}\} =: V(G_i, \Delta_i)$. By Property 1 of [Lemma 3.3](#), $V^{\text{high}}(H_i) \subseteq V_i(G_i)$, and together with $V_i(G_i) \subseteq V_i(G)$, this implies $V^{\text{high}}(H_i) \subseteq V_i(G)$, which proves Property 1 of this lemma. Moreover, Property 3 of [Lemma 3.3](#), using the fact that $i_{\min} = \Theta(\log \log \lambda)$, gives that

$$|V_i(G_i) \setminus V^{\text{high}}(H_i)| \leq \frac{|V_i(G_i)|}{\Delta_i^{\Omega(1)}} \leq \frac{|V_i(G)|}{\Delta_i^{\Omega(1)}}.$$

Then, consider the remaining vertices $v \in V_i(G) \setminus V_i(G_i)$. Since $\text{dist}_G(v, V_i(G)) = 0$, it holds that $D_G(v) > \Delta_i$, i.e., $\text{dist}_G(v, V_{>i}(G)) \leq 4$. Thus,

$$|V_{\geq i}(G) \setminus V_i(G_i)| \leq |\{v \in V(G) \mid \text{dist}_G(v, V_{>i}(G)) \leq 4\}| \leq \sum_{j>i} \Delta_j^{O(1)} |V_j(G)|,$$

which combined with the above bound completes the proof of Property 2. Finally, as G_i 's are node-disjoint, we can compute all H_i 's simultaneously in $O(1)$ LOCAL rounds. \square

Next, we show how to use the graphs constructed above to run a single execution of our algorithmic primitive on all degree classes simultaneously.

Lemma 3.5 (Multi-Class Single-Stage Algorithm). *There is a LOCAL algorithm that computes an independent set \mathcal{I} (or a matching \mathcal{M}) of a given graph G such that in the remaining graph $G' = G \setminus \mathcal{I}$ (or $G \setminus \mathcal{M}$) with strictly positive probability the following holds:*

$$|V_{\geq i}(G')| \leq \frac{|V_i(G)|}{\Delta_i^{\Omega(1)}} + \sum_{j>i} \Delta_j^{O(1)} |V_j(G)|,$$

for every $i \in [i_{\min}, i_{\max}]$. Moreover, the only source of randomness in the algorithm is $O(\log C)$ shared random bits with $C \geq \text{poly}(\Delta)$, where C is an upper bound on the number of colors (or IDs) assigned to vertices such that any two nodes at distance at most 4 in G are given different colors.

Proof. Let us analyze the independent set case, the argument for the matching case is essentially the same. First, we compute in $O(1)$ rounds for every $i \in [i_{\min}, i_{\max}]$ a subgraph H_i of G using the algorithm of Lemma 3.4. Then, we simultaneously run the algorithm of Lemma 3.2 on each H_i to compute an independent set \mathcal{I}_i , which is independent also in since H_i is obtained from G without discarding any edge, i.e., $H_i = G[V(H_i)]$. Let $\mathcal{I} = \bigcup_i \mathcal{I}_i$, which is valid since any two subgraphs H_i, H_j are at distance at least two by Property 3 of Lemma 3.4. Moreover, by Property 1 and 2 of Lemma 3.2, it is enough to show that $|V^{\text{high}}(H_i) \setminus (\mathcal{I}_i \cup N_G(\mathcal{I}_i))| \leq |V^{\text{high}}(H_i)| / \Delta_i^{\Omega(1)}$ for each i . By an application of Markov's inequality, Lemma 3.2 fails in achieving the above guarantee for a fixed i with probability at most $\Delta_i^{-\Omega(1)}$. By a union bound, the total failure probability is upper bounded by $\sum_i \frac{1}{\Delta_i^{\Omega(1)}} \leq 1/2$ since we can assume that $\Delta_{i_{\min}} = \text{poly}(\lambda) = \Omega(1)$. Therefore, all the at most i_{\max} runs of Lemma 3.2 succeed with strictly positive probability. This means that there is a sequence of $O(\log C)$ random bits that makes all subgraphs $H_i \setminus \mathcal{I}_i$ good. Lastly, our coloring C of G^4 ensures that nodes whose choices are pairwise independent in Lemma 3.2 are given distinct colors. \square

Running the above algorithm for multiple stages leads to the following lemma.

Lemma 3.6 (Multi-Class Multi-Stage Algorithm). *Let $k \in \mathbb{N}$ and assume that $k \geq s$ for an absolute constant s . There is a LOCAL algorithm running in $O(k)$ rounds that computes an independent set \mathcal{I} (or a matching \mathcal{M}) of a given graph G such that in the remaining graph $G' = G \setminus \mathcal{I}$ (or $G \setminus \mathcal{M}$) with strictly positive probability the following holds:*

$$|V_{\geq i}(G')| \leq |V_{\geq i}(G)| / \Delta_i^{\Omega(k)},$$

for each $i \in [i_{\min}, i_{\max}]$. Moreover, $O(k \cdot \log C)$ shared random bits are the only source of randomness in the algorithm with C defined as above.

Proof. We apply the algorithm of [Lemma 3.5](#) for k times in a sequential fashion. Let $G^{(0)} = G$ and $G^{(\ell)}$ denote the graph obtained after the ℓ -th execution of [Lemma 3.5](#), for $0 \leq \ell \leq k$. We construct $G^{(\ell)}$ by running the algorithm on $G^{(\ell-1)}$ and removing nodes in the computed independent set and their neighbors (or nodes incident to the matching) from $G^{(\ell-1)}$. Then, $G' = G^{(k)}$. The overall running time is $O(k)$ since each run takes $O(1)$ rounds. We let each run use $O(\log C)$ different random bits so that each run succeeds independently with strictly positive probability by [Lemma 3.5](#). It then follows that the probability that all the runs succeed is strictly positive and that the total number of shared random bits required is $O(k \cdot \log C)$. It remains to prove the upper bound on the size of $|V_{\geq i}(G')|$ in the resulting graph G' . The proof is by induction on ℓ . The base case with $\ell = 0$ clearly holds. Assume that the statement holds for $\ell = k - 1$ and fix an arbitrary $i \in [i_{min}, i_{max}]$. By [Lemma 3.5](#) for some constant $c > 0$, we obtain

$$\begin{aligned} |V_{\geq i}(G^{(\ell+1)})| &\leq \frac{|V_i(G^{(\ell)})|}{\Delta_i^c} + \sum_{j>i} \Delta_j^{O(1)} |V_j(G^{(\ell)})| \leq \frac{|V_{\geq i}(G^{(\ell)})|}{\Delta_i^{c \cdot k}} + \sum_{j>i} \Delta_j^{O(1)} \frac{|V_{\geq j}(G^{(\ell)})|}{\Delta_j^{c \cdot (k-1)}} \\ &\leq \frac{|V_{\geq i}(G^{(\ell)})|}{\Delta_i^{c \cdot k}} + |V_{\geq i}(G^{(\ell)})| \sum_{j>i} \Delta_i^{-(c \cdot (k-1) - O(1))(2^j - 2^i)} \\ &\leq \frac{|V_{\geq i}(G^{(\ell)})|}{\Delta_i^{\Omega(k)}} \left(1 + \sum_{j \geq i} \Delta_i^{(2^i - 2^j + 1)} \right) = \frac{|V_{\geq i}(G^{(\ell)})|}{\Delta_i^{\Omega(k)}}. \end{aligned}$$

□

3.2 MPC Simulation and Derandomization

Let us now turn our attention to the low-memory MPC model. In the following, we assume that $\Delta = O(n^\delta)$, for any $\delta > 0$, and explain how to lift this assumption last. First, we show that the derandomization of [Lemma 3.3](#) leads to the following result.

Lemma 3.7 (Single-Class Reduction). *For any fixed $i \in [i_{min}, i_{max}]$, there is a deterministic fully-scalable MPC algorithm running in $O(c)$ rounds that computes an independent set \mathcal{I} (or a matching \mathcal{M}) of a given graph G such that in the remaining graph $G' = G \setminus \mathcal{I}$ (or $G \setminus \mathcal{M}$) the following holds:*

$$|V_{\geq i}(G')| \leq |V_{\geq i}(G)| / \Delta_i^c.$$

Proof. We present an $O(1)$ -time algorithm that achieves a $\Delta_i^{\Omega(1)}$ reduction of $|V_{\geq i}(G)|$. The lemma then follows from repeating it $O(c)$ times.

The first step of the algorithm applies [Lemma 3.3](#) with input G and Δ_i to obtain a β -high-graph H with $\beta = \Delta_i^{\Omega(1)}$. Assuming that each node can store its one-hop neighbors on a single machine, [Lemma 3.3](#) can be simulated on a low-memory MPC in $O(1)$ rounds. Observe that $V_{\geq i}(G) = \{v \in V(G) \mid \deg_G(v) > \sqrt{\Delta_i}\} =: V(G, \Delta_i)$. By Property 1 and 3 of [Lemma 3.3](#), $|V(G, \Delta_i) \setminus V^{high}(H)| \leq \frac{|V(G, \Delta_i)|}{\Delta_i^{\Omega(1)}}$ and $|V^{high}(H)| \leq |V_{\geq i}(G)|$. Thus, it remains to prove that we can deterministically find an independent set \mathcal{I} (or a matching \mathcal{M}) of H such that in the remaining graph H' , $|V^{high}(H')| \leq |V^{high}(H)| / \Delta_i^{\Omega(1)}$ holds. To this end, we prove that the algorithm of [Lemma 3.2](#) can be derandomized on a low-memory MPC in $O(1)$ rounds. In the following, we omit specifying that V^{low} and V^{high} are with respect to H .

We first explain how to compute a C -coloring of V^{low} such that nodes whose random choices are assumed to be independent are given distinct colors. We color a *conflict* graph on nodes in V^{low}

in $O(1)$ rounds constructed as follows. Let every V^{low} -node send its V^{low} -neighborhood to each of the at most β^3 nodes in V^{high} at distance at most 2. The total information exchanged in this step is at most $\sum_{v \in V(G, \Delta_i)'} \beta^{(1+2+2)} \leq \sum_{v \in V(G, \Delta_i)'} \deg_G(v)$. Then, every $v \in H_{\text{Good}}$ (as defined in [Lemma 3.3](#)) adds an edge between each pair of vertices in the neighborhoods received. The number of edges that each node v adds is $O(\beta^{10}) \ll \sqrt{\Delta_i} = O(\deg_G(v))$. Thus, a $O(\Delta_i^2 \log^2 n)$ -coloring of the conflict graph can be computed in $O(1)$ rounds by [Lemma B.6](#). This yields $O(\log C) = O(\delta \log \Delta_i + \log \log n)$ and thus the family of hash functions \mathcal{H} used in [Lemma 3.2](#) can be stored on a single machine. For each $v \in V^{high}$, using the exchanged information and by communicating the assigned color, the machine that v is assigned to can check whether v has no neighbors in \mathcal{I}_h (or matching proposals) for every hash function h . We can then aggregate these numbers across machines for every hash function using [Lemma 2.1](#) in $O(1)$ time and find one good function $h^* \in \mathcal{H}$, which gives the expected result. \square

The above single-class reduction is applied to each degree class sequentially in the next lemma.

Lemma 3.8 (Preprocessing MPC). *Let $c \in \mathbb{N}$ be a parameter. There exists a deterministic low-memory MPC algorithm running in $O(c \log \log \Delta)$ rounds that computes an independent set \mathcal{I} (or a matching \mathcal{M}) of a given graph G such that in the remaining graph $G' = G \setminus \mathcal{I}$ (or $G \setminus \mathcal{M}$) the following holds for every $i \in [i_{\min}, i_{\max}]$:*

$$|V_{\geq i}(G')| \leq |V_{\geq i}(G)| / \Delta_i^c.$$

Proof. This lemma follows by applying [Lemma 3.7](#) once for each $i \in [i_{\min}, i_{\max}]$, which takes $O(c \log \log \Delta)$ rounds overall. We define a sequence of graphs $G_{i_{\min}}, \dots, G_{i_{\max}}$ with $G_{i_{\max}} = G$. Let \mathcal{I}_i be the independent set that we obtain by invoking [Lemma 3.7](#) with inputs G_i and c . Let $G_{i-1} := G_i \setminus \mathcal{I}_i$ and define the independent set $\mathcal{I} = \bigcup_{i \in [i_{\min}, i_{\max}]} \mathcal{I}_i$. This finishes the description of the algorithm and we can indeed compute \mathcal{I} in $O(\log \log \Delta)$ rounds deterministically on a low-memory MPC. The procedure for computing a matching \mathcal{M} is equivalent. \square

The next lemma is a key technical step to achieve our end result. It shows how to efficiently derandomize our multi-class multi-stage LOCAL algorithm.

Lemma 3.9. *Let $k \in \mathbb{N}$. There is a deterministic low-memory MPC algorithm that in $O(1)$ rounds computes an independent set \mathcal{I} (or a matching \mathcal{M}) of a given graph G with maximum degree Δ_{sup} such that in the remaining graph $G' = G \setminus \mathcal{I}$ (or $G \setminus \mathcal{M}$) the following holds for every $i \in [i_{\min}, i_{\max}]$*

$$|V_{\geq i}(G')| \leq |V_{\geq i}(G)| / \Delta_i^{\Omega(k)},$$

provided that the following conditions are satisfied:

- a) *Each node $v \in V(G)$ has stored its k -hop neighborhood in G on a single machine.*
- b) *$k \geq c'$ for some constant c' and $k \leq \frac{\log(n)}{\log(\Delta_{\text{sup}} \cdot \log^{(k)} n)}$.*

Proof. The first step of the algorithm computes a coloring of G with $C = \text{poly}(\Delta_{\text{sup}}) \cdot \log^{(k)} n$ colors such that vertices at distance at most 4 are assigned distinct colors. This can be achieved by simulating $O(k)$ executions of [Lemma B.6](#) in $O(1)$ MPC rounds using knowledge of the k -hop neighborhood. In particular, this provides a proper coloring for simulating [Lemma 3.6](#) with input parameters G and $\kappa \in \mathbb{N}$, where $\kappa = \Theta(k)$ is chosen such that: (i) the number of random bits

required $b = O(\kappa \cdot \log(\Delta_{sup} \cdot \log^{(k)} n))$ gives $2^b = O(n^\alpha)$, i.e., the κ families of pairwise independent hash functions used by [Lemma 3.6](#) fit into the memory of a single machine; (ii) the LOCAL running time $O(\kappa)$ of [Lemma 3.6](#) is at most k , i.e., each node can simulate it using its k -hop neighborhood without any communication; and (iii) κ is larger than the absolute constant s of [Lemma 3.6](#). All conditions can be met at the same time using the above assumption on k .

We note that the following multi-stage derandomization is inspired by that of [[CDP21b](#), Section 5.2]. Let \mathcal{H} be a 2-wise independent hash family as explained in [Lemma 3.2](#). By the probabilistic method, there is a sequence of hash functions $h_1, \dots, h_\kappa \in \mathcal{H}^k$ that achieves the result of [Lemma 3.6](#). Moreover, by the choice of κ , all possible sequences h_1, \dots, h_κ can be stored and evaluated on any single machine. Each high-degree node considers all possible sequences of hash functions $\mathbf{h} = \langle h_1, \dots, h_\kappa \rangle$ and simulates [Lemma 3.6](#) according to \mathbf{h} . Let $\mathcal{I}^{\mathbf{h}}$ be the independent set found. Each node can check whether it is incident to $\mathcal{I}^{\mathbf{h}}$ and compute its degree in $G \setminus \mathcal{I}^{\mathbf{h}}$. By aggregating these numbers for each class $V_{\geq i}(G)$, we can compute $V_{\geq i}(G \setminus \mathcal{I}^{\mathbf{h}})$ and check whether $V_{\geq i}(G') \leq V_{\geq i}(G) / \Delta_i^{\Omega(i)}$ for each i . Thus, we select one sequence \mathbf{h}^* defining $\mathcal{I}^{\mathbf{h}^*}$ which ensures that the number of nodes in each class satisfies the above condition. The same approach can be easily extended to maximal matching by running the matching version of [Lemma 3.2](#). \square

We are now ready to present our deterministic low-memory MPC $\text{poly}(\lambda)$ -degree reduction.

Theorem 1.1. *There is a $O(\log \log n)$ -round deterministic low-space MPC algorithm with linear global memory that computes an independent set \mathcal{I} (or a matching \mathcal{M}) of a λ -arboricity input graph G such that the resulting graph $G \setminus \mathcal{I}$ (or $G \setminus \mathcal{M}$) has degree at most $\text{poly}(\lambda)$.*

Proof. The first step of the algorithm is to apply the preprocessing of [Lemma 3.8](#), which takes $O(\log \log \Delta)$ rounds. Then, for $\ell = 0, 1, \dots, O(\log \log n)$ constant-round iterations, we perform the following steps: (i) run our MPC multi-class multi-stage algorithm ([Lemma 3.9](#)) for $c = O(1)$ times; and (ii) perform one step of graph exponentiation. Then, the returned independent set (or matching) is given by the union of the partial solutions computed in each iteration at step (i). To execute step (i), any two consecutive runs of [Lemma 3.9](#) are interleaved by a constant-round coordination step where we update the 2^ℓ -hop neighborhood of each (survived) node as follows. Suppose that $u \in V$ knows its 2^ℓ -hop neighborhood at the beginning of the first run in graph $G^{(\ell,1)}$. Notice that $G^{(\ell,2)}$ is obtained from $G^{(\ell,1)}$ by removing $\mathcal{I}_{h^*} \cup N(\mathcal{I}_{h^*})$. Therefore, to update the 2^ℓ -hop neighborhood of u in $G^{(\ell,2)}$, each node $v \in \mathcal{I}_{h^*} \cup N(\mathcal{I}_{h^*})$ communicates that it is part of the current solution to all nodes in its 2^ℓ -hop neighborhood in $G^{(\ell,1)}$. This process is then repeated another $c - 1$ times (the matching case is equivalent).

The crux of the analysis is to prove that $V_{\geq i}(G^{(\ell_i)}) = \emptyset$ by the end of iteration $\ell_i = \lfloor \log \alpha \log_{\Delta_i} n \rfloor - 1$. Recall that by the preprocessing step we can assume that $V_{\geq i}(G^{(0)}) \leq V_{\geq i}(G) / \Delta_i^t$ for any constant $t > 0$. This allows us to conclude that $V_{\geq i}(G^{(\ell_i)}) = \emptyset$ for any $\ell_i = O(1)$. For the other values of ℓ_i , the proof is by induction on i . Observe that $\ell_i < \ell_j$ for any $j < i \in [i_{min}, i_{max}]$ and let $k := 2^{\ell_i} = (\alpha \log_{\Delta_i} n) \geq c'$ since $\ell_i = \Omega(1)$. Fix an arbitrary i . After iteration ℓ_i , the algorithm has performed ℓ_i graph exponentiation steps, implying that each node knows its k -hop neighborhood. One can verify that also $k \leq \frac{\log(n)}{\log(\Delta(G^{(\ell)}) \cdot \log^{(k)} n)}$ holds. Therefore, by c repeated invocations of [Lemma 3.9](#) in step (i), we get $|V_{\geq i}(G^{\ell_i+1})| \leq |V_{\geq i}(G^{\ell_i})| / \Delta_i^{c \cdot \Omega(k)} = 0$ for c suff. large, since $k = \Omega(\alpha \log_{\Delta_i} n)$.

This proves that after $\ell_{i_{min}} = O(\log \log n)$ rounds our degree reduction is completed. Moreover, the local memory constraint is also respected. To see why, observe that at any iteration $\ell \in (\ell_{i+1}, \ell_i]$, the size of the k -hop neighborhood is at most $\Delta_i^{k+1} = O(n^\alpha)$ because all higher degree classes are empty by the end of the (ℓ_{i+1}) -th iteration, i.e., Δ_i is the maximum degree in

$G^{(\ell_{i+1}+1)}, \dots, G^{(\ell_i)}$. Finally, we prove that the global memory usage is linear in the input size. Let $D_\ell(v, d) = \max_{\text{dist}(u,v) \leq d, \text{ in } G^{(\ell)}} \deg_{G^{(\ell)}}(u)$. The total memory required for the graph exponentiation process at iteration ℓ is upper bounded by $\sum_{v \in V(G^\ell)} D_\ell(v, k)^k \leq \sum_i V_i(G^\ell) \Delta_i^{2k+1}$. This inequality can be seen as a charging scheme where v charges its highest-degree k -hop neighbor, which has degree at most Δ_i and thus v 's neighborhood requires at most Δ_i^{k+1} words for being stored. Moreover, the total number of nodes that charge $v \in V_i$ is at most Δ_i^k . By our preprocessing step and step (i) of the algorithm, it holds that $V_{\geq i}(G^{\ell+1}) \leq V_{\geq i}(G)/\Delta_i^{2k+1}$. Observe that for small values of $k = O(1)$, we may not be able to run [Lemma 3.9](#) due to the condition $k \geq c'$ but we can choose t such that $V_{\geq i}(G^\ell) \leq V_{\geq i}(G)/\Delta_i^t \leq V_{\geq i}(G)/\Delta_i^{2k+2}$ for $k = O(1)$. Thus,

$$\sum_i V_i(G^\ell) \Delta_i^{2k+1} \leq \sum_i \frac{V_{\geq i}(G)}{\Delta_i} = O(m).$$

This proves that the global memory constraint is respected for vertices in the k -hop neighborhood of $V_{\geq i_{\min}}(G)$. A vertex with degree at most $\text{poly}(\lambda)$ whose highest degree vertex in its 8-hop neighborhood is at most $\text{poly}(\lambda)$ will remain in G and its degree will not change throughout the execution of our algorithm, thus we can safely *freeze* it, i.e., it will not run the algorithm and thus the overall global space constraint is also respected. \square

Next, we combine our degree reduction with the $O(\log \Delta + \log \log n)$ -round algorithm of [[CDP21b](#)].

Theorem 1.2. *There is a deterministic low-space MPC algorithm that computes a maximal independent set and a maximal matching in $O(\log \lambda + \log \log n)$ rounds using $O(n^\alpha)$ local space and $O(n^{1+\varepsilon} + m)$ global space, for any constant $\varepsilon > 0$.*

Proof. Observe first that we can assume that $\lambda = O(n^{\delta/4})$, as otherwise $\Delta \ll \text{poly}(\lambda)$ and we can thus directly apply the $O(\log \Delta + \log \log n)$ -round algorithm [[CDP21b](#)]. Our $O(\log \log n)$ -round $\text{poly}(\lambda)$ -degree reduction can be applied on any graph with maximum degree $O(n^\delta)$, for some constant $\delta \in (0, 1)$. Thus, when the maximum degree of the graph under consideration is $O(n^\delta)$, we apply our degree reduction followed by [[CDP21b](#)] on the remaining graph of $\text{poly}(\lambda)$ -maximum degree to obtain the claimed complexity. Otherwise, our algorithm works as follows. We construct a H -partition of degree $d = n^{\delta/3}$ consisting of H_1, \dots, H_L layers, i.e., disjoint set of vertices, with $O(\log_{d/\lambda} n) = L = O(1)$ in $O(L) = O(1)$ rounds. Recall that the maximum degree within each layer is at most $d = O(n^\delta)$. For MIS, we can simply process each layer sequentially. For each $i \in [L]$, we compute a maximal independent set \mathcal{I} of the subgraph induced by H_i and remove nodes in $\mathcal{I} \cup N(\mathcal{I})$. For MM, we compute a matching $\mathcal{M} = \bigcup_{i=1}^L \mathcal{M}_i$ such that $G \setminus \mathcal{M}$ contains no vertices with degree larger than d^3 in H_i , i.e., each high-degree vertex is either removed or all but at most d^3 of its incident edges are in \mathcal{M} . To achieve that, we run the process explained in [Appendix C](#). \square

4 MIS and MM with Near-Linear Global Memory

In the sublinear regime of MPC with near-linear global memory, i.e., $\tilde{O}(n + m)$, we obtain the following three running time bounds, each of which is asymptotically superior for different values of λ .

Theorem 1.3. *There is a MPC algorithm that deterministically computes a MIS and a MM with round complexity on the order of*

$$\min \left\{ \begin{array}{l} \log n, \\ \log \lambda \cdot \log \log n, \\ \lambda^{1+\varepsilon} + \log \log n \quad \text{for MM,} \\ \lambda^{2+\varepsilon} + \log \log n \quad \text{for MIS} \end{array} \right\},$$

for any constant $\varepsilon > 0$, using $O(n^\alpha)$ local space and $O(m + n)$ global space.

4.1 High-Arboricity Case

In this section, we prove the first running time bound of [Theorem 1.3](#). When the input graph G has arboricity $\lambda = n^{\Omega(1)}$, any $O(\log \lambda)$ -round algorithm can spend $O(\log n)$ rounds for computing a solution. The main challenge in converting classical $O(\log n)$ -round Luby's algorithms to fully-scalable MPC algorithms is that a machine may not be able to store the whole neighborhood of a node in its memory. To overcome such limitation, Czumaj, Davies, and Parter [[CDP21b](#)] devise a constant-round sparsification procedure that reduces the maximum degree to $O(n^\delta)$, for any constant $\delta > 0$, while preserving a partial solution that decreases the problem size by a constant factor. This allows to convert each randomized step of Luby's into a deterministic step. Crucially, the derandomization of each phase of Luby's requires storing the two-hop neighborhoods on a single machine to check whether a node or edge survives to the next phase. This results in a $\Omega(n^{1+2\delta})$ -global space usage, as each vertex has up to $O(n^{2\delta})$ many 2-hop neighbors. We introduce a *pessimistic estimator* that produces asymptotically the same results and can be computed using only knowledge of the one-hop neighborhood, i.e., using only linear global memory. In the following, we prove this result for the maximal matching case and refer to [Appendix D](#) for the MIS case. Our starting point is the maximal matching sparsification procedure of [[CDP21b](#), Section 3], which is summarized in the following lemma and works with $O(n + m)$ total space.

Lemma 4.1 ([\[CDP21b\]](#)). *There is a deterministic low-memory MPC constant-round sparsification procedure that returns a subset of nodes $B \subseteq V$ and a subset of edges $E' \subseteq E$ such that:*

- a) *For every $v \in V$ it holds that $\deg_{E'}(v) = O(n^\delta)$, for any δ , $0 < \delta < 1$.*
- b) *Every node $v \in B$ either satisfies $\sum_{\{u,v\} \in E'} \frac{1}{\deg_{E'}(\{u,v\})} \geq \frac{1}{27}$, or is incident to an edge $\{u,v\} \in E'$ whose degree in E' is 0.*
- c) *For the subset B of V it holds that $\sum_{v \in B} \deg(v) \geq \frac{\delta|E|}{8}$.*

We use the subsets E' of edges and B of vertices returned by [Lemma 4.1](#) to construct a matching $\mathcal{M} \subseteq E'$ that is incident to $\Omega(\delta|E|)$ edges. We define for each $v \in B$ a subset of *relevant* edges $S(v) \subseteq E'(v)$ such that $\sum_{e \in S(v)} \frac{1}{\deg_{E'}(\{u,v\})} \in [\frac{1}{27}, 1]$, by [Property 2](#). Let \mathcal{H} be a family of pairwise independent hash functions and let $h \in \mathcal{H}$ map each edge $e = \{u,v\}$ in E' to a value $z_e \in [n^3]$. We say that e is *sampled* and joins the set of sampled edges S_h iff $z_e < \frac{n^3}{3 \deg_{E'}(e)}$. Let $S_h(v) \stackrel{\text{def}}{=} S(v) \cap S_h$ denote the set of edges in $S(v)$ that are sampled. Define \mathcal{M}_h to be the set of sampled edges with no neighboring edges sampled. Observe that, for a node v , if the following two conditions hold: (i) $|S_h(v)| = 1$ and (ii) $e = \{u,v\} = \{e' \in S_h \mid u \in e'\}$, i.e., e is the only sampled edge in u 's neighborhood, then v is matched under h . For simplicity, let us remove from consideration all nodes

$v \in B$ with $S(v) = \{e\}$. We now define the following pessimistic estimator $P(h)$:

$$P(h) = \sum_{v \in B: |S_h(v)|=1} \deg(v) - \sum_{v \in B} \deg(v) \cdot \left(\sum_{\{u,v\} \in S_h(v)} \mathbb{1}\{\exists e' \in S_h \sim e' \ni u\} \right).$$

To compute $P(h)$, every $v \in B$ checks $|S_h(v)|$ and, for each edge $e = \{u, v\} \in S_h(v)$, node u checks whether there is a $e' = \{u, w\} \in S_h$ with $w \neq v$. This shows that $P(h)$ can be computed by storing the one-hop neighborhoods of vertices on single machines. We now lower bound $\mathbb{E}[P(h)]$. Let A_e be the event $e \in S_h$ and B_e be the bad event $\{\exists e' \in E' \sim e A_{e'}\}$ that e is neighboring a sampled edge.

$$\begin{aligned} \mathbb{E}[P(h)] &= \sum_{v \in B} \deg(v) \cdot \Pr[|S_h(v)| = 1] - \sum_{v \in B} \deg(v) \cdot \left(\sum_{e \in S(v)} \Pr[A_e \wedge B_e] \right) \\ &= \sum_{v \in B} \deg(v) \cdot \left(\Pr[|S_h(v)| = 1] - \sum_{e \in S(v)} \Pr[A_e \wedge B_e] \right). \end{aligned}$$

The probability of the event A_e is $\frac{1}{3 \deg_{E'}(e)} - \frac{1}{n^3} \leq \Pr[A_e] \leq \frac{1}{3 \deg_{E'}(e)}$. Conditioned on A_e and using pairwise independence of z_e and $z_{e'}$, we obtain

$$\Pr[B_e | A_e] \leq \sum_{e' \in E' \sim e} \Pr[A_{e'}] \leq \deg_{E'}(e) \cdot \frac{1}{3 \deg_{E'}(e)} = \frac{1}{3}.$$

Then, by applying the inclusion-exclusion principle and noticing that $\Pr[A_e, A_{e'}] = \Pr[A_e] \cdot \Pr[A_{e'}]$ by pairwise independence, we get

$$\begin{aligned} \Pr[|S_h(v)| = 1] &\geq \sum_{e \in S(v)} \Pr[A_e] - \sum_{e \in S(v)} \sum_{e' \in S(v)} \Pr[A_e] \cdot \Pr[A_{e'}] \\ &\geq \sum_{e \in S(v)} \Pr[A_e] \left(1 - \sum_{e' \in S(v)} \Pr[A_{e'}] \right). \end{aligned}$$

Observe that $\Pr[A_e \wedge B_e] = \Pr[A_e] \Pr[B_e | A_e] \leq \frac{1}{3} \Pr[A_e]$ by the calculations above. Thus,

$$\begin{aligned} &\Pr[|S_h(v)| = 1] - \sum_{e \in S(v)} \Pr[A_e \wedge B_e] \\ &= \sum_{e \in S(v)} \Pr[A_e] \left(\frac{2}{3} - \sum_{e' \in S(v)} \Pr[A_{e'}] \right) \\ &\geq \sum_{e \in S(v)} \Pr[A_e] \left(\frac{2}{3} - \frac{1}{3} \sum_{e' \in S(v)} \frac{1}{\deg_{E'}(e')} \right) \geq \frac{1}{3} \cdot \sum_{e \in S(v)} \Pr[A_e] \\ &\geq \frac{1}{3} \cdot \sum_{e \in S(v)} \left(\frac{1}{3 \deg_{E'}(e)} - \frac{1}{n^3} \right) \\ &\geq \frac{1}{9} \cdot \sum_{e \in S(v)} \frac{1}{\deg_{E'}(e)} - \frac{1}{3n^2} \geq \frac{1}{243} - \frac{1}{3n^2}, \end{aligned}$$

where the last inequality follows from Property 2. Note that we can assume $\frac{1}{243} - \frac{1}{3n^2} \geq \frac{1}{250}$ for n large enough. This yields $\mathbb{E}[P(h)] \geq \frac{1}{250} \sum_{v \in B} \deg(v) \geq \frac{\delta|E|}{2000}$, as desired. Summarized, our algorithm applies the sparsification procedure of Lemma 4.1 followed by the derandomization approach of Appendix B with objective function $P(h)$. By the method of conditional expectation, we select a hash function h^* such that $P(h^*) \geq \frac{\delta}{4000} |E|$, i.e., a matching that decreases the number of edges by $\frac{\delta}{4000} |E|$. Repeating it $O(\log n)$ times ensures the matching maximality.

4.2 Medium-Arboricity Case

This section is devoted to the $O(\log \lambda \log \log n)$ -bound of Theorem 1.3. Whenever $\lambda = o(2^{\log n / \log \log n})$, this algorithm achieves sublogarithmic running time. On our graph of remaining degree $\text{poly}(\lambda)$ by Theorem 1.1, we run the following algorithm. For $i = 0, 1, \dots, \log \log_{\Delta} n^{\alpha} + O(1)$:

- a) Run the derandomized version of Luby's algorithm for $2^i \cdot \Theta(\log \Delta)$ LOCAL rounds using the derandomization of Section 4.1 for $i = 0$ and that of [CDP21b, Section 5] otherwise.
- b) Each vertex performs one graph exponentiation step until $\Delta^{2^i} = O(n^{\alpha})$.

The proofs of Section 3.2 and [CDP21b, Section 5] subsume the proof of the above algorithm. The key observation is that at any iteration i the first step ensures a decrease of the number of active vertices and edges by a $\Omega(\Delta^{2^i})$ factor and thus $\log \log_{\Delta} n^{\alpha} + O(1)$ iterations suffice.

4.3 Low-Arboricity Case

The following lemma proves the last two running time bounds of Theorem 1.3, completing its proof. Recall that by Theorem 1.1 we can assume that our graph has remaining degree $\text{poly}(\lambda)$.

Lemma 4.2. *There is a deterministic low-memory MPC algorithm that computes an MIS and an MM of G in time $O(\lambda^{2+\varepsilon} + \log \log n)$ and $O(\lambda^{1+\varepsilon} + \log \log n)$, respectively, for any constant $\varepsilon > 0$, using linear total space. The same algorithm runs in time $O(\log \log n)$ when λ is $O(\log^{1/2-\delta} \log n)$ and $O(\log^{1-\delta} \log n)$, respectively, for any constant $\delta > 0$.*

Proof. We first compute a degree $d = (\lambda^{1+\varepsilon})$ H -partition of the remaining graph G in $O(\log \log n)$ rounds. Let k be the largest integer such that $\Delta^{2^k} \leq n^{\alpha}$, where $\Delta = \text{poly}(\lambda)$. For $i = 0, \dots, k+O(1)$:

- a) Nodes simulate $s \cdot 2^i$ rounds of the H -partition algorithm for suff. large $s = O(1)$.
- b) If $i < k$, then each node performs one step of graph exponentiation.

The correctness and runtime and memory bounds of the above MPC H -partition algorithm follow from [BFU18, Lemma 4.2], which is based on the observation that a $\Omega(\Delta)$ progress is achieved in $t = O(1)$ LOCAL rounds by the properties of the H -partition. The MIS result follows from computing a $d^2 = O(\lambda^{2+\varepsilon})$ coloring in $O(\log^* n)$ rounds by applying the algorithm ARB-LINIAL'S COLORING of Barenboim and Elkin [BE10]. For the MM case, the d forest-decomposition produced by the H -partition is given in input to the maximal matching algorithm by Panconesi and Rizzi [PR01], which runs in $O(d) = O(\lambda^{1+\varepsilon})$ rounds. \square

5 Deterministic Arb-Coloring via All-to-All Communication

In this section, we study the complexity of deterministic arboricity-dependent coloring in all-to-all communication models, specifically, CONGESTED-CLIQUE and linear-memory MPC, where each machine has $O(n)$ memory. In these models, Czumaj, Davis, and Parter [CDP20] give a deterministic algorithm that solves $(\Delta + 1)$ coloring, and its list-coloring variant, in $O(1)$ time. Henceforth, we refer to it as CDP’s algorithm. Towards our constant-round arboricity-dependent coloring algorithm, in the next corollary, we show that CDP’s algorithm provides a $O(\lambda)$ coloring of λ -arboricity graphs in $O(\log \lambda)$ rounds and a coloring with $O(\lambda^{1+\varepsilon})$ colors in $O(1)$ time.

Corollary 5.1. *Given a graph G with arboricity λ and a parameter d satisfying $2\lambda < d \leq \lambda^{1+\varepsilon}$, for constant $\varepsilon > 0$, a legal $O(d)$ vertex coloring of G can be computed deterministically in $O(\log_{d/\lambda} \lambda)$ rounds of CONGESTED-CLIQUE and linear-memory MPC with optimal global memory.*

Proof. The algorithm consists of three stages. The first stage computes the first $L = O(\log_{d/\lambda} \lambda)$ layers of the H -partition of G with degree d , and removes nodes in these L layers from the graph. The number of remaining nodes whose index layer is higher than L is at most $(\lambda/d)^L \cdot n$ by the definition of the H -partition. Therefore, at most $\lambda \cdot (\frac{\lambda}{d})^L n = O(n)$ edges remain and the remaining graph can be gathered in a single machine and colored with $d + 1$ colors locally. The second stage of the algorithm colors vertices in layers $L, \dots, 2$ in a sequential fashion using d additional colors. Consider an arbitrary layer $\ell \in [2, L]$. Each node has a palette of $2d + 1$ colors and at most d neighbors already colored. Let each node discard colors blocked by its neighbors and observe that layer ℓ induces an instance of $(\Delta + 1)$ -list coloring solvable in $O(1)$ rounds by CDP’s algorithm. The global memory required to store the color palettes is $n_\ell \cdot O(d)$, where n_ℓ is the number of nodes in layer ℓ . Since $n_\ell \leq \frac{\lambda n}{d}$ for $\ell \geq 2$, the algorithm requires $\frac{\lambda n}{d} \cdot O(d) = O(m)$ total space. In the third stage of the algorithm, we color nodes in the first layer using the constant-round $(\Delta + 1)$ -coloring algorithm of CDP and a fresh palette of $d + 1$ colors, so that the global memory remains linear. The final coloring is a legal vertex coloring with $3d + 2 = O(d)$ colors, as desired. \square

Next, we prove the main result of this section and its extension to CONGESTED-CLIQUE.

Theorem 1.4. *Given a graph G with arboricity λ , a legal $O(\lambda)$ vertex coloring of G can be computed deterministically in $O(1)$ on a linear-memory MPC using $n \cdot \text{poly}(\lambda)$ global memory.*

The first step of the algorithm is a preprocessing step. We compute the first $L = O(1)$ layers of the H -partition of G with degree $\Delta \stackrel{\text{def}}{=} \lambda^{1+\delta}$, for $0 < \delta \leq \frac{2\varepsilon}{1-2\varepsilon}$. The number of edges induced by unlayered nodes is at most $O(n)$ by arboricity properties. Thus, we can gather and color unlayered vertices with 2λ colors onto a single machine. In the rest of the algorithm, we discuss how to color the subgraph H_j induced by the j -th layer, for $j \in [L]$, with a fresh palette of $O(\lambda)$ colors.

To color each remaining layer we perform a graph partitioning routine. Vertices are randomly partitioned in many subgraphs B_1, \dots, B_ℓ of maximum *out*-degree $O(\frac{\lambda}{\ell})$ and size $O(\frac{n}{\ell})$. We show that such a partition exists by using the concept of pessimistic estimators. Then, a good partition is found by defining the global quality of a partition as a function of quantities computable by individual machines. However, doing so requires two steps. First, we select among all possible partitions those whose parts have *all* linear size. Second, for each partition, we locally check how many *bad nodes* are in each of its parts and sum these numbers up to find a good partition. Once a good partition is found, each of its ℓ subgraphs can be $O(\frac{\lambda}{\ell})$ -colored while the subgraph induced by bad nodes can be colored with 2λ colors.

The Graph Partitioning Algorithm:: Let $\ell = \lambda^{0.6}$ be a parameter. The partition $V = B_1 \cup \dots \cup B_\ell$ is obtained placing each node v in a part selected according to a k -wise independent

random choice. Denote $\text{deg}_B^{\text{out}}(v)$ as the outdegree of vertex v in the subgraph induced by the vertices $B \subseteq V$. We require that the output of the partitioning algorithm satisfies the following two properties. For the sake of the analysis, let us imagine that we are given an orientation of the edges of G with outdegree 2λ .

i) Size of Each Part Bin i in $[\ell]$ is *good* if $|B_i| = O(\frac{n}{\ell})$. Observe that $\mathbb{E}[|B_i|] = \frac{n}{\ell} = \Omega(n^{0.4})$. Consequently, the probability that $|B_i|$ is at most $2 \cdot \mathbb{E}[|B_i|]$ is upper bounded by n^{-3} , for $k \geq 16$, by applying [Lemma B.5](#) with X_1, \dots, X_n as i.r.v. for the events that the i -th vertex is in B_i . By a union bound over ℓ bins, with probability at least $1 - n^{-2}$, all bins contain fewer than $\frac{2n}{\ell}$ nodes.

ii) Outdegree of Each Vertex: A node v in bin i is *good* if $\text{deg}_{B_i}^{\text{out}}(v) = O(\frac{\lambda}{\ell})$. It is required that all $v \in V$ but at most n/λ^3 nodes are good in expectation. We apply [Lemma B.5](#) with $X_1, \dots, X_{\text{deg}^{\text{out}}(v)}$ as i.r.v. for the events that each outneighbor of v is placed in the same bin as v . These variables are $(k-1)$ -wise independent and each has expectation ℓ^{-1} . Accordingly, the expected outdegree $\mathbb{E}[X]$ of v is at most $\frac{2\lambda}{\ell} = \Omega(\lambda^{0.4})$. Therefore, its outdegree is larger than $\frac{4\lambda}{\ell}$ with probability less than λ^{-3} , for $k \geq 17$, and we can conclude the required property.

Finding a Good Partition:: Let \mathcal{H} be a k -wise independent family of hash functions $h: [n] \mapsto [\ell]$. Each hash function h induces a partition of the graph into ℓ parts $B_1(h), \dots, B_\ell(h)$. Similarly to [\[CDP20\]](#), we analyze the likelihood that a randomly chosen hash function h induces any bad bin and many bad nodes by defining the following pessimistic estimator $P(h)$:

$$P(h) = |\{\text{bad nodes under } h\}| + |\{\text{bad bins under } h\}| \cdot n.$$

Combining the bounds from the previous paragraph gives:

$$\mathbb{E}[P(h)] = \mathbb{E}[|\{\text{bad nodes}\}|] + \mathbb{E}[|\{\text{bad bins}\}|] \cdot n \leq \frac{n}{\lambda^3} + \frac{1}{n} \leq \frac{2n}{\lambda^3}.$$

Therefore, by the probabilistic method, there is one hash function h^* that gives no bad bins and at most $\frac{2n}{\lambda^3}$ bad nodes. However, $P(h)$ cannot be easily computed without the orientation used for the analysis. Due to that, we relax the above conditions and identify first a subset $\mathcal{H}' \subseteq \mathcal{H}$ such that $h^* \in \mathcal{H}'$ and each $h \in \mathcal{H}'$ gives a graph partitioning in which each subgraph has size $O(n)$. Second, we find a good partitioning by analyzing each hash function, i.e., induced subgraph, concurrently.

i) Select Candidate Functions Observe that h^* is in \mathcal{H}' . Indeed, the bound on the size of each part together with the bound on the outdegree of each vertex gives

$$|E(G[B_i(h)])| = \sum_{v \in B_i(h)} \text{deg}_{B_i(h)}(v) \leq \frac{2n}{\ell} \cdot \frac{4\lambda}{\ell} + \frac{2n}{\lambda^3} \cdot \Delta = O(n).$$

To deterministically find \mathcal{H}' , we assign each hash function $h \in \mathcal{H}$ to a machine x_h . Let each node compute its degree under h and send it to x_h . The machine x_h is then able to determine whether each subgraph induced by h has size $O(n)$ by summing up the degrees of vertices in each particular bin. This process requires a total space of $O(\lambda n |\mathcal{H}|)$.

ii) Find a Good Partitioning For every $h \in \mathcal{H}'$ and $i \in [\ell]$, we compute a $\frac{10\lambda}{\ell}$ -coloring of the subgraph $G[B_i(h)]$ and sum up the number of nodes that remain uncolored after this coloring step across all bins for each h . We prove that there is a function $h^* \in \mathcal{H}'$ that leaves only $O(n/\lambda)$ nodes

uncolored, which can be colored locally with a new palette of size 2λ . Since $|G[B_i(h)]| = O(n)$, this computation can be run offline for each subgraph on a single machine with $O(\lambda n |\mathcal{H}|)$ total space.

Consider a subgraph $G[B_i(h)]$ for $h \in \mathcal{H}'$. This subgraph may have both good and bad nodes. We run the H -partition algorithm with degree $d = \frac{10\lambda}{\ell} - 1$ until when there is no vertex of degree at most d left. Once this process finishes, we obtain a partial H -partition \mathcal{X} of $B_i(h)$ that can be $(d+1)$ -colored. Then, nodes in $B'_i(h) \stackrel{\text{def}}{=} B_i(h) \setminus \mathcal{X}$ induce an uncolored subgraph of minimum degree at least $d+1$. This implies that $|E(G[B'_i(h)])| \geq \frac{5\lambda}{\ell} \cdot |B'_i(h)|$. On the other hand, good nodes in $B'_i(h)$ contribute with at most $\frac{4\lambda}{\ell} \cdot |B'_i(h)|$ edges and bad nodes with at most $\frac{2n}{\lambda^3} \cdot \Delta$ edges. Thus,

$$\frac{5\lambda}{\ell} \cdot |B'_i(h)| \leq \frac{4\lambda}{\ell} \cdot |B'_i(h)| + \frac{2n}{\lambda^3} \cdot \Delta \iff |B'_i(h)| \leq \frac{2\ell\Delta n}{\lambda^4} \leq \frac{n}{\lambda^2},$$

which proves the existence of such good $h^* \in \mathcal{H}'$. We then find a partition whose bins can be $\frac{10\lambda}{\ell}$ -colored (with different palettes) leaving at most $\ell \cdot \frac{n}{\lambda^2}$ nodes uncolored across all parts. Hence, uncolored vertices induce $\lambda \cdot \frac{\ell n}{\lambda^2} = O(n)$ edges in the original graph.

Reducing the Total Space: The total space requirement of $O(\lambda n |\mathcal{H}|)$ can be made on the order of $n \cdot \text{poly}(\lambda)$ by reducing the size of \mathcal{H} to be polynomial in the arboricity. To this end, we first note that w.l.o.g. one can assume that $\lambda \leq n^{\frac{1}{2}-\varepsilon}$, for any constant ε , $0 < \varepsilon < \frac{1}{2}$, as otherwise $\text{poly}(n) = \text{poly}(\lambda)$. Second, we observe that k -wise independence is required only among the random variables associated with vertices that share a neighbor. An assignment of nodes to IDs such that no two nodes with a shared neighbor are assigned the same ID corresponds to a legal coloring of the subgraph H_j^2 . In the subgraph H_j^2 , each vertex has degree at most $\Delta^2 = \lambda^{2+2\delta} = O(n)$, by our choice of δ and the assumption that $\lambda \leq n^{\frac{1}{2}-\varepsilon}$. Applying CDP's algorithm in parallel on each H_j^2 provides a $\text{poly}(\lambda)$ coloring in $O(1)$ time, as desired.

We extend the near-linear MPC coloring algorithm to CONGESTED-CLIQUE as follows.

Corollary 5.2. *When $\lambda = O(n^\delta)$, for some constant δ such that the $n \cdot \text{poly}(\lambda)$ -global memory usage of [Theorem 1.4](#) can be made on the order of n^2 , then the same result can be achieved in CONGESTED-CLIQUE.*

Proof. This result follows from the equivalence between linear-memory MPC and CONGESTED-CLIQUE. Specifically, each MPC step can be simulated in a constant number of CONGESTED-CLIQUE rounds using Lenzen's routing [[Len13](#)]. Since each of the n nodes in CONGESTED-CLIQUE can communicate up to $O(n)$ words and our algorithm uses $O(n^2)$ total memory by the assumption on λ , then [Theorem 1.4](#) can be run in CONGESTED-CLIQUE. \square

References

- [ABI86] Noga Alon, László Babai, and Alon Itai. A fast and simple randomized parallel algorithm for the maximal independent set problem. *Journal of Algorithms*, 7(4):567–583, 1986.
- [AS16] Noga Alon and Joel H Spencer. *The probabilistic method*. John Wiley & Sons, 2016.
- [BBD⁺19] Soheil Behnezhad, Sebastian Brandt, Mahsa Derakhshan, Manuela Fischer, MohammadTaghi Hajiaghayi, Richard M. Karp, and Jara Uitto. Massively parallel computation of matching and mis in sparse graphs. In *Proceedings of the 2019 ACM Sym-*

- posium on Principles of Distributed Computing*, PODC '19, page 481–490, New York, NY, USA, 2019. Association for Computing Machinery.
- [BDE⁺19] Soheil Behnezhad, Laxman Dhulipala, Hossein Esfandiari, Jakub Lacki, and Vahab Mirrokni. Near-optimal massively parallel graph connectivity. In *2019 IEEE 60th Annual Symposium on Foundations of Computer Science (FOCS)*, pages 1615–1636, 2019.
- [BDH18] Soheil Behnezhad, Mahsa Derakhshan, and MohammadTaghi Hajiaghayi. Brief announcement: Semi-mapreduce meets congested clique. *CoRR*, abs/1802.10297, 2018.
- [BE10] Leonid Barenboim and Michael Elkin. Sublogarithmic distributed mis algorithm for sparse graphs using nash-williams decomposition. *Distributed Computing*, 22(5):363–379, 2010.
- [BE11] Leonid Barenboim and Michael Elkin. Deterministic distributed vertex coloring in polylogarithmic time. *J. ACM*, 58(5), 2011.
- [BE13] Leonid Barenboim and Michael Elkin. Distributed graph coloring: Fundamentals and recent developments. *Synthesis Lectures on Distributed Computing Theory*, 4(1):1–171, 2013.
- [BEPS16] Leonid Barenboim, Michael Elkin, Seth Pettie, and Johannes Schneider. The locality of distributed symmetry breaking. *J. ACM*, 63(3), 6 2016.
- [BFU18] Sebastian Brandt, Manuela Fischer, and Jara Uitto. Matching and MIS for uniformly sparse graphs in the low-memory MPC model. *CoRR*, abs/1807.05374, 2018.
- [BFU19] Sebastian Brandt, Manuela Fischer, and Jara Uitto. Breaking the linear-memory barrier in MPC: Fast MIS on trees with strongly sublinear memory. In Keren Censor-Hillel and Michele Flammini, editors, *Structural Information and Communication Complexity*, pages 124–138, Cham, 2019. Springer International Publishing.
- [BK18] Leonid Barenboim and Victor Khazanov. Distributed symmetry-breaking algorithms for congested cliques. In Fedor V. Fomin and Vladimir V. Podolskii, editors, *Computer Science – Theory and Applications*, pages 41–52, Cham, 2018. Springer International Publishing.
- [BKM20] Philipp Bamberger, Fabian Kuhn, and Yannic Maus. Efficient deterministic distributed coloring with small bandwidth. In *Proceedings of the 39th Symposium on Principles of Distributed Computing*, PODC '20, page 243–252, New York, NY, USA, 2020. Association for Computing Machinery.
- [BR94] M. Bellare and J. Rompel. Randomness-efficient oblivious sampling. In *Proceedings 35th Annual Symposium on Foundations of Computer Science*, pages 276–287, 1994.
- [CC22] Sam Coy and Artur Czumaj. Deterministic massively parallel connectivity. In *Proceedings of the 54th Annual ACM SIGACT Symposium on Theory of Computing*, STOC 2022, page 162–175, New York, NY, USA, 2022. Association for Computing Machinery.
- [CDP20] Artur Czumaj, Peter Davies, and Merav Parter. Simple, deterministic, constant-round coloring in the congested clique. In *Proceedings of the 39th Symposium on Principles of Distributed Computing*, PODC '20, page 309–318, New York, NY, USA, 2020. Association for Computing Machinery.

- [CDP21a] Artur Czumaj, Peter Davies, and Merav Parter. Component stability in low-space massively parallel computation. In *Proceedings of the 2021 ACM Symposium on Principles of Distributed Computing*, PODC’21, page 481–491, New York, NY, USA, 2021. Association for Computing Machinery.
- [CDP21b] Artur Czumaj, Peter Davies, and Merav Parter. Graph sparsification for derandomizing massively parallel computation with low space. *ACM Trans. Algorithms*, 17(2), 5 2021.
- [CDP21c] Artur Czumaj, Peter Davies, and Merav Parter. Improved deterministic ($\delta+1$) coloring in low-space mpc. In *Proceedings of the 2021 ACM Symposium on Principles of Distributed Computing*, PODC’21, page 469–479, New York, NY, USA, 2021. Association for Computing Machinery.
- [CFG⁺19] Yi-Jun Chang, Manuela Fischer, Mohsen Ghaffari, Jara Uitto, and Yufan Zheng. The complexity of ($\delta+1$) coloring in congested clique, massively parallel computation, and centralized local computation. In *Proceedings of the 2019 ACM Symposium on Principles of Distributed Computing*, PODC ’19, page 471–480, New York, NY, USA, 2019. Association for Computing Machinery.
- [CG89] Benny Chor and Oded Goldreich. On the power of two-point based sampling. *Journal of Complexity*, 5(1):96–106, 1989.
- [CHPS20] Keren Censor-Hillel, Merav Parter, and Gregory Schwartzman. Derandomizing local distributed algorithms under bandwidth restrictions. *Distributed Computing*, 33(3):349–366, Jun 2020.
- [CLM⁺18] Artur Czumaj, Jakub Lacki, Aleksander Madry, Slobodan Mitrović, Krzysztof Onak, and Piotr Sankowski. Round compression for parallel matching algorithms. In *Proceedings of the 50th Annual ACM SIGACT Symposium on Theory of Computing*, STOC 2018, page 471–484, New York, NY, USA, 2018. Association for Computing Machinery.
- [CW79] J. Lawrence Carter and Mark N. Wegman. Universal classes of hash functions. *Journal of Computer and System Sciences*, 18(2):143–154, 1979.
- [DG08] Jeffrey Dean and Sanjay Ghemawat. Mapreduce: Simplified data processing on large clusters. *Commun. ACM*, 51(1):107–113, 1 2008.
- [EFF85] Paul Erdős, Peter Frankl, and Zoltán Füredi. Families of finite sets in which no set is covered by the union of r others. *Israel J. Math*, 51(1-2):79–89, 1985.
- [EGL⁺98] Guy Even, Oded Goldreich, Michael Luby, Noam Nisan, and Boban Veličković. Efficient approximation of product distributions. *Random Structures & Algorithms*, 13(1):1–16, 1998.
- [FGG22] Manuela Fischer, Jeff Giliberti, and Christoph Grunau. Improved Deterministic Connectivity in Massively Parallel Computation. In Christian Scheideler, editor, *36th International Symposium on Distributed Computing (DISC 2022)*, volume 246 of *Leibniz International Proceedings in Informatics (LIPIcs)*, pages 22:1–22:17, Dagstuhl, Germany, 2022. Schloss Dagstuhl – Leibniz-Zentrum für Informatik.
- [Fis21] Manuela Fischer. *Local Algorithms for Classic Graph Problems*. Doctoral thesis, ETH Zurich, Zurich, 2021.

- [FMS⁺10] Jon Feldman, S. Muthukrishnan, Anastasios Sidiropoulos, Cliff Stein, and Zoya Svitkina. On distributing symmetric streaming computations. *ACM Trans. Algorithms*, 6(4), 9 2010.
- [GGJ20] Mohsen Ghaffari, Christoph Grunau, and Ce Jin. Improved MPC Algorithms for MIS, Matching, and Coloring on Trees and Beyond. In Hagit Attiya, editor, *34th International Symposium on Distributed Computing (DISC 2020)*, volume 179 of *Leibniz International Proceedings in Informatics (LIPIcs)*, pages 34:1–34:18, Dagstuhl, Germany, 2020. Schloss Dagstuhl–Leibniz-Zentrum für Informatik.
- [GGK⁺18] Mohsen Ghaffari, Themis Gouleakis, Christian Konrad, Slobodan Mitrović, and Ronitt Rubinfeld. Improved massively parallel computation algorithms for mis, matching, and vertex cover. In *Proceedings of the 2018 ACM Symposium on Principles of Distributed Computing*, PODC '18, page 129–138, New York, NY, USA, 2018. Association for Computing Machinery.
- [Gha16] Mohsen Ghaffari. An improved distributed algorithm for maximal independent set. In *Proceedings of the 2016 Annual ACM-SIAM Symposium on Discrete Algorithms (SODA)*, pages 270–277, 2016.
- [GKU19] Mohsen Ghaffari, Fabian Kuhn, and Jara Uitto. Conditional hardness results for massively parallel computation from distributed lower bounds. In *2019 IEEE 60th Annual Symposium on Foundations of Computer Science (FOCS)*, pages 1650–1663, 2019.
- [GL17] Mohsen Ghaffari and Christiana Lymouri. Simple and Near-Optimal Distributed Coloring for Sparse Graphs. In Andréa W. Richa, editor, *31st International Symposium on Distributed Computing (DISC 2017)*, volume 91 of *Leibniz International Proceedings in Informatics (LIPIcs)*, pages 20:1–20:14, Dagstuhl, Germany, 2017. Schloss Dagstuhl–Leibniz-Zentrum fuer Informatik.
- [Goo99] Michael T. Goodrich. Communication-efficient parallel sorting. *SIAM Journal on Computing*, 29(2):416–432, 1999.
- [GS19] Mohsen Ghaffari and Ali Sayyadi. Distributed Arboricity-Dependent Graph Coloring via All-to-All Communication. In Christel Baier, Ioannis Chatzigiannakis, Paola Flocchini, and Stefano Leonardi, editors, *46th International Colloquium on Automata, Languages, and Programming (ICALP 2019)*, volume 132 of *Leibniz International Proceedings in Informatics (LIPIcs)*, pages 142:1–142:14, Dagstuhl, Germany, 2019. Schloss Dagstuhl–Leibniz-Zentrum fuer Informatik.
- [GSZ11] Michael T. Goodrich, Nodari Sitchinava, and Qin Zhang. Sorting, searching, and simulation in the mapreduce framework. In Takao Asano, Shin-ichi Nakano, Yoshio Okamoto, and Osamu Watanabe, editors, *Algorithms and Computation*, pages 374–383, Berlin, Heidelberg, 2011. Springer Berlin Heidelberg.
- [GU19] Mohsen Ghaffari and Jara Uitto. Sparsifying distributed algorithms with ramifications in massively parallel computation and centralized local computation. In *Proceedings of the 2019 Annual ACM-SIAM Symposium on Discrete Algorithms (SODA)*, pages 1636–1653, 2019.

- [HP15] James W. Hegeman and Sriram V. Pemmaraju. Lessons from the congested clique applied to mapreduce. *Theoretical Computer Science*, 608:268–281, 2015. Structural Information and Communication Complexity.
- [II86] Amos Israeli and A. Itai. A fast and simple randomized parallel algorithm for maximal matching. *Information Processing Letters*, 22(2):77–80, 1986.
- [KPP20] Kishore Kothapalli, Shreyas Pai, and Sriram V. Pemmaraju. Sample-And-Gather: Fast Ruling Set Algorithms in the Low-Memory MPC Model. In Nitin Saxena and Sunil Simon, editors, *40th IARCS Annual Conference on Foundations of Software Technology and Theoretical Computer Science (FSTTCS 2020)*, volume 182 of *Leibniz International Proceedings in Informatics (LIPIcs)*, pages 28:1–28:18, Dagstuhl, Germany, 2020. Schloss Dagstuhl–Leibniz-Zentrum für Informatik.
- [KSV10] Howard Karloff, Siddharth Suri, and Sergei Vassilvitskii. A model of computation for mapreduce. In *Proceedings of the 2010 Annual ACM-SIAM Symposium on Discrete Algorithms (SODA)*, pages 938–948, 2010.
- [KSV13] Amos Korman, Jean-Sébastien Sereni, and Laurent Viennot. Toward more localized local algorithms: removing assumptions concerning global knowledge. *Distributed Computing*, 26(5):289–308, 2013.
- [Kuh09] Fabian Kuhn. Weak graph colorings: Distributed algorithms and applications. In *Proceedings of the Twenty-First Annual Symposium on Parallelism in Algorithms and Architectures, SPAA '09*, page 138–144, New York, NY, USA, 2009. Association for Computing Machinery.
- [Len13] Christoph Lenzen. Optimal deterministic routing and sorting on the congested clique. In *Proceedings of the 2013 ACM Symposium on Principles of Distributed Computing, PODC '13*, page 42–50, New York, NY, USA, 2013. Association for Computing Machinery.
- [Lin92] Nathan Linial. Locality in distributed graph algorithms. *SIAM Journal on Computing*, 21(1):193–201, 1992.
- [LPSP05] Zvi Lotker, Boaz Patt-Shamir, Elan Pavlov, and David Peleg. Minimum-weight spanning tree construction in $o(\log \log n)$ communication rounds. *SIAM Journal on Computing*, 35(1):120–131, 2005.
- [LU21] Rustam Latypov and Jara Uitto. Deterministic 3-coloring of trees in the sublinear MPC model. *CoRR*, abs/2105.13980, 2021.
- [Lub85] M Luby. A simple parallel algorithm for the maximal independent set problem. In *Proceedings of the Seventeenth Annual ACM Symposium on Theory of Computing, STOC '85*, page 1–10, New York, NY, USA, 1985. Association for Computing Machinery.
- [Lub93] Michael Luby. Removing randomness in parallel computation without a processor penalty. *Journal of Computer and System Sciences*, 47(2):250–286, 1993.
- [LW06] Michael Luby and Avi Wigderson. Pairwise independence and derandomization. *Foundations and Trends in Theoretical Computer Science*, 1(4):237–301, 2006.

- [LW10] Christoph Lenzen and Roger Wattenhofer. Brief announcement: Exponential speed-up of local algorithms using non-local communication. In *Proceedings of the 29th ACM SIGACT-SIGOPS Symposium on Principles of Distributed Computing*, PODC '10, page 295–296, New York, NY, USA, 2010. Association for Computing Machinery.
- [MR95] Rajeev Motwani and Prabhakar Raghavan. *Randomized algorithms*. Cambridge university press, 1995.
- [MSN94] Rajeev Motwani, Joseph (Seffi) Naor, and Moni Naor. The probabilistic method yields deterministic parallel algorithms. *Journal of Computer and System Sciences*, 49(3):478–516, 1994. 30th IEEE Conference on Foundations of Computer Science.
- [NW61] C. St.J. A. Nash-Williams. Edge-Disjoint Spanning Trees of Finite Graphs. *Journal of the London Mathematical Society*, s1-36(1):445–450, 01 1961.
- [NW64] C. St.J. A. Nash-Williams. Decomposition of Finite Graphs Into Forests. *Journal of the London Mathematical Society*, s1-39(1):12–12, 01 1964.
- [Par18] Merav Parter. (Delta+1) Coloring in the Congested Clique Model. In Ioannis Chatzigiannakis, Christos Kaklamanis, Dániel Marx, and Donald Sannella, editors, *45th International Colloquium on Automata, Languages, and Programming (ICALP 2018)*, volume 107 of *Leibniz International Proceedings in Informatics (LIPIcs)*, pages 160:1–160:14, Dagstuhl, Germany, 2018. Schloss Dagstuhl–Leibniz-Zentrum fuer Informatik.
- [PP22] Shreyas Pai and Sriram V. Pemmaraju. Brief announcement: Deterministic massively parallel algorithms for ruling sets. In *Proceedings of the 2022 ACM Symposium on Principles of Distributed Computing*, PODC'22, page 366–368, New York, NY, USA, 2022. Association for Computing Machinery.
- [PR01] Alessandro Panconesi and Romeo Rizzi. Some simple distributed algorithms for sparse networks. *Distributed computing*, 14(2):97–100, 2001.
- [PS18] Merav Parter and Hsin-Hao Su. Randomized (Delta+1)-Coloring in $O(\log^* \Delta)$ Congested Clique Rounds. In Ulrich Schmid and Josef Widder, editors, *32nd International Symposium on Distributed Computing (DISC 2018)*, volume 121 of *Leibniz International Proceedings in Informatics (LIPIcs)*, pages 39:1–39:18, Dagstuhl, Germany, 2018. Schloss Dagstuhl–Leibniz-Zentrum fuer Informatik.
- [Rag88] Prabhakar Raghavan. Probabilistic construction of deterministic algorithms: Approximating packing integer programs. *Journal of Computer and System Sciences*, 37(2):130–143, 1988.
- [WC79] Mark N. Wegman and J. Lawrence Carter. New classes and applications of hash functions. In *20th Annual Symposium on Foundations of Computer Science (sfcs 1979)*, pages 175–182, 1979.
- [ZCF⁺10] Matei Zaharia, Mosharaf Chowdhury, Michael J. Franklin, Scott Shenker, and Ion Stoica. Spark: Cluster computing with working sets. In *Proceedings of the 2nd USENIX Conference on Hot Topics in Cloud Computing*, HotCloud'10, page 10, USA, 2010. USENIX Association.

A Arboricity Properties of Graphs and H-partition

The notion of arboricity characterizes the sparsity of a graph. It is equal to the minimum number of forests into which the edge set of the graph can be partitioned. Nash-Williams [NW61, NW64] showed that the arboricity equals the density of the graph, i.e., the ratio of the number of edges to that of nodes in any subgraph.

Lemma A.1 ([BE13, BEPS16]). *Let G be a graph of m edges, n nodes, and arboricity λ . Then*

- a) $m < \lambda n$.
- b) *The arboricity of any subgraph $G' \subseteq G$ is at most λ .*
- c) *The number of nodes with degree at least $t \geq \lambda + 1$ is less than $\lambda n / (t - \lambda)$.*
- d) *The number of edges whose endpoints both have degree at least $t \geq \lambda + 1$ is less than $\lambda m / (t - \lambda)$.*

Definition A.2 (*H-Partition*). *An H-partition \mathcal{H} of a λ -arboricity graph G parameterized by its degree d , for any $d > 2\lambda$, is a partition of the vertices of G into layers H_1, \dots, H_L such that every vertex $v \in H_i$ has at most d neighbors in layers with indexes equal to or higher than i , i.e., $\bigcup_{j=i}^L L_j$.*

There is a simple distributed algorithm to construct an H -partition. Each layer is computed in a constant number of rounds by applying the classical greedy peeling algorithm as follows: Repeatedly, vertices of remaining degree at most d are peeled off from the graph and form a new layer. Since the number of vertices of degree larger than d is at most $\frac{2\lambda}{d} \cdot n$, the size L of \mathcal{H} , i.e., the overall number of layers, is at most $\left\lceil \log_{d/2\lambda} n \right\rceil = O(\log_{\frac{d}{2\lambda}} n)$. Given an H -partition, a d forest decomposition, i.e., an acyclic orientation of the edges such that every vertex has outdegree at most d , can be obtained as follows. An edge (u, v) is oriented toward the vertex with a higher index layer in the given H -partition or, if they are in the same layer, toward the vertex with a greater ID. By construction, the orientation is acyclic and each vertex has at most d outneighbors. Now, let each node v assign a distinct label from the set $\{1, \dots, d\}$ to each of its outgoing edges. The set of edges labeled by label i forms a forest. For a more detailed proof, we refer to [BE13].

Remark A.3. *While our algorithms may seem to require knowing λ , by employing the standard technique of [KSV13] to run the algorithm with doubly-exponentially increasing estimates for λ in parallel, combined with global communication, we can find an estimate for λ that produces the same asymptotic result incurring only a $\tilde{O}(1)$ factor overhead in the global space and total computation.*

B Derandomization via All-to-All Communication

A k -wise independent family of hash functions is defined as follows:

Definition B.1 (*k-wise independence*). *Let $N, k, \ell \in \mathbb{N}$ with $k \leq N$. A family of hash functions $\mathcal{H} = \{h : [N] \rightarrow \{0, 1\}^\ell\}$ is k -wise independent if for all $I \subseteq \{1, \dots, n\}$ with $|I| \leq k$, the random variables $X_i := h(i)$ ¹ with $i \in I$ are independent and uniformly distributed in $\{0, 1\}^\ell$, when h is chosen uniformly at random from \mathcal{H} . If $k = 2$ then \mathcal{H} is called pairwise independent.*

Given a randomized process that works under k -wise independence, we apply the following lemma to construct a k -wise independent family of hash functions \mathcal{H} .

¹ $h(\cdot)$ denotes the length- ℓ bit sequence by the corresponding integer in $\{0, \dots, 2^\ell - 1\}$.

Lemma B.2 ([ABI86, CG89, EGL⁺98]). *For every $N, k, \ell \in \mathbb{N}$, there is a family of k -wise independent hash functions $\mathcal{H} = \{h : [N] \rightarrow \{0, 1\}^\ell\}$ such that choosing a uniformly random function h from \mathcal{H} takes at most $k(\ell + \log N) + O(1)$ random bits, and evaluating a function from \mathcal{H} takes time $\text{poly}(\ell, \log N)$ time.*

For a more systematic treatment of limited independence and its applications, we refer the reader to [AS16, CW79, LW06, MR95, Rag88, WC79]. We now define an objective function that is a sum of functions calculable by individual machines and is at least (or at most) some value Q . Its expected value over the choice of a random hash function $h \in \mathcal{H}$ is then

$$\mathbb{E}_{h \in \mathcal{H}} \left[q(h) \stackrel{\text{def}}{=} \sum_{\text{machines } x} q_x(h) \right] \geq Q.$$

By the probabilistic method, this implies the existence of a hash function $h^* \in \mathcal{H}$ for which $q(h^*)$ is at least (or at most) Q . If the family of hash functions fits into the memory of a single machine, then each machine x can locally compute $q(h)$ (which is a function of the vertices that machine x is assigned) for each h . Then, we sum the values $q(h)$ computed by every machine for each h and find one good hash function h^* in $O(1)$ MPC rounds. When the family of hash functions cannot be collected onto a single machine but its size is $\text{poly}(n)$, i.e., each function can be specified using $O(\log n)$ bits, we can still find one good hash function in $O(1)$ MPC rounds as follows.

Let $\tau = O(\log n)$ denote the length of the random seed and $\chi = \log \mathbf{S} = \alpha \log n$. We proceed in $\left\lceil \frac{\tau}{\chi} \right\rceil$ iterations. We search for a good function h^* by having machines agree on a χ -bit chunk at a time. Let $\mathcal{H}^{(i)}$ be the subset of hash functions from \mathcal{H} considered at iteration i . Clearly, $\mathcal{H}^{(0)} = \mathcal{H}$ and $\mathcal{H}^{(i)} \supseteq \mathcal{H}^{(i+1)}$. We will ensure that $\mathbb{E}_{h \in \mathcal{H}^{(i)}} [q(h)] \geq \mathbb{E}_{h \in \mathcal{H}^{(i-1)}} [q(h)]$ until $\mathcal{H}^{(i)}$ consists of a single element defining h^* . In phase i , for $1 \leq i \leq \left\lceil \frac{\tau}{\chi} \right\rceil$, we determine $\mathcal{H}^{(i)}$ by fixing the bits at positions $1 + (i-1) \left\lceil \frac{\tau}{\chi} \right\rceil, \dots, i \left\lceil \frac{\tau}{\chi} \right\rceil$. We assume that each machine knows the prefix \mathbf{b} chosen in previous iterations. Next, each machine considers the extension of \mathbf{b} by all possible seeds of length χ . Let $\mathcal{H}_1, \dots, \mathcal{H}_{2^\chi}$ be a partition of $\mathcal{H}^{(i-1)}$ such that \mathcal{H}_j contains all hash functions $h \in \mathcal{H}^{(i-1)}$ whose bit sequence consists of \mathbf{b} as prefix followed by the bit representation b_j of j .

For every \mathcal{H}_j , each machine computes locally $\mathbb{E}_{h \in \mathcal{H}_j} [q(h)]$ for all $1 \leq j \leq 2^\chi$. This computation can be performed *locally* by taking each hash function $h \in \mathcal{H}_j$ and computing $q_x(h)$, which is the target function for the nodes (or edges) that machine x is responsible for. Once we know $q_x(h)$ for every $h \in \mathcal{H}_j$, then $\mathbb{E}_{h \in \mathcal{H}_j} [q_x(h)]$ is simply the average of all these numbers. A more efficient way to compute $\mathbb{E}_{h \in \mathcal{H}_j} [q_x(h)]$ is by letting each machine compute the expected value of $q_x(h)$ for each of its vertices (or edges) conditioned on $\mathbf{b} \circ b_j$ (note that each node u can compute this probability if it depends only on its neighbors and, by knowing their IDs, u can simulate their choices). Using [Lemma 2.1](#), we compute $\sum_{\text{machines } x} \mathbb{E}_{h \in \mathcal{H}_j} [q_x(h)]$ by summing up the individual expectations. Note that by linearity of expectations, it holds that $\sum_{\text{machines } x} \mathbb{E}_{h \in \mathcal{H}_j} [q_x(h)] = \mathbb{E}_{h \in \mathcal{H}_j} [q(h)]$. Then, we are ensured that there is an index k such that $\mathbb{E}_{h \in \mathcal{H}_k} [q(h)] \geq Q$, i.e., picking a u.a.r. function h from \mathcal{H}_k gives an objective that is at least (or at most) Q . Thus, we select $\mathcal{H}^{(i)} = \mathcal{H}_k$ and extend the bit prefix $\mathbf{b} \leftarrow \mathbf{b} \circ b_k$ with the bit representation b_k of k . In the next iteration, we repeat the same process until when one good hash function h^* is found. Since $\left\lceil \frac{\tau}{\chi} \right\rceil = O(1/\alpha) = O(1)$, this distributed implementation of the method of conditional expectation runs in $O(1)$ MPC rounds.

Concentration Inequalities: To show that a randomized process requires only k -wise independence, we use the following results. For $k = 2$, a bound that is usually satisfactory is obtained from Chebyshev's inequality. For larger k , we apply the subsequent tail inequality, which depends on k .

Theorem B.3 (Chebyshev). Let X_1, \dots, X_n be random variables taking values in $[0, 1]$. Let $X = X_1 + \dots + X_n$ denote their sum and $\mu \leq \mathbb{E}[X]$. Then

$$\Pr [|X - \mathbb{E}[X]| \geq \mathbb{E}[X]] \leq \frac{\text{Var}[X]}{\mu^2}.$$

Corollary B.4. If X_1, \dots, X_n are pairwise independent, then $\text{Var}[X] = \sum_{i=1}^n \text{Var}[X_i] \leq \mathbb{E}[X]$ and

$$\Pr [|X - \mathbb{E}[X]| \geq \mathbb{E}[X]] \leq \frac{\sum_{i=1}^n \text{Var}[X_i]}{\mathbb{E}[X]^2} \leq \frac{1}{\mathbb{E}[X]} \leq \frac{1}{\mu}.$$

Lemma B.5 (Lemma 2.3 of [BR94]). Let $k \geq 4$ be an even integer. Let X_1, \dots, X_n be random variables taking values in $[0, 1]$. Let $X = X_1 + \dots + X_n$ denote their sum and let $\mu \leq \mathbb{E}[X]$ satisfying $\mu \geq k$. Then, for any $\epsilon > 0$, we have

$$\Pr [|X - \mathbb{E}[X]| \geq \epsilon \cdot \mathbb{E}[X]] \leq 8 \left(\frac{2k}{\epsilon^2 \mu} \right)^{k/2}.$$

Reducing The Seed Length via Coloring: If the outcome of a vertex depends only on the random choices of its neighbors at distance at most t , then k -wise independence among random variables of vertices within pairwise distance t is sufficient. Whenever this is the case, we find a coloring that maps vertex IDs to shorter names, i.e., colors, such that “adjacent” vertices are assigned different names. To achieve that, we apply Linial’s coloring algorithm [Lin92], which, given a proper C -coloring, produces a new legal coloring with a color palette of size $O(\Delta \log^2 C)$, as stated in the following lemma based on an explicit algebraic construction [EFF85, Kuh09]. For a proof of its MPC adaptation, we refer to [FGG22].

Lemma B.6. Let $G = (V, E)$ be a graph of maximum degree $\Delta \leq n^\alpha$ and assume we are given a proper C -coloring of G . Then, there is a deterministic algorithm that computes a $O(\Delta^2 \log^2 C)$ coloring of G in $O(1)$ MPC rounds using $O(n^\alpha)$ local space, $O(n+m)$ global space, and $\tilde{O}(n \cdot \text{poly}(\Delta))$ total computation. If $C = O(\Delta^3)$, then the number of colors can be reduced to $O(\Delta^2)$.

C Missing Part of Theorem 1.1

Lemma C.1. Every vertex in H_i with degree at least d^3 gets removed or all but at most d^3 of its incident edges are removed.

Proof. Every node $u \in \bigcup_{j=1}^{i-1} H_j$ marks one edge $e = \{u, v\}$ with $v \in H_i \cap N(u)$ at random. Each node $v \in H_i$ selects one incident marked edge arbitrarily. We prove that this process can be derandomized to obtain a suitable matching. Let v be a node in layer i with degree at least d^3 . Since v has at most d neighbors in H_i , there are at least $d^3 - d \gg 2d^2$ vertices in lower layers. Let X_u be a family of k -wise independent random variables with $X_u = 1$ if u marks the edge $\{u, v\}$ and $X_u = 0$ otherwise, for each $u \in U(v) \stackrel{\text{def}}{=} N(v) \cap \bigcup_{j=1}^{i-1} H_j$. Define $X = \sum_{u \in U(v)} X_u$ and observe that $\mathbb{E}[X] \geq 2d$ since $\Pr[X_u = 1] \geq 1/d$ and $|U(v)| \geq 2d^2$. By applying Lemma B.5 with $k = 21/\delta$, we have $\Pr[X = 0] \leq 8 \left(\frac{1}{d}\right)^{k/2} \leq n^{-3}$. Now, let $\mathcal{H} = \{h: V \mapsto [d]\}$ be a family of k -wise independent hash functions specified by $k \cdot (\log n + \log d) + O(1) = O(\log n)$ bits by Lemma B.2. Each function $h \in \mathcal{H}$ defines a matching $\mathcal{M}(h)$ that includes each node $v \in H_i$ with at least one marked edge,

i.e., if $h(u) = v$ for $u \in U(v)$. For each $v \in H_i$ of degree at least d^3 , our derandomization scheme groups the edges of v in blocks of size exactly $2d^2 = O(n^\delta)$, possibly deleting some spare edges. Each machine will now ensure that its assigned blocks are marked, i.e., each block has at least one marked edge under h . The above concentration bound together with a union bound over the set of all blocks ensures that a randomly chosen h has all blocks *marked* with probability at least n^{-1} . Thus, each machine x , which is responsible for some blocks of edges $B_j(v)$ incident to node v , can compute locally the number of edges $\{u, v\} \in B_j(v)$ such that $h(u) = v$ for each hash function $h \in \mathcal{H}$ and determine whether $B_j(v)$ is marked. By the distributed method of conditional expectation (Appendix B) with the objective function $q_x(h) = \mathbb{1}\{B_j(v) \text{ is marked for every } v\}$, we find a function h^* that makes all blocks marked in $O(1)$ time. \square

D MIS Algorithm for High-Arboricity Graphs

The sparsification of [CDP21b, Section 4] has the following properties.

Lemma D.1 ([CDP21b]). *There is a deterministic low-memory MPC constant-round sparsification procedure that returns subsets of nodes $B, Q \subseteq V$ and a subset of edges $E' \subseteq E$ such that:*

- a) *For every $v \in B \cup Q$ it holds that $\deg_{E'}(v) = O(n^\delta)$ and that $\deg_Q(v) = O(n^\delta)$, for any δ , $0 < \delta < 1$.*
- b) *Every node $v \in B$ either satisfies $\sum_{u \in N_{E'}(v)} \frac{1}{\deg_Q(u)} \geq \frac{\delta}{10}$, or it has a neighbor $u \in Q$ whose degree in Q is 0.*
- c) *For the subset B of V it holds that $\sum_{v \in B} \deg(v) \geq \frac{\delta|E|}{8}$.*

We use the subsets E' of edges and B, Q of vertices returned by Lemma D.1 to find an independent set $\mathcal{I} \subseteq Q$ such that $\mathcal{I} \cup N(\mathcal{I})$ is incident to a linear number of edges. For each $v \in B$, we define a subset of *relevant* nodes by $S(v) \subseteq N_{E'}(v)$, with $\sum_{u \in S(v)} \frac{1}{\deg_Q(u)} \in [\delta/10, 1]$ by Property 2. Let \mathcal{H} be a family of pairwise independent hash functions and let $h \in \mathcal{H}$ map each node v in Q to a value $z_v \in [n^3]$. We say that v is *sampled* and joins the set of sampled nodes S_h iff $z_v < \frac{n^3}{3 \deg_Q(v)}$.

Let $S_h(u) \stackrel{\text{def}}{=} S(u) \cap S_h$ denote the set of nodes in $S(u)$ that are sampled for each $u \in B$. Define \mathcal{I}_h to be the set of sampled nodes such that no neighbor is sampled. Observe that, for a node $v \in B$, if the following two conditions hold: (i) $S_h(v) = \{u\}$ and (ii) $S_h \cap N_Q(u) = \emptyset$, then v is incident to \mathcal{I}_h . For simplicity, let us remove from consideration all vertices adjacent to a vertex u with degree 0 in Q . To find a good \mathcal{I}_h , we define the following pessimistic estimator $P(h)$:

$$P(h) = \sum_{v \in B: |S_h(v)|=1} \deg(v) - \sum_{v \in B} \deg(v) \cdot \left(\sum_{u \in S_h(v)} \mathbb{1}\{\exists u' \in N_Q(u) u' \in S_h\} \right).$$

To compute $P(h)$, each node $v \in B$ checks $|S_h(v)|$ and, for each edge $e = \{u, v\}$ with $u \in S_h(v)$, node u checks whether u is neighboring a sampled node. Let A_u be the event that $u \in S_h$ and B_u

denote the bad event $\{\exists_{u' \in N_Q(u)} u' \in S_h\}$ that u neighbors a sampled node. We have

$$\begin{aligned} \mathbb{E}[P(h)] &= \sum_{v \in B} \deg(v) \cdot \Pr[|S_h(v)| = 1] - \\ &\quad \sum_{v \in B} \deg(v) \cdot \left(\sum_{u \in S(v)} \Pr[A_u \wedge B_u] \right) \\ &= \sum_{v \in B} \deg(v) \cdot \left(\Pr[|S_h(v)| = 1] - \sum_{u \in S(v)} \Pr[A_u \wedge B_u] \right). \end{aligned}$$

The probability of the event A_u is $\frac{1}{3 \deg_Q(u)} - \frac{1}{n^3} \leq \Pr[A_u] \leq \frac{1}{3 \deg_Q(u)}$. Conditioned on A_u and by independence of $z_u, z_{u'}$, the probability of B_u is

$$\Pr[B_u | A_u] \leq \sum_{u' \in N_Q(u)} \Pr[A_{u'}] \leq \deg_Q(u) \cdot \frac{1}{3 \deg_Q(u)} = \frac{1}{3}.$$

Then, by applying the inclusion-exclusion principle and observing that $\Pr[A_u, A_{u'}] = \Pr[A_u] \cdot \Pr[A_{u'}]$ by pairwise independence, we get

$$\begin{aligned} \Pr[|S_h(v)| \geq 1] &\geq \sum_{u \in S(v)} \Pr[A_u] - \sum_{\substack{u, u' \in S(v), \\ u \neq u'}} \Pr[A_u] \cdot \Pr[A_{u'}] \\ &\geq \sum_{u \in S(v)} \Pr[A_u] \left(1 - \sum_{u' \in S(v)} \Pr[A_{u'}] \right). \end{aligned}$$

Observe that $\Pr[A_u \wedge B_u] = \Pr[A_u] \cdot \Pr[B_u | u \in S_h] \leq \frac{1}{3} \Pr[A_u]$ by the calculations above. Thus,

$$\begin{aligned} &\Pr[|S_h(v)| = 1] - \sum_{u \in S(v)} \Pr[A_u \wedge B_u] \\ &\geq \sum_{u \in S(v)} \Pr[A_u] \left(\frac{2}{3} - \sum_{u' \in S(v)} \Pr[A_{u'}] \right) \\ &= \sum_{u \in S(v)} \Pr[A_u] \left(\frac{2}{3} - \frac{1}{3} \sum_{u' \in S(v)} \frac{1}{\deg_Q(u')} \right) \geq \frac{1}{3} \cdot \sum_{u \in S(v)} \Pr[A_u] \\ &\geq \frac{1}{3} \cdot \sum_{u \in S(v)} \left(\frac{1}{3 \deg_Q(u)} - \frac{1}{n^3} \right) \geq \frac{1}{9} \cdot \sum_{u \in S(v)} \frac{1}{\deg_Q(u)} - \frac{1}{3n^2} \\ &\geq \frac{\delta}{90} - \frac{1}{3n^2}, \end{aligned}$$

where the last inequality follows from Property 2. Note that we can assume $\frac{\delta}{90} - \frac{1}{3n^2} \geq \frac{\delta}{100}$ for n large enough. We can now conclude that $\mathbb{E}[P(h)] \geq \frac{\delta}{100} \sum_{v \in B} \deg(v) \geq \frac{\delta^2 |E|}{800}$, as desired. Summarized, our algorithm applies the sparsification procedure of Lemma D.1 followed by the above derandomization process with objective function $P(h)$. We can thus find a hash function h^*

such that $P(h^*) \geq \frac{\delta^2}{800} |E|$, i.e., an independent set \mathcal{I}_{h^*} incident to at least $\frac{\delta}{1600} |E|$ edges. Thus, after $O(\log n)$ iterations, the returned independent set is maximal.

E Missing Proofs of Deterministic Arboricity-Based Degree Reduction

In the following, we prove [Lemma 3.3](#).

Proof of Lemma 3.3. Let $\mathcal{J} = \{v \in V(G, \Delta_i) \mid \deg_{V(G, \Delta_i)}(v) \geq \deg_G(v)/2\}$ denote high-degree nodes having a majority of their neighbors in $V(G, \Delta_i)$. Then, let each node $v \in V(G, \Delta_i)' \stackrel{\text{def}}{=} V(G, \Delta_i) \setminus \mathcal{J}$, which has $\deg_{V \setminus V(G, \Delta_i)}(v) \geq \deg_G(v)/2 \geq \sqrt{\Delta_i}/2$, discard some edges arbitrarily such that $\deg_{V \setminus V(G, \Delta_i)}(v) = 2\beta^8$. Let \tilde{E} be the set of remaining edges crossing the cut $(V(G, \Delta_i), V \setminus V(G, \Delta_i))$. Let $\mathcal{S} = \{u \mid v \in V(G, \Delta_i)' \text{ and } \{u, v\} \in \tilde{E}\}$ be the low-degree neighborhood of $V(G, \Delta_i)'$. We define good \mathcal{S} -nodes and good $V(G, \Delta_i)$ -nodes as follows.

$$\begin{aligned} \mathcal{S}_{\text{Good}} &= \{u \in \mathcal{S} \mid \deg_{\tilde{E}}(u) < \beta, \deg_{\mathcal{S}}(u) < \beta^2\}, \text{ and} \\ V(G, \Delta_i)_{\text{Good}} &= \left\{v \in V(G, \Delta_i)' \mid \deg_{(\mathcal{S}_{\text{Good}}, \tilde{E})}(v) \geq \beta^8\right\}. \end{aligned}$$

Then, each node $v \in V(G, \Delta_i)_{\text{Good}}$ arbitrarily selects a subset $T(v)$ of size β^4 of $\mathcal{S}_{\text{Good}}$ -nodes it is incident to. Thus, the β -high-subgraph of G is given by the vertices $(V(G, \Delta_i)_{\text{Good}} \sqcup \mathcal{S}_{\text{Good}})$ and the two set of edges $E_1 = \{(u, v) \in E \mid v \in V(G, \Delta_i)_{\text{Good}}, u \in T(v)\}$ and $E_2 = \{(u, u') \in E \mid u, u' \in \bigcup_{v \in V(G, \Delta_i)_{\text{Good}}} T(v)\}$. Finally, the number of *bad* nodes that are in \mathcal{J} or $V(G, \Delta_i)' \setminus V(G, \Delta_i)_{\text{Good}}$ is upper bounded by $\frac{5\lambda|V(G, \Delta_i)|}{\beta - \lambda} \leq |V(G, \Delta_i)|/\Delta_i^{\Omega(1)}$ by the analysis of [\[BEPS16\]](#) and our choice of $\beta = \Delta_i^{\Omega(1)}$ with $\Delta_i \geq \text{poly}(\lambda)$. \square