

# Rank Generalized Subspace subcode

Ousmane Ndiaye<sup>1</sup>, Peter Arnaud Kidoudou<sup>2</sup>, and Hervé Tale Kalachi<sup>3</sup>

<sup>1</sup> Université Cheikh Anta Diop de Dakar, FST, DMI, LACGAA,  
Senegal,

`ousmane3.ndiaye@ucad.edu.sn`

<sup>2</sup> université Marien Ngouabi (UMNG), Faculty of Science and Technology

`peter.kidoudou@umng.cg`

<sup>3</sup> Computer Engineering Department, National Advanced School of Engineering of  
Yaoundé, University of Yaoundé 1, Yaoundé, Cameroon,

`hervekalachi@gmail.com`

**Abstract.** Rank metric codes were studied by E. Gabidulin in 1985 after a brief introduction by Delaste in 1978 as an alternative to Reed-Solomon codes based on linear polynomials. They have found applications in many areas including linear network coding and space-time coding.

They are also used in cryptography to reduce the size of the keys compared to Hamming metric codes at the same level of security. Despite this progress, these codes suffer from structural attacks due to the strong algebraic structure from which they are defined. It therefore becomes interesting to find new families in order to address these questions. This explains their elimination from the NIST post-quantum cryptography competition.

In this paper we provide a generalisation of subspace subcodes in rank metric introduced by Gabidulin and Loidreau. We also characterize this family by giving an algorithm which allows to have its generator and parity-check matrices based on the associated extended codes. We also have bounded the cardinal of these codes both in the general case and in the case of Gabidulin codes. We have also studied the specific case of Gabidulin codes whose the underlined Gabidulin decoding algorithms are known.

**Keywords:** Coding theory, rank metric, Gabidulin code, Cryptography, Shortened code, Punctured code, Subfield subcodes.

## 1 Introduction

Rank metric codes were studied by E. Gabidulin in 1985 [7] after a brief introduction by Delaste in 1978 [5] who gives a description based on finite fields and its properties. By their construction these codes are very close to Reed-Solomon [18] codes since the codewords are obtained by evaluation of  $q$ -polynomials on a support included in an extension of degree  $m$  of  $\mathbb{F}_q$ . Gabidulin codes are one of the first general constructions of linear codes that are maximum rank distant (MRD). They have found applications in linear network coding (LRPC codes), for example, when the transmitter and receiver are oblivious to the inner workings and topology of the network.

Rank metric codes are also used recently in the theory of space-time codes. This was introduced by Lu and Kumar from Gabidulin codes[14].

In cryptography we need several difficult problems, many of which could be solved by the quantum machine (factorization, discrete log, ...). The theory of codes is a serious candidate to offer perspectives in the face of this formidable machine, in particular the problem of decoding by syndrome in Hamming or Rank metrics. Recently they are widely used in cryptography to provide cryptographic primitives for encryption, signature, hashing or pseudo-random number generation. The main reason for using rank metric codes is the possibility of reducing the size of the keys compared to Hamming metric codes at the same level of security. Despite this prowess, these codes suffer from structural attacks due to the strong algebraic structure from which they are defined. It therefore becomes interesting to find new families in order to address these questions. Rank metric cryptography began with the GPT cryptosystem and its variants [9,3] based on Gabidulin codes [14], which are rank metric analogues of Reed-Solomon codes and an alternative to the Sidelnikov and Shestakov attack while trying to keep the benefits of the last one. However, the strong algebraic structure of these codes has been successfully exploited to attack the original GPT cryptosystem and its variants with the Overbeck attack and its variants [17].

Recently candidates for public key cryptosystems based on rank metric codes [15] have been proposed but were all eliminated by security default. It therefore becomes theoretically interesting to find new families of codes in non-trivial rank metrics on subextensions of low degree or quite simply on vector subspaces.

The notion of subcodes whose components of each codeword belong to the same sub-vector space, named subcodes on the subspace, was first introduced in Hamming metrics on RS codes by Hattori, McEliece, and Solomon, G. [11]. A few years later, the same notion was introduced in rank metrics by Gabidulin and Loidreau for applications in publickey cryptography [8,3].

Recently Berger, Gueye and Klamti have proposed a generalization of these subcodes into Hamming metrics [2] whose constituents are in subspaces that are not necessarily equal. Just after Berger, Gueye, Klamti and Ruatta [1] proposed a cryptosystem based on quasi-cyclic subcodes of SSRS codes.

In this paper we introduce and characterize the family of generalized subspace subcodes of a Code in rank metrics by giving an algorithm which allows to have its generator and parity-check matrices based on the associated extended codes. We also have bounded the cardinal of these codes both in the general case and in the case of Gabidulin codes as a generalization of the results obtained in [8]. We have also studied the specific case of Gabidulin codes whose decoding algorithms are known.

The document is organized as follows, we will start with section 2 Preliminaries to identify the generalities relating to rank metric codes et derived codes, then section 3 results on Generalized Subspace subcodes in rank metric. We will finish with the section 4 to present the results on Generalized Subspace subcodes of Gabidulin codes.

## 2 Preliminaries

### 2.1 Rank Metric Codes

The *rank weight*  $w_R(x)$  of a word  $x = (x_1, \dots, x_n)$  in an extension field  $\mathbb{F}_{q^m}^n$  is defined by the maximal number of its elements that are linearly independent over the base field  $\mathbb{F}_q$ , where  $m$  and  $n$  are positive integers and  $q$  a prime number. The *rank distance*  $d_R$  between two words is defined by the rank weight of their difference, i.e.  $d_R(x, y) = w_R(x - y)$ .

A rank metric code is a  $k$ -dimensional subspace of an  $n$ -dimensional vector space over a finite field  $\mathbb{F}_{q^m}$ , where  $k$  is a positive integer. Given a code  $C \subset \mathbb{F}_{q^m}^n$ , its minimum rank distance is

$$d_R(C) = \min_{c_1 \neq c_2 \in C} w_R(c_1 - c_2) = \min_{c \in C} w_R(c).$$

**Definition 1.** (*Matrix code [10]*)

A matrix code  $C$  of length  $m \times n$  over  $\mathbb{F}_q$  is a subspace of the vector space of matrices of size  $m \times n$  with entries in  $\mathbb{F}_q$ . If  $C$  is of dimension  $K$ , we say that  $C$  is an  $[m \times n, K]_q$  matrix code, or simply an  $[m \times n, K]$  code if there is no ambiguity.

**Definition 2.** (*matrix code associated to an  $\mathbb{F}_{q^m}$ -linear code*).

Let  $C$  be an  $[n, k]$  linear code over  $\mathbb{F}_{q^m}$ . Each word  $c$  of  $C$  can be associated to an  $m \times n$  matrix over  $\mathbb{F}_q$  by representing each coordinate  $c_i$  by a column vector

$(c_{i_1}, \dots, c_{i_m})^\top$  where  $c_i = \sum_{j=1}^m c_{ij} \beta_j$  with  $(\beta_1, \dots, \beta_m)$  being an arbitrary basis

of  $\mathbb{F}_{q^m}$  viewed as a vector space over  $\mathbb{F}_q$  and  $c_{ij} \in \mathbb{F}_q$ . In other words the  $c_{ij}$ 's are the coordinates of  $c_i$  in this basis. The matrix code associated to  $C$  is of type  $[m \times n, km]_q$ .

The weight of a word  $c \in C$  is the rank of its associated matrix and does not depend on the choice of the basis. If  $C$  is a  $k$ -dimensional linear code, it is said to be a  $[n, k, d = d_R(C)]_r$  code. The parameters are related by an equivalent of Singleton bound for rank distance see [7]:

$$\text{Card}(C) \leq q^{\min(m(n-d+1), n(m-d+1))}.$$

And a code satisfying the equality  $\text{Card}(C) = q^{\min(m(n-d+1), n(m-d+1))}$  is called a Maximum Rank Distance (MRD) code.

### 2.2 Punctured and Shortened codes

Punctured and Shortened codes of a fixed code are very important derivative codes to characterize certain sub-codes but also to mount structural attacks against code-based cryptosystems. We are going to use them on extended codes to characterize subcodes on subspaces in rank metrics. We recall here their definition and some properties that we need.

**Definition 3.** (*Punctured code*)

Let  $\mathcal{C} \subset \mathbb{F}_q^n$  be a linear code,  $\mathcal{I} \subseteq \{1, \dots, n\}$  a set of coordinates. The punctured code of  $\mathcal{C}$  on  $\mathcal{I}$ , noted  $P_{\mathcal{I}}(\mathcal{C})$  is defined by :

$$P_{\mathcal{I}}(\mathcal{C}) = \{(c_i)_{i \in \{1, \dots, n\} \setminus \mathcal{I}} \mid c \in \mathcal{C}\}.$$

This code is of length  $n - |\mathcal{I}|$ .

**Proposition 1.** Let  $\mathcal{C} \subset \mathbb{F}_q^n$  an  $[n, k, d]$ -code,  $\mathcal{I} \subseteq \{1, \dots, n\}$ . Then  $P_{\mathcal{I}}(\mathcal{C})$  is an  $[n - |\mathcal{I}|, k', d']$ -code such that:

$$k - |\mathcal{I}| \leq k' \leq k \text{ and } d - |\mathcal{I}| \leq d' \leq d.$$

**Definition 4.** (*Shortened Code*)

Let  $\mathcal{C} \subset \mathbb{F}_q^n$  be a linear code,  $\mathcal{I} \subseteq \{1, \dots, n\}$  a set of coordinates. The Shortened code of  $\mathcal{C}$  on  $\mathcal{I}$ , noted  $S_{\mathcal{I}}(\mathcal{C})$  is defined by :

$$S_{\mathcal{I}}(\mathcal{C}) = P_{\mathcal{I}}(\{c \in \mathcal{C} \setminus \mathcal{I} \mid c_i = 0, \forall i \in \mathcal{I}\}).$$

This code is of length  $n - |\mathcal{I}|$ .

**Proposition 2.** Let  $\mathcal{C} \subset \mathbb{F}_q^n$  an  $[n, k, d]$ -code,  $\mathcal{I} \subseteq \{1, \dots, n\}$ . Then  $S_{\mathcal{I}}(\mathcal{C})$  is an  $[n - |\mathcal{I}|, k', d']$ -code such that:

$$k - |\mathcal{I}| \leq k' \leq k \text{ and } d \leq d'.$$

**Theorem 1.** (*Link between Shortened and Punched Codes* [[12], Theorem 1.5.7])  
Let  $\mathcal{C} \subset \mathbb{F}_q^n$  a  $[n, k, d]$ -code,  $\mathcal{I} \subseteq \{1, \dots, n\}$ . Then

1.  $S_{\mathcal{I}}(\mathcal{C}^{\perp}) = P_{\mathcal{I}}(\mathcal{C})^{\perp}$
2.  $S_{\mathcal{I}}(\mathcal{C})^{\perp} = P_{\mathcal{I}}(\mathcal{C}^{\perp})$

### 3 Generalized Subspace subcodes in rank metric

In rank metric, the Subspace subcodes were introduced in [8] with a study on their decoding algorithm.

In this section we give a generalization of Subspace subcodes in rank metric introduced in [8] by E. M. Gabidulin and P. Loidreau. First of all we will give a generalization of the definition of the rank of a vector.

**Definition 5 ([8]).** Let  $\mathcal{C}$  be matrix code of length  $m \times n$  over  $\mathbb{F}_q$  of parameters  $[n, k, d = d_R(\mathcal{C})]_{q^m}$ . Let  $V$  be an  $\mathbb{F}_q$ -subspaces of  $\mathbb{F}_q^m$  of dimension  $s \leq m$ . The subspace subcode of  $\mathcal{C}$  over  $V$  is the  $\mathbb{F}_q$ -vector space  $(\mathcal{C}|V) = \mathcal{C} \cap V^n$

$(\mathcal{C}|V)$  is formed of the codewords whose components lie in the alphabet formed by the subspace  $V$ . This code is not usually  $\mathbb{F}_q^m$ -linear but it is still  $\mathbb{F}_q$ -linear and linear over some intermediary extension depending on  $V$ . This code also corresponds by projection to the subgroup subcode [13] on the alphabet is  $\mathbb{F}_q^{\dim(V)}$ . In the following we introduce a generalization by choosing on each coordinate a different vector subspace.

**Definition 6.** Let  $C$  be linear code of length  $n$  over  $\mathbb{F}_{q^m}$  of parameters  $[n, k, d = d_R(C)]_{q^m}$ . Let  $V_1, \dots, V_n$  be a set of  $n$   $\mathbb{F}_q$ -subspaces of  $\mathbb{F}_{q^m}$  of dimension respectively  $s_i \leq m$ . Set  $W = \prod_{i=1}^n V_i$ , constituted of  $n$ -tuples with the  $i$ -th coordinate in  $V_i$ . The Rank Generalized subspace subcode of  $C$  relative to  $W$  is the  $\mathbb{F}_q$ -vector space  $RGSS_W(C) = C \cap W$

In [8] all  $V_i$  are equal whereas here they are not necessarily. Let  $B = \{b_1, b_2, \dots, b_m\}$  be a basis of  $\mathbb{F}_{q^m}$  as a  $\mathbb{F}_q$ -vector space. We can construct the map  $\phi_B : \mathbb{F}_{q^m} \rightarrow \mathbb{F}_q^m$  defined by, if  $x = \sum_{i=1}^m x_i b_i$ ,  $x_i \in \mathbb{F}_q$ , then  $\phi_B(x) = (x_1, x_2, \dots, x_m)$ . This map will be extended on  $\mathbb{F}_{q^m}^n$  by the isomorphism:

$$\begin{aligned} \text{Exp}_{B,n} : \mathbb{F}_{q^m}^n &\rightarrow \mathbb{F}_q^{mn} \\ (c_1, c_2, \dots, c_n) &\mapsto (\phi_B(c_1), \phi_B(c_2), \dots, \phi_B(c_n)), \end{aligned}$$

Applied to all codewords, this gives a new linear code of length  $nm$  called Expanded Codes.

For the definition of generator matrices of subcodes on the subspaces we will need to generalize the expansion functions adapted to several bases simultaneously. Given  $n$  bases  $(B_1, \dots, B_n)$  of  $F_{q^m}$

$$\begin{aligned} \text{Exp}_{(B_i)_{i,n}} : \mathbb{F}_{q^m}^n &\rightarrow \mathbb{F}_q^{mn} \\ (c_1, c_2, \dots, c_n) &\mapsto (\phi_{B_1}(c_1), \phi_{B_2}(c_2), \dots, \phi_{B_n}(c_n)), \end{aligned}$$

**Definition 7.** Let  $C$  be a linear code of length  $n$  and dimension  $k$  over  $F_{q^m}$ . The expanded code of  $C$  also called ( $q$ -ary image of a code  $C$ ) with respect to the  $n$  bases  $(B_1, \dots, B_n)$  of  $F_{q^m}$  is a linear code over the base field  $\mathbb{F}_q$  defined as:

$$\text{Im}_{q,(B_i)_i}(C) = \text{Exp}_{(B_i)_{i,n}}(C)$$

**Lemma 1 ([19], Theorem 1).**

1. Let  $C$  having a generator matrix

$$G = \begin{pmatrix} g_1 \\ g_2 \\ \vdots \\ g_k \end{pmatrix} \in (\mathbb{F}_{q^m}^n)^k.$$

Then the expanded code of  $C$  over  $F_q$  with respect to a basis  $B = \{b_1, b_2, \dots, b_m\}$  of  $\mathbb{F}_{q^m}$  has the expanded generator matrix  $\hat{G}_B$  such that

$$\hat{G}_B = \text{ExpMat}_{B,n}(G) = \begin{pmatrix} \text{Exp}_{B,n}(b_1 g_1) \\ \text{Exp}_{B,n}(b_2 g_1) \\ \vdots \\ \text{Exp}_{B,n}(b_m g_1) \end{pmatrix}_{1 \leq i \leq k} \in (\mathbb{F}_q^{mn})^{mk}.$$

2. Let  $C$  having a parity-check matrix

$$H = \begin{pmatrix} h_1 \\ h_2 \\ \vdots \\ h_n \end{pmatrix}^T \in (\mathbb{F}_{q^m}^n)^k.$$

Then the expanded code of  $C$  over  $F_q$  with respect to a basis  $B = \{b_1, b_2, \dots, b_m\}$  of  $\mathbb{F}_{q^m}$  has the expanded parity check matrix  $\hat{H}_B$  such that

$$\hat{H}_B = \text{ExpMat}_{B, n-k}(H^T)^T = \begin{pmatrix} \text{Exp}_{B, n-k}(b_1 h_j) \\ \text{Exp}_{B, n-k}(b_2 h_j) \\ \vdots \\ \text{Exp}_{B, n-k}(b_m h_j) \end{pmatrix}_{1 \leq j \leq n}^T \in (\mathbb{F}_q^{mn})^{m(n-k)}.$$

In the general case, we need to process codewords whose  $n$  components are in different subspaces and therefore to process different bases. In practice, a single basis is sufficient to extend messages in  $\mathbb{F}_{q^m}^k$  to be encoded.

**Proposition 3.** 1. Let  $C$  having a generator matrix

$$G = \begin{pmatrix} g_1 \\ g_2 \\ \vdots \\ g_k \end{pmatrix} \in (\mathbb{F}_{q^m}^n)^k.$$

Then the expanded code of  $C$  over  $F_q$  from the basis  $B = \{b_1, b_2, \dots, b_m\}$  with respect to the  $n$  bases  $(B_1, \dots, B_n)$  of  $F_{q^m}$  has the expanded generator matrix  $\hat{G}_{(B_j)_j}^B$  such that

$$\hat{G}_{(B_j)_j}^B = \text{ExpMat}_{(B_j)_j, n}^B(G) = \begin{pmatrix} \text{Exp}_{(B_j)_j, n}(b_1 g_i) \\ \text{Exp}_{(B_j)_j, n}(b_2 g_i) \\ \vdots \\ \text{Exp}_{(B_j)_j, n}(b_m g_i) \end{pmatrix}_{1 \leq i \leq k} \in (\mathbb{F}_q^{mn})^{mk}.$$

2. Let  $C$  having a parity-check matrix

$$H = \begin{pmatrix} h_1 \\ h_2 \\ \vdots \\ h_n \end{pmatrix}^T \in (\mathbb{F}_{q^m}^n)^k.$$

Then the expanded code of  $C$  over  $F_q$  from the basis  $B = \{b_1, b_2, \dots, b_m\}$  with respect to the  $n$  bases  $(B_1, \dots, B_n)$  of  $F_{q^m}$  has the expanded parity check

matrix  $\hat{H}_{(B_j)_j}^B$  such that

$$\hat{H}_{(B_j)_j}^B = \text{ExpMat}_{(B_j)_j, n-k}(H^T)^T = \begin{pmatrix} \text{Exp}_{(B_j)_j, n-k}(b_1 h_i) \\ \text{Exp}_{(B_j)_j, n-k}(b_2 h_i) \\ \vdots \\ \text{Exp}_{(B_j)_j, n-k}(b_m h_i) \end{pmatrix}_{1 \leq i \leq n}^T \in (\mathbb{F}_q^{mn})^{m(n-k)}.$$

**Proposition 4.** *The  $q$ -ary image of a code  $C$  from the basis  $B$  with respect to the  $n$  bases  $(B_1, \dots, B_n)$  of  $\mathbb{F}_{q^m}$ ,  $\text{Im}_{q, (B_i)_i}(C)$  has generator matrix the block matrix  $(M_{g_{i,j}}^T)_{1 \leq i \leq k, 1 \leq j \leq n} \in (\mathbb{F}_q^{m \times m})^{k \times n}$  where the matrix  $M_{g_{i,j}} = \mathcal{M}_{B, B_j}(f_{g_{i,j}})$  corresponds to  $f_{g_{i,j}}(x) = g_{i,j}x$ .*

**Definition 8.** *Let, for  $1 \leq j \leq n$ ,  $u_j = \{u_{1,j}, \dots, u_{s_j,j}\} \subset \{(j-1)m+1, (j-1)m+2, \dots, (j-1)m+m\}$  and  $U = \{u_1, \dots, u_n\}$ . We denote by  $S_U$  (respectively  $P_U$ ) the operation of shortening (respectively puncturing) the  $q$ -ary image of  $C$  on positions  $I_U = \{1, 2, \dots, nm\} \setminus U$ , i.e.*

$$S_U(C) = S_{I_U}(\text{Im}_{q, (B_i)_i}(C)) \text{ and } P_U(C) = P_{I_U}(\text{Im}_{q, (B_i)_i}(C)).$$

**Proposition 5.** *Let  $C$  be a linear code of length  $n$  over  $\mathbb{F}_{q^m}$ ,  $B = \{b_1, b_2, \dots, b_m\}$  be a basis of  $\mathbb{F}_{q^m}$  and  $V = \langle b_1, \dots, b_s \rangle$  an  $s$ -dimensional  $\mathbb{F}_q$ -subspaces of  $\mathbb{F}_{q^m}$  and  $U = \{u_1, \dots, u_n\}$  such that for  $1 \leq j \leq n$ ,  $u_j = \{(j-1)m+1, \dots, (j-1)m+s\}$ . The code  $S_U(C)$  is  $q$ -ary image of the subspace subcode of  $C$  over  $V$  with respect to the basis  $B$ .*

*Proof.* Let  $y = (y_{1,1}, \dots, y_{s,1}, \dots, y_{1,j}, \dots, y_{s,j}, \dots, y_{1,n}, \dots, y_{s,n}) \in S_U(C)$  then  $\exists c \in \text{Im}_q(C)$  such that  $y = P_{I_U}(c)$  whose components  $c_i = 0$  for  $i \notin U$ .

As  $V = \phi_{B,n}^{-1}(\{(x_1, \dots, x_s, 0, \dots, 0) | x_1, \dots, x_s \in \mathbb{F}_q\})$ , therefore  $\phi_{B,n}^{-1}(c) \in C \cap V^n$  so  $c \in \phi_{B,n}(C \cap V^n)$  then  $y \in P_{I_U}(\phi_{B,n}(C \cap V^n))$  that means

$$S_U(C) = \phi_{B,n}(C \cap V^n) = \text{Im}_{q,B}(C \cap V^n)$$

**Lemma 2 ([4], lemma 34).** *Let  $C$  be a linear code of length  $n$  over  $\mathbb{F}_{q^m}$ ,  $B = \{b_1, b_2, \dots, b_m\}$  be a basis of  $\mathbb{F}_{q^m}$ . Let  $(Q_j)_j \in (GL_m(\mathbb{F}_q))^n$ . The following equality holds.*

$$\text{Im}_{q, (Q_j^{-1}B)_j}(C) = \text{Exp}_{(Q_j^{-1}B)_j, n}(C) = \text{Exp}_{B, n}(C) \cdot \begin{pmatrix} Q_1 & & \\ & \ddots & \\ & & Q_n \end{pmatrix},$$

$$\hat{G}_{(B_j)_j}^B = \hat{G}_B \cdot \begin{pmatrix} Q_1 & & \\ & \ddots & \\ & & Q_n \end{pmatrix}, \text{ and}$$

$$\hat{H}_{(B_j)_j}^B = \hat{H}_B \cdot \begin{pmatrix} (Q_1^{-1})^T & & \\ & \ddots & \\ & & (Q_n^{-1})^T \end{pmatrix}$$

**Corollary 1.** Let  $C$  be a linear code of length  $n$  over  $\mathbb{F}_{q^m}$ ,  $B = \{b_1, b_2, \dots, b_m\}$  be a basis of  $\mathbb{F}_{q^m}$  and  $V = \langle d_1, \dots, d_s \rangle$  an  $s$ -dimensional  $\mathbb{F}_q$ -subspaces of  $\mathbb{F}_{q^m}$ . The  $q$ -ary image of the subspace subcode  $(C|V) = C \cap V^n$  can be expressed as  $S_U(C)$  on any completed basis  $D = \{d_1, d_2, \dots, d_s, \dots, d_m\}$  of  $\mathbb{F}_{q^m}$

*Proof.* According to Proposition 5 and the completed basis  $D = \{d_1, d_2, \dots, d_s, d_{s+1}, \dots, d_m\}$ , then  $S_U(C) = \phi_{D,n}(C \cap V^n)$ .

As  $QD = B$  with  $Q$  be the change-of-basis matrix from the basis  $B$  to the basis

$$D, \text{ then } S_U(C) = \phi_{Q^{-1}B,n}(C \cap V^n) = \text{Exp}_{B,n}(C \cap V^n) \cdot \begin{pmatrix} Q & & \\ & \ddots & \\ & & Q \end{pmatrix}$$

**Corollary 2.** Let  $C$  be a linear code of length  $n$  over  $\mathbb{F}_{q^m}$ ,  $B$  be a basis of  $\mathbb{F}_{q^m}$  and  $V_i = \langle d_{1,i}, \dots, d_{s_i,i} \rangle$   $s_i$ -dimensional  $\mathbb{F}_q$ -subspaces of  $\mathbb{F}_{q^m}$ . The  $q$ -ary image of  $RGSS_W(C) = C \cap W$ , where  $W = \prod_{i=1}^n V_i$ , can be expressed as  $S_U(C)$  from any basis  $B = \{b_1, b_2, \dots, b_m\}$  with respect to the  $n$  completed bases  $(B_1, \dots, B_n)$  from those of  $V_i$  respectively.

By using the relation between shortened code and punctured code, one can build the generating matrix of a subcode on the subspace. A generator matrix of  $\text{Exp}_{(Q_j^{-1}B)_j,n}(C \cap V^n)$  can be computed from its parity check matrix defined by  $P_u(\hat{H}_{(Q_j^{-1}B)_j})$  according to 1.

**Proposition 6.** Let  $C$  be matrix code of length  $m \times n$  over  $\mathbb{F}_q$  of parameters  $[n, k, d = d_R(C)]_{q^m}$ . Let  $V_1, \dots, V_n$  be a set of  $n$   $\mathbb{F}_q$ -subspaces of  $\mathbb{F}_{q^m}$  of dimension respectively  $s_i \leq m$ . Set  $W = \prod_{i=1}^n V_i$ , constituted of  $n$ -tuples with the  $i$ -th coordinate in  $V_i$ . If  $\sum_{i=1}^n s_i - m(n - k) > 0$  then:

$$q^{\sum_{i=1}^n s_i - m(n-k)} \leq |RGSS_W(C)|$$

*Proof.* Without altering the generality, we can assume that  $s_1 \leq s_2 \leq \dots \leq s_n$ , so up to isomorphisms  $V_1 \subset \dots \subset V_n$ , even if it means permuting the columns and obtaining an isometrically equivalent code. So there exists a serie of bases respectively of  $V_1, \dots, V_n$ , called  $b_1, b_2, \dots, b_n$  such that  $b_1 \subset \dots \subset b_n$  et  $b_i = \{\beta_1, \beta_2, \dots, \beta_{s_i}\}$ . Let  $c = (c_1, \dots, c_n) \in W$ , then  $c_i = u_{1i}\beta_1 + \dots + u_{s_i i}\beta_{s_i} + 0\beta_{s_i+1} + \dots + 0\beta_{s_n}$  which translates as:  $c = b_n U = (\beta_1, \beta_2, \dots, \beta_{s_n})U$  with  $U = (u_{i,t})_{i=1,t=1}^{s_n,n} \in \mathbb{F}_q^{s_n \times n}$ . Let  $H = (h_{j,t})_{j=1,t=1}^{n-k,n} \in \mathbb{F}_{q^m}^{(n-k) \times n}$  a parity-check matrix of  $C$ .

$$c \in RGSS_W(C) \Leftrightarrow \begin{cases} c = (\beta_1, \beta_2, \dots, \beta_{s_n})U \\ (\beta_1, \beta_2, \dots, \beta_{s_n})UH^T = 0 \end{cases} .$$



Let  $(\gamma_1, \dots, \gamma_m)$  a basis of  $\mathbb{F}_{q^m}$  sur  $\mathbb{F}_q$ .  
 $\forall i, j, t$  we have  $\beta_i h_{j,t} = \sum_{k=1}^m \delta_{i,t}^{(j,k)} \gamma_k$  where  $\delta_{i,t}^{(j,k)} \in \mathbb{F}_q$ . Then we have  
 $\forall j = 1, \dots, n-k, \forall k = 1, \dots, m, \sum_{i=1, t=1}^{s_i, n} \delta_{i,t}^{(j,k)} u_{s_i, t} = 0$

It is a linear system in  $\sum_{i=1}^n s_i$  unknowns and  $m(n-k)$  equations. Therefore the space of solution has dimension at least  $\sum_{i=1}^n s_i - m(n-k)$ . Therefore

$$q^{\sum_{i=1}^n s_i - m(n-k)} \leq |RGSS_W(C)|$$

This leads to the result obtained in [8] as a special case, since  $s_1 = \dots = s_n$ .

**Corollary 3.** [8]

Let  $\mathcal{C}$  be matrix code of length  $m \times n$  over  $\mathbb{F}_q$  of parameters  $[n, k, d = d_R(C)]_{q^m}$ . Let  $V$  be a  $\mathbb{F}_q$ -subspace of  $\mathbb{F}_{q^m}$  of dimension  $s \leq m$ . If  $ns - m(n-k) > 0$  then:

$$q^{ns - m(n-k)} \leq |\mathcal{C} \cap V^n|$$

## 4 Generalized Subspace subcodes of Gabidulin codes

### 4.1 Gabidulin codes

Gabidulin codes [7], special case of matrix codes, were defined by linear polynomials that were studied for the first time by O. Ore in [16]. These polynomial are of the form  $P(z) = \sum_i p_i x^{q^i}$ , where  $p_i \in \mathbb{F}_{q^m}$  and  $p_i \neq 0$  for finitely many  $i$ . By convention, we write  $[i] := q^i$ , so  $P(z)$  becomes  $P(z) = \sum_i p_i z^{[i]}$ . If  $P \neq 0$ , its  $q$ -degree is  $deg_q(P) = \max(\{i : p_i \neq 0\})$ . Considering addition and multiplication by a scalar, we notice that  $q$ -polynomials are  $\mathbb{F}_q$ -linear maps from  $\mathbb{F}_{q^m}$  to  $\mathbb{F}_{q^m}$ . The addition and composition of  $q$ -polynomials give this a non-commutative ring structure denoted  $\mathcal{P}_{q^m}$ .

**Definition 9.** Let  $g = (g_1, g_2, \dots, g_n) \in \mathbb{F}_{q^m}^n$  an ordered set of  $n \leq m$  elements of  $\mathbb{F}_{q^m}$ , which are linearly independent over  $\mathbb{F}_q$  and  $k < n$ . The corresponding  $[n, k]$  Gabidulin code of support  $g$ , of dimension  $k$  and length  $n$  is defined by

$$Gab_k(g) = \{(P(g_1), \dots, P(g_n)) \in \mathbb{F}_{q^m}^n : P \in \mathcal{P}_{q^m}, deg_q(P) < k\}$$

A Gabidulin code  $Gab_k(g)$  is a  $[n, k]$  code with a generator matrix  $G = (g_j^{[i-1]}) \in \mathbb{F}_{q^m}^{k \times n}$ ,  $1 \leq i \leq k, 1 \leq j \leq n$ , where the generating elements  $g_j \in \mathbb{F}_{q^m}$  have to be linearly independent over  $\mathbb{F}_q$ . Gabidulin codes satisfy the Singleton bound with rank distance  $d_R = n - k + 1$ . Thus, they can correct up to  $\tau_{max} = \lfloor \frac{n-k}{2} \rfloor$  errors. The Gabidulin code  $Gab_k(g)$  of support  $g$  and dimension  $k$  is

generated by the matrix:

$$G = \begin{pmatrix} g_1^{[0]} & \cdots & g_n^{[0]} \\ g_1^{[1]} & \cdots & g_n^{[1]} \\ \vdots & \cdots & \vdots \\ g_1^{[k-1]} & \cdots & g_n^{[k-1]} \end{pmatrix}$$

This definition is close to those of Reed-Solomon codes: set of distinct elements is replaced by a set of linearly independent elements, and the classical power  $g_j^i$  is replaced by the "Frobenius power"  $g_j^{[i]}$ . It is well known that a parity-check matrix of an  $[n, k, d]$  Gabidulin code is of the form:

$$H = \begin{pmatrix} h_1^{[0]} & \cdots & h_n^{[0]} \\ h_1^{[1]} & \cdots & h_n^{[1]} \\ \vdots & \cdots & \vdots \\ h_1^{[d-2]} & \cdots & h_n^{[d-2]} \end{pmatrix}$$

#### 4.2 Generalized Subspace subcodes of Gabidulin codes

**Proposition 7.** *Let  $Gab_k(g)$  be a Gabidulin code of length  $n$  over  $\mathbb{F}_{q^m}$  of parameters  $[n, k, d]_{q^m}$ . Let  $V_1, \dots, V_n$  be a set of  $n$   $\mathbb{F}_q$ -subspaces of  $\mathbb{F}_{q^m}$  of dimension respectively  $s_i \leq m$ . Set  $W = \prod_{i=1}^n V_i$ , constituted of  $n$ -tuples with the  $i$ -th coordinate in  $V_i$ . If  $\sum_{i=1}^n s_i - m(n-k) > 0$  then:*

$$q^{\sum_{i=1}^n s_i - m(n-k)} \leq |RGSS_W(Gab_k(g))| \leq q^{m(\max_{1 \leq i \leq n} s_i) - d + 1}$$

*Proof.* According to the previous proposition we have

$$c \in RGSS_W(C) \Leftrightarrow \begin{cases} c = (\beta_1, \beta_2, \dots, \beta_{s_n})U \\ (\beta_1, \beta_2, \dots, \beta_{s_n})UH^T = 0 \end{cases}$$

$$\text{where } H = \begin{pmatrix} h_1^{[0]} & \cdots & h_n^{[0]} \\ h_1^{[1]} & \cdots & h_n^{[1]} \\ \vdots & \cdots & \vdots \\ h_1^{[d-2]} & \cdots & h_n^{[d-2]} \end{pmatrix}.$$

By setting  $L = UH^T$ , we have  $L_{i,j} = \sum_{l=1}^n u_{i,l} h_l^{[j-1]} = (\sum_{l=1}^n u_{i,l} h_l)^{[j-1]} = L_{i,1}^{[j-1]}$ .

This means, for  $1 \leq j \leq d-1$ ,  $0 = b_n UH^T$  then  $0 = (\beta_1, \beta_2, \dots, \beta_{s_n}) \cdot \begin{pmatrix} w_1^{[j-1]} \\ w_2^{[j-1]} \\ \vdots \\ w_{s_n}^{[j-1]} \end{pmatrix}$

where  $w_i = L_{i,1}$ ,  $\Rightarrow 0 = \beta_1 w_1^{[j-1]} + \beta_2 w_2^{[j-1]} + \dots + \beta_{s_n} w_{s_n}^{[j-1]} = (\beta_1^{[m-j+1]} w_1 + \beta_2^{[m-j+1]} w_2 + \dots + \beta_{s_n}^{[m-j+1]} w_{s_n})^{[j-1]} \Rightarrow 0 = \beta_1^{[m-j+1]} w_1 + \beta_2^{[m-j+1]} w_2 + \dots + \beta_{s_n}^{[m-j+1]} w_{s_n}$

$$\Rightarrow 0 = (w_1, \dots, w_{s_n}) \begin{pmatrix} \beta_1^{[m-j+1]} \\ \beta_2^{[m-j+1]} \\ \vdots \\ \beta_{s_n}^{[m-j+1]} \end{pmatrix}$$

which leads to the result

$$(w_1, \dots, w_{s_n}) \begin{pmatrix} \beta_1^{[m]} & \beta_1^{[m-1]} & \dots & \beta_1^{[m-d+2]} \\ \beta_2^{[m]} & \beta_2^{[m-1]} & \dots & \beta_2^{[m-d+2]} \\ \vdots & \vdots & \dots & \vdots \\ \beta_{s_n}^{[m]} & \beta_{s_n}^{[m-1]} & \dots & \beta_{s_n}^{[m-d+2]} \end{pmatrix} = 0$$

Let  $\mathcal{B}_W$  be the Gabidulin code having parity-check matrix  $T = (\beta_j^{[m-i+1]})_{i=1, j=1}^{d-1, s_n}$  then  $c = b_n U \in RGSS_W(Gab_k(g)) \Rightarrow (w_1, \dots, w_{s_n}) \in \mathcal{B}_W \Rightarrow |RGSS_W(Gab_k(g))| \leq |\mathcal{B}_W| = q^{m(s_n-d+1)} = q^{m(s_n-d+1)} = q^{m(\max_i(s_i)-d+1)}$ .

according to proposition 6

$$q^{\sum_{i=1}^n s_i - m(n-k)} \leq |RGSS_W(Gab_k(g))| \leq q^{m(\max_{1 \leq i \leq n} (s_i) - d + 1)}$$

**Corollary 4.** [8]

Let  $Gab_k(g)$  be a Gabidulin code of length  $n$  over  $\mathbb{F}_{q^m}$  of parameters  $[n, k, d]_{q^m}$ . Let  $V$  be an  $\mathbb{F}_q$ -subspaces of  $\mathbb{F}_{q^m}$  of dimension  $s \leq m$ . If  $ns - m(n-k) > 0$  then:

$$q^{ns - m(n-k)} \leq |Gab_k(g)|_V \leq q^{m(s-d+1)}$$

**Proposition 8.** The  $q$ -ary image of a Gabidulin code  $Gab_k(g)$  of length  $n$  over  $\mathbb{F}_{q^m}$  of parameters  $[n, k, d]_{q^m}$  from the basis  $B$  with respect to the  $n$  bases  $(B_1, \dots, B_n)$  of  $\mathbb{F}_{q^m}$ ,  $Im_{q, (B_i)_i}(Gab_k(g))$  has generator matrix the block matrix  $((M_{g_j}^{q^{i-1}})^T)_{1 \leq i \leq k, 1 \leq j \leq n} \in (\mathbb{F}_q^{m \times m})^{k \times n}$  where the matrix  $M_{g_j} = \mathcal{M}_{B, B_j}(f_{g_j})$  corresponds to  $f_{g_j}(x) = g_j x$ .

## 5 Parent codes of Gabidulin RGSS codes

For decoding needs, it is possible to use a code linked to it by an injective morphism which preserves the rank. In the following we will give the construction of these codes called Parent code introduced in [6].

**Definition 10.** (Parent Code)

The linear code over  $\mathbb{F}_{q^m}$  defined above  $\mathcal{B}_W$ , with parity-check matrix  $T = (\beta_j^{[m-i+1]})_{i=1, j=1}^{d-1, s_n}$  is called the parent code of  $RGSS_W(Gab_k(g))$ . It is denoted by  $PRGSS_W(Gab_k(g))$ .

---

**Algorithm 1** Generator matrix  $G$  of  $RGSS_W(Gab_k(g))$ 


---

**Require:** A generator matrix  $G \in \mathbb{F}_q^{k \times n}$  of  $Gab_k(g)$ , and  $D_1, \dots, D_n$  be a set of  $n$   $\mathbb{F}_q$ -free family of cardinal respectively  $s_j \leq m$ .

**Ensure:**  $G_U$  generator matrix of  $Im_{q, (B_j)_j}^B(RGSS_W(Gab_k(g)))$

$U = \bigcup_{j=1}^n u_j$  such that for  $1 \leq j \leq n$ ,  $u_j = \{(j-1)m+1, \dots, (j-1)m+s_j\}$ .

Complete the bases  $D_1, \dots, D_n$  into  $B_1, \dots, B_n$

Set  $Q_j$  be the change-of-basis matrix from the basis  $B$  to the basis  $B_j$ ,

Compute a generator matrix  $\hat{G}^B$  of  $Im_{q, B}(Gab_k(g))$

Compute a parity check matrix  $\hat{H}^B$  from  $\hat{G}^B$

Compute  $\hat{H}_{(B_j)_j}^B = \hat{H}_B \cdot \text{Diag}((Q_1^{-1})^T, \dots, (Q_n^{-1})^T)$

Compute  $M_U = P_U(\hat{H}_{(B_j)_j}^B)$  as the parity-check matrix of extend  $RGSS_W(Gab_k(g))$

Compute  $G_U$  generator matrix of  $Im_{q, (B_j)_j}^B(RGSS_W(Gab_k(g)))$  from  $M_U$ .

---

**Proposition 9.** *the parent code of  $RGSS_W(Gab_k(g))$  coincides with the parent code of  $Gab_k(g)|_{V_{\max(s_i)}}$  up to isomorphism.*

**Proposition 10.** *Let  $Gab_k(g)$  be a Gabidulin code of length  $n$  over  $\mathbb{F}_q^m$  of parameters  $[n, k, d]_q^m$  with a parity check matrix admitting  $h = (h_1, h_2, \dots, h_n)$  as first row. Let  $V_1, \dots, V_n$  be a set of  $n$   $\mathbb{F}_q$ -subspaces of  $\mathbb{F}_q^m$  of dimension respectively  $s_i \leq m$  and Let  $b_i = \{\beta_1, \beta_2, \dots, \beta_{s_i}\}$  a basis of  $V_i$  with  $1 \leq i \leq n$  such that the bases form an inclusion chain and  $b$  the maximal basis up to isomorphism. Then the map:*

$$f_b : W \rightarrow (\mathbb{F}_q^m)^{\max(s_i)}, c = bU \mapsto f_b(c) = hU^T$$

*is a rank-preserving injective  $\mathbb{F}_q$ -linear map and  $f_b(RGSS_W(Gab_k(g))) \subset P_{RGSS_W(Gab_k(g))}$*

*Proof.* Since  $h = (h_1, h_2, \dots, h_n)$  are linearly independent over  $\mathbb{F}_q$ , then  $\ker(f_b) =$

$\{0\}$  so  $f_b$  injective and  $Rk(bU) = Rk(U) = Rk(hU)$  for any  $U \in \mathbb{F}_q^{\max(s_i) \times n}$ .

By construction, we have  $f_b(RGSS_W(Gab_k(g))) = P_{RGSS_W(Gab_k(g))}$ .

we can therefore note that the minimum distance of  $RGSS_W(Gab_k(g))$  is smaller or equal than that of  $P_{RGSS_W(Gab_k(g))}$ .

## References

1. Thierry P. Berger, Cheikh Thiécoumba Gueye, Jean Belo Klamti, and Olivier Ruatta. Designing a public key cryptosystem based on quasi-cyclic subspace subcodes of reed-solomon codes. In Cheikh Thiécoumba Gueye, Edoardo Persichetti, Pierre-Louis Cayrel, and Johannes Buchmann, editors, *Algebra, Codes and Cryptology*, pages 97–113, Cham, 2019. Springer International Publishing.
2. Thierry P. Berger, Cheikh Thiécoumba Gueye, and Jean Belo Klamti. Generalized subspace subcodes with application in cryptology. *IEEE Transactions on Information Theory*, 65(8):4641–4657, 2019.
3. Thierry P. Berger and Pierre Loidreau. How to mask the structure of codes for a cryptographic use. *Designs, Codes and Cryptography*, 35:63–79, 2005.
4. Alain Couvreur and Matthieu Lequesne. On the security of subspace subcodes of Reed-Solomon codes for public key encryption. *IEEE Transactions on Information Theory*, 68(1):632–648, October 2021.
5. Ph Delsarte. Bilinear forms over a finite field, with applications to coding theory. *Journal of Combinatorial Theory, Series A*, 25(3):226–241, 1978.
6. E.M. Gabidulin and P. Loidreau. On subcodes of codes in rank metric. In *Proceedings. International Symposium on Information Theory, 2005. ISIT 2005.*, pages 121–123, 2005.
7. Ernest Mukhamedovich Gabidulin. Theory of codes with maximum rank distance. *Problemy peredachi informatsii*, 21(1):3–16, 1985.
8. Ernst M. Gabidulin and Pierre Loidreau. Properties of subspace subcodes of gabidulin codes. *Advances in Mathematics of Communications*, 2(2):147–157, 2008.
9. Ernst M Gabidulin, AV Paramonov, and OV Tretjakov. Ideals over a non-commutative ring and their application in cryptology. In *Workshop on the Theory and Application of Cryptographic Techniques*, pages 482–489. Springer, 1991.
10. Philippe Gaborit, Adrien Hauteville, and Jean-Pierre Tillich. Ranksynd a prng based on rank metric. In Tsuyoshi Takagi, editor, *Post-Quantum Cryptography*, pages 18–28, Cham, 2016. Springer International Publishing.
11. M. Hattori, R.J. McEliece, and G. Solomon. Subspace subcodes of reed-solomon codes. *IEEE Transactions on Information Theory*, 44(5):1861–1880, 1998.
12. W. Cary Huffman and Vera Pless. *Fundamentals of Error-Correcting Codes*. Cambridge University Press, 2003.
13. J.M. Jensen. Subgroup subcodes. *IEEE Transactions on Information Theory*, 41(3):781–785, 1995.
14. Hsiao-Feng Lu and P.V. Kumar. A unified construction of space-time codes with optimal rate-diversity tradeoff. *IEEE Transactions on Information Theory*, 51(5):1709–1730, 2005.
15. Carlos Aguilar Melchor, Nicolas Aragon, Magali Bardet, Slim Bettaieb, Loïc Bidoux, Olivier Blazy, and Jean-Christophe Deneuville. Rollo-rank-ouroboros, lake & locker. 2019.
16. Oystein Ore. On a special class of polynomials. *Transactions of the American Mathematical Society*, 35(3):559–584, 1933.
17. Raphael Overbeck. A new structural attack for gpt and variants. In *International Conference on Cryptology in Malaysia*, pages 50–63. Springer, 2005.
18. Irving S. Reed and Gustave Solomon. Polynomial codes over certain finite fields. *Journal of The Society for Industrial and Applied Mathematics*, 8:300–304, 1960.
19. Yingquan Wu. On expanded cyclic and reed-solomon codes. *IEEE Transactions on Information Theory*, 57(2):601–620, 2011.