

On the Role of Morphological Information for Contextual Lemmatization

Olia Toporkov^a, Rodrigo Agerri^{a,*}

^a*HiTZ Center - Ixa, University of the Basque Country UPV/EHU, Donostia-San Sebastián, Spain*

Abstract

Lemmatization is a Natural Language Processing (NLP) task which consists of producing, from a given inflected word, its canonical form or lemma. Lemmatization is one of the basic tasks that facilitate downstream NLP applications, and is of particular importance for high-inflected languages. Given that the process to obtain a lemma from an inflected word can be explained by looking at its morphosyntactic category, including fine-grained morphosyntactic information to train contextual lemmatizers has become common practice, without analyzing whether that is the optimum in terms of downstream performance. Thus, in this paper we empirically investigate the role of morphological information to develop contextual lemmatizers in six languages within a varied spectrum of morphological complexity: Basque, Turkish, Russian, Czech, Spanish and English. Furthermore, and unlike the vast majority of previous work, we also evaluate lemmatizers in out-of-domain settings, which constitutes, after all, their most common application use. The results of our study are rather surprising: (i) providing lemmatizers with fine-grained morphological features during training is not that beneficial, not even for agglutinative languages; (ii) in fact, modern contextual word representations seem to implicitly encode enough morphological information to obtain good contextual lemmatizers without seeing any explicit morphological signal; (iii) the best lemmatizers out-of-domain are those using simple UPOS tags or those trained without morphology; (iv) current evaluation practices for lemmatization are not adequate to clearly discriminate between models.

Keywords: Lemmatization, Information Extraction, Edit Distance, Sequence Labelling, Semi-supervised learning, Natural Language Processing

1. Introduction

Lemmatization is one of the basic NLP tasks which consists of converting an inflected word form (e.g. *eating*, *ate*, *eaten*) into its canonical form (e.g. *eat*), usually known as lemma. Lemmatization is commonly used when performing many NLP tasks such as

*Corresponding author

Email addresses: olia.toporkov@ehu.eus (Olia Toporkov), rodrigo.agerri@ehu.eus (Rodrigo Agerri)

information retrieval, named-entity recognition, sentiment analysis, word sense disambiguation, and others. For example, for agglutinative languages named entities are also inflected, which means that lemmatization is required as an additional process. Thus, lemmatization is more challenging for languages with rich morphology as the number of variations for every different word form in such languages is very high. Table 1 illustrates this point by showing the difference in inflections of the word ‘cat’ for four languages with different morphological structure. They offer a spectrum of varied complexity, ranging from the more complex ones, Basque and Russian, to the less inflected ones, such as Spanish and English, in that order.

English	Spanish	Russian	Basque
cat	gato	КОТ	katu
cats	gatos	КОТЫ	katuak
		КОТА	katua
		КОТУ	katuari
		КОТОМ	katuarekin
		КОТЕ	katuek
		КОТОВ	katuekin
		КОТАМ	katuei
		КОТАМИ	katuen
		КОТАХ	katuak
			katuarentzat
			katuentzat

Table 1: Examples of inflected forms of the word ‘cat’ in Basque, English, Spanish and Russian.

As we can see in Table 1, the word ‘cat’ can vary in English by changing from singular to plural. In Spanish gender (masculine/feminine) is also marked. Things get more complicated with cased languages. For example, in Russian there are six cases while for Basque there are 16, some of which can be doubly inflected.

Both the context in which it occurs and the morphosyntactic form of a word play a crucial role to approach automatic lemmatization (Haspelmath and Sims, 2013). Thus, in Figure 1 we can see a fragment of a Russian sentence in which each inflected word form has a corresponding lemma (in red). Furthermore, each inflected form has an associated number of morphosyntactic features (expressed as tags) depending on its case, number, gender, animacy and others. Morphological analysis is crucial for lemmatization as it explains the process required to produce the lemma from the word form, which is why it has traditionally been used as a stepping stone to design systems to perform lemmatization.

As many other tasks in NLP, first approaches to lemmatization were rule-based, but nowadays the best performing models address lemmatization as a supervised task in which learning in context is crucial. Regardless of the learning method used, three main trends can be observed in current contextual lemmatization: (i) those that use gold standard or learned morphological tags to generate features to learn lemmatization in a pipeline approach (Chrupala et al., 2008; Yildiz and Tantuğ, 2019); (ii) those that aim to jointly learn morphological tagging and lemmatization as a single task Müller et al. (2015a); Malaviya et al. (2019); Straka et al. (2019); (iii) systems that do not use any

Morph.tag:	ADP	DAT; NEUT; PL; INAN; N	PROPN; SG; GEN; ANIM; MASC	ADV	PFV; NFIN; ACT; V	SG; INAN; ACC; N; MASC
Lemma:	по	сочинение	Галилей	можно	делать	вывод [...]
Inflection:	По	сочинениям	Галилея	можно	сделать	вывод [...]
Translation:	<i>By</i>	<i>the writings</i>	<i>of Galileo</i>	<i>we can</i>	<i>make</i>	<i>a conclusion [...]</i>

Figure 1: Example of a morphologically tagged and lemmatized sentence in Russian using the Unimorph annotation scheme

explicit morphological signal to learn to lemmatize (Chakrabarty et al., 2017; Bergmanis and Goldwater, 2018).

Research on contextual (mostly neural) lemmatization was greatly accelerated by the first release of the Universal Dependencies (UD) data (de Marneffe et al., 2014; Nivre et al., 2017), but specially by the contextual lemmatization shared task organized at Sigmorphon 2019, which included Unimorph datasets for more than 50 languages (McCarthy et al., 2019). It should be noted that the best models in the task used morphological information either as features (Yildiz and Tantuğ, 2019) or as part of a joint or a multi-task approach (Straka et al., 2019). However, the large majority of previous approaches have used the full morphological tag from Unimorph/UD assuming that fine-grained morphological information must be always beneficial for lemmatization, especially for highly inflected languages, but without analyzing whether that is the optimum in terms of downstream performance.

In order to address this issue, in this paper we empirically investigate the role of morphological information to develop contextual lemmatizers in six languages within a varied spectrum of morphological complexity: Basque, Turkish, Russian, Czech, Spanish and English. Furthermore, previous work has shown that morphological taggers substantially degrade when evaluated out-of-domain, be that any type of text different from the data used for training in terms of topic, text genre, temporality, etc. (Manning, 2011). This point led us to research whether lemmatizers based on fine-grained morphological information will degrade more when used out-of-domain than those requiring only coarse-grained UPOS tags. We believe that this is also an important point because lemmatizers are mostly used out-of-domain, namely, to lemmatize data different from the type that was employed for training.

Taking these issues into consideration, in this paper we set to investigate the following research questions with respect to the actual role of morphological information to perform contextual lemmatization: (i) is fine-grained morphological information really necessary, even for high-inflected languages? (ii) are modern context-based word representations enough to learn competitive contextual lemmatizers without including any explicit morphological signal for training? (iii) do morphologically enriched lemmatizers perform worse out-of-domain as the complexity of the morphological features increases?

(iv) what is the optimal strategy to obtain robust contextual lemmatizers for out-of-domain settings? (v) are current evaluation practices adequate to meaningfully evaluate and compare contextual lemmatization techniques?

The conclusions from our experimental study are the following: (i) fine-grained morphological features do not always benefit, not even for agglutinative languages; (ii) modern contextual word representations seem to implicitly encode enough morphological information to obtain state-of-the-art contextual lemmatizers without seeing any explicit morphological signal; (iii) the best lemmatizers out-of-domain are those using simple UPOS tags or those trained without explicit morphology; (iv) current evaluation practices for lemmatization are not adequate to clearly discriminate between models, and other evaluation metrics are required to better understand and manifest the shortcomings of current lemmatization techniques. The generated code and datasets are publicly available to facilitate reproducibility of results and further research on this topic¹.

The rest of the paper is structured as follows. Next section discusses the most relevant work related to contextual lemmatization. The systems and datasets used in our experiments are presented in Sections 4 and 3, respectively. Section 5 presents the experimental setup applied to obtain the results, which are reported in Section 6. Section 7 provides a discussion and error analysis of the results. We finish with some concluding remarks in Section 8.

2. Background

First approaches in lemmatization consisted of systems based on dictionary lookup and/or rule-based finite state machines (Karttunen et al., 1992; Oflazer, 1993; Alegria et al., 1996; van den Bosch and Daelemans, 1999; Dhonnchadha, 2002; Segalovich, 2003; Carreras et al., 2004; Stroppa and Yvon, 2005; Jongejan and Dalianis, 2009). Grammatical rules in such systems were either hand-crafted or learned automatically by using machine learning and such rules were leveraged to perform lemmatization together with the use of lexicons or morphological analyzers that returned the correct lemma. The problem of unseen and rare words was solved by generating a set of exceptions added to the general set of rules (Karttunen et al., 1992; Oflazer, 1993) or using a probabilistic approach (Segalovich, 2003). Such systems resulted in very language-dependent approaches, and in most of the cases they required a huge linguistic knowledge and effort, especially in the case of those languages with more complex, high-inflected morphology.

The appearance of large annotated corpora with morphological information and lemmas facilitated the development of machine learning methods for lemmatization in multiple languages. One of the core projects that gathered annotated corpora for more than 90 languages is the Universal Dependencies initiative (Nivre et al., 2017). This project offers a unified morphosyntactic annotation across languages with language-specific extensions when necessary. Based on the UD resources, the Universal Morphology (UniMorph) project (McCarthy et al., 2020) defines a universal tagset for morphological annotation, namely, the Unimorph schema, where each inflected word form is associated with a lemma and a set of morphological features. The current UniMorph dataset includes

¹<https://github.com/oltoporkov/morphological-information-datasets>

118 languages, including extremely low-source languages such as Quechua, Navajo and Haida.

The assumption that context could help with unseen and ambiguous words led to the creation of supervised contextual lemmatizers. The pioneer work on this topic is perhaps the statistical contextual lemmatization model provided by Morfette (Chrupala et al., 2008). Morfette uses a Maximum Entropy classifier to predict morphological tags and lemmas in a pipeline approach. Interestingly, instead of learning the lemmas themselves, Chrupala et al. (2008) proposes to learn automatically induced lemma classes based on the shortest edit script (SES), which consists of the distance between the inflected word form and its lemma. Morfette has influenced many other works on contextual lemmatization, such as the system of Gesmundo and Samardžić (2012), IXA pipes (Agerri et al., 2014; Agerri and Rigau, 2016), Lemming (Müller et al., 2015b) and the system of Malaviya et al. (2019). The importance of using context to learn lemmatization is investigated in the work of Bergmanis and Goldwater (2018). They compare context-free and context-sensitive versions of their neural lemmatizer Lematus and evaluate them across 20 languages. Results show that including context substantially improves lemmatization accuracy and it helps to better deal with the out-of-vocabulary problem.

The next step in the development of contextual lemmatization systems came with the supervised approaches based on deep learning algorithms and vector-based word representations (Chakrabarty et al., 2017; Dayanik et al., 2018; Bergmanis and Goldwater, 2018; Malaviya et al., 2019). The parallel development of the transformer architecture (Vaswani et al., 2017) and the appearance of BERT (Devlin et al., 2019) and other transformer-based Masked Language Models (MLMs) offered the possibility to significantly improve lemmatization results. Thus, most of the participating systems in the SIGMORPHON 2019 shared task on contextual lemmatization were based on MLMs (McCarthy et al., 2019). The datasets used in the shared task were extracted from Universal Dependencies and their initial morphological annotations were converted to the Unimorph schema for 66 languages. The baseline provided by the task was based on the work of Malaviya et al. (2019), a system which performs joint morphological tagging and lemmatization.

To the best of our knowledge, current state-of-the-art results in contextual lemmatization are provided by those models that achieved best results in the SIGMORPHON 2019 shared task. The highest overall accuracy was achieved by UDPipe (Straka et al., 2019). Using UDPipe 2.0 (Straka, 2018) as a baseline, they added pre-trained contextualized BERT and Flair embeddings as an additional input to the network. The overall accuracy (average across all languages) was 95.78, the best among all the participants.

The second best result (95 overall word accuracy) in the task was obtained by the CHARLES-SAARLAND system (Kondratyuk, 2019). This system consists of a combination of a shared BERT encoder and joint lemma and morphology tag decoder. The model uses a two-stage training process, in which it first performs a multilingual training over all treebanks, and then they execute the same process monolingually, maintaining the previously learned multilingual weights. Morphological tags in this case are calculated jointly and lemmas are also represented as SES. The experiments are performed using multilingual BERT in combination with the methods introduced by UDify (Kondratyuk and Straka, 2019) for BERT fine-tuning and regularization.

The third best result was (94.76) reported by Morpheus (Yildiz and Tantuğ, 2019). Morpheus uses a two-level LSTM network which gets as input the vector-based repre-

sentations of words, morphological tags and SES. Morpheus then aims to jointly output, for a given sequence, their corresponding morphological labels and the SES representing the lemma class which is later decoded into its lemma form.

Thus, it can be seen that a common trend in current contextual lemmatization is to use the morphological information provided by the full Unimorph labels without taking into consideration whether this is the optimal setting. Furthermore, lemmatization techniques are only evaluated in-domain, resulting in extremely, and perhaps deceptive, high results for the large majority of the 66 languages included in the SIGMORPHON 2019 data.

3. Languages and Datasets

In order to address the research questions formulated in the Introduction, we selected the following six languages: Basque, Turkish, Russian, Czech, Spanish and English. Such a choice will allow us to compare the role of fine-grained morphological information to learn contextual lemmatization within a range of languages of varied morphological complexity. In this Section we briefly describe general morphological characteristics of each language as well as the specific datasets used.

3.1. Languages

Basque and Turkish are agglutinative languages with morphology mostly of the suffixing type. Basque is a language isolate and does not belong to any language group while Turkish is a member of the Oghuz group of the Turkic family. These two languages have no grammatical gender, with some particular exceptions for domestic animals, people and foreign words (Turkish) or in some colloquial forms when the gender of the addressee is expressed for the second person singular pronoun (Basque). Turkish and Basque have two number types (singular and plural), and in Basque there is also the unmarked number (undefined or *mugagabea*). In both Turkish and Basque the cases are expressed by suffixation.

Basque is an ergative-absolutive language containing 16 cases, meaning that the grammatical case marks both the subject of an intransitive verb and the object of a transitive verb. The verb conjugation is also specific for this language: the majority of the verbs are formed by a combination of a gerund form and a conjugated auxiliary verb.

Turkish has six general cases; nouns and adjectives are not distinguished morphologically and adjectives can also be used as adverbs without modifications or by doubling of the word. For verbs there are 9 simple and 20 compound tenses. There is a relatively small set of core vocabulary and the majority of Turkish words originate from applying derivative suffixes to nouns and verbal stems.

The two Slavic languages, namely, Russian and Czech, exhibit a highly inflectional morphology and a wide number of morphological features. Russian belongs to the East Slavic language group, while Czech is a West Slavic language. These two languages have nominal declension which involves six main grammatical cases for Russian and seven for Czech. Both languages distinguish between two number (singular and plural) and three gender types (masculine, feminine and neuter). Furthermore, the masculine gender is subdivided into animate and inanimate. Verbs are conjugated for tense (past, present or future) and mood.

Spanish is a Romance language that belongs to Indo-European language family. It is a fusional language, which has a tendency to use a single inflectional morpheme to denote multiple grammatical, syntactic or semantic features. Nouns and adjectives in Spanish have two gender (male, female) and two number types (singular and plural). Besides, articles and some pronouns and determiners also possess a neuter gender. There are 3 main verb tenses (past, present and future) and each verb has around fifty conjugated forms. Apart from that, Spanish has 3 verboid forms (infinitive, gerund, past participle), perfective and imperfective aspects for past, 4 moods and 3 persons.

Finally, English is a Germanic language, also part of Indo-European language family. It has much lower inflection in comparison to previously mentioned languages. Only nouns, pronouns and verbs are inflected, while the rest of the parts of speech are invariable. In English animate nouns have two genders (masculine or feminine) and the third person singular pronouns distinguish three gender types: masculine, feminine, and neuter, while for most of the nouns there is no grammatical gender. Nouns have only a genitive case and personal pronouns are mostly declined in subjective and objective case. English has a variety of auxiliary verbs that help to express the categories of mood and aspect and participate in the formation of verb tenses.

3.2. Datasets

The datasets we used are distributed as part of the data used for the SIGMORPHON 2019 shared task (McCarthy et al., 2019). The source of the original datasets comes from the Universal Dependencies (UD) project (de Marneffe et al., 2014), but the morphological annotations are converted from UD annotations to the UniMorph schema (Kirov et al., 2018) with the aim to increase agreement across languages. As our experiments will include both in-domain and out-of-domain evaluations, we selected some datasets for each of the settings.

With respect to in-domain, we chose one corpus per language using the standard train and development partitions. For Basque we used the Basque Dependency Treebank (BDT) (Aldezabal et al., 2008), which contains mainly literary and journalistic texts. The corpus was manually annotated and then automatically converted to UD format. For Czech we used the CAC treebank (Hladka et al., 2008) based on the Czech Academic Corpus 2.0. This corpus includes mostly unabridged articles from a wide range of media such as newspapers, magazines and transcripts of spoken language from radio and TV programs. The corpus was annotated manually and then converted to UD format. With respect to English we chose English Web Treebank (EWT) (Silveira et al., 2014). This corpus includes different Web sources: blogs, various media, e-mails, reviews and Yahoo! answers. In the EWT corpus the lemmas were assigned by UD-converter and manually corrected. UPOS tags were also converted to UD format from manual annotations. For Russian we used GSD corpus, extracted from Wikipedia and manually annotated by native speakers. In the case of Spanish we selected the GSD corpus as well, consisting of texts from blogs, reviews, news and Wikipedia. Finally, for Turkish we used ITU-METU-Sabancı Treebank (IMST) (Sulubacak et al., 2016). It consists of well-edited sentences from a wide range of domains, manually annotated and automatically converted to UD format.

For the out-of-domain evaluation setting we picked the test sets of other datasets included in Unimorph, different from the ones selected for in-domain experimentation. In the case of Basque, only one corpus was available in the Universal Dependencies project,

so we used the Armiarma corpus which consists of literary critics semi-automatically annotated using Eustagger (Alegria et al., 1996). For Czech and Turkish we used the PUD data - part of the Parallel Universal Dependencies treebanks created for the CoNLL 2017 shared task (Zeman et al., 2017). The corpora consist of 1,000 sentences from the news domain and Wikipedia annotated for 18 languages. The Czech language PUD data was manually annotated and then automatically converted to UD format. For Turkish the original data was automatically converted to UD format, but later manually reannotated (Türk et al., 2019). In the case of English we used the Georgetown University Multilayer (GUM) corpus (Zeldes, 2017). This corpus presents a collection of annotated Web texts from interviews, news, travel guides, academic writing, biographies and fiction from such sources as Wikipedia, Wikinet and Reddit. Its lemmas were manually annotated, while UPOS tags were converted to UD format from manual annotations. For Russian we used SynTagRus (Lyashevskaya et al., 2016), which consists of texts from a variety of genres, such as contemporary fiction, popular science, as well as news and journal articles from the 1960-2016 period. Its lemmas, UPOS tags and morphological features were manually annotated in non-UD style and then automatically converted to UD format. For Spanish we chose the AnCora corpus (Taulé et al., 2008), which contains mainly texts from news. All the elements of this corpus were converted to UD format from manual annotations.

4. Systems

In this section we present the systems that we will be applying in our investigation. First, research on the role of fine-grained morphological information for contextual lemmatization will be performed in-domain using the statistical lemmatizer from the IXA pipes toolkit (Agerri and Rigau, 2016) and Morpheus, the third best system in the SIGMORPHON 2019 shared task. These two systems were chosen due to several reasons: (i) both use morphological information as features to learn lemmatization and, (ii) both systems use SES to represent automatically induced lemma classes; (iii) they both address contextual lemmatization as sequence tagging.

In order to investigate whether modern contextual word representations are enough to learn competitive lemmatizers both in- and out-of-domain, we train baseline models using Flair (Akbik et al., 2018), multilingual MLMs mBERT and XLM-RoBERTa Devlin et al. (2019); Conneau et al. (2020) as well as language-specific MLMs for each of the languages: BERTeus for Basque (Agerri et al., 2020), slavicBERT for Czech (Arhipov et al., 2019), RoBERTa for English (Liu et al., 2019), Russian ruBERT (Kuratov and Arhipov, 2019), Spanish BETO (Cañete et al., 2020) and BERTurk for Turkish Schweter (2020). As with Morpheus and IXA pipes, we treat contextual lemmatization as a sequence tagging task and fine-tune the language models by adding a single linear layer to the top.

4.1. Systems using morphology

IXA pipes is a set of multilingual tools which is based on a pipeline approach (Agerri et al., 2014; Agerri and Rigau, 2016). IXA pipes learns perceptron (Collins, 2002) models based on shallow local features combined with pre-trained clustering features induced over large unannotated corpora. The lemmatizer implemented in IXA pipes is inspired by the work of Chrupala et al. (2008), where the model learns the SES between the word form and its lemma. IXA pipes allows to learn lemmatization using gold-standard or learned morphological tags.

Language	Model	Architecture	Training corpus and number of tokens
Basque	BERTeus	BERT	35M tokens (Wikipedia) + 191M tokens (online)
Czech	slavicBERT	BERT	Russian news and Wikipedia in Russian, Bulgarian, Czech and Polish
English	RoBERTa	BERT	BookCorpus (16GB) + CC-News (76GB) OpenWebText (38GB) + Stories (31GB)
Russian	ruBERT	BERT	Dataset for original BERT (BooksCorpus(800M)), English Wikipedia (2500M), Russian news and Wikipedia for subword vocabulary
Spanish	BETO	BERT	Wikipedia and OPUS project in Spanish (3B words)
Turkish	BERTurk	BERT	OSCAR corpus, Wikipedia, OPUS corpora, corpus of Kemal Oflaizer (35GB total)

Table 2: List of language-specific models used in the experiments for each of the target languages.

Morpheus is a neural contextual lemmatizer and morphological tagger which consists of two separate sequential decoders for generating morphological tags and lemmas. The input words and morphological features are encoded in context-aware vector representations using a two-level LSTM network and the decoders predict both the morphological tags and the SES, which are later decoded into its lemma (Yildiz and Tantuğ, 2019). Morpheus obtained the third best overall result in the SIGMORPHON 2019 shared task (McCarthy et al., 2019).

4.2. Systems without explicit morphological information

We train a number of models that use modern contextual word representations by addressing lemmatization as a classic sequence tagging task. Thus, the input consists of words encoded as contextual vector representations and the task is to assign the best sequence of SES to a given input sequence.

Flair is an NLP framework based on a BiLSTM-CRF architecture (Huang et al., 2015; Ma and Hovy, 2016) and pre-trained language models that leverage character-based word representations which, according to the authors, capture implicit information about natural language syntax and semantics. Flair has obtained excellent results in sequence labelling tasks such as named-entity recognition, POS tagging and chunking (Akbik et al., 2018). The library includes pre-trained Flair language models for every language except Turkish.

With respect to the MLMs, we use two multilingual models and 6 language models trained specifically for each of the languages included in our study. Multilingual BERT (Devlin et al., 2019) is a transformer-based masked language model, pre-trained on the Wikipedias of 104 languages with both the masking and next sentence prediction objectives. Furthermore, we also use XLM-RoBERTa (Conneau et al., 2020), trained on 2.5TB of filtered CommonCrawl data for 100 languages. XLM-RoBERTa uses RoBERTa-base and therefore it is based on the BERT architecture but (i) trained only on the MLM task, (ii) on larger batches (iii) on longer sequences and (iv), with dynamic mask generation. Thus, multilingual BERT was trained with a batch size of 256 and 512 sequence length for 1M steps, using both the MLM and NSP tasks. Regarding XLM-RoBERTa, both versions (base and large) were trained over 1.5M steps with batch 8192 and sequences of 512 length. In this study we limit ourselves to the use of the base models.

Details about the six language-specific MLMs used are provided by Table 2. BERTeus (Agerri et al., 2020) is a BERT-base model trained on the BMC Basque corpus, which includes the Basque Wikipedia and news articles from online newspapers. Apart from the training data, the other difference from original BERT is the subword tokenization, which is closer to linguistically interpretable strings in Basque. BERTeus significantly outperforms multilingual BERT and XLM-RoBERTa in tasks such as POS tagging, named-entity recognition, topic modelling and sentiment analysis.

BERTurk² is a cased BERT-base model for Turkish. This model was trained on a filtered and sentence segmented version of the Turkish OSCAR corpus (Ortiz Suárez et al., 2019), together with Wikipedia, various OPUS corpora (Tiedemann, 2016) and data provided by Kemal Oflazer, which resulted in total size of 35GB.

For Czech we used slavicBERT (Arhipov et al., 2019), developed taking multilingual BERT as a basis and further pre-trained using Russian news and the Wikipedias of four Slavic languages: Russian, Bulgarian, Czech and Polish. The authors also rebuilt the vocabulary of subword tokens, using the subword-nmt repository³.

RuBERT was developed in a similar fashion as slavicBERT but only with Russian as target language using the Russian Wikipedia and news corpora (Kuratov and Arhipov, 2019). They generated a new subword vocabulary obtained from subword-nmt which contains longer Russian words and subwords.

For Spanish we used BETO (Cañete et al., 2020) - a BERT-base language model, trained on a large Spanish corpus. The authors of this model upgraded the initial BERT model by using the Dynamic Masking technique, introduced in RoBERTa. BETO performed 2M steps in two different stages: 900K steps with a batch size of 2048 and maximum sequence length of 128, and the rest of the training with batch size of 256 and maximum sequence length of 512. We use the version trained with cased data, which included the Spanish Wikipedia and various sources from the OPUS project (Tiedemann, 2012) in a final corpus size of around 3 billion words.

RoBERTa-base is the model chosen for English. RoBERTa (Liu et al., 2019) is an optimized version of BERT, as commented above. To train this model the authors, apart from the standard datasets used to train the BERT model, also used the CC-news dataset, including English news articles from all over the world published between January 2017 and December 2019. The total size of the training data exceeds 160GB of uncompressed text.

4.3. Baselines

We use two models as baselines. First, the system used as baseline for the SIGMORPHON 2019 shared task (McCarthy et al., 2019) a joint neural model for morphological tagging and lemmatization presented by Malaviya et al. (2019). This system performs morphological tagging by using a LSTM tagger described in Heigold et al. (2017) and Cotterell and Heigold (2017). The lemmatizer is a neural sequence-to-sequence model (Wu and Cotterell, 2019) which includes a hard attention mechanism with a training scheme based on dynamic programming. The tagger and lemmatizer are connected together by jackknifing (Agić and Schluter, 2017), which allows to avoid exposure bias and improve lemmatization results.

²<https://github.com/stefan-it/turkish-bert>

³<https://github.com/rsennrich/subword-nmt/>

The second baseline is the winner of the SIGMORPHON’19 shared task (Straka et al., 2019). UDpipe is a multitask model which jointly learns morphological tagging and lemmatization. The system architecture consists of three bidirectional LSTMs that process the input and softmax classifiers that generate lemmas and morphosyntactic features. Lemmatization is performed as a multiclass classification task, where the system predicts the correct lemma rule or SES.

5. Experimental Setup

The systems described above were trained on the datasets listed in Section 3.2 using the following methodology.

For the two IXA pipes models (using gold-standard and learned morphology) we used the default feature set, with and without clustering features, specified in Agerri and Rigau (2016). The default hyperparameters were also applied to train Morpheus (Yildiz and Tantug, 2019). The input character embedding length d_a is set to 128, the length of the word vectors d_e to 1024 and the length of the context-aware word vectors d_c to 2048. Moreover, the length of character vectors in the minimum edit prediction component d_u and the length of the morphological tag vectors d_v are set to 256. The hidden unit sizes in the decoder LSTMs d_g and d_q are set to 1024. The Adam optimization algorithm is used with learning rate $3e - 4$ to minimize the loss (Kingma and Ba, 2015).

Flair is used off-the-self with FastText CommonCrawl word embeddings (Grave et al., 2018) combined with Flair contextual embeddings for each of the languages. The hidden size of the LSTM is set to 256 with a batch of 16.

The MLMs were fine-tuned for lemmatization as a sequence tagging task by adding a single linear layer on top of the model being fine-tuned. A grid search of hyperparameters was performed to pick the best batch size (16, 32), epochs (5, 10, 15, 20, 25) and learning rate (1e-5, 2e-5, 3e-5, 5e-5). We pick the best model on the development set in terms of word accuracy and loss. A fixed seed is used to ensure reproducibility of the results.

For multilingual BERT we used a maximum sequence length of 128, batch size 32 and $5e - 5$ as learning rate while for XLM-RoBERTa we used the same configuration but with a batch of 16. For Russian we perform grid search on two language-specific models, namely, ruBERT and slavicBERT. RuBERT obtained the best results with a maximum sequence length of 128, batch size 16, and $5e - 5$ learning rate over 15 epochs. For the rest of the models the best configuration was that of XLM-RoBERTa over 5 epochs for BETO and RoBERTa-base, 10 epochs for BERTeus, 15 epochs for BERTurk and 20 epochs with slavicBERT for Czech.

6. Experimental Results

In this section we present the experiments to empirically address the following research questions with respect to the actual role of morphological information to perform contextual lemmatization: (i) is fine-grained morphological information really necessary, even for agglutinative languages? (ii) are modern context-based word representations enough to learn good contextual lemmatizers without including any explicit morphological signal during training? (iii) do morphologically enriched lemmatizers perform worse out-of-domain as the complexity of the morphological features increases? (iv) what is

the optimal strategy to obtain robust contextual lemmatizers for out-of-domain settings? (v) are current evaluation practices adequate to meaningfully evaluate and compare contextual lemmatization techniques?

Unlike the vast majority of previous work on contextual lemmatization, which has been mostly evaluated *in-domain* (McCarthy et al., 2019), we also report results in *out-of-domain* settings. It should be noted that by *out-of-domain* we mean to evaluate the model on a different data distribution from the data used for training.

First, Section 6.1 studies the in-domain performance of contextual lemmatizers depending on the type of morphological features used to inform the models during training. The objective is two-fold: (i) to determine whether complex (or any at all) morphological information is required to obtain competitive lemmatizers and (ii) to establish whether modern contextual word representations and large language models allow us to perform lemmatization without any morphological information.

Morphological label
UPOS
UPOS+Case+Gender
UPOS+Case+Number
UPOS+Case+Gender+Number
UPOS+AllFeaturesOrdered

Table 3: List of Unimorph morphological tags used.

Second, in the *out-of-domain* evaluation presented in Section 6.2 we analyze whether morphologically informed lemmatizers suffer from cascading errors when evaluated out-of-domain and, if so, whether the morphological complexity is a determining factor. Furthermore, comparing them with contextual lemmatizers developed without an explicit morphological signal would allow us to obtain a full picture as to what is the best strategy for out-of-domain settings (the most common application scenario).

6.1. In-domain evaluations

For the first experiment we train the two variants of the IXA pipes statistical system, *ixa-pipe-gs* and *ixa-pipe-mm* (Agerri and Rigau, 2016), and one neural lemmatizer, *Morpheus* (Yildiz and Tantuğ, 2019). As explained in Section 4, all three require explicit morphological information and they all apply a short-edit-script (SES) to automatically induced lemma classes from the training data.

Furthermore, we combined the Unimorph morphological tags to generate labels of different complexity. Thus, taking UPOS tags as a basis we obtain 5 different morphological tags, as shown in Table 3. The first 4 are combinations of UPOS, Case, Gender and Number. The last label includes UPOS and every feature present for a given word in Unimorph in the following order: {UPOS+Case+Gender+Number+Rest-of-the-features}. For some word types, such as prepositions or infinitives, Unimorph only includes the UPOS tag. In order to illustrate this, Table 4 provides an example originally in Russian including the information required to train contextual lemmatizers, namely, the word, some morphological tag, and the lemma.

Putting it all together, Table 5 characterizes the final datasets used for in- and out-of-domain evaluation. The number of tokens, unique labels per category and unique SES

Word form	Morphological label {UPOS+Case+ Gender}	Lemma
Проект [<i>Project</i>]	NNOMMASC	проект [<i>project</i>]
сильно [<i>a lot</i>]	ADV	сильно [<i>a lot</i>]
отличался [<i>differed</i>]	VMASC	отличаться [<i>to differ</i>]
от [<i>from</i>]	ADP	от [<i>from</i>]
предыдущих [<i>previous</i>]	ADJGEN	предыдущий [<i>previous</i>]
подлодок [<i>submarines</i>]	NGENFEM	подлодка [<i>submarine</i>]
.	—	.

Table 4: An example of the data used to train contextual lemmatizers with morphological information.

(calculated using the UDpipe method) illustrate the varied complexity of the languages involved⁴. Thus, those languages with more complex morphology have a higher number of unique labels that include additional morphological features. The same pattern can be seen in the amount of lemma classes (SES), significantly larger for the languages with more complex morphology. In the case of Turkish the low number of lemmas could be explained by the fact that most of Turkish words are formed by applying derivative suffixes to nouns and verbal stems. Moreover, the core vocabulary in this particular corpus is rather small. Finally, we decided to order the subtags comprising the full Unimorph labels as the number of unique labels decreased significantly.

Figure 2 reports the in-domain results of training the three systems for the six languages with the 5 different types of morphological labels (detailed results per language and morphological configuration in Appendix A). First, the results show that the neural lemmatizer Morpheus outperforms the statistical lemmatizers for every language except English and Spanish. In fact, for languages with more complex morphology, such as Basque and Turkish, the differences are larger. Second, if we look at the impact of including fine-grained morphological features it can be seen that no single morphological tag performs best across systems and languages. Thus, while adding Case, Number and/or Gender seems to be slightly beneficial, differences in performance are substantial only when using the statistical lemmatizer using gold-standard morphological labels (ixa-pipe-gs) and especially for agglutinative languages (Basque and Turkish). Third, the results clearly show that adding every available morphological feature is not beneficial *per se*. Finally, the statistical lemmatizer trained with learned morphological tags (ixa-pipe-mm) performs worst in every case except for English and Spanish.

Summarizing, *in-domain* performance for high-inflected languages improves when some fine-grained morphological attributes (case and number or gender) are used to train the statistical lemmatizers. However, for English and Spanish using UPOS is enough. In

⁴Even though it is not required for out-of-domain evaluation, the Unimorph information is not available for the Basque Armiarma corpus because it is not part of the Unimorph project.

language	corpus	number of tokens	upos	upos+case +gender +number	upos +allfeat. ord.	upos +allfeat. not.ord.	SES (lemma) class)
Basque	train (BDT)	97336	15	205	1143	1683	1306
	dev (BDT)	12206	14	148	556	787	402
	test (BDT)	11901	14	153	545	773	428
	test (Armiarma)	299206	-	-	-	-	1495
Czech	train (CAC)	395043	16	332	1266	1784	946
	dev (CAC)	50087	16	298	876	1129	536
	test (CAC)	49253	15	284	827	1036	556
	test (PUD)	1930	14	175	288	292	151
Russian	train (GSD)	79989	14	241	851	1384	553
	dev (GSD)	9526	14	191	435	673	235
	test (GSD)	9874	14	203	455	713	258
	test (SynTagRus)	109855	15	247	757	1243	896
Spanish	train (GSD)	345545	25	116	287	510	310
	dev (GSD)	42545	23	100	208	342	200
	test (GSD)	43497	23	103	222	387	200
	test (AnCora)	54449	15	75	178	309	298
English	train (EWT)	204857	16	43	94	173	233
	dev (EWT)	24470	16	41	88	160	120
	test (EWT)	25527	16	41	85	156	115
	test (GUM)	8189	17	42	72	124	80
Turkish	train (IMST)	46417	15	124	1541	1897	211
	dev (IMST)	5708	15	95	605	748	106
	test (IMST)	5734	16	100	589	725	104
	test (PUD)	1795	15	66	217	220	59

Table 5: Language complexity reflected in the number of labels according to the augmentation of morphological features, number of lemma classes and corpus tokens.

the case of neural lemmatization with Morpheus, we can see that no substantial gains are obtained by adding fine-grained morphological features to UPOS tags, not even for agglutinative languages such as Basque or Turkish.

Taking this last point into consideration, the next natural step is to consider whether it is possible to learn good contextual lemmatizers without providing any explicit morphological signal during training. Previous work on probing contextual word representations and Transformer-based Masked Language Models (MLMs) suggests that such models implicitly encode information about part-of-speech and morphological features (Manning et al., 2020; Akbik et al., 2018; Conneau et al., 2018; Belinkov et al., 2017). Following this, for this experiment we fine-tune various well-known multilingual and monolingual language models (detailed in Section 4) by using only the word forms and the automatically induced short-edit-scripts (SES) as implemented by UDPipe (Straka et al., 2019).

Figure 3 reports the results. From left-to-right, the first three bars correspond to the best statistical and Morpheus models using explicit morphological information as previously reported in Figure 2. The next four list the results from Flair, mBERT, XLM-RoBERTa and a language-specific monolingual model (none of these four use any explicit




Figure 2: Results on the development sets of the systems that use morphology to train contextual lemmatizers; U: UPOS label, UCG: UPOS+Case+Gender, UCN: UPOS+Case+Number, UCGN: UPOS+Case+Gender+Number, UALLo: UPOSAllFeaturesOrdered.




Figure 3: Overall *in-domain* lemmatization results for models with and without explicit morphological features; monolingual transformers: Russian - ruBERT, Czech - slavicBERT, Basque - BERTeus, Turkish - BERTurk, English - RoBERTa, Spanish - BETO.

morphological feature) whereas *base* (dark purple) refers to the system of Malaviya et al. (2019), employed as a baseline for the Sigmorphon 2019 shared task (McCarthy et al., 2019). For state-of-the-art comparison, the last column on the right provides the results from UDpipe (Straka et al., 2019) (light purple color). Finally, the dark blue bars represent the best result for each language without considering either the baseline system or UDpipe.

The first noticeable trend is that every model beats the baseline except the IXA pipes-based statistical lemmatizers, which perform over the baseline and comparatively to the other models for English and Spanish only, the languages with the less complex morphology. The second and, perhaps, most important fact is that the four models (Flair, mBERT, XLM-RoBERTa and mono) which do not use any morphological signal for training obtain a remarkable performance across languages, XLM-RoBERTa being the best overall, even better than language-specific monolingual models. Moreover, they outperform Morpheus for 4 out of the 6 languages, a neural model which was the third best system in the Sigmorphon 2019 benchmark and which uses all the morphological information available in the Unimorph data. Additionally, they perform competitively with respect to UDpipe, which obtains the best results for 5 out of the 6 languages

included in our study. UDPipe’s strong performance is somewhat expected as it was the overall winner of the Sigmorphon 2019 lemmatization task. In this sense, UDPipe is a rather complex system consisting of a multitask model to predict POS tags, lemmas and dependencies by applying three shared bidirectional LSTM layers which take as input a variety of word and character embeddings, the final model being an ensemble of 9 possible embedding combinations. However, the results obtained by the models we trained without any explicit morphological signal are based on a simple baseline setting, where the Transformer and Flair models are fine-tuned using the automatically induced SES as the target labels in a token classification task. These results seem to confirm that, as it was the case for POS tagging and other tasks (Manning et al., 2020), contextual word representations implicitly encode morphological information which made them perform strongly for lemmatization.

However, we can see that for agglutinative languages such as Basque and Turkish, the neural models using explicit morphological features (Morpheus, Malaviya et al. 2019 and UDPipe) still outperform those without it (although for Basque the differences are much smaller). Still, the overall results show that, apart from Basque and Turkish, differences between say, XLM-RoBERTa and the best model for each language are rather minimal. This demonstrates that it is possible to generate competitive contextual lemmatization without any explicit morphological information using a very simple technique, although a more sophisticated or perhaps multilingual approach may be required to match or improve the state-of-the-art currently represented by UDPipe.

6.2. Out-of-domain evaluation

Although lemmatizers are mostly used out-of-domain, the large majority of the experimental results published so far do not take this issue into account when evaluating approaches to contextual lemmatization. In this section we empirically investigate the out-of-domain performance of the lemmatizers from the previous section to establish whether: (i) using fine-grained morphological information causes cascading errors in the lemmatization performance; (ii) whether the lack of morphological information helps to obtain more robust lemmatizers across domains.

For a better comparison, Figure 4 presents both the in-domain results presented in the previous section together with their corresponding out-of-domain performance on the datasets presented in Section 3. Detailed results are included in Appendix A.

Figure 4 allows to see the general trend in performance across domains and with respect to the type of morphological information used. First, and as it could be expected, out-of-domain performance is substantially worse for every evaluation setting and particularly significant for highly-inflected languages. Second, in terms of the type of morphological label, there are no clear differences between the models using just UPOS tags or those using more fine-grained information, the exception being Russian and Turkish with the *ixa-pipe-mm* system, for which the highest result with {UPOS+Case+Number} is around 1 point in word accuracy better than UPOS. Furthermore, there is not a common type of morphological information that works best across languages. Third, while the statistical lemmatizers are competitive for Spanish and English they are clearly inferior for Basque and Turkish. Finally, when looking at the results in terms of the models using gold-standard morphological annotations (*ixa-pipe-gs* and Morpheus) it is interesting that they degrade less out-of-domain than the model using learned morphological tags for most of the cases except for Russian. Summarizing, we can conclude that adding



Figure 4: Lemmatization results in-domain and out-of-domain for the systems that use morphology for lemmatization. U: UPOS; UCG: UPOS+Case+Gender; UCN: UPOS+Case+Number; UCGN: UPOS+Case+Gender+Number; UALLo: UPOSAllFeaturesOrdered; mm: ixa-pipe-mm with learned morphological tags; gs: ixa-pipe-gs with gold morphological tags; morph: Morpheus.




Figure 5: Overall in-domain and out-of-domain results.

fine-grained morphological information to UPOS does not in general result in better out-of-domain performance.

Following this, we would like to evaluate the out-of-domain performance when not even UPOS labels are used for training. From what we have seen in-domain, the systems that operate without morphology achieve competitive results with respect to the models using morphological information. Figure 5 provides an overview of both the in- and out-of-domain results obtained for both types of systems, confirming this trend. Thus, it is remarkable that the XLM-RoBERTa model scores best out-of-domain for Basque and Czech, and a very close second in Russian and Turkish. The results for Spanish and English deserve further analysis, as the IXA pipes statistical models clearly outperform every other system for these two languages, with differences around 7 points in word accuracy. In any case, Figure 5 shows that the results of every model significantly degrade when evaluated out-of-domain, the most common application of lemmatizers. Thus, even for high-scoring languages such as English and Spanish, out-of-domain performance worsens between 3 and 5 points in word accuracy. For high-inflected languages the differences are around 8 for Basque and more than 10 for Turkish.

To sum up, our experiments empirically demonstrate that fine-grained morphological information to train contextual lemmatizers does not lead to substantially better in- or out-of-domain performance, not even for languages of varied complex morphology, such as Basque, Czech, Russian and Turkish. Thus, only for Basque and Turkish did Morpheus (using UPOS tags) outperformed XLM-RoBERTa models. Following this, and as previously hypothesized for other NLP tasks (Manning et al., 2020), modern

contextual word representations seem to implicitly capture morphological information valuable to train lemmatizers without requiring any explicit morphological signal. We have proved this by training off-the-shelf language models to perform lemmatization as a token classification task. Finally, statistical models are only competitive to perform contextual lemmatization on languages with a morphology on the simple side of the complexity spectrum, such as English or Spanish.

7. Discussion

In this paper we performed a number of experiments to better understand the role of morphological information to learn contextual lemmatization. Our findings can be summarized as follows: (i) fine-grained morphological information does not help to substantially improve contextual lemmatization, not even for high-inflected languages; using UPOS tags is enough for comparable performance; (ii) contextual word representations such as those employed in Transformer and Flair models seem to encode enough implicit morphological information to allow us to train good performing lemmatizers without any explicit morphological signal; (iii) the best-performing lemmatizers out-of-domain are those using either simple UPOS tags or no morphology at all; (iv) evaluating lemmatization on word accuracy is not the best strategy; results are too high and too similar to each other to be able to discriminate between models. By using word accuracy we are assigning the same importance to cases in which the lemma is equivalent to the word form (e.g. ‘the’) as to complex cases in which the word form includes case, number and/or gender information (e.g. ‘medikuarena’, which in Basque means “to the doctor”, with its corresponding lemma ‘mediku’). We believe that this may lead to a high overestimation in the evaluation of the lemmatizers.

In this section, we address some remaining open issues with the aim of understanding better the main errors and difficulties still facing lemmatization. First, we discuss the convenience of using an alternative metric to word accuracy. Second, we analyze the performance of XLM-RoBERTa by evaluating accuracy per SES. Finally, we perform some error analysis on the out-of-domain performance of the XLM-RoBERTa model for Spanish, to see why it is different to the rest of the languages.

7.1. Sentence Accuracy

Looking at the in-domain results for lemmatization reported in the previous sections and in the majority of recent work (Malaviya et al., 2019; McCarthy et al., 2019; Yildiz and Tantıg, 2019; Straka et al., 2019), with word accuracy in-domain scores around 96 or higher, it is not surprising to wonder whether contextual lemmatization is a solved task. However, if we look at the evaluation method a bit more closely, things are not as clear as they seem. As it has been argued for POS tagging (Manning, 2011), word accuracy as an evaluation measure is easy because you get many free points for punctuation marks and the many tokens that are not ambiguous with respect to its lemma, namely, those cases in which the lemma and the word form are the same. Following this, a more realistic metric might consist of looking at the rate of getting the whole sentence correctly lemmatized, just as it was proposed for POS tagging (Manning, 2011).

Figure 6 reports the sentence accuracy of the six languages we used in our experiments both for in- and out-of-domain. In contrast to the word accuracies reported in




Figure 6: Sentence accuracy results for in- and out-of-domain settings.

Figure 5, we can see that the corresponding sentence accuracy results drop significantly. In addition to demonstrating that lemmatizers have a large margin of improvement, sentence accuracy allows us to better discriminate between different models. We can see this phenomenon in the English and Spanish results. Thus, while every model obtained very similar in-domain word accuracy in Spanish, using sentence accuracy helps to discriminate between the statistical and the neural lemmatizers. Furthermore, it also shows that among the neural models XLM-RoBERTa clearly outperforms the rest of the models by almost 1 percent.

The effect of sentence accuracy for the in-domain evaluation is vastly magnified when considering out-of-domain performance, with the extremely low scores across languages providing further evidence of how far lemmatization remains from being solved.

7.2. Word accuracy per SES

The next natural step in our analysis is identifying which specific cases are most difficult for lemmatizers. In order to do so, we propose to compute word accuracy per SES. This simply consists of calculating the word accuracy for each of the SES labels automatically induced from the data. This has the benefit of allowing to identify which specific SES are the most difficult to learn. In order to illustrate this point, we took XLM-RoBERTa as an example use case and analyze their predictions for the languages which could be inspected in-house, namely, Basque, English, Spanish and Russian. Thus,

Table 6 presents examples and results for the 10 most frequent SES for each of these 4 languages development sets.

As we can see in Table 6, the most common lemma transformation to be learned is based on the edit script “do nothing”, namely, the lemmatizer needs to learn that the lemma and the word have the same form. It is also interesting to see how the ratio of such lemma type changes across languages, from English, where such cases are observed in almost 77% of the cases to Basque, where only half of the lemmas correspond to this rule. However, in terms of word accuracy, the results are remarkably similar for all 4 languages, in the range of 99-99.30%. This demonstrates that the traditional evaluation method greatly overestimates the lemmatizers’ performance.

By looking at other specific cases, we can see that in English problematic examples to learn are those related to the casing of some characters (e.g. *Martin* → *Martin*, *NASA* → *NASA*). Other noticeable issue refers to the verbs in gerund form, (e.g. *try**ing*** → *try*, *driving* → *drive*).

With respect to Spanish interesting difficult lemmas are observed with articles in feminine form (e.g. *la* → *el*, *una* → *uno*), where the masculine form is considered the canonical form or lemma, and feminine articles and adjectives should be lemmatized by changing the gender of the word from female to male.

In Russian the most challenging case corresponds to the lemmatization of the nouns that end with a soft sign **ь** with the word accuracy for this SES as low as 93.94%. The possible reason of such low accuracy could be the absence of a specific grammar rule that defines the gender of such nouns and, therefore, the termination these nouns have in different cases. The second lowest accuracy among the 10 most popular SES in Russian is for adjectives, cases in which to obtain the lemma one should delete the last character of the word and add a letter **й** (pronounced as *iy kratkoe*, short *y*), that in Russian determines the suffix for some masculine nouns and adjectives in singular and nominative case. The words could be in different cases and genders, so it is necessary to know such information for correct lemmatization (e.g. *городское* → *городско**й*** (neutral gender, nominative case), *семейным* → *семейно**й*** (masculine gender, instrumental case)).

Finally, for Basque the most problematic cases with a rather low word accuracy of only 90.08% can be found among the nouns in ergative (e.g. *Frantziak* → *Frantzia*) or locative cases (e.g. *Moskun* (in Moscow) → *Mosku*, *Katalunian* (in Catalonia) → *Katalunia*). The other two most difficult SES occur when the word forms are in possessive case (e.g. *lagunaren* → *lagun*) and for nouns in indefinite form (e.g., *aldaketar**ik*** (change) → *aldaketa*).

It should be noted that an extra obstacle to improving some of these difficult cases is the low number of samples available. Nonetheless, this analysis shows that lemmatizers still do not properly learn to lemmatize relatively common word forms.

7.3. Analyzing Spanish out-of-domain results

In Section 6.2 we saw that out-of-domain performance of Transformer-based models for Spanish was not following the pattern of the rest of the languages. Instead, they were 6-7% worse than the results obtained by the IXA pipes statistical lemmatizers (*ixa-pipe-mm* and *ixa-pipe-gs*). By checking the most common error patterns of XLM-RoBERTa, we found out that most of the performance loss was caused by inconsistencies in the manual annotation of lemmas between the data used for in-domain and out-of-domain

	SES	Casing script	Edit script	W.acc	%	Examples
en	↓0;d +	all lowercase	do nothing	99.29	76.87%	positive→ <i>positive</i>
	↑0 ↓1;d +	1st up, then low	do nothing	96.29	6.97%	Martin→ <i>Martin</i>
	↓0;d +	all lowercase	remove last ch	98.58	5.52%	things→ <i>thing</i>
	↓0;abe	all lowercase	ignore form, use <i>be</i>	99.81	2.02%	is→ <i>be</i>
	↓0;d +	all lowercase	remove 2 last ch	97.42	1.52%	does→ <i>do</i>
	↓0;d +	all lowercase	remove 3 last ch	96.45	1.10%	trying→ <i>try</i>
	↑0 ↓1;d +	all uppercase	do nothing	94.22	0.68%	NASA→ <i>NASA</i>
	↓0;d +b +	all lowercase	first 2 char to <i>b</i>	99.33	0.59%	are→ <i>be</i>
	↓0;d +v+e+	all lowercase	last ch to <i>ve</i>	100.00	0.51%	has→ <i>have</i>
↓0;d +e+	all lowercase	3 last ch to <i>e</i>	96.23	0.42%	driving→ <i>drive</i>	
es	↓0;d +	all lowercase	do nothing	99.36	72.40%	acuerdo→ <i>acuerdo</i>
	↓0;d +	all lowercase	del last ch	97.22	5.29%	estrellass→ <i>estrella</i>
	↓0;d+e +	all lowercase	add <i>e</i> , del last ch	96.73	3.36%	la→ <i>el</i>
	↓0;d +o+	all lowercase	del last ch, add <i>o</i>	96.21	2.37%	una→ <i>uno</i>
	↓0;d+e +	all lowercase	add <i>e</i> , del 2 last ch	99.78	2.13%	los→ <i>el</i>
	↓0;d +	all lowercase	del 2 last ch	97.36	1.40%	flores→ <i>flor</i>
	↓0;aél	all lowercase	ignore form, use <i>él</i>	99.83	1.32%	se→ <i>él</i>
	↓0;d +r+	all lowercase	add <i>r</i>	100.00	0.91%	hace→ <i>hacer</i>
	↓0;d +o+	all lowercase	add <i>o</i>	97.73	0.91%	primer→ <i>primero</i>
↓0;d +a+r+	all lowercase	del last ch, add <i>ar</i>	98.07	0.83%	desarrolló→ <i>desarrollar</i>	
ru	↓0;d +	all lowercase	do nothing	99.16	57.80%	Петербург→ <i>Петербург</i>
	↓0;d +	all lowercase	del last ch	97.67	6.97%	церковью→ <i>церковь</i>
	↓0;d +a+	all lowercase	del last ch, add <i>a</i>	96.65	3.32%	экономику→ <i>экономика</i>
	↓0;d +ÿ+	all lowercase	del last ch, add <i>ÿ</i>	96.08	3.10%	городское→ <i>городской</i>
	↓0;d +	all lowercase	del 2 last ch	99.03	2.10%	странами→ <i>страна</i>
	↓0;d +e+	all lowercase	del last ch, add <i>e</i>	98.04	2.07%	моря→ <i>море</i>
	↓0;d +ÿ+	all lowercase	del last ch, add <i>ÿ</i>	97.83	1.86%	историю→ <i>история</i>
	↓0;d +т+ь+	all lowercase	del last ch, add <i>ть</i>	98.88	1.81%	получил→ <i>получить</i>
	↓0;d +ь+	all lowercase	del last ch, add <i>ь</i>	93.94	1.67%	сентября→ <i>сентябрь</i>
↓0;d +т+ь+	all lowercase	del 2 last, add <i>ть</i>	98.10	1.60%	были→ <i>быть</i>	
eu	↓0;d +	all lowercase	do nothing	99.05	49.63%	sartu→ <i>sartu</i>
	↓0;d +	all lowercase	remove 2 last ch	97.72	9.93%	librean→ <i>libre</i>
	↓0;d +	all lowercase	remove last ch	96.27	6.54%	korrikan→ <i>korrika</i>
	↓0;d +	all lowercase	remove 3 last ch	93.24	3.60%	aldaketarik→ <i>aldaketa</i>
	↑0 ↓1;d +	1st up, then low	do nothing	98.54	3.46%	MAPEI→ <i>Mapei</i>
	↓0;d +	all lowercase	del 4 last ch	93.00	2.52%	lagunaren→ <i>lagun</i>
	↑0 ↓1;d +	1st up, then low	del 2 last ch	95.54	1.88%	Egiptora→ <i>Egipto</i>
	↓0;d +i+z	all lowercase	del 1st ch,	100.00	1.38%	da→ <i>izan</i>
	↑+n+		add <i>iz,n</i>			
↑0 ↓1;d +	1st up, then low	del last ch	90.08	1.10%	Frantziak→ <i>Frantzia</i>	

Table 6: 10 most frequent SES, brief description, corresponding word accuracy, weight (in %) in the corpus and examples of words and their lemmas for English, Spanish, Russian and Basque; SES are computed following UDPipe’s method (Straka et al., 2019).

evaluation. More specifically, the GSD Spanish corpus included in Unimorph wrongly annotates lemmas for proper names such as Madrid, London or Paris entirely in lowercase, namely, *madrid*, *london* and *paris*. However, the Ancora Spanish corpus used for out-of-domain evaluation correctly annotates these cases specifying their corresponding lemmas with the first character in uppercase. This inconsistency results in 3781 examples of proper names in the Ancora test set which are all lemmatized following the pattern seen during training with the GSD training set. Consequently, the word accuracy obtained by the model for this type of examples in the Ancora test set is 0%. In order to confirm this issue, we corrected the wrongly annotated proper names in the GSD training data, fine-tuned again the model and saw the out-of-domain performance of XLM-RoBERTa go up from 90.26% to 96.75%, a more consistent result with respect to the out-of-domain scores for the other 5 languages.

This issue manifests the importance of consistent manual annotation across corpora from different domains in order to fairly evaluate out-of-domain performance of contextual lemmatizers.

8. Concluding Remarks

Lemmatization remains an important Natural Language Processing task, especially for languages with high-inflected morphology. In this paper we provide an in-depth study on the role of morphological information to learn contextual lemmatizers. By taking a language sample of varied morphological complexity, we have analyzed whether fine-grained morphological signal is indeed beneficial for contextual lemmatization. Furthermore, and in contrast to previous work, we also evaluate lemmatizers in an out-of-domain setting, which constitutes, after all, their most common application use. Our results empirically demonstrate that: (i) informing lemmatizers with fine-grained morphological features during training is not that beneficial, not even for agglutinative languages; (ii) modern contextual word representations seem to implicitly encode enough morphological information to obtain good contextual lemmatizers without seeing any explicit morphological signal; (iii) the best lemmatizers out-of-domain are those using simple UPOS tags or those trained without morphology.

Furthermore, we have discussed current evaluation practice for lemmatization, showing that using simple word accuracy is not adequate to clearly discriminate between models, and it provides a deceptive view regarding the performance of lemmatizers. An additional analysis looking at specific lemma classes (SES) has shown that many common word forms are still not properly predicted. The conclusion is that lemmatization remains a challenging task. Future work is therefore needed to improve out-of-domain results. Furthermore, it is perhaps a good time to propose an alternative word-level metric to evaluate lemmatization that, complemented with sentence accuracy, may provide a more realistic view of the performance of contextual lemmatizers.

Acknowledgements

This work has been supported by the HiTZ center and the Basque Government (Research group funding IT-1805-22). OIa Toporkov is funded by a UPV/EHU grant “Formación de Personal Investigador”. We also acknowledge the funding from the following

MCIN/AEI/10.13039/501100011033 projects: (i) DeepKnowledge (PID2021-127770B-C21) and ERDF A way of making Europe; (ii) Disargue (TED2021-130810B-C21) and European Union NextGenerationEU/PRTR (iii) Antidote (PCI2020-120717-2) and European Union NextGenerationEU/PRTR. Rodrigo Aggerri currently holds the RYC-2017-23647 fellowship (MCIN/AEI/10.13039/501100011033 and ESF Investing in your future).

References

- Aggerri, R., Bermudez, J., Rigau, G., 2014. IXA pipeline: Efficient and ready to use multilingual NLP tools, in: Proceedings of the Ninth International Conference on Language Resources and Evaluation (LREC'14), European Language Resources Association (ELRA), Reykjavik, Iceland. pp. 3823–3828. URL: http://www.lrec-conf.org/proceedings/lrec2014/pdf/775_Paper.pdf.
- Aggerri, R., Rigau, G., 2016. Robust multilingual named entity recognition with shallow semi-supervised features. *Artificial Intelligence* 238, 63–82.
- Aggerri, R., San Vicente, I., Campos, J.A., Barrena, A., Saralegi, X., Soroa, A., Agirre, E., 2020. Give your text representation models some love: the case for Basque, in: Proceedings of the 12th Language Resources and Evaluation Conference, European Language Resources Association, Marseille, France. pp. 4781–4788. URL: <https://aclanthology.org/2020.lrec-1.588>.
- Agić, Ž., Schluter, N., 2017. How (not) to train a dependency parser: The curious case of jackknifing part-of-speech taggers, in: Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers), Association for Computational Linguistics, Vancouver, Canada. pp. 679–684. URL: <https://aclanthology.org/P17-2107>, doi:10.18653/v1/P17-2107.
- Akbik, A., Blythe, D., Vollgraf, R., 2018. Contextual string embeddings for sequence labeling, in: Proceedings of the 27th International Conference on Computational Linguistics, Association for Computational Linguistics, Santa Fe, New Mexico, USA. pp. 1638–1649. URL: <https://aclanthology.org/C18-1139>.
- Aldezabal, I., Aranzabe, M., Diaz de Ilarraza, A., Fernández, K., 2008. From dependencies to constituents in the reference corpus for the processing of basque. *Procesamiento del Lenguaje Natural*, 41, 147–154.
- Alegria, I., Artola, X., Sarasola, K., Urkia, M., 1996. Automatic morphological analysis of basque. *Literary and Linguistic Computing* 11, 193–203.
- Arhipov, M., Trofimova, M., Kuratov, Y., Sorokin, A., 2019. Tuning multilingual transformers for language-specific named entity recognition, in: Proceedings of the 7th Workshop on Balto-Slavic Natural Language Processing, Association for Computational Linguistics, Florence, Italy. pp. 89–93. URL: <https://aclanthology.org/W19-3712>, doi:10.18653/v1/W19-3712.
- Belinkov, Y., Durrani, N., Dalvi, F., Sajjad, H., Glass, J.R., 2017. What do neural machine translation models learn about morphology?, in: ACL.
- Bergmanis, T., Goldwater, S., 2018. Context sensitive neural lemmatization with Lematus, in: Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers), Association for Computational Linguistics, New Orleans, Louisiana. pp. 1391–1400. URL: <https://aclanthology.org/N18-1126>, doi:10.18653/v1/N18-1126.
- van den Bosch, A., Daelemans, W., 1999. Memory-based morphological analysis, in: Proceedings of the 37th Annual Meeting of the Association for Computational Linguistics, Association for Computational Linguistics, College Park, Maryland, USA. pp. 285–292. URL: <https://aclanthology.org/P99-1037>, doi:10.3115/1034678.1034726.
- Carreras, X., Chao, I., Padró, L., Padró, M., 2004. Freeling: An open-source suite of language analyzers, in: LREC.
- Cañete, J., Chaperon, G., Fuentes, R., Ho, J.H., Kang, H., Pérez, J., 2020. Spanish pre-trained bert model and evaluation data, in: PML4DC at ICLR 2020.
- Chakrabarty, A., Pandit, O.A., Garain, U., 2017. Context sensitive lemmatization using two successive bidirectional gated recurrent networks, in: Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), Association for Computational Linguistics, Vancouver, Canada. pp. 1481–1491. URL: <https://aclanthology.org/P17-1136>, doi:10.18653/v1/P17-1136.
- Chrupala, G., Dinu, G., van Genabith, J., 2008. Learning morphology with Morfette, in: Proceedings of the Sixth International Conference on Language Resources and Evaluation (LREC'08), European

- Language Resources Association (ELRA), Marrakech, Morocco. URL: http://www.lrec-conf.org/proceedings/lrec2008/pdf/594_paper.pdf.
- Collins, M., 2002. Discriminative training methods for Hidden Markov Models: Theory and experiments with perceptron algorithms, in: Proceedings of the 2002 Conference on Empirical Methods in Natural Language Processing (EMNLP 2002), Association for Computational Linguistics. pp. 1–8.
- Conneau, A., Khandelwal, K., Goyal, N., Chaudhary, V., Wenzek, G., Guzmán, F., Grave, E., Ott, M., Zettlemoyer, L., Stoyanov, V., 2020. Unsupervised cross-lingual representation learning at scale, in: Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics, Association for Computational Linguistics, Online. pp. 8440–8451. URL: <https://aclanthology.org/2020.acl-main.747>, doi:10.18653/v1/2020.acl-main.747.
- Conneau, A., Kruszewski, G., Lample, G., Barrault, L., Baroni, M., 2018. What you can cram into a single $\&!#\ast$ vector: Probing sentence embeddings for linguistic properties, in: Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), Association for Computational Linguistics, Melbourne, Australia. pp. 2126–2136. URL: <https://aclanthology.org/P18-1198>, doi:10.18653/v1/P18-1198.
- Cotterell, R., Heigold, G., 2017. Cross-lingual character-level neural morphological tagging, in: Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing, Association for Computational Linguistics, Copenhagen, Denmark. pp. 748–759. URL: <https://aclanthology.org/D17-1078>, doi:10.18653/v1/D17-1078.
- Dayanik, E., Akyürek, E., Yuret, D., 2018. Morphnet: A sequence-to-sequence model that combines morphological analysis and disambiguation. CoRR abs/1805.07946.
- Devlin, J., Chang, M.W., Lee, K., Toutanova, K., 2019. BERT: Pre-training of deep bidirectional transformers for language understanding, in: Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers), Association for Computational Linguistics, Minneapolis, Minnesota. pp. 4171–4186. URL: <https://aclanthology.org/N19-1423>, doi:10.18653/v1/N19-1423.
- Dhonchadha, E.U., 2002. A two-level morphological analyser and generator for irish using finite-state transducers, in: LREC.
- Gesmundo, A., Samardžić, T., 2012. Lemmatisation as a tagging task, in: Proceedings of the 50th Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers), Association for Computational Linguistics, Jeju Island, Korea. pp. 368–372. URL: <https://aclanthology.org/P12-2072>.
- Grave, E., Bojanowski, P., Gupta, P., Joulin, A., Mikolov, T., 2018. Learning word vectors for 157 languages, in: Proceedings of the Eleventh International Conference on Language Resources and Evaluation (LREC 2018), European Language Resources Association (ELRA), Miyazaki, Japan. URL: <https://aclanthology.org/L18-1550>.
- Haspelmath, M., Sims, A., 2013. Understanding morphology. Routledge.
- Heigold, G., Neumann, G., van Genabith, J., 2017. An extensive empirical evaluation of character-based morphological tagging for 14 languages, in: Proceedings of the 15th Conference of the European Chapter of the Association for Computational Linguistics: Volume 1, Long Papers, Association for Computational Linguistics, Valencia, Spain. pp. 505–513. URL: <https://aclanthology.org/E17-1048>.
- Hladka, B., Hajič, J., Hana, J., Hlaváčová, J., Mírovský, J., Raab, J., 2008. The czech academic corpus 2.0 guide. The Prague Bulletin of Mathematical Linguistics 89, 41–96.
- Huang, Z., Xu, W., Yu, K., 2015. Bidirectional lstm-crf models for sequence tagging. ArXiv abs/1508.01991.
- Jongejan, B., Dalianis, H., 2009. Automatic training of lemmatization rules that handle morphological changes in pre-, in- and suffixes alike, in: Proceedings of the Joint Conference of the 47th Annual Meeting of the ACL and the 4th International Joint Conference on Natural Language Processing of the AFNLP, Association for Computational Linguistics, Suntec, Singapore. pp. 145–153. URL: <https://aclanthology.org/P09-1017>.
- Karttunen, L., Kaplan, R.M., Zaenen, A., 1992. Two-level morphology with composition, in: COLING 1992 Volume 1: The 14th International Conference on Computational Linguistics. URL: <https://aclanthology.org/C92-1025>.
- Kingma, D.P., Ba, J., 2015. Adam: A method for stochastic optimization. CoRR abs/1412.6980.
- Kirov, C., Cotterell, R., Sylak-Glassman, J., Walther, G., Vylomova, E., Xia, P., Faruqi, M., Mielke, S.J., McCarthy, A., Kübler, S., Yarowsky, D., Eisner, J., Hulden, M., 2018. UniMorph 2.0: Universal Morphology, in: Proceedings of the Eleventh International Conference on Language Resources and Evaluation (LREC 2018), European Language Resources Association (ELRA), Miyazaki, Japan. URL: <https://aclanthology.org/L18-1293>.

- Kondratyuk, D., 2019. Cross-lingual lemmatization and morphology tagging with two-stage multilingual BERT fine-tuning, in: Proceedings of the 16th Workshop on Computational Research in Phonetics, Phonology, and Morphology, Association for Computational Linguistics, Florence, Italy. pp. 12–18. URL: <https://aclanthology.org/W19-4203>, doi:10.18653/v1/W19-4203.
- Kondratyuk, D., Straka, M., 2019. 75 languages, 1 model: Parsing Universal Dependencies universally, in: Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP), Association for Computational Linguistics, Hong Kong, China. pp. 2779–2795. URL: <https://aclanthology.org/D19-1279>, doi:10.18653/v1/D19-1279.
- Kuratov, Y., Arkhipov, M.Y., 2019. Adaptation of deep bidirectional multilingual transformers for russian language. CoRR abs/1905.07213.
- Liu, Y., Ott, M., Goyal, N., Du, J., Joshi, M., Chen, D., Levy, O., Lewis, M., Zettlemoyer, L., Stoyanov, V., 2019. Roberta: A robustly optimized bert pretraining approach. [arXiv:1907.11692](https://arxiv.org/abs/1907.11692).
- Lyashevskaya, O., Drohanova, K., Zeman, D., Alexeeva, M., Gavrilova, T., Mustafina, N., Shakurova, E., 2016. Universal dependencies for russian: A new syntactic dependencies tagset. SSRN Electronic Journal .
- Ma, X., Hovy, E., 2016. End-to-end sequence labeling via bi-directional LSTM-CNNs-CRF, in: Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), Association for Computational Linguistics, Berlin, Germany. pp. 1064–1074. URL: <https://aclanthology.org/P16-1101>, doi:10.18653/v1/P16-1101.
- Malaviya, C., Wu, S., Cotterell, R., 2019. A simple joint model for improved contextual neural lemmatization, in: Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers), Association for Computational Linguistics, Minneapolis, Minnesota. pp. 1517–1528. URL: <https://aclanthology.org/N19-1155>, doi:10.18653/v1/N19-1155.
- Manning, C.D., 2011. Part-of-speech tagging from 97% to 100%: Is it time for some linguistics?, in: Conference on Intelligent Text Processing and Computational Linguistics.
- Manning, C.D., Clark, K., Hewitt, J., Khandelwal, U., Levy, O., 2020. Emergent linguistic structure in artificial neural networks trained by self-supervision. Proceedings of the National Academy of Sciences 117, 30046 – 30054.
- de Marneffe, M.C., Dozat, T., Silveira, N., Haverinen, K., Ginter, F., Nivre, J., Manning, C.D., 2014. Universal Stanford dependencies: A cross-linguistic typology, in: Proceedings of the Ninth International Conference on Language Resources and Evaluation (LREC’14), European Language Resources Association (ELRA), Reykjavik, Iceland. pp. 4585–4592. URL: http://www.lrec-conf.org/proceedings/lrec2014/pdf/1062_Paper.pdf.
- McCarthy, A.D., Kirov, C., Grella, M., Nidhi, A., Xia, P., Gorman, K., Vylomova, E., Mielke, S.J., Nicolai, G., Silfverberg, M., Arkhangelskiy, T., Krizhanovsky, N., Krizhanovsky, A., Klyachko, E., Sorokin, A., Mansfield, J., Ernštreits, V., Pinter, Y., Jacobs, C.L., Cotterell, R., Hulden, M., Yarowsky, D., 2020. UniMorph 3.0: Universal Morphology, in: Proceedings of the 12th Language Resources and Evaluation Conference, European Language Resources Association, Marseille, France. pp. 3922–3931. URL: <https://aclanthology.org/2020.lrec-1.483>.
- McCarthy, A.D., Vylomova, E., Wu, S., Malaviya, C., Wolf-Sonkin, L., Nicolai, G., Kirov, C., Silfverberg, M., Mielke, S.J., Heinz, J., Cotterell, R., Hulden, M., 2019. The SIGMORPHON 2019 shared task: Morphological analysis in context and cross-lingual transfer for inflection, in: Proceedings of the 16th Workshop on Computational Research in Phonetics, Phonology, and Morphology, Association for Computational Linguistics, Florence, Italy. pp. 229–244. URL: <https://aclanthology.org/W19-4226>, doi:10.18653/v1/W19-4226.
- Müller, T., Cotterell, R., Fraser, A., Schütze, H., 2015a. Joint lemmatization and morphological tagging with lemming, in: Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing, Lisbon, Portugal. pp. 2268–2274.
- Müller, T., Cotterell, R., Fraser, A., Schütze, H., 2015b. Joint lemmatization and morphological tagging with lemming, in: Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing, Association for Computational Linguistics, Lisbon, Portugal. pp. 2268–2274. URL: <https://aclanthology.org/D15-1272>, doi:10.18653/v1/D15-1272.
- Nivre, J., Zeman, D., Ginter, F., Tyers, F., 2017. Universal Dependencies, in: Proceedings of the 15th Conference of the European Chapter of the Association for Computational Linguistics: Tutorial Abstracts, Association for Computational Linguistics, Valencia, Spain. URL: <https://aclanthology.org/E17-5001>.
- Oflazer, K., 1993. Two-level description of Turkish morphology, in: Sixth Conference of the European

- Chapter of the Association for Computational Linguistics, Association for Computational Linguistics, Utrecht, The Netherlands. URL: <https://aclanthology.org/E93-1066>.
- Ortiz Suárez, P.J., Sagot, B., Romary, L., 2019. Asynchronous pipelines for processing huge corpora on medium to low resource infrastructures, in: Bański, P., Barbaresi, A., Biber, H., Breiteneder, E., Clematide, S., Kupietz, M., Lungen, H., Iliadi, C. (Eds.), *Proceedings of the Workshop on Challenges in the Management of Large Corpora (CMLC-7) 2019*. Cardiff, 22nd July 2019, pp. 9–16.
- Schweter, S., 2020. Berturk - bert models for turkish. URL: <https://doi.org/10.5281/zenodo.3770924>, doi:10.5281/zenodo.3770924.
- Segalovich, I., 2003. A fast morphological algorithm with unknown word guessing induced by a dictionary for a web search engine, in: *MLMTA*.
- Silveira, N., Dozat, T., de Marneffe, M.C., Bowman, S., Connor, M., Bauer, J., Manning, C., 2014. A gold standard dependency corpus for English, in: *Proceedings of the Ninth International Conference on Language Resources and Evaluation (LREC'14)*, European Language Resources Association (ELRA), Reykjavik, Iceland. pp. 2897–2904. URL: http://www.lrec-conf.org/proceedings/lrec2014/pdf/1089_Paper.pdf.
- Straka, M., 2018. UDPipe 2.0 prototype at CoNLL 2018 UD shared task, in: *Proceedings of the CoNLL 2018 Shared Task: Multilingual Parsing from Raw Text to Universal Dependencies*, Association for Computational Linguistics, Brussels, Belgium. pp. 197–207. URL: <https://aclanthology.org/K18-2020>, doi:10.18653/v1/K18-2020.
- Straka, M., Straková, J., Hajic, J., 2019. UDPipe at SIGMORPHON 2019: Contextualized embeddings, regularization with morphological categories, corpora merging, in: *Proceedings of the 16th Workshop on Computational Research in Phonetics, Phonology, and Morphology*, Association for Computational Linguistics, Florence, Italy. pp. 95–103. URL: <https://aclanthology.org/W19-4212>, doi:10.18653/v1/W19-4212.
- Stroppa, N., Yvon, F., 2005. An analogical learner for morphological analysis, in: *Proceedings of the Ninth Conference on Computational Natural Language Learning (CoNLL-2005)*, Association for Computational Linguistics, Ann Arbor, Michigan. pp. 120–127. URL: <https://aclanthology.org/W05-0616>.
- Sulubacak, U., Gokirmak, M., Tyers, F., Çöltekin, Ç., Nivre, J., Eryigit, G., 2016. Universal Dependencies for Turkish, in: *Proceedings of COLING 2016, the 26th International Conference on Computational Linguistics: Technical Papers*, The COLING 2016 Organizing Committee, Osaka, Japan. pp. 3444–3454. URL: <https://aclanthology.org/C16-1325>.
- Taulé, M., Martí, M.A., Recasens, M., 2008. AnCora: Multilevel annotated corpora for Catalan and Spanish, in: *Proceedings of the Sixth International Conference on Language Resources and Evaluation (LREC'08)*, European Language Resources Association (ELRA), Marrakech, Morocco. URL: http://www.lrec-conf.org/proceedings/lrec2008/pdf/35_paper.pdf.
- Tiedemann, J., 2012. Parallel data, tools and interfaces in OPUS, in: *Proceedings of the Eighth International Conference on Language Resources and Evaluation (LREC'12)*, European Language Resources Association (ELRA), Istanbul, Turkey. pp. 2214–2218. URL: http://www.lrec-conf.org/proceedings/lrec2012/pdf/463_Paper.pdf.
- Tiedemann, J., 2016. OPUS – parallel corpora for everyone, in: *Proceedings of the 19th Annual Conference of the European Association for Machine Translation: Projects/Products*, Baltic Journal of Modern Computing, Riga, Latvia. URL: <https://aclanthology.org/2016.eamt-2.8>.
- Türk, U., Atmaca, F., Özateş, Ş.B., Köksal, A., Ozturk Basaran, B., Gungor, T., Özgür, A., 2019. Turkish treebanking: Unifying and constructing efforts, in: *Proceedings of the 13th Linguistic Annotation Workshop*, Association for Computational Linguistics, Florence, Italy. pp. 166–177. URL: <https://aclanthology.org/W19-4019>, doi:10.18653/v1/W19-4019.
- Vaswani, A., Shazeer, N.M., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A.N., Kaiser, L., Polosukhin, I., 2017. Attention is all you need. *ArXiv abs/1706.03762*.
- Wu, S., Cotterell, R., 2019. Exact hard monotonic attention for character-level transduction, in: *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, Association for Computational Linguistics, Florence, Italy. pp. 1530–1537. URL: <https://aclanthology.org/P19-1148>, doi:10.18653/v1/P19-1148.
- Yildiz, E., Tantuğ, A.C., 2019. Morpheus: A neural network for jointly learning contextual lemmatization and morphological tagging, in: *Proceedings of the 16th Workshop on Computational Research in Phonetics, Phonology, and Morphology*, Association for Computational Linguistics, Florence, Italy. pp. 25–34. URL: <https://aclanthology.org/W19-4205>, doi:10.18653/v1/W19-4205.
- Zeldes, A., 2017. The GUM corpus: Creating multilayer resources in the classroom. *Language Resources and Evaluation* 51, 581–612.

Zeman, D., Popel, M., Straka, M., Hajič, J., Nivre, J., Ginter, F., Luotolahti, J., Pyysalo, S., Petrov, S., Potthast, M., Tyers, F., Badmaeva, E., Gokirmak, M., Nedoluzhko, A., Cinková, S., Hajič jr., J., Hlaváčová, J., Kettnerová, V., Urešová, Z., Kanerva, J., Ojala, S., Missilä, A., Manning, C.D., Schuster, S., Reddy, S., Taji, D., Habash, N., Leung, H., de Marneffe, M.C., Sanguinetti, M., Simi, M., Kanayama, H., de Paiva, V., Droганova, K., Martínez Alonso, H., Çöltekin, Ç., Sulubacak, U., Uszkoreit, H., Macketanz, V., Burchardt, A., Harris, K., Marheinecke, K., Rehm, G., Kayadelen, T., Attia, M., Elkahky, A., Yu, Z., Pitler, E., Lertpradit, S., Mandl, M., Kirchner, J., Alcalde, H.F., Strnadová, J., Banerjee, E., Manurung, R., Stella, A., Shimada, A., Kwak, S., Mendonça, G., Lando, T., Nitisaroj, R., Li, J., 2017. CoNLL 2017 shared task: Multilingual parsing from raw text to Universal Dependencies, in: Proceedings of the CoNLL 2017 Shared Task: Multilingual Parsing from Raw Text to Universal Dependencies, Association for Computational Linguistics, Vancouver, Canada. pp. 1–19. URL: <https://aclanthology.org/K17-3001>, doi:10.18653/v1/K17-3001.

Appendix A. Detailed Lemmatization Results with Morphological Features

UPOS						
in-domain			out-of-domain			
	ixa-mm	ixa-gs	morph	ixa-mm	ixa-gs	morph
en	99.11	98.91	98.10	95.38	95.25	92.92
es	98.91	98.76	98.24	97.53	97.41	90.29
ru	94.36	93.74	96.20	90.00	89.40	87.59
eu	93.11	92.29	96.39	85.22	86.79	88.97
cs	97.86	97.28	98.75	92.33	93.68	91.66
tr	84.65	87.76	96.44	79.22	81.67	84.96

UCG						
in-domain			out-of-domain			
	ixa-mm	ixa-gs	morph	ixa-mm	ixa-gs	morph
en	99.10	98.92	97.99	95.20	95.24	92.97
es	98.94	98.70	98.98	97.54	97.43	90.31
ru	94.85	93.30	96.21	90.97	89.33	87.67
eu	92.65	92.39	96.34	85.23	86.74	89.09
cs	97.29	96.64	98.76	91.61	91.35	91.92
tr	85.09	87.09	96.18	80.06	81.23	84.74

UCN						
in-domain			out-of-domain			
	ixa-mm	ixa-gs	morph	ixa-mm	ixa-gs	morph
en	99.06	98.87	98.01	95.16	95.16	92.86
es	98.92	98.75	99.02	97.56	97.44	90.35
ru	95.07	93.70	96.20	91.00	89.60	87.58
eu	93.03	92.35	96.39	85.47	86.36	89.03
cs	97.44	96.87	98.71	91.04	92.07	92.23
tr	85.52	87.18	96.11	80.33	81.00	84.40

UCGN						
in-domain			out-of-domain			
	ixa-mm	ixa-gs	morph	ixa-mm	ixa-gs	morph
en	99.08	98.96	97.99	95.21	95.15	92.95
es	98.89	98.71	98.97	97.59	97.44	90.38
ru	95.00	93.08	96.44	90.80	89.13	87.66
eu	93.03	92.28	96.39	85.38	86.55	88.86
cs	97.17	96.68	98.70	91.71	91.50	91.97
tr	85.52	87.18	96.20	80.33	81.00	84.46

UAllo						
in-domain			out-of-domain			
	ixa-mm	ixa-gs	morph	ixa-mm	ixa-gs	morph
en	99.04	98.95	98.06	95.08	95.13	93.15
es	98.86	98.74	99.00	97.54	97.45	90.34
ru	94.75	93.22	96.30	90.88	88.66	87.57
eu	93.41	94.06	96.50	85.33	86.31	89.11
cs	97.03	96.63	98.70	91.19	91.81	92.02
tr	84.90	86.57	96.22	79.39	80.50	84.96

Table A.7: Lemmatization results in-domain and out-of-domain for the systems that use morphology for lemmatization. ixa-mm: IXA pipes with learned morphological tags; ixa-gs: IXA pipes with gold standard morphology; morph = Morpheus; UCG: UPOS+Case+Gender, UCN: UPOS+Case+Number, UCGN: UPOS+Case+Gender+Number; UAllo: UPOSAllFeaturesOrdered.