# A THEORY OF LINK PREDICTION VIA RELATIONAL WEISFEILER-LEMAN

#### **Xingyue Huang**

Department of Computer Science University of Oxford, UK xingyue.huang@cs.ox.ac.uk

#### **Miguel Romero Orth**

Universidad Adolfo Ibáñez & CENIA Chile miguel.romero.o@uai.cl

## İsmail İlkan Ceylan

Department of Computer Science University of Oxford, UK ismail.ceylan@cs.ox.ac.uk

### Pablo Barceló

Institute for Mathematical and Computational Engineering, PUC Chile & IMFD Chile & CENIA Chile pbarcelo@uc.cl

### **ABSTRACT**

Graph neural networks are prominent models for representation learning over graph-structured data. While the capabilities and limitations of these models are well-understood for simple graphs, our understanding remains highly incomplete in the context of knowledge graphs. The goal of this work is to provide a systematic understanding of the landscape of graph neural networks for knowledge graphs pertaining the prominent task of link prediction. Our analysis entails a unifying perspective on seemingly unrelated models, and unlocks a series of other models. The expressive power of various models is characterized via a corresponding relational Weisfeiler-Leman algorithm with different initialization regimes. This analysis is extended to provide a precise logical characterization of the class of functions captured by a class of graph neural networks. Our theoretical findings explain the benefits of some widely employed practical design choices, which are validated empirically.

# 1 Introduction

Graph neural networks (GNNs) [1, 2] are prominent models for representation learning over graph-structured data, where the idea is to iteratively compute vector representations of nodes of an input graph through a series of invariant (resp., equivariant) transformations. While the landscape of GNNs is overwhelmingly rich, the vast majority of such models are instances of *message passing neural networks* [3] which are well-studied, leading to a theoretical understanding on their capabilities and limitations [4, 5]. In turn, our understanding is rather limited for GNN models dedicated to learning over *knowledge graphs*, which are applied in a wide range of domains.

To make our context precise, we first consider an extension of message passing neural networks with relation-specific message functions, which we call *relational* message passing neural networks. Two prominent examples of this framework are RGCN [6] and CompGCN [7], and their expressive power has recently been characterized through a dedicated relational Weisfeiler-Leman test [8]. While offering principled means for learning over knowledge graphs, the standard relational message passing framework is tailored for computing *unary* node representations and therefore models of this class are better suited for node-level tasks (e.g., node/entity classification). Actually, it is well-known that even a good node-level representation might not necessarily induce a good edge representation, hindering the applicability of such models for the crucial task of link prediction [9]. This has led to the design of GNN architectures

specifically tailored for link prediction over knowledge graphs [10, 11, 12, 13], for which our understanding remains limited.

The goal of this paper is to offer a theory of the capabilities and limitations of a class of relational GNN architectures which compute *pairwise* node representations to be utilized for link prediction. Although most such architectures can be seen to be subsumed by *higher-order* message passing neural networks that compute pairwise representations on nodes, the inherently quadratic behavior of the latter justifies local approximations which align better with models used in practice. Of particular interest to us is Neural Bellman-Ford Networks (NBFNets) [11], which define a message passing approach, originally inspired by the Bellman-Ford algorithm. We argue in salient detail that the crucial insight of this approach is in leveraging the idea of computing *conditional* pairwise-node representations, which leads to more expressive models at a relatively more reasonable computational cost, given its local nature.

Building on this fundamental aspect, we define *conditional* message passing neural networks, which extend traditional ones by a conditional message passing paradigm: every node representation is conditional on a source node and a query relation, which allows for computing pairwise node representations. This framework strictly contains NBFNets and allows for a systematic treatment of various other models. Through a careful study of this framework, we can explain the conceptual differences between different models along with their respective expressive power.

Our contributions can be summarized as follows:

- We introduce *conditional* message passing neural networks which encode representations of nodes v conditioned on a (source) node u and a query relation q, yielding pairwise node representations. We discuss the model design space, including a discussion on different initialization regimes (closely related to labeling trick [9]), and define a condition for an initialization function to satisfy to yield pairwise node representations.
- We define a relational Weisfeiler-Leman algorithm, and prove that *conditional* message passing neural networks can match the expressive power of this algorithm. This study reveals interesting insights about NBFNets, suggesting that their strong empirical performance is precisely due to the expressive power, which can be matched by other instances of this framework.
- Viewing conditional message passing neural networks as classifiers over pairs of nodes, we give a logical characterization based on a subclass of binary formulas from the guarded fragment of first order logic with three variables and counting. This provides us with a declarative and well-studied formal counterpart of the framework.
- We conduct an experimental analysis to verify the impact of various model choices, particularly pertaining to initialization, history, and message computation functions, empirically validating our theoretical findings.

All proofs can be found in the appendix of this paper.

## 2 Related Work and Motivation

Early GNN models for knowledge graphs are relational variations of message passing neural networks. A prototypical example is the RGCN architecture [6], which extends graph convolutional networks (GCNs) [14] with relation-specific message functions. CompGCN [7] and several other models [15] follow this line of work with differences in the specific choices for the aggregate, update and message functions. In essence, these models encode *unary* node representations, and they typically rely on a *pairwise decoder* function to predict the likelihood of a link which is known to have limitations for link prediction [9]. There is a good understanding of the expressive power of these models [8], and we frame these results within our setting and prove slightly more general versions (Section 3).

A different approach is given for single-relational graphs by SEAL [16], where the idea is to encode (labeled) subgraphs (instead of nodes). GraIL [10] extends this idea to knowledge graphs, and one important virtue of these models is that they are *inductive* even if there are no node features in the input graph. The idea is to use a form of labeling trick [9] based on pairwise shortest path distances in sampled subgraphs, but these models suffer from scalability issues.

Recent works aim to integrate ideas from earlier path-based link prediction models [17, 18] into modern GNN architectures, resulting in models such as PathCon [12], Geodesic GNNs [13], and NBFNets [11]. Our study is very closely related to NBFNets which is inspired by the generalized version of the Bellman-Ford algorithm for finding shortest paths. This class of models aggregates over relational paths by keeping track of conditional pairwise-node representations. While NBFNets can be intuitively seen as the neural counterpart of the Bellman-Ford algorithm, they do *not* provably align with this algorithm since the "semiring assumption" is invalidated through the use of non-linearities (which is explicit in the original paper). This leaves open many questions regarding the capabilities and limitations of

this class of models. We argue that the key insight is in locally computing pairwise representations through conditioning on a source node, and this has roots in earlier works, such as ID-GNNs [19].

We introduce conditional message passing neural networks as a strict generalization of NBFNets [11] and related models such as NeuralLP [20], or DRUM [21], and theoretically study their properties in relation to local variants of relational Weisfeiler-Leman algorithms. Broadly, our study can be seen as the relational counterpart of the expressiveness studies conducted for GNNs [4, 5, 22], particularly related to higher-order GNNs [5], which align with higher-order dimensional variants of the WL test. Our characterization relies on *local* versions of higher-order WL tests, which is studied [23], albeit not in a relational context. Our work can be seen as a continuation and generalization of the results given for relational message passing neural networks [8] to a broader class of models.

## 3 Background

## 3.1 Knowledge graphs and invariants

**Knowledge graphs.** A knowledge graph is a tuple G = (V, E, R, c), where V is a set of nodes,  $E \subseteq R \times V \times V$  is a set of labeled edges, or facts, R is the set of relation types and  $c: V \to D$  is a node coloring. When  $D = \mathbb{R}^d$ , we also say that c is a d-dimensional feature map, and typically use  $\boldsymbol{x}$  instead of c. We write r(u,v) to denote a fact, where  $r \in R$  and  $u,v \in V$ . The neighborhood of a node  $v \in V$  relative to a relation  $r \in R$  is defined as  $\mathcal{N}_r(v) := \{u \mid r(u,v) \in E\}$ .

**Graph invariants.** We define k-ary graph invariants [24], for which we first define isomorphism over knowledge graphs. An isomorphism from a knowledge graph G = (V, E, R, c) to a knowledge graph G' = (V', E', R, c') is a bijection  $f: V \to V'$  such that c(v) = c'(f(v)) for all  $v \in V$ , and  $r(u, v) \in E$  if and only if  $r(f(u), f(v)) \in E'$ , for all  $r \in R$  and  $u, v \in V$ . A 0-ary graph invariant is a function  $\xi$  defined on knowledge graphs such that  $\xi(G) = \xi(G')$  for all isomorphic knowledge graphs G and G'. For  $k \ge 1$ , a k-ary graph invariant is a function  $\xi$  that associates with each knowledge graph G = (V, E, R, c) a function  $\xi(G)$  defined on  $V^k$  such that for all knowledge graphs G and G', all isomorphisms f from G to G', and all k-tuples of nodes  $v \in V^k$ , it holds that  $\xi(G)(v) = \xi(G')(f(v))$ . If k = 1, this defines a node invariant, or unary invariant, and if k = 2, this defines a binary invariant, which is central to our study.

**Refinements.** A function  $\xi(G): V^k \to D$  refines a function  $\xi'(G): V^k \to D$ , denoted as  $\xi(G) \preceq \xi'(G)$ , if for all  $v, v' \in V^k$ ,  $\xi(G)(v) = \xi(G)(v')$  implies  $\xi'(G)(v) = \xi'(G)(v')$ . We call such functions equivalent, denoted as  $\xi(G) \equiv \xi'(G)$ , if  $\xi(G) \preceq \xi'(G)$  and  $\xi'(G) \preceq \xi(G)$ . A k-ary graph invariant  $\xi$  refines a k-ary graph invariant  $\xi'$ , if  $\xi(G)$  refines  $\xi'(G)$  for all knowledge graphs G.

### 3.2 Relational message passing neural networks

We introduce the framework of relational message passing neural networks (R-MPNNs), which is basic to our study. This framework allows us to compute node representations for knowledge graphs and capture several known models such as RGCN [6] and CompGCN [7], among others. The idea is that R-MPNNs iteratively update the feature of a node v based on the different relation types  $r \in R$  and the features of the corresponding neighbors in  $\mathcal{N}_r(v)$ .

Let G = (V, E, R, x) be a knowledge graph, where x is a feature map. An R-MPNN computes sequence of feature maps  $\mathbf{h}^{(t)}: V \to \mathbb{R}^{d(T)}$ , for  $t \geq 0$ . For simplicity, we write  $\mathbf{h}_v^{(t)}$  instead of  $\mathbf{h}^{(t)}(v)$ . For each node  $v \in V$ , the representations  $\mathbf{h}_v^{(t)}$  are iteratively computed as:

$$\begin{split} & \boldsymbol{h}_v^{(0)} = \boldsymbol{x}_v \\ & \boldsymbol{h}_v^{(t+1)} = \phi \big( \boldsymbol{h}_v^{(f(t))}, \psi(\{\!\!\{\boldsymbol{\theta}_r(\boldsymbol{h}_w^{(t)}) | \ w \in \mathcal{N}_r(v), r \in R\}\!\!\} \big), \end{split}$$

where  $\phi$ ,  $\psi$ , and  $\theta_r$  are differentiable *update*, *aggregation*, and relation-specific *message* functions, respectively, and  $f: \mathbb{N} \to \mathbb{N}$  is a *history* function<sup>1</sup>, which is always non-decreasing and satisfies  $f(t) \leq t$ . R-MPNN has a fixed number of layers  $T \geq 0$ , and then, the final node representations are given by the map  $\mathbf{h}^{(T)}: V \to \mathbb{R}^{d(T)}$ .

An R-MPNN then computes node invariants (as defined in Section 3.1) at every layer, given by  $h^{(t)}$ , which results in an encoder function enc that associates with each knowledge graph G a function  $enc(G): V \to \mathbb{R}^{d(T)}$ , which effectively defines a node invariant (corresponding to  $h^{(T)}$ ). These final representations can therefore be used for node-level predictions (resp., graph-level predictions after *pooling*, e.g. summing all node embeddings) by applying

<sup>&</sup>lt;sup>1</sup>Typically f(t) = t, but later we consider different options.

a node-level decoder (resp., graph-level decoder). To apply R-MPNNs to link-level tasks, the most typical choice is to use a binary decoder  $\operatorname{dec}_q: \mathbb{R}^{d(T)} \times \mathbb{R}^{d(T)} \to \mathbb{R}$ , which produces a score for the likelihood of the fact q(u, v), for  $q \in R$ .

## 3.3 Expressive power of R-MPNNs

The expressive power of R-MPNNs has been recently characterized in terms of the well-known Weisfeiler-Leman test [8]. We define the *relational local* 1-WL  $test^2$ , denoted by  $rwl_1$ , as follows. Let G = (V, E, R, c) be a knowledge graph. For each  $t \ge 0$ , the test updates the coloring as follows:

$$\begin{split} & \operatorname{rwl}_1^{(0)}(v) = c(v), \\ & \operatorname{rwl}_1^{(t+1)}(v) = \tau \big( \operatorname{rwl}_1^{(t)}(v), \{\!\!\{ (\operatorname{rwl}_1^{(t)}(v), r) | \ w \in \mathcal{N}_r(v), r \in R \}\!\!\} \big), \end{split}$$

where  $\tau$  injectively maps the above pair to a unique color, which has not been used in previous iterations. Note that  $\text{rwl}_1^{(t)}$  defines a node invariant for all  $t \geq 0$ .

The following correspondence between R-MPNNs and rwl<sub>1</sub> generalizes results from [8].

**Theorem 3.1.** Let G = (V, E, R, c) be a knowledge graph.

- 1. For all initial feature maps  $\mathbf{x}$  with  $c \equiv \mathbf{x}$ , all R-MPNNs with T layers, and  $0 \le t \le T$ , we have  $\mathrm{rwl}_1^{(t)} \preceq \mathbf{h}^{(t)}$ .
- 2. For all  $T \ge 0$  and history function f, there is an initial feature map x with  $c \equiv x$  and an R-MPNN with T layers and history function f, such that for all  $0 \le t \le T$ , we have  $\text{rwl}_1^{(t)} \equiv h^{(t)}$ .

The proof of Theorem 3.1 can be found in Appendix A.1. Intuitively, item (1) states that the relational local 1-WL algorithm upper bounds the power of any R-MPNN  $\mathcal{A}$ : if the test cannot distinguish two nodes, then  $\mathcal{A}$  cannot either. On the other hand, item (2) states that R-MPNNs can be as expressive as rwl<sub>1</sub>: for any time limit T, there is an R-MPNN that simulates T iterations of the test.

Remark 3.2. A direct corollary of Theorem 3.1 is that R-MPNNs have the same expressive power as rwl<sub>1</sub>, independently of their history function.

#### 4 Conditional MPNNs

It is well-known that R-MPNNs have serious limitations for the task of link prediction [9], which has led to the study of several efficient models that compute pairwise representations directly. Unfortunately, and in contrast with the case of R-MPNNs, our understanding of these models is limited. In this section, we introduce the framework of conditional MPNNs that offers a natural framework for the systematic study of various of these models.

Let G = (V, E, R, x) be a knowledge graph, where x is a feature map. A *conditional message passing neural network* (C-MPNN) iteratively computes pairwise representations relative to a fixed query  $q \in R$ , and a fixed node  $u \in V$ , as:

$$\begin{aligned} & \boldsymbol{h}_{v|u,q}^{(0)} = \delta(u, v, q), \\ & \boldsymbol{h}_{v|u,q}^{(t+1)} = \phi \big( \boldsymbol{h}_{v|u,q}^{f(t)}, \psi(\{ \theta_r(\boldsymbol{h}_{w|u,q}^{(t)}, q) | w \in \mathcal{N}_r(v), r \in R \} \} \big) \big) \end{aligned}$$

where  $\delta$ ,  $\phi$ ,  $\psi$ , and  $\theta_r$  are differentiable *initialization*, *update*, *aggregation*, and relation-specific *message* functions, respectively, and f is the history function. We denote by  $\boldsymbol{h}_q^{(t)}: V \times V \to \mathbb{R}^{d(t)}$  the function  $\boldsymbol{h}_q^{(t)}(u,v) := \boldsymbol{h}_{v|u,q}^{(t)}$ . A C-MPNN has a fixed number of layers  $T \geq 0$ , and then the final pair representations are given by  $\boldsymbol{h}_q^{(T)}$ .

Intuitively, C-MPNNs condition on a source node u in order to compute representations of (u,v) for all target nodes v. C-MPNNs compute binary invariants, provided that the initialization  $\delta$  is a binary invariant. To ensure that the resulting model computes pairwise representations, we require  $\delta(u,v,q)$  to be a nontrivial function in the sense that it needs to satisfy *target node distinguishability*: for all  $q \in R$  and  $v \neq u \in V$ , it holds that  $\delta(u,u,q) \neq \delta(u,v,q)$ .

This is very closely related to the *Labeling Trick* proposed by [9], which is an initialization method aiming to differentiate a set  $\{u,v\}$  of target nodes from the remaining nodes in a graph. However, the *Labeling Trick* only applies when both the source u and target nodes v are labeled. Recent state-of-the-art models such as ID-GNN [19] and NBFNet [11]

<sup>&</sup>lt;sup>2</sup>This test over single-relation graphs is often called *color refinement* [24]. In [8] it is also called *multi-relational* 1-WL.

utilize a similar method, but only with the source node u labeled differently in initialization. Our definition captures precisely this, and we offer a theoretical analysis of the capabilities of the aforementioned models accordingly.

One alternative is to directly learn pairwise representations following similar ideas to those of higher-order GNNs, but these algorithms are not scalable. Models such as NBFNets represent a trade-off between computational complexity and expressivity. The advantage of learning conditional representations  $h_{v|u,q}$  is to be able to learn such representations in parallel for all  $v \in V$ , amortizing the computational overhead; see [11] for a discussion.

### 4.1 Design space and models

The design space of C-MPNNs is very large. Consider, for a query relation  $q \in R$  and a fixed node u, the following basic model instance:

$$egin{aligned} oldsymbol{h}_{v|u,q}^{(0)} &= \mathbb{1}_{u=v} * oldsymbol{z}_q, \ oldsymbol{h}_{v|u,q}^{(t+1)} &= \sigma \Big( oldsymbol{W}^{(t)} ig( oldsymbol{h}_{v|u,q}^{(t)} + \sum_{r \in R} \sum_{w \in \mathcal{N}_r(v)} heta_r^1 ig( oldsymbol{h}_{w|u,q}^{(t)}, oldsymbol{z}_q ig) ig) \Big), \end{aligned}$$

where  $\theta_r^1(\boldsymbol{h}_{w|u,q}^{(t)}, \boldsymbol{z}_q) = \boldsymbol{h}_{w|u,q}^{(t)} * \boldsymbol{W}_r^{(t)} \boldsymbol{z}_q$  is the message function with \* representing element-wise multiplication,  $\boldsymbol{z}_q$  is a learnable vector representing the query  $q \in R$ , the function  $\mathbb{1}_{u=v}(v)$  is the indicator function which returns the all-ones vector 1 if u=v and the all-zeros vector 0 otherwise with the corresponding size and  $\sigma$  is a non-linearity<sup>3</sup>. The matrices  $\boldsymbol{W}^{(t)}$  and  $\boldsymbol{W}_r^{(t)}$  are model parameters.

Initialization. We consider the following natural variants for initialization:

$$\begin{split} &\delta_1(u,v,q) = \mathbb{1}_{u=v} * \mathbf{1}, \\ &\delta_2(u,v,q) = \mathbb{1}_{u=v} * \boldsymbol{z}_q, \\ &\delta_3(u,v,q) = \mathbb{1}_{u=v} * (\boldsymbol{z}_q + \epsilon_u) \end{split}$$

Clearly, both  $\delta_1$  and  $\delta_2$  satisfy target node distinguishability assumption if we assume  $z_q \neq 0$ , where  $\delta_2$ , in addition, allows query-specific initialization to be considered. Suppose we further relax the condition to be target node distinguishability in expectation. We can then define  $\delta_3$ , which can also distinguish between each conditioned node u given the same query vector  $z_q$  by adding an error vector  $\epsilon_u$  sampled from  $\mathcal{N}(0,1)$  to the conditioned node's initialization.

Aggregation. We consider sum aggregation and Principal Neighborhood Aggregation (PNA) [25].

Message. We consider the following variations of message functions:

$$\begin{split} & \theta_r^1(\boldsymbol{h}_{w|u,q}^{(t)}, \boldsymbol{z}_q) = \boldsymbol{h}_{w|u,q}^{(t)} * \boldsymbol{W}_r^{(t)} \boldsymbol{z}_q, \\ & \theta_r^2(\boldsymbol{h}_{w|u,q}^{(t)}, \boldsymbol{z}_q) = \boldsymbol{h}_{w|u,q}^{(t)} * \boldsymbol{b}_r, \\ & \theta_r^3(\boldsymbol{h}_{w|u,q}^{(t)}, \boldsymbol{z}_q) = \boldsymbol{W}_r^{(t)} \boldsymbol{h}_{w|u,q}^{(t)} \end{split}$$

Observe that  $\theta_r^1$  computes a query-dependent message, whereas  $\theta_r^2$  and  $\theta_r^3$  can be seen analogous to message computations of CompGCN and RGCN, respectively.

**History.** In addition, we can set f, which intuitively is the function that determines the history of node embeddings to be considered. By setting f(t) = t, we obtain a standard message-passing algorithm where the update function considers the representation of the node in the previous iteration. We can alternatively set f(t) = 0, in which case we obtain (a slight generalization of) NBFNets.

**Models.** We refer to these models as C-MPNN $(\delta, \psi, \theta_r, f)$ , where  $\delta = \{\delta_0, \dots, \delta_4\}$ ,  $\psi \in \{\text{sum}, \text{PNA}\}$ ,  $\theta \in \{\theta_r^1, \theta_r^2, \theta_r^3\}$ , and f is a history function. For example, we write the basic model as C-MPNN $(\delta_2, \text{sum}, \theta_r^1, f(t) = t)$ .

## 5 Characterizing the Expressive Power

## 5.1 A relational Weisfeiler-Leman characterization

To analyze the expressive power of C-MPNNs, we introduce the *relational asymmetric local* 2-WL, denoted by rawl<sub>2</sub>. In this case, we work with knowledge graphs of the form  $G = (V, E, R, c, \eta)$ , where  $\eta : V \times V \to D$  is a *pairwise* 

<sup>&</sup>lt;sup>3</sup>We omit the bias term for ease of presentation. One can add a bias term after the linear transformation  $W^{(t)}$ . Likewise for  $\theta_r^1$ .

coloring. We say that  $\eta$  satisfies target node distinguishability if  $\eta(u, u) \neq \eta(u, v)$  for all  $u \neq v \in V$ . The notions of isomorphism and invariants extend to this context in a natural way. For each  $t \geq 0$ , we update the coloring as:

$$\begin{aligned} & \operatorname{rawl}_2^{(0)}(u,v) = \eta(u,v), \\ & \operatorname{rawl}_2^{(t+1)}(u,v) = \tau \big( \operatorname{rawl}_2^{(t)}(u,v), \{\!\!\{ (\operatorname{rawl}_2^{(t)}(u,w),r) \mid w \in \mathcal{N}_r(v), r \in R ) \}\!\!\} \big) \end{aligned}$$

where  $\tau$  injectively maps the above pair to a unique color, which has not been used in previous iterations. Observe that  $\mathsf{rawl}_2^{(t)}$  defines a binary invariant, for all  $t \geq 0$ .

The test is asymmetric: given a pair (u, v), we only look at neighbors of (u, v) obtained by changing the second coordinate of the pair. In contrast, usual versions of (local) k-WL are symmetric as neighbors may change any coordinate.

Interestingly, the rawl<sub>2</sub> test characterizes the power of C-MPNNs in terms of distinguishing pairs of nodes.

**Theorem 5.1.** Let  $G = (V, E, R, x, \eta)$  be a knowledge graph, where x is a feature map and  $\eta$  is a pairwise coloring satisfying target node distinguishability. Let  $q \in R$  be any query relation. Then:

- 1. For all C-MPNNs with T layers and initialization  $\delta$  with  $\delta \equiv \eta$ , and  $0 \le t \le T$ , we have  $\mathsf{rawl}_2^{(t)} \le \boldsymbol{h}_q^{(t)}$ .
- 2. For all  $T \ge 0$  and history function f, there is a C-MPNN with T layers and history function f such that for all  $0 \le t \le T$ , we have  $\operatorname{rawl}_2^{(t)} \equiv \boldsymbol{h}_q^{(t)}$ .

The proof of Theorem 5.1 can be found in Appendix A.2. The idea of the proof is to reduce to the one-dimensional case, that is, R-MPNNs and  $rwl_1$ , via an auxiliary graph  $G^2$  that encodes pairs of nodes of G, and then apply the equivalence between R-MPNNs and  $rwl_1$  from Theorem 3.1. We stress that the lower bound (item (2)) holds even for the basic model of C-MPNNs and the three proposed message functions from Section 4.1 (see Remark A.7).

The expressive power of C-MPNNs is independent of the history function as in any case it is matched by rawl<sub>2</sub>. This suggests that the difference between traditional message passing models using functions f(t) = t and path-based models (such as NBFNets [11]) using f(t) = 0 is not relevant, at least from a theoretical point of view.

# 5.2 Logical characterization

We now turn to the problem of which binary classifiers can be expressed as C-MPNNs. That is, we look at C-MPNNs that classify each pair of nodes in a knowledge graph as true or false. Following [22], we study logical binary classifiers, i.e., those that can be defined in the formalism of first-order logic (FO). Briefly, a first-order formula  $\phi(x,y)$  with two free variables x,y defines a logical binary classifier that assigns value true to the pair (u,v) of nodes in knowledge graph G whenever  $G \models \phi(u,v)$ , i.e.,  $\phi$  holds in G when x is interpreted as u and y as v. A logical classifier  $\phi(x,y)$  is captured by a C-MPNN A if over every knowledge graph G the pairs (u,v) of nodes that are classified as true by  $\phi$  and A are the same.

A natural problem then is to understand what are the logical classifiers captured by C-MPNNs. Fix a set of relation types R and a set of pair colors  $\mathcal C$ . We consider knowledge graphs of the form  $G=(V,E,R,\eta)$  where  $\eta$  is a mapping assigning colors from  $\mathcal C$  to pairs of nodes from V. In this context, FO formulas can refer to the different relation types in R and the different pair colors in  $\mathcal C$ . Our characterization is established in terms of a simple fragment of FO, which we call  ${\sf rGFO}^3_{\rm cnt}$ , and is inductively defined as follows: First, a(x,y) for  $a\in\mathcal C$ , is in  ${\sf rGFO}^3_{\rm cnt}$ . Second, if  $\phi(x,y)$  and  $\psi(x,y)$  are in  ${\sf rGFO}^3_{\rm cnt}$ ,  $N\geq 1$  is a positive integer, and  $r\in R$ , then the formulas

$$\neg \varphi(x,y), \quad \varphi(x,y) \wedge \psi(x,y), \quad \exists^{\geq N} z \left( \varphi(x,z) \wedge r(z,y) \right)$$

are also in rGFO $_{\mathrm{cnt}}^3$ . Intuitively, a(u,v) holds in  $G=(V,E,R,\eta)$  if  $\eta(u,v)=a$ , and  $\exists^{\geq N}z\,(\varphi(u,z)\wedge r(z,v))$  holds in G if v has at least N incoming edges labeled R from nodes w for which  $\phi(u,w)$  holds in G. We use the acronym rGFO $_{\mathrm{cnt}}^3$  as it can be proved that this logic corresponds to a restriction of the Guarded fragment of FO with three variables and counting.

Interestingly, we can show the following:

**Theorem 5.2.** A logical binary classifier is captured by C-MPNNs if and only if it can be expressed in rGFO<sub>cnt</sub><sup>3</sup>.

We refer the reader to Appendix A.3 for technical details and the proof of Theorem 5.2.

# 5.3 Locating $rawl_2$ in the relational WL landscape

Note that  $rawl_2$ , and hence C-MPNNs, are *one-directional*: the neighborhood  $\mathcal{N}_r(v)$  only considers facts in one direction, in this case, *from* neighbors to v. Hence, a natural extension is to consider *bi-directional* neighborhoods.




Figure 1: Hierarchy of expressive power for the local 2-WL algorithms considered in this paper.  $A \to B$  if and only if  $A \leq B$ . Note that  $\mathsf{rwl}_2$  and  $\mathsf{rawl}_2^+$  are incomparable by Proposition A.15, and  $\mathsf{rwl}_2^+ \leq \mathsf{rawl}_2^+$  can be shown analogously using proof in Proposition A.13.

Fortunately, we can define this extension by simply applying the same test  $rawl_1$  to knowledge graphs extended with *inverse* relations. We formalize this below.

For a test T, we sometimes write  $\mathsf{T}(G,u,v)$ , or  $\mathsf{T}(G,v)$  in case of unary tests, to emphasize that the test is applied over G, and  $\mathsf{T}(G)$  for the node/pairwise coloring given by the test. Let  $G=(V,E,R,c,\eta)$  be a knowledge graph. We define its augmented knowledge graph to be  $G^+=(V,E^+,R^+,c,\eta)$ , where  $R^+$  is the disjoint union of R and  $\{r^-\mid r\in R\}$ , and

$$E^{+} = E \cup \{r^{-}(v, u) \mid r(u, v) \in E, u \neq v\}.$$

We define the augmented relational asymmetric local 2-WL test on G, denoted by  $\operatorname{rawl}_2^+$ , as  $\operatorname{rawl}_2^{+(t)}(G,u,v) = \operatorname{rawl}_2^{(t)}(G^+,u,v)$ , for all  $t \geq 0$  and  $u,v \in V$ . As we show below,  $\operatorname{rawl}_2^+$  is strictly more powerful than  $\operatorname{rawl}_2$ .

**Proposition 5.3.** *The following statements hold:* 

- 1. For all  $t \geq 0$  and all knowledge graphs G, we have  $\operatorname{rawl}_2^{+(t)}(G) \leq \operatorname{rawl}_2^{(t)}(G)$ .
- 2. There is a knowledge graph G and nodes u,v,u',v' such that  $\operatorname{rawl}_2^{+(1)}(G,u,v) \neq \operatorname{rawl}_2^{+(1)}(G,u',v')$  but  $\operatorname{rawl}_2^{(t)}(G,u,v) = \operatorname{rawl}_2^{(t)}(G,u',v')$  for all  $t \geq 1$ .

We can also extend C-MPNNs with bi-directionality in an obvious way, obtaining *augmented* C-MPNNs. By applying Theorem 5.1 to the augmented graph  $G^+$ , we obtain the equivalence between augmented C-MPNNs and the test rawl<sub>2</sub><sup>+</sup> directly. In turn, Proposition 5.3 implies that augmented C-MPNNs are strictly more powerful that C-MPNNs in distinguishing nodes in a graph.

It is common practice to extend knowledge graphs with inverse relations [11, 20, 21, 7]. Our results formally explain the benefits of this design choice, showing that it leads to provably more powerful models.

We conclude this section by relating rawl<sub>2</sub> to a known relational variant of 2-WL, namely, the *relational (symmetric)* local 2-WL test, denoted by rwl<sub>2</sub>. Given a knowledge graph  $G = (V, E, R, c, \eta)$ , this test assigns pairwise colors via the following update rule:

$$\mathsf{rwl}_2^{(t+1)}(u,v) = \tau \left(\mathsf{rwl}_2^{(t)}(u,v), \{\!\!\{ (\mathsf{rwl}_2^{(t)}(w,v),r) \mid w \in \mathcal{N}_r(u), r \in R \}\!\!\}, \{\!\!\{ (\mathsf{rwl}_2^{(t)}(u,w),r) \mid w \in \mathcal{N}_r(v), r \in R \}\!\!\} \right)$$

This test and a corresponding neural model, for arbitrary order  $k \ge 2$ , have been recently studied in [8] under the name of *multi-relational local k-WL*. We define the augmented version rwl<sub>2</sub><sup>+</sup> in an obvious way.

Figure 1 shows the hierarchy of expressive power for all these models. The technical details showing these results can be found in Appendix A.4.

# 6 Experimental Evaluation

We experiment on common knowledge graph benchmarks and aim to answer the following questions:

- **Q1** What is the impact of the history function on the model performance? In particular, do models with f(t) = t perform comparably to those with f(t) = 0?
- Q2 How do the specific choices for aggregation and message functions affect the model performance?
- **Q3** What is the impact of the initialization function on the model performance? What happens when the target identifiability property does not hold?

Table 1: Inductive relation prediction of C-MPNN with  $\delta_2$  initialization. The best results for each choice of aggregation function are shown in **bold** and the second best results are <u>underlined</u>.

<b>Model Instances</b>			WN18RR				FB15k-237			
$\psi$	$\theta_r$	f(t)	v1	<b>v2</b>	v3	<b>v4</b>	v1	<b>v2</b>	v3	<b>v4</b>
sum	$\theta_r^1$	0	0.934	0.896	0.894	0.881	0.784	0.900	0.940	0.923
sum	$\theta_r^1$	t	0.932	0.896	0.900	0.881	0.794	0.906	0.947	0.933
sum	$\theta_r^2$	0	0.939	0.906	0.881	0.881	0.734	0.899	0.911	0.941
sum	$\theta_r^2$	t	0.937	0.906	0.865	0.884	0.728	0.883	0.929	0.931
sum	$\theta_r^3$	0	0.943	0.898	0.888	0.877	0.850	0.934	0.919	0.941
sum	$\theta_r^3$	t	0.934	0.896	0.892	0.880	0.844	0.943	0.926	0.950
PNA	$\theta_r^1$	0	0.943	0.897	0.898	0.886	0.801	0.945	0.934	0.960
PNA	$ heta_r^1$	t	0.941	0.895	0.904	0.886	0.804	0.949	0.945	0.954
PNA	$\theta_r^2$	0	0.946	0.900	0.896	0.887	0.715	0.896	0.887	0.886
PNA	$\theta_r^2$	t	0.947	0.902	0.901	0.888	0.709	0.899	0.875	0.894
PNA	$\theta_r^3$	0	0.947	0.898	0.899	0.884	0.767	0.933	0.835	0.911
PNA	$\theta_r^3$	t	0.944	0.897	0.894	0.882	0.766	0.916	0.893	0.930

#### 6.1 Experimental setup

**Datasets.** We use the datasets WN18RR [26] and FB15k-237 [27], for inductive relation prediction tasks, following a standardized train-test split given in four versions [10]. We augment each fact r(u, v) with an inverse fact  $r^{-1}(v, u)$ . There are no node features for either of the datasets, and the initialization is given by the respective initialization function  $\delta$ . This allows all the proposed GNN models to be applied in the inductive setup and to better align with the corresponding relational Weisfeiler-Leman algorithms. The statistics of the datasets are reported in Appendix 3.

**Implementation.** All models use 6 layers, each with 32 hidden dimensions. The decoder function parameterized the probability of a fact q(u,v) as  $p(v \mid u,q) = \sigma(f(\boldsymbol{h}_{v|u,q}^{(T)}))$ , where  $\sigma$  is the sigmoid function, and f is a 2-layer MLP with 64 hidden dimensions. We adopted layer-normalization [28] and short-cut connection after each aggregation and before applying ReLU. For the experiments concerning the message function  $\theta_r^3$ , we follow the basis decomposition for the FB15k237 dataset with 30 basis functions. We ran all the experiments for 20 epochs on 1 Tesla T4 GPU, using the codebase of NBFNet<sup>4</sup> with mild modifications to accommodate all models studied in this paper. We discard the edges that directly connect query node pairs to prevent overfitting. The best checkpoint for each model instance is selected based on its performance on the validation set. All hyperparameter details are reported in Appendix 4.

**Evaluation.** We consider *filtered ranking protocol* [29]: for each test fact r(u, v), we construct 50 negative samples r(u', v'), randomly replacing either the head entity or the tail entity, and we report HITS@10, which is the rate of correctly predict entities appearing in the top 10 entries for each instance list prediction. We report averaged results of *five* independent runs for all experiments.

## **6.2** Empirical results

We report inductive link prediction results for different C-MPNN models in Table 1. These models are all initialized with  $\delta_2$ . Each row of Table 1 corresponds to a specific model, which allows us to compare the model components<sup>5</sup>.

**History functions** (Q1). First of all, we note that there is no significant difference between the models with different history functions. Specifically, for any choice of aggregate and message functions, the model which sets f(t) = t performs comparably to the model which sets f(t) = 0. These findings support our theoretical findings, which state that path-based message passing and traditional message passing essentially have the same expressive power. This may appear as a subtle point, but it is very important for informing future work: the strength of this class of models for link prediction is fundamentally due to their ability to compute more expressive *binary invariants*, which holds regardless of the choice of the history function.

<sup>&</sup>lt;sup>4</sup>https://github.com/DeepGraphLearning/NBFNet

<sup>&</sup>lt;sup>5</sup>NBFNets [11] use different message functions for different datasets. We separately report for each model instance to specifically pinpoint the impact of each model component.

Initialization Method	WN18RR				FB15k-237			
$\delta(u, v, q)$	v1	v2	v3	v4	v1	<b>v2</b>	v3	<b>v4</b>
$\delta_0(u, v, q) = 0$	0.615	0.715	0.811	0.654	0.777	0.903	0.894	0.910
$\delta_1(u,v,q) = \mathbb{1}_{u=v} * 1$	0.932	0.894	0.902	0.883	0.809	0.927	0.944	0.911
$\delta_2(u,v,q) = \mathbb{1}_{u=v} * \boldsymbol{z}_q$	0.932	0.896	0.900	0.881	0.794	0.906	0.947	0.933
$\delta_3(u, v, q) = \mathbb{1}_{u=v} * (\mathbf{z}_q + \epsilon_u)$	0.934	0.890	0.894	0.877	0.804	0.924	0.941	0.944
$\delta_4(u, v, q) = \mathbb{1}_{u=v} * \epsilon_q$	0.918	0.874	0.844	0.865	0.514	0.743	0.829	0.748

Table 2: Inductive relation prediction of C-MPNN( $\delta$ , sum,  $\theta_1^1$ , f(t) = t) with different initialization methods,

Message functions (Q2). We start by highlighting that there is no significant difference between different message functions on WN18RR, which is unsurprising: WN18RR splits contain at most 11 relation types, which undermines the impact of the differences in message functions. In contrast, the results on FB15k237 are very informative in this respect: models using  $\theta_r^2$  clearly perform worse than all the other choices, which can be explained by the fact that  $\theta_r^2$  utilizes fewer relation-specific parameters. Most importantly, the message function  $\theta_r^3$  appears strong and robust across models. This is essentially the message function of RGCN and follows the idea of basis decomposition to regularize the parameter matrices. Models using  $\theta_r^3$  with fewer parameters (see the appendix) can match or substantially exceed the performance of the models using  $\theta_r^3$ , where the latter is the primary message function used in NBFNets. This may appear counter-intuitive since  $\theta_r^3$  does not have a learnable query vector  $\mathbf{z}_q$ , but recall that this vector is nonetheless part of the model via the initialization function  $\delta_2$ .

Aggregation functions (Q2). We report experiments with two aggregation functions:  $\psi = \text{sum}$  and  $\psi = \text{PNA}$ . As before, we do not observe significant trends on WN18RR, but PNA tends to result in slightly better-performing models. On FB15k237, there seems to be an intricate interplay between aggregation and message functions. For the message function  $\theta_r^1$ , models using PNA outperform models using sum. On the other hand, for both  $\theta_r^2$  and  $\theta_r^3$ , sum aggregation is substantially better. These findings suggest that a sophisticated aggregation, such as PNA, may not be necessary since it can be matched (and even outperformed) with a sum aggregation. In fact, the model with  $\psi = \text{sum}$  and  $\theta_r^3$  is very closely related to RGCN and appears to be one of the best-performing models across the board. This supports our theory since, intuitively, this model can be seen as an adaptation of RGCN to compute binary invariants while keeping the choices for model components the same as RGCN.

Initialization functions (Q3). We argued that the initialization function  $\delta(u,v,q)$  needs to satisfy the property of target node distinguishability to compute binary invariants. To validate the impact of different initialization regimes, we conduct a further experiment which is reported in Table 2. In addition to the initialization functions  $\delta_1, \delta_2, \delta_3$  defined in Section 4.1, we also experiment with a very simple function  $\delta_0$  which assigns 0 to all nodes. As expected, if we use  $\delta_0$  for initialization, we observe a very sharp decrease in model performance in WN18RR, but less so in FB15k237. Intuitively, the model suffers more in WN18RR since there are much fewer relations, and it is harder to distinguish node pairs without an initialization designed to achieve this. Perhaps one of the simplest functions satisfying target node distinguishability criteria is  $\delta_1 = \mathbb{1}_{u=v} * 1$ , which pays no respect to the target query relation. Empirically,  $\delta_1$  achieves strong results, showing that even the simplest function ensuring this property could boost the model performance. Interestingly, the performance of models using  $\delta_1$  match or exceed models using  $\delta_2$ , even though the latter additionally has a relation-specific learnable query vector. Note, however, that this shall not undermine the role of the learnable query relation: integrating the learnable query vector either in the initialization function or in the message computation function seems to suffice.

Random initialization (Q3). The idea of random node initialization is known to lead to more expressive models [30, 31]. Inspired by this, we can incorporate varying degrees of randomization to the initialization, satisfying the target node distinguishability property in expectation. The key advantage is that the resulting models are still inductive and achieve a nontrivial expressiveness gain over alternatives. The simplest idea is to replace the learnable query vector with a random vector, which results in a function denoted  $\delta_4$ . This naive randomization yields very poor performance, showing the benefit of a learnable query relation. It is, therefore, natural to have a learnable query vector but to slightly perturb this vector as in  $\delta_3$ . In this case, the models with  $\delta_3$  perform closer to the models with  $\delta_2$ , but we do not see a particular advantage on these benchmarks.

## 7 Discussions and Outlook

We studied a broad general class of GNNs designed for link prediction over knowledge graphs with a focus on formally characterizing their expressive power. Our study shows that recent state-of-the-art models are at a 'sweet spot': while

they compute binary invariants, they do so through some local variations of higher-dimensional Weisfeler-Leman tests. This is precisely defined and characterized within our framework. This study paints a more complete picture for our overall understanding of existing models and informs future work on possible directions.

## References

- [1] Franco Scarselli, Marco Gori, Ah Chung Tsoi, Markus Hagenbuchner, and Gabriele Monfardini. The graph neural network model. *IEEE Transactions on Neural Networks*, 2009.
- [2] Marco Gori, Gabriele Monfardini, and Franco Scarselli. A new model for learning in graph domains. In *Proceedings of the 2005 IEEE International Joint Conference on Neural Networks, IJCNN*, 2005.
- [3] Justin Gilmer, Samuel S. Schoenholz, Patrick F. Riley, Oriol Vinyals, and George E. Dahl. Neural message passing for quantum chemistry. In *Proceedings of the Thirty-Fourth International Conference on Machine Learning, ICML*, 2017.
- [4] Keyulu Xu, Weihua Hu, Jure Leskovec, and Stefanie Jegelka. How powerful are graph neural networks? In *Proceedings of the Seventh Annual Conference on Learning Representations, ICLR*, 2019.
- [5] Christopher Morris, Martin Ritzert, Matthias Fey, William L. Hamilton, Jan Eric Lenssen, Gaurav Rattan, and Martin Grohe. Weisfeiler and Leman go neural: Higher-order graph neural networks. In *Proceedings of the Thirty-Third AAAI Conference on Artificial Intelligence, AAAI*, 2019.
- [6] Michael Sejr Schlichtkrull, Thomas N. Kipf, Peter Bloem, Rianne van den Berg, Ivan Titov, and Max Welling. Modeling relational data with graph convolutional networks. In *Proceedings of the Fifteenth International Conference on the Semantic Web, ESWC*, 2018.
- [7] Shikhar Vashishth, Soumya Sanyal, Vikram Nitin, and Partha Talukdar. Composition-based multi-relational graph convolutional networks. In *International Conference on Learning Representations*, 2020.
- [8] Pablo Barceló, Mikhail Galkin, Christopher Morris, and Miguel Romero. Weisfeiler and leman go relational. In *Learning on Graphs, LoG*, 2022.
- [9] Muhan Zhang, Pan Li, Yinglong Xia, Kai Wang, and Long Jin. Labeling trick: A theory of using graph neural networks for multi-node representation learning. In *Advances in Neural Information Processing Systems*, 2021.
- [10] Komal K. Teru, Etienne G. Denis, and William L. Hamilton. Inductive relation prediction by subgraph reasoning. In *Proceedings of the 37th International Conference on Machine Learning*, 2020.
- [11] Zhaocheng Zhu, Zuobai Zhang, Louis-Pascal Xhonneux, and Jian Tang. Neural bellman-ford networks: A general graph neural network framework for link prediction. *Advances in Neural Information Processing Systems*, 2021.
- [12] Hongwei Wang, Hongyu Ren, and Jure Leskovec. Relational message passing for knowledge graph completion. In *Proceedings of the 27th ACM SIGKDD Conference on Knowledge Discovery amp; Data Mining*, 2021.
- [13] Lecheng Kong, Yixin Chen, and Muhan Zhang. Geodesic graph neural network for efficient graph representation learning. In *Advances in Neural Information Processing Systems*, 2022.
- [14] Thomas Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. In Proceedings of the Fifth International Conference on Learning Representations, ICLR, 2017.
- [15] Donghan Yu, Yiming Yang, Ruohong Zhang, and Yuexin Wu. Generalized multi-relational graph convolution network. *ArXiv*, 2020.
- [16] Muhan Zhang and Yixin Chen. Link prediction based on graph neural networks. In *Advances in Neural Information Processing Systems*, 2018.
- [17] Bryan Perozzi, Rami Al-Rfou, and Steven Skiena. Deepwalk: online learning of social representations. In *The* 20th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, KDD, 2014.
- [18] Aditya Grover and Jure Leskovec. Node2vec: Scalable feature learning for networks. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, 2016.
- [19] Jiaxuan You, Jonathan M. Gomes-Selman, Rex Ying, and Jure Leskovec. Identity-aware graph neural networks. In Thirty-Fifth AAAI Conference on Artificial Intelligence, AAAI 2021, Thirty-Third Conference on Innovative Applications of Artificial Intelligence, IAAI 2021, The Eleventh Symposium on Educational Advances in Artificial Intelligence, EAAI 2021, 2021.
- [20] Fan Yang, Zhilin Yang, and William W Cohen. Differentiable learning of logical rules for knowledge base reasoning. In *Advances in Neural Information Processing Systems*, 2017.

- [21] Ali Sadeghian, Mohammadreza Armandpour, Patrick Ding, and Daisy Zhe Wang. Drum: End-to-end differentiable rule mining on knowledge graphs. In *Proceedings of the 33rd International Conference on Neural Information Processing Systems*, 2019.
- [22] Pablo Barceló, Egor V. Kostylev, Mikaël Monet, Jorge Pérez, Juan L. Reutter, and Juan Pablo Silva. The logical expressiveness of graph neural networks. In *Proceedings of the Eighth International Conference on Learning Representations, ICLR*, 2020.
- [23] Christopher Morris, Gaurav Rattan, and Petra Mutzel. Weisfeiler and leman go sparse: Towards scalable higher-order graph embeddings. In *Proceedings of the Thirty-Fourth Annual Conference on Advances in Neural Information Processing Systems, NeurIPS*, 2020.
- [24] Martin Grohe. The logic of graph neural networks. In *Proceedings of the 36th Annual ACM/IEEE Symposium on Logic in Computer Science*, 2021.
- [25] Gabriele Corso, Luca Cavalleri, Dominique Beaini, Pietro Liò, and Petar Veličković. Principal neighbourhood aggregation for graph nets. In *Advances in Neural Information Processing Systems*, 2020.
- [26] Kristina Toutanova and Danqi Chen. Observed versus latent features for knowledge base and text inference. In *Proceedings of the 3rd Workshop on Continuous Vector Space Models and their Compositionality*, 2015.
- [27] Tim Dettmers, Minervini Pasquale, Stenetorp Pontus, and Sebastian Riedel. Convolutional 2d knowledge graph embeddings. In *Proceedings of the 32th AAAI Conference on Artificial Intelligence*, 2018.
- [28] Lei Jimmy Ba, Jamie Ryan Kiros, and Geoffrey E. Hinton. Layer normalization. CoRR, 2016.
- [29] Antoine Bordes, Nicolas Usunier, Alberto Garcia-Duran, Jason Weston, and Oksana Yakhnenko. Translating embeddings for modeling multi-relational data. In *Advances in Neural Information Processing Systems*, 2013.
- [30] Ryoma Sato, Makoto Yamada, and Hisashi Kashima. Random features strengthen graph neural networks. In *Proceedings of the 2021 SIAM International Conference on Data Mining, SDM*, 2021.
- [31] Ralph Abboud, İsmail İlkan Ceylan, Martin Grohe, and Thomas Lukasiewicz. The surprising power of graph neural networks with random node initialization. In *Proceedings of the Thirtieth International Joint Conference on Artificial Intelligence, IJCAI*, 2021.
- [32] Maarten de Rijke. A note on graded modal logic. Stud Logica, 2000.
- [33] Martin Otto. Graded modal logic and counting bisimulation, 2019.
- [34] Luis Antonio Galárraga, Christina Teflioudi, Katja Hose, and Fabian Suchanek. Amie: Association rule mining under incomplete evidence in ontological knowledge bases. In *Proceedings of the 22nd International Conference* on World Wide Web, 2013.
- [35] Zhiqing Sun, Zhi-Hong Deng, Jian-Yun Nie, and Jian Tang. Rotate: Knowledge graph embedding by relational rotation in complex space. In *International Conference on Learning Representations*, 2019.

# A Missing proofs

### A.1 Proof of Theorem 3.1

Let us recall the statement of the theorem.

**Theorem 3.1.** Let G = (V, E, R, c) be a knowledge graph, where c is a node coloring. Then:

- 1. For all initial feature maps x with  $c \equiv x$ , all R-MPNNs with T layers, and  $0 \le t \le T$ , we have  $\operatorname{rwl}_1^{(t)} \le h^{(t)}$ .
- 2. For all  $T \ge 0$  and history function f, there is an initial feature map x with  $c \equiv x$  and an R-MPNN with T layers and history function f, such that for all  $0 \le t \le T$ , we have  $\operatorname{rwl}_1^{(t)} \equiv h^{(t)}$ .

In order to prove the theorem, we define a variant of  $\mathrm{rwl}_1$  as follows. For a history function  $f:\mathbb{N}\to\mathbb{N}$  (recall f is non-decreasing and  $f(t)\leq t$ ), and given a knowledge graph G=(V,E,R,c), we define the  $\mathrm{rwl}_{1,f}$  test via the following update rules:

$$\begin{split} & \operatorname{rwl}_{1,f}^{(0)}(v) = c(v) \\ & \operatorname{rwl}_{1,f}^{(t+1)}(v) = \tau \big( \operatorname{rwl}_{1,f}^{(f(t))}(v), \{\!\!\{ (\operatorname{rwl}_{1,f}^{(t)}(v), r) | \ w \in \mathcal{N}_r(v), r \in R \}\!\!\} \big), \end{split}$$

where  $\tau$  injectively maps the above pair to a unique color, which has not been used in previous iterations. Note that  $\mathrm{rwl}_1$  corresponds to  $\mathrm{rwl}_{1,id}$  for the identity function id(t)=t.

We have that  $\operatorname{rwl}_{1,f}^{(t)}$  is always a refinement of  $\operatorname{rwl}_{1,f}^{(t-1)}$ . Note that this is trivial for f(t)=t but not for arbitrary history functions.

**Proposition A.1.** Let G = (V, E, R, c) be a knowledge graph and f be a history function. Then for all  $t \ge 0$ , we have  $\mathsf{rwl}_{1,f}^{(t+1)} \le \mathsf{rwl}_{1,f}^{(t)}$ .

*Proof.* We proceed by induction on t. For t=0, note that  $\mathsf{rwl}_{1,f}^{(1)}(u) = \mathsf{rwl}_{1,f}^{(1)}(v)$  implies  $\mathsf{rwl}_{1,f}^{(f(0))}(u) = \mathsf{rwl}_{1,f}^{(f(0))}(v)$  and f(0)=0. For the inductive case, suppose  $\mathsf{rwl}_{1,f}^{(t+1)}(u) = \mathsf{rwl}_{1,f}^{(t+1)}(v)$ , for  $t\geq 1$  and  $u,v\in V$ . By injectivity of  $\tau$ , we have that:

$$\begin{aligned} \operatorname{rwl}_{1,f}^{(f(t))}(u) &= \operatorname{rwl}_{1,f}^{(f(t))}(v) \\ \{\!\!\{ (\operatorname{rwl}_{1,f}^{(t)}(w), r) \mid w \in \mathcal{N}_r(u), r \in R \}\!\!\} &= \{\!\!\{ (\operatorname{rwl}_{1,f}^{(t)}(w), r) \mid w \in \mathcal{N}_r(v), r \in R \}\!\!\}. \end{aligned}$$

By inductive hypothesis and the facts that  $f(t-1) \leq f(t)$  (as f is non-decreasing) and  $\operatorname{rwl}_{1,f}^{(f(t))}(u) = \operatorname{rwl}_{1,f}^{(f(t))}(v)$ , we obtain  $\operatorname{rwl}_{1,f}^{(f(t-1))}(u) = \operatorname{rwl}_{1,f}^{(f(t-1))}(v)$ . On the other hand, by inductive hypothesis, we obtain that

$$\{\!\!\{(\operatorname{rwl}_{1,f}^{(t-1)}(w),r)\mid w\in\mathcal{N}_r(u),r\in R\}\!\!\}=\{\!\!\{(\operatorname{rwl}_{1,f}^{(t-1)}(w),r)\mid w\in\mathcal{N}_r(v),r\in R\}\!\!\}.$$

We conclude that  $\operatorname{rwl}_{1,f}^{(t)}(u) = \operatorname{rwl}_{1,f}^{(t)}(v)$ .

As it turns out,  $rwl_{1,f}^{(t)}$  defines the same coloring independently of f:

**Proposition A.2.** Let G = (V, E, R, c) be a knowledge graph and f, f' be history functions. Then for all  $t \ge 0$ , we have that  $\mathsf{rwl}_{1,f}^{(t)} = \mathsf{rwl}_{1,f'}^{(t)}$ .

*Proof.* We apply induction on t. For t=0, we have  $\operatorname{rwl}_{1,f}^{(0)}\equiv c\equiv\operatorname{rwl}_{1,f'}^{(0)}$ . For the inductive case, suppose  $\operatorname{rwl}_{1,f}^{(t)}(u)=\operatorname{rwl}_{1,f}^{(t)}(v)$ , for  $t\geq 1$  and  $u,v\in V$ . Since  $f'(t-1)\leq t-1$  and by Proposition A.1, we have that  $\operatorname{rwl}_{1,f}^{(f'(t-1))}(u)=\operatorname{rwl}_{1,f'}^{(f'(t-1))}(v)$ . The inductive hypothesis implies that  $\operatorname{rwl}_{1,f'}^{(f'(t-1))}(u)=\operatorname{rwl}_{1,f'}^{(f'(t-1))}(v)$ . On the other hand, by injectivity of  $\tau$  we have

$$\{\!\!\{(\operatorname{rwl}_{1,f}^{(t-1)}(w),r)\mid w\in\mathcal{N}_r(u),r\in R\}\!\!\}=\{\!\!\{(\operatorname{rwl}_{1,f}^{(t-1)}(w),r)\mid w\in\mathcal{N}_r(v),r\in R\}\!\!\}.$$

The inductive hypothesis implies that

$$\{ (\operatorname{rwl}_{1,f'}^{(t-1)}(w), r) \mid w \in \mathcal{N}_r(u), r \in R \} = \{ (\operatorname{rwl}_{1,f'}^{(t-1)}(w), r) \mid w \in \mathcal{N}_r(v), r \in R \} \}.$$

Summing up, we have that  $\operatorname{rwl}_{1,f'}^{(t)}(u) = \operatorname{rwl}_{1,f'}^{(t)}(v)$ , and hence  $\operatorname{rwl}_{1,f}^{(t)} \preceq \operatorname{rwl}_{1,f'}^{(t)}$ . The case  $\operatorname{rwl}_{1,f'}^{(t)} \preceq \operatorname{rwl}_{1,f}^{(t)}$  follows by symmetry.  $\square$ 

Now we are ready to prove the theorem.

We start with item (1). Take an initial feature map  $\boldsymbol{x}$  with  $c \equiv \boldsymbol{x}$ , an R-MPNN with T layers, and history function f. It suffices to show that  $\mathrm{rwl}_{1,f}^{(t)} \preceq \boldsymbol{h}^{(t)}$ , for all  $0 \leq t \leq T$ . Indeed, by Proposition A.2, we have  $\mathrm{rwl}_{1,f}^{(t)} \equiv \mathrm{rwl}_{1,id}^{(t)} 
$$\begin{split} \operatorname{rwl}_{1,f}^{(f(t-1))}(u) &= \operatorname{rwl}_{1,f}^{(f(t-1))}(v) \\ \{\!\!\{ (\operatorname{rwl}_{1,f}^{(t-1)}(w), r) \mid w \in \mathcal{N}_r(u), r \in R \}\!\!\} &= \{\!\!\{ (\operatorname{rwl}_{1,f}^{(t-1)}(w), r) \mid w \in \mathcal{N}_r(v), r \in R \}\!\!\}. \end{split}$$

By inductive hypothesis we have (recall  $f(t-1) \le t-1$ ):

$$m{h}_u^{(f(t-1))} = m{h}_v^{(f(t-1))}$$
  $\{\!\!\{m{h}_w^{(t-1)} \mid w \in \mathcal{N}_r(u)\}\!\!\} = \{\!\!\{m{h}_w^{(t-1)} \mid w \in \mathcal{N}_r(v)\}\!\!\}$  for each  $r \in R$ .

This implies that  $\{\theta_r(\boldsymbol{h}_w^{(t-1)}) \mid w \in \mathcal{N}_r(u)\} = \{\theta_r(\boldsymbol{h}_w^{(t-1)}) \mid w \in \mathcal{N}_r(v)\}$ , for each  $r \in R$ , and hence:

$$\{\!\!\{\theta_r(\boldsymbol{h}_w^{(t-1)}) \mid w \in \mathcal{N}_r(u), r \in R\}\!\!\} = \{\!\!\{\theta_r(\boldsymbol{h}_w^{(t-1)}) \mid w \in \mathcal{N}_r(v), r \in R\}\!\!\}$$

We conclude that

$$\begin{aligned} \boldsymbol{h}_{u}^{(t)} &= \phi(\boldsymbol{h}_{u}^{(f(t-1))}, \psi(\{\{\theta_{r}(\boldsymbol{h}_{w}^{(t-1)}) \mid w \in \mathcal{N}_{r}(u), r \in R\}\}) \\ &= \phi(\boldsymbol{h}_{v}^{(f(t-1))}, \psi(\{\{\theta_{r}(\boldsymbol{h}_{w}^{(t-1)}) \mid w \in \mathcal{N}_{r}(v), r \in R\}\}) \\ &= \boldsymbol{h}_{v}^{(t)}. \end{aligned}$$

For item (2), we refine the proof of Theorem 2 from [8], which is based on ideas from [5]. In comparison with [8], in our case, we have arbitrary adjacency matrices for each relation type, not only symmetric ones, and arbitrary history functions, not only the identity. However, the arguments still apply. Moreover, the most important difference is that here we aim for a model of R-MPNN that uses a single parameter matrix, instead of two parameter matrices as in [8] (one for self-representations and the other for neighbors representations). This makes the simulation of  $rwl_1$  more challenging.

We use models of R-MPNNs of the following form:

$$\boldsymbol{h}_{v}^{(t+1)} = \operatorname{sign}\Big(\boldsymbol{W}^{(t)}\big(\boldsymbol{h}_{v}^{(f(t))} + \sum_{r \in R} \sum_{w \in \mathcal{N}_{r}(v)} \alpha_{r} \boldsymbol{h}_{w}^{(t)}\big) - \boldsymbol{b}\Big),$$

where  $W^{(t)}$  is a parameter matrix and b is the bias term (we shall use the all-ones vector b = 1). As message function  $\theta_r$  we use *vector scaling*, that is,  $\theta_r(h) = \alpha_r h$ , where  $\alpha_r$  is a parameter of the model. For the non-linearity, we use the sign function sign. We note that the proof also works for the ReLU function, following arguments from Corollary 16 in [5].

For a matrix B, we denote by  $B_i$  its i-th column. Let n = |V| and without loss of generality assume  $V = \{1, \ldots, n\}$ . We will write features maps  $h: V \to \mathbb{R}^d$  for G = (V, E, R, c) also as matrices  $H \in \mathbb{R}^{d \times n}$ , where the column  $H_v$  corresponds to the d-dimensional feature vector for v. Then we can also write our R-MPNN model in matrix form:

$$\boldsymbol{H}^{(t+1)} = \operatorname{sign}\left(\boldsymbol{W}^{(t)}\left(\boldsymbol{H}^{(f(t))} + \sum_{r \in R} \alpha_r \boldsymbol{H}^{(t)} \boldsymbol{A}_r\right) - \boldsymbol{J}\right),$$

where  $A_r$  is the adjacency matrix of G for relation type  $r \in R$  and J is the all-ones matrix of appropriate dimensions. Let Fts be the following  $n \times n$  matrix:

$$Fts = \begin{bmatrix} -1 & -1 & \cdots & -1 & -1 \\ 1 & -1 & \ddots & & -1 \\ \vdots & \ddots & \ddots & \ddots & \vdots \\ 1 & & \ddots & -1 & -1 \\ 1 & 1 & \cdots & 1 & -1 \end{bmatrix}$$

That is,  $(Fts)_{ij} = -1$  if  $j \ge i$ , and  $(Fts)_{ij} = 1$  otherwise. Note that the columns of Fts are linearly independent. We shall use the columns of Fts as node features in our simulation.

The following lemma is an adaptation of Lemma 9 from [5].

**Lemma A.3.** Let  $B \in \mathbb{N}^{n \times p}$  be a matrix such that  $p \leq n$ , and all the columns are pairwise distinct and different from the all-zeros column. Then there is a matrix  $X \in \mathbb{R}^{n \times n}$  such that the matrix  $\operatorname{sign}(XB - J) \in \{-1, 1\}^{n \times p}$  is precisely the sub-matrix of Fts given by its first p columns.

*Proof.* Let  $z=(1,m,m^2,\ldots,m^{n-1})\in\mathbb{N}^{1\times n}$ , where m is the largest entry in B, and  $b=zB\in\mathbb{N}^{1\times p}$ . By construction, the entries of b are positive and pairwise distinct. Without loss of generality, we assume that  $b=(b_1,b_2,\ldots,b_p)$  for  $b_1>b_2>\cdots>b_p>0$ . As the  $b_i$  are ordered, we can choose numbers  $x_1,\ldots,x_p\in\mathbb{R}$  such that  $b_i\cdot x_j<1$  if  $i\geq j$ , and  $b_i\cdot x_j>1$  if i< j, for all  $i,j\in\{1,\ldots,p\}$ . Let  $x=(x_1,\ldots,x_p,2/b_p,\ldots,2/b_p)^T\in\mathbb{R}^{n\times 1}$ . Note that  $(2/b_p)\cdot b_i>1$ , for all  $i\in\{1,\ldots,p\}$ . Then  $\mathrm{sign}(xb-J)$  is precisely the sub-matrix of Fts given by its first p columns. We can choose  $X=xz\in\mathbb{R}^{n\times n}$ . □

Now we are ready to show item (2). Let f be any history function and  $T \geq 0$ . It suffices to show that there is a feature map  $\boldsymbol{x}$  with  $c \equiv \boldsymbol{x}$  and an R-MPNN with T layers and history function f such that  $\operatorname{rwl}_{1,f}^{(t)} \equiv \boldsymbol{h}^{(t)}$ , for all  $0 \leq t \leq T$ . Indeed, by Proposition A.2, we have  $\operatorname{rwl}_{1,f}^{(t)} \equiv \operatorname{rwl}_{1,id}^{(t)} \equiv \operatorname{rwl}_{1}^{(t)}$ , where id is the identity function id(t) = t, and then the result follows. We conclude item (2) by showing the following lemma:

**Lemma A.4.** There is a feature map  $\mathbf{h}^{(0)}: V \to \mathbb{R}^n$ , and for all  $0 \le t < T$ , there is a feature map  $\mathbf{h}^{(t+1)}: V \to \mathbb{R}^n$ , a matrix  $\mathbf{W}^{(t)} \in \mathbb{R}^{n \times n}$  and scaling factors  $\alpha_r^{(t)} \in \mathbb{R}$ , for each  $r \in R$ , such that:

- $\boldsymbol{h}^{(t)} \equiv \text{rwl}_{1,f}^{(t)}$ .
- The columns of  $H^{(t)} \in \mathbb{R}^{n \times n}$  are columns of Fts (recall  $H^{(t)}$  is the matrix representation of  $h^{(t)}$ ).
- $\boldsymbol{H}^{(t+1)} = \operatorname{sign}\left(\boldsymbol{W}^{(t)}\left(\boldsymbol{H}^{(f(t))} + \sum_{r \in R} \alpha_r^{(t)} \boldsymbol{H}^{(t)} \boldsymbol{A}_r\right) \boldsymbol{J}\right)$ .

*Proof.* We proceed by induction on t. Suppose that the node coloring  $\mathrm{rwl}_{1,f}^{(0)} \equiv c$  uses colors  $1,\ldots,p$ , for  $p \leq n$ . Then we choose  $\boldsymbol{h}^{(0)}$  (this is the initial feature map  $\boldsymbol{x}$  in the statement of item (2)) such that  $\boldsymbol{h}_v^{(0)} = \boldsymbol{Fts}_{c(v)}$ , that is,  $\boldsymbol{h}_v^{(0)}$  is the c(v)-th column of  $\boldsymbol{Fts}$ . We have that  $\boldsymbol{h}^{(0)}$  satisfies the required conditions.

For the inductive case, assume that  $\boldsymbol{h}^{(t')} \equiv \operatorname{rwl}_{1,f}^{(t')}$  and the columns of  $\boldsymbol{H}^{(t')}$  are columns of  $\boldsymbol{Fts}$ , for all  $0 \leq t' \leq t < T$ . We need to find  $\boldsymbol{h}^{(t+1)}$ ,  $\boldsymbol{W}^{(t)}$  and  $\alpha_r^{(t)}$  satisfying the conditions. Let  $\boldsymbol{M} \in \mathbb{R}^{n \times n}$  be the matrix inverse of  $\boldsymbol{Fts}$ . If  $\boldsymbol{H}_v^{(t')}$  is the i-th column of  $\boldsymbol{Fts}$ , we say that v has color i at iteration t'. Observe that for all  $0 \leq t' \leq t$ , we have

$$(\boldsymbol{M}\boldsymbol{H}^{(t')})_{iv} = \begin{cases} 1 & \text{if } v \text{ has color } i \text{ at iteration } t' \\ 0 & \text{otherwise.} \end{cases}$$

In other words, the v-th column of  $MH^{(t')}$  is simply a one-hot encoding of the color of v at iteration t'. For each  $r \in R$  we have

$$(\boldsymbol{M}\boldsymbol{H}^{(t)}\boldsymbol{A}_r)_{iv} = |\{w \in \mathcal{N}_r(v) \mid w \text{ has color } i \text{ at iteration } t\}|.$$

Hence the v-th column of  $MH^{(t)}A_r$  is an encoding of the multiset of colors for the neighborhood  $\mathcal{N}_r(v)$ , at iteration t. Let  $r_1,\ldots,r_m$  be an enumeration of the relation types in R. Let  $D\in\mathbb{R}^{(m+1)n\times n}$  be the matrix obtained by horizontally concatenating the matrices  $MH^{(f(t))}$ ,  $MH^{(t)}A_{r_1},\ldots,MH^{(t)}A_{r_m}$ . Since  $H^{(f(t))}\equiv \mathrm{rwl}_{1,f}^{(f(t))}$  and  $H^{(t)}\equiv \mathrm{rwl}_{1,f}^{(t)}$ , we have that  $D\equiv \mathrm{rwl}_{1,f}^{(t+1)}$ . Now note that  $D\equiv E$ , where

$$E = MH^{(f(t))} + \sum_{i=1}^{m} (n+1)^{i} MH^{(t)} A_{r_{i}}.$$

Indeed,  $E_{iv}$  is simply the (n+1)-base representation of the vector  $(D_{iv}, D_{(n+i)v}, D_{(2n+i)v}, \dots, D_{(mn+i)v})$ , and hence  $E_u = E_v$  if and only if  $D_u = D_v$  (note that the entries of D are in  $\{0, \dots, n\}$ ). In particular,  $E \equiv \mathsf{rwl}_{1,f}^{(t+1)}$ .

Let p be the number of distinct columns of E and let  $\widetilde{E} \in \mathbb{N}^{n \times p}$  be the matrix whose columns are the distinct columns of E in an arbitrary but fixed order. We can apply Lemma A.3 to  $\widetilde{E}$  and obtain a matrix  $X \in \mathbb{R}^{n \times n}$  such that  $\operatorname{sign}(X\widetilde{E}-J)$  is precisely the sub-matrix of Fts given by its first p columns. We choose  $H^{(t+1)} = \operatorname{sign}(XE-J) \in \mathbb{R}^{n \times n}$ ,  $W^{(t)} = XM \in \mathbb{R}^{n \times n}$  and  $\alpha_{r_i}^{(t)} = (n+1)^i$ . Note that the columns of  $H^{(t+1)}$  are columns of  $H^{(t+1)}$  are columns of  $H^{(t+1)}$ . Finally, we have

$$\begin{split} \boldsymbol{H}^{(t+1)} &= \operatorname{sign}(\boldsymbol{X}\boldsymbol{E} - \boldsymbol{J}) \\ &= \operatorname{sign}(\boldsymbol{X} \big( \boldsymbol{M} \boldsymbol{H}^{(f(t))} + \sum_{i=1}^{m} (n+1)^{i} \boldsymbol{M} \boldsymbol{H}^{(t)} \boldsymbol{A}_{r_{i}} \big) - \boldsymbol{J}) \\ &= \operatorname{sign}(\boldsymbol{W}^{(t)} \big( \boldsymbol{H}^{(f(t))} + \sum_{i=1}^{m} \alpha_{r_{i}}^{(t)} \boldsymbol{H}^{(t)} \boldsymbol{A}_{r_{i}} \big) - \boldsymbol{J}). \end{split}$$

Note that our result applies to more complex message functions such as  $\theta_r(h) = h * b_r$ , where \* stands for element-wise multiplication and  $b_r$  is a vector parameter, and  $\theta_r(h) = W_r h$ , where  $W_r$  is matrix parameter, as they can easily express vector scaling. The first case has been used for the model CompGCN [7], while the second case has been used for R-GCN [6].

#### A.2 Proof of Theorem 5.1

We recall the statement of the theorem:

**Theorem 5.1.** Let  $G = (V, E, R, x, \eta)$  be a knowledge graph, where x is a feature map, and  $\eta$  is a pairwise coloring satisfying target node distinguishability. Let  $q \in R$  be any query relation. Then:

- 1. For all C-MPNNs with T layers and initialization  $\delta$  satisfying  $\delta \equiv \eta$ , and all  $0 \le t \le T$ , we have  $\mathsf{rawl}_2^{(t)} \le h_q^{(t)}$ .
- 2. For all  $T \ge 0$  and history function f, there is an C-MPNN with T layers and history function f such that for all  $0 \le t \le T$ , we have  $\text{rawl}_2^{(t)} \equiv \boldsymbol{h}_q^{(t)}$ .

We prove the theorem via a reduction to R-MPNNs and the relational local 1-WL. Before doing so we need some auxiliary results.

Let  $G=(V,E,R,c,\eta)$  be a knowledge graph where  $\eta$  is a pairwise coloring. We denote by  $G^2$  the knowledge graph  $G^2=(V\times V,E',R,c_\eta)$  where  $E'=\{r((u,w),(u,v))\mid r(w,v)\in E,r\in R\}$  and  $c_\eta$  is the node coloring  $c_\eta((u,v))=\eta(u,v)$ . Note that the coloring c is irrelevant in the construction. Intuitively,  $G^2$  encodes the adjacency relation between pairs of nodes of G used in C-MPNNs. We stress that G and  $G^2$  have the same relation type set R. If  $\mathcal A$  is a C-MPNN and  $\mathcal B$  is an R-MPNN, we write  $\mathbf h_{\mathcal A,G}^{(t)}(u,v):=\mathbf h_q^{(t)}(u,v)$  and  $\mathbf h_{\mathcal B,G^2}^{(t)}((u,v)):=\mathbf h^{(t)}((u,v))$  for the features computed by  $\mathcal A$  and  $\mathcal B$  over G and  $G^2$ , respectively. We sometimes write  $\mathcal N_r^H(v)$  to emphasize that the neighborhood is taken over the knowledge graph H. Finally, we say that an initial feature map  $\mathbf y$  for  $G^2$  satisfies target node distinguishability if  $\mathbf y((u,u))\neq \mathbf y((u,v))$  for all  $u\neq v$ .

We have the following equivalence between C-MPNNs and R-MPNNs:

**Proposition A.5.** Let  $G = (V, E, R, x, \eta)^6$  be a knowledge graph where x is a feature map, and  $\eta$  is a pairwise coloring. Let  $q \in R$  be any query relation. Then:

- 1. For every C-MPNN  $\mathcal A$  with T layers, there is an initial feature map  $\mathbf y$  for  $G^2$  an R-MPNN  $\mathcal B$  with T layers such that for all  $0 \le t \le T$  and  $u, v \in V$ , we have  $\mathbf h^{(t)}_{\mathcal A, G}(u, v) = \mathbf h^{(t)}_{\mathcal B, G^2}((u, v))$ .
- 2. For every initial feature map  $\mathbf{y}$  for  $G^2$  satisfying target node distinguishability and every R-MPNN  $\mathcal{B}$  with T layers, there is a C-MPNN  $\mathcal{A}$  with T layers such that for all  $0 \le t \le T$  and  $u, v \in V$ , we have  $\mathbf{h}_{\mathcal{A},G}^{(t)}(u,v) = \mathbf{h}_{\mathcal{B},G^2}^{(t)}((u,v))$ .

<sup>&</sup>lt;sup>6</sup>The pairwise coloring  $\eta$  does not play any role in the proposition.

*Proof.* We start with item (1). The sought R-MPNN  $\mathcal{B}$  has the same history function and the same message, aggregation, and update functions as  $\mathcal{A}$  for all the T layers. The initial feature map  $\boldsymbol{y}$  is defined as  $\boldsymbol{y}((u,v)) = \delta(u,v,q)$ , where  $\delta$  is the initialization function of  $\mathcal{A}$ .

We show the equivalence by induction on t. For t=0, we have  $\boldsymbol{h}_{\mathcal{A}}^{(0)}(u,v)=\delta(u,v,q)=\boldsymbol{y}((u,v))=\boldsymbol{h}_{\mathcal{B}}^{(0)}((u,v)).$  For the inductive case, take  $u,v\in V$ . We have

$$\begin{aligned} \boldsymbol{h}_{\mathcal{A}}^{(t+1)}(u,v) &= \phi \big( \boldsymbol{h}_{\mathcal{A}}^{(f(t))}(u,v), \psi \big( \{ \theta_r(\boldsymbol{h}_{\mathcal{A}}^{(t)}(u,w),q) | \ w \in \mathcal{N}_r^G(v), r \in R \} \big) \big) \\ &= \phi \big( \boldsymbol{h}_{\mathcal{B}}^{(f(t))}((u,v)), \psi \big( \{ \theta_r(\boldsymbol{h}_{\mathcal{B}}^{(t)}((u,w)),q) | \ (u,w) \in \mathcal{N}_r^{G^2}((u,v)), r \in R \} \big) \big) \\ &= \boldsymbol{h}_{\mathcal{B}}^{(t+1)}((u,v)). \end{aligned}$$

For item (2), we take  $\mathcal{A}$  to have the same history function and the same message, aggregation, and update functions than  $\mathcal{B}$ , for all the T layers, and initialization function  $\delta$  such that  $\delta(u,v,q)=\boldsymbol{y}((u,v))$ . The argument for the equivalence is the same as item (1).

Regarding WL algorithms, we have a similar equivalence:

**Proposition A.6.** Let  $G = (V, E, R, c, \eta)$  be a knowledge graph where  $\eta$  is a pairwise coloring. For all  $t \geq 0$  and  $u, v \in V$ , we have that  $\operatorname{rawl}_2^{(t)}(u, v)$  computed over G coincides with  $\operatorname{rwl}_1^{(t)}((u, v))$  computed over  $G^2 = (V \times V, E', R, c_{\eta})$ .

$$\begin{split} \textit{Proof.} \ \ &\text{For} \ t=0, \ \text{we have} \ \text{rawl}_2^{(0)}(u,v) = \eta(u,v) = c_{\eta}((u,v)) = \text{rwl}_1^{(0)}((u,v)). \ \text{For the inductive case, we have} \\ &\text{rawl}_2^{(t+1)}(u,v) = \tau \big( \text{rawl}_2^{(t)}(u,v), \{\!\!\{ (\text{rawl}_2^{(t)}(u,w),r) \mid w \in \mathcal{N}_r^G(v), r \in R ) \}\!\!\} \big) \\ &= \tau \big( \text{rwl}_1^{(t)}((u,v)), \{\!\!\{ (\text{rwl}_1^{(t)}((u,w)),r) \mid (u,w) \in \mathcal{N}_r^{G^2}((u,v)), r \in R ) \}\!\!\} \big) \\ &= \text{rwl}_1^{(t+1)}((u,v)). \end{split}$$

Now we are ready to prove the theorem.

For  $G=(V,E,R,\boldsymbol{x},\eta)$ , we consider  $G^2=(V\times V,E',R,c_\eta)$ . We start with item (1). Let  $\mathcal A$  be a C-MPNN with T layers and initialization  $\delta$  satisfying  $\delta\equiv\eta$  and let  $0\leq t\leq T$ . Let  $\boldsymbol{y}$  be an initial feature map for  $G^2$  and  $\mathcal B$  be an R-MPNN with T layers as in Proposition A.5, item (1). Note that  $\boldsymbol{y}\equiv c_\eta$  as  $\boldsymbol{y}((u,v))=\delta(u,v,q)$ . We can apply Theorem 3.1, item (1) to  $G^2$ ,  $\boldsymbol{y}$  and  $\mathcal B$  and conclude that  $\mathrm{rwl}_1^{(t)}\preceq \boldsymbol{h}_{\mathcal B,G^2}^{(t)}$ . This implies that  $\mathrm{rawl}_1^{(t)}\preceq \boldsymbol{h}_{\mathcal A,G}^{(t)}$ .

For item (2), let  $T\geq 0$  and f be a history function. We can apply Theorem 3.1, item (2), to  $G^2$  to obtain a initial feature map  ${\boldsymbol y}$  with  ${\boldsymbol y}\equiv c_\eta$  and an R-MPNN  ${\mathcal B}$  with T layers and history function f such that for all  $0\leq t\leq T$ , we have  ${\rm rwl}_1^{(t)}\equiv {\boldsymbol h}_{{\mathcal B},G^2}^{(t)}$ . Note that  ${\boldsymbol y}$  satisfies target node distinguishability since  $\eta$  does. Let  ${\mathcal A}$  be the C-MPNN obtained from Proposition A.5, item (2). We have that  ${\rm rawl}_2^{(t)}\equiv {\boldsymbol h}_{{\mathcal A},G}^{(t)}$  as required.

*Remark* A.7. Note that item (2) holds for the basic model of C-MPNNs presented in Section 4.1, with the three proposed message functions  $\theta_r^1, \theta_r^2, \theta_r^3$ , as they can express vector scaling.

#### A.3 Proof of Theorem 5.2

We recall the statement of the theorem:

**Theorem 5.2.** A logical binary classifier is captured by C-MPNNs if and only if it can be expressed in rGFO<sub>cnt</sub><sup>3</sup>.

The proof is a reduction to the one-dimensional case, that is, R-MPNNs and the so-called *graded modal logic*. So in order to show Theorem 5.2 we need some definitions and auxiliary results.

Fix a set of relation types R and a set of node colors C. We consider knowledge graphs of the form G = (V, E, R, c) where c is a node coloring assigning colors from C. In this context, logical formulas can refer to relation types from R and node colors from C. Following [22], a logical (node) classifier is a unary formula expressible in first-order logic (FO), classifying each node u on a knowledge graph G according to whether the formula holds or not for u over G.

We define a fragment  ${\sf rGFO}^2_{\rm cnt}$  of FO as follows. A  ${\sf rGFO}^2_{\rm cnt}$  formula is either a(x) for  $a \in \mathcal{C}$ , or one of the following, where  $\varphi$  and  $\psi$  are  ${\sf rGFO}^2_{\rm cnt}$  formulas,  $N \geq 1$  is a positive integer and  $r \in R$ :

$$\neg \varphi(x), \quad \varphi(x) \wedge \psi(x), \quad \exists^{\geq N} y \, (\varphi(y) \wedge r(y,x)).$$

We remark that  $rGFO_{cnt}^2$  is actually the fragment of FO used in [22] to characterize GNNs, which is well-known to be equivalent to *graded modal logic* [32] as also exploited in [22].

The following proposition provides useful translations from graded modal logic to  ${\rm rGFO}_{\rm cnt}^3$  and vice versa. Recall from Section A.2, that given a knowledge graph  $G=(V,E,R,\eta)$  where  $\eta$  is a pairwise coloring, we define the knowledge graph  $G^2=(V\times V,E',R,c_\eta)$  where  $E'=\{r((u,w),(u,v))\mid r(w,v)\in E,r\in R\}$  and  $c_\eta$  is the node coloring  $c_\eta((u,v))=\eta(u,v)$ .

# **Proposition A.8.** We have the following:

- 1. For all  ${\sf rGFO}^3_{\sf cnt}$  formula  $\varphi(x,y)$ , there is a graded modal logic formula  $\tilde{\varphi}(x)$  such that for all knowledge graph  $G=(V,E,R,\eta)$ , we have  $G,u,v\models\varphi$  if and only if  $G^2,(u,v)\models\tilde{\varphi}$ .
- 2. For all graded modal logic formula  $\varphi(x)$ , there is a  $\mathsf{rGFO}^3_{\mathrm{ent}}$  formula  $\tilde{\varphi}(x,y)$  such that for all knowledge graph  $G = (V, E, R, \eta)$ , we have  $G, u, v \models \tilde{\varphi}$  if and only if  $G^2, (u, v) \models \varphi$ .

*Proof.* We start with item (1). We define  $\tilde{\varphi}(x)$  by induction on the formula  $\varphi(x,y)$ :

- 1. If  $\varphi(x,y) = a(x,y)$  for color a, then  $\tilde{\varphi}(x) = a(x)$ .
- 2. If  $\varphi(x,y) = \neg \psi(x,y)$ , then  $\tilde{\varphi}(x) = \neg \tilde{\psi}(x)$ .
- 3. If  $\varphi(x,y) = \varphi_1(x,y) \wedge \varphi_2(x,y)$ , then  $\tilde{\varphi}(x) = \tilde{\varphi}_1(x) \wedge \tilde{\varphi}_2(x)$ .
- $\text{4. If } \varphi(x,y) = \exists^{\geq N} z \, (\psi(x,z) \wedge r(z,y)) \text{ then } \tilde{\varphi}(x) = \exists^{\geq N} y \, (\tilde{\psi}(y) \wedge r(y,x)).$

Fix  $G = (V, E, R, \eta)$  and  $G^2 = (V \times V, E', R, c_{\eta})$ . We show by induction on the formula  $\varphi$  that  $G, u, v \models \varphi$  if and only if  $G^2$ ,  $(u, v) \models \tilde{\varphi}$ .

For the base case, that is, case (1) above, we have that  $\varphi(x,y) = a(x,y)$  and hence  $G, u, v \models \varphi$  iff  $\eta(u,v) = a$  iff  $c_{\eta}(u,v) \models a$  iff  $G^{2}, (u,v) \models \tilde{\varphi}$ .

Now we consider the inductive case. For case (2) above, we have  $\varphi(x,y) = \neg \psi(x,y)$ . Then  $G,u,v \models \varphi$  iff  $G,u,v \not\models \psi$  iff  $G^2,(u,v) \not\models \tilde{\psi}$  iff  $G^2,(u,v) \models \tilde{\varphi}$ .

For case (3), we have  $\varphi(x,y)=\varphi_1(x,y)\wedge\varphi_2(x,y)$ . Then  $G,u,v\models\varphi$  iff  $G,u,v\models\varphi_1$  and  $G,u,v\models\varphi_2$  iff  $G^2,(u,v)\models\tilde{\varphi_1}$  and  $G^2,(u,v)\models\tilde{\varphi_2}$  iff  $G^2,(u,v)\models\tilde{\varphi_2}$ .

Finally, for case (4), we have  $\varphi(x,y)=\exists^{\geq N}z\,(\psi(x,z)\wedge r(z,y)).$  Assume  $G,u,v\models\varphi$ , then there exist at least N nodes  $w\in V$  such that  $G,u,w\models\psi$  and  $r(w,v)\in E.$  By the definition of  $G^2$ , there exist at least N nodes in  $G^2$  of the form (u,w) such that  $G^2,(u,w)\models\tilde{\psi}$  and  $r((u,w),(u,v))\in E'.$  It follows that  $G^2,(u,v)\models\tilde{\varphi}.$  On the other hand, suppose  $G^2,(u,v)\models\tilde{\varphi}.$  Then there exist at least N nodes (o,o') in  $G^2$  such that  $G,(o,o')\models\tilde{\psi}$  and  $r((o,o'),(u,v))\in E'.$  By definition of  $G^2$  each (o,o') must be of the form (o,o')=(u,w) for some  $w\in V$  such that r(w,v). Then there are at least N nodes  $w\in V$  such that  $G,u,w\models\psi$  and  $F(u,v)\in E$ . It follows that  $F(u,v)\in E$ .

Item (2) is similar. We define  $\tilde{\varphi}(x,y)$  by induction on the formula  $\varphi(x)$ :

- 1. If  $\varphi(x) = a(x)$  for color a, then  $\tilde{\varphi}(x, y) = a(x, y)$ .
- 2. If  $\varphi(x) = \neg \psi(x)$ , then  $\tilde{\varphi}(x, y) = \neg \tilde{\psi}(x, y)$ .
- 3. If  $\varphi(x) = \varphi_1(x) \wedge \varphi_2(x)$ , then  $\tilde{\varphi}(x,y) = \tilde{\varphi}_1(x,y) \wedge \tilde{\varphi}_2(x,y)$ .
- $\text{4. If } \varphi(x) = \exists^{\geq N} y \, (\psi(y) \wedge r(y,x)) \text{ then } \tilde{\varphi}(x,y) = \exists^{\geq N} z \, (\tilde{\psi}(x,z) \wedge r(z,y)).$

Following the same inductive argument from item (1), we obtain that  $G, u, v \models \tilde{\varphi}$  if and only if  $G^2, (u, v) \models \varphi$ .  $\square$ 

The following theorem is an adaptation of Theorem 4.2 from [22]. The main difference with [22] is that here we need to handle multiple relation types.

**Theorem A.9.** A logical classifier is captured by R-MPNNs if and only if it can be expressed in graded modal logic.

*Proof.* We start with the backward direction. Let  $\varphi(x)$  be a graded modal logic formula for relation types R and node colors  $\mathcal{C}$ . Let  $\varphi_1,\ldots,\varphi_L$  be an enumeration of the subformulas of  $\varphi$  such that if  $\varphi_i$  is a subformula of  $\varphi_j$ , then  $i\leq j$ . In particular,  $\varphi_L=\varphi$ . We shall define an R-MPNN  $\mathcal{B}_\varphi$  with L layers computing L-dimensional features in each layer. The idea is that at layer  $\ell\in\{1,\ldots,L\}$ , the  $\ell$ -th component of the feature  $\mathbf{h}_v^{(\ell)}$  is computed correctly and corresponds to 1 if  $\varphi_\ell$  is satisfied in node v, and 0 otherwise. We add an additional final layer that simply outputs the last component of the feature vector.

We use models of R-MPNNs of the following form:

$$\boldsymbol{h}_{v}^{(t+1)} = \sigma \Big( \boldsymbol{W} \boldsymbol{h}_{v}^{(t)} + \sum_{r \in R} \sum_{w \in \mathcal{N}_{r}(v)} \boldsymbol{W}_{r} \boldsymbol{h}_{w}^{(t)} + \boldsymbol{b} \Big),$$

where  $\boldsymbol{W} \in \mathbb{R}^{L \times L}$  is a parameter matrix and  $\boldsymbol{b} \in \mathbb{R}^L$  is the bias term. As message function  $\theta_r$  we use  $\theta_r(\boldsymbol{h}) = \boldsymbol{W}_r \boldsymbol{h}$ , where  $\boldsymbol{W}_r \in \mathbb{R}^{L \times L}$  is a parameter matrix. For the non-linearity  $\sigma$  we use the truncated ReLU function  $\sigma(x) = \min(\max(0, x), 1)$ . The  $\ell$ -th row of  $\boldsymbol{W}$  and  $\boldsymbol{W}_r$ , and the  $\ell$ -th entry of  $\boldsymbol{b}$  are defined as follows (omitted entries are 0):

- 1. If  $\varphi_{\ell}(x) = a(x)$  for a color  $a \in \mathcal{C}$ , then  $\mathbf{W}_{\ell\ell} = 1$ .
- 2. If  $\varphi_{\ell}(x) = \neg \varphi_k(x)$  then  $\mathbf{W}_{\ell k} = -1$ , and  $b_{\ell} = 1$ .
- 3. If  $\varphi_{\ell}(x) = \varphi_{j}(x) \wedge \varphi_{k}(x)$  then  $\mathbf{W}_{\ell j} = 1$ ,  $\mathbf{W}_{\ell k} = 1$  and  $b_{\ell} = -1$ .
- 4. If  $\varphi_{\ell}(x) = \exists^{\geq N} y (\varphi_k(y) \wedge r(y, x))$  then  $(\mathbf{W}_r)_{\ell k} = 1$  and  $b_{\ell} = -N + 1$ .

Let G=(V,E,R,c) be a knowledge graph with node colors from  $\mathcal{C}$ . In order to apply  $\mathcal{B}_{\varphi}$  to G, we choose initial features  $\mathbf{h}_v^{(0)}$  such that  $(\mathbf{h}_v^{(0)})_i=1$  if  $\varphi_i$  is the color of v, that is, the formula a(x) for a=c(v), and  $(\mathbf{h}_v^{(0)})_i=0$  otherwise. In other words, the L-dimensional initial feature  $\mathbf{h}_v^{(0)}$  is a one-hot encoding of the color of v. It follows from the same arguments than Proposition 4.1 in [22] that for all  $\ell\in\{1,\ldots,L\}$  we have  $(\mathbf{h}_v^{(t)})_\ell=1$  if  $G,v\models\varphi_\ell$  and  $(\mathbf{h}_v^{(t)})_\ell=0$  otherwise, for all  $v\in V$  and  $t\in\{\ell,\ldots,L\}$ . In particular, after L layers,  $\mathcal{B}_{\varphi}$  calculates  $\mathbf{h}_v^{(L)}$  such that  $(\mathbf{h}_v^{(L)})_L=1$  if  $G,v\models\varphi$  and  $(\mathbf{h}_v^{(L)})_L=0$  otherwise. As layer L+1 extracts the L-th component of the feature vector, the result follows.

For the forward direction, we follow the strategy of Theorem 4.2 from [22]. Given a knowledge graph G = (V, E, R, c) and a number  $L \in \mathbb{N}$ , we define the *unravelling* of  $v \in V$  at depth L, denoted  $\mathsf{Unr}_G^L(v)$  is the knowledge graph having:

- A node  $(v, u_1, \dots, u_i)$  for each directed path  $u_i, \dots, u_1, v$  in G of length  $i \leq L$ .
- For each  $r \in R$ , a fact  $r((v, u_1, \dots, u_i), (v, u_1, \dots, u_{i-1}))$  for all facts  $r(u_i, u_{i-1}) \in E$  (here  $u_0 := v$ ).
- Each node  $(v, u_1, \ldots, u_i)$  is colored with  $c(u_i)$ , that is, the same color as  $u_i$ .

Note that the notion of directed path is defined in the obvious way, as for directed graphs but ignoring relation types. Note also that  $\mathsf{Unr}_G^L(v)$  is a tree in the sense that the underlying undirected graph is a tree.

The following proposition is a trivial adaptation of Observation C.3 from [22]. We write  $\operatorname{Unr}_G^L(v) \simeq \operatorname{Unr}_{G'}^L(v')$  if there exists an isomorphism f from  $\operatorname{Unr}_G^L(v)$  to  $\operatorname{Unr}_{G'}^L(v')$  such that f(v) = v'.

**Proposition A.10.** Let G and G' be two knowledge graphs and v and v' be nodes in G and G', respectively. Then, for all  $L \in \mathbb{N}$ , we have that  $\operatorname{rwl}_1^{(L)}(v)$  on G coincides with  $\operatorname{rwl}_1^{(L)}(v')$  on G' if and only if  $\operatorname{Unr}_G^L(v) \simeq \operatorname{Unr}_{G'}^L(v')$ .

As a consequence of Theorem 3.1, we obtain:

**Proposition A.11.** Let G and G' be two knowledge graphs and v and v' be nodes in G and G', respectively, such that  $\operatorname{Unr}_{G}^{L}(v) \simeq \operatorname{Unr}_{G'}^{L}(v')$  for all  $L \in \mathbb{N}$ . Then for any R-MPNN with T layers, we have that  $h_{v}^{(T)}$  on G coincides with  $h_{v'}^{(T)}$  on G'.

Finally, the following theorem follows from Theorem C.5 in [22], which in turn follows from Theorem 2.2 in [33]. The key observation here is that the results from [33] are actually presented for multi-modal logics, that is, multiple relation types.

**Theorem A.12.** [33] Let  $\alpha$  be a unary FO formula over knowledge graphs. If  $\alpha$  is not equivalent to a graded modal logic formula, then there exist two knowledge graphs G and G', and two nodes v in G and v' in G' such that  $\operatorname{Unr}_{G'}^L(v) \simeq \operatorname{Unr}_{G'}^L(v')$  for all  $L \in \mathbb{N}$  and such that  $G, v \models \alpha$  but  $G', v' \not\models \alpha$ .

Now we are ready to obtain the forward direction of the theorem. Suppose that a logical classifier  $\alpha$  is capture by an R-MPNN  $\mathcal B$  with T layers, and assume by contradiction that  $\alpha$  is not equivalent to a graded modal logic formula. Then we can apply Theorem A.12 and obtain two knowledge graphs G and G', and two nodes v in G and v' in G' such that  $\operatorname{Unr}_G^L(v) \simeq \operatorname{Unr}_{G'}^L(v')$  for all  $L \in \mathbb N$  and such that  $G, v \models \alpha$  but  $G', v' \not\models \alpha$ . Applying Proposition A.11, we have that  $h_v^{(T)}$  on G coincides with  $h_{v'}^{(T)}$  on G', and hence  $\mathcal B$  classifies either both v and v' as true over G and G', respectively, or both as false. This is a contradiction.

Now Theorem 5.2 follows easily. Let  $\alpha$  be a logical binary classifier and suppose it is capture by a C-MPNN  $\mathcal{A}$ . By Proposition A.5,item (1), we know that  $\mathcal{A}$  can be simulated by a R-MPNN  $\mathcal{B}$  over  $G^2$ . In turn, we can apply Theorem A.9 and obtain a formula  $\varphi$  in graded modal logic equivalent to  $\mathcal{B}$ . Finally, we can apply the translation in Proposition A.8, item (2), and obtain corresponding formula  $\tilde{\varphi}$  in rGFO $_{\mathrm{cnt}}^2$ . We claim that  $\tilde{\varphi}$  captures  $\mathcal{A}$ . Let G be a knowledge graph and u,v two nodes. We have that  $G,u,v\models\tilde{\varphi}$  iff  $G^2,(u,v)\models\varphi$  iff  $\mathcal{B}$  classifies (u,v) as true over  $G^2$  iff  $\mathcal{A}$  classifies (u,v) as true over G.

The other direction is obtained analogously following the reverse translations.

## A.4 Missing proofs in Section 5.3

First, recall the definition of rawl<sub>2</sub> and rwl<sub>2</sub>. Given a knowledge graph  $G = (V, E, R, c, \eta)$ , we have

$$\begin{split} \operatorname{rawl}_2^{(0)}(u,v) &= \eta(u,v), \\ \operatorname{rawl}_2^{(t+1)}(u,v) &= \tau \left( \operatorname{rawl}_2^{(t)}(u,v), \{\!\!\{ (\operatorname{rawl}_2^{(t)}(u,w),r) \mid w \in \mathcal{N}_r(v), r \in R) \}\!\!\} \right), \\ \operatorname{rwl}_2^{(0)}(u,v) &= \eta(u,v), \\ \operatorname{rwl}_2^{(t+1)}(u,v) &= \tau \left( \operatorname{rwl}_2^{(t)}(u,v), \{\!\!\{ (\operatorname{rwl}_2^{(t)}(w,v),r) \mid w \in \mathcal{N}_r(u), r \in R) \}\!\!\}, \{\!\!\{ (\operatorname{rwl}_2^{(t)}(u,w),r) \mid w \in \mathcal{N}_r(v), r \in R) \}\!\!\} \right). \end{split}$$

Now we recall the definition of  $\operatorname{rawl}_2^+$  and  $\operatorname{rwl}_2^+$ , which are defined in augmented graph instead with  $G^+ = (V, E^+, R^+, c, \eta)$ , where  $R^+$  is the disjoint union of R and  $\{r^- \mid r \in R\}$ , and  $E^+ = E \cup \{r^-(v, u) \mid r(u, v) \in E, u \neq v\}$ . Thus, for all  $t \geq 0$  and  $u, v \in V$ , we have

$$\begin{aligned} & \operatorname{rawl}_2^{+\,(t)}(G,u,v) = \operatorname{rawl}_2^{(t)}(G^+,u,v), \\ & \operatorname{rwl}_2^{+\,(t)}(G,u,v) = \operatorname{rwl}_2^{(t)}(G^+,u,v). \end{aligned}$$

We will drop the notation of G during the proof when the context is clear for simplicity.

**Proposition A.13.** For all  $t \geq 0$  and all knowledge graph G, let  $\mathsf{rwl}_2^{(0)}(G) \equiv \mathsf{rawl}_2^{(0)}(G)$ . The following statements hold:

- 1. For every t > 0, it holds that  $\operatorname{rwl}_2^{(t)}(G) \leq \operatorname{rawl}_2^{(t)}(G)$ .
- 2. There is a knowledge graph G and pair of nodes (u,v) and (u',v') such that  ${\sf rawl}_2^{(t)}(G,u,v) = {\sf rawl}_2^{(t)}(G,u',v')$  for all  $t \geq 0$  but  ${\sf rwl}_2^{(1)}(G,u,v) \neq {\sf rwl}_2^{(1)}(G,u',v')$ .

*Proof.* First, we show  $\operatorname{rwl}_2^{(t)}(G) \leq \operatorname{rawl}_2^{(t)}(G)$  and proceed by induction on t. The base case for t=0 is trivial by assumption. For the inductive step, given that we have  $\operatorname{rwl}_2^{(k+1)}(u,v) = \operatorname{rwl}_2^{(k+1)}(u',v')$ , by the definition of  $\operatorname{rwl}_2^{(k+1)}(u,v)$  and  $\operatorname{rwl}_2^{(k+1)}(u',v')$ , and as  $\tau$  is injective, it holds that

$$\begin{split} \operatorname{rwl}_2^{(k)}(u,v) &= \operatorname{rwl}_2^{(k)}(u',v') \\ \{\!\!\{ (\operatorname{rwl}_2^{(k)}(x,v),r) \mid x \in \mathcal{N}_r(u), r \in R \}\!\!\} &= \{\!\!\{ (\operatorname{rwl}_2^{(k)}(x',v'),r') \mid x' \in \mathcal{N}_{r'}(u'), r' \in R \}\!\!\} \\ \{\!\!\{ (\operatorname{rwl}_2^{(k)}(u,x),r) \mid x \in \mathcal{N}_r(v), r \in R \}\!\!\} &= \{\!\!\{ (\operatorname{rwl}_2^{(k)}(u',x'),r') \mid x' \in \mathcal{N}_{r'}(v'), r' \in R \}\!\!\} \end{split}$$

$$u$$
  $v$ 

$$x \xrightarrow{r} u'$$

Figure 2: Graph G' as the counter-example in Proposition A.13. It is also shown in Proposition A.15 to prove  $\operatorname{rawl}_2^{+(t)}(u,v) = \operatorname{rawl}_2^{+(t)}(u',v')$  for all  $t \geq 0$  but  $\operatorname{rwl}_2^{(1)}(u,v) \neq \operatorname{rwl}_2^{(1)}(u',v')$ .

Now, by the inductive hypothesis we have  $\operatorname{rawl}_2^{(k)}(u,v) = \operatorname{rawl}_2^{(k)}(u',v')$ . We can further transform the last equation by applying the inductive hypothesis again after unpacking the multiset. This results in

$$\{ (\mathsf{rawl}_2^{(k)}(u,x),r) \mid x \in \mathcal{N}_r(v), r \in R \} = \{ (\mathsf{rawl}_2^{(k)}(u',x'),r') \mid x' \in \mathcal{N}_{r'}(v'), r' \in R \} \}$$

Thus, it holds that  $\operatorname{rawl}_2^{(k+1)}(u,v) = \operatorname{rawl}_2^{(k+1)}(u',v')$  by definition of  $\operatorname{rawl}_2^{(k+1)}(u,v)$  and  $\operatorname{rawl}_2^{(k+1)}(u',v')$ .

For counter-example, we show the case for  $t \geq 0$ . Consider a relational graph  $G' = (V', E', R, c, \eta)$  such that  $V' = \{u, u', v, x\}, E' = \{r(x, u')\},$  and  $R = \{r\}$  with the initial labeling  $\eta$  for node pairs (u, v) and (u', v) satisfies  $\operatorname{rwl}_2^{(0)}(u, v) = \operatorname{rwl}_2^{(0)}(u', v)$  and  $\operatorname{rawl}_2^{(0)}(u, v) = \operatorname{rawl}_2^{(0)}(u', v)$ . For such graph G', we consider node pair (u, v) and (u', v). For  $\operatorname{rawl}_2^{(t)}(u, v) = \operatorname{rawl}_2^{(t)}(u', v)$ . The base case is trivial by assumption. The inductive step shows that by the inductive hypothesis:

$$\begin{split} \operatorname{rawl}_2^{(t+1)}(u,v) &= \tau(\operatorname{rawl}_2^{(t)}(u,v), \{\!\!\{ \}\!\!\}) \\ &= \tau(\operatorname{rawl}_2^{(t)}(u',v), \{\!\!\{ \}\!\!\}) \\ &= \operatorname{rawl}_2^{(t+1)}(u',v) \end{split}$$

On the other hand, we have

$$\begin{split} & \operatorname{rwl}_2^{(1)}(u,v) = \tau(\operatorname{rwl}_2^{(0)}(u,v), \{\!\!\{\}\!\!\}, \{\!\!\{\}\!\!\}) \\ & \neq \operatorname{rwl}_2^{(1)}(u,v') = \tau(\operatorname{rwl}_2^{(0)}(u,v'), \{\!\!\{(\operatorname{rwl}_2^{(0)}(x,v'),r))\}\!\!\}, \{\!\!\{\}\!\!\}) \end{split}$$

**Proposition 5.3.** *The following statements hold:* 

- 1. For all  $t \geq 0$  and all knowledge graph G, we have  $\operatorname{rawl}_{2}^{+(t)}(G) \leq \operatorname{rawl}_{2}^{(t)}(G)$ .
- 2. There is a knowledge graph G and nodes u, v, u', v' such that  $\mathsf{rawl}_2^{+(1)}(G, u, v) \neq \mathsf{rawl}_2^{+(1)}(G, u', v')$  but  $\mathsf{rawl}_2^{(t)}(G, u, v) = \mathsf{rawl}_2^{(t)}(G, u', v')$  for all  $t \geq 1$ .

*Proof.* To prove  $rawl_2^+(G) \leq rawl_2(G)$  first, we consider induction on iteration t. The base case for t = 0 is trivial by the assumption, so it is enough to consider the inductive step. We need to show that for some k,

$$\mathsf{rawl}_2^{+(k+1)}(u,v) = \mathsf{rawl}_2^{+(k+1)}(u',v') \implies \mathsf{rawl}_2^{(k+1)}(u,v) = \mathsf{rawl}_2^{(k+1)}(u',v')$$

By the definition of  $\operatorname{rawl}_2^{+(k+1)}(u,v)$ ,  $\operatorname{rawl}_2^{+(k+1)}(u',v')$  and the injectivity of  $\tau$ , it holds that

$$\begin{aligned} \operatorname{rawl}_2^{+(k)}(u,v) &= \operatorname{rawl}_2^{+(k)}(u',v') \\ \{\!\!\{ (\operatorname{rawl}_2^{+(k)}(u,x),r) \mid x \in \mathcal{N}_r^+(v), r \in R^+ \}\!\!\} &= \{\!\!\{ (\operatorname{rawl}_2^{+(k)}(u',x'),r') \mid x' \in \mathcal{N}_{r'}^+(v'), r' \in R^+ \}\!\!\} \end{aligned}$$

Because all inverse relations  $r^-$  are newly introduced, so it is impossible to be mixed with r, we can split the second equation into the following equations:

By the inductive hypothesis and unpacking the first equation, we can further imply that

$$\{\!\!\{(\mathsf{rawl}_2^{(k)}(u,x),r)\mid x\in\mathcal{N}_r(v),r\in R\}\!\!\}=\{\!\!\{(\mathsf{rawl}_2^{(k)}(u',x'),r')\mid x'\in\mathcal{N}_{r'}(v'),r'\in R\}\!\!\}$$

$$v \qquad x \xleftarrow{r_1} u \qquad v$$

$$v' \xrightarrow{r_2} u \qquad x' \xleftarrow{r_2} u' \qquad v'$$

Figure 3: Two counterexamples shown in Proposition 5.3 and A.14. The left graph G' is to show  $\operatorname{rawl}_2^{(t)}(u,v) = \operatorname{rawl}_2^{(t)}(u',v')$  for all  $t \geq 0$  but  $\operatorname{rawl}_2^{+(1)}(u,v) \neq \operatorname{rawl}_2^{+(1)}(u',v')$ , whereas the right graph G'' is to show  $\operatorname{rwl}_2^{(t)}(u,v) = \operatorname{rwl}_2^{(t)}(u',v')$  for all  $t \geq 0$  but  $\operatorname{rwl}_2^{+(1)}(u,v) \neq \operatorname{rwl}_2^{+(1)}(u',v')$ .

Thus, By definition of  $rawl_2^{(k+1)}(u,v)$ ,  $rawl_2^{(k+1)}(u',v')$  it holds that

$$\mathrm{rawl}_2^{(k+1)}(u,v) = \mathrm{rawl}_2^{(k+1)}(u',v')$$

For the counterexample, we consider a relational graph with two types of relation  $G'=(V',E',R',c,\eta)$  such that  $V'=\{u,v,v'\}, \ E'=\{r_1(v,u),r_2(v',u)\}, \ \text{and} \ R'=\{r_1,r_2\}.$  Let the initial pairwise labeling  $\eta$  for node pairs (u,v) and (u',v) satisfy  $\operatorname{rawl}_2^{+(0)}(u,v)=\operatorname{rawl}_2^{+(0)}(u,v')$  and  $\operatorname{rawl}_2^{(0)}(u,v)=\operatorname{rawl}_2^{(0)}(u,v').$  For such graph G', we consider node pair (u,v) and (u,v'). For  $\operatorname{rawl}_2^{(t)}$  where  $t\geq 0$ , we show by induction that  $\operatorname{rawl}_2^{(t)}(u,v)=\operatorname{rawl}_2^{(t)}(u,v').$  The base case is trivial by assumption. The inductive step shows that by the inductive hypothesis,

$$\begin{split} \operatorname{rawl}_2^{(t+1)}(u,v) &= \tau(\operatorname{rawl}_2^{(t)}(u,v), \{\!\!\{ \}\!\!\}) \\ &= \tau(\operatorname{rawl}_2^{(t)}(u,v'), \{\!\!\{ \}\!\!\}) \\ &= \operatorname{rawl}_2^{(t+1)}(u,v') \end{split}$$

On the other hand, we have

$$\begin{split} \operatorname{rawl}_2^{+(1)}(u,v) &= \tau(\operatorname{rawl}_2^{+(0)}(u,v), \{\!\!\{ (\operatorname{rawl}_2^{+(0)}(x,v), r_1^-) \}\!\!\}) \\ &\neq \operatorname{rawl}_2^{+(1)}(u,v') = \tau(\operatorname{rawl}_2^{+(0)}(u,v'), \{\!\!\{ (\operatorname{rawl}_2^{+(0)}(x,v'), r_2^-) ) \}\!\!\}) \end{split}$$

**Proposition A.14.** For all  $t \ge 0$  and all knowledge graph G, let  $\mathsf{rwl}_2^{+(0)}(G) \equiv \mathsf{rwl}_2^{(0)}(G)$ . The following statements hold:

- 1. For every t > 0,  $\text{rwl}_{2}^{+(t)}(G) \leq \text{rwl}_{2}^{(t)}(G)$
- 2. There is a knowledge graph G'' and pair of nodes (u,v) and (u',v') such that  $\operatorname{rwl}_2^{(t)}(G'',u,v) = \operatorname{rwl}_2^{(t)}(G'',u',v')$  for all  $t \geq 0$  but  $\operatorname{rwl}_2^{+(1)}(G'',u,v) \neq \operatorname{rwl}_2^{+(1)}(G'',u',v')$ .

*Proof.* As before, we first prove  $\operatorname{rwl}_2^+(G) \preceq \operatorname{rwl}_2(G)$  by induction on iteration t. The base case for t=0 is trivial by the assumption. By the inductive hypothesis,

$$\operatorname{rwl}_2^{+(k)}(u,v) = \operatorname{rwl}_2^{+(k)}(u',v') \implies \operatorname{rwl}_2^{(k)}(u,v) = \operatorname{rwl}_2^{(k)}(u',v')$$

for some k. Thus, assuming  $\operatorname{rwl}_2^{+(k+1)}(u,v) = \operatorname{rwl}_2^{+(k+1)}(u',v')$ , by the definition of  $\operatorname{rwl}_2^{+(k+1)}(u,v)$  and  $\operatorname{rwl}_2^{+(k+1)}(u',v')$  and by the injectivity of  $\tau$ , it holds that

$$\begin{aligned} \operatorname{rwl}_2^{+(k)}(u,v) &= \operatorname{rwl}_2^{+(k)}(u',v') \\ \{\!\!\{ (\operatorname{rwl}_2^{+(k)}(x,v),r) \mid x \in \mathcal{N}_r^+(u), r \in R^+ \}\!\!\} &= \{\!\!\{ (\operatorname{rwl}_2^{+(k)}(x',v'),r') \mid x' \in \mathcal{N}_{r'}^+(u'), r' \in R^+ \}\!\!\} \\ \{\!\!\{ (\operatorname{rwl}_2^{+(k)}(u,x),r) \mid x \in \mathcal{N}_r^+(v), r \in R^+ \}\!\!\} &= \{\!\!\{ (\operatorname{rwl}_2^{+(k)}(u',x'),r') \mid x' \in \mathcal{N}_{r'}^+(v'), r' \in R^+ \}\!\!\} \end{aligned}$$

By the similar argument in proving  $\operatorname{rawl}_2^+ \leq \operatorname{rawl}_2$ , we can split the multiset into two equations by decomposing  $\mathcal{N}_r^+(u) = \mathcal{N}_r(u) \cup \mathcal{N}_{r^-}(u)$  and  $\mathcal{N}_r^+(v) = \mathcal{N}_r(v) \cup \mathcal{N}_{r^-}(v)$ . Thus, we have

$$\begin{split} & \{ (\mathsf{rwl}_2^{+(k)}(x,v),r) \mid x \in \mathcal{N}_r(u), r \in R \} = \{ (\mathsf{rwl}_2^{+(k)}(x',v'),r') \mid x' \in \mathcal{N}_{r'}(u'), r' \in R \} \\ & \{ (\mathsf{rwl}_2^{+(k)}(y,v),r^-) \mid y \in \mathcal{N}_{r^-}(u), r \in R \} = \{ (\mathsf{rwl}_2^{+(k)}(y',v'),r'^-) \mid y' \in \mathcal{N}_{r'^-}(u'), r' \in R \} \\ & \{ (\mathsf{rwl}_2^{+(k)}(u,x),r) \mid x \in \mathcal{N}_r(v), r \in R \} = \{ (\mathsf{rwl}_2^{+(k)}(u',x'),r') \mid x' \in \mathcal{N}_{r'}(v'), r' \in R \} \\ & \{ (\mathsf{rwl}_2^{+(k)}(u,y),r^-) \mid y \in \mathcal{N}_{r^-}(v), r \in R \} = \{ (\mathsf{rwl}_2^{+(k)}(u',y'),r'^-) \mid y' \in \mathcal{N}_{r'^-}(v'), r' \in R \} \} \end{split}$$

By the inductive hypothesis and unpacking the first and the third equations, we can further imply that

$$\begin{split} \operatorname{rwl}_2^{(k)}(u,v) &= \operatorname{rwl}_2^{(k)}(u',v') \\ \{\!\!\{ (\operatorname{rwl}_2^{(k)}(x,v),r) \mid x \in \mathcal{N}_r(u), r \in R \}\!\!\} &= \{\!\!\{ (\operatorname{rwl}_2^{(k)}(x',v'),r') \mid x' \in \mathcal{N}_{r'}(u'), r' \in R \}\!\!\} \\ \{\!\!\{ (\operatorname{rwl}_2^{(k)}(u,x),r) \mid x \in \mathcal{N}_r(v), r \in R \}\!\!\} &= \{\!\!\{ (\operatorname{rwl}_2^{(k)}(u',x'),r') \mid x' \in \mathcal{N}_{r'}(v'), r' \in R \}\!\!\} \end{split}$$

This would results in  $\operatorname{rwl}_2^{(k+1)}(u,v) = \operatorname{rwl}_2^{(k+1)}(u',v') \text{ by the definition of } \operatorname{rwl}_2^{(k+1)}(u,v) \text{ and } \operatorname{rwl}_2^{(k+1)}(u',v')$ 

For the counter-example, we consider a relational graph  $G''=(V'',E'',R'',c,\eta)$  such that  $V''=\{u,u',v,v',x,x'\}$ ,  $E''=\{r_1(u,x),r_2(u',x')\}$ , and  $R''=\{r_1,r_2\}$ . For such graph G'', we set the initial labeling  $\eta$  for node pairs (u,v) and (u',v') to satisfy  $\operatorname{rwl}_2^{+(0)}(u,v)=\operatorname{rwl}_2^{+(0)}(u',v')$  and  $\operatorname{rwl}_2^{(0)}(u,v)=\operatorname{rwl}_2^{(0)}(u',v')$ . For such graph G'', we consider node pair (u,v) and (u',v').

Consider  $\mathrm{rwl}_2^{(t)}$  where  $t\geq 0$ , we show by induction that  $\mathrm{rwl}_2^{(t)}(u,v)=\mathrm{rwl}_2^{(t)}(u',v')$ . The base case is trivial by assumption. The inductive step shows that by inductive hypothesis,

$$\begin{split} \operatorname{rwl}_2^{(t+1)}(u,v) &= \tau(\operatorname{rwl}_2^{(t)}(u,v),\{\!\!\{\}\!\!\},\{\!\!\{\}\!\!\}) \\ &= \tau(\operatorname{rwl}_2^{(t)}(u',v'),\{\!\!\{\}\!\!\},\{\!\!\{\}\!\!\}) \\ &= \operatorname{rwl}_2^{(t+1)}(u',v') \end{split}$$

On the other hand, we have

$$\begin{split} & \operatorname{rwl}_2^{+(1)}(u,v) = \tau(\operatorname{rwl}_2^{+(0)}(u,v), \{\!\!\{ (\operatorname{rwl}_2^{+(0)}(x,v), r_1^-) \}\!\!\}, \{\!\!\{ \}\!\!\} ) \\ & \neq \operatorname{rwl}_2^{+(1)}(u',v') = \tau(\operatorname{rwl}_2^{+(0)}(u',v'), \{\!\!\{ (\operatorname{rwl}_2^{+(0)}(x',v'), r_2^-) ) \}\!\!\}, \{\!\!\{ \}\!\!\} ) \end{split}$$

**Proposition A.15.** For all  $t \geq 0$  and all knowledge graph G, let  $\mathsf{rwl}_2^{(0)}(G) \equiv \mathsf{rawl}_2^{+(0)}(G)$ , then the following statement holds:

1. There is a knowledge graph G and pair of nodes (u,v) and (u',v') such that  ${\sf rwl}_2^{(t)}(G,u,v) = {\sf rwl}_2^{(t)}(G,u',v')$  for all  $t \geq 0$  but  ${\sf rawl}_2^{+(1)}(G,u,v) \neq {\sf rawl}_2^{+(1)}(G,u',v')$ .

2. There is a knowledge graph G' and pair of nodes (u, v) and (u', v') such that  $\mathsf{rawl}_2^{+(t)}(G', u, v) = \mathsf{rawl}_2^{+(t)}(G', u', v')$  for all  $t \ge 0$  but  $\mathsf{rwl}_2^{(1)}(G', u, v) \ne \mathsf{rwl}_2^{(1)}(G', u', v')$ .

*Proof.* To show  $\operatorname{rwl}_2(G)$  does not refine  $\operatorname{rawl}_2^+(G)$ , we consider a relational graph  $G=(V,E,R,c,\eta)$  such that  $V=\{u,u',v,v',x,x'\}, E=\{r_1(v,x),r_2(v',x')\}$ , and  $R=\{r_1,r_2\}$ . We let the initial labeling  $\eta$  for node pairs (u,v) and (u',v') to satisfy  $\operatorname{rwl}_2^{(0)}(u,v)=\operatorname{rwl}_2^{(0)}(u',v')$  and  $\operatorname{rwl}_2^{(0)}(u,v)=\operatorname{rwl}_2^{(0)}(u',v')$ . For such graph G, we consider node pair (u,v) and (u',v'). For  $\operatorname{rwl}_2^{(t)}$  where  $t\geq 0$ , we show by induction that  $\operatorname{rwl}_2^{(t)}(u,v)=\operatorname{rwl}_2^{(t)}(u',v')$ . The base case is trivial by assumption. The inductive step shows that by the inductive hypothesis,

$$\begin{split} \operatorname{rwl}_2^{(t+1)}(u,v) &= \tau(\operatorname{rwl}_2^{(t)}(u,v), \{\!\!\{\,\!\!\}, \{\!\!\{\,\!\!\}\,\!\!\}) \\ &= \tau(\operatorname{rwl}_2^{(t)}(u',v'), \{\!\!\{\,\!\!\}\,\!\!\}, \{\!\!\{\,\!\!\}\,\!\!\}) \\ &= \operatorname{rwl}_2^{(t+1)}(u',v') \end{split}$$

$$u \qquad v \xrightarrow{r_1} x$$

$$u'$$
  $v' \xrightarrow{r_2} x'$ 

Figure 4: Counterexample shown in Proposition A.15 to prove  $\operatorname{rwl}_2^{(t)}(u,v) = \operatorname{rwl}_2^{(t)}(u',v')$  for all  $t \geq 0$  but  $\operatorname{rawl}_2^{+(1)}(u,v) \neq \operatorname{rawl}_2^{+(1)}(u',v')$ .

On the other hand, we have

$$\begin{aligned} & \operatorname{rawl}_2^{+(1)}(u,v) = \tau(\operatorname{rawl}_2^{+(0)}(u,v), \{\!\!\{ (\operatorname{rawl}_2^{+(0)}(u,x), r_1^-) \}\!\!\}) \\ \neq & \operatorname{rawl}_2^{+(1)}(u,v') = \tau(\operatorname{rawl}_2^{+(0)}(u',v'), \{\!\!\{ (\operatorname{rawl}_2^{+(0)}(u',x'), r_2^-) \}\!\!\}) \end{aligned}$$

Finally, to show  $\operatorname{rawl}_2^+$  does not refine  $\operatorname{rwl}_2$ , we demonstrate the case for  $t \geq 0$ . Consider a relational graph  $G' = (V', E', R', c, \eta)$  such that  $V' = \{u, u', v, x\}$ ,  $E' = \{r(x, u')\}$ , and  $R' = \{r\}$ . We let the initial labeling  $\eta$  for node pairs (u, v) and (u', v) satisfy  $\operatorname{rwl}_2^{(0)}(u, v) = \operatorname{rwl}_2^{(0)}(u', v)$  and  $\operatorname{rawl}_2^{+(0)}(u, v) = \operatorname{rawl}_2^{+(0)}(u', v)$ . For such graph G', we consider node pair (u, v) and (u', v). For  $\operatorname{rawl}_2^{+(t)}$  where  $t \geq 0$ , and show by induction that  $\operatorname{rawl}_2^{+(t)}(u, v) = \operatorname{rawl}_2^{+(t)}(u', v)$ . The base case is trivial by assumption. The inductive step shows that by the inductive hypothesis,

$$\begin{split} \operatorname{rawl}_2^{+(t+1)}(u,v) &= \tau(\operatorname{rawl}_2^{+(t)}(u,v), \{\!\!\{\}\!\!\}) \\ &= \tau(\operatorname{rawl}_2^{+(t)}(u',v), \{\!\!\{\}\!\!\}) \\ &= \operatorname{rawl}_2^{+(t+1)}(u',v) \end{split}$$

On the other hand, we have

$$\begin{split} & \operatorname{rwl}_2^{(1)}(u,v) = \tau(\operatorname{rwl}_2^{(0)}(u,v),\{\!\!\{\}\!\!\},\{\!\!\{\}\!\!\}) \\ & \neq \operatorname{rwl}_2^{(1)}(u,v') = \tau(\operatorname{rwl}_2^{(0)}(u,v'),\{\!\!\{(\operatorname{rwl}_2^{(0)}(x,v'),r))\}\!\!\},\{\!\!\{\}\!\!\}) \end{split}$$

Note that the counter-example graph G' here is identical to the one in Proposition A.13.

# **B** Further Experimental Details

In this section, we report further experimental details. The detailed statistics of the datasets are shown in Table 3. The hyperparameters used for inductive relation prediction are reported in Table 4. The corresponding number of trainable parameters for each model variation are reported in Table 5.

All of the model variations minimize the negative log-likelihood of positive and negative facts. We follow the *partial completeness assumption* [34] by randomly corrupting the head entity or the tail entity to generate the negative samples. We parameterize the conditional probability of a fact q(u,v) by  $p(v\mid u,q)=\sigma(f(\boldsymbol{h}_{v\mid u,q}^{(T)}))$ , where  $\sigma$  is the sigmoid function and f is 2-layer MLP. Following RotatE [35], we adopt *self-adversarial negative sampling* by sampling negative triples from the following distribution with  $\alpha$  as the *adversarial temperature*:

$$\mathcal{L}(v \mid u, q) = -\log p(v \mid u, q) - \sum_{i=1}^{k} w_{i,\alpha} \log(1 - p(v_i' \mid u_i', q))$$

where k is the number of negative samples for one positive sample and  $(u_i',q,v_i')$  is the i-th negative sample. Finally,  $w_i$  is the weight for the i-th negative sample, defined by  $w_{i,\alpha} := \operatorname{Softmax}(\frac{\log(1-p(v_i'|u_i',q))}{\alpha})$ .

Table 3: Dataset Statistics for inductive relation prediction of C-MPNN. **#Query\*** is the number of queries used in the Validation set. In the Training set, all triplets are used as queries.

Dataset		#Relation	Tra	in & Valid	ation	Test			
Dataset		#IXCIALIOII	#Nodes	#Triplet	#Query*	#Nodes	#Triplet	#Query	
	$v_1$	9	2,746	5,410	630	922	1,618	188	
WN18RR	$v_2$	10	6,954	$15,\!262$	1,838	2,757	4,011	441	
WINTOKK	$v_3$	11	12,078	25,901	3,097	5,084	6,327	605	
	$v_4$	9	3,861	7,940	934	7,084	$12,\!334$	$1,\!429$	
	$v_1$	180	1,594	4,245	489	1,093	1,993	205	
FB15k-237	$v_2$	200	2,608	9,739	$1,\!166$	1,660	4,145	478	
TD13K-237	$v_3$	215	$3,\!668$	17,986	$2,\!194$	2,501	7,406	865	
	$v_4$	219	4,707	27,203	3,352	3,051	11,714	1,424	

Table 4: Hyperparameter for inductive relation prediction of C-MPNN.

Hyperparamet	ter	WN18RR	FB15k-237	
GNN Layer	$\begin{array}{c} \operatorname{Depth}(T) \\ \operatorname{Hidden Dimension} \end{array}$	6 32	6 32	
MLP Layer	Depth Hidden Dimension	2 64	2 64	
Optimization	Optimizer Learning Rate	Adam 5e-3	Adam 5e-3	
Learning	Batch size #Negative Sample Epoch Adversarial Temperature	8 50 20 1	8 50 20 1	

Table 5: Number of trainable parameter in inductive relation prediction of C-MPNN with  $\delta_2$  initialization.

Model	Model Instances		WN18RR				FB15k-237			
$\psi$	$ heta_r$	v1	v2	v3	v4	v1	v2	v3	<b>v4</b>	
sum	$\theta_r^1$	132k	144k	157k	132k	2,310k	2,564k	2,755k	2,806k	
sum	$\theta_r^2$	21k	22k	22k	21k	98k	107k	113k	115k	
sum	$\theta_r^3$	128k	141k	153k	128k	2,240k	2,488k	2,673k	2,722k	
PNA	$\theta_r^1$	199k	212k	225k	199k	2,377k	2,632k	2,823k	2,874k	
PNA	$\theta_r^2$	89k	89k	90k	89k	165k	174k	181k	183k	
PNA	$\theta_r^3$	196k	208k	221k	196k	2,308k	2,555k	2,740k	2,790k	