

---

# DEEP INCREMENTAL LEARNING MODELS FOR TEMPORAL TABULAR DATASETS WITH DISTRIBUTION SHIFTS \*

---

**Thomas Wong**  
Imperial College London  
London  
mw4315@ic.ac.uk

**Mauricio Barahona**  
Imperial College London  
London  
m.barahona@imperial.ac.uk

## ABSTRACT

In this paper, we present a robust incremental learning model for regression tasks on temporal tabular datasets. Using commonly available tabular and time-series prediction models as building blocks, a machine-learning model is built incrementally to adapt to distributional shifts in data. Using the concept of self-similarity, the model uses only two basic building blocks of machine learning models, gradient boosting decision trees and neural networks to build models for any required complexity. The model is demonstrated to have robust performances under adverse situations such as regime changes, fat-tailed distributions and low signal-to-noise ratios. Model robustness are studied under different hyper-parameters and model complexity settings using XGBoost models trained on the Numerai dataset as a detailed case study.

With the use of model ensembling, there is a little loss in model performances if standard XGBoost models (5000 boosting rounds) are used instead of large XGBoost models (50000 boosting rounds). The model is efficient with much lower hardware requirement than other machine learning models as no specialised neural architectures are used and each model building block can be independently trained in parallel.

**Keywords** Machine Learning, Time-Series Prediction, Deep Learning,

## 1 Introduction

**Background of incremental learning** As machine learning models are increasingly used in real-life applications, incremental learning is becoming an increasingly important research problem as practitioners trying to deploy artificial intelligence systems over different use cases. For example, class incremental learning [1, 2, 3] are needed for real-time classification systems where different categories of images cannot be known in advance.

Many important applications, such as Internet of Things (IoT) [4] and cyber-security [5], would involve stream data, where data(features) are continuously updated and predictions are made **point-in-time**. A key challenge in incremental learning is that when there are distributional shifts in data that results in **model drifts** during inference, which is the drop of out-of-sample performances of prediction models when the models learnt relationships from the training set that significantly differ from those in the test set.

Reinforcement learning [6, 7, 8] is a related modelling approach where a model(agent) learns a policy to optimise rewards by interacting with the environment. Reinforcement learning is particular useful when the actions of the model can influence the environment and there are multiple agents interacting with each other [9]. Under the assumption that the actions of models have no influence to the data stream (environment), reinforcement learning reduces to incremental learning when the reward of agents is not used as input features. In other words, the input features (environment) are **independent** to the actions of the agent(predictions of the model) as there is no feedback loop between the agent and environment. Applying trained reinforcement learning agents into unknown situations, such as trading [10], perception in self-driving cars [11] and robotics [12] remains a great challenge. Domain adaption for reinforcement learning

---

\**Citation: Authors. Title. Pages.... DOI:000000/11111.*

algorithms [13, 14] bridges the gap between controlled environments and real-life situations using different advanced and complex algorithms. Key challenges such as robustness of agent behaviour [15] and interpretability [16] remains unsolved.

Deep incremental learning, introduced in this paper, is a hybrid approach which allows predictions from (base) models to be reused in future predictions for prediction tasks performed data streams. Unlike reinforcement learning which allows flow of information between agent and environment in both directions, deep incremental learning only allows a single directional flow of information from one layer to the next one as a waterfall. The **point-in-time** nature of predictions are preserved so that no look-ahead bias is introduced. Deep incremental learning can be considered as an extension of model stacking [17] taken the stream nature of data into account.

The incremental problem studied here is a ranking task based on data streams of tabular features and targets, defined as temporal tabular datasets, which is first introduced in [18].

## Definitions

**Definition 1** (Temporal Tabular Datasets). A temporal tabular dataset is a collection of matrices  $\{X_i, y_i\}_{1 \leq i \leq T}$  collected over time eras 1 to  $T$ . Each matrix  $X_i$  represents data available at era  $i$  with shape  $N_i \times M$ , where  $N_i$  is the number of data samples in era  $i$  and  $M$  is the number of features describing the samples.  $y_i$  are the targets corresponding to the features  $X_i$ , which can be single-dimensional or multi-dimensional. Note that the definition of the features are fixed throughout the eras, in the sense that the same computational formula is used to compute the features at each era. On the other hand, the number of data samples  $N_i$  does not have to be constant across time. In practical applications, the number of data samples in each era is assumed to be globally bounded. Unlike standard online learning problems, where the data arrived can be used to update machine learning models right after prediction is made, there is a **fixed** and known time lag for the targets from an era to be known, defined as **data embargo**. For example, for a dataset with a data embargo of 5, at era  $X$  the features of Era  $X$  would be known and then a prediction of the ranking of items at that time could be made. The targets of era  $X$  are only known at era  $X + 5$ , which can then be used to calculate the quality of predictions according to a suitably chosen metric.

For general tabular datasets, the features can be in different formats, such as numerical, ordinal or categorical. With suitable pre-processing techniques, features can be transformed into equal-sized or Gaussian-binned numerical(ordinal) values. The datasets used in this paper are already standardised into discrete bins.

There are two approaches to model temporal tabular datasets. The first is to apply standard tabular machine learning models as usual, taking into account the temporal order of data during cross-validation. The second is to model the **derived** time-series defined as follows.

**Definition 2** (Derived Time Series). Time series can be derived from the temporal tabular dataset with different transformations. Transformations considered here are restricted to those that can be applied to each data era **independently**. Commonly used transformations include: Dimension reduction operations which transforms the matrix of a single slice of tabular features at era  $i$  with its targets into a one-dimensional tensor, formally defined as  $f(X, y) : (\mathbb{R}^{N_i \times M}, \mathbb{R}^{N_i \times 1}) \mapsto \mathbb{R}^M$  where  $X$  and  $y$  are the features and targets,  $N_i$  is the number of observations at era  $i$ ,  $M$  is the number of features. This procedure is defined as deriving the **feature performances** of the temporal tabular dataset.

Any machine learning model can be considered as a sequence of transformations between different tensors. Restricting to transformations between tabular and time-series data only, 4 different basic transformations are obtained as follows:

### 1. Transformation from tabular data to tabular

- Standard tabular machine learning models which transform the given feature target pair  $(X, y)$  into  $y'$  where the first(data) dimension of  $X, y, y'$  are equal dimensions and  $y$  and  $y'$  matches all dimensions. The transformations is performed **point-wise**, where at inference each item can be predicted independently. There are many examples for this class of machine learning models, including (and not limited to) gradient-boosting decision trees, and multi-layer perceptron networks.
- List-wise tabular machine learning models which transform the **whole** list of items at a time. For a temporal tabular dataset, this means the item rankings are predicted **all at once**. Examples include various list-wise models for learn-to-rank problems [19].

### 2. Transformation from tabular data to time-series

- Deriving time series using the procedure defined in 2 or other suitable transformations.

### 3. Transformation from time-series to tabular data

	Era 1	Era 2	Era 3	Era 4	Era 5	Era 6	Era 7	Era 8	Era 9	Era 10	Era 11	Era 12	Era 13	Era 14	Era 15	Era 16	Era 17	Era 18	Era 19	Era 20	
Model 1	Yellow	Yellow	Yellow	Yellow	Black	Blue	Blue	Blue	Blue	Blue	Blue	Blue	Blue	Blue	Blue	Blue	Blue	Blue	Blue	Blue	Blue
Model 2						Yellow	Yellow	Yellow	Yellow	Black	Blue	Blue	Blue	Blue	Blue	Blue	Blue	Blue	Blue	Blue	Blue
Model 3											Yellow	Yellow	Yellow	Yellow	Black	Blue	Blue	Blue	Blue	Blue	Blue

Figure 1: Example of reusing model predictions in an incremental learning model

- Feature Engineering methods for time-series data such as Signature transforms [20] and Random Fourier transforms [21] which transforms a slice of time-series into a single dimensional tensor which captures the characteristics of the time-series.
4. Transformation from time-series to time-series
    - Sequence models in deep learning, such as LSTM [22] and Transformers [23].

The above transformations are the building blocks of the deep incremental learning model. For tabular prediction tasks, any chain of transformations starting with tabular features and ending with tabular targets can be used. This expands the class of models from standard tabular models to other multi-step models such as **factor-timing** models. In factor-timing models, the features are first transformed into a time series, capturing the history of feature performances and then using the ranking of predicted feature performances to formulate a factor-timing portfolio. The time-series model for predicting feature performances could be any of the above-mentioned methods.

**How incremental learning is different from traditional machine learning** The incremental nature of prediction tasks on data streams challenges the traditional assumptions of machine learning problems. In particular, a (single-pass) cross-validation which splits the data into **fixed** training, validation and test periods is not the most suitable framework. Instead, an incremental learning framework should be used to retrain and/or update model parameters. Under this framework, a model is represented by a continuous stream of parameters instead of a single set of parameters. The procedure also adds new hyper-parameters, such as training size and retrain period to the machine learning model. In practice, these hyper-parameters could be selected based on computational resources available rather than optimised. The size of memory will limit the maximum training size and the amount of GPU or other processing units available will limit how often the models are retrained/updated.

When retrain period is greater than 1, there is an extra degree of freedom in when to start the incremental learning procedure. For example, if models are retrained every 10th era, then starting the incremental learning procedure at Era 1, Era 2, ... to Era 10 would give 10 different training procedures using different training sets. This choice could have a non-negligible impact on prediction performances [24] for non-stationary datasets.

The clear distinction between features, targets and predictions is also blurred in the incremental learning setting, as predictions from each model can be used as additional features in building other models. New targets can also be created by subtracting against the predictions made. This suggests model training should be considered as a **multi-step** problem instead of a single-step problem.

As an example, consider an incremental learning problem with a data lag of 1, then in figure 1, three models are trained under the incremental learning framework. The training period of each model is fixed at 4. At Era 6, information up to Week 4 (where both the features and targets are known) is used to train Model 1 and then obtain predictions from Era 6 on-wards. At Era 11, information up to Week 9 is used for model training. Features between Week 6 and Week 9 are combined with predictions from Model 1 to train a new model (Model 2). Similarly, at Era 16, Model 3 is trained using data from Era 11 to Era 14, which consists of the original given features, and predictions from Model 1 and Model 2.

There are various benefits of reusing model predictions within an incremental learning model. It provides a hierarchical structure of models, in which each model can be interpreted as an improvement/adaption of the previous ones to distributional shifts in data and the prediction quality of each model can be inspected independently. Moreover, reusing model predictions introduced a feedback learning loop where model predictions correct themselves in an incremental manner.

The above incremental learning model can be applied to not just a **single** machine learning model, but a **collection** of machine learning models in parallel, which is defined as **layers** of models. The notion is borrowed from MLP, where each node within a layer is now an independently trained model.

A major difference between our incremental learning model from MLP is that training is done in a single forward pass rather than by back-propagation. This allows us to train very complicated models even with little resources, as there is

no need to put the whole model in (distributed) memory to pass gradients between layers. As each model within a layer can be trained independently, training models **within** a layer becomes an embarrassingly parallel task when multiple GPUs can be used. The program code of the model is also easier to maintain as there is no need to use specialised software packages to distribute data between GPUs.

Recent work in deep learning research suggests back-propagation is not strictly necessary for model training [25]. Deep Regression Ensemble (DRE) [26] is an example where back-propagation is not used in training. The model is built by training multiple layers of ridge regression models with random feature projections. The model can be considered as a multi-layer perceptron network where some layers have frozen weights. The deep incremental model presented here is significantly **different** from DRE as no restrictions are made on the machine learning models used.

### 1.1 Practical considerations

Unlike standard machine learning problems where model training is done offline, where memory and computational time is usually not a major consideration in model design, incremental learning models deployed to live data streams would be limited by both the memory and computational time during inference and online retrain/update of model parameters. The exact requirements varied between problems and therefore it is not possible to offer a one-size-fits-all solution.

All models in this paper are trained on a single CUDA-enabled GPU of 10GB memory for model training. While this assumption precludes the use of very advanced deep learning methods, incremental learning models(models) can be built for any model complexity/expressiveness using commonly used tabular and time-series models as building blocks. The model can be designed to process an infinite data stream of temporal tabular data effectively without ever-growing memory consumption, by caching only the latest values in the incremental learning process.

## 2 Machine Learning Models for Time Series Datasets

In this section, we introduce machine learning models that are commonly used for time-series datasets and how to create **factor-timing** models based on predictions from time-series models.

**Multi-variate time-series** A multi-variate time-series  $X$  of  $T$  steps and  $N$  channels can be represented as  $X = (\mathbf{x}_1, \mathbf{x}_2, \dots, \mathbf{x}_i, \dots, \mathbf{x}_T)$ , with  $1 \leq i \leq T$  and each vector  $\mathbf{x}_i \in \mathbb{R}^N$  represents the values of the  $N$  channels at time  $i$ . The number of channels of the time series is assumed to be fixed throughout time with regular and synchronous sampling, i.e. the values in each vector from multiple channels arrive at the same time at a fixed frequency.

**Definition 3** (Time Series Model). Given a time series  $X_T \in \mathbb{R}^{T \times M}$  where  $T$  is the size of the time dimension and  $M$  is the number of features. A (one-step) ahead time-series model is a function  $f : \mathbb{R}^{T \times M} \mapsto \mathbb{R}^M$ .

In practice, the function  $f$  is often learned by training statistical/machine learning models using future values of  $X_T$ , which is obtained by shifting the values of  $X_T$  across the time dimension.

### 2.1 Factor Timing Models

Factor-timing models are created based on predicted rankings of features from the time series models as shown in Algorithm 1. The raw predicted values from the time-series models are converted into normalised rankings which can be used as weights of a linear factor-timing model. Within an incremental learning framework, a new factor-timing model is trained at each time step using the latest historical values of the derived feature importance time series.

### 2.2 Statistical Rules

Simple statistical rules can be applied on each feature time-series **independently** to summarise the history of time-series. Moving averages are commonly used to capture trends in time-series. In this paper, rather than fixing different look-back sizes to compute the moving averages of time-series, exponential moving averages (EMA) with different weight decays are used. This approach avoids the need for a warm-up period in computing traditional window-based moving averages. The formula to compute EMA is given in the following.

**Definition 4** (Exponential Moving Average). Given an univariate time series  $X = (X_1, X_2, \dots, X_t, \dots)$ , the exponential moving average  $y_t$  of the time-series at time  $t$  with weight decay  $\alpha$  is defined as

$$\begin{aligned} y_1 &= X_1 \\ y_t &= (1 - \alpha)y_{t-1} + \alpha X_t \end{aligned}$$

---

**Algorithm 1:** Factor Timing Model

---

**Input:** At prediction era  $t$ , predicted values from time series model  $\hat{y}_t \in \mathbb{R}^d$ , temporal tabular dataset  $X_t \in \mathbb{R}^{N_t \times d}$  where  $d$  is the number of features

**Output:** factor timing model  $\hat{z}_t \in \mathbb{R}^{N_t}$

Calculate the normalised ranking of features  $\hat{r}_t$  from predictions of the time series model

$$\hat{r}_t = \text{rank}(\hat{y}_t) - 0.5$$

where rank is the function which calculates the percentile rank of a value within a vector.  $\hat{r}_t$  are ranged between  $-0.5$  and  $0.5$

Apply truncation to the normalised ranking of features if needed, given upper bound  $u$  and lower bound  $l$  on the normalised rankings,  $-0.5 < l < u < 0.5$

$$r_t = \max(\min(\hat{r}_t, u), l)$$

Calculate linear factor-timing predictions  $\hat{z}_t = X_t r_t$

---

### 2.3 Feature Engineering Models

Feature engineering methods can be applied to multi-variate time series so that tabular features are obtained.

**Feature extraction** Feature extraction methods are defined as functions that map the two-dimensional time-series  $X \in \mathbb{R}^{T \times N}$  to a one-dimensional feature space  $f(X) \in \mathbb{R}^K$  where  $K$  is the number of features. Feature extraction methods reduce the dimension and noise in time-series data. With feature extraction methods, traditional machine learning models such as ridge regression or gradient boosting decision trees can be used without relying on advanced neural network architectures such as Recurrent Neural Networks (RNN), Long-Short-Term-Memory (LSTM) Networks or Transformers [23].

**Look-back windows** For time series which can potentially grow in infinity, a look-back window is needed to restrict the data size when calculating features from time series. To avoid look-ahead bias features that represent the state of time-series at time  $i$  can only be calculated using values obtained up to time  $i$ , which is  $(\mathbf{x}_1, \mathbf{x}_2, \dots, \mathbf{x}_i)$ . In most use cases, data collected more recently often have more importance than data collected from a more distant past. Therefore, analysis is often restricted to use the most recent  $k$  data points only, which are  $(\mathbf{x}_{i-k}, \mathbf{x}_{i+1-k}, \dots, \mathbf{x}_i)$ . This represents the state of the time series at time  $i$  with a look-back window of size  $k$ . Feature extraction methods are applied to data within the look-back window only. Multiple look-back windows can be used to extract features corresponding to short-term and long-term price trends. At each time  $i$ , features extracted with different look-back windows are concatenated to represent the state of the time series.

#### 2.3.1 Signature Transforms

Signature transforms [27, 28, 20] are **deterministic** transformations which can be used to extract features from multi-variate time series. Signature transforms are applied on continuous paths. A path  $X$  is defined as a continuous function from a finite interval  $[a, b]$  to  $\mathbb{R}^d$  with  $d$  the dimension of the path.  $X$  can be parameterised in coordinate form as  $X_t = (X_t^1, X_t^2, \dots, X_t^d)$  with each  $X_t^i$  being a single dimensional path.

For each index  $1 \leq i \leq d$ , the increment of  $i$ -th coordinate of path at time  $t \in [a, b]$ ,  $S(X)_{a,t}^i$ , is defined as

$$S(X)_{a,t}^i = \int_{a < s < t} dX_s^i = X_t^i - X_a^i$$

As  $S(X)_{a,t}^i$  is also a real-valued path, the integrals can be calculated iteratively. A  $k$ -fold iterated integral of  $X$  along the indices  $i_1, \dots, i_k$  is defined as

$$S(X)_{a,t}^{i_1, \dots, i_k} = \int_{a < t_k < t} \dots \int_{a < t_1 < t_2} dX_{t_1}^{i_1} \dots dX_{t_k}^{i_k}$$

The Signature of a path  $X : [a, b] \mapsto \mathbb{R}^d$ , denoted by  $S(X)_{a,b}$ , is defined as the infinite series of all iterated integrals of  $X$ , which can be represented as follows

$$\begin{aligned} S(X)_{a,b} &= (1, S(X)_{a,b}^1, \dots, S(X)_{a,b}^d, S(X)_{a,b}^{1,1}, \dots) \\ &= \bigoplus_{n=1}^{\infty} S(X)_{a,b}^n \end{aligned}$$

An alternative definition of signature as the response of an exponential nonlinear system is given in [20].

Log Signature can be computed by taking the logarithm on the formal power series of Signature. No information is lost as it is possible to recover the (original) Signature from Log Signature by taking the exponential [28, 20]. Log Signature provides a more compact representation of the time series than Signature.

$$\log S(X)_{a,b} = \bigoplus_{n=1}^{\infty} \frac{(-1)^{(n-1)}}{n} S(X)_{a,b}^{\otimes n}$$

Signatures can be computed efficiently using the Python package `signatory` [29]. The signature is a multiplicative functional in which Chen's identity holds. This allows quick computation of signatures on overlapping slices in a path. Signatures provide a unique representation of a path which is invariant under reparameterisation [28, 20]. Rough Path Theory suggests the signature of a path is a good candidate set of linear functionals which captures the aspects of the data necessary for forecasting. In particular, continuous functions of paths are approximately linear on signatures [30]. This can be considered as a version of the universal approximation theorem [31] for signature transforms.

**Limitations for signature transforms in high dimensional datasets** The number of signatures and log-signatures increases exponentially with the number of channels. For time series with a large number of channels, random sampling can be applied to select a small number ( $5 < N < 20$ ) of time-series with replacement from the original time series on which signature transforms are applied. Random sampling can be repeated a given number of times to generate representative features of the whole multivariate time series. Similar ideas are considered in [32], in which random projections on the high dimensional time series are used to reduce dimensionality before applying signature transforms.

Let  $\tilde{X}$  be a multivariate time series with  $T$  time-steps and  $d$  dimensional features, denote  $\tilde{X}_s \in \mathbb{R}^d$  be the observation of the time series at timestep  $s$ . Procedure 2 can be used to obtain paths, which are slices of time-series with different lookback windows. Random Signature transforms 3 can then be used to compute the signature of the path, which summarises the information of the time series.

---

**Algorithm 2:** Lookback Window Slicing

---

**Input:** time series  $\tilde{X} \in \mathbb{R}^{T \times d}$ , lookback  $\delta$

**Output:** paths  $X_t \in \mathbb{R}^{t \times d}$

**for**  $1 \leq t \leq T$  **do**

    Set start of slice  $s_1 = \max(1, t - \delta)$  ;

    Set end of slice  $s_2 = t$  ;

$X_t = (\tilde{X}_{s_1}, \tilde{X}_{s_1+1}, \dots, \tilde{X}_{s_2})$  ;

**end**

---



---

**Algorithm 3:** Random Signature Transform

---

**Input:** path  $X_t \in \mathbb{R}^{t \times d}$ , level of signature  $L$ , number of channels  $C$ , number of feature sets  $p$ , where  $d > C$  ;

**Output:** log signatures  $s_t \in \mathbb{R}^{pN}$

Define  $N =$  Number of Log Signatures of a path with  $C$  channels up to level  $L$  ;

**for**  $1 \leq i \leq p$  **do**

    Sample with replacement  $C$  Columns from  $X_t$ , defined as  $\tilde{X}_t^i$  ;

    Compute the Log Signatures  $s_t^i \in \mathbb{R}^N$  of  $\tilde{X}_t^i$  ;

**end**

Combine all log signatures  $s_t = (s_t^1, \dots, s_t^p)$

---

### 2.3.2 Random Fourier Transforms

Random Fourier Transforms are used in [33] to model the return of financial price time series. They can be applied to the feature performance time-series at each time step as in Algorithm 4. The key idea is to approximate a mixture model of Gaussian kernels with trigonometric functions [21].

---

**Algorithm 4:** Random Fourier Transform [33]
 

---

**Input:** signal vector  $x_t \in \mathbb{R}^d$ , number of features sets  $p$ ,  
**Output:** transformed vector  $s_t \in \mathbb{R}^{14p}$

```

for  $1 \leq i \leq p$  do
  Sample  $w_i \sim \mathcal{N}(0, I_{d \times d})$ ;
  Set grid  $(\gamma_i)_{i=1}^4 = (0.1, 0.5, 1, 2, 4, 8, 16, 0.1, 0.5, 1, 2, 4, 8, 16)$ ;
  for  $1 \leq j \leq 7$  do
    | Set  $s_{t,14i+j} = \frac{1}{\sqrt{7p}} \sin(\gamma_j w_i^T x_t)$ 
  end
  for  $8 \leq j \leq 14$  do
    | Set  $s_{t,14i+j} = \frac{1}{\sqrt{7p}} \cos(\gamma_j w_i^T x_t)$ 
  end
end

```

---

### 2.3.3 Ridge Regression

Applying the above feature engineering methods, tabular features that have sizes greater than the number of observations are created. This results in an over-parameterised model where regularisation is required as there are multiple models that can perfectly fit the data. In this paper, ridge regression, which is a standard choice of linear regression models with L2-regularisation is used. Ridge regression has closed-form solutions and there is an efficient implementation which can calculate ridge regression models with different L2-regularisation on the same dataset.

### 2.3.4 Selection of Look-back Window

For all the feature engineering methods mentioned above, a look-back window needs to be selected. Choosing different sizes of look-back windows corresponds to extracting the dynamics of feature performances at different time scales in the data stream. The lookback can be set to a fixed size or be "infinite", which means using all the available history of the time series at the time of prediction.

## 3 Machine Learning Models for Tabular Datasets

There are rich literature comparing different machine learning approaches on tabular datasets [34, 35, 36, 37]. A key limitation of these studies is the most datasets chosen are static and small in size (with less than 200 features and less than 10k data rows). Here, we are working with dynamic datasets which are large in size (with more than 1000 numerical features and more than 200k data rows). While researchers hold different views on which of GBDT and MLP models are more suitable for (general purpose) tabular regression/classification tasks, many bench-marking studies [34, 35, 36] demonstrated that advance deep learning methods such as transformers [38] under-performed traditional approaches such as gradient boosting decision trees and multi-layer perceptron networks. These complex deep learning methods often require a huge amount of computational resources, limiting their use in large-scale real-time incremental learning systems.

In this paper, Gradient Boosting Decision Trees (GBDT) and multi-layer perceptron networks (MLP) are studied in detailed as both demonstrated strong performances in a many bench-marking studies [34, 35, 36] and efficient implementations exist for these algorithms which allows scalable model training and inference.

### 3.1 Gradient Boosting Models

Gradient Boosting Decision Trees is a standard tool for tabular data modelling. There are many efficient implementations, for example, XGBoost [39], LightGBM [40] and CatBoost [41]. In this paper, XGBoost is used as it offers good GPU acceleration and flexible feature sub-sampling at the node level.

**Gradient Boosting Algorithm** Gradient Boosting is a generic algorithm for combining base learners in a sequential manner to obtain better predictions. A common choice of base learners would be decision trees. The aim of (gradient) boosting is to reduce **bias** of the ensemble learner. The aim is different to that of bagging, which fits multiple independent base learners at the same time, and the ensemble learner has a lower **variance** than each base learner. For practical implementations, bagging and boosting can often be used together. For example, in XGBoost, multiple trees (forests) can be fit in each boosting round. However empirical experience (and many textbooks [42]) suggests boosting works better than bagging. Therefore, only a single tree is trained in each boosting round for the gradient boosting models used in this study. Algorithm 5 shows the pseudo-code for the general gradient boosting for a regression problem.

---

**Algorithm 5:** Gradient boosting algorithm [43, 44]

---

Given  $N$  data samples  $(\mathbf{x}_i, y_i), 1 \leq i \leq N$  with the aim to find an increasing better estimate  $\hat{f}(\mathbf{x})$  of the minimising function  $f(x)$  which minimise the loss  $\mathcal{L}(f)$  between targets and predicted values.  
 $\mathcal{L}(f) = \sum_i l(y_i, f(\mathbf{x}_i))$  where  $l$  is a given loss function such as mean square losses for regression problems.  
 Function  $f$  is restricted to the class of additive models  $f(\mathbf{x}) = \sum_{k=1}^K w_k h(\mathbf{x}, \alpha_k)$  where  $h(\cdot, \alpha)$  is a weak learner with parameters  $\alpha$  and  $w_k$  are the weights.  
 Initialise  $f_0(\mathbf{x}) = \arg \min_{\alpha_0} \sum_{i=1}^N l(y_i, h(\mathbf{x}_i, \alpha_0))$   
**for**  $k = 1 : K$  **do**  
     Compute the gradient residual using  $g_{ik} = - \left[ \frac{\partial l(y_i, f_{k-1}(\mathbf{x}_i))}{\partial f_{k-1}(\mathbf{x}_i)} \right]$   
     Use the weak learner to compute  $\alpha_k$  which minimises  $\sum_{i=1}^N (g_{ik} - h(\mathbf{x}_i, \alpha_k))^2$   
     Update with learning rate  $\lambda$   $f_k(\mathbf{x}) = f_{k-1}(\mathbf{x}) + \lambda h(\mathbf{x}, \alpha_k)$   
**end**  
**Return**  $f(\mathbf{x}) = f_K(\mathbf{x})$

---

**XGBoost Implementation** XGBoost [39] modifies the above "standard" gradient boosting algorithms with approximation algorithms in split finding. Instead of finding the best(exact) split by searching over all possible split points on all the features, a histogram is constructed where splitting is based on percentiles of features. XGBoost supports two different growth policies for the leaf nodes, where nodes closest to the root are split (depth-wise) or the nodes with the highest change of loss function are split (loss-guide). The default tree-growing policy is depth-wise and performs better in most benchmark studies. XGBoost also supports L1 and L2 regularisation of model weights. Other standard model regularisation techniques such as limiting the maximum depth of trees and the minimum number of data samples in a leaf node are also supported.

**Model Snapshots** For GBDT models, it is easy to extract model snapshots, defined as the model parameters captured at the different parts of the training process. This can be done without any additional memory costs at inference.

Model snapshots of a GBDT model can be obtained as follows. The snapshots start with the first tree and the number of trees to be used (the ending tree) are set to be 10%, 20%, ..., 100% of the number of boosting rounds. This trivially gives 10 different GBDT models representing different model complexities from a **single** model. To avoid early convergence of the learning process, the learning rate can be set to a small value.

### 3.2 Deep Learning Models

**Feature projection and Loss Function** Pearson correlation calculated on the whole **era** of target and predictions is used as the loss function at each training epoch. Feature projection, if needed, can be applied from the outputs of network architecture. The neutralised predictions are further standardised to zero mean and unit norm. The negative Pearson correlation of the standardised predictions and targets is then used as the loss function to train the network parameters.

**Training process** PyTorch Lightning [45] is used to build neural network models as it supports modular design and allows rapid prototyping. Early stopping is applied based on the validation set based on a given number of rounds (patience). The batch size of the neural network is set to be the size of each era. The Adam optimiser in PyTorch with the default settings for the learning rate schedule is used. L2-regularisation on the model weights is also applied. Gradient clipping is also be applied to prevent the gradient explosion problem for correlation-based loss functions.



**Architecture** The network architecture is a sequential neural network with two parts, firstly a "Feature Engineering" part which consists of multiple feature engineering blocks and then the "funnel" part which is a standard MLP with decreasing layer sizes.

Each feature engineering block has an Auto-Encoder-like structure, where the number of features is unchanged after passing each block. Setting a neuron scale ratio of less than 1 corresponds to the case of introducing a bottleneck to the network architecture so as to learn a latent representation of data in a lower dimensional space. Algorithm 6 shows how to create the feature engineering part of the network.

Funnel architecture, as used in [46] is an effective way to define the neuron sizes in a network for different input feature sizes. Algorithm 7 shows how to create the funnel part of the network.

Each Linear layer is followed by a ReLU activation layer and dropout layer where 10% of weights are randomly zeroed.

**Definition 5** (Linear Layer).

A Linear Layer  $(M_1, M_2)$  within a sequential neural network is a transformation  $X_2 = f(X_1)$  with input tensor  $X_1 \in \mathbb{R}^{N \times M_1}$  and output tensor  $X_2 \in \mathbb{R}^{N \times M_2}$  where  $N$  is the batch size of data. For a given non-linear activation function  $\sigma(\cdot)$  such as ReLU, let  $W \in \mathbb{R}^{M_2 \times M_1}$  be the weight tensor and  $b \in \mathbb{R}^{M_2}$  be the bias tensor to be learnt in the training process, the Linear layer is defined as

$$f(X_1) = \sigma(X_1 W^T + b)$$

---

**Algorithm 6:** Feature Engineering network architecture

---

**Input:** Input feature size  $M$ , Number of encoding layers  $L$ , neuron scale ratio  $r$

**Output:** Sequential Feature Engineering Network Architecture

**for**  $1 \leq l \leq L$  **do**

    Encoding Layer  $l$ : Linear layer  $(M, M * r)$

    Decoding Layer  $l$ : Linear layer  $(M * r, M)$

**end**

---



---

**Algorithm 7:** Funnel network architecture

---

**Input:** Input feature size  $M$ , Output feature size  $K$ , Number of intermediate layers  $L$ , neuron scale ratio  $r$

**Output:** Sequential Funnel Network Architecture

Input Layer: Linear layer  $(M, M * r)$

**for**  $1 \leq l \leq L$  **do**

    Intermediate Layer  $l$ : Linear layer  $(M * r^l, M * r^{l+1})$

**end**

Output Layer: Linear layer  $(M * r^{L+1}, K)$

---

## 4 Deep incremental learning model

A deep incremental learning model can be built using the tabular and factor-timing models as components. Algorithm 8 outlines the overall structure of the model. Each layer in the deep incremental learning model is trained sequentially. At the start of training in a layer, features and targets that are shared by each component model are prepared.

Each factor-timing and tabular model within the layer is trained in an incremental manner as described in Section 1, in which model parameters are updated as new data arrives. Each component model within a layer can be trained in parallel.

**Self-Similarity nature of model** The incremental learning model demonstrates self-similarity with a fractal-like structure. In other words, the overall model shared a similar structure with each of its components.

The incremental learning model can be interpreted as a stacked model with  $\sum_{i=1}^L K_i$  base learners trained with  $L$  iterations, where  $K_i$  base learners are trained in the  $i$ -th iteration. Ideas from bagging and boosting are integrated within the model. Each layer consists of multiple models trained in parallel as in bagging so that variance is reduced by combining predictions from different models within a layer. The stacked model here can be considered as a degenerate case of boosting where the learning rate of the target is set to zero, such that the target is not adjusted based on

**Algorithm 8:** Deep Incremental learning model with model stacking

---

**Input:** Temporal Tabular Dataset  $\{X_i, y_i\}_{1 \leq i \leq T}$ , number of layers  $L$ , the number of models within each layer  $(K_1, \dots, K_L)$ , training size  $a$ , data embargo  $b$ ,

**for**  $1 \leq l \leq L$  **do**

Calculate the start of model predictions for layer  $l$  as  $1 + l(a + b)$

Prepare Features  $\{X_j^l\}$  where  $(l - 1)(a + b) \leq j \leq (l - 1)(a + b) + a$  where  $X_j^l$  consists of predictions from previous layers.

**for**  $1 \leq k \leq K_L$  **do**

Perform Data and Feature Sub-sampling for each component model

Train component model using features  $\{X_j^l, y_j\}$

Obtain predictions of the model from era  $1 + l(a + b)$  onward

**end**

**end**

---

predictions from previous layers between layers. The above architecture can be modified to allow for boosting between layers if needed.

The incremental learning model can also be interpreted as a neural network model where each node is now a machine learning model instead of a parameter. As predictions from previous layers can be used as features for the following layers, this simulates the residual connections in some neural network architecture. Each layer in the model will refine the prediction as neural networks.

The self-similarity structure stems from the fact that the component models within each layer can be chosen to be Gradient Boosting Decision Trees (GBDT) and Multi-layer Perceptron Neural Networks (MLP) so that the learning mechanism of each individual component is similar to the overall model. The self-similarity structure can be extended repeatedly by interpreting the incremental learning model as a base learner for another incremental learning model. Therefore, the complexity of the incremental learning model is not constrained and can be applied in theory to any machine learning problems for a required complexity.

**Trees and Neural Networks are alike** Gradient Boosting Decision Trees (GBDT) and neural networks are usually considered two distinct classes of machine learning models. However recent researches such as soft decision trees [47] and transformers [48] suggests it is possible to make neural network models more tree-like. Similarly, replacing the base learner in GBDT models with weakly trained shallow nets can make GBDT models more neural-like.

A better way to understand machine learning models is to place each model in a **continuous** spectrum of model density, from sparse to dense representations/structures. Decision Trees are an example of sparse models. Neural networks are an example of dense models. Most machine learning models employ decision rules or regression with non-linear activation as the basic operations of learning. Depending on the exact algorithm used, a machine learning model will consist of a mix of dense and sparse structures, and thus a binary classification of the nature of the model is not suitable.

In most applications, the choice of model depends on the nature of the input features. In general, sparse models are good for unstructured data or categorical features. Dense models are good for structured data (For example images, text) or numerical features.

**Adaptive nature of model** The incremental learning model supports **dynamic** model training, as parameters of each component model are updated regularly to adapt to distributional shifts in data. Under the traditional machine learning framework, hyper-parameters of machine learning models are selected by cross-validations. A big limitation of using cross-validations for incremental learning problems is that the optimal hyper-parameters based on a **single** test period might not work in future. This is replaced by **dynamic** hyper-parameter optimisation in the incremental learning model. Predictions from previous layers based on different model hyper-parameters are combined in the next layer. The model parameters in the next layer can then be interpreted as the dynamic soft selection of hyper-parameters. Soft hyper-parameter selection is also related to Bayesian methods of learning the regularisation hyper-parameter of regression models. Instead of attempting to derive the posterior distributions of the model hyper-parameters, which is difficult when there are no closed-form solutions, the weight parameters can be considered as an approximation to the posterior distribution.

Model stacking over deep learning models with different random seeds [49], different hyper-parameters [50] and [51] are shown to demonstrate robust performances for **static** datasets. The deep incremental learning model presented here can be considered as an extension of these techniques to **stream** datasets and other machine learning models in general.

In particular, models incrementally trained with data streams with different sizes of training datasets and timesteps between model updates can be stacked to obtain more robust predictions.

**Universal Approximation** It is well-known that MLP and GBDT models have the universal function approximation property [31]. Deep Learning models for sequences, such as LSTM [52] are also shown to have the universal function approximation property for any dynamical systems. The above incremental learning model is a composition of models that each has the universal function approximation property, therefore, it also has the universal approximation property for the underlying stochastic processes that drive the infinite data generation of the temporal tabular datasets.

#### 4.1 Connections with common machine learning tasks

The incremental learning model presented above is a complete end-to-end autoML tool which transforms the given features into predictions. Different machine learning tasks, such as feature engineering and model stacking are integrated within the model as demonstrated in the following. A key insight is that tabular models such as GBDT or MLP can be used repeatedly in different layers of the model to achieve the purpose of different machine learning tasks, which were previously considered separate tasks. In particular, even with just two building blocks, GBDT and MLP models, very complex and effective incremental learning models can be built.

**Feature Engineering/Selection** Feature Engineering is an important part of modelling tabular data. A wide range of standard feature engineering methods, including random non-linear transforms [53] and data-based methods such as feature tools [54] are proposed to learn higher-order feature relationships. Standard tabular models are then trained on the original features with the newly created features. More recent methods would use deep learning methods, in particular sequential attention for feature selection and engineering, examples include TabNet[38] and TabTransformer [55]. For these models, feature engineering and tabular data modelling are performed in a single model. A major limitation of these models is high (active) memory consumption during model training. Another limitation is that many feature engineering methods are developed for **static** datasets whereas a set of relationships learn on **fixed** training set. Unless these feature engineering components are retrained regularly as the downstream tabular models, the learnt relationships might not hold over distribution shifts of data.

Most feature engineering methods applied to tabular data are a transformation from tabular features to another set of tabular features and are not much different than a collection of weakly trained tabular models. Under the incremental learning framework, predictions from shallow trees and networks in the early layers can be considered as new features generated for downstream layers. It is not strictly necessary to make a distinction between feature engineering and tabular modelling. Training models in a multi-step layered structure avoids the look-ahead bias issue naturally.

Feature Selection can be considered a special case of feature engineering where the feature engineering transformation is a Boolean mask.

**Feature Projection** Feature Projection and its dynamic variant (Dynamic Feature Projection) introduced in the previous Numerai study [18] can also be reformulated under the incremental learning framework as follows.

The need of feature projection is based on the assumption that unconstrained model training methods will result in model predictions that are explained by a small subset of features. While these models work well under data regimes that are similar to the training set, these models will suffer when there are distributional shifts in data. In investment terminology, unconstrained models are like investment portfolios concentrated in a small amount of assets, and therefore carry high risks under changes of market regimes.

Feature projection, which can be used to limit both the maximal feature concentration risks and (linear)-dependencies of the model on the selected features can mitigate the impact of data distributional shifts by both spreading the model risk across a wider range of features and focusing more on the non-linear relationships between features. Dynamic feature projection suggests for data streams with distributional shifts, the optimal subset of features for projection is **dynamic** rather than **fixed**.

A key issue that remained unresolved in the previous study [18] is that the degree of feature projection and the size of the subset of features to be projected is given by useful heuristics, rather than being optimised based on data available. Clearly, these parameters can be learned from the dataset and adjusted according to data distribution shifts. Under the incremental learning model, model predictions undergoing different feature projection processes can be combined as a soft selection of model hyper-parameters. The optimal degree of feature projection depends on both the feature correlation structure and the target construction process.

**Advanced Architectures of neural networks** Many advanced architectures of neural networks outperform basic multi-layer perceptron networks [38, 47, 55] on a small amount of datasets presented in the research, which all of the datasets studied are **static** machine learning problems. However, some research suggest the contrary when running the models using different hyper-parameters or on **different** datasets [37, 36, 35]. As a result, the decision of whether advanced architectures are better than standard MLP for incremental learning tasks on tabular datasets remains an open problem.

For most incremental learning problems, the only purpose is to generate high-quality and robust forecasts on **future** observations using models trained on **past** data only. A good performance based on **historical** data is not relevant if the backtest performances cannot carry on into the future.

An inherent limitation in interpreting research results from machine learning on temporal-based datasets is that results reported in a published journal article are only a **snapshot** on the underlying data stream. When there are significant distribution shifts in data, conclusions can become invalid on new data arrived.

Deep learning methods with advanced architectures are inherently difficult to interpret. Under the incremental learning framework presented here which combines standalone machine learning models **component-wise**, each component model can be evaluated independently and compared to inspect the changes in prediction quality in different layers.

**Model Stacking/Selection** Stacking is a simple but highly effective technique to combine different machine learning model predictions. The concept of stacking is not limited to machine learning. In finance, portfolio optimisation are studied in detail to improve investment returns, where a convex optimisation is solved at each time step to find the linear combination of assets or strategies that maximise risk-adjusted return.

Under the incremental learning framework, model stacking can be performed dynamically, which combined predicted ranking from different machine learning models at each era with different weights. Instead of considering model stacking as a **separate** step to model training, model stacking can be incorporated as an extra layer in the incremental learning model.

## 5 Case Study with Numerai competition

### 5.1 Numerai Dataset

**Features and Targets** The v4.1 of the Numerai dataset [56], which consists of a total of 1586 features is used for analysis in this paper. The dataset is in the format of a Temporal Tabular dataset. The dataset contains multiple targets, which represent normalised stock returns by different statistical methods. A new target, 'target-cyrus-v4-20' is used for scoring the trained models. Common risk factors in stock trading are removed during the target construction process. As a result, feature projection is not necessary for models trained with this target and will not be used in the following analysis.

To reduce computational time for grid searches, two different methods are used for feature selection. The first one is by random sampling and the second one is by taking the median over correlated features.

In the first method, a random sample of features can be drawn from the 1586 features in the dataset.

The second method is used to reduce the dimensionality of data when calculating the feature importance's time series. This method makes use of the observed feature correlation structure in the Numerai dataset. The features that demonstrate high multicollinearity are grouped and replaced with their Median (called 'Group X Median'). A reason to use Median instead of Mean is to preserve the binned data structures (as each feature is binned values between  $-2$  to  $2$  after making the mean zero).

The features from Numerai can be separated into two different sets. One of the sets consists of 1445 features which can be grouped in 289 groups by the multicollinearity criteria (Pearson correlation  $> 0.9$ ) consistently in different eras. Each group consists of an equal number of 5 features. This set of 1445 features is called **Set A**. The other set consists of 141 features that cannot be grouped by the multicollinearity criteria. This set of 141 features is called **Set B**. For features in **Set A**, the median of each group is computed. This group of 289 Median features and the **Set B** features, in total 430 features are then used to calculate the **feature performances** time-series, which are then used to build a factor timing portfolio described above. The feature performance time series is calculated based on the Pearson correlation of each feature with the target in each era.

**Data Lag** Setting the data lag for predictions would depend on the robustness of the data pipeline from Numerai. The theoretical minimum for the scoring target to resolve is 5 weeks (4 weeks of market data and 1 week for data

processing) but some participants has pointed out it can take up to 6 weeks to resolve the target. To take account into both the data lag for the data generation process from Numerai and the time to train models, a conservative data lag of 15 weeks is used for training the models.

**Scoring Function** Numerai calculates a variant of Pearson correlation score with the following formula [57].

Let  $y_p$  be the predictions ranked between 0 and 1,  $y_t$  be the targets centred between -0.5 and 0.5,  $\Phi(\cdot)$  be the Distribution function of standard Gaussian,  $\mathbf{sgn}(\cdot)$  and  $\mathbf{abs}(\cdot)$  be the element-wise sign and absolute value function, then Numerai Corr  $\rho_n$  is given by

$$\begin{aligned} y_g &= \Phi^{-1}(y_p) \\ y_{g15} &= \mathbf{sgn}(y_g) \cdot \mathbf{abs}(y_g)^{1.5} \\ y_{t15} &= \mathbf{sgn}(y_t) \cdot \mathbf{abs}(y_t)^{1.5} \\ \rho_n &= \mathbf{Corr}(y_{g15}, y_{t15}) \end{aligned}$$

Corr is the Pearson correlation function. The purpose of applying a power transformation is to emphasise the contribution from the highest and lowest predictions.

## 6 Training incremental learning models with Numerai data

A two-step process is used to train incremental learning models with the Numerai dataset. The first step is to use data before Era 800 for the hyper-parameter optimisation of tabular and factor-timing models. After that, the incremental learning model is run to get online predictions from Era 800 onward.

### 6.1 Hyper-parameter optimisation for tabular models

For different tabular models introduced in section 3, hyper-parameter optimisation is performed using data before Era 800. The training and validation set is data between Era 1 and Era 600, with 25% of data as the validation set. Due to memory constraints, data sub-sampling is applied during model training. 25% of the eras in the training period is used with sampling performed at regular intervals. The performance of the models between Era 601 and Era 800 (evaluation period) is then used to select hyper-parameters for the tabular models. The Mean Corr and Sharpe Ratio of the prediction ranking correlation in the evaluation period is reported. Details of computing these performance metrics can be found in [ThomasW23]. Due to memory issues for training neural network models, a global feature selection process is used to select 50% of the 1586 features at the start of each model process by random.

**Factor Timing Models** Different factor timing models are trained as described in Section 2.

Signature transforms and random Fourier transforms models with different model complexities, defined as the ratio of the number of time-series features computed to the number of data points in the time-series are trained. In order to study models from different complexity regimes, the model complexity is varied between 0.1 and 10 to obtain models from under-parameterised regime to over-parameterised regime.

Table 1 reported the model performances in the evaluation period for factor timing models based on exponential moving averages. Tables 2, 3 reported the model performances in the evaluation period for signatures transforms, random Fourier transforms models, averaged over different ridge regularisation parameters (0.01,0.1,1.0,10.0,100.0) and 5 different random seeds. The lookback period of calculating the signatures and random Fourier transforms is set to using all the available data

Exponential Moving Averages models with weight decay between 0.0025 and 0.002 performed better than signatures and random Fourier transforms models in general. Weight decay of 0.005 is the best weight decay parameter between eras 601 and 800. For signature transforms models, higher complexity gives slightly better performances but is not significant. For random Fourier transforms models, higher complexity gives poorer performances when the model complexity ratio is higher than 2.5.

Repeating the above analysis between Eras 601 and 1050, tables 4, 5 and 6 show performances of statistical rule-based models, signature and random Fourier transforms models. Exponential Moving Averages models with weight decay 0.005 has the highest Sharpe ratio and the second highest Mean Corr. However, models with weight decay 0.01 and 0.02 have a higher Calmar ratio. Signature transforms models have similar performances over different model complexities. Signature transforms models performed better than random Fourier transforms models over different model complexities. Exponential Moving Average models with suitable weight decay parameters performed the best.

Weight Decay	Mean Corr	Sharpe	Calmar
0.000625	0.0047	0.3181	0.0273
0.00125	0.0057	0.3590	0.0378
0.0025	0.0082	0.4791	0.0598
0.005	0.0091	0.5488	0.0850
0.01	0.0088	0.5396	0.0757
0.02	0.0085	0.5161	0.0741
0.04	0.0068	0.4157	0.0360
0.08	0.0058	0.3614	0.0260
0.16	0.0046	0.2930	0.0203

Table 1: Exponential Moving Averages models

Lookback	Model Complexity	Mean Corr	Sharpe	Calmar
All	0.1	0.0074 ± 0.0008	0.4392 ± 0.0503	0.0582 ± 0.0071
All	0.25	0.0076 ± 0.0009	0.4517 ± 0.0571	0.0605 ± 0.0102
All	0.5	0.0077 ± 0.0009	0.4637 ± 0.0630	0.0635 ± 0.0129
All	0.75	0.0079 ± 0.0010	0.4721 ± 0.0653	0.0658 ± 0.0140
All	1	0.0080 ± 0.0010	0.4800 ± 0.0702	0.0688 ± 0.0171
All	2.5	0.0082 ± 0.0010	0.4923 ± 0.0671	0.0685 ± 0.0123
All	5	0.0083 ± 0.0009	0.5005 ± 0.0660	0.0701 ± 0.0142
All	7.5	0.0083 ± 0.0008	0.5038 ± 0.0628	0.0720 ± 0.0162
All	10	0.0084 ± 0.0008	0.5056 ± 0.0607	0.0727 ± 0.0184

Table 2: Signature transform models

Lookback	Model Complexity	Mean Corr	Sharpe	Calmar
All	0.1	0.0077 ± 0.0008	0.4684 ± 0.0513	0.0585 ± 0.0116
All	0.25	0.0082 ± 0.0008	0.4954 ± 0.0496	0.0632 ± 0.0120
All	0.5	0.0075 ± 0.0008	0.4551 ± 0.0441	0.0570 ± 0.0117
All	0.75	0.0075 ± 0.0010	0.4499 ± 0.0540	0.0525 ± 0.0063
All	1	0.0067 ± 0.0005	0.3975 ± 0.0298	0.0502 ± 0.0075
All	2.5	0.0065 ± 0.0011	0.3900 ± 0.0651	0.0530 ± 0.0107
All	5	0.0029 ± 0.0025	0.1443 ± 0.1316	0.0207 ± 0.0194
All	7.5	0.0019 ± 0.0020	0.1284 ± 0.1304	0.0174 ± 0.0182
All	10	0.0024 ± 0.0021	0.1523 ± 0.1309	0.0182 ± 0.0191

Table 3: Fourier transform models between Eras 601 and 800

Comparing the partial results between Eras 601 and 800 and the "full" results between Eras 601 and 1050 demonstrates why selecting model hyper-parameters for incremental learning tasks on non-stationary data streams based on **finite** snapshots of data might not be robust over longer horizons. Some hyper-parameters might perform better than others over a short amount of time but not over longer observations.

Weight Decay	Mean Corr	Sharpe	Calmar
0.000625	0.0044	0.2540	0.0090
0.00125	0.0058	0.3099	0.0111
0.0025	0.0087	0.4220	0.0152
0.005	0.0086	0.4992	0.0248
0.01	0.0077	0.4977	0.0454
0.02	0.0075	0.4759	0.0436
0.04	0.0059	0.3594	0.0211
0.08	0.0045	0.2494	0.0108
0.16	0.0029	0.1598	0.0049

Table 4: Exponential Moving Averages models between Era 601 and 1050

Lookback	Model Complexity	Mean Corr	Sharpe	Calmar
All	0.1	0.0079 ± 0.0006	0.4269 ± 0.0370	0.0196 ± 0.0030
All	0.25	0.0079 ± 0.0005	0.4334 ± 0.0373	0.0216 ± 0.0062
All	0.5	0.0080 ± 0.0005	0.4420 ± 0.0433	0.0236 ± 0.0093
All	0.75	0.0080 ± 0.0005	0.4468 ± 0.0451	0.0243 ± 0.0097
All	1	0.0081 ± 0.0005	0.4516 ± 0.0468	0.0250 ± 0.0096
All	2.5	0.0081 ± 0.0005	0.4557 ± 0.0428	0.0268 ± 0.0089
All	5	0.0080 ± 0.0007	0.4486 ± 0.0498	0.0267 ± 0.0095
All	7.5	0.0079 ± 0.0009	0.4430 ± 0.0622	0.0265 ± 0.0121
All	10	0.0078 ± 0.0011	0.4384 ± 0.0737	0.0260 ± 0.0129

Table 5: Signature transform models between Era 601 and 1050

Lookback	Model Complexity	Mean Corr	Sharpe	Calmar
All	0.1	0.0071 ± 0.0005	0.3834 ± 0.0235	0.0163 ± 0.0028
All	0.25	0.0070 ± 0.0010	0.3737 ± 0.0452	0.0152 ± 0.0025
All	0.5	0.0064 ± 0.0008	0.3525 ± 0.0364	0.0151 ± 0.0038
All	0.75	0.0064 ± 0.0006	0.3416 ± 0.0270	0.0123 ± 0.0018
All	1	0.0063 ± 0.0006	0.3364 ± 0.0246	0.0136 ± 0.0026
All	2.5	0.0057 ± 0.0012	0.3141 ± 0.0561	0.0146 ± 0.0031
All	5	0.0019 ± 0.0018	0.0937 ± 0.0940	0.0070 ± 0.0069
All	7.5	0.0016 ± 0.0010	0.0997 ± 0.0632	0.0051 ± 0.0037
All	10	0.0014 ± 0.0014	0.0893 ± 0.0870	0.0059 ± 0.0060

Table 6: Fourier transform models between Eras 601 and 1050

For models hyper-parameters that do not depend on randomness, such as exponential moving averages or other rule-based trend indicators, hypothesis testing cannot be applied directly to select hyper-parameters directly. Instead, soft hyper-parameter selection within an incremental learning framework are used to find an optimal **dynamic** combination of predictions.

A deep XGBoost model is created by combining the 9 exponential moving averages (EMA) models incrementally. For every 10th era, a shallow XGBoost model with the following hyper-parameters is trained using model predictions from the most recent 185 eras (with suitable data lag). Monotonic constraints are imposed so that we do not assign negative weights to the model predictions.

- Grow policy: Depth-wise
- Number of boosting rounds: 20
- Early Stopping 20
- Learning rate: 0.1
- Max Depth: 8
- Max Leaves: 128
- Min Samples per node: 10
- Data subsample: 0.75
- Feature subsample by tree: 0.75
- Feature subsample by level/node: 1
- L1 regularisation: 0.001
- L2 regularisation: 0.001

In table 7, the performance from the deep EMA model (Deep) is compared with each of the EMA models with different weight decays (Base) in Era 601 to Era 1050. Deep incremental learning can create better predictions by combining EMA models with different weight decays.

Table 7: Deep EWMA models

Method	Mean Corr	Sharpe	Calmar
Base	0.0062 $\pm$ 0.0021	0.3586 $\pm$ 0.1233	0.0206 $\pm$ 0.0148
Deep	0.0087 $\pm$ 0.0001	0.4773 $\pm$ 0.0062	0.0282 $\pm$ 0.0014

**XGBoost** RMSE, the standard loss function for regression problems is used to train the XGBoost models. Early stopping based on **Pearson** correlation in the validation set is applied to control the model complexity. A grid search is performed to select the data sub-sample and feature sub-sample ratios of the XGBoost models.

- Data subsample: 0.25,0.5,0.75
- Feature subsample by tree: 0.25,0.5,0.75

Other hyper-parameters of the XGBoost models are fixed as follows.

- Grow policy: Depth-wise
- Number of boosting rounds: 5000
- Learning rate: 0.01
- Early stopping: 250
- Max Depth: 8
- Max Leaves: 128
- Min Samples per node: 10
- Feature subsample by level/node: 1
- L1 regularisation: 0.001
- L2 regularisation: 0.001

Table 8 compares performances of XGBoost models by different data subsample ratios and feature subsample ratios **without** feature projection, mean and standard deviation over 5 different random seeds are reported.

Calmar ratio is the performance metric with the most variance between different random seeds, suggesting selecting models based on Calmar ratio is not robust. Mean Corr is the least varied metric between random seeds and therefore should be used for hyper-parameter selection.

Models with data sub-sampling of 75% performed better than models with data sub-sampling of 50% and 25%, with a lower variance between model performances over different random seeds also. For the study of incremental learning in the next section, the data sub-sampling is set to 75% and the feature sub-sampling is set to 75%. Selection is based on having the highest Mean Corr.

Table 8: XGBoost models without feature projection

Data subsample	Feature subsample	Mean Corr	Sharpe	Calmar
0.75	0.75	0.0262 $\pm$ 0.0007	1.3450 $\pm$ 0.0643	0.6316 $\pm$ 0.1958
0.75	0.50	0.0259 $\pm$ 0.0006	1.3372 $\pm$ 0.0440	0.6682 $\pm$ 0.1698
0.75	0.25	0.0257 $\pm$ 0.0004	1.3029 $\pm$ 0.0264	0.5339 $\pm$ 0.1332
0.50	0.75	0.0240 $\pm$ 0.0007	1.2146 $\pm$ 0.0485	0.3911 $\pm$ 0.0448
0.50	0.50	0.0245 $\pm$ 0.0013	1.2786 $\pm$ 0.1002	0.5224 $\pm$ 0.2025
0.50	0.25	0.0242 $\pm$ 0.0014	1.2139 $\pm$ 0.0602	0.3413 $\pm$ 0.0409
0.25	0.75	0.0211 $\pm$ 0.0011	1.0994 $\pm$ 0.0592	0.2488 $\pm$ 0.0785
0.25	0.50	0.0213 $\pm$ 0.0012	1.0982 $\pm$ 0.0621	0.2405 $\pm$ 0.0786
0.25	0.25	0.0211 $\pm$ 0.0012	1.1156 $\pm$ 0.1068	0.3492 $\pm$ 0.1011

**Neural Networks** Neural Networks models **without** feature projection are trained with different number of encoding and funnel layers using the architecture described in Section 3.

- Degree of Feature projection: 0.0
- Number of Feature Eng Layers: 0,1,2,3,4



- Number of Funnel Layers: 1,2,3

Other hyper-parameters of the neural network models are fixed in the grid search as follows.

- Loss Function: Pearson Corr
- Number of epochs: 100
- Early Stopping: 10
- Learning Rate: 0.001
- Dropout: 0.1
- Encoding Neuron Scale: 0.8
- Funnel Neuron Scale: 0.8
- Gradient Clip: 0.5

In Table 9 shows the performances of neural network models with different network architectures over 5 different random seeds, where mean and standard deviation of Mean Corr, Sharpe and Calmar ratios are reported.

The architecture with the highest Mean Corr is the model without feature engineering layers and a standard MLP model with 2 linear layers. When the number of funnel layers equals to 1, the MLP model is equivalent to a (regularised) linear model and has the worst performance. Increasing the number of feature engineering layers does not significantly improve Mean Corr. As model complexity increases, model performances are more varied over different random seeds, suggesting the lack of robustness of deep neural network models.

Table 9: Neural Network models without feature projection

Feature Eng Layers	Funnel Layers	Mean Corr	Sharpe	Calmar
0	1	0.0159 ± 0.0016	0.8042 ± 0.0631	0.0826 ± 0.0087
0	2	0.0235 ± 0.0001	1.1344 ± 0.0119	0.2692 ± 0.0201
0	3	0.0223 ± 0.0005	1.0478 ± 0.0372	0.2117 ± 0.0072
1	1	0.0222 ± 0.0003	1.0509 ± 0.0112	0.2118 ± 0.0068
1	2	0.0216 ± 0.0003	1.0061 ± 0.0377	0.2021 ± 0.0128
1	3	0.0224 ± 0.0003	1.0575 ± 0.0121	0.2212 ± 0.0269
2	1	0.0217 ± 0.0004	1.0176 ± 0.0357	0.2104 ± 0.0178
2	2	0.0218 ± 0.0009	1.0346 ± 0.0571	0.2005 ± 0.0076
2	3	0.0226 ± 0.0006	1.0754 ± 0.0352	0.2348 ± 0.0242
3	1	0.0224 ± 0.0006	1.0467 ± 0.0402	0.2226 ± 0.0281
3	2	0.0221 ± 0.0009	1.0564 ± 0.0441	0.2332 ± 0.0291
3	3	0.0217 ± 0.0007	1.0245 ± 0.0414	0.2049 ± 0.0156
4	1	0.0215 ± 0.0006	1.0131 ± 0.0192	0.1980 ± 0.0146
4	2	0.0219 ± 0.0010	1.0490 ± 0.0673	0.2229 ± 0.0309
4	3	0.0218 ± 0.0017	1.0459 ± 0.0880	0.2513 ± 0.0229

**Model Snapshots of XGBoost models** Traditional machine learning suggests there exists an optimal model complexity where the trade-off of bias and variance is optimal (for a loss function that behaves like the Mean-Squared error). However, modern machine learning research suggests using an over-parameterised model might improve performance in a test set even when model training loss cannot be further improved. The improvement is significant in cases where the model specification is incomplete and low signal-to-noise ratio in the given features. This counter-intuitive phenomenon is explored in different research papers [58, 59, 60, 61] from both theoretical and empirical perspectives.

The two viewpoints are summarised as follows.

- Viewpoint 1: (Classical Approach): There exists an optimal model complexity which can be found by performing bootstrapping-like procedures, such as cross-validation.
- Viewpoint 2: (Modern Approach): Over-parameterised model will outperform the optimal model under the classical approach.

XGBoost models are trained **without** early stopping for 5000 rounds and learning rate of 0.01 for 5 different random seeds. Detailed hyper-parameters are listed below.

- Grow policy: Depth-wise
- Number of boosting rounds: 5000
- Learning rate: 0.01
- Max Depth: 8
- Max Leaves: 128
- Min Samples per node: 10
- Data subsample: 0.75
- Feature subsample by tree: 0.75
- Feature subsample by level/node: 1
- L1 regularisation: 0.001
- L2 regularisation: 0.001

Model snapshots are created by running the first 10%, 20%, ..., 100% of boosting rounds during inference. Performances of model snapshots from Era 601 to Era 800 are reported in table 10. Increasing the number of boosting rounds does not significantly improve Mean Corr. Models with around 1000-1500 boosting rounds have the highest Mean Corr. Sharpe ratios do not change significantly for models with more than 1500 boosting rounds. Models with 4000 boosting rounds have the highest Calmar ratio averaged over the random seeds but are also the most varied. It suggests that over-parameterised models might be able to reduce the Max Drawdown and other downside risks in predictions. However, it cannot be ruled out whether over-parameterised models performed better due to chance.

Table 10: Model Snapshots of XGBoost Models (Max Boosting rounds is 5000)

Snapshot	Mean Corr	Sharpe	Calmar
0.1	$0.0248 \pm 0.0005$	$1.2390 \pm 0.0419$	$0.4566 \pm 0.0799$
0.2	$0.0264 \pm 0.0006$	$1.3673 \pm 0.0426$	$0.6460 \pm 0.1041$
0.3	$0.0262 \pm 0.0006$	$1.4057 \pm 0.0637$	$0.7951 \pm 0.1211$
0.4	$0.0255 \pm 0.0007$	$1.4040 \pm 0.0552$	$0.8435 \pm 0.1663$
0.5	$0.0247 \pm 0.0005$	$1.3882 \pm 0.0387$	$0.9256 \pm 0.2884$
0.6	$0.0242 \pm 0.0004$	$1.3935 \pm 0.0406$	$1.1110 \pm 0.3865$
0.7	$0.0238 \pm 0.0003$	$1.4009 \pm 0.0506$	$1.1242 \pm 0.3917$
0.8	$0.0234 \pm 0.0005$	$1.3973 \pm 0.0421$	$1.3520 \pm 0.5284$
0.9	$0.0228 \pm 0.0005$	$1.3610 \pm 0.0357$	$1.1738 \pm 0.4327$
1.0	$0.0223 \pm 0.0005$	$1.3560 \pm 0.0320$	$1.0753 \pm 0.3592$

**Conclusion** Factor timing models, which are based on learning the dynamics of weights from the feature correlations on each era under-performed other tabular models such as XGBoost and MLP. In fact, feature engineering models do not perform better than simple rule-based models when evaluated over a long enough timeframe.

The Numerai dataset demonstrates a very strong non-stationary nature such that the linear weights of the regression model trained on each era cannot be effectively used to predict future weights. In other words, **linear** relationships between features and target is not stable such that forecast cannot be made accurately using historical values. It suggests the dataset should be modelled with tabular machine learning models, with regular updates on model weights, rather than using time-series methods to predict the regression parameters for each era.

Exponential Moving Averages models have a strong and robust performance compared to other factor timing models despite their simplicity. The key hyper-parameter, weight decay can be selected using a deep incremental learning framework which adjust dynamically over time.

XGBoost models performed better than MLP models over a wide range of hyper-parameters. The binned nature of features favours the use of decision trees over neural networks.

A key design choice for XGBoost models is whether to apply early stopping, as it reflects two different viewpoints (Classical vs Modern) towards optimal model complexity. Mean Corr drops slightly when the number of boosting rounds increases beyond a threshold around the early stopping criteria, suggesting early stopping can be applied to improve model performances. However, large XGBoost models can reduce the downside risks of models within the period shown but it is not certain whether the effect is significant.

Increasing complexity of MLP models cannot improve model performances as expected by the Modern ML viewpoint. The best performance is achieved by a standard MLP with two layers, which provides the minimal amount of non-linearity required so that the model does not degenerate to a ridge regression model. As suggested in [60], the performance of over-parameterised models are affected by a myriad of factors including model architecture and training process. It cannot be ruled out that there are other model architectures that can make deep learning models performing better than XGBoost. Only the most basic neural network architectures are considered here due to computational resources constraints. However, as suggested from research on bench-marking of tabular ML models [36], recent deep learning models for tabular data such as TabNet does not always perform better than XGBoost.

## 6.2 Incremental Learning model for XGBoost models

The XGBoost models with the optimised design choices (based on data up to Era 800) are used in incremental learning models with different training sizes and retrain periods. Train size is how many eras of data are used to create the training and validation set. retrain period represents how often the model parameters are updated with the latest data. A retrain period of 100 means the model is retrained every 100th era.

**Adjusting the retrain period** The train size of models is fixed to be 585 as above. The retrain period is set to be 400,200,100,50,25, respectively. Table 11 lists the performances of the XGBoost models trained with the same optimised hyper-parameters between Era 801 and Era 1050 over 5 different random seeds. Retraining models more frequently improves model performances up to a retraining period of 50.

Table 11: XGBoost Models with different retrain periods, train size is fixed to 585

retrain period	Mean Corr	Sharpe	Calmar
25	0.0223 $\pm$ 0.0010	1.0854 $\pm$ 0.0419	0.2573 $\pm$ 0.0232
50	0.0224 $\pm$ 0.0007	1.1096 $\pm$ 0.0385	0.2975 $\pm$ 0.0305
100	0.0206 $\pm$ 0.0004	1.0134 $\pm$ 0.0352	0.2739 $\pm$ 0.0250
200	0.0210 $\pm$ 0.0004	1.0166 $\pm$ 0.0295	0.3010 $\pm$ 0.0605
400	0.0192 $\pm$ 0.0007	0.9293 $\pm$ 0.0632	0.1445 $\pm$ 0.0382

**When train size is small** Tables 12, 13, 14, 15, 16 list the model performances when train size is set to 485,385,285,185,85 with different retrain periods. Model performances drop as train size is decreased. Retraining models more frequently has limited effects on model performances. All models with train sizes less than or equal to 485 have smaller Sharpe ratios than models with train sizes 585.

Table 12: XGBoost Models with different retrain periods, train size is fixed to 485

retrain period	Mean Corr	Sharpe	Calmar
25	0.0170 $\pm$ 0.0010	0.8406 $\pm$ 0.0611	0.1230 $\pm$ 0.0279
50	0.0188 $\pm$ 0.0006	0.8885 $\pm$ 0.0486	0.1281 $\pm$ 0.0288
100	0.0176 $\pm$ 0.0007	0.8394 $\pm$ 0.0233	0.1191 $\pm$ 0.0226

Table 13: XGBoost Models with different retrain periods, train size is fixed to 385

retrain period	Mean Corr	Sharpe	Calmar
25	0.0164 $\pm$ 0.0007	0.7451 $\pm$ 0.0360	0.0915 $\pm$ 0.0210
50	0.0177 $\pm$ 0.0004	0.8109 $\pm$ 0.0338	0.0999 $\pm$ 0.0182
100	0.0160 $\pm$ 0.0006	0.7438 $\pm$ 0.0287	0.0902 $\pm$ 0.0178

Table 14: XGBoost Models with different retrain periods, train size is fixed to 285

retrain period	Mean Corr	Sharpe	Calmar
25	0.0125 $\pm$ 0.0014	0.6511 $\pm$ 0.0655	0.0776 $\pm$ 0.0117
50	0.0140 $\pm$ 0.0017	0.6733 $\pm$ 0.0776	0.0779 $\pm$ 0.0287
100	0.0130 $\pm$ 0.0008	0.6209 $\pm$ 0.0381	0.0716 $\pm$ 0.0237

Table 15: XGBoost Models with different retrain periods, train size is fixed to 185

retrain period	Mean Corr	Sharpe	Calmar
25	0.0081 $\pm$ 0.0017	0.4278 $\pm$ 0.0993	0.0306 $\pm$ 0.0165
50	0.0073 $\pm$ 0.0015	0.3779 $\pm$ 0.0823	0.0297 $\pm$ 0.0139

Table 16: XGBoost Models with different retrain periods, train size is fixed to 85

retrain period	Mean Corr	Sharpe	Calmar
25	0.0059 $\pm$ 0.0012	0.3318 $\pm$ 0.0787	0.0294 $\pm$ 0.0143
50	0.0051 $\pm$ 0.0015	0.2708 $\pm$ 0.0813	0.0230 $\pm$ 0.0137

**When training size is larger** Tables 17 and 18 list the performances of the XGBoost models trained with the same optimised hyper-parameters between Era 801 and Era 1050, with the train size increased to 685 and 785.

Model performances do not always increase with models trained on more data. This is the key difference between **stationary** and **non-stationary** datasets. For learning problems where data distribution does not change much between training and test, adding more (noiseless) data in general will improve model performances. The Numerai dataset used here is non-stationary in nature and increasing the training set might hurt model performance by including less relevant history.

When the train size is 685, decreasing the retrain period can improve Mean Corr and Sharpe ratio but the effect is not significant when retrain period is less than 100. When train size is 785, there is no clear relationship between retrain period and model performances.

Table 17: XGBoost Models with different retrain periods, train size is fixed to 685

retrain period	Mean Corr	Sharpe	Calmar
25	0.0208 $\pm$ 0.0005	1.0250 $\pm$ 0.0324	0.2054 $\pm$ 0.0164
50	0.0202 $\pm$ 0.0005	0.9875 $\pm$ 0.0460	0.1906 $\pm$ 0.0280
100	0.0197 $\pm$ 0.0009	0.9291 $\pm$ 0.0577	0.1855 $\pm$ 0.0263
200	0.0189 $\pm$ 0.0014	0.8907 $\pm$ 0.0869	0.1214 $\pm$ 0.0290
400	0.0182 $\pm$ 0.0014	0.9013 $\pm$ 0.1028	0.1188 $\pm$ 0.0340

Table 18: XGBoost Models with different retrain periods, train size is fixed to 785

retrain period	Mean Corr	Sharpe	Calmar
25	0.0207 $\pm$ 0.0005	1.0116 $\pm$ 0.0423	0.2048 $\pm$ 0.0509
50	0.0211 $\pm$ 0.0006	1.0463 $\pm$ 0.0187	0.2246 $\pm$ 0.0259
100	0.0202 $\pm$ 0.0006	0.9853 $\pm$ 0.0213	0.2281 $\pm$ 0.0278
200	0.0216 $\pm$ 0.0004	1.0968 $\pm$ 0.0345	0.2444 $\pm$ 0.0355
400	0.0209 $\pm$ 0.0004	1.0561 $\pm$ 0.0285	0.1957 $\pm$ 0.0125

**Discussion** The non-stationary nature of data streams is demonstrated in the lack of relationship between model performances and retrain periods for models with different train sizes. Each XGBoost model has the same hyper-parameters and the training process only differs in the training data used to train XGBoost models regularly. There are no significant differences between model performances (for fixed train sizes) once retrain periods are shorter than 100 eras.

A useful empirical rule to select training size is to ensure the training set is large enough to cover different data regimes that are possible to come up in future. Once the training set includes enough data samples from different regimes, further increase in train size will have limited improvement to model performance.

## 7 Deep Incremental Learning Models

Deep incremental learning models combine models trained with different hyper-parameters to obtain more robust predictions. In the following, we study two different ways to ensemble XGBoost models, first by combining XGBoost models with different retrain periods, second by combining XGBoost model snapshots with different model complexity.

**Deep XGBoost ensembles with different retrain periods** 20 standard XGBoost models (5000 boosting rounds) are trained as follows. The train size is fixed to 585. Models are retrained every 200,100,50,25 eras, where 5 models with different random seeds are trained for each retrain periods. Other hyper-parameters of the XGBoost models are set as follows.

- Grow policy: Depth-wise
- Number of boosting rounds: 5000
- Early Stopping 250
- Learning rate: 0.01
- Max Depth: 8
- Max Leaves: 128
- Min Samples per node: 10
- Data subsample: 0.75
- Feature subsample by tree: 0.75
- Feature subsample by level/node: 1
- L1 regularisation: 0.001
- L2 regularisation: 0.001

A deep XGBoost model is created by combining the 20 models incrementally. For every 10th era, a shallow XGBoost model with the following hyper-parameters is trained using model predictions from the most recent 185 eras (with suitable data lag). Monotonic constraints are imposed so that we do not assign negative weights to the model predictions. This is repeated over 5 times over different random seeds.

- Grow policy: Depth-wise
- Number of boosting rounds: 20
- Early Stopping 20
- Learning rate: 0.1
- Max Depth: 8
- Max Leaves: 128
- Min Samples per node: 10
- Data subsample: 0.75
- Feature subsample by tree: 0.75
- Feature subsample by level/node: 1
- L1 regularisation: 0.001
- L2 regularisation: 0.001

In table 19, the performance from the deep XGBoost models in Layer 2 (Deep) in Era 801 to Era 1050 are reported. The performance of each individual XGBoost model in Layer 1 (Base) is also reported.

Deep XGBoost models can improve Mean Corr and other portfolio metrics. The improvement in Mean Corr is significant (with p-values less than 0.0001) with unpaired t-test for two samples. Deep XGBoost models are more robust as it has a lower variance than each of the individual models.

Table 19: Deep XGBoost models with different retrain periods (5000 boosting rounds)

Method	Mean Corr	Sharpe	Calmar
Base	0.0211 ± 0.0010	1.0374 ± 0.0544	0.2399 ± 0.0536
Deep	0.0240 ± 0.0001	1.1379 ± 0.0067	0.2750 ± 0.0129

Repeating the above analysis with the number of boosting rounds changed from 5000 (standard) to 500(small)/50000(large), tables 20 and 21 compare the performance of the deep XGBoost models with the average models.

- Number of boosting rounds: 500
- Early Stopping 25
- Learning rate: 0.1
  
- Number of boosting rounds: 50000
- Early Stopping 2500
- Learning rate: 0.001

For small XGBoost models (500 boosting rounds), deep model ensemble significantly improves Mean Corr. Model performances are poorer than models trained with 5000 boosting rounds as expected. Even if the base learners (small XGBoost models with 500 trees) are very weak predictors on their own (and are only 10% size of the original trees), 90% performance of the XGBoost model with 5000 trees can be recovered in the deep XGBoost models.

For large XGBoost models (50000 boosting rounds), deep model ensemble still improves Mean Corr (p-value for t-test is 0.0381). However, there is a smaller gap between Mean Corr of the individual models in Layer 1 and the deep models in Layer 2. It suggests the better the quality of base learners, the lesser the need to apply further optimisation on those.

Deep Ensemble of large XGBoost models is not significantly better than deep ensemble of standard XGBoost models. Under the deep incremental learning framework, there is no need to train **single** large machine learning models as component models. Computing hardware requirement can be reduced with minimal loss on model performances.

Table 20: Deep XGBoost models with different retrain periods (500 boosting rounds)

Method	Mean Corr	Sharpe	Calmar
Base	0.0122 ± 0.0005	0.6987 ± 0.0959	0.1161 ± 0.0455
Deep	0.0206 ± 0.0001	1.0453 ± 0.0106	0.1949 ± 0.0085

Table 21: Deep XGBoost models with different retrain periods (50000 boosting rounds)

Method	Mean Corr	Sharpe	Calmar
Base	0.0231 ± 0.0009	1.1354 ± 0.0696	0.3506 ± 0.1182
Deep	0.0240 ± 0.00004	1.1701 ± 0.0041	0.4036 ± 0.0105

**Deep XGBoost ensembles with different model complexity** XGBoost models with 5000,50000 boosting rounds are trained for 5 different random seeds. For each XGBoost model, 10 model snapshots are collected. The 50 predictions are then combined in the second layer of the deep incremental model. For every 10th era, a shallow XGBoost model with the following hyper-parameters is trained using model predictions from the most recent 185 eras (with suitable data lag). Monotonic constraints are imposed so that we do not assign negative weights to the model predictions. The hyper-parameters of the XGBoost models are as above.

In tables 22 and 23, the performance from the deep XGBoost model in Layer 2 (Deep) is compared with the individual XGBoost snapshots in Layer 1 (Base) in Era 801 to Era 1050.

For standard XGBoost models (5000 boosting rounds), deep model ensemble improves Mean Corr (p-value for t-test is 0.0004). Sharpe and Calmar ratio are not much different from the individual models. For large XGBoost models (50000 boosting rounds), deep model ensemble still improves Mean Corr but not as significant as above (p-value for t-test is 0.0630). Deep XGBoost models over different model snapshots does not significantly outperform the deep XGBoost models over models with early-stopping.

Table 22: Deep XGBoost models with different model complexity (5000 boosting rounds)

Method	Mean Corr	Sharpe	Calmar
Base	0.0215 ± 0.0010	1.1354 ± 0.0696	0.3506 ± 0.1182
Deep	0.0234 ± 0.0001	1.1671 ± 0.0078	0.3443 ± 0.0132

**Summary** Model ensemble is an effective way to improve robustness of model predictions, in particular when the base learners are not strong predictors on their own, such as the case with small XGBoost models (500 boosting rounds). As the quality of base learners gets better, such as the case with large XGBoost models (50000 boosting rounds), the

Table 23: Deep XGBoost models with different model complexity (50000 boosting rounds)

Method	Mean Corr	Sharpe	Calmar
Base	$0.0231 \pm 0.0009$	$1.1896 \pm 0.0614$	$0.4256 \pm 0.1435$
Deep	$0.0239 \pm 0.0001$	$1.1668 \pm 0.0062$	$0.3535 \pm 0.0145$

improvement becomes less significant. A possible reason is because the base learner considered here, GBDT models already made use of gradient-boosting to refine its predictions, therefore applying the same technique again will give limited gains in performances.

For the Numerai dataset in this study, there is no significant benefit in using large XGBoost models within a deep model ensemble. Training standard XGBoost models with 5000 boosting rounds (with early stopping enabled) can already obtain models with the highest Mean Corr considered. Training large XGBoost models with 50000 boosting rounds and early stopping can improve Calmar ratio but the effect is not significant.

In most bench-marking studies of tabular machine learning models, performances of individual models trained with different random seeds, for different model configurations are reported, and the ensemble performances is not reported. As model complexity is not standardised across different machine learning methods under comparison, it is unfair to compare the performances of an over-parameterised model, typically deep-learning based with standard XGBoost models. A single over-parameterised deep learning model might outperform a single XGBoost model, but it is unlikely that the same deep learning model can outperform an ensemble of XGBoost models over different complexities and incremental learning settings.

The typical workflow of running hyper-parameter optimisation of different machine learning methods with the same computational budget might not be the best approach since it does not separate the efficiency of the algorithm implementations, which is an issue on software engineering/high performance computing from (theoretical) model complexity, which is purely related to model design and unrelated to the exact implementations of algorithms. In order to make sure results related to computational resources are replicable, detailed documentation of hardware and OS environment used to train the models are required.

For incremental learning tasks, diversified models can be created using degree of freedoms that are unrelated to a particular machine learning methods(random seeds, retrain period, global feature and data sub-sampling) and to some extent, model designs that are applicable to a wide range of models (model snapshots over different complexities). For fair comparison of machine learning methods, it is not enough to simply compare the methods with the same set of data cross-validations but also under different data sampling schemes and model complexity regimes. Reporting the aggregated performances over different training settings would provide more useful insights for real-life performances of prediction systems.

## 8 Discussion

In this paper, both traditional tabular and factor-timing models are studied for the incremental learning problem on the temporal tabular dataset from Numerai. Traditional tabular models, if retrained regularly can adapt to distribution shifts in data which cannot be modelled by factor-timing models effectively.

Not all methods of increasing model complexities can improve model performances. For factor-timing models, increasing the size of random feature sets or increasing the number of layers in transformers layers are inefficient ways of data learning. For transformer models, there is no clear relationship between model complexities and performances, results from hyper-parameter optimisation are not robust and might not be useful for future predictions. For MLP models, increasing the number of layers does not always improve model performance. The optimal model complexity depends on both the architecture and training process. For XGBoost models, increasing the complexity of a **single** model by disabling early stopping will increase the risk of over-fitting. However, increasing model complexity horizontally through different model ensemble methods such as bagging is more robust than training a single large model as there is fewer risks in over-fitting the data over different models. Not all approaches to building complex models are equal. Some approaches are more robust than others based on both theoretical and empirical findings.

There is no simple rule to select whether to use classic or over-parameterised machine learning models. The optimal model complexity depends on the training process and datasets for a **static** machine learning problem. Within an incremental learning framework, training multiple models with different complexities and then applying soft hyper-parameter selection within a deep model framework is better than using cross-validation to select a **single** set of 'optimal' hyper-parameters.

Incremental learning is an effective way to adapt to distribution shifts in data. Both the training size and model retrain/update period should be selected based on walk-forward prediction performances of the early parts of the data stream. The training size needs to be large enough to cover different data regimes in history and not too large to include old data that are no longer relevant. In general, increasing the model retrain period can improve model performances but the requirements on computational resources also increase. Therefore, trade-offs between computational costs and the marginal gain in model performances are made for practical incremental learning systems.

The Numerai datasets used in this paper showed that **both** viewpoints on model complexity are incomplete picture on the reality of data modelling. Classical viewpoint expects over-fitting of model after certain number of boosting rounds. Mean Corr drops slightly as number of boosting rounds increases but Sharpe ratio is not changed significantly. Robustness of models improves as Calmar ratio increases when models become larger. This suggests rather than being an over-fitted model, larger models are more robust towards downside risks. Modern ML viewpoint is also not correct as both deep factor-timing models based on Signature and random Fourier transforms under-performed simple trend-based models. Complex MLP architectures also under-performed a simple MLP model with 2 layers. This observation is unexpected since these methods are used as examples in research papers advocating the modern ML viewpoint [33, 62].

For XGBoost models of different number of boosting rounds, snapshots taken after 20% of boosting rounds are all useful candidates to be used in an ensemble. It is not possible to reject the null hypothesis that model snapshots with at least 20% of boosting rounds have equal performances based on results from 5 different random seeds. The case study using Numerai datasets here does not provide any evidence supporting or against the use of early-stopping based on model performances alone. The choice of whether to apply early-stopping should then be decided based on computational resources or other practical implementations for each researcher.

In most practical applications, **multiple** machine learning methods are used together to create an ensemble prediction. The incremental learning model presented in this papers provides a comprehensive way to integrate different machine learning models in a consistent and systematic way to create point-in-time predictions. With a multi-layer structure and modularised design within each layer, the deep incremental learning model can flexibly model datasets with different complexities and structures. Further work can be done by integrating different deep tabular models into the model and benchmark different machine learning method under the incremental learning framework.

For crowd-sourcing scientific projects which submissions from the public are combined to form a meta model, the deep incremental learning model presented here provided a mechanism to combine many weak models into a strong ensemble. As each component model considered in this study has a very low hardware requirement (only a single GPU is required), this is accessible to most data scientists on Kaggle or other data science competitions. Indeed, the promising results shown in this paper using only standard approaches (XGBoost, MLP) on a dataset with real use-cases suggests even if the data scientists in the crowd-sourcing projects might not be aware of the latest advances in machine learning, they can still contribute towards different projects in a meaningful way.

## 9 Acknowledgements

This was supported in part by the Wellcome Trust under Grant 108908/B/15/Z and by the EPSRC under grant EP/N014529/1 funding the EPSRC Centre for Mathematics of Precision Healthcare at Imperial. We sincerely thank Numerai GP, LLC for providing the datasets used in the study.



## References

- [1] F. Zhu et al. “Class-incremental learning via dual augmentation”. In: *Advances in Neural Information Processing Systems* 34 (2021), pp. 14306–14318.
- [2] Y. Pei et al. “Learning a Condensed Frame for Memory-Efficient Video Class-Incremental Learning”. In: *Advances in Neural Information Processing Systems*. Ed. by S. Koyejo et al. Vol. 35. Curran Associates, Inc., 2022, pp. 31002–31016. URL: [https://proceedings.neurips.cc/paper\\_files/paper/2022/file/c8ac22c0d4b263618f2a4f4657948912-Paper-Conference.pdf](https://proceedings.neurips.cc/paper_files/paper/2022/file/c8ac22c0d4b263618f2a4f4657948912-Paper-Conference.pdf).
- [3] Y. Zou et al. “Margin-Based Few-Shot Class-Incremental Learning with Class-Level Overfitting Mitigation”. In: *Advances in Neural Information Processing Systems*. Ed. by S. Koyejo et al. Vol. 35. Curran Associates, Inc., 2022, pp. 27267–27279. URL: [https://proceedings.neurips.cc/paper\\_files/paper/2022/file/ae817e85f71ef86d5c9566598e185b89-Paper-Conference.pdf](https://proceedings.neurips.cc/paper_files/paper/2022/file/ae817e85f71ef86d5c9566598e185b89-Paper-Conference.pdf).
- [4] M. Song et al. “In-situ ai: Towards autonomous and incremental deep learning for iot systems”. In: *2018 IEEE International Symposium on High Performance Computer Architecture (HPCA)*. IEEE, 2018, pp. 92–103.
- [5] A. L. Buczak and E. Guven. “A survey of data mining and machine learning methods for cyber security intrusion detection”. In: *IEEE Communications surveys & tutorials* 18.2 (2015), pp. 1153–1176.
- [6] K. Arulkumaran et al. “Deep reinforcement learning: A brief survey”. In: *IEEE Signal Processing Magazine* 34.6 (2017), pp. 26–38.
- [7] Y. Hong, Y. Jin, and Y. Tang. “Rethinking Individual Global Max in Cooperative Multi-Agent Reinforcement Learning”. In: *Advances in Neural Information Processing Systems*. Ed. by S. Koyejo et al. Vol. 35. Curran Associates, Inc., 2022, pp. 32438–32449. URL: [https://proceedings.neurips.cc/paper\\_files/paper/2022/file/d112fdd31c830900d1f2e4ccebffb54f-Paper-Conference.pdf](https://proceedings.neurips.cc/paper_files/paper/2022/file/d112fdd31c830900d1f2e4ccebffb54f-Paper-Conference.pdf).
- [8] O. Bastani et al. “Regret Bounds for Risk-Sensitive Reinforcement Learning”. In: *Advances in Neural Information Processing Systems*. Ed. by S. Koyejo et al. Vol. 35. Curran Associates, Inc., 2022, pp. 36259–36269. URL: [https://proceedings.neurips.cc/paper\\_files/paper/2022/file/eb4898d622e9a48b5f9713ea1fcff2bf-Paper-Conference.pdf](https://proceedings.neurips.cc/paper_files/paper/2022/file/eb4898d622e9a48b5f9713ea1fcff2bf-Paper-Conference.pdf).
- [9] K. Zhang et al. “Robust Multi-Agent Reinforcement Learning with Model Uncertainty”. In: *Advances in Neural Information Processing Systems*. Ed. by H. Larochelle et al. Vol. 33. Curran Associates, Inc., 2020, pp. 10571–10583. URL: [https://proceedings.neurips.cc/paper\\_files/paper/2020/file/774412967f19ea61d448977ad9749078-Paper.pdf](https://proceedings.neurips.cc/paper_files/paper/2020/file/774412967f19ea61d448977ad9749078-Paper.pdf).
- [10] Y. Deng et al. “Deep direct reinforcement learning for financial signal representation and trading”. In: *IEEE transactions on neural networks and learning systems* 28.3 (2016), pp. 653–664.
- [11] D. Acuna, J. Phillion, and S. Fidler. “Towards Optimal Strategies for Training Self-Driving Perception Models in Simulation”. In: *Advances in Neural Information Processing Systems*. Ed. by M. Ranzato et al. Vol. 34. Curran Associates, Inc., 2021, pp. 1686–1699. URL: [https://proceedings.neurips.cc/paper\\_files/paper/2021/file/0d5bd023a3ee11c7abca5b42a93c4866-Paper.pdf](https://proceedings.neurips.cc/paper_files/paper/2021/file/0d5bd023a3ee11c7abca5b42a93c4866-Paper.pdf).
- [12] J. Kober, J. A. Bagnell, and J. Peters. “Reinforcement learning in robotics: A survey”. In: *The International Journal of Robotics Research* 32.11 (2013), pp. 1238–1274.
- [13] K. Arndt et al. “Meta reinforcement learning for sim-to-real domain adaptation”. In: *2020 IEEE international conference on robotics and automation (ICRA)*. IEEE, 2020, pp. 2725–2731.
- [14] I. Higgins et al. “Darla: Improving zero-shot transfer in reinforcement learning”. In: *International Conference on Machine Learning*. PMLR, 2017, pp. 1480–1490.
- [15] X. Ma, K. Driggs-Campbell, and M. J. Kochenderfer. “Improved robustness and safety for autonomous vehicle control with adversarial reinforcement learning”. In: *2018 IEEE Intelligent Vehicles Symposium (IV)*. IEEE, 2018, pp. 1665–1671.
- [16] A. Mott et al. “Towards interpretable reinforcement learning using attention augmented agents”. In: *Advances in neural information processing systems* 32 (2019).
- [17] A. I. Naimi and L. B. Balzer. “Stacked generalization: an introduction to super learning”. In: *European journal of epidemiology* 33 (2018), pp. 459–464.
- [18] T. Wong and M. Barahona. *Dynamic Feature Engineering and model selection methods for temporal tabular datasets with regime changes*. 2023. arXiv: 2301.00790 [q-fin.CP].
- [19] M. Li et al. *Learning to Rank for Active Learning: A Listwise Approach*. 2020. arXiv: 2008.00078 [cs.CV].
- [20] T. Lyons and A. D. McLeod. *Signature Methods in Machine Learning*. 2022. DOI: 10.48550/ARXIV.2206.14674. URL: <https://arxiv.org/abs/2206.14674>.
- [21] D. J. Sutherland and J. Schneider. *On the Error of Random Fourier Features*. 2015.

- [22] S. Hochreiter and J. Schmidhuber. “Long Short-Term Memory”. In: *Neural Computation* 9.8 (1997), pp. 1735–1780.
- [23] B. Lim et al. *Temporal Fusion Transformers for Interpretable Multi-horizon Time Series Forecasting*. 2019. DOI: 10.48550/ARXIV.1912.09363. URL: <https://arxiv.org/abs/1912.09363>.
- [24] C. Hoffstein, N. Faber, and S. Braun. “Rebalance timing luck: the (dumb) luck of smart beta”. In: *Available at SSRN 3673910* (2020).
- [25] G. Hinton. *The Forward-Forward Algorithm: Some Preliminary Investigations*. 2022. DOI: 10.48550/ARXIV.2212.13345. URL: <https://arxiv.org/abs/2212.13345>.
- [26] A. Didisheim, B. Kelly, and S. Malamud. *Deep Regression Ensembles*. 2022.
- [27] T. J. Lyons. “Differential Equations Driven by Rough Paths : Ecole d’Été de Probabilités de Saint-Flour XXXIV-2004”. eng. In: *École d’Été de Probabilités de Saint-Flour, 1908*. Berlin, Heidelberg: Springer Berlin Heidelberg, 2007. ISBN: 1-280-85347-6.
- [28] I. Chevyrev and A. Kormilitzin. *A Primer on the Signature Method in Machine Learning*. 2016. DOI: 10.48550/ARXIV.1603.03788. URL: <https://arxiv.org/abs/1603.03788>.
- [29] P. Kidger and T. Lyons. “Signatory: differentiable computations of the signature and logsignature transforms, on both {CPU} and {GPU}”. In: *International Conference on Learning Representations*. 2021. URL: <https://openreview.net/forum?id=lqU2cs3Zca>.
- [30] M. Lemerrier et al. “Distribution Regression for Sequential Data”. In: *Proceedings of The 24th International Conference on Artificial Intelligence and Statistics*. Ed. by A. Banerjee and K. Fukumizu. Vol. 130. Proceedings of Machine Learning Research. PMLR, 13–15 Apr 2021, pp. 3754–3762. URL: <https://proceedings.mlr.press/v130/lemerrier21a.html>.
- [31] G. Cybenko. “Approximation by superpositions of a sigmoidal function”. In: *Mathematics of control, signals and systems* 2.4 (1989), pp. 303–314.
- [32] J. Morrill et al. *A Generalised Signature Method for Multivariate Time Series Feature Extraction*. 2020. DOI: 10.48550/ARXIV.2006.00873. URL: <https://arxiv.org/abs/2006.00873>.
- [33] B. T. Kelly, S. Malamud, and K. Zhou. “The Virtue of Complexity Everywhere”. In: *Available at SSRN* (2022).
- [34] D. McElfresh et al. *When Do Neural Nets Outperform Boosted Trees on Tabular Data?* 2023. arXiv: 2305.02997 [cs.LG].
- [35] R. Shwartz-Ziv and A. Armon. *Tabular Data: Deep Learning is Not All You Need*. 2021. DOI: 10.48550/ARXIV.2106.03253. URL: <https://arxiv.org/abs/2106.03253>.
- [36] L. Grinsztajn, E. Oyallon, and G. Varoquaux. *Why do tree-based models still outperform deep learning on tabular data?* 2022. DOI: 10.48550/ARXIV.2207.08815. URL: <https://arxiv.org/abs/2207.08815>.
- [37] A. Kadra et al. *Well-tuned Simple Nets Excel on Tabular Datasets*. 2021. DOI: 10.48550/ARXIV.2106.11189. URL: <https://arxiv.org/abs/2106.11189>.
- [38] S. Ö. Arik and T. Pfister. “TabNet: Attentive Interpretable Tabular Learning”. In: *Proceedings of the AAAI Conference on Artificial Intelligence* 35.8 (May 2021), pp. 6679–6687. URL: <https://ojs.aaai.org/index.php/AAAI/article/view/16826>.
- [39] T. Chen and C. Guestrin. “XGBoost: A Scalable Tree Boosting System”. In: *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*. KDD ’16. San Francisco, California, USA: Association for Computing Machinery, 2016, pp. 785–794. ISBN: 9781450342322. DOI: 10.1145/2939672.2939785. URL: <https://doi.org/10.1145/2939672.2939785>.
- [40] G. Ke et al. “LightGBM: A Highly Efficient Gradient Boosting Decision Tree”. In: *Advances in Neural Information Processing Systems*. Ed. by I. Guyon et al. Vol. 30. Curran Associates, Inc., 2017. URL: <https://proceedings.neurips.cc/paper/2017/file/6449f44a102fde848669bdd9eb6b76fa-Paper.pdf>.
- [41] L. Prokhorenkova et al. “CatBoost: unbiased boosting with categorical features”. In: *Advances in Neural Information Processing Systems*. Ed. by S. Bengio et al. Vol. 31. Curran Associates, Inc., 2018. URL: <https://proceedings.neurips.cc/paper/2018/file/14491b756b3a51daac41c24863285549-Paper.pdf>.
- [42] K. P. Murphy. *Probabilistic Machine Learning: An introduction*. MIT Press, 2022. URL: [probml.ai](http://probml.ai).
- [43] J. H. Friedman. “Greedy function approximation: A gradient boosting machine”. eng. In: *The Annals of statistics* 29.5 (2001), pp. 1189–1232. ISSN: 0090-5364.
- [44] P. Buhlmann and T. Hothorn. “Boosting Algorithms: Regularization, Prediction and Model Fitting”. In: *Statistical Science* 22.4 (Nov. 2007). DOI: 10.1214/07-sts242.
- [45] W. Falcon and The PyTorch Lightning team. *PyTorch Lightning*. Version 1.4. Mar. 2019. DOI: 10.5281/zenodo.3828935. URL: <https://github.com/Lightning-AI/lightning>.

- [46] L. Zimmer, M. Lindauer, and F. Hutter. “Auto-PyTorch Tabular: Multi-Fidelity MetaLearning for Efficient and Robust AutoDL”. In: (2021), pp. 3079–3090. DOI: 10.1109/TPAMI.2021.3067763.
- [47] S. Popov, S. Morozov, and A. Babenko. *Neural Oblivious Decision Ensembles for Deep Learning on Tabular Data*. 2019. DOI: 10.48550/ARXIV.1909.06312. URL: <https://arxiv.org/abs/1909.06312>.
- [48] A. Vaswani et al. *Attention Is All You Need*. 2017. DOI: 10.48550/ARXIV.1706.03762. URL: <https://arxiv.org/abs/1706.03762>.
- [49] B. Lakshminarayanan, A. Pritzel, and C. Blundell. “Simple and scalable predictive uncertainty estimation using deep ensembles”. In: *Advances in neural information processing systems* 30 (2017).
- [50] F. Wenzel et al. “Hyperparameter Ensembles for Robustness and Uncertainty Quantification”. In: *Neural Information Processing Systems (NeurIPS)*. 2020. URL: <https://papers.nips.cc/paper/2020/hash/481fbfa59da2581098e841b7afc122f1-Abstract.html>.
- [51] S. Zaidi et al. “Neural ensemble search for uncertainty estimation and dataset shift”. In: *Advances in Neural Information Processing Systems* 34 (2021), pp. 7898–7911.
- [52] A. M. Schäfer and H. G. Zimmermann. “Recurrent neural networks are universal approximators”. In: *Artificial Neural Networks–ICANN 2006: 16th International Conference, Athens, Greece, September 10–14, 2006. Proceedings, Part I* 16. Springer. 2006, pp. 632–640.
- [53] F. Horn, R. Pack, and M. Rieger. *The autofeat Python Library for Automated Feature Engineering and Selection*. 2019. DOI: 10.48550/ARXIV.1901.07329. URL: <https://arxiv.org/abs/1901.07329>.
- [54] J. M. Kanter and K. Veeramachaneni. “Deep feature synthesis: Towards automating data science endeavors”. In: *2015 IEEE International Conference on Data Science and Advanced Analytics (DSAA)*. 2015, pp. 1–10. DOI: 10.1109/DSAA.2015.7344858.
- [55] X. Huang et al. *TabTransformer: Tabular Data Modeling Using Contextual Embeddings*. 2020. DOI: 10.48550/ARXIV.2012.06678. URL: <https://arxiv.org/abs/2012.06678>.
- [56] Numerai. *Numerai Hedge Fund*. (2023, Feb 15). URL: <https://numer.ai/data/v4.1>.
- [57] Numerai. *Numerai Hedge Fund*. (2023, Apr 19). URL: <https://docs.numer.ai/tournament/correlation-corr>.
- [58] T. Hastie et al. *Surprises in High-Dimensional Ridgeless Least Squares Interpolation*. 2019. DOI: 10.48550/ARXIV.1903.08560. URL: <https://arxiv.org/abs/1903.08560>.
- [59] P. Nakkiran et al. “Deep double descent: where bigger models and more data hurt”. eng. In: *Journal of statistical mechanics* 2021.12 (2021), pp. 124003–. ISSN: 1742-5468.
- [60] N. TeresaHuang, D. W. Hogg, and S. Villar. “Dimensionality Reduction, Regularization, and Generalization in Overparameterized Regressions”. In: *SIAM Journal on Mathematics of Data Science* 4.1 (2022), pp. 126–152. DOI: 10.1137/20M1387821.
- [61] D. Chen, W. Chang, and P. Chaudhari. *Learning Capacity: A Measure of the Effective Dimensionality of a Model*. 2023. arXiv: 2305.17332 [cs.LG].
- [62] M. Belkin et al. “Reconciling modern machine-learning practice and the classical bias–variance trade-off”. In: *Proceedings of the National Academy of Sciences* 116.32 (2019), pp. 15849–15854.