

The Representational Status of Deep Learning Models

Eamon Duede

Department of Philosophy

Committee on Conceptual & Historical Studies of Science

Pritzker School of Molecular Engineering

University of Chicago

eduede@uchicago.edu

March 22, 2023

Abstract

This paper aims to clarify the representational status of Deep Learning Models (DLMs). While commonly referred to as ‘representations’, what this entails is ambiguous due to a conflation of functional and relational conceptions of representation. This paper argues that while DLMs represent their targets in a relational sense, they are best understood as highly idealized models. This result has immediate implications for explainable AI (XAI) and directs philosophical attention toward examining the idealized nature of DLM representations and their role in future scientific investigation.

1 Introductory

It is commonplace to refer to a fully trained deep learning architecture as a ‘representation’ or a ‘model’. However, this interchangeable usage can lead to confusion, as the specific meanings behind these terms can vary depending on the field and context of use. What is meant by ‘representation’ or ‘model’ in one context might be rather incoherent in another. For example, when AI researchers examine how ‘representations’ in a deep network are affected by elements of that network’s architecture, what counts as a representation is the observed ‘pattern of neural activation’ attributable to that architectural element in concert with neural inputs [OEN⁺22]. In this context, ‘representation’ has much in common with its use in neuroscience, where neural activation patterns are viewed as *functional* [Cao22]. Understood functionally, representations are mechanisms that have identifiable effects on behavior or serve to facilitate the accomplishment of some goal [Dre81, Dre91, Mil89, Nea95]. Of course, considerable ambiguity remains within the AI and neuroscience communities on how best to spell out that functional conception [BLK22].

While the AI and neuroscience literatures tend to focus on a functional conception of representation, the philosophical literature on scientific models focuses on a *relational* conception. Here, models stand in a representational relationship to their targets. In general, this has been understood to mean that features of the model are either similar to, correspond with, denote, or otherwise exemplify relevant aspects of the model’s target system. If some such relation holds, the model is said to represent its target. However, as with the functional conception, philosophers remain divided on how best to cash out the fine details of the relational conception. Nevertheless, while there is surely scope for some overlap,¹ in general, the functional and relational conceptions of representation appear distinct.

The aim of this paper is to gain clarity on the otherwise overlooked question of the representational status of deep learning models (DLMs) understood in the way implied by the relational conception. Viewed from the functional perspective of systems neuroscience or fundamental AI research, the question as to whether deep learning models are representational is a trivial one —of course they are. But, this is to misunderstand the question posed by the present study. Considered from the relational perspective, the representational status of deep learning models remains unresolved.

The position I will argue for and defend throughout the paper is that deep learning models do represent their targets in the relational sense. However, I show that, in general,

¹For instance, the brain likely represents both functionally and relationally [Sha18].

we have no good reason to believe that DLMS encode fine-grained (e.g., common features, accurate mirroring, mapping, etc.) representations of their targets. That is, the available evidence does not warrant a general belief that a deep learning model’s units, sets or layers of units, and associated weights represent individual aspects of the target system. Rather, scientists are, at most, justified in ascribing to DLMS a representational status akin to that of highly idealized models. This result has immediate epistemic consequences for interpretability approaches in the budding field of explainable AI (XAI). Additionally, this analysis helps to redirect philosophical attention towards exploring the idealized nature of deep learning representations and their relationship both to models more generally and their potential role in future scientific inquiry.

There are at least two main reasons why the representational status of deep learning models has been neglected. The first is an effect due to ambiguity in the concept of representation in philosophy [BR14, dO21] and in neuroscience [B⁺21, Cao18]. Historically, these fields have had a tendency to carelessly conflate functional and relational notions of representation. The broad, historical and conceptual influence these literatures have had on contemporary research in AI [Har08, Cao22] has, in turn, lead to confusion in the AI literature [Yar19, Sha22, Mit21, SH19]. Indeed, as I will show throughout, not only are deep learning models routinely referred to as ‘representations’ in the AI literature, but their architectural components are also described using language that has the effect of schooling the eye to mistakenly see DLMS as more richly representational than is currently justified. Second, a general lack of model transparency [Cre20] makes it difficult to directly determine the representational status of DLMS, allowing certain conceptions and misconceptions to become entrenched.

Resolving the representational status of deep learning is not merely an exercise in the metaphysics of AI. Nor is it philosophical nitpicking of careless AI researchers. The issue has immediate epistemological and ethical consequences. For instance, many (though not all) current model interpretability efforts appear to *assume* a richer representational status than has yet been established, rendering such approaches highly under-determined, unfalsifiable, and likely spurious [LM20]. This can lead, in turn, to unjustified beliefs about model reliability [Due22b], targets [Rud19], or unethical decision-making practices where accountability and value-alignment are salient [BC⁺22, FS⁺21, Hof17].

Going forward, I will use the term ‘representation’ to refer to that which stands in a representational relation, as understood on a *relational* conception. I will, of course, have occasion to discuss representations from the functional perspective when, for instance, I discuss neural activation patterns in deep neural networks and human brains in *Section 4*. In such cases, I will clarify that I mean by ‘representation’ in the sense denoted by

the functional perspective and will, for the most part, adopt the term ‘learned transformation’ to avoid confusion.

Here, then, is the plan: In *Section 2*, focusing on the role of representation, I briefly review the recent literature on scientific models to bring out a graded distinction between representationally fine-grained models and those that are highly idealized. In *Section 3*, I turn to a discussion of deep learning models, including their structure and training process, as well as the challenges of resolving their representational status presented by opacity. In doing so, I clarify relevant terminology and adopt a stable vocabulary to avoid ambiguity. In *Section 4*, I examine whether more technical, conceptual, and philosophical considerations support the idea that DLMS encode fine-grained representations. I conclude in *Section 5* that DLMS are representational in an idealized sense and that there is no evidence that they are fine-grained models of their targets, thereby highlighting potential epistemic and practical risks associated with interpreting them as such.

2 Representational Scientific Models

The question that concerns us in the present study is not whether DLMS are *models*. While there is certainly debate concerned with which things count as models, for the purposes of this paper, I simply assert that scientific models are whichever things scientists take to be or use as models.² Instead, this paper seeks to understand whether and to what extent deep learning models are *representational* models understood from the *relational perspective*.

There is a large and diverse literature that argues that not all models are faithfully representational [Wim87, VF10]; that models merely denote targets or exemplify relevant properties [Fri10, FN16]; that models are essentially tools and not necessarily representations [Gie04, Par20, BK09]; that what makes something a model is the functions it serves regardless of its representational status [Suá04, Con07]; that the appropriate epistemic evaluation of a model is a function of adequacy [Par20] and not its similarity to targets –on and on. What gives rise to and motivates much of the diversity in this literature is a concern to make sense of how models can give us knowledge about the world in cases where they explicitly *misrepresent* the world. Of course, by necessity, all instances of *misrepresentation* are cases of representation, since there is *something* that is being represented, just badly.³ After all, it is well established that most models *misrepresent* their targets [CM84, Bat10, Ric12] and the more highly idealized the model, the less repre-

²This view is not without substantial motivation and support from empirical, conceptual, and historical evaluations of scientific practice [Plu01, Par20, Gie10].

³I am thankful to an anonymous referee for pointing this out.

sentationally faithful it is. Nevertheless, it has been argued that, in the extreme case, so called ‘targetless’ models do not represent any real, nomologically possible, targets at all [FN⁺20, Wei12, Lev15, Mas19].⁴ Regardless, it is fairly straightforward to show that deep learning models have targets (see *Section 3*).

How, exactly, to cash out the representational relation that is thought to obtain in cases of representational modeling is dicey. While some scholars have advocated for technical specifications such as relations of isomorphism [Fre03, VF80, DCF03], what most every representational account of scientific models turns on are notions or requirements of ‘similarity’ and ‘correspondence’ between the model and the target [Gie10, Wei12, B⁺21].⁵ Of course, similarity admits of degrees and, moreover, there are a variety of ways in which model and target can be similar. After all, a physical, scale model of a bridge can be more or less similar to its target. For instance, it might have the same number of components. But, its similarity would increase by having the same relative positions and size ratios of those components. And, more similar still by using the same materials –and so on, until it is a exact, Borges, replica.

So, when it comes to representational models, an essential aspect of similarity is the degree to which salient interpretations in terms of the target can be assigned to constituent elements of the model. In *highly idealized* models, the bulk of the salient features of the target system are either drastically distorted or omitted. The more *fine-grained* the representation is, the more one can specify in a regular and systematic manner what all or most of the constituents of the model *mean* in terms of the target system, as well as how the structure or composition of those constituents contributes to that meaning. For instance, a model’s structure and composition (the syntax of the model) can capture relations of dependence or correlation between elements or parameters (its semantics) in the model.

Consider an ordinary least squares (OLS) linear model: $y = \beta_0 + \sum_{j=1}^k \beta_j x_j + \varepsilon$. Here, nearly all of the variables have salient, semantic interpretations in terms of and corresponding to observed, individual aspects of the target. Now, compare an OLS regression model to Lattice Gas Automata (LGA) used (though has fallen out of vogue) in physics to model liquid and gas flows. Here, time is discrete, one-dimensional points correspond to regions, everything exists on a two-dimensional lattice where edges between vertices are effectively nowhere —and so on. Philosophers of science have studied the LGA as belonging to the class of highly idealized, ‘minimal models’ [BR14].

⁴But, see [VJ] for a recent argument that there are no ‘targetless’ models.

⁵Many philosophers have pointed out that similarity-based views fail in corner cases and give rise to unresolvable logical, ontological, and epistemic problems [Wim87, Par20, Suá03].

A highly-idealized model such as a minimal model is, therefore, one for which it is not possible to assign a semantic interpretation in terms of specific aspects of the target to either a large number of its constituents, its structure and composition, or both. In these cases, the model (say, some low dimensional lattice and a set of update rules) can still be used to explain the behavior of some broad class of phenomena (such as fluid flows), but not because it accurately represents its target [BR14, Lan15].⁶ Nevertheless, highly-idealized models such as minimal models *are* representational in so far as they have real targets. In the case of the LGA, the model is used to represent large-scale aggregate patterns in the flow of fluids and is often deployed as a computationally cheap surrogate for otherwise costly simulations for modeling fluid mechanics such as Navier-Stokes. However, if one were to examine the LGA as if it were a fine-grained representation, then one would be liable to draw inferences concerning the physical dependencies, constitution, and so on, of actual fluids that are not, in fact, represented in the model.⁷

In attempting to determine the representational status of deep learning models, we must first ask whether they are representational at all. That is, do DLMs have real targets? As I will show in *Section 3*, the answer to this question is straightforwardly ‘yes’. To say that a DLM is representational is to place it somewhere on a graded spectrum, from highly-idealized to highly fine-grained models. In *Section 4*, I will show that DLMs are best characterized as high-idealized models –they do not provide fine-grained representations of their targets.

3 Deep Learning and Representational Ambiguity

Deep learning is a machine learning approach that utilizes artificial neural networks [L⁺15, GBC16]. In machine learning, the output of running a ‘learning algorithm’ on a training dataset \mathcal{D} is often referred to as a ‘model’. The ‘model’ is an estimated function \hat{f} that takes inputs X and maps them to outputs Y . Inputs and outputs are known as ‘features’ or ‘attributes’ and are vectors of values in some domain such as real numbers, integers, ordinals, Booleans –on and on. For now, in order to avoid confusion, I will use the term ‘estimator’ to refer to \hat{f} . For most standard deep learning applications, the aim is to find an estimator that most accurately approximates the true function f^* that is

⁶For [BR14], similarity relations do not play a role at all for *explanation*. Rather, the model’s membership in a shared universality class with the target does the explaining. Yet, see [Lan15] for an argument that this amounts to a similarity relation after all. Regardless of the fine details, there is no debate as to whether minimal models represent targets, but rather, *how they explain*. In this paper, I am concerned simply with degree of representational similarity. Minimal models are highly idealized and, so, very dissimilar from their targets, regardless of how they explain them.

⁷See [WF17] for a discussion of the Ising model which, for some targets, is highly-idealized, while, in relation to others (namely some crystalline structures) is relatively fine-grained.

responsible for generating \mathcal{D} .

For simplicity, I will consider traditional, feed-forward deep neural networks trained in a supervised manner [Fla12].⁸ In a fully connected deep neural network architecture, each unit in a given layer is connected to every unit in the subsequent layer. The value of the output of a given unit is a function of the weighted sum of all outputs of all units from the previous layer (which are inputs to the unit).⁹ In this way, the resulting estimator \hat{f} outputs results $\hat{f}(x)$ through a process in which successive layers of computational units mathematically transform ϑ_k inputs from proceeding layers such that $\hat{f}(x_i) = \vartheta_l(\vartheta_{l-1}(\dots\vartheta_1(x_i; W_1); W_2)\dots; W_l)$ where x_i is an input to the network and W_k is a matrix of weights on the connections between layers.

The network’s internal transformations are often referred to as ‘representations’ and the optimization process by which they are arrived at is known as ‘representation learning’ [B⁺13]. In this context, ‘representation’ carries a functional meaning. So, to avoid confusion in what follows, I will adopt the term ‘learned transformations’ to refer to a DLM’s internal data operations. In *Section 4*, I will consider whether learned transformations can be viewed as representational in the relational sense. The precise transformations at a layer ϑ_k are learned by iteratively updating all weights on all connections, sequentially minimizing a loss function \mathcal{L} through backpropagation of errors [RHW86]. The estimator’s learned transformations are optimized such that the risk R over the training distribution P is minimized for $R_p(\hat{f}) := \mathbb{E}_{(X,Y)\sim P}[\mathcal{L}(\hat{f}(X), Y)]$.

The mathematical particulars of a deep learning estimator are fully transparent and available to direct inspection [Les19]. This fact is sufficient to establish that \hat{f} is representational. To see this, consider that the numerical values of both the input and output layers of the network are taken or interpreted to denote states of a specific target system and are isomorphic to a data-model of those states [Sup66, Fla12]. Both layers are represented as arrays of values $\langle a_1, a_2, \dots, a_k \rangle$ that correspond to sets of values in their data models $\{x_1, x_2, \dots, x_k\}$ which, in turn, correspond with sets of elements in the target system {‘height in cm’, ‘weight in kg’, ... , ‘points per game’}. From this, it seems unobjectionable that the input and output layers represent targets (and often particular aspects of those targets). So, deep learning estimators are *representational*. Since it has

⁸What follows generalizes with some modification to almost all of the common deep learning approaches in use today. The main claims of this paper do not depend on DL approaches being fully feed-forward, and are unchanged when considering recurrent neural networks and transformer architectures.

⁹Let a_n^l denote the output of the n^{th} unit in the l^{th} layer such that $a_n^l = g(\sum_m w_{nm}^l a_m^{l-1})$ where g is an activation function such as ReLU ($\max(0, \sum_m w_{nm}^l a_m^{l-1})$). We can rewrite the equation for unit-wise output to represent layer-wise output by vectorizing our components and keeping track of the weights at a given layer in a matrix W which gives $\vartheta^l = g(W^l \vartheta^{l-1})$.

already been established in *Section 2* that deep learning estimators are models, we can now say that they are *representational models*.

Having established that deep learning models are representational, we can now turn to the hard question of how finely-grained they are. If DLMs are fine-grained representations of their targets, then, in principle, one can assign an interpretation to a large proportion of the units and weights that comprise the network’s hidden layers. If, on the other hand, they are highly-idealized, then, in principle, one cannot assign such interpretations. However, assigning interpretations to a deep learning model’s learned transformations is, *in practice*, notoriously frustrated by opacity [Lip18, Rüz22, Rud19, Due22b].

DLMs are said to be epistemically opaque [Hum04]. This means that, following Humphreys, it is impossible for someone to know all of the factors that are epistemically relevant to the model’s behavior. The point is perhaps best made by [Cre20], who identifies three levels of transparency in complex, computational systems: ‘Algorithmic’, ‘Structural’, and ‘Runtime’.¹⁰ DLMs lack algorithmic transparency, as it is impossible to identify the high-level logical rules that govern the learned transformations of inputs to outputs. They also lack structural transparency, rendering it unclear whether or how the distribution of weights and parameterization implements the high-level logical rules.

As a result, opacity blocks a full assessment of the representational status of deep learning models for local and global reasons. Locally, because the models are structurally opaque, it is impossible to directly evaluate *how* components (units and weights) of the hidden layers relate to aspects of the target. Globally, because the models are algorithmically opaque, it is impossible to directly evaluate *whether* the components of the hidden layers relate to aspects of the target. Of course, this argument does not establish that DLMs are not richly-representational. Rather, it shows that, due to opacity, one cannot directly establish the representational status of deep learning models. Instead, one must turn to either theoretical or empirical considerations, which is our task in *Section 4*.

4 Considerations of Composition and Distribution

Despite opacity, there may still be empirical, conceptual, and philosophical reasons to believe that deep learning models are more richly representational than merely highly-idealized models. The aim of this section, then, is to get clear about what we are and are not justified in believing about whether a deep learning model’s learned transformations

¹⁰See also [Zer22] for an account of opacity that turns on notions of intelligibility and fathomability.

relate representationally to aspects of the model’s target system. From the preceding arguments, we have seen that 1) the inputs to and outputs from the model can be characterized in terms of the target, and 2) the outputs of the model are a function (a series of learned transformations) of its inputs. Much of the research in explainable AI (XAI) focuses on developing techniques for interpreting learned transformations as a way of making sense of patterns in the model’s data operations [RS20].

There are, however, model-directed and world-directed ways of interpreting a model. From a model-directed perspective, the interpretation aims at making sense of how the model arrives at its outputs, as well as how the model would behave under certain perturbations. For instance, consider gradient saliency [EBCV09] applied to an input layer. Here, one calculates a saliency quantity as the gradient of the loss function with respect to changes in the input as a way to evaluate how the model’s accuracy is a function of inputs from bounded neighborhoods in feature space. A procedure of this kind allows researchers to make model-directed interpretations of intervals within individual input dimensions that contribute the most to the model’s accuracy. Recently, [Due22a] has argued that procedures of this kind can, in the context of scientific *pursuit*, give researchers prima facie evidence that the corresponding aspects of the target represented by the salient inputs are most relevant for the predicted aspects of the target represented by the outputs. Crucially, however, such interpretations are local and do not give researchers understanding of how the model reliably relates inputs to outputs globally [Räz22, Due22b]. Indeed, such approaches have come under greater theoretical scrutiny [NZP18], are empirically fragile [GAZ19], and may not be appropriate for tasks requiring a grasp of overall, high-level network logic, such as detecting anomalies, explaining the saliency of the connection between inputs and outputs, or debugging a model [AGM⁺18].

While AI researchers focus on model-directed evaluations of learned transformations, ambiguity in the literature has led some within the AI community and many outside of it to believe that learned transformations are, in fact, representations or aspects of underlying mechanisms in the target system [Rud19, Lip18, Mit19, Mit21, Bog21]. In particular, because deep learning models learn their own transformations from data, it is thought that interpretation of these transformations might reveal, as yet undiscovered, mechanisms in the target [SM19, DW19]. In this way, the model-directed interpretive aim slips quietly toward a world-directed one.

The remainder of the paper is dedicated to a careful evaluation of some of the key claims in the AI literature concerning learned transformations in DLNs that give rise to and motivate this slippage. In particular, I will attempt to assess how far these claims can be pressed in the service of supporting the belief that deep learning models are any more

representational than highly-idealized models. While written from the functional perspective, the claims that I will be evaluating are exceedingly suggestive of the view that deep learning models are fine-grained representations of their targets. In particular, I focus on questions of whether the compositional and distributed nature of learned transformations lends support to the idea that DLMS are fine-grained representations. I show how easy it is for these claims to be heard from the relational perspective but demonstrate how, when carefully examined, they fail to support the belief that deep learning models are any more representational than has already been established. While it is surely the case that AI researchers (insiders) are able to sift through the many instances of loose, metaphorical, or otherwise slippery meaning, as I will show, there is no reason to believe that scientists in other disciplines (not to mention philosophers) are always as nimble.

4.1 Composition

Consider the following claims. Deep learning models are hierarchical, *composed* of “multiple levels of representation” such that information at a given level is transformed “into a representation at a higher, slightly more abstract level.” [L⁺15, p.436] And that “deep architectures can lead to abstract representations because more abstract concepts can often be constructed in terms of less abstract ones.” [B⁺13, p.1802].

If one is not sensitive to the distinction between functional and relational conceptions of representation, it can be tempting to believe that what is being claimed here is that deep learning models encode conceptual primitives at each layer that are then composed into more abstract concepts. If this were true of deep learning models, then, *in principle*, it should be possible to extract from DLMS representations (in the relational sense) of aspects or mechanisms of the target. For example, in [J⁺18] the authors study the performance and learned transformations of a DLM which predicts formation enthalpy of materials. They examine the activations of the network across multiple hidden layers to evaluate how the network is arriving at its predictions. The authors claim to observe that the first layer of the network clearly groups elements based on their group number and period and that later layers represent interactions between elements. Here is the explanation they provide: “The early layers of the network are learning features based directly on the input values (i.e., presence of certain types of elements)... but it is clear that the later layers are more related to interactions between elements than the presence of single elements. Overall, the activations for both single elements and binary compounds demonstrate the power of deep learning networks to learn essential domain knowledge without specially-designed inputs [J⁺18, p.7].” Citing the quote from [L⁺15] above, the authors reason that the network is able to learn domain knowledge in this way because

“each layer of the network is gradually learning more complex features in a way similar to networks built for image classification.” [J+18, p.7]

Deep neural networks (particularly ConvNets) certainly pool *information* from one layer into the next. As I demonstrated in *Section 3*, successive layers are mathematical transformations of information in prior layers. Yet, as I argue in this section, the claim that DLNs *compose* salient concepts into something like knowledge of the empirical domain from which the training data are drawn is not justified. The reason for this is that we do not have any good prior reason to believe that the network is, at any level, representing such contents. Rather, that is the assumption we are *starting* with. It is no help to insist that what is composed are ‘conceptual primitives’ or ‘micro-features’ [Hin84] that are just too complex for humans to intuit, because this claim is in need of as much (if not more) support as the claim that the contents are, in principle, humanly interpretable. After all, if they are not, *even in principle*, humanly interpretable, then what reason would we have for believing that they are there at all?

Nevertheless, there are at least three distinct approaches to supporting the idea that deep learning models are composed of multiple levels of representation as opposed to mere information transformation. *Approach 1* involves arguing that the deep neural networks provide biologically plausible models of human cognition; *Approach 2* argues that there is compelling empirical evidence that neural networks compose abstract, meaningful concepts from meaningful conceptual primitives; *Approach 3* argues that the nature of composition in DNNs is representation composition and, therefore, representational.

Approach 1: One intuition that could motivate the idea that learned transformations are composed into representational contents comes from our neuroscientific understanding of composition in the human (and primate) visual cortex. Like a deep network, the visual cortex is organized into layers of neurons in which those at one layer ‘output’ their activation magnitudes to neurons at the next layer. Empirical evidence in *neuroscience* supports the conclusion that succeeding layers detect increasingly complex contents *composed* of the elements detected by prior layers in *mammalian brains*. Early layers detect edges or boundaries where there are sharp discontinuities in certain regions. Excitations by edges are passed to higher-layer neurons that are, in turn, excited by stable combinations of edges, and so on until the visual cortex somehow produces in you recognition of an object. Given that DLNs are arranged into ‘layers’ and are feed-forward in much the same way, the thought is that they are likely to behave like the visual cortex. This thinking applies neatly to ConvNets which are also arranged in such that they have ‘receptive fields’ (a region of pixel space values passed to a unit). Indeed, because ConvNets perform so well at vision tasks in comparison to mammalian visual abilities [CHY+14], it

is widely assumed that the best explanation for their accuracy is that they behave rather like the visual cortex. That is, they are arranged and perform in such a way as to be a biologically plausible model of parts of human cognition.

Yet, this would amount to nothing more than question-begging and would be rather like claiming that airplanes can fly because birds also have wings. Philosopher Catherine Stinson has argued persuasively for the implausibility of something like *Approach 1* [Sti20]. Briefly, there are significant differences between visual processing in the brain and what takes place in ConvNets. In addition to a feed-forward flow of information (which brains and ConvNets ‘share’), in the visual cortex, there is roughly an order of magnitude *more* feed-backward flow of information. There is no analogous information back-flow in a deep network. Moreover, brains are better thought of as analog devices, not digital, and units in deep nets lack *virtually all* of the dynamics of biological neurons [CK19, JK21]. In *Section 4.2*, I consider the more general posit that, because DNNs are brain-*like*, they must be representational.

Approach 2: Saliency methods applied to a network’s hidden layers can appear to annotate regions of feature space that networks leverage in classification. For example, a correctly classified image of an eagle might generate a saliency map which indicates the salience of pixel values in the areas corresponding to what humans observe to be the eagle’s beak, eyes, and the region of high color contrast between its head and torso. The conclusion that researchers might draw from this is that ‘beak’, ‘eyes’, and ‘white head’ are the aspects of the target image that the network learns and relies upon in modeling ‘eagleness’.

Yet, procedures of this kind are mercilessly underdetermined (a concern shared increasingly within the machine learning community [D⁺20, NZP18, GAZ19, AGM⁺18] and the philosophical community [Räz22, RB22, Due22b]). As I argued above, the results of saliency procedures applied to the input layer might conceivably provide insight into how input aspects of the target affect the accuracy of the model on certain tasks. Yet, these local procedures are model-directed—they tell us something about how regions of input feature space contribute to model accuracy, *not* how aspects of the input target are related to aspects of the output target.

Moreover, the underdetermination of such procedures blocks our ability to empirically evaluate their representational efficacy. For instance, it could be that the heatmap is rather cool around the eagle but warm around the background indicating that the network has picked up on statistical correlations that have nothing to do with eagles (like blurry backgrounds that tend to accompany wildlife photos [L⁺13]). This kind of thing,

known as shortcut learning, is common, and it is notoriously difficult to determine when it is and is not happening [G⁺20, A⁺19]. In fact, recent analysis has found that deep ConvNets trained on popular benchmarks overwhelmingly use nonsense, statistical shortcuts that generalize across the data distribution of benchmark images [C⁺20]. This ‘model overinterpretation’ is defined to “occur when a classifier finds strong class-evidence in regions of an image that contain no semantically salient features [C⁺20, pg. 1]” and that this ‘pathology’ applies equally to adversarially robust models.

Even if we make a strong assumption that a model is not keying on statistical shortcuts, visual inspection of saliency maps is still highly underdetermined. For instance, it could be that *inactivity* of certain units is as, if not more, important to classification. After all, that p is *not* q is informative. In fact, *Approach 2* and *Approach 1* both suffer from empirical counter examples drawn from evidence that inactive or low-active neurons in the mammalian brain are informationally salient [JK21]. Adversarial examples in image classification also serve as strong counter examples against *Approach 2*. Here, humanly imperceptible perturbations made to the pixel values of otherwise correctly machine-classified images induce astonishingly inaccurate classifications for which the network is, nevertheless, extremely confident [N⁺15].

Approach 3: As we saw in *Section 3*, deep learning models are transitive, compositional functions. One might be tempted to think that the formal properties of neural network function composition give us a reason to think that they encode representations at each layer. The thinking is something like “deep learning really is a *representation*-learning method in which concepts go in, are represented as functions which are further composed, recombined and assembled, and higher-level, abstract concepts come out.” As Buckner puts it, the abstract concepts that come out are “hierarchically composed all the way down, from pixels and color channels to lines, angles, and shape” and that formal aspects of deep networks serve to “detect and compose each layer of features into those at the next layer of abstraction.” [Buc18, pg. 5347]

The AI literature tends to use the terms ‘layer’ and ‘level’ interchangeably which facilitates an easy association (and *conflation*) with notions of levels of organization. This, in turn, has both metaphysical and ontological consequences for how we interpret what is happening *layer-wise* within a neural network. The compositional thesis leverages the metaphor that layers are *levels* of organization and, moreover, since there is a lot of function composition going on in a DLM, the connection to abstract concept composition is ready-made [FP88]. Thinking of this kind can be seen playing out in the materials science paper cited above.

To say that a representation at a given level is a “transformed representation” of the previous level is, presumably, to say something like layer l_n is a representation of l_{n-1} . In the same way, l_1 would be a representation of l_0 . This means that each layer is, itself, a representation, and, moreover, it is a representation of a representation. If successive layers are representations of prior layers, we must conclude that l_n (the final layer) is a representation of l_0 (the initial layer). We already saw that the output of a deep network is a highly nonlinear transformation of the input. However, if we accept this kind of approach, it still does not establish that individual layers represent aspects of the target. Rather, it establishes that succeeding layers represent preceding layers.

There is, however, the possibility of *informational transitivity* such that, if B represents A , and C represents B , then information about A will be present in the representation C . If we consider a photograph of a painting of an orchard that contains the whole painting, then the visual information encoded in the painting is, for the most part, preserved. Nevertheless, the photograph is a representation of *the painting*, not the orchard. This process can be repeated by, say, painting a picture of the photograph and then photographing the new painting —on and on. Presumably, specific informational signals such as locality will be preserved such that, if a pixel in the second photograph is red, then an adjacent, contiguous pixel will be red with high probability. If that pixel is not red, then this region in pixel space likely corresponds to a boundary between one object and another. This provides some *prima facie* reason to believe that the contents of the original painting are informationally present in the final photograph. Extending this line of reasoning to the flow of information through a deep neural network *seems* reasonable, particularly considering that the output layer is reached by recursively transforming recursively transformed vectors. However, adversarial examples provide good reason to doubt that this so-called ‘smoothness prior’, or locality generalization, is guaranteed. In fact, informational signals are not reliably stable throughout DLMs [S⁺13]. In this sense, not only is function composition distinct from semantic composition, but, function composition can lead to semantic loss. Strangely, non-robust models have proven to be very effective for prediction raising the possibility that semantic coherence and predictive efficacy do not go hand in hand [T⁺18, I⁺19, ZF19]. Besides, even if the smoothness prior *did* hold, this would be consistent with a functional conception of representation where an extension of the concept to a relational conception would still stand in need of justification.

From what we have seen, considerations of composition fail to provide us with a good reason to believe that any given DLM encodes a fine-grained representational model of its target. Moreover, none of the empirical evidence that purports to support the claim has achieved that aim. I turn now to considerations of distribution.

4.2 Distribution

That deep learning models are ‘distributed’ is often leveraged to explain why interpretations of the model are difficult to divine. Their distributed nature provides *prima facie* reason to believe that *if* DLMS encode fine-grained representations of their targets, *then* these representations will be difficult to suss out since they are distributed throughout an often astonishingly extensive network. This is an example of what Creel refers to as structural opacity. Here, the high-level logic that governs the transformation of input to output, describable in terms of the target system, is inaccessible due to how that logic is realized in the network [Cre20]. Of course, given the preceding discussion, we have encountered no good reason to believe the antecedent of this conditional.

Nevertheless, it is worth considering whether distribution yields good reasons to believe that DLMS encode fine-grain representations of their targets *independent* of considerations of composition. The concept of distribution allows for two distinct *Tacks* to accomplish this, each based on a slightly different way of understanding the distribution thesis.

Tack 1: This maneuver argues from a particular interpretation of the idea of distributed transformations expressed in slightly different terms by Hinton and Bengio. Hinton’s version: “A distributed representation uses a unit for a set of items, and it implicitly encodes a particular item as the intersection of the sets that correspond to the active units.” [Hin84, p.94] Bengio’s version: “. . . each concept is represented by having k features being turned on or active, while each feature is involved in representing many concepts.” [B⁺13, p.1801] To see how *Tack 1* interprets these claims, it is helpful to consider an example of a distributed representation that fits the interpretation. Biological taxonomic trees are distributed representations because an organism’s *Family* can be represented as the *intersection* of more general or abstract taxonomic ranks, each of which participates in representing many families. Since a fine-grained representational model is such that one can specify in a regular and systematic manner what the constituents of the model mean, interpreting the distribution thesis along the lines of *Tack 1* gives us a clear path to shore. Here, the constituents of the distributed representation are the individual units, and, in principle, the interpretation of the model can be carried out in the same manner as that of the taxonomic tree. The difficulty, when it comes to interpreting DLMS, according to *Tack 1*, is that, with many units, determining the sets of contents that they represent is daunting. In this way, perhaps distribution gives us both a reason to believe that DLMS are fine-grained representations of their targets *and* explains why they are structurally opaque.

Yet, *Tack 1* is a nonstarter because it is simply a restatement of the argument from composition, yet, this time, in terms of distribution. As we saw when considering composition (*Section 4.1*), to proceed under the assumption that individual units represent in the way proposed by *Tack 1* is just question-begging. However, one might argue that *Tack 1* does not require a compositional thesis because the individual *layers* of the network are distributed representations. Here, each layer is a vector of units, and the orthogonality of individual units is analogous to the parameters in a linear model such that the weights on a given unit encode the relative contribution of the content *represented by that unit* to the output [G⁺14] which is the entire next layer. However, this claim simply pushes the compositional thesis down to the intra-layer level and does nothing to justify the claim that individual *units* have specifiable contents in terms of the system—it assumes it. Moreover, on this interpretation, DLNs appear to be *local* rather than distributed schemes.

Tack 2: This tack argues for a much stronger interpretation of distribution than *Tack 1*. Here, distribution is interpreted the as implying that representational contents are *fully distributed* throughout the network such that “each [unit] is involved in representing many different [contents]” means *every* weight on *every* unit is involved in computing the representation of *every* content. Given that every unit is “active” in representing every entity (regardless of whether its output is zero), only the entire function can be said to represent any *particular* content. Varying a weight *anywhere*, distributes changes to the representation *everywhere*. A familiar and perhaps more intuitive example of such distributional effects comes from the mathematics of Fourier transforms, whereby a modification of f anywhere distributes changes to \hat{f} everywhere.

It is worth pointing out that a view like the one motivated by *Tack 2* is certainly consistent and compatible with a *functional* understanding of representation. That is, there is no reason to think that a model’s learned transformations cannot be fully distributed in this way (which might be one reason why widespread transfer learning has proved so difficult). However, if we have a distributed (*relational*) representation of some aspects of the model’s target, where might we look for the assignable meaning? For any given content, the content of that representation would be distributed throughout all units and innumerable connections. So, it isn’t any wonder that digging out fine-grained contents from DLNs has proved impractical. In this way, *Tack 2* explains why we struggle to recover mechanisms, knowledge, and other fine-grained contents from DLNs.

But, how does this interpretation support the antecedent claim that the network encodes fine-grained representational contents of its target? It runs into immediate conceptual

difficulty. Far from giving us good reason to believe that the DLMs are fine-grained representational models, *Tack 2* gives us good reason to believe that the model’s contents must be either highly contingent or completely arbitrary. Given that, in a distributed representation, each unit is involved in representing *every* content, there is certainly no *a priori* reason to suspect that individual units would encode *discrete*, semantically meaningful contents. After all, every unit is sensitive to every parameter in the input space and, unlike local representational schemes, in distributed representations, a change in the value of a single weight (which would be affected by either adding or subtracting a single sample to the training data, changing the number of training epochs, adjusting the learning rate, adding a layer, or not changing anything and simply doing the whole training again), causes a change in the sensitivity and learned transformations everywhere such that the contribution made by each of the individual units to relating to every content in the target system is modified. Given that unit-wise contribution is globally modifiable by means of distinct modifications to individual weights, there can be no good conceptual reason to believe that individual units encode specifiable semantic content because that content is far from invariant and highly contingent.

To resolve this difficulty, *Tack 2* must appeal to the idea that fully distributed representation allows for a plausible analogy between learned transformations in DLMs and functional representations in brains. After all, we have good reason to believe that a brain encodes representational models of its environments, these representations are distributed in the brain’s neural architecture, and we have a tough time finding them in neural correlates [Sha18]. Since we see representational models in highly distributed machines like brains, we should expect them in similar machines. That is, one might insist, “this is how brains work. Surely, you do not want to deny that brains encode distributed representations!”.

However, there are several problems with this approach (some of which we have encountered already). First, the way fine-grained representational models represent the world and how the world is represented in the brain are very different. While it is true that brains are distributed systems in which specific neurons have been observed to be sensitive to particular contents in the world, that is a) consistent with a functional conception of representation, and b) a far cry from believing that a fine-grained representational model of the world could be *read off* of the neural architecture of a human brain. The neuroscientific community abandoned such thinking in the early 2000s. While we have good reason to believe that the brain encodes highly fine-grained representational models, this is not because we have observed them in brains. Studies of neural correlates are notoriously under-determined in much the same way as the salience methods discussed above. Instead, brains routinely make their representations explicit to consciousness

through various cognitive and communicative acts. In fact, it has recently been argued that representational encodings of the sort that one might seek to locate in DLMs are both logically and empirically in conflict with the causal structure and activity of the brain [Bre19]. As Rumelhart, the famous cognitive scientist and AI pioneer, once said, “information is not stored anywhere in particular. Rather it is stored everywhere. Information is better thought of as ‘evoked’ than ‘found’.” [R+86]. Even if certain units appear to *correlate* with certain determinate features of reality, the semantic content of that unit remains highly under-determined. That the brain has evolved a means to transcribe *its* models is certainly not a good reason to believe that DLMs encode such models. Finally, Hinton himself admits that given the nature of distributed representation, units could “correspond to conceptual primitives, or they may have no particular meaning as individuals” [R+86, p. 33]. In fact, as I have shown, there is no good reason why they should.

Writing more than three decades before Rumelhart, Wittgenstein quipped that “nothing seems more possible to me than that people some day will come to the definite opinion that there is no copy in the . . . nervous system which corresponds to a *particular* thought, or a *particular* idea, or memory.” [Wit96] And, we have no good reason to think that the same must not be said of deep learning models. *Tacks 1* and *2*, then, are fruitlessly beating to windward.

Throughout *Sections 3* and *4*, I have argued that the nature of deep learning models provides us with no good reason to believe that they encode fine-grained representational models of their targets. If, in the course of a scientific investigation, a DLM is examined in such a way that a scientist infers an explanation for its predictions in terms of relations that hold between features of the target system, then we need good reasons (justification) for believing that what is inferred is, in fact, encoded in the network, and these reasons must be independent of the belief that DLMs are fine-grained representational models. But, no such justification is forthcoming. This has been my claim throughout.

As a result, I claim that deep learning models are best conceived as type of highly-idealized model, though situating deep learning in that wider class is a topic for future analysis.¹¹

¹¹It is worth pointing out, however, that their failure to generalize beyond the target distribution upon which they were trained seems to rule out the possibility that they should be thought of as minimal-models.

5 Conclusion

Deep learning has become increasingly central to science, in large part due to its capacity to quickly, efficiently, and accurately predict and classify phenomena of scientific interest. It is common for both scientists and deep learning researchers to refer to DLMs as having encoded representational models of their targets. Research into understanding and interpreting these models proceeds under a pair of assumptions. The first is that DLMs functionally represent data in a way that is conducive to accurate prediction and classification. These learned transformations of data can be interrogated in a manner that allows for some local understanding of how aspects of the input data contribute to the model’s overall accuracy. This model-directed assumption, though empirically dubious, is justified by a conception of representation that is mechanistic and functional in nature [Cao22]. The second assumption, however, takes learned transformations to represent aspects of the target system in a fine-grained relational sense. On this assumption, it is possible to, in principle, interpret the model’s learned transformations in a world-directed manner to learn about features, relations, mechanisms, or other features of the target system. If this were the case, then successful interpretation could furnish scientists with higher and more sophisticated levels of scientific understanding about the world. Yet, the arguments of this paper have sought to demonstrate that, in general, we have no good reason to believe that DLMs are fine-grained representations of their targets. At most, we are justified in classifying them as highly-idealized models.

This result exposes a potential epistemic risk associated with attempts to interpret DLMs as fine-grained representational models, as such attempts suffer from being either highly under-determined or unfalsifiable. This means that, as of now, the direct interpretation of deep learning model parameters for scientific explanations is not epistemically justified. However, and importantly, this does not mean that deep learning cannot aid in furthering scientific discovery [Due22a]. For instance, predictions made on the basis of DLMs can serve as data used for the evaluation or extension of certain theories [D⁺18], supply researchers with novel intuitions concerning the behavior of specific systems [W⁺19], or simply bypass computational roadblocks on the way to discovery [S⁺20]. In short, while we have no good reason to believe that deep learning models stand in fine-grained representational relation to the world, this does not mean that their behavior [RCO⁺22] and astonishing predictive capacities cannot be leveraged as a means to deeper, more fundamental scientific understanding [Wim87].

6 Acknowledgements

I am grateful to Katie Creel, Kevin Davey, James Evans, Ian Foster, David Kinney, Tyler Millhouse, Jennifer Nagel, Tom Pashby, Jamshid Sourati, Rick Stevens, William Wimsatt, and audiences at the University of Chicago’s Theoretical Philosophy Workshop and the Environmental Data Science Seminar Series for valuable discussions on earlier drafts of this manuscript.

7 Funding

This work was supported by the US National Science Foundation #2022023 NRT-HDR: AI-enabled Molecular Engineering of Materials and Systems (AIMEMS) for Sustainability.

References

- [A⁺19] Martin Arjovsky et al. Invariant risk minimization. *arXiv preprint arXiv:1907.02893*, 2019.
- [AGM⁺18] Julius Adebayo, Justin Gilmer, Michael Muelly, Ian Goodfellow, Moritz Hardt, and Been Kim. Sanity checks for saliency maps. *Advances in neural information processing systems*, 31, 2018.
- [B⁺13] Yoshua Bengio et al. Representation learning: A review and new perspectives. *IEEE TPAMI*, 35(8):1798–1828, 2013.
- [B⁺21] Ben Baker et al. A philosophical understanding of representation for neuroscience. *arXiv preprint arXiv:2102.06592*, 2021.
- [Bat10] Robert W Batterman. On the explanatory role of mathematics in empirical science. *The British journal for the Philosophy of Science*, 2010.
- [BC⁺22] Jonathan Birch, Kathleen A Creel, et al. Clinical decisions using ai must consider patient values. *Nature Medicine*, 28(2):229–232, 2022.
- [BK09] Mieke Boon and Tarja Knuuttila. Models as epistemic tools in engineering sciences. In *Philosophy of technology and engineering sciences*, pages 693–726. Elsevier, 2009.
- [BLK22] Ben Baker, Benjamin Lansdell, and Konrad P Kording. Three aspects of representation in neuroscience. *Trends in Cognitive Sciences*, 2022.

- [Bog21] Florian J Boge. Two dimensions of opacity and the deep learning predicament. *Minds and Machines*, pages 1–33, 2021.
- [BR14] Robert W Batterman and Collin C Rice. Minimal model explanations. *Philosophy of Science*, 81(3):349–376, 2014.
- [Bre19] Romain Brette. Is coding a relevant metaphor for the brain? *Behavioral and Brain Sciences*, 42, 2019.
- [Buc18] Cameron Buckner. Empiricism without magic: Transformational abstraction in deep convolutional neural networks. *Synthese*, 195(12):5339–5372, 2018.
- [C⁺20] Brandon Carter et al. Overinterpretation reveals image classification model pathologies. *arXiv preprint arXiv:2003.08907*, 2020.
- [Cao18] Rosa Cao. Computational explanations and neural coding. In *The Routledge handbook of the computational mind*, pages 283–296. Routledge, 2018.
- [Cao22] Rosa Cao. Putting representations to use. *Synthese*, 200(2):151, 2022.
- [CHY⁺14] Charles F Cadieu, Ha Hong, Daniel LK Yamins, Nicolas Pinto, Diego Ardila, Ethan A Solomon, Najib J Majaj, and James J DiCarlo. Deep neural networks rival the representation of primate it cortex for core visual object recognition. *PLoS computational biology*, 10(12):e1003963, 2014.
- [CK19] Radoslaw M Cichy and Daniel Kaiser. Deep neural networks as scientific models. *Trends in cognitive sciences*, 23(4):305–317, 2019.
- [CM84] Nancy Cartwright and Ernan McMullin. *How the laws of physics lie*, 1984.
- [Con07] Gabriele Contessa. Scientific representation, interpretation, and surrogate reasoning. *Philosophy of science*, 74(1):48–68, 2007.
- [Cre20] Kathleen A Creel. Transparency in complex computational systems. *Philosophy of Science*, 87(4):568–589, 2020.
- [D⁺18] Phoebe MR DeVries et al. Deep learning of aftershock patterns following large earthquakes. *Nature*, 560(7720):632, 2018.
- [D⁺20] Alexander D’Amour et al. Underspecification presents challenges for credibility in modern machine learning. *arXiv preprint arXiv:2011.03395*, 2020.
- [DCF03] Newton CA Da Costa and Steven French. *Science and partial truth: A unitary approach to models and scientific reasoning*. Oxford University Press on Demand, 2003.

- [dO21] Guilherme Sanches de Oliveira. Representationalism is a dead end. *Synthese*, 198(1):209–235, 2021.
- [Dre81] Fred Dretske. *Knowledge and the Flow of Information*. 1981.
- [Dre91] Fred Dretske. *Explaining behavior: Reasons in a world of causes*. MIT press, 1991.
- [Due22a] Eamon Duede. Deep learning opacity in scientific discovery. (*Forthcoming at Philosophy of Science*) *arXiv preprint arXiv:2206.00520*, 2022.
- [Due22b] Eamon Duede. Instruments, agents, and artificial intelligence: novel epistemic categories of reliability. *Synthese*, 200(6):491, 2022.
- [DW19] Raffaele Tito D’Agnolo and Andrea Wulzer. Learning new physics from a machine. *Physical Review D*, 99(1):015014, 2019.
- [EBCV09] Dumitru Erhan, Y. Bengio, Aaron Courville, and Pascal Vincent. Visualizing higher-layer features of a deep network. *Technical Report, Université de Montréal*, 01 2009.
- [Fla12] Peter Flach. *Machine learning: the art and science of algorithms that make sense of data*. Cambridge university press, 2012.
- [FN16] Roman Frigg and James Nguyen. The fiction view of models reloaded. *The Monist*, 99(3):225–242, 2016.
- [FN+20] Roman Frigg, James Nguyen, et al. *Modelling nature: An opinionated introduction to scientific representation*. Springer, 2020.
- [FP88] Jerry A Fodor and Zenon W Pylyshyn. Connectionism and cognitive architecture: A critical analysis. *Cognition*, 28(1-2):3–71, 1988.
- [Fre03] Steven French. A model-theoretic account of representation,. *Philosophy of Science*, 70(5):1472–1483, 2003.
- [Fri10] Roman Frigg. Fiction and scientific representation. In *Beyond mimesis and convention*, pages 97–138. Springer, 2010.
- [FS+21] Gregory Falco, Ben Shneiderman, et al. Governing ai safety through independent audits. *Nature Machine Intelligence*, 3(7):566–571, 2021.
- [G+14] Ross Girshick et al. Rich feature hierarchies for accurate object detection and semantic segmentation. In *IEEE CVPR*, pages 580–587, 2014.

- [G⁺20] Robert Geirhos et al. Shortcut learning in deep neural networks. *Nature Machine Intelligence*, 2(11):665–673, 2020.
- [GAZ19] Amirata Ghorbani, Abubakar Abid, and James Zou. Interpretation of neural networks is fragile. In *Proceedings of the AAAI conference on artificial intelligence*, volume 33, pages 3681–3688, 2019.
- [GBC16] Ian Goodfellow, Yoshua Bengio, and Aaron Courville. *Deep learning*. MIT press, 2016.
- [Gie04] Ronald N Giere. How models are used to represent reality. *Philosophy of science*, 71(5):742–752, 2004.
- [Gie10] Ronald N Giere. *Explaining science: A cognitive approach*. University of Chicago Press, 2010.
- [Har08] Inman Harvey. Misrepresentations. In *ALIFE*, pages 227–233, 2008.
- [Hin84] Geoffrey E Hinton. Distributed representations. 1984.
- [Hof17] Robert R Hoffman. A taxonomy of emergent trusting in the human–machine relationship. *Cognitive Systems Engineering*, pages 137–164, 2017.
- [Hum04] Paul Humphreys. *Extending ourselves: Computational science, empiricism, and scientific method*. Oxford University Press, 2004.
- [I⁺19] Andrew Ilyas et al. Adversarial examples are not bugs, they are features. *arXiv preprint arXiv:1905.02175*, 2019.
- [J⁺18] Dipendra Jha et al. Elemnet: Deep learning the chemistry of materials from only elemental composition. *Scientific reports*, 8(1):1–13, 2018.
- [JK21] Ilenna Simone Jones and Konrad Paul Kording. Might a single neuron solve interesting machine learning problems through successive computations on its dendritic tree? *Neural Computation*, 33(6):1554–1571, 2021.
- [L⁺13] Will Landecker et al. Interpreting individual classifications of hierarchical networks. In *2013 IEEE CIDM*, pages 32–38. IEEE, 2013.
- [L⁺15] Yann LeCun et al. Deep learning. *nature*, 521(7553):436, 2015.
- [Lan15] Marc Lange. On “minimal model explanations”: A reply to batterman and rice. *Philosophy of Science*, 82(2):292–305, 2015.
- [Les19] David Leslie. Understanding artificial intelligence ethics and safety. *arXiv preprint arXiv:1906.05684*, 2019.

- [Lev15] Arnon Levy. Modeling without models. *Philosophical studies*, 172:781–798, 2015.
- [Lip18] Zachary C Lipton. The mythos of model interpretability. *Queue*, 16(3):31–57, 2018.
- [LM20] Matthew L Leavitt and Ari Morcos. Towards falsifiable interpretability research. *arXiv preprint arXiv:2010.12016*, 2020.
- [Mas19] Michela Massimi. Two kinds of exploratory models. *Philosophy of Science*, 86(5):869–881, 2019.
- [Mil89] Ruth Garrett Millikan. Biosemantics. *The journal of philosophy*, 86(6):281–297, 1989.
- [Mit19] Melanie Mitchell. *Artificial intelligence: A guide for thinking humans*. Penguin UK, 2019.
- [Mit21] Melanie Mitchell. Why ai is harder than we think. *arXiv preprint arXiv:2104.12871*, 2021.
- [N⁺15] Anh Nguyen et al. Deep neural networks are easily fooled. In *IEEE CVPR*, pages 427–436, 2015.
- [Nea95] Karen Neander. Misrepresenting & malfunctioning. *Philosophical Studies*, 79:109–141, 1995.
- [NZP18] Weili Nie, Yang Zhang, and Ankit Patel. A theoretical explanation for perplexing behaviors of backpropagation-based visualizations. In *International Conference on Machine Learning*, pages 3809–3818. PMLR, 2018.
- [OEN⁺22] Catherine Olsson, Nelson Elhage, Neel Nanda, Nicholas Joseph, Nova Das-Sarma, Tom Henighan, Ben Mann, Amanda Askell, Yuntao Bai, Anna Chen, et al. In-context learning and induction heads. *arXiv preprint arXiv:2209.11895*, 2022.
- [Par20] Wendy S Parker. Model evaluation: An adequacy-for-purpose view. *Philosophy of Science*, 87(3):457–477, 2020.
- [Plu01] Anya Plutynski. Modeling evolution in theory and practice. *Philosophy of Science*, 68(S3):S225–S236, 2001.
- [R⁺86] David E Rumelhart et al. A general framework for parallel distributed processing. *Parallel distributed processing*, 1(45-76):26, 1986.

- [R az22] Tim R az. Understanding deep learning with statistical relevance. *Philosophy of Science*, 89(1):20–41, 2022.
- [RB22] Tim R az and Claus Beisbart. The importance of understanding deep learning. *Erkenntnis*, pages 1–18, 2022.
- [RCO⁺22] Iyad Rahwan, Manuel Cebrian, Nick Obradovich, Josh Bongard, Jean-Fran ois Bonnefon, Cynthia Breazeal, Jacob W Crandall, Nicholas A Christakis, Iain D Couzin, Matthew O Jackson, et al. Machine behaviour. *Machine Learning and the City: Applications in Architecture and Urban Design*, pages 143–166, 2022.
- [RHW86] David E Rumelhart, Geoffrey E Hinton, and Ronald J Williams. Learning representations by back-propagating errors. *nature*, 323(6088):533–536, 1986.
- [Ric12] Collin Rice. Optimality explanations: A plea for an alternative approach. *Biology & Philosophy*, 27:685–703, 2012.
- [RS20] Maithra Raghu and Eric Schmidt. A survey of deep learning for scientific discovery. *arXiv preprint arXiv:2003.11755*, 2020.
- [Rud19] Cynthia Rudin. Stop explaining black box machine learning models for high stakes decisions and use interpretable models instead. *Nature Machine Intelligence*, 1(5):206–215, 2019.
- [S⁺13] Christian Szegedy et al. Intriguing properties of neural networks. *arXiv preprint arXiv:1312.6199*, 2013.
- [S⁺20] Andrew W Senior et al. Improved protein structure prediction using potentials from deep learning. *Nature*, 577(7792):706–710, 2020.
- [SH19] Henry Shevlin and Marta Halina. Apply rich psychological terms in ai with care. *Nature Machine Intelligence*, 1(4):165–167, 2019.
- [Sha18] Oron Shagrir. The brain as an input–output model of the world. *Minds and Machines*, 28:53–75, 2018.
- [Sha22] Murray Shanahan. Talking about large language models. *arXiv preprint arXiv:2212.03551*, 2022.
- [SM19] Wojciech Samek and Klaus-Robert M uller. Towards explainable artificial intelligence. *Explainable AI: interpreting, explaining and visualizing deep learning*, pages 5–22, 2019.

- [Sti20] Catherine Stinson. From implausible artificial neurons to idealized cognitive models: Rebooting philosophy of artificial intelligence. *Philosophy of Science*, 87(4):590–611, 2020.
- [Suá03] Mauricio Suárez. Scientific representation: Against similarity and isomorphism. *International studies in the philosophy of science*, 17(3):225–244, 2003.
- [Suá04] Mauricio Suárez. An inferential conception of scientific representation. *Philosophy of science*, 71(5):767–779, 2004.
- [Sup66] Patrick Suppes. Models of data. In *Studies in logic and the foundations of mathematics*, volume 44, pages 252–261. Elsevier, 1966.
- [T⁺18] Dimitris Tsipras et al. Robustness may be at odds with accuracy. *arXiv preprint arXiv:1805.12152*, 2018.
- [VF80] Bas C Van Fraassen. *The scientific image*. Oxford University Press, 1980.
- [VF10] Bas C Van Fraassen. *Scientific representation: Paradoxes of perspective*, 2010.
- [VJ] Philippe Verreault-Julien. Representing non-actual targets? *Philosophy of Science*, pages 1–10.
- [W⁺19] Shangying Wang et al. Massive computational acceleration by using neural networks to emulate mechanism-based biological models. *bioRxiv*, page 559559, 2019.
- [Wei12] Michael Weisberg. *Simulation and similarity: Using models to understand the world*. Oxford University Press, 2012.
- [WF17] Charlotte Werndl and Roman Frigg. Mind the gap: Boltzmannian versus gibbsian equilibrium. *Philosophy of Science*, 84(5):1289–1302, 2017.
- [Wim87] William C Wimsatt. False models as means to truer theories. *Neutral models in biology*, pages 23–55, 1987.
- [Wit96] Ludwig Wittgenstein. *Last Writings on the Philosophy of Psychology, volume 1*, volume 1. University of chicago press, 1996.
- [Yar19] Tal Yarkoni. The generalizability crisis. *Behavioral and Brain Sciences*, pages 1–37, 2019.
- [Zer22] John Zerilli. Explaining machine learning decisions. *Philosophy of Science*, 89(1):1–19, 2022.
- [ZF19] Zhenglong Zhou and Chaz Firestone. Humans can decipher adversarial images. *Nature communications*, 10(1):1334, 2019.