# Trading Communication for Computation in Byzantine-Resilient Gradient Coding

Christoph Hofmeister, Luis Maßny, Eitan Yaakobi, and Rawad Bitar

Abstract—We consider gradient coding in the presence of an adversary, controlling so-called malicious workers trying to corrupt the computations. Previous works propose the use of MDS codes to treat the inputs of the malicious workers as errors and correct them using the error-correction properties of the code. This comes at the expense of increasing the replication, i.e., the number of workers each partial gradient is computed by. In this work, we reduce replication by proposing a method that detects the erroneous inputs from the malicious workers, hence transforming them into erasures. For s malicious workers, our solution can reduce the replication to s+1 instead of 2s+1 for each partial gradient at the expense of only s additional computations at the main node and additional rounds of light communication between the main node and the workers. We give fundamental limits of the general framework for fractional repetition data allocation. Our scheme is optimal in terms of replication and local computation but incurs a communication cost that is asymptotically, in the size of the dataset, a multiplicative factor away from the derived bound.

#### I. Introduction

Consider the setting of a main node possessing large amounts of data on which a machine learning model shall be trained using gradient descent. To speed up the learning process, the main node distributes the computations to several worker nodes [1], [2]. One of the main vulnerabilities of distributed gradient descent is the presence of Byzantine errors corrupting some workers' computation results [3]. Even a single corrupted computation result can drastically deteriorate the performance of the algorithm [4].

The problem of tolerating Byzantine errors in distributed computing has been considered in different settings. For example, for linear computations, i.e., matrixmatrix or matrix-vector multiplications, [5], [6] use Freivalds' algorithm to detect Byzantine errors with high probability and exclude them in further processing. For polynomial computations, [7] uses properties of error-correcting codes to correct the erroneous results. Other approaches towards the mitigation of erroneous results include the use of group testing and Reed-Solomon codes [8], and homomorphic hash functions [9]. For a more comprehensive review of the existing literature, we refer the interested reader to [5].

For distributed gradient descent each worker computes a gradient of a so-called loss function for local training

CH, LM, and RB are with the School of Computation, Information and Technology at the Technical University of Munich, Germany. Emails: {christoph.hofmeister, luis.massny, rawad.bitar}@tum.de

EY is with the CS department of Technion—Israel Institute of Technology, Israel. Email: yaakobi@cs.technion.ac.il

This project has received funding from the Technical University of Munich - Institute for Advanced Studies, funded by the German Excellence Initiative and European Union Seventh Framework Programme under Grant Agreement No. 291763, by the Bavarian Ministry of Economic Affairs, Regional Development and Energy within the scope of the 6G Future Lab Bavaria, and by DFG (German Research Foundation) projects under Grant Agreement No. WA 3907/7-1 and No. BI 2492/1-1.

data. The main node aggregates the locally computed gradients into a total gradient. The problem of Byzantine errors in this context, has been first tackled using robust aggregation functions, which select only a subset of the workers' results. The selection is based on minimizing the distance to other results [4], [10]–[14], by assigning a sanity score to each result [15], or by general consistency checks [16]. Using such aggregation functions, however, the resulting gradient estimate may be only an inexact approximation of the desired total gradient in the error-free case. This increases the runtime for the gradient descent algorithm, see e.g. [17] and references therein, and might perform poorly in some particular settings, e.g., when the distribution of the training data is not identical among the workers [18], [19]. Moreover, advanced gradient descent techniques, such as the momentum method [20], are in general not compatible with approximate schemes [19].

Due to the latter, the problem of tolerating Byzantine errors in distributed gradient descent with exact recovery has been approached from a coding-theoretic perspective. For linear and polynomial computations, coding over the input data at the main node has been proposed in [7] and [21]. Since the computations in gradient descent are highly non-linear in general, these approaches might not be applicable. Instead, the work of [22] introduces DRACO, a framework that performs coding over the computation results at the workers. The authors build on the idea of gradient coding [19], which had originally been designed to mitigate the effect of stragglers, i.e., slow or unresponsive workers. By replicating each gradient computation to s+1 different workers, gradient coding can tolerate s stragglers by treating them as erasures. Applying the same ideas, DRACO can tolerate s malicious workers instead, treating the computations of malicious workers as errors. This comes at the cost of increasing the replication of each gradient computation to 2s + 1, hence, causing a large computation overhead. Both DRACO and gradient coding are shown to achieve an optimal replication for the respective problem settings.

In this work, we also consider the problem of exact gradient coding in the presence of an adversary controlling s malicious workers, that introduce Byzantine errors in their computation results. In contrast to [22], we define a more general framework in which the main node can run a small number of computations itself to aid in decoding. We propose a scheme that requires a replication of only s+1 at the expense of running s local gradient computations<sup>1</sup>. The idea of running local computations at the main node is also used in [23], [24], where the main node computes an estimate of the true gradient from

 $^1$ A replication of s+1 means that each gradient computation is run s+1 times; the cost of s local computations is very small in comparison.

only few data samples and discards worker results that have a large distance to this estimate. In contrast to our work, those solutions do not guarantee exact recovery of the total gradient at the main node. We design additional light communication between the workers and the main node to help identify which gradients should be computed locally. We generalize the framework to the case where less than s local computations are allowed at the main node and explore the tradeoff between replication and local computation.

#### II. PROBLEM SETTING

We first set the notation. Matrices and vectors are denoted by upper-case and lower-case bold letters, respectively.  $\mathbf{A}_{i,j}$  refers to the element in row i and column j of the matrix  $\mathbf{A}$ . Scalars are denoted by lower-case letters, sets by calligraphic letters, and lists by fraktal letters, respectively, e.g., a,  $\mathcal{A}$  and  $\mathfrak{A}$ . For an integer  $a \geq 1$ , we define  $[a] \stackrel{\text{def}}{=} \{1,2,\ldots,a\}$ . Let  $\mathfrak{A}_i, i=1,\ldots,t$ , be a collection of lists, we define  $\mathfrak{A}^{(t)}$  to be their concatenation. We use  $\mathbf{1}_{m \times n}$  and  $\mathbf{0}_{m \times n}$  to denote the all-one and all-zero matrices of dimension  $m \times n$ . For a list of symbols, cf. Appendix G.

We consider a synchronous distributed gradient descent setting, in which the goal is to fit the parameters  $\boldsymbol{\theta} \in \mathbb{R}^d$  of a model to a dataset consisting of p samples  $\mathbf{x}_i \in \mathbb{R}^d, i \in [p]$ . This is done by finding (local) optima for the problem  $\underset{\boldsymbol{\theta} \in \mathbb{R}^d}{\operatorname{arg min}} \sum_{i \in [p]} \ell(\boldsymbol{\theta}, \mathbf{x}_i)$  for a per-sample loss

function  $\ell(\boldsymbol{\theta}, \mathbf{x}_i)$ . The gradient descent algorithm starts with a random initialization for the parameter vector, defined as  $\boldsymbol{\theta}^{(0)}$ , and then iteratively applies the update rule  $\boldsymbol{\theta}^{(\tau+1)} = \boldsymbol{\theta}^{(\tau)} - \frac{\eta^{(\tau)}}{p} \sum_{i \in [p]} \nabla \ell(\boldsymbol{\theta}^{(\tau)}, \mathbf{x}_i)$ , where  $\tau$  is the iteration index and  $\eta^{(\tau)} \in \mathbb{R}$  is referred to as the learning rate. For notational convenience we define the evaluation of the gradient of the loss function at individual samples as  $\mathbf{g}_i^{(\tau)} \stackrel{\text{def}}{=} \nabla \ell(\boldsymbol{\theta}^{(\tau)}, \mathbf{x}_i)$  and call them *partial gradients*. We assume the gradients are represented over some finite alphabet  $\mathcal{A}$ , i.e.,  $\mathbf{g}_i^{(\tau)} \in \mathcal{A}^d$ .

Consider a system comprising a main node and n worker nodes, s of which might be malicious. The malicious workers can send arbitrarily corrupted information to the main node. At the start of the procedure, the main node distributes the samples to the workers with some redundancy. Then, each iteration  $\tau$  starts with the main node broadcasting the current parameter vector  $\boldsymbol{\theta}^{(\tau)}$ . The workers then compute the partial gradients  $\mathbf{g}_i^{(\tau)}$  corresponding to the samples they store. At the end of the iteration, the main node must obtain the *full gradient*  $\mathbf{g}^{(\tau)} \stackrel{\text{def}}{=} \sum_{i \in [p]} \mathbf{g}_i^{(\tau)}$  irrespective of the actions of the s malicious workers.

In this work we are concerned with the problem of reliably reconstructing  $\mathbf{g}^{(\tau)}$  exactly at the main node in each iteration  $\tau$ . In the sequel, we only consider a single iteration of gradient descent and omit the superscript  $\tau$ .

#### III. BYZANTINE-RESILIENT GRADIENT CODING

For a better grasp of our ideas, we start with a toy example that captures the concepts introduced and studied.

#### A. How to Catch Liars Efficiently?

Consider a game among three friends Alice (A), Bob (B) and Dan. A and B have p private numbers  $g_1, \ldots, g_p$  whose sum should be communicated correctly to Dan (D). The problem is that one player is trying to cheat on D.

At the first stage each player sends the sum of all numbers to D. Then, the game is played in rounds. At each round, D can first ask A and B questions about  $g_1, \ldots, g_p$ . Only one player is guaranteed to reply truthfully. Then, D can query an oracle to uncover the true value of some of the  $g_i$ 's. The game is repeated until D correctly obtains the desired sum.

**Example 1.** Assume w.l.o.g that A is cheating on D, p=4 and that  $g_i=i$ . In a first stage A and B send the sum of their numbers to D. Assume that A sends the value 2 and B sends the correct value 10. At the first round, D asks A and B to send the sum  $g_1+g_2$ . To create confusion, A acts truthfully and also sends the value 3. Now, D knows that  $g_3+g_4$  is either -1 or 8. So, D decides not to query the oracle yet. He instead moves to the second round and asks A and B to send the value of  $g_3$ . Again, both players send the value 3. Hence, D now knows that  $g_4$  has to be -4 if A is acting honestly or 5 if B is acting honestly. He then decides to query the oracle, obtain  $g_4$ , catch the liar A and obtain the true sum.

This game is the crux of our framework. The private numbers are the gradients computed at the workers, querying the oracle represents local computations at the main node and asking questions is the introduced light communication between the main node and the workers. The figures of merit of this game are: *i*) the minimum number of queries to the oracle that D needs; and *ii*) given that D can only obtain the minimum number of oracle queries and can play several rounds, how many questions does D need to ask the other players to recover the desired sum correctly. For a more elaborate example in the same spirit see Appendix A.

#### B. The Framework

Carrying over this idea to the gradient coding framework, we define next gradient coding schemes resilient against an adversary controlling s malicious workers.

**Definition 1** (Byzantine-resilient gradient coding scheme). A Byzantine-resilient gradient coding scheme tolerating s malicious workers, referred to as s-BGC, is a tuple  $(\mathbf{A}, \mathfrak{E}, \operatorname{dec}, \Pi)$  where

- $\mathbf{A} \in \{0,1\}^{p \times n}$  is a **data assignment matrix** in which  $\mathbf{A}_{i,j}$  is equal to 1 if the *i*-th data sample is given to the *j*-th worker and 0 otherwise,
- the j-th worker and 0 otherwise,
    $\mathfrak{E} \stackrel{\text{def}}{=} (\operatorname{enc}_{j,e} \mid j \in [n], e \in [v])$  is the list of nv encoding functions used by the workers such that  $\operatorname{enc}_{j,1}$  corresponds to a gradient code dictated by  $\mathbf{A}$  and  $\operatorname{enc}_{j,e}$  depends only on the gradients assigned to  $W_j$ ,
- $\Pi = (\Pi_1, \Pi_2)$  is a multi-round protocol in which  $\Pi_1$  selects the indices of the encoding functions to be used by the workers and  $\Pi_2$  selects gradients to be locally computed at the main node,
- and dec is a **decoding function** used by the main node after running the protocol  $\Pi$  to always output the correct full gradient if the number of malicious workers is at most s.

Each worker initially (t=0) sends a vector  $\mathbf{z}_{0,j} \stackrel{\text{def}}{=} \operatorname{enc}_{j,1}(\mathbf{g}_1,\ldots,\mathbf{g}_p) \in \mathcal{A}^d$  that is a codeword symbol of a gradient code [19]. The protocol  $\Pi$  then runs for  $r \in \mathbb{N}$  rounds. In each round  $t \in [r]$ , the main node uses  $\Pi_1$  to select an encoding function  $\operatorname{enc}_{j,e_{t,j}}$  for each worker  $W_j$  and communicates its index  $e_{t,j}$  to the respective worker. Each worker  $W_j$  then computes a response  $\mathbf{z}_{t,j} = \operatorname{enc}_{j,e_{j,t}}(\mathbf{g}_1,\ldots,\mathbf{g}_p) \in \mathcal{A}^{d_{t,j}}$  for some  $d_{t,j} \in \mathbb{N}_0$  and sends a vector  $\widetilde{\mathbf{z}}_{t,j} \in \mathcal{A}^{d_{t,j}}$  to the main node. For honest workers  $\widetilde{\mathbf{z}}_{t,j} = \mathbf{z}_{t,j}$ , while for malicious workers,  $\widetilde{\mathbf{z}}_{t,j}$  may be chosen arbitrarily.

In every round, the main node uses  $\Pi_2$  to choose a set of partial gradients to compute locally. We denote the list of indices of the locally computed partial gradients in round t by  $\mathfrak{I}_t$  and the corresponding list of partial gradient values by  $\mathfrak{G}_t \stackrel{\text{def}}{=} (\mathbf{g}_i \mid i \in \mathfrak{I}_t)$ . Analogously, we define  $\mathfrak{I}_t \stackrel{\text{def}}{=} (\mathbf{z}_{t,j} \mid \forall j \in [n])$  and  $\widetilde{\mathfrak{I}}_t \stackrel{\text{def}}{=} (\widetilde{\mathbf{z}}_{t,j} \mid \forall j \in [n])$ . The protocol  $\Pi_1$  selects the indices of the encoding

The protocol  $\Pi_1$  selects the indices of the encoding functions to be used in the current round t based on the received results and locally computed gradients from previous rounds. After receiving the results in the current round, the main node uses  $\Pi_2$  to select the gradients to compute locally in this round, i.e.,

$$e_{1,t}, \dots, e_{n,t} = \Pi_1 \left( t, \widetilde{\mathfrak{Z}}^{(t-1)}, \mathfrak{I}^{(t-1)}, \mathfrak{G}^{(t-1)} \right),$$
 (1)  
$$\mathfrak{I}_t = \Pi_2 \left( t, \widetilde{\mathfrak{Z}}^{(t)}, \mathfrak{I}^{(t-1)}, \mathfrak{G}^{(t-1)} \right).$$
 (2)

After round r, the main node computes an estimate  $\widehat{\mathbf{g}}$  of  $\mathbf{g}$  using the decoding function  $\widehat{\mathbf{g}} = \mathrm{dec}\left(\widetilde{\mathfrak{Z}}^{(r)}, \mathfrak{I}^{(r)}, \mathfrak{G}^{(r)}\right)$ . The total number of partial gradients computed at the main node is defined as  $c \stackrel{\text{def}}{=} |\mathfrak{I}^{(r)}|$ .

A valid s-BGC scheme must output  $\hat{\mathbf{g}} = \mathbf{g}$  if the number of malicious workers is at most s.

#### C. Figures of Merit

An s-BGC scheme is evaluated by the maximum number of rounds r and the maximum number of local computations c required by  $\Pi$ , and its replication factor and communication overhead defined next.

**Definition 2** (Replication factor and communication overhead). The replication factor of an s-BGC scheme is the average number of workers to which each sample is assigned, i.e.,

 $\rho \stackrel{\text{\tiny def}}{=} \frac{\sum_{i \in [p], j \in [n]} \mathbf{A}_{i,j}}{p}.$ 

The **communication overhead** is the maximum number of symbols from A transmitted from the workers to the main node during  $\Pi$ , i.e.,

$$\kappa \stackrel{\text{\tiny def}}{=} \sum_{t \in [r], j \in [n]} d_{t,j}.$$

We say that a tuple  $(\mathbf{A}, \mathfrak{E}, \operatorname{dec}, \Pi)$  is a  $(r, c, \rho, \kappa)$ -s-BGC scheme if in the presence of at most s malicious workers, the scheme always outputs  $\widehat{\mathbf{g}} = \mathbf{g}$  by requiring at most r communication rounds, at most c local computations, and has replication factor  $\rho$  and a communication overhead less than or equal to  $\kappa$ .

We study settings in which the number of workers n divides s+1, i.e., n=m(s+1) for some integer m and only consider balanced data assignments, i.e.,




Fig. 1. Tradeoff between total worker to main-node communication and number of local computations for our scheme. The parameters are  $s=10,\,1\leq u\leq 11,\,m=1,\,p=1\times 10^4,\,d=1\times 10^6,\,|\mathcal{A}|=2^{16}.$  When considering total communication, the cost of the protocol is outweighed by the cost of transmitting the gradient values. The gap to our bound, given in Theorem 2, is less than  $5\,\mathrm{kB}.$  For c=0 local computations, our scheme is equivalent to DRACO [22]. By requiring less workers, our scheme with u=1 reduces communication by  $48\,\%$  at the expense of at most c=10 local gradient computations at the main node. For comparison, each worker node performs  $p=1\times 10^4$  gradient computations.

every worker computes the same number of gradients. We focus on the particular case of a fractional repetition data assignment [19]. That is, the main node partitions the workers into m groups of size  $\frac{n}{m}$  each and assigns the same data samples to all workers within a group. The data assignment matrix is constructed as

$$\mathbf{A} = \begin{bmatrix} \mathbf{1} \frac{p}{m} \times \frac{n}{m} & \mathbf{0} \frac{p}{m} \times \frac{n}{m} & \cdots & \mathbf{0} \frac{p}{m} \times \frac{n}{m} \\ \mathbf{0} \frac{p}{m} \times \frac{n}{m} & \mathbf{1} \frac{p}{m} \times \frac{n}{m} & \cdots & \mathbf{0} \frac{p}{m} \times \frac{n}{m} \\ \vdots & \vdots & \ddots & \vdots \\ \mathbf{0} \frac{p}{m} \times \frac{n}{m} & \mathbf{0} \frac{p}{m} \times \frac{n}{m} & \cdots & \mathbf{1} \frac{p}{m} \times \frac{n}{m} \end{bmatrix}.$$
(3)

Since we focus on this particular data assignment, the initial worker responses are given by the sum of all computed gradients  $\mathbf{z}_{0,j} = \sum_{i \in [p]} \mathbf{g}_i$ , which form a valid gradient code.

## IV. BOUNDS AND CODE CONSTRUCTIONS OF s-BGC SCHEMES

For the non-trivial case of c< p, i.e., the main node does not compute all the partial gradients locally, the replication factor of any s-BGC scheme is bounded from below by  $\rho \geq s+1$ . In addition, we note that if c=0, then the replication factor of any s-BGC scheme is bounded from below as  $\rho \geq 2s+1$  and can be achieved through DRACO [22]. Conversely, if  $\rho \geq 2s+1$ , then  $c=\kappa=0$  was shown to be achievable. Thus, we are most interested in the case  $s+1\leq \rho \leq 2s+1$ , and we investigate the fundamental tradeoff between c,  $\rho$  and  $\kappa$  for any r.

In particular, we show that for c=s the replication factor  $\rho=s+1$  is achievable. For 0< c< s, we show that for any  $1\leq u\leq s+1$ , if  $\rho\leq s+u$ , then  $c\geq \left\lfloor\frac{s}{u}\right\rfloor$ . For  $\rho=s+u$  and  $c=\left\lfloor\frac{s}{u}\right\rfloor$ , we give a lower bound on  $\kappa$ . We then construct an s-BGC scheme that requires  $c\leq \left\lfloor\frac{s}{u}\right\rfloor$  local computations,  $\rho=s+u$ ,  $r\leq (s+1-u)\left\lceil\log_2\left(\frac{p}{m}\right)\right\rceil$  rounds and  $\kappa\leq (s+1-u)\left(2\left\lceil\log_2\left(\frac{p}{m}\right)\right\rceil+\frac{s+3u}{2\log_2|\mathcal{A}|}\right)$ . As depicted in Fig. 1, for realistic parameter ranges, the local computations drastically reduce the required communication. The communication overhead of the protocol  $\kappa$  is outweighed by the initial transmission of  $\mathbf{z}_{0,j}$ . For a

comparison between our achievability result and converse for  $\kappa$ , cf. Appendix F.

We prove our lower bounds by considering the case where the adversary chooses the following behaviour for the malicious workers.

#### A. Symmetrization Attack for Bounds

The adversary chooses a (potentially corrupted) value for each malicious worker and each partial gradient. We denote worker  $W_j$ 's *claimed* partial gradient results for  $\mathbf{g}_i$  as  $\widetilde{\mathbf{g}}_i^{(j)} \in \mathcal{A}^d$  for all  $j \in [n]$  and  $i \in [p]$ . For honest workers we say  $\widetilde{\mathbf{g}}_i^{(j)} = \mathbf{g}_i$ . Each worker  $W_j$  computes their responses consistently based on those values, i.e.,

$$\widetilde{\mathbf{z}}_{t,j} = \operatorname{enc}_{j,e_{j,t}} \left( \widetilde{\mathbf{g}}_{1}^{(j)}, \dots, \widetilde{\mathbf{g}}_{p}^{(j)} \right),$$

$$\forall t \in \{0, \dots, r\}, j \in [n], e_{j} \in [v].$$

For clarity of exposition, we first lay out how the adversary chooses the claimed gradient values for m=1 groups of size s+1, i.e., u=1, before we generalize to arbitrary  $m,u\in\mathbb{N}$ .

For u=1 and m=1, the adversary draws a set  $\widetilde{\mathcal{I}}\subseteq [p]$  of size  $|\widetilde{\mathcal{I}}|=\lfloor\frac{s}{u}\rfloor=s$  uniformly at random and assigns each malicious worker  $W_j$  a unique gradient index from  $\widetilde{\mathcal{I}}$ . For each index, it sets the corresponding worker's claimed value to a distinct random vector unequal the true value and all other malicious worker's values to the true partial gradient value. With probability  $\frac{1}{2}$ , it picks a single gradient index from  $\widetilde{\mathcal{I}}$  uniformly at random and sets all malicious workers' values to the same erroneous random partial gradient value. The resulting claimed gradients take on the form as depicted in Table I. For partial gradients

	$\widetilde{\mathbf{g}}_1^{(j)}$	$\widetilde{\mathbf{g}}_2^{(j)}$		$\widetilde{\mathbf{g}}_{s}^{(j)}$	$\widetilde{\mathbf{g}}_{s+1}^{(j)}$	 $\widetilde{\mathbf{g}}_{p}^{(j)}$
$W_1 W_2$	$\mathbf{g}_1''$	$\mathbf{g}_2'$	• • •	$\mathbf{g}_s'$	$\mathbf{g}'_{s+1}$	 $\mathbf{g}_p'$
	$\mathbf{g}_1'$	$\mathbf{g}_2''$		$\mathbf{g}_s'$	$\mathbf{g}_{s+1}'$	 $\mathbf{g}_p'$
$W_s$	$\mathbf{g}_1'$	$\mathbf{g}_2'$	·.	$\mathbf{g}_{s}^{\prime\prime}$	$\mathbf{g}_{s+1}'$	 $\mathbf{g}'_n$
$W_{s+1}$	$\mathbf{g}_1'$	$\mathbf{g}_2^7$	 TA	$\mathbf{g}_s'$ BLE I	$\mathbf{g}_{s+1}'$	 $\mathbf{g}_p^{\prime}$

CLAIMED PARTIAL GRADIENTS FOR SYMMETRIZATION ATTACK.

with index in  $\widetilde{\mathcal{I}}$  there are two competing values  $\mathbf{g}_i'$  and  $\mathbf{g}_i''$  whereas for all other gradient indices the claimed values by all workers agree.

For u>1, the adversary randomly partitions the malicious workers into  $\lfloor s/u \rfloor -1$  sets of size u and (depending on divisibility) one group of size  $s \mod u$ . Each of the sets of size u behaves like one malicious worker in the case u=1. The workers in the remaining set of less than u workers (if non-empty) pick their claimed gradients randomly either like a random other set of workers or like the honest workers. The resulting claimed gradients take on the form as depicted in Table III in Appendix B.

For m>1, the adversary chooses the first group and chooses the claimed gradients according to the attack strategy for m'=1 and p'=p/m in that group. In all other groups, the claimed gradients are equal to their true values.

#### B. Fundamental Limits

**Theorem 1** (Lower bound on c and  $\rho$ ). Suppose that n = m(s+u) for integers  $m, u \ge 1$ . For any tuple ( $\mathbf{A}$ ,  $\mathfrak{E}$ , dec,  $\Pi$ ), with  $\mathbf{A}$  as in (3), to be a  $(r,c,\rho,\kappa)$ -s-BGC scheme, it

holds that if  $\rho \leq s+u$ , then  $c \geq \left\lfloor \frac{s}{u} \right\rfloor$  (conversely, if  $c < \left\lfloor \frac{s}{u} \right\rfloor$  then  $\rho > s+u$ ) for any number of rounds r and any communication overhead  $\kappa$ .

*Proof:* We demonstrate that any tuple  $(\mathbf{A}, \mathfrak{E}, \operatorname{dec}, \Pi)$  with fractional repetition data allocation which uses  $c \leq \left\lfloor \frac{s}{u} \right\rfloor - 1$  local computations cannot be an s-BGC scheme. Specifically, we show that the malicious workers can always perform a symmetrization attack preventing the main node from deterministically computing the full gradient. Let the malicious workers behave as explained in Section IV-A.

We abstract  $\mathfrak{E}$  and  $\Pi_1$  by assuming that the values of all partial gradients  $\widetilde{\mathbf{g}}_i^{(j)}$  computed by the workers are available at the main node. Note that regardless of  $\mathfrak{E}$  and  $\Pi_1$  the main node cannot gain any additional information from the workers' responses. We now show that for  $c \leq \left\lfloor \frac{s}{u} \right\rfloor - 1$  there exists no choice of a decoding function dec and  $\Pi_2$  for which the main node deterministically outputs the true full gradient. To that end, for any possible  $\Pi_2$ , we give two cases for which the inputs to the decoding function are identical but the true full gradients differ.

The claimed partial gradients take on values as in Table I for u=1 and Table III for u>1. There are  $\left\lfloor \frac{s}{u} \right\rfloor$  partial gradients, say  $\mathbf{g}_1,\dots,\mathbf{g}_{\left\lfloor \frac{s}{u} \right\rfloor}$ , such that for each partial gradient  $\mathbf{g}_i$  worker  $W_i$  sends a value  $\widetilde{\mathbf{g}}_i^{(i)}=\mathbf{g}_i''$  that is different from the value  $\mathbf{g}_i'$  sent by all other workers. For any list  $\mathfrak{I}^{(r)}$  of locally computed gradients of size  $\left|\mathfrak{I}^{(r)}\right| \leq s-1$  (produced by any  $\Pi_2$ ) there exists an index  $i \in [s]$  such that  $i \notin \mathfrak{I}^{(r)}$ . Consider the following two cases:

$$\begin{array}{l} \text{Case 1: } \mathbf{g}_i = \mathbf{g}_i' \; \forall i \in \left[\frac{p}{m}\right] \; \text{and} \\ \text{Case 2: } \; \mathbf{g}_i = \mathbf{g}_i' \; \forall i \in \left[\frac{p}{m}\right] \setminus \left\{\widetilde{i}\right\} \; \text{and} \; \mathbf{g}_{\widetilde{i}} = \mathbf{g}_{\widetilde{i}}''. \end{array}$$

It is easy to see that both cases occur with non-zero probability according to the attack strategy in Section IV-A. In both cases, the inputs to dec only depend on the fixed  $\mathfrak{I}^{(r)}$ , the  $\widetilde{\mathbf{g}}_i^{(j)}$ ,  $j \in [s+1]$ ,  $i \in [\frac{p}{m}]$  and the  $\mathbf{g}_i$ ,  $i \in \mathfrak{I}^{(r)}$ , all of which take on identical values in both cases. The value of the full gradient  $\mathbf{g}$ , however, is  $\sum_{i \in [p]} \mathbf{g}_i'$  in Case 1 and  $\mathbf{g}_i'' + \sum_{i \in [p] \setminus \{\widetilde{i}\}} \mathbf{g}_i'$  in Case 2. Hence, for  $c < \lfloor \frac{s}{u} \rfloor$  no decoding function can deterministically produce the correct full gradient.

**Theorem 2** (Lower bound on  $\kappa$  for fixed c and  $\rho$ ). Suppose that n=m(s+u) for integers  $m,u\geq 1$ . For any tuple ( $\mathbf{A}$ ,  $\mathfrak{E}$ , dec,  $\Pi$ ), with  $\mathbf{A}$  as in (3), to be a  $(r,c,\rho,\kappa)$ -s-BGC scheme with  $\rho=s+u$  and  $c=\left\lfloor\frac{s}{u}\right\rfloor$ , then it must hold that

$$\kappa \ge \log_{|\mathcal{A}|} \binom{p/m}{\lfloor s/u \rfloor}.$$

*Proof:* The proof is given in Appendix D

#### C. Construction of an s-BGC Scheme

**Theorem 3.** The scheme constructed below is an s-BGC scheme with a parameter u such that  $1 \le u \le s+1$  and requires  $r \le (s+1-u)\lceil \log_2(\frac{p}{m}) \rceil$  rounds,  $c \le \lfloor \frac{s}{u} \rfloor$  local gradient computations,  $\rho = s+u$ , and  $\kappa \le (s+1-u)\Bigl(2\lceil \log_2(\frac{p}{m}) \rceil + \frac{s+3u}{2\log_2|\mathcal{A}|}\Bigr)$ .

*Proof:* We defer the proof to Appendix E.

We construct an  $(r,c,\rho,\kappa)$ -s-BGC scheme that has a replication factor  $\rho=s+u,\ u\geq 1,$  and requires the optimal local computation load  $c\leq \lfloor\frac{s}{u}\rfloor$  at the main node. The protocol  $\Pi$  runs for  $r\leq (s+1-u)\lceil\log_2(\frac{p}{m})\rceil$  rounds and achieves a communication overhead  $\kappa\leq (s+1-u)\left(2\lceil\log_2(\frac{p}{m})\rceil+\frac{s+3u}{2\log_2|\mathcal{A}|}\right)$ . Our scheme uses a fractional repetition data assignment with m groups each of size s+u. Informally, in each group, the main node runs an elimination tournament consisting of matches (similar to the one explained in Example 1) between pairs of workers that return contradicting responses. An algorithmic description of the elimination tournament is given in Algorithm 2 for the general case. For clarity of exposition, we explain the idea of our scheme for the special case of u=1. The general case for  $u\geq 2$  follows similar steps and is given in Appendix C.

The tournament consists of a series of matches between two workers. During a match, each worker constructs a binary tree based on their computed partial gradients, which we refer to as the match tree. The root of the tree is labeled by the sum of all partial gradients computed at that worker  $(\widetilde{z}_{0,j})$ . The child nodes are constructed based on the partial gradients that are contained in the parent node. Each node has two children: the first one is labeled by the sum of the first half of the parent node's partial gradients; the second one is labeled by the sum of the second half of the parent node's partial gradients. Thus, the labeling is done such that the sum of the labels of any two siblings gives the label of their parent node.

Proceeding in this way recursively, each worker ends up with the leaves of the tree being labeled by individual partial gradients. For example, when m=1 and p=4, the tree is depicted in Fig. 2. During a match, the main node requests the labels for particular nodes in this tree from the two competing workers, and compares them. If the root labels of two match trees differ, then by definition there must be a child node for which the corresponding label differs in those trees. By induction, it is clear that there has to be a path from the root to a leaf, such that the corresponding labels of all involved nodes differ between the two match trees. Applying this observation to the example in Fig. 2, if  $\widetilde{\mathbf{g}}_1^{(j)} + \widetilde{\mathbf{g}}_2^{(j)} + \widetilde{\mathbf{g}}_3^{(j)} + \widetilde{\mathbf{g}}_4^{(j)}$  is different for two workers, then  $\widetilde{\mathbf{g}}_1^{(j)} + \widetilde{\mathbf{g}}_2^{(j)}$  or  $\widetilde{\mathbf{g}}_3^{(j)} + \widetilde{\mathbf{g}}_4^{(j)}$  must also differ (or both). In the latter case, we end up with  $\widetilde{\mathbf{g}}_3^{(j)}$  being different between the workers.




Fig. 2. Example of a match tree for  $W_j$  and parameters m = 1, p = 4.

The match starts at the root. In this case, each worker  $W_j$  would have already sent the node label in  $\mathbf{z}_{0,j}$  to the main node, i.e.,

$$\mathbf{z}_{0,j} = \mathrm{enc}_{j,1}(\mathbf{g}_1, \dots, \mathbf{g}_p) = \sum_{\substack{i \in [p] \\ \mathbf{A}_{i,j} = 1}} \mathbf{g}_i.$$

Note that, without errors, all workers' messages agree within a group. In case of discrepancies between the responses  $\widetilde{\mathbf{z}}_{0,j}$  of the workers within a group, the main

node selects a pair of disagreeing workers  $W_{j_1}, W_{j_2}$  and further descends in the tree as follows.

For every node in the tree, the main node requests and compares the left child's label from both workers, encoded in  $\mathbf{z}_{t,j_1}$  and  $\mathbf{z}_{t,j_2}$ . The main node then moves on to a child whose label the workers disagree on. Note that, based on the current node's label and the left child's label, the main node can infer the right child's label. If the competing workers agree on the left child's label, they must disagree on the right child's label. This procedure is repeated until a leaf is reached. Note that, even if the workers send inconsistent labels at each round, this procedure is guaranteed to reach a leaf node for which the (sent or inferred) values of the individual gradient is different for the two workers. Algorithm 1 formalizes this procedure for m=1.

Note that it is possible to reduce the communication load by picking a coordinate  $\zeta$  in which the workers' initial responses disagree, i.e.,  $[\mathbf{z}_{0,j_1}]_{\zeta} \neq [\mathbf{z}_{0,j_2}]_{\zeta}$ . That is, the workers only encode the  $\zeta$ -th coordinate of the node labels. By this method, it is still guaranteed that the main node can identify a partial gradient for which the competing workers disagree.

Having identified disagreeing values  $\widetilde{\mathbf{g}}_i^{(j_1)}$  and  $\widetilde{\mathbf{g}}_i^{(j_2)}$  of a partial gradient  $\mathbf{g}_i$ , the main node computes the correct of this partial gradient locally. It then marks the worker(s) whose values differ from the value computed locally as malicious. The algorithm ends up with disagreeing leaf labels by design. Therefore, each match is guaranteed to eliminate at least one malicious worker and no honest workers. After performing at most s matches, the main node is guaranteed to identify all malicious workers. The main node takes the encoded gradient of one worker identified as being honest from each group and sums up the group-wise results to obtain  $\widehat{\mathbf{g}} = \mathbf{g}$ .

#### D. Discussion

According to Theorem 1, the interactive protocol of our scheme achieves the lowest possible number of locally computed partial gradients for the fractional repetition data assignment and  $\rho = s + u$ . Note that for  $u \ge s + 1$ , i.e.,  $\rho \geq 2s+1$ , no local computation is necessary. In fact, since there is only one set of consistent workers W that has  $|\mathcal{W}| \geq u$  per fractional repetition group, the scheme immediately identifies W as the honest set and terminates without any additional computation or communication. Thus, as shown in [22], our scheme achieves the optimal performance in this case. Although we consider  $1 \le u \le$ s+1 in Theorem 3 for technical reasons, the scheme works for any  $u \geq 1$ . Note that the achievable bound on  $\kappa$  in Theorem 3 is off from the converse bound in Theorem 2 by a constant factor asymptotically, see Fig. 3 in Appendix F. The reason is that we use a rather simple and conservative lower bound on the amount of information that is required to be transmitted by the workers in Theorem 2. Among others, we assume that all workers have knowledge about the malicious worker's identities and also the malicious workers contribute useful information. Improvement of the converse bound is left for future work.

#### V. CONCLUSION

We considered the problem of distributed learning in the presence of Byzantine computation errors. We introduced a framework that extends the known gradient coding framework by adding an interactive light communication between the main node and the workers and verifying local computations at the main node. In the scope of this framework, we proposed a new scheme that can tolerate s malicious workers with a computational redundancy of s+u for any  $u \geq 1$ . We showed that with a fractional repetition data assignment, the scheme achieves the optimal number of local computations at the main node. Future work includes the improvements of the converse and achievability bounds, the generalization of the fundamental limits to a broader class of data assignments, and the investigation into optimal Byzantine-resilient gradient coding schemes.

#### REFERENCES

- [1] X. Lian, C. Zhang, H. Zhang, C.-J. Hsieh, W. Zhang, and J. Liu, "Can decentralized algorithms outperform centralized algorithms? A case study for decentralized parallel stochastic gradient descent,' Advances in Neural Information Processing Systems, vol. 30, 2017.
- [2] M. Abadi, P. Barham, J. Chen, Z. Chen, A. Davis, J. Dean, M. Devin, S. Ghemawat, G. Irving, M. Isard et al., "{TensorFlow}: A system for {Large-Scale} machine learning," in 12th USENIX symposium on operating systems design and implementation (OSDI 16), 2016, pp. 265-283.
- [3] L. Lamport, R. Shostak, and M. Pease, "The Byzantine Generals Problem," ACM Transactions on Programming Languages and Systems, vol. 4, no. 3, p. 20.
- G. Damaskinos, E.-M. El-Mhamdi, R. Guerraoui, A. Guirguis, and S. Rouault, "AggregaThor: Byzantine machine learning via robust gradient aggregation," Proceedings of Machine Learning and Systems, vol. 1, pp. 81–106, 2019.
- [5] C. Hofmeister, R. Bitar, M. Xhemrishi, and A. Wachter-Zeh, "Secure private and adaptive matrix multiplication beyond the singleton bound," IEEE Journal on Selected Areas in Information Theory, vol. 3, no. 2, pp. 275-285, 2022.
- T. Tang, R. E. Ali, H. Hashemi, T. Gangwani, S. Avestimehr, and M. Annavaram, "Adaptive verifiable coded computing: Towards fast, secure and private distributed machine learning," pp. 628-638,
- [7] Q. Yu, S. Li, N. Raviv, S. M. M. Kalan, M. Soltanolkotabi, and S. A. Avestimehr, "Lagrange coded computing: Optimal design for resiliency, security, and privacy," in Proceedings of the Twenty-Second International Conference on Artificial Intelligence and Statistics, ser. Proceedings of Machine Learning Research, vol. 89. PMLR, 16-18 Apr 2019, pp. 1215-1225.
- [8] A. Solanki, M. Cardone, and S. Mohajer, "Non-Colluding Attacks Identification in Distributed Computing," in 2019 IEEE Information
- Theory Workshop (ITW), Visby, Sweden, Aug. 2019, pp. 1–5. Y. Keshtkarjahromi, R. Bitar, V. Dasari, S. El Rouayheb, and H. Seferoglu, "Secure Coded Cooperative Computation at the Heterogeneous Edge against Byzantine Attacks," in 2019 IEEE Global Communications Conference (GLOBECOM), Dec. 2019, pp. 1-6.

- [10] E. M. El Mhamdi, R. Guerraoui, and S. Rouault, "The hidden vulnerability of distributed learning in Byzantium," in Proceedings of the 35th International Conference on Machine Learning, ser. Proceedings of Machine Learning Research, vol. 80. PMLR, 10-15 Jul 2018, pp. 3521-3530.
- [11] Y. Chen, L. Su, and J. Xu, "Distributed Statistical Machine Learning in Adversarial Settings: Byzantine Gradient Descent," Proceedings of the ACM on Measurement and Analysis of Computing Systems, vol. 1, no. 2, pp. 1–25, Dec. 2017.
  [12] P. Blanchard, E. M. El Mhamdi, R. Guerraoui, and J. Stainer,
- "Machine learning with adversaries: Byzantine tolerant gradient descent," in Advances in Neural Information Processing Systems, vol. 30. Curran Associates, Inc., 2017.
- [13] S. Rajput, H. Wang, Z. Charles, and D. Papailiopoulos, "Detox: A redundancy-based framework for faster and more robust gradient aggregation," Advances in Neural Information Processing Systems, vol. 32, 2019.
- [14] E.-M. El-Mhamdi, R. Guerraoui, and S. Rouault, "Fast and robust distributed learning in high dimension," in International Symposium
- on Reliable Distributed Systems (SRDS). IEEE, 2020, pp. 71–80. [15] C. Xie, S. Koyejo, and I. Gupta, "Zeno: Distributed stochastic gradient descent with suspicion-based fault-tolerance," in Proceedings of the 36th International Conference on Machine Learning, ser. Proceedings of Machine Learning Research, vol. 97. PMLR, 09-15 Jun 2019, pp. 6893–6901.
- [16] K. Konstantinidis and A. Ramamoorthy, "Aspis: Robust detection for distributed learning," in 2022 IEEE International Symposium on Information Theory (ISIT), 2022, pp. 2058-2063.
- [17] R. Bitar, M. Wootters, and S. El Rouayheb, "Stochastic Gradient Coding for Straggler Mitigation in Distributed Learning," IEEE Journal on Selected Areas in Information Theory, vol. 1, no. 1, pp. 277-291, May 2020.
- [18] J. Chen, X. Pan, R. Monga, S. Bengio, and R. Jozefowicz, "Revisiting distributed synchronous SGD," 2016. [Online]. Available: https://arxiv.org/abs/1604.00981
- R. Tandon, Q. Lei, A. G. Dimakis, and N. Karampatziakis, "Gradient coding: Avoiding stragglers in distributed learning," in Proceedings of the 34th International Conference on Machine Learning, ser. Proceedings of Machine Learning Research, vol. 70.
- PMLR, 06–11 Aug 2017, pp. 3368–3376. [20] I. Sutskever, J. Martens, G. Dahl, and G. Hinton, "On the importance of initialization and momentum in deep learning," in Proceedings of the 30th International Conference on Machine Learning. PMLR, May 2013, pp. 1139–1147.
  [21] D. Data, L. Song, and S. N. Diggavi, "Data Encoding for
- Byzantine-Resilient Distributed Optimization," IEEE Transactions
- on Information Theory, vol. 67, no. 2, pp. 1117–1140, Feb. 2021.

  [22] L. Chen, H. Wang, Z. Charles, and D. Papaliopoulos, "DRACO:

  Byzantine-resilient distributed training via redundant gradients,"

  in Proceedings of the 25th Lynna in J. C. C. in Proceedings of the 35th International Conference on Machine Learning, ser. Proceedings of Machine Learning Research, vol. 80. PMLR, 10–15 Jul 2018, pp. 903–912. X. Cao and L. Lai, "Distributed Gradient Descent Algorithm
- Robust to an Arbitrary Number of Byzantine Attackers,' Transactions on Signal Processing, vol. 67, no. 22, pp. 5850-5864, Nov. 2019.
- S. Prakash, H. Hashemi, Y. Wang, M. Annavaram, and S. Avestimehr, "Secure and fault tolerant decentralized learning," 2020. [Online]. Available: https://arxiv.org/abs/2010.07541

#### APPENDIX

#### A. Elaborate Example on How to Catch Liars Efficiently

The following example demonstrates the main problem studied in the paper and gives intuition for our main results. Consider a game among friends. Alice, Bob and Carol play against Dan.

- 1) Alice, Bob, and Carol secretly agree on a list of four integers  $g_1, \ldots, g_8$  and put them in separate envelopes.
- Two players between Alice, Bob, and Carol are designated as liars, without Dan knowing which is which. The remaining player has to be truthful.
- 3) Dan's goal is to find the sum of the numbers  $g_1 + \cdots + g_8$ . The game is played in rounds. In each round he can first a) ask the other players questions about  $g_1, \ldots, g_8$  and then b) look in any number of envelopes.
- 4) Dan needs to find the correct sum every time.

What is the minimum number of envelopes he needs to look inside? If he checks the minimum number of envelopes, how many questions does he need to ask?

If the number of questions asked were unlimited, he could ask each player for all values  $g_1, \ldots, g_8$ . With  $\widetilde{g}_i^{(j)}$  we denote the value the value player  $j \in \{\text{Alice, Bob, Carol}\}$  claims is in the envelope for  $g_i$ ,  $i \in [8]$ . Since the players only answer questions about these numbers and assuming the liars are smart enough to avoid contradictions so as to not be detected, Dan cannot gain any more information by asking more questions.

Not in every case can Dan identify the correct sum based just on these answers. For example, Table II shows three cases that are indistinguishable based on the values of all  $\tilde{g}_{i}^{(j)}$ .

TABLE II INDISTINGUISHABLE CASES.

Dan picks any  $g_i$ ,  $i \in [8]$  on which at least two players' answers disagree and checks the corresponding envelope. He is guaranteed to identify at least one liar. After eliminating the identified liar(s) he repeats the process. After opening at most two envelopes it is guaranteed that all non-eliminated players, including the honest one, agree on the sum  $g_1 + \cdots + g_8$  and it is therefore correct. It can be verified, that the cases in Table II cannot be distinguished after opening any one envelope. Thus, using this strategy Dan opens the smallest possible number of envelopes in the worst case.

Now, Dan additionally wishes to minimize the number of questions asked. With the above strategy, Dan asks each player eight questions, for a total of 24.

Dan realizes that, using multiple rounds, he can reduce the number of questions he needs to ask using the following recursive procedure. First, he asks every player for the desired sum  $g_1 + \cdots + g_8$  and the sum of the first half of the

values,  $g_1+g_2+g_3+g_4$ . Dan picks any two players, whose values for the total sum differs. He infers their values for  $g_5+\cdots+g_8$  as  $(g_1+\cdots+g_8)-(g_1+\cdots+g_4)$ . If the two players agree on  $g_1+\cdots+g_4$ , they are guaranteed to disagree on  $g_5+\cdots+g_8$ . Assume they disagree on  $g_5+\cdots+g_8$ , then Dan requests  $g_5+g_6$  from both players. Again, they are guaranteed to disagree either on  $g_5+g_6$  or  $g_7+g_8$ . Assume they disagree on  $g_5+g_6$ . Dan asks for  $g_5$ . After having obtained a single integer, either  $g_5$  or  $g_6$  on which the two players disagree, Dan opens the corresponding envelope and thus identifies and eliminates at least one liar. In the worst case Dan has to repeat the above procedure once more on the remaining two values. Now, he asks only 15 questions as opposed to the 24 from before.

#### B. Symmetrization Attack Table

	$\widetilde{\mathbf{g}}_1^{(j)}$	$\widetilde{\mathbf{g}}_2^{(j)}$		$\widetilde{\mathbf{g}}_{\left\lfloor\frac{s}{u}\right\rfloor}^{(j)}$	$\widetilde{\mathbf{g}}_{\left\lfloor\frac{s}{u}\right\rfloor+1}^{(j)}$		$\widetilde{\mathbf{g}}_{p}^{(j)}$
$W_1$ $W_2$	$\mathbf{g}_1''$ $\mathbf{g}_1''$	$\mathbf{g}_2'\\\mathbf{g}_2'$	•••	$egin{array}{c} \mathbf{g}'_{\lfloor rac{s}{u}  floor} \ \mathbf{g}'_{\lfloor rac{s}{u}  floor} \end{array}$	$\mathbf{g}'_{\lfloor rac{s}{u}  floor + 1} \ \mathbf{g}'_{\lfloor rac{s}{u}  floor + 1}$		$\mathbf{g}_p'\\\mathbf{g}_p'$
$\vdots \ W_u$	$\mathbf{g}_1''$	$\mathbf{g}_2'$	:	$\mathbf{g}'_{\lfloor rac{s}{u}  floor}$	:		$\mathbf{g}_p'$
$W_{u+1}$ $W_{u+2}$	$\mathbf{g}_1'$ $\mathbf{g}_1'$	$\mathbf{g}_2''$ $\mathbf{g}_2''$			$\mathbf{g}'_{\lfloor \frac{s}{u} \rfloor + 1}$ $\mathbf{g}'_{\lfloor \frac{s}{u} \rfloor + 1}$		$\mathbf{g}_p'$ $\mathbf{g}_p'$
$\vdots$ $W_{2u}$	$\mathbf{g}_1'$	$\mathbf{g}_2''$	:	$\mathbf{g}'_{\lfloor \frac{s}{u} \rfloor}$	$\mathbf{g}'_{\lfloor \frac{s}{u} \rfloor + 1}$		$g_p'$
:	:	:	٠.	:	:		:
$W_{\lfloor \frac{s}{u} \rfloor u - u + 1}$ $W_{\lfloor \frac{s}{u} \rfloor u - u + 2}$	$\mathbf{g}_1'$ $\mathbf{g}_1'$	$\mathbf{g}_2'$ $\mathbf{g}_2'$		$egin{array}{c} \mathbf{g}_{\lfloor rac{s}{u}  floor}'' \ \mathbf{g}_{\lfloor rac{s}{u}  floor}'' \end{array}$	$\mathbf{g}'_{\lfloor \frac{s}{u} \rfloor + 1}$ $\mathbf{g}'_{\lfloor \frac{s}{u} \rfloor + 1}$		$\mathbf{g}_p'$ $\mathbf{g}_p'$
$W_{\lfloor rac{s}{u}  floor u}$	$\mathbf{g}_1'$	$\mathbf{g}_2'$	:	$\mathbf{g}''_{\lfloor rac{s}{u}  floor}$	$g'_{\lfloor \frac{s}{u} \rfloor + 1}$		$\mathbf{g}_p'$
$W_{\lfloor \frac{s}{u} \rfloor u + 1}$ $W_{\lfloor \frac{s}{u} \rfloor u + 2}$	$\mathbf{g}_1'$ $\mathbf{g}_1'$	$\mathbf{g}_2'$ $\mathbf{g}_2'$		$egin{array}{c} \mathbf{g}'_{\lfloor rac{s}{u}  floor} \ \mathbf{g}'_{\lfloor rac{s}{u}  floor} \end{array}$	$\mathbf{g}'_{\lfloor \frac{s}{u} \rfloor + 1}$ $\mathbf{g}'_{\lfloor \frac{s}{u} \rfloor + 1}$		$\mathbf{g}_p'$ $\mathbf{g}_p'$
$W_{s+u}$	$\mathbf{g}_1'$	$\mathbf{g}_2'$	:	$\mathbf{g}'_{\lfloor rac{s}{u}  floor}$	$\mathbf{g}'_{\lfloor rac{s}{u}  floor + 1}$	• • • •	$\mathbf{g}_p'$

TABLE III
CLAIMED PARTIAL GRADIENTS FOR SYMMETRIZATION ATTACK.

#### C. General Scheme Description

In this section, we explain the extension of our scheme for the general case of  $u \geq 1$ . In this case, we also exploit the fact that there are u honest workers that are guaranteed to agree in their responses. Therefore, the main node can eliminate all responses that are supported by only less than u workers. Furthermore, a response must be a correct response if it is supported by more than s workers. Therefore, the main node does only need to consider sets  $\mathcal{W} \in [n]$  of workers that agree on their responses, and which satisfies  $u \leq |\mathcal{W}| \leq s$ . For the clarity of presentation, we thus, only consider those sets as inputs to Algorithm 2.

Additionally, we leverage a little more communication to reduce the number of local gradient computations to at most  $\lfloor \frac{s}{u} \rfloor$ . The intuition here is that the main node can pick a representative from every set  $\mathcal{W}$  and run matches between the representatives. Note however, that even if the

main node identifies a representative of W as malicious by a local computation, this does not imply that every worker in W is malicious. For example, a malicious worker could return the same initial response as the honest workers, but when being picked as representative, intentionally send wrong node labels. We overcome this by asking all workers in a set W to either commit or not commit to the representative's leaf label, which has been identified in a match. In order to force the main node to run a local computation, there must be at least u workers in Wthat commit to the representative's leaf label. If not, we can mark all the workers that committed to the label as malicious immediately. If there are at least u commitments to a malicious leaf label, the main node can mark all those workers (at least u) as malicious by running a local computation. This procedure is reflected by the elimination tournament in Algorithm 2.

#### D. Proof of Theorem 2

We consider a single group consisting of n=s+u workers. Since the datasets per group as well as the sets of workers are disjoint, the communication necessary for m groups of size p/m is at least as big as for m'=1 group of size p/m. Further, we assume the behaviour of the malicious workers as in Section IV-A.

To proceed with the proof, we need the following direct consequence of the proof technique used to prove Theorem 1.

**Corollary 1** (Computation of Disagreement Gradients). For any  $(r,c,\rho,\kappa)$ -s-BGC scheme ( $\mathbf{A}$ ,  $\mathfrak{E}$ , dec,  $\Pi$ ), with  $\rho=s+u$  and  $\mathbf{A}$  as in (3), if the adversary behaves according to Section IV-A, then the list of locally computed gradients must contain the list of all gradients on which the workers disagree, i.e.,  $\forall i \in \widetilde{I} : \widetilde{i} \in \mathfrak{I}^{(r)}$ .

*Proof:* The proof follows the same steps as for Theorem 1. Note that if there exists an index  $\widetilde{i} \in \widetilde{\mathcal{I}} : \widetilde{i} \notin \mathfrak{I}^{(r)}$ , there are two cases that cannot be distinguished based on the information available at the main node.

According to Corollary 1, for  $c = \lfloor \frac{s}{u} \rfloor$ , we require every item of  $\widetilde{\mathcal{I}}$  to be in  $\mathfrak{I}^{(T)}$ , while  $c = |\mathfrak{I}^{(r)}| = |\widetilde{\mathcal{I}}| = \lfloor \frac{s}{u} \rfloor$ . In other words, the main node must exactly compute all the gradients in  $\widetilde{\mathcal{I}}$  locally. If there is a non-zero probability that a different gradient is computed locally, the scheme cannot be a valid s-BGC scheme. Overall,  $\widetilde{\mathcal{I}}$  must be uniquely determined by the main node's available information at the end of the protocol, leading to  $\mathrm{H}(\widetilde{\mathcal{I}} \mid \mathcal{D}, \mathfrak{G}) = 0$ , where  $\mathcal{D}$  denotes the list of random variables corresponding to all data transmitted from all workers to the main node and  $\mathfrak{G}$  denotes the list of the random variables corresponding to the values of the locally computed gradients.

Using this we have

$$H(\mathcal{D} | \mathfrak{G}) \ge I(\mathcal{D}; \widetilde{\mathcal{I}} | \mathfrak{G})$$

$$= H(\widetilde{\mathcal{I}} | \mathfrak{G}) - H(\widetilde{\mathcal{I}} | \mathfrak{G}, \mathcal{D})$$

$$= H(\widetilde{\mathcal{I}} | \mathfrak{G})$$

$$= H(\widetilde{\mathcal{I}} | \mathfrak{G})$$

$$(5)$$

$$= H(\widetilde{\mathcal{I}})$$

$$= \log_{|\mathcal{A}|} \binom{p/m}{\lfloor s/u \rfloor},$$
(6)

where (4) follows from the definition of mutual information, (5) follows since  $\widetilde{\mathcal{I}}$  is independent from  $\mathfrak{G}$  and (6)

holds since  $\widetilde{\mathcal{I}}$  is a uniform selection of  $c=\lfloor s/u \rfloor$  indices out of [p/m]. To transmit the information in  $\mathcal{D}$  with zero error to the main node, the workers need to send at least  $\log_{|\mathcal{A}|} \binom{p/m}{\lfloor s/u \rfloor}$  symbols from  $\mathcal{A}$ .

#### E. Proof of Theorem 3

In order to show the correctness of our scheme, we recall the following facts from before. The elimination tournament runs as long as there are contradicting responses among the non-eliminated workers. In each iteration of the elimination tournament, the main node eliminates at least one malicious worker (either by majority vote or by local computation). As soon as less than u malicious workers are left, the elimination terminates. Therefore, the elimination tournament is guaranteed to terminate after at most s+1-u iterations. W.l.o.g. we consider  $1 \le u \le s+1$ here. For  $u \ge s + 1$ , the elimination tournament will terminate immediately for the reason explained before. Furthermore, honest workers are never eliminated, since they always respond with a correct value and never commit to an incorrect value. Having at least  $u \leq 1$  honest workers in each fractional repetition group, the main node can recover the correct group result after the elimination tournament terminated, and hence, for the output it always holds  $\hat{\mathbf{g}} = \mathbf{g}$ . After having shown that our scheme is an s-BGC scheme, we show the tuple  $(r, c, \rho, \kappa)$  in the remainder.

We start with the number of locally computed gradients c. As explained above, each local computation of a partial gradient, eliminates at least u malicious workers in our scheme. The procedure halts when there are no more discrepancies among the initial responses of the non-eliminated workers, which is at latest when all s malicious workers are identified. Therefore, the number of gradients computed locally is

$$c \leq \left| \frac{s}{u} \right|$$
.

Next, we analyze the communication rate  $\kappa$ . Every match causes each of the two competing workers to send up to  $\lceil \log_2(\frac{p}{m}) \rceil$  symbols. The reason is that a competing worker sends one symbol for each node on a specific path of the match tree. The number of nodes in such a path is upper bounded by the height of the tree, which is  $\lceil \log_2(\frac{p}{m}) \rceil$ . We have at most s+1-u matches. That is, the total amount of symbols transmitted for all matches is at most  $2(s+1-u)\lceil \log_2(\frac{p}{m}) \rceil$ . Finally, each committing round after a match causes an additional communication load. Every worker of the competing consistent worker subsets transmits one bit, indicating whether or not the worker commits to the response of its representative. The communication load caused by committing is maximized by; first, maximizing the number of matches; and second, maximizing the number of involved nodes per match. This is achieved at the same time in the case where there are only two large subsets of consistent workers: the first consisting of the u honest workers, and the second consisting of the s malicious workers. Furthermore, the malicious workers never commit to a representative's malicious value. Hence, we have s + 1 - u matches. The first match s + u has one-bit voting messages. Since at least one malicious worker can be eliminated, the number of voting messages will decrease by at least one per match accordingly. Therefore, the number of voting messages in the l-th match is given by u+s-(l-1). Summing over all  $l=1,\ldots,s+1-u$ , we can bound the total number of one-bit voting messages by  $\frac{(s+1-u)(s+3u)}{2\log_2|\mathcal{A}|}$ . In terms of symbols from  $\mathcal{A}$ , this is a load of  $\frac{(s+1-u)(s+3u)}{2\log_2|\mathcal{A}|}$ . In total, we obtain

$$\kappa \le (s+1-u)\left(2\left\lceil\log_2\left(\frac{p}{m}\right)\right\rceil + \frac{s+3u}{2\log_2|\mathcal{A}|}\right).$$

Finally, we analyze the number of communication rounds r. The number of communication rounds in a match is again upper bounded by the height of the tree, i.e.,  $\lceil \log_2(\frac{p}{m}) \rceil$ . Matches in different fractional repetition groups can be performed concurrently in the same rounds of the interactive protocol. As explained before, there can be up to s matches. Again, if all malicious workers are in the same group, and if there are only two consistent worker subsets in this group of size u and s, respectively, then all s+1-u matches have to be executed sequentially. Resolving all conflicts, thus, requires

$$r \le (s+1-u) \left\lceil \log_2\left(\frac{p}{m}\right) \right\rceil.$$

F. Achievability vs. Converse for  $\kappa$ 

For convenience, we reproduce our achievability and converse bound on  $\kappa$  from Theorem 3 and Theorem 2, respectively. For fractional repetition data allocation, with m groups, n=m(s+u) workers, s of which are malicious, our scheme requires data transmission of at most

$$\kappa_{\text{achieve}} = (s+1-u) \left( 2 \left\lceil \log_2 \left( \frac{p}{m} \right) \right\rceil + \frac{s+3u}{2 \log_2 |\mathcal{A}|} \right)$$

during the interactive protocol as measured in symbols from A. Our lower bound shows, that for any computation optimal s-BGC,  $\kappa$  is at least

$$\kappa_{\text{bound}} = \log_{|\mathcal{A}|} \binom{p/m}{\lfloor s/u \rfloor}$$




Fig. 3. Comparison of converse and achievability for  $\kappa$  over the dataset size p. We consider a system of n=10 workers, m=1 group and an alphabet size  $|\mathcal{A}|=2^{16}$ . As the percentage of malicious workers rises from  $50\,\%$  to  $90\,\%$  the communication overhead of the scheme increases.

The gap between our scheme and the bound is depicted in Fig. 3. It shows that for any parameter s, the scheme is a constant factor away from the bound. Typically, in distributed gradient descent applications the number of parameters d and the number of samples p are very large, whereas the number of workers n and as a consequence s, u and m are small by comparison. For large numbers of samples p, the ratio  $\kappa_{\rm achieve}/\kappa_{\rm bound}$  tends to

$$\lim_{p \to \infty} \frac{\kappa_{\text{achieve}}}{\kappa_{\text{bound}}} = 2\log_2(|\mathcal{A}|) \frac{(s-u+1)}{\lfloor s/u \rfloor}.$$
 (7)

The convergence behaviour can be observed in Fig. 4. Note that depending on the alphabet the communication




Fig. 4. Convergence of the ratio  $\frac{\kappa_{\rm achieve}}{\kappa_{\rm bound}}$  to the limit given in (7) for large numbers of samples. The parameters are  $n=10,\,m=10,\,|\mathcal{A}|=2^{16}.$  For s=5 and s=9 the limits as in (7) yield the same value.

overhead of our scheme can be slightly improved as stated in the following.

**Remark 1** (Compression Beyond the Alphabet Size). If for every pair of elements  $a,b \in \mathcal{A}$  there exists a function  $f: \mathcal{A} \mapsto \mathcal{B}$ , that maps from  $\mathcal{A}$  to a smaller alphabet  $\mathcal{B}$ , such that  $f(a) \neq f(b)$  and an operation  $\oplus$  with the property  $\forall c,d,e,g \in \mathcal{A}: f(c+d) \neq f(e+g) \Longrightarrow f(c) \neq f(d)$  or  $f(e) \neq f(g)$ , then our scheme can be improved to  $\kappa \geq (s+1-u)\left(2\lceil\log_{|\mathcal{A}|}(|\mathcal{B}|)\rceil\lceil\log_2\left(\frac{p}{m}\right)\rceil + \frac{s+3u}{2\log_2|\mathcal{A}|}\right)$ . At the start of each match the main node chooses not only the index  $\zeta$  but also the appropriate function f and communicates it to the two workers. They then use f to compress their transmitted symbols during the match.

#### G. Notation

```
n
           the number of workers
           the number of malicious workers
           the number of groups in case of fractional repetition data
  m
           allocation
           the number of guaranteed honest workers per group in case
  u
           of fractional repetition data allocation
           the number of partial gradients
  p
  \mathcal{A}
           the message alphabet
           true gradient of the loss function over the full data set (total
  \mathbf{g}
  \hat{\mathbf{g}}
           estimated gradient of the loss function over the full data
           set (total gradient)
           true gradient of the loss function for sample \mathbf{x}_i (partial
  \mathbf{g}_i
\widetilde{\mathbf{g}}_i^{(j)}
           claimed value of gradient \mathbf{g}_i from worker j according to
           the attack strategy detailed in Section IV-A
  \mathbf{A}
           data allocation matrix of size p \times n
           list of encoding functions
enc_{j,e}
           e-th encoding function available to worker j
 dec
           decoding function used by the main node
  Π
           interactive protocol
           replication factor per partial gradient
  \kappa
           communication overhead during the interactive protocol \Pi
           the number of local computations at the main node
           the number of rounds of the interactive protocol \Pi
           the round index of the interactive protocol \Pi
  \overset{	au}{\widetilde{\mathfrak{Z}}}_{t}
           the round index of the gradient descent iteration
           list of potentially corrupted worker responses in round t
  \mathfrak{Z}_t^t
           list of uncorrupted worker responses in round t
           list of indices of partial gradients that are locally computed
           at the main node in round t
  \mathfrak{G}_t
           list of values of partial gradients that are locally computed
           at the main node in round t
  \widetilde{\mathcal{T}}
           set of gradient indices on which workers disagree accord-
           ing to the attack strategy detailed in Section IV-A
```

### TABLE IV MAIN NOTATION.

#### H. Algorithms

```
Algorithm 1: Match between two workers.
```

```
Input: Workers W_{j_1} and W_{j_2}, s.t. \widetilde{\mathbf{z}}_{0,j_1} \neq \widetilde{\mathbf{z}}_{0,j_2}.

Output: Values \widetilde{\mathbf{g}}_{i_{\mathrm{check}}}^{(j_1)}, \widetilde{\mathbf{g}}_{i_{\mathrm{check}}}^{(j_2)} and index i_{\mathrm{check}}.

i_{\min} \leftarrow 1;

i_{\max} \leftarrow p;

\zeta \in \left\{ \zeta' \, \middle| \, [\widetilde{\mathbf{z}}_{0,j_1}]_{\zeta'} \neq [\widetilde{\mathbf{z}}_{0,j_2}]_{\zeta'} \right\};

while i_{\max} - i_{\min} > 0 do

\begin{vmatrix} i_{\mathrm{half}} \leftarrow i_{\min} + \left\lceil \frac{i_{\max} - i_{\min}}{2} \right\rceil \\ i_{\mathrm{edin}} - \sum_{i=i_{\min}}^{i_{\mathrm{half}}} \left[ \widetilde{\mathbf{g}}_{i}^{(j_1)} \right]_{\zeta} \right] from W_{j_1};

request \mathbf{z}_{t,j_1} \leftarrow \sum_{i=i_{\min}}^{i_{\mathrm{half}}} \left[ \widetilde{\mathbf{g}}_{i}^{(j_2)} \right]_{\zeta} \right] from W_{j_2};

if \widetilde{\mathbf{z}}_{t,j_1} = \widetilde{\mathbf{z}}_{t,j_2} then

\begin{vmatrix} i_{\min} \leftarrow i_{\mathrm{half}} \\ i_{\min} \leftarrow i_{\mathrm{half}} \end{vmatrix};

else

\begin{vmatrix} i_{\max} \leftarrow i_{\mathrm{half}} \\ i_{\max} \leftarrow i_{\mathrm{half}} \end{vmatrix};

end

t \leftarrow t + 1;

end

i_{\mathrm{check}} \leftarrow i_{\min};
```

#### Algorithm 2: Elimination Tournament.

```
: Set \mathcal{G} of disjoint worker groups, where
                                \mathcal{W} \in \mathcal{G} has \mathcal{W} \subset [n] and u \leq |\mathcal{W}| \leq s.
Require: draw(), commit(), localComp().
Output : Set S of malicious workers.
\mathcal{S} \leftarrow \{1, 2, \dots, n\} \setminus \cup_{\mathcal{W} \in \mathcal{G}} \mathcal{W};
while |\mathcal{G}| > 1 do
            W_1 \leftarrow draw(\mathcal{G}); W_1 \leftarrow draw(W_1);
           \mathcal{W}_{2} \leftarrow draw(\mathcal{G} \setminus \{\mathcal{W}_{1}\}); W_{2} \leftarrow draw(\mathcal{W}_{2}); \\ \left[\widetilde{\mathbf{g}}_{i}^{(1)}\right]_{\zeta}, \left[\widetilde{\mathbf{g}}_{i}^{(2)}\right]_{\zeta}, i, \zeta \leftarrow match(W_{1}, W_{2})
                (Algorithm 1);
           \begin{split} & \mathcal{V}_{1} \leftarrow commit(\left[\widetilde{\mathbf{g}}_{i}^{(1)}\right]_{\zeta}, i, \zeta, \mathcal{W}_{1}); \\ & \mathcal{V}_{2} \leftarrow commit(\left[\widetilde{\mathbf{g}}_{i}^{(2)}\right]_{\zeta}, i, \zeta, \mathcal{W}_{2}); \end{split}
                        \mathcal{S} \leftarrow \mathcal{S} \cup \mathcal{V}_1;
                       \mathcal{W}_1 \leftarrow \mathcal{W}_1 \setminus \mathcal{V}_1;
            if |\mathcal{V}_2| < u then
                       \mathcal{S} \leftarrow \mathcal{S} \cup \mathcal{V}_2;
                      \mathcal{W}_2 \leftarrow \mathcal{W}_2 \setminus \mathcal{V}_2;
            if |\mathcal{V}_1| \geq u and |\mathcal{V}_2| \geq u then
                        [\mathbf{g}_i]_{\zeta} \leftarrow localComp(i,\zeta);
                       \begin{aligned} & \mathbf{if} \left[ \widetilde{\mathbf{g}}_{i}^{(1)} \right]_{\zeta} \neq \left[ \mathbf{g}_{i} \right]_{\zeta} \mathbf{then} \\ & \left| \begin{array}{c} \mathcal{S} \leftarrow \mathcal{S} \cup \mathcal{V}_{1}; \\ \mathcal{W}_{1} \leftarrow \mathcal{W}_{1} \setminus \mathcal{V}_{1}; \end{array} \right. \end{aligned}
                       if \left[\widetilde{\mathbf{g}}_{i}^{(2)}\right]_{\zeta} \neq \left[\mathbf{g}_{i}\right]_{\zeta} then \mathcal{S} \leftarrow \mathcal{S} \cup \mathcal{V}_{2};
                                    \mathcal{W}_2 \leftarrow \mathcal{W}_2 \setminus \mathcal{V}_2;
                        end
             end
           for i = 1, 2 do
                       if |\mathcal{W}_i| < u then
                                \mathcal{G} \leftarrow \mathcal{G} \setminus \mathcal{W}_i;
                        end
           end
end
```